



# RF EXPOSURE REPORT

**REPORT NO.:** SA981002H05

**MODEL NO.:** UWA-BR100

**ACCORDING:** FCC Guidelines for Human Exposure  
IEEE C95.1

**APPLICANT:** Sony Corporation

**ADDRESS:** 1-7-1 Konan Minato-ku, Tokyo, 108-0075, JAPAN

**ISSUED BY:** Bureau Veritas Consumer Products Services (H.K.)  
Ltd., Taoyuan Branch

**LAB LOCATION:** No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen,  
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan.

# RF Exposure Measurement

## 1. Introduction

In this document, we try to prove the safety of radiation harmfulness to the human body for our product. The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The Gain of the antenna used in this product is measured in a Fully Anechoic Chamber (FAC) calibrated for antenna measurement in our lab, and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis transmission formula is a far field assumption, the calculated result of that is an over-prediction for near field power density. We will take that as the worst case to specify the safety range.

## 2. RF Exposure Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (minutes)
<b>(A)Limits For Occupational / Control Exposures</b>				
300-1500	...	...	F/300	6
1500-100,000	...	...	5	6
<b>(B)Limits For General Population / Uncontrolled Exposure</b>				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

### 3. Friis Formula

Friis transmission formula :  $P_d = (P_{out} * G) / (4 * \pi * r^2)$

where

$P_d$  = power density in  $mW/cm^2$

$P_{out}$  = output power to antenna in mW

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$R$  = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE,  $1 mW/cm^2$ . If we know the maximum Gain of the antenna and the total power input to the antenna, through the calculation, we will know the MPE value at distance 20cm.

Ref. : David K. Cheng, *Field and Wave Electromagnetics*, Second Edition,  
Page 640, Eq. (11-133).

### 4. EUT Operating condition

The software provided by Manufacturer enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

### 5. Classification

This USB dongle will be sold and used with SONY TV series. So the antenna of this product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance with the antenna should be included in users manual. So, this device is classified as **Mobile Device**.

## 6. TEST RESULTS

### 6.1 Antenna Gain

There are two antennas provided to this EUT, please refer to the following table:

Chain	Manufacture	Model name	Antenna Gain		Antenna Type	Connector
			For 2.4GHz Gain (dBi)	For 5GHz Gain (dBi)		
Chain (0) Antenna (1)	Alpha	NA	1.11	Band1: 4.4 Band2: 4.57 Band3: 5.52 Band4: 4.08	Printed	NA
Chain (1) Antenna (2)	Alpha	NA	0.05	Band1: 5.75 Band2: 5.32 Band3: 5.17 Band4: 5.03	Printed	NA

## 6.2 Output Power Into Antenna & RF Exposure value at distance 20cm:

For 15.247(2.4GHz):

**802.11b:**

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm <sup>2</sup> )	Limit of Power Density (mW/cm <sup>2</sup> )
1	2412	59.6	0.015	1.0
6	2437	57.5	0.015	1.0
11	2462	59.9	0.015	1.0

**802.11g:**

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm <sup>2</sup> )	Limit of Power Density (mW/cm <sup>2</sup> )
1	2412	328.3	0.084	1.0
6	2437	344.2	0.088	1.0
11	2462	368.2	0.095	1.0

**802.11n (20MHz):**

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm <sup>2</sup> )	Limit of Power Density (mW/cm <sup>2</sup> )
1	2412	325.1	0.084	1.0
6	2437	372.5	0.096	1.0
11	2462	386.1	0.099	1.0

**802.11n (40MHz):**

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm <sup>2</sup> )	Limit of Power Density (mW/cm <sup>2</sup> )
1	2422	111.8	0.029	1.0
4	2437	413.1	0.106	1.0
7	2452	285.8	0.073	1.0

**For 15.247(5GHz):**

**802.11a:**

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm <sup>2</sup> )	Limit of Power Density (mW/cm <sup>2</sup> )
149	5745	93.3	0.047	1.0
157	5785	95.5	0.049	1.0
165	5825	100.0	0.051	1.0

**802.11n (20MHz):**

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm <sup>2</sup> )	Limit of Power Density (mW/cm <sup>2</sup> )
149	5745	193.2	0.122	1.0
157	5785	193.2	0.122	1.0
165	5825	200.2	0.127	1.0

**802.11n (40MHz):**

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm <sup>2</sup> )	Limit of Power Density (mW/cm <sup>2</sup> )
151	5755	187.4	0.119	1.0
159	5795	168.3	0.107	1.0



**For 15.407(5GHz):**

**802.11a:**

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm <sup>2</sup> )	Limit of Power Density (mW/cm <sup>2</sup> )
36	5180	8.7	0.006	1.0
40	5200	9.3	0.007	1.0
48	5240	11.5	0.008	1.0
52	5260	11.5	0.008	1.0
60	5300	11.2	0.008	1.0
64	5320	11.0	0.008	1.0
100	5500	13.5	0.010	1.0
120	5600	10.5	0.007	1.0
140	5700	10.2	0.007	1.0

**802.11n (20MHz):**

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm <sup>2</sup> )	Limit of Power Density (mW/cm <sup>2</sup> )
36	5180	17.2	0.013	1.0
40	5200	17.7	0.013	1.0
48	5240	20.8	0.016	1.0
52	5260	21.0	0.016	1.0
60	5300	21.5	0.016	1.0
64	5320	21.7	0.016	1.0
100	5500	20.7	0.015	1.0
120	5600	18.2	0.014	1.0
140	5700	20.5	0.015	1.0

**802.11n (40MHz):**

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm <sup>2</sup> )	Limit of Power Density (mW/cm <sup>2</sup> )
38	5190	8.2	0.006	1.0
46	5230	11.8	0.009	1.0
54	5270	12.2	0.009	1.0
62	5310	12.0	0.009	1.0
102	5510	16.4	0.012	1.0
118	5590	13.8	0.010	1.0
134	5670	12.9	0.010	1.0