

## RF Exposure / MPE Calculation

**No. : 28IE0011-HO-01**

**Applicant** : Sony Corporation  
**Type of Equipment** : Digital Photo Frame  
**Model No.** : VGF-CP1  
**FCC ID** : AK8VGFCP1

---

Sony Corporation declares that Model : VGF-CP1  
complies with FCC radiation exposure requirement specified in the FCC Rules 2.1093(for portable)/2.1091 (for mobile).

### **RF Exposure Calculations:**

The following information provides the minimum separation distance for the highest gain antenna provided with the "VGF-CP1" as calculated from FCC OET Bulletin 65 Appendix A, Table (B) Limits for General Population / Uncontrolled Exposure. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0mW/cm<sup>2</sup> uncontrolled exposure limit. The Friis formula used was:

$$S = (P * G) / (4 * \pi * r^2)$$

Where

**P = 120.78 mW (Maximum peak output power)**  
**G = 1.05 Numerical Antenna gain; equal 0.22 dBi**  
**r = 20.0 cm**

For: VGF-CP1

$$S = 0.02528 \text{ mW/cm}^2$$

---

**UL Japan, Inc.**

**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124