



RADIO TEST REPORT

Test Report No. : 10441271H-A-R2

Applicant : Sony Computer Entertainment Inc.
Type of Equipment : PlayStation® TV
Model No. : VTE-1001
FCC ID : AK8VTE1001F2
Test regulation : FCC Part 15 Subpart C: 2014
*WLAN part
Test Result : Complied

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the above regulation.
4. The test results in this report are traceable to the national or international standards.
5. This test report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.
6. This report is a revised version of 10441271H-A-R1. 10441271H-A-R1 is replaced with this report.

Date of test: August 29, 2013 to September 11, 2014

Representative test engineer:

Takumi Shimada
Engineer
Consumer Technology Division

Approved by:

Masanori Nishiyama
Manager
Consumer Technology Division



NVLAP LAB CODE: 200572-0

This laboratory is accredited by the NVLAP LAB CODE 200572-0, U.S.A. The tests reported herein have been performed in accordance with its terms of accreditation. *As for the range of Accreditation in NVLAP, you may refer to the WEB address, <http://www.ul.com/japan/jpn/pages/services/emc/about/mark1/index.jsp#nvlap>

UL Japan, Inc.
Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN
Telephone : +81 596 24 8999
Facsimile : +81 596 24 8124

13-EM-F0429

CONTENTS	PAGE
SECTION 1: Customer information.....	4
SECTION 2: Equipment under test (E.U.T.).....	4
SECTION 3: Test specification, procedures & results.....	6
SECTION 4: Operation of E.U.T. during testing.....	9
SECTION 5: Conducted Emission.....	11
SECTION 6: Radiated Spurious Emission	12
SECTION 7: Antenna Terminal Conducted Tests.....	13
APPENDIX 1: Data of EMI test.....	14
Conducted Emission	14
6dB Bandwidth	15
Maximum Peak Output Power	18
Average Output Power	20
Radiated Spurious Emission	21
Conducted Spurious Emission	29
Power Density	30
99%Occupied Bandwidth	33
APPENDIX 2: Test instruments	35
APPENDIX 3: Photographs of test setup	37
Conducted Emission	37
Radiated Spurious Emission	38
Worst Case Position (Horizontal: Y-axis/ Vertical:Y-axis).....	39
Test Configuration and peripherals	40

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

SECTION 1: Customer information

Company Name	Sony Computer Entertainment Inc.
Brand Name	SONY
Address	1-7-1 Konan, Minato-ku, Tokyo, 108-0075 Japan
Telephone Number	+81-3-6748-6333
Facsimile Number	+81-3-6748-6383
Contact Person	Kiyoto Sasaki

SECTION 2: Equipment under test (E.U.T.)

2.1 Identification of E.U.T.

Type of Equipment	PlayStation® TV
Model No	VTE-1001
Serial No	Refer to Section 4, Clause 4.2
Country of Manufacture	China
Receipt Date of Sample	August 27, 2013 for AT ¹ * sample August 2, 2014 for AT ² , CE and RE* sample
Condition of EUT	Engineering prototype (Not for Sale: This sample is equivalent to mass-produced items.)
Modification of EUT	No modification by the test lab.

*AT¹: Antenna Terminal Conducted tests(except for 99%Occupied Bandwidth)

AT²: Antenna Terminal Conducted tests(99%Occupied Bandwidth)

CE: Conducted Emission test

RE: Radiated Spurious Emission test

2.2 Product Description

VTE-1001 is PlayStation® TV.

WLAN antenna and Bluetooth antenna transmit simultaneously, but there is no correlation between WLAN antenna and Bluetooth antenna.

Product Specification

Maximum clock frequency in the system	444MHz
Operating Temperature	5-35 deg. C
Power Supply	DC 5.0V
Size	105.0 x 65.0 x 13.6 mm
Weight	Approx. 110g

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Radio Specification

WLAN (IEEE802.11b/g/n-20)

Equipment Type	Transceiver
Frequency of Operation	2412-2462MHz
Type of Modulation	DSSS, OFDM
Bandwidth & Channel spacing	20MHz & 5MHz
Method of frequency generation	Synthesizer
Power Supply (inner)	DC 1.8V/DC 3.1V
Antenna Type	Inverted F
Antenna Gain	1.25dBi (Peak)

Bluetooth (BDR/EDR)

Equipment Type	Transceiver
Frequency of Operation	2402-2480MHz
Type of Modulation	FHSS (GFSK, $\pi/4$ DQPSK, 8DPSK)
Bandwidth & Channel spacing	1MHz & 1MHz
Method of frequency generation	Synthesizer
Power Supply (inner)	DC 1.8V
Antenna Type	Inverted F
Antenna Gain	-0.88dBi (peak)

*This test report applies for WLAN.

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

SECTION 3: Test specification, procedures & results

3.1 Test Specification

Test Specification : FCC Part 15 Subpart C: 2014, final revised on May 1, 2014 and effective June 2, 2014

Title : FCC 47CFR Part15 Radio Frequency Device Subpart C Intentional Radiators Section 15.207 Conducted limits Section 15.247 Operation within the bands 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz

* The EUT complies with FCC Part 15 Subpart B: 2014, final revised on May 1, 2014 and effective June 2, 2014.

3.2 Procedures and results

Item	Test Procedure	Specification	Worst margin	Results	Remarks
Conducted Emission	FCC: ANSI C63.4:2003 7. AC powerline Conducted Emission measurements ----- IC: RSS-Gen 7.2.4	FCC: Section 15.207 ----- IC: RSS-Gen 7.2.4	QP 18.8dB, 2.26600MHz, N AV 9.8dB, 0.82648MHz, L	Complied	-
6dB Bandwidth	FCC: "Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247(issued on June 5, 2014)" ----- IC: RSS-Gen 4.6.2	FCC: Section 15.247(a)(2) ----- IC: RSS-210 A8.2(a)	See data.	Complied	Conducted *1)
Maximum Peak Output Power	FCC: "Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247(issued on June 5, 2014)" ----- IC: RSS-Gen 4.8	FCC: Section 15.247(b)(3) ----- IC: RSS-210 A8.4(4)		Complied	Conducted *1)
Power Density	FCC: "Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247(issued on June 5, 2014)" ----- IC: -	FCC: Section 15.247 (e) ----- IC: RSS-210 A8.2(b)		Complied	Conducted *1)
Spurious Emission Restricted Band Edges	FCC: "Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247(issued on June 5, 2014)" ----- IC: RSS-Gen 4.9	FCC: Section15.247(d) ----- IC: RSS-210 A8.5 RSS-Gen 7.2.3	3.3dB 2390.000MHz, AV, Horizontal	Complied	Conducted/ Radiated

Note: UL Japan, Inc.'s EMI Work Procedures No. 13-EM-W0420 and 13-EM-W0422.
*1) For antenna terminal conducted tests other than 99% Occupied Bandwidth test, test data of 10348320H-E was used.
* In case any questions arise about test procedure, ANSI C63.4: 2003 is also referred.
** This test report was confirmed to comply with the current technical requirements in KDB versions (KDB 558074 D01 v03r02 (June 5, 2014)) RF Module of the EUT was not changed from the one tested in Report NO. 10348320H-E.

FCC Part 15.31 (e)

This EUT provides stable voltage (DC 1.8V/3.1V) constantly to RF Part regardless of input voltage. Therefore, this EUT complies with the requirement.

FCC Part 15.203 Antenna requirement

It is impossible for end users to replace the antenna, because the antenna is mounted inside of the EUT. Therefore, the equipment complies with the antenna requirement of Section 15.203.

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

3.3 Addition to standard

Item	Test Procedure	Specification	Worst margin	Results	Remarks
99% Occupied Bandwidth	IC: RSS-Gen 4.6.1	IC: RSS-Gen 4.6.1	N/A	-	Conducted

Other than above, no addition, exclusion nor deviation has been made from the standard.

3.4 Uncertainty

EMI

The following uncertainties have been calculated to provide a confidence level of 95% using a coverage factor k=2.

Test room (semi-anechoic chamber)	Conducted emission (+dB)
	150kHz-30MHz
No.1	3.5dB
No.2	3.5dB
No.3	3.6dB
No.4	3.5dB

Test room (semi-anechoic chamber)	Radiated emission						
	(3m*)(+dB)				(1m*)(+dB)		(0.5m*)(+dB)
	9kHz -30MHz	30MHz -300MHz	300MHz -1GHz	1GHz -10GHz	10GHz -18GHz	18GHz -26.5GHz	26.5GHz -40GHz
No.1	4.0dB	5.1dB	5.0dB	5.1dB	6.0dB	4.9dB	4.3dB
No.2	3.9dB	5.2dB	5.0dB	4.9dB	5.9dB	4.7dB	4.2dB
No.3	4.3dB	5.1dB	5.2dB	5.2dB	6.0dB	4.8dB	4.2dB
No.4	4.6dB	5.2dB	5.0dB	5.2dB	6.0dB	5.7dB	4.2dB

*3m/1m/0.5m = Measurement distance

Power meter (+dB)	
Below 1GHz	Above 1GHz
0.7dB	1.5dB

Antenna terminal conducted emission and Power density (+dB)			Antenna terminal conducted emission (+dB)		Channel power (+dB)
Below 1GHz	1GHz-3GHz	3GHz-18GHz	18GHz-26.5GHz	26.5GHz-40GHz	
1.5dB	1.7dB	2.8dB	2.8dB	2.9dB	2.6dB

Conducted Emission test

The data listed in this test report has enough margin, more than the site margin.

Radiated emission test (3m)

The data listed in this report meets the limits unless the uncertainty is taken into consideration.

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

3.5 Test Location

UL Japan, Inc. Ise EMC Lab. *NVLAP Lab. code: 200572-0
4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN
Telephone : +81 596 24 8999 Facsimile : +81 596 24 8124

	IC Registration Number	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Other rooms
No.1 semi-anechoic chamber	2973C-1	19.2 x 11.2 x 7.7m	7.0 x 6.0m	No.1 Power source room
No.2 semi-anechoic chamber	2973C-2	7.5 x 5.8 x 5.2m	4.0 x 4.0m	-
No.3 semi-anechoic chamber	2973C-3	12.0 x 8.5 x 5.9m	6.8 x 5.75m	No.3 Preparation room
No.3 shielded room	-	4.0 x 6.0 x 2.7m	N/A	-
No.4 semi-anechoic chamber	2973C-4	12.0 x 8.5 x 5.9m	6.8 x 5.75m	No.4 Preparation room
No.4 shielded room	-	4.0 x 6.0 x 2.7m	N/A	-
No.5 semi-anechoic chamber	-	6.0 x 6.0 x 3.9m	6.0 x 6.0m	-
No.6 shielded room	-	4.0 x 4.5 x 2.7m	4.0 x 4.5 m	-
No.6 measurement room	-	4.75 x 5.4 x 3.0m	4.75 x 4.15 m	-
No.7 shielded room	-	4.7 x 7.5 x 2.7m	4.7 x 7.5m	-
No.8 measurement room	-	3.1 x 5.0 x 2.7m	N/A	-
No.9 measurement room	-	8.0 x 4.6 x 2.8m	2.4 x 2.4m	-
No.11 measurement room	-	6.2 x 4.7 x 3.0m	4.8 x 4.6m	-

* Size of vertical conducting plane (for Conducted Emission test) : 2.0 x 2.0m for No.1, No.2, No.3, and No.4 semi-anechoic chambers and No.3 and No.4 shielded rooms.

3.6 Data of EMI, Test instruments, and Test set up

Refer to APPENDIX.

UL Japan, Inc. Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN
Telephone : +81 596 24 8999
Facsimile : +81 596 24 8124

SECTION 4: Operation of E.U.T. during testing

4.1 Operating Mode(s)

Test operating mode was determined as follows according to “Section 1 of 6 802.11 a/b/g/n testing - Managing Complex Regulatory Approvals - ” of TCB Council Workshop October 2009.

Mode	Remarks*
IEEE 802.11b (11b)	1Mbps, PN9
IEEE 802.11g (11g)	24Mbps, PN9
IEEE 802.11n MIMO 20MHz BW (11n-20)	MCS4, PN9
*Transmitting duty was 100% on all tests.	
*The worst condition was determined based on the test result of Maximum Peak Output Power (Mid Channel)	
*Power of the EUT was set by the software as follows; Power settings: Same as production model Software: LABTOOL-VTE10-L.L-Ver.1.0.2 *This setting of software is the worst case. Any conditions under the normal use do not exceed the condition of setting. In addition, end users cannot change the settings of the output power of the product.	

*The details of Operating mode(s)

Test Item	Operating Mode	Tested frequency
Conducted Emission Spurious Emission (Conducted)	11g Tx *1)	2462MHz *1)
6dB Bandwidth	11b Tx	2412MHz
99% Occupied Bandwidth	11g Tx	2437MHz
Maximum Peak Output Power Power Density	11n-20 Tx	2462MHz
Spurious Emission (Radiated)	11b Tx	2412MHz
	11g Tx	2437MHz
		2462MHz
	11n-20 Tx	2412MHz
		2462MHz
*1) The test was performed on the mode as a representative, because it had the highest power at antenna terminal test.		

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

4.2 Configuration and peripherals

This page has been submitted for a separate exhibit.

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

SECTION 5: Conducted Emission

Test Procedure and conditions

EUT was placed on a urethane platform of nominal size, 1.0m by 1.5m, raised 0.8m above the conducting ground plane. The rear of tabletop was located 40cm to the vertical conducting plane. The rear of EUT, including peripherals aligned and flushed with rear of tabletop. All other surfaces of tabletop were at least 80cm from any other grounded conducting surface. EUT was located 80cm from a Line Impedance Stabilization Network (LISN)/ Artificial mains Network (AMN) and excess AC cable was bundled in center.

For the tests on EUT with other peripherals (as a whole system)

I/O cables that were connected to the peripherals were bundled in center. They were folded back and forth forming a bundle 30cm to 40cm long and were hanged at a 40cm height to the ground plane. All unused 50ohm connectors of the LISN(AMN) were resistivity terminated in 50ohm when not connected to the measuring equipment.

The AC Mains Terminal Continuous disturbance Voltage has been measured with the EUT in a Semi Anechoic Chamber.

The EUT was connected to a LISN (AMN).

An overview sweep with peak detection has been performed.

The test results and limit are rounded off to one decimal place, so some differences might be observed.

Detector : QP and CISPR AV
Measurement range : 0.15-30MHz
Test data : APPENDIX
Test result : Pass

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

SECTION 6: Radiated Spurious Emission

Test Procedure

It was measured based on "11.0 Emissions in non-restricted frequency bands" of "558074 D01 DTS Meas Guidance v03r02 (Issued on June 5, 2014)".

EUT was placed on a urethane platform of nominal size, 1.0m by 1.5m, raised 0.8m above the conducting ground plane. The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with a ground plane.

The height of the measuring antenna varied between 1 and 4m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field strength.

The measurements were performed for both vertical and horizontal antenna polarization with the Test Receiver, or the Spectrum Analyzer.

The measurements were made with the following detector function of the test receiver and the Spectrum analyzer (in linear mode).

The test was made with the detector (RBW/VBW) in the following table.

When using Spectrum analyzer, the test was made with adjusting span to zero by using peak hold.

Test Antennas are used as below;

Frequency	Below 30MHz	30MHz to 300MHz	300MHz to 1GHz	Above 1GHz
Antenna Type	Loop	Biconical	Logperiodic	Horn

In any 100kHz bandwidth outside the restricted band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator confirmed 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on a radiated measurement.

20dBc was applied to the frequency over the limit of FCC 15.209 / Table 5 of RSS-Gen 7.2.5(IC) and outside the restricted band of FCC15.205 / Table 3 of RSS-Gen 7.2.2 (IC).

Frequency	Below 1GHz	Above 1GHz		20dBc
Instrument used	Test Receiver	Spectrum Analyzer		Spectrum Analyzer
Detector	QP	PK	AV *1)	PK
IF Bandwidth	BW 120kHz	RBW: 1MHz VBW: 3MHz	Average Power Method: <u>WLAN: 12.2.5.1</u> RBW: 1MHz VBW: 3MHz Detector: Power Averaging (RMS) Trace: Free Run	RBW: 100kHz VBW: 300kHz
Test Distance	3m	3m (below 10GHz), 1m *2) (above 10GHz)		3m (below 10GHz), 1m *2) (above 10GHz)

*1) Average Power Measurement was performed based on 6.0 & 12.2.5 of "558074 D01 DTS Meas Guidance v03r02 (Issued on June 5, 2014)"

*2) Distance Factor: $20 \times \log(3.0\text{m}/1.0\text{m}) = 9.5\text{dB}$

- The carrier level and noise levels were confirmed at each position of X, Y and Z axes of EUT to see the position of maximum noise, and the test was made at the position that has the maximum noise.

The test results and limit are rounded off to one decimal place, so some differences might be observed.

Measurement range : 30M-26.5GHz
Test data : APPENDIX
Test result : Pass

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

SECTION 7: Antenna Terminal Conducted Tests

Test Procedure

The tests were made with below setting connected to the antenna port.

Test	Span	RBW	VBW	Sweep time	Detector	Trace	Instrument used
6dB Bandwidth	20MHz	100kHz	300kHz	Auto	Peak	Max Hold	Spectrum Analyzer
99% Occupied Bandwidth	Enough width to display 20dB Bandwidth	1 to 3% of Span	Three times of RBW	Auto	Sample	Clear write	Spectrum Analyzer
Maximum Peak Output Power	-	-	-	Auto	Peak Average *1)	-	Power Meter (Sensor: 50MHz BW)
Peak Power Density	1.5 times the 6dB Bandwidth	3kHz	10kHz	Auto	Peak	Max Hold	Spectrum Analyzer *2)
Conducted Spurious Emission *3)	9kHz to 150kHz	200Hz	620Hz	Auto	Peak	Max Hold	Spectrum Analyzer
	150kHz to 30MHz	9.1kHz	27kHz				

*1) Reference data

*2) Section 10.2 Method PKPSD (peak PSD) of "Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 (Issued on June 5, 2014)".

*3) In the frequency range below 30MHz, RBW was narrowed to separate the noise contents.

Then, wide-band noise near the limit was checked separately, however the noise was low enough as shown in the chart.(9kHz-150kHz:RBW=200Hz, 150kHz-30MHz:RBW=9.1kHz).

The test results and limit are rounded off to two decimals place, so some differences might be observed.

Test data : **APPENDIX**
Test result : **Pass**

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

APPENDIX 1: Data of EMI test

Conducted Emission


DATA OF CONDUCTED EMISSION TEST

UL Japan, Inc. Ise EMC Lab. No.1 Semi Anechoic Chamber
 Date : 2014/08/20

Report No. : 10441271H
 Temp./Humi. : 24deg. C / 62% RH
 Engineer : Yuta Moriya

Mode / Remarks : Tx 11g 2462MHz 24Mbps

LIMIT : FCC15.207 QP
 FCC15.207 AV



Frequency [MHz]	Reading Level		Corr. Factor	Results		Limit		Margin		Phase	Comment
	QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dB]	AV [dB]		
0.62074	23.2	15.4	13.4	36.6	28.8	56.0	46.0	19.4	17.2	N	
0.82320	18.2	10.1	13.4	31.6	23.5	56.0	46.0	24.4	22.5	N	
1.54347	21.7	12.9	13.5	35.2	26.4	56.0	46.0	20.8	19.6	N	
2.16146	22.9	15.3	13.7	36.6	29.0	56.0	46.0	19.4	17.0	N	
2.26600	23.5	16.6	13.7	37.2	30.3	56.0	46.0	18.8	15.7	N	
3.60557	18.5	11.6	13.8	32.3	25.4	56.0	46.0	23.7	20.6	N	
0.62074	23.3	15.7	13.4	36.7	29.1	56.0	46.0	19.3	16.9	L	
0.82648	19.9	22.8	13.4	33.3	36.2	56.0	46.0	22.7	9.8	L	
1.54347	20.7	10.8	13.5	34.2	24.3	56.0	46.0	21.8	21.7	L	
2.16146	20.1	10.4	13.7	33.8	24.1	56.0	46.0	22.2	21.9	L	
2.26680	21.2	11.8	13.7	34.9	25.5	56.0	46.0	21.1	20.5	L	
3.60551	17.0	7.4	13.8	30.8	21.2	56.0	46.0	25.2	24.8	L	

CHART : WITH FACTOR. Peak hold data. CALCULATION : RESULT[dBuV] = READING[dBuV] + C.F[dB] (LISN + CABLE + ATTEN.)
 Except for the above table : adequate margin data below the limits.

UL Japan, Inc.
Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

6dB Bandwidth

Test place Ise EMC Lab. No.3 Semi Anechoic Chamber
Report No. 10441271H
Date 09/05/2013
Temperature/ Humidity 23 deg. C/ 68% RH
Engineer Takumi Shimada
Mode Tx

11b

Frequency [MHz]	6dB Bandwidth [MHz]	Limit [kHz]
2412	9.986	>500
2437	9.985	>500
2462	9.973	>500

11g

Frequency [MHz]	6dB Bandwidth [MHz]	Limit [kHz]
2412	16.564	>500
2437	16.557	>500
2462	16.554	>500

11n-20

Frequency [MHz]	6dB Bandwidth [MHz]	Limit [kHz]
2412	17.819	>500
2437	17.824	>500
2462	17.805	>500

UL Japan, Inc.


Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

6dB Bandwidth



UL Japan, Inc.
Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN


Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124


6dB Bandwidth

11n-20


2412MHz



2437MHz



2462MHz



UL Japan, Inc.
Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Maximum Peak Output Power

Test place : Ise EMC Lab. No.2 Semi Anechoic Chamber
Report No. : 10441271H
Date : 08/29/2013
Temperature/ Humidity : 23 deg. C / 68 %RH
Engineer : Takumi Shimada
Mode : Tx 11b / 11g / 11n-20

11b 1Mbps

Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. [dB]	Result		Limit		Margin [dB]
				[dBm]	[mW]	[dBm]	[mW]	
2412	1.81	0.50	9.97	12.28	16.90	30.00	1000	17.72
2437	2.00	0.50	9.97	12.47	17.66	30.00	1000	17.53
2462	2.23	0.50	9.97	12.70	18.62	30.00	1000	17.30

11g 24Mbps

Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. [dB]	Result		Limit		Margin [dB]
				[dBm]	[mW]	[dBm]	[mW]	
2412	8.79	0.50	9.97	19.26	84.33	30.00	1000	10.74
2437	9.07	0.50	9.97	19.54	89.95	30.00	1000	10.46
2462	9.24	0.50	9.97	19.71	93.54	30.00	1000	10.29

11n-20 MCS4

Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. [dB]	Result		Limit		Margin [dB]
				[dBm]	[mW]	[dBm]	[mW]	
2412	7.93	0.50	9.97	18.40	69.18	30.00	1000	11.60
2437	8.24	0.50	9.97	18.71	74.30	30.00	1000	11.29
2462	8.27	0.50	9.97	18.74	74.82	30.00	1000	11.26

Sample Calculation:

Result = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Maximum Peak Output Power

Worst Rate Check

Test place	Ise EMC Lab. No.2 Semi Anechoic Chamber
Report No.	10441271H
Date	08/29/2013
Temperature/ Humidity	23 deg. C / 68 %RH
Engineer	Takumi Shimada
Mode	Tx 11b / 11g / 11n-20

11b,2437MHz

Rate	Reading	Remark
[Mbps]	[dBm]	
1	2.00	*
2	1.78	
5.5	1.24	
11	1.71	

*: Worst Rate

All comparizon were carried out on same frequency and measurement factors.

11g,2437MHz

Rate	Reading	Remark
[Mbps]	[dBm]	
6	8.61	
9	8.41	
12	8.72	
18	8.27	
24	9.07	*
36	8.32	
48	8.43	
54	8.76	

*: Worst Rate

All comparizon were carried out on same frequency and measurement factors.

11n-20,2437MHz

MCS Number	Reading	Remark
	[dBm]	
0	8.12	
1	8.23	
2	8.21	
3	8.15	
4	8.24	*
5	8.13	
6	8.09	
7	8.22	

*: Worst Rate

All comparizon were carried out on same frequency and measurement factors.

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Average Output Power

Test place	Ise EMC Lab. No.2 Semi Anechoic Chamber
Report No.	10441271H
Date	08/29/2013
Temperature/ Humidity	23 deg. C / 68 %RH
Engineer	Takumi Shimada
Mode	Tx 11b / 11g / 11n-20

[AV]

11b

1Mbps

Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. [dB]	Result		Limit		Margin [dB]
				[dBm]	[mW]	[dBm]	[mW]	
2412	-0.72	0.50	9.97	9.75	9.44	30.00	1000	20.25
2437	-0.53	0.50	9.97	9.94	9.86	30.00	1000	20.06
2462	-0.34	0.50	9.97	10.13	10.30	30.00	1000	19.87

11g

24Mbps

Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. [dB]	Result		Limit		Margin [dB]
				[dBm]	[mW]	[dBm]	[mW]	
2412	-0.74	0.50	9.97	9.73	9.40	30.00	1000	20.27
2437	-0.51	0.50	9.97	9.96	9.91	30.00	1000	20.04
2462	-0.41	0.50	9.97	10.06	10.14	30.00	1000	19.94

11n-20

MCS4

Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. [dB]	Result		Limit		Margin [dB]
				[dBm]	[mW]	[dBm]	[mW]	
2412	-0.76	0.50	9.97	9.71	9.35	30.00	1000	20.29
2437	-0.54	0.50	9.97	9.93	9.84	30.00	1000	20.07
2462	-0.43	0.50	9.97	10.04	10.09	30.00	1000	19.96

Sample Calculation:

Result = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Radiated Spurious Emission

Test place : Ise EMC Lab. No.2 Semi Anechoic Chamber
Report No. : 10441271H
Date : 08/15/2014
Temperature/ Humidity : 22 deg. C / 56% RH
Engineer : Yuta Moriya
(Above 1GHz)
Mode : 11b Tx 2412MHz

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	2390.000	PK	46.0	27.0	3.0	34.7	41.3	73.9	32.6	
Hori	4824.000	PK	45.6	31.9	5.3	33.9	48.9	73.9	25.0	
Hori	7236.000	PK	43.3	35.7	6.6	33.8	51.8	73.9	22.1	
Hori	9648.000	PK	43.4	38.1	7.0	34.4	54.1	73.9	19.8	
Hori	2390.000	AV	38.2	27.0	3.0	34.7	33.5	53.9	20.4	
Hori	4824.000	AV	40.1	31.9	5.3	33.9	43.4	53.9	10.5	
Hori	7236.000	AV	35.3	35.7	6.6	33.8	43.8	53.9	10.1	
Hori	9648.000	AV	35.2	38.1	7.0	34.4	45.9	53.9	8.0	
Vert	2390.000	PK	45.1	27.0	3.0	34.7	40.4	73.9	33.5	
Vert	4824.000	PK	45.8	31.9	5.3	33.9	49.1	73.9	24.8	
Vert	7236.000	PK	43.9	35.7	6.6	33.8	52.4	73.9	21.5	
Vert	9648.000	PK	42.7	38.1	7.0	34.4	53.4	73.9	20.5	
Vert	2390.000	AV	37.6	27.0	3.0	34.7	32.9	53.9	21.0	
Vert	4824.000	AV	40.6	31.9	5.3	33.9	43.9	53.9	10.0	
Vert	7236.000	AV	35.7	35.7	6.6	33.8	44.2	53.9	9.7	
Vert	9648.000	AV	35.2	38.1	7.0	34.4	45.9	53.9	8.0	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter-Distance factor(above 10GHz)) - Gain(Amplifier)

*Other frequency noises omitted in this report were not seen or had enough margin (more than 20dB).

*The 10th harmonic was not seen so the result was its base noise level.

Distance factor: 10GHz-26.5GHz 20log(3.0m/1.0m)= 9.5dB

20dBc Data Sheet

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	2412.000	PK	101.9	27.0	3.0	34.7	97.2	-	-	Carrier
Hori	2397.000	PK	58.0	27.0	3.0	34.7	53.3	77.2	23.9	
Hori	2400.000	PK	45.9	27.0	3.0	34.7	41.2	77.2	36.0	
Vert	2412.000	PK	102.4	27.0	3.0	34.7	97.7	-	-	Carrier
Vert	2397.000	PK	58.1	27.0	3.0	34.7	53.4	77.7	24.3	
Vert	2400.000	PK	44.8	27.0	3.0	34.7	40.1	77.7	37.6	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter-Distance factor(above 10GHz)) - Gain(Amplifier)

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Radiated Spurious Emission

Test place	Ise EMC Lab. No.2 Semi Anechoic Chamber
Report No.	10441271H
Date	08/15/2014
Temperature/ Humidity	22 deg. C / 56% RH
Engineer	Yuta Moriya
	(Above 1GHz)
Mode	11b Tx 2437MHz

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	4874.000	PK	47.5	32.0	5.3	33.9	50.9	73.9	23.0	
Hori	7311.000	PK	43.0	35.8	6.7	33.8	51.7	73.9	22.2	
Hori	9748.000	PK	42.4	38.3	7.1	34.5	53.3	73.9	20.6	
Hori	4874.000	AV	43.2	32.0	5.3	33.9	46.6	53.9	7.3	
Hori	7311.000	AV	34.9	35.8	6.7	33.8	43.6	53.9	10.3	
Hori	9748.000	AV	35.6	38.3	7.1	34.5	46.5	53.9	7.4	
Vert	4874.000	PK	47.7	32.0	5.3	33.9	51.1	73.9	22.8	
Vert	7311.000	PK	43.3	35.8	6.7	33.8	52.0	73.9	21.9	
Vert	9748.000	PK	43.4	38.3	7.1	34.5	54.3	73.9	19.6	
Vert	4874.000	AV	43.2	32.0	5.3	33.9	46.6	53.9	7.3	
Vert	7311.000	AV	35.5	35.8	6.7	33.8	44.2	53.9	9.7	
Vert	9748.000	AV	35.5	38.3	7.1	34.5	46.4	53.9	7.5	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter-Distance factor(above 10GHz)) - Gain(Amplifier)

*Other frequency noises omitted in this report were not seen or had enough margin (more than 20dB).

*The 10th harmonic was not seen so the result was its base noise level.

Distance factor: 10GHz-26.5GHz 20log(3.0m/1.0m)= 9.5dB

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Radiated Spurious Emission

Test place : Ise EMC Lab. No.2 Semi Anechoic Chamber
Report No. : 10441271H
Date : 08/15/2014
Temperature/ Humidity : 22 deg. C / 56% RH
Engineer : Yuta Moriya
(Above 1GHz)
Mode : 11b Tx 2462MHz

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	2483.500	PK	45.5	26.9	3.1	34.7	40.8	73.9	33.1	
Hori	4924.000	PK	49.3	32.1	5.3	33.9	52.8	73.9	21.1	
Hori	7386.000	PK	44.2	35.8	6.6	33.8	52.8	73.9	21.2	
Hori	9848.000	PK	42.8	38.5	7.1	34.5	53.9	73.9	20.0	
Hori	2483.500	AV	38.1	26.9	3.1	34.7	33.4	53.9	20.6	
Hori	4924.000	AV	45.7	32.1	5.3	33.9	49.2	53.9	4.7	
Hori	7386.000	AV	34.8	35.8	6.6	33.8	43.4	53.9	10.5	
Hori	9848.000	AV	35.3	38.5	7.1	34.5	46.4	53.9	7.5	
Vert	2483.500	PK	45.5	26.9	3.1	34.7	40.8	73.9	33.1	
Vert	4924.000	PK	49.3	32.1	5.3	33.9	52.8	73.9	21.1	
Vert	7386.000	PK	42.9	35.8	6.6	33.8	51.5	73.9	22.4	
Vert	9848.000	PK	42.9	38.5	7.1	34.5	54.0	73.9	19.9	
Vert	2483.500	AV	37.2	26.9	3.1	34.7	32.5	53.9	21.4	
Vert	4924.000	AV	46.3	32.1	5.3	33.9	49.8	53.9	4.2	
Vert	7386.000	AV	36.2	35.8	6.6	33.8	44.8	53.9	9.1	
Vert	9848.000	AV	34.3	38.5	7.1	34.5	45.4	53.9	8.5	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter-Distance factor(above 10GHz)) - Gain(Amplifier)

*Other frequency noises omitted in this report were not seen or had enough margin (more than 20dB).

*The 10th harmonic was not seen so the result was its base noise level.

Distance factor: 10GHz-26.5GHz 20log(3.0m/1.0m)= 9.5dB

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Radiated Spurious Emission

Test place : Ise EMC Lab. No.2 Semi Anechoic Chamber
Report No. : 10441271H
Date : 08/15/2014
Temperature/ Humidity : 22 deg. C / 56% RH
Engineer : Yuta Moriya
(Above 1GHz)
Mode : 11g Tx 2412MHz

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	2390.000	PK	61.3	27.0	3.0	34.7	56.6	73.9	17.3	
Hori	4824.000	PK	43.0	31.9	5.3	33.9	46.3	73.9	27.6	
Hori	7236.000	PK	44.6	35.7	6.6	33.8	53.1	73.9	20.8	
Hori	9648.000	PK	42.9	38.1	7.0	34.4	53.6	73.9	20.3	
Hori	2390.000	AV	51.3	27.0	3.0	34.7	46.6	53.9	7.3	
Hori	4824.000	AV	35.1	31.9	5.3	33.9	38.4	53.9	15.5	
Hori	7236.000	AV	35.4	35.7	6.6	33.8	43.9	53.9	10.0	
Hori	9648.000	AV	34.9	38.1	7.0	34.4	45.6	53.9	8.4	
Vert	2390.000	PK	61.3	27.0	3.0	34.7	56.6	73.9	17.3	
Vert	4824.000	PK	43.8	31.9	5.3	33.9	47.1	73.9	26.8	
Vert	7236.000	PK	43.5	35.7	6.6	33.8	52.0	73.9	21.9	
Vert	9648.000	PK	43.6	38.1	7.0	34.4	54.3	73.9	19.6	
Vert	2390.000	AV	51.1	27.0	3.0	34.7	46.4	53.9	7.5	
Vert	4824.000	AV	35.8	31.9	5.3	33.9	39.1	53.9	14.8	
Vert	7236.000	AV	34.9	35.7	6.6	33.8	43.4	53.9	10.5	
Vert	9648.000	AV	36.3	38.1	7.0	34.4	47.0	53.9	6.9	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter-Distance factor(above 10GHz)) - Gain(Amplifier)

*Other frequency noises omitted in this report were not seen or had enough margin (more than 20dB).

*The 10th harmonic was not seen so the result was its base noise level.

Distance factor: 10GHz-26.5GHz 20log(3.0m/1.0m)= 9.5dB

20dBc Data Sheet

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	2412.000	PK	99.0	27.0	3.0	34.7	94.3	-	-	Carrier
Hori	2400.000	PK	58.4	27.0	3.0	34.7	53.7	74.3	20.6	
Vert	2412.000	PK	98.1	27.0	3.0	34.7	93.4	-	-	Carrier
Vert	2400.000	PK	58.3	27.0	3.0	34.7	53.6	73.4	19.8	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter-Distance factor(above 10GHz)) - Gain(Amplifier)

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Radiated Spurious Emission

Test place : Ise EMC Lab. No.2 Semi Anechoic Chamber
Report No. : 10441271H
Date : 08/15/2014
Temperature/ Humidity : 22 deg. C / 56% RH
Engineer : Yuta Moriya
(Above 1GHz)
Mode : 11g Tx 2437MHz

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	4874.000	PK	46.4	32.0	5.3	33.9	49.8	73.9	24.1	
Hori	7311.000	PK	43.5	35.8	6.7	33.8	52.2	73.9	21.7	
Hori	9748.000	PK	43.4	38.3	7.1	34.5	54.3	73.9	19.6	
Hori	4874.000	AV	38.5	32.0	5.3	33.9	41.9	53.9	12.0	
Hori	7311.000	AV	35.8	35.8	6.7	33.8	44.5	53.9	9.4	
Hori	9748.000	AV	34.6	38.3	7.1	34.5	45.5	53.9	8.4	
Vert	4874.000	PK	47.1	32.0	5.3	33.9	50.5	73.9	23.4	
Vert	7311.000	PK	43.3	35.8	6.7	33.8	52.0	73.9	21.9	
Vert	9748.000	PK	43.2	38.3	7.1	34.5	54.1	73.9	19.8	
Vert	4874.000	AV	38.6	32.0	5.3	33.9	42.0	53.9	11.9	
Vert	7311.000	AV	35.9	35.8	6.7	33.8	44.6	53.9	9.3	
Vert	9748.000	AV	36.6	38.3	7.1	34.5	47.5	53.9	6.4	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter-Distance factor(above 10GHz)) - Gain(Amplifier)

*Other frequency noises omitted in this report were not seen or had enough margin (more than 20dB).

*The 10th harmonic was not seen so the result was its base noise level.

Distance factor: 10GHz-26.5GHz $20\log(3.0m/1.0m) = 9.5dB$

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Radiated Spurious Emission

Test place Ise EMC Lab. No.2 and 1 Semi Anechoic Chamber
Report No. 10441271H
Date 08/15/2014 08/19/2014
Temperature/ Humidity 22 deg. C / 56% RH 23 deg. C / 63% RH
Engineer Yuta Moriya Satofumi Matsuyama
(Above 1GHz) (Below 1GHz)
Mode 11g Tx 2462MHz

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	74.171	QP	46.2	6.5	8.1	38.8	22.0	40.0	18.0	
Hori	148.341	QP	41.7	14.8	9.0	38.9	26.6	43.5	16.9	
Hori	222.524	QP	45.4	16.8	9.8	39.0	33.0	46.0	13.0	
Hori	296.701	QP	44.1	19.6	10.4	38.6	35.5	46.0	10.5	
Hori	370.877	QP	52.1	16.4	11.0	38.4	41.1	46.0	4.9	
Hori	445.053	QP	45.0	17.6	11.6	38.3	35.9	46.0	10.1	
Hori	2483.500	PK	63.1	26.9	3.1	34.7	58.4	73.9	15.5	
Hori	4924.000	PK	47.0	32.1	5.3	33.9	50.5	73.9	23.4	
Hori	7386.000	PK	43.0	35.8	6.6	33.8	51.6	73.9	22.3	
Hori	9848.000	PK	43.7	38.5	7.1	34.5	54.8	73.9	19.1	
Hori	2483.500	AV	53.6	26.9	3.1	34.7	48.9	53.9	5.0	
Hori	4924.000	AV	39.0	32.1	5.3	33.9	42.5	53.9	11.4	
Hori	7386.000	AV	35.5	35.8	6.6	33.8	44.1	53.9	9.8	
Hori	9848.000	AV	35.7	38.5	7.1	34.5	46.8	53.9	7.1	
Vert	74.173	QP	50.1	6.5	8.1	38.8	25.9	40.0	14.1	
Vert	148.340	QP	38.6	14.8	9.0	38.9	23.5	43.5	20.0	
Vert	222.521	QP	44.1	16.8	9.8	39.0	31.7	46.0	14.3	
Vert	296.701	QP	42.3	19.6	10.4	38.6	33.7	46.0	12.3	
Vert	370.880	QP	51.2	16.4	11.0	38.4	40.2	46.0	5.8	
Vert	445.056	QP	43.3	17.6	11.6	38.3	34.2	46.0	11.8	
Vert	2483.500	PK	61.3	26.9	3.1	34.7	56.6	73.9	17.3	
Vert	4924.000	PK	47.5	32.1	5.3	33.9	51.0	73.9	22.9	
Vert	7386.000	PK	43.1	35.8	6.6	33.8	51.7	73.9	22.3	
Vert	9848.000	PK	42.0	38.5	7.1	34.5	53.1	73.9	20.8	
Vert	2483.500	AV	52.6	26.9	3.1	34.7	47.9	53.9	6.1	
Vert	4924.000	AV	38.9	32.1	5.3	33.9	42.4	53.9	11.5	
Vert	7386.000	AV	35.8	35.8	6.6	33.8	44.4	53.9	9.5	
Vert	9848.000	AV	34.4	38.5	7.1	34.5	45.5	53.9	8.4	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter-Distance factor(above 10GHz)) - Gain(Amplifier)

*Other frequency noises omitted in this report were not seen or had enough margin (more than 20dB).

*The 10th harmonic was not seen so the result was its base noise level.

Distance factor: 10GHz-26.5GHz 20log(3.0m/1.0m)= 9.5dB

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Radiated Spurious Emission

Test place : Ise EMC Lab. No.2 Semi Anechoic Chamber
Report No. : 10441271H
Date : 08/15/2014
Temperature/ Humidity : 22 deg. C / 56% RH
Engineer : Yuta Moriya
(Above 1GHz)
Mode : 11n-20 Tx

2412MHz Band edge

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	2390.000	PK	68.7	27.0	3.0	34.7	64.0	73.9	9.9	
Hori	2390.000	AV	55.3	27.0	3.0	34.7	50.6	53.9	3.3	
Vert	2390.000	PK	66.5	27.0	3.0	34.7	61.8	73.9	12.1	
Vert	2390.000	AV	54.4	27.0	3.0	34.7	49.7	53.9	4.2	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter-Distance factor(above 10GHz)) - Gain(Amplifier)

20dBc Data Sheet

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	2412.000	PK	96.6	27.0	3.0	34.7	91.9	-	-	Carrier
Hori	2400.000	PK	63.5	27.0	3.0	34.7	58.8	71.9	13.1	
Vert	2412.000	PK	96.6	27.0	3.0	34.7	91.9	-	-	Carrier
Vert	2400.000	PK	63.1	27.0	3.0	34.7	58.4	71.9	13.5	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter-Distance factor(above 10GHz)) - Gain(Amplifier)

2462MHz Band edge

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	2483.500	PK	66.7	26.9	3.1	34.7	62.0	73.9	11.9	
Hori	2483.500	AV	54.9	26.9	3.1	34.7	50.2	53.9	3.7	
Vert	2483.500	PK	65.4	26.9	3.1	34.7	60.7	73.9	13.2	
Vert	2483.500	AV	54.5	26.9	3.1	34.7	49.8	53.9	4.1	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter-Distance factor(above 10GHz)) - Gain(Amplifier)

UL Japan, Inc.

Ise EMC Lab.


4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Burst rate confirmation

Test place	Ise EMC Lab. No.1 Semi Anechoic Chamber
Report No.	10441271H
Date	08/20/2014
Temperature/ Humidity	24 deg. C/ 62% RH
Engineer	Yuta Moriya
Mode	Tx



UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN


Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Conducted Spurious Emission

Test place	Ise EMC Lab. No.3 Semi Anechoic Chamber
Report No.	10441271H
Date	09/05/2013
Temperature/ Humidity	23 deg. C/ 68% RH
Engineer	Takumi Shimada
Mode	Tx

11g Tx 2462MHz



Frequency [kHz]	Reading [dBm]	Cable Loss [dB]	Attenuator [dB]	Antenna Gain [dBi]	EIRP [dBm]	Distance [m]	Ground bounce [dB]	E (field strength) [dBuV/m]	Limit [dBuV/m]
67.40	-95.8	0.01	10.0	0.7	-85.1	300.0	6.0	-23.9	31.0
150	-87.5	0.01	10.0	0.7	-76.7	300.0	6.0	-15.5	24.1

$E = \text{EIRP} - 20 \log(D) + \text{Ground bounce} + 104.8 [\text{dBuV/m}]$
 $\text{EIRP} = \text{Reading} + \text{Cable Loss} + \text{Attenuator} + \text{Antenna Gain}$

UL Japan, Inc.
Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN
 Telephone : +81 596 24 8999
 Facsimile : +81 596 24 8124

Power Density

Test place : Ise EMC Lab. No.3 Semi Anechoic Chamber
Report No. : 10441271H
Date : 09/05/2013
Temperature/ Humidity : 23 deg. C/ 68% RH
Engineer : Takumi Shimada
Mode : 11b Tx, 11g Tx, 11n-20 Tx

11b

Freq.	Reading	Cable Loss	Atten.	Result	Limit	Margin
[MHz]	[dBm]	[dB]	[dB]	[dBm]	[dBm]	[dB]
2412.00	-30.32	1.39	10.01	-18.92	8.00	26.92
2437.00	-30.19	1.39	10.01	-18.79	8.00	26.79
2462.00	-30.06	1.39	10.01	-18.66	8.00	26.66

11g

Freq.	Reading	Cable Loss	Atten.	Result	Limit	Margin
[MHz]	[dBm]	[dB]	[dB]	[dBm]	[dBm]	[dB]
2412.00	-27.36	1.39	10.01	-15.96	8.00	23.96
2437.00	-27.29	1.39	10.01	-15.89	8.00	23.89
2462.00	-27.24	1.39	10.01	-15.84	8.00	23.84

11g

Freq.	Reading	Cable Loss	Atten.	Result	Limit	Margin
[MHz]	[dBm]	[dB]	[dB]	[dBm]	[dBm]	[dB]
2412.00	-29.57	1.39	10.01	-18.17	8.00	26.17
2437.00	-29.81	1.39	10.01	-18.41	8.00	26.41
2462.00	-28.67	1.39	10.01	-17.27	8.00	25.27

Sample Calculation:

Result = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator

UL Japan, Inc.


Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124


Power Density




Power Density

11n-20


2412MHz



2437MHz



2462MHz



UL Japan, Inc.
Ise EMC Lab.


4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124


99% Occupied Bandwidth

Test place	Ise EMC Lab. No.3 Semi Anechoic Chamber
Report No.	10441271H
Date	09/11/2014
Temperature/ Humidity	21 deg. C / 54% RH
Engineer	Takumi Shimada
Mode	11b Tx, 11g Tx



99% Occupied Bandwidth

Test place	Ise EMC Lab. No.3 Semi Anechoic Chamber
Report No.	10441271H
Date	09/11/2014
Temperature/ Humidity	21 deg. C / 54% RH
Engineer	Takumi Shimada
Mode	Tx 11n-20



UL Japan, Inc.
Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN
 Telephone : +81 596 24 8999
 Facsimile : +81 596 24 8124

APPENDIX 2: Test instruments

EMI Test Equipment (for Antenna Terminal conducted test: except for 99%Occupied Bandwidth)

Control No.	Instrument	Manufacturer	Model No	Serial No	Test Item	Calibration Date * Interval(month)
MAT-24	Attenuator(10dB)(above1GHz)	Agilent	8493C	71389	AT	2013/06/05 * 12 *1)
MPM-12	Power Meter	Anritsu	ML2495A	0825002	AT	2013/06/12 * 12 *1)
MPSE-17	Power sensor	Anritsu	MA2411B	0738285	AT	2013/06/12 * 12 *1)
MAT-25	Attenuator(10dB)(above1GHz)	Agilent	8493C	71642	AT	2013/06/20 * 12 *1)
MCC-144	Microwave Cable	Junkosha	MWX221	1207S407	AT	2013/08/19 * 12 *1)
MOS-22	Thermo-Hygrometer	Custom	CTH-201	0003	AT	2013/02/26 * 12 *1)
MSA-10	Spectrum Analyzer	Agilent	E4448A	MY46180655	AT	2013/02/22 * 12 *1)

EMI Test Equipment (for Antenna Terminal conducted test: 99%Occupied Bandwidth)

Control No.	Instrument	Manufacturer	Model No	Serial No	Test Item	Calibration Date * Interval(month)
MRENT-116	Spectrum Analyzer	Agilent	E4440A	MY46187620	AT	2014/03/05 * 12
MAT-23	Attenuator(10dB) 1-18GHz	Orient Microwave	BX10-0476-00	-	AT	2014/03/13 * 12
MPM-09	Power Meter	Anritsu	ML2495A	6K00003348	AT	2013/10/21 * 12
MPSE-12	Power sensor	Anritsu	MA2411B	011598	AT	2013/10/21 * 12
MOS-21	Thermo-Hygrometer	Custom	CTH-201	0002	AT	2013/12/17 * 12

***1) This test equipment was used for the tests before the expiration date of the calibration.**

The expiration date of the calibration is the end of the expired month.

All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.

As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.

Test Item: AT: Antenna Terminal Conducted test

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

EMI Test Equipment (for Conducted emission test and Radiated emission test)

Control No.	Instrument	Manufacturer	Model No	Serial No	Test Item	Calibration Date * Interval(month)
MAEC-02	Semi Anechoic Chamber(NSA)	TDK	Semi Anechoic Chamber 3m	DA-06902	RE	2014/06/25 * 12
MOS-22	Thermo-Hygrometer	Custom	CTH-201	0003	RE	2014/02/20 * 12
MJM-14	Measure	KOMELON	KMC-36	-	RE	-
COTS-MEMI	EMI measurement program	TSJ	TEPTO-DV	-	RE	-
MSA-10	Spectrum Analyzer	Agilent	E4448A	MY46180655	RE	2014/02/20 * 12
MHA-06	Horn Antenna 1-18GHz	Schwarzbeck	BBHA9120D	254	RE	2014/02/21 * 12
MCC-166	Microwave Cable	Junkosha	MWX221	1303S120(1m) / 1311S167(5m)	RE	2013/11/27 * 12
MPA-10	Pre Amplifier	Agilent	8449B	3008A02142	RE	2014/01/21 * 12
MHA-02	Horn Antenna 18-26.5GHz	EMCO	3160-09	1265	RE	2014/02/21 * 12
MHF-25	High Pass Filter 3.5-18.0GHz	UL Japan	HPF SELECTOR	001	RE	2013/09/01 * 12
MAEC-01	Semi Anechoic Chamber(NSA)	TDK	Semi Anechoic Chamber 10m	DA-06881	RE/CE	2013/08/01 * 12 *1)
MOS-27	Thermo-Hygrometer	CUSTOM	CTH-201	A08Q26	RE/CE	2014/02/20 * 12
MJM-21	Measure	KOMELON	KMC-36	-	RE/CE	-
MTR-09	EMI Test Receiver	Rohde & Schwarz	ESU26	100412	RE/CE	2014/06/06 * 12
KBA-05	Biconical Antenna	Schwarzbeck	BBA9106	2513	RE	2013/11/24 * 12
KLA-04	Logperiodic Antenna	Schwarzbeck	USLP9143	361	RE	2013/11/24 * 12
MAT-08	Attenuator(6dB)	Weinschel Corp	2	BK7971	RE	2013/11/26 * 12
MCC-02	Coaxial Cable	Suhner/storm/Agilent/TSJ	-	-	RE	2013/09/12 * 12
MPA-19	Pre Amplifier	MITEQ	MLA-10K01-B01-35	1237616	RE	2014/02/17 * 12
MLS-25	LISN(AMN)	Schwarzbeck	NSLK8127	8127-731	CE(EUT)	2014/07/09 * 12
MLS-26	LISN(AMN)	Schwarzbeck	NSLK8127	8127-732	CE(AE)	2014/07/09 * 12
MTA-30	Terminator	TME	CT-01	-	CE	2014/01/20 * 12
MCC-03	Coaxial Cable	Fujikura/Suhner/TSJ	5D-2W(20m)/3D-2W(7.5m)/RG400u(1.5m)/RFM-E421(Switcher)	- /01068(Switcher)	CE	2013/09/12 * 12
MAT-64	Attenuator(13dB)	JFW Industries, Inc.	50FP-013H2 N	-	CE	2014/01/29 * 12

*1) This test equipment was used for the tests before the expiration date of the calibration.

The expiration date of the calibration is the end of the expired month.

All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.

As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.

Test Item: CE: Conducted Emission test

RE: Radiated Emission test

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124