

RF Exposure / SAR Statement

No. : 32DE0050-SH-01-A

Applicant : Sony Corporation
Type of Equipment : AV CENTER
Model No. : XAV-64BT
FCC ID : AK8XAV64BT

Sony Corporation declares that Model : AV CENTER
complies with FCC radiation exposure requirement specified in the FCC Rules 2.1091.
The "XAV-64BT" has 1.49 mW of conducted Peak Output power and 0.57 mW of EIRP.
This equipment is considered as a mobile device so that SAR testing is excluded.
The Following calculation is the reference data for 20cm distance.

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided with the "XAV-64BT" as calculated from FCC OET Bulletin 65 Appendix A, Table (B) Limits for General Population / Uncontrolled Exposure. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0mW/cm² uncontrolled exposure limit. The Friis formula used was:

$$S = (P * G) / (4 * \pi * r^2)$$

Where

P = 1.49 mW (Maximum peak output power)
G = 0.38 Numerical Antenna gain; equal -4.20 dBi
r = 20.0 cm

For: XAV-64BT

$$S = 0.00011 \text{ mW/cm}^2$$

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401