

TABLE OF CONTENTS

<u>RULE</u>	<u>DESCRIPTION</u>	<u>PAGE</u>
	Test Report	1
2.1033(c)	General Information Required	2
2.1033(c) (14)	Rule Summary	4
	Standard Test Conditions and Engineering Practices	5
2.1046(a)	Carrier Output Power (Conducted)	6
2.1051	Unwanted Emissions (Transmitter Conducted)	8
2.1053(a)	Field Strength of Spurious Radiation	11
2.1049(c) (1)	Emission Masks (Occupied Bandwidth)	14
90.214	Transient Frequency Behavior	18
2.1047(a)	Audio Low Pass Filter (Voice Input)	24
2.1047(a)	Audio Frequency Response	27
2.1047(b)	Modulation Limiting	29
2.1055(a) (1)	Frequency Stability (Temperature Variation)	32
2.1055(b) (1)	Frequency Stability (Voltage Variation)	35
2.202(g)	Necessary Bandwidth and Emission Bandwidth	36

PAGE NO. 1 of 36.

Required information per ISO/IEC Guide 25-1990, paragraph 13.2:

- a) TEST REPORT
- b) Laboratory: M. Flom Associates, Inc.
(FCC: 31040/SIT) 3356 N. San Marcos Place, Suite 107
(Canada: IC 2044) Chandler, AZ 85224
- c) Report Number: d98c0030
- d) Client: Kenwood Communications Corporation
P.O. Box 22745
Long Beach, CA 90801-5745
- e) Identification: TK-880-2
FCC ID: ALH24593120
Description: UHF FM Transceiver
- f) EUT Condition: Not required unless specified in individual tests.
- g) Report Date: December 9, 1998
EUT Received: November 11, 1998
- h, j, k): As indicated in individual tests.
- i) Sampling method: No sampling procedure used.
- l) Uncertainty: In accordance with MFA internal quality manual.
- m) Supervised by: 
Morton Flom, P. Eng.
- n) Results: The results presented in this report relate only to the item tested.
- o) Reproduction: This report must not be reproduced, except in full, without written permission from this laboratory.

PAGE NO.

2 of 36.

LIST OF GENERAL INFORMATION REQUIRED FOR CERTIFICATION

IN ACCORDANCE WITH FCC RULES AND REGULATIONS,
VOLUME II, PART 2 AND TO

22, 74, 90

Sub-part 2.1033

(c) (1): NAME AND ADDRESS OF APPLICANT:

Kenwood Communications Corporation
2201 E. Dominguez St
P.O. Box 22745
Long Beach, CA 90801-5745

MANUFACTURER:

Kenwood Electronics Technologies Pte. Ltd.
1 Ang Mo Kio Street 60
Singapore 569110

(c) (2): FCC ID: ALH24593120MODEL NO: TK-880-2(c) (3): INSTRUCTION MANUAL(S):

PLEASE SEE ATTACHED EXHIBITS

(c) (4): TYPE OF EMISSION: 16K0F3E, 11K0F3E(c) (5): FREQUENCY RANGE, MHz: 485 to 512

(c) (6): POWER RATING, Watts: 25
Switchable Variable x N/A

(c) (7): MAXIMUM POWER RATING, Watts: 500

PAGE NO.

3 of 36.

Subpart 2.1033 (continued)

(c)(8): VOLTAGES & CURRENTS IN ALL ELEMENTS IN FINAL R. F. STAGE,
INCLUDING FINAL TRANSISTOR OR SOLID STATE DEVICE:

COLLECTOR CURRENT, A = per manual
COLLECTOR VOLTAGE, Vdc = per manual
SUPPLY VOLTAGE, Vdc = 13.6

(c)(9): TUNE-UP PROCEDURE:

PLEASE SEE ATTACHED EXHIBITS

(c)(10): CIRCUIT DIAGRAM/CIRCUIT DESCRIPTION:
Including description of circuitry & devices provided for
determining and stabilizing frequency, for suppression of
spurious radiation, for limiting modulation and limiting
power.

PLEASE SEE ATTACHED EXHIBITS

(c)(11): LABEL INFORMATION:

PLEASE SEE ATTACHED EXHIBITS

(c)(12): PHOTOGRAPHS:

PLEASE SEE ATTACHED EXHIBITS

(c)(13): DIGITAL MODULATION DESCRIPTION:

ATTACHED EXHIBITS
 x N/A

(c)(14): TEST AND MEASUREMENT DATA:

FOLLOWS

PAGE NO.

4 of 36.

Sub-part 2.1033(c) (14):
TEST AND MEASUREMENT DATA

All tests and measurement data shown were performed in accordance with FCC Rules and Regulations, Volume II, Part 2, Sub-part J, Sections 2.947, 2.1033(c), 2.1041, 2.1046, 2.1047, 2.1079, 2.1051, 2.1053, 2.1055, 2.1057 and the following individual Parts:

21 - Domestic Public Fixed Radio Services	
22 - Public Mobile Services	x
22 Subpart H - Cellular Radiotelephone Service	
22.901(d) - Alternative technologies and auxiliary services	
23 - International Fixed Public Radiocommunication services	
24 - Personal Communications Services	
74 Subpart H - Low Power Auxiliary Stations	x
80 - Stations in the Maritime Services	
80 Subpart E - General Technical Standards	
80 Subpart F - Equipment Authorization for Compulsory Ships	
80 Subpart K - Private Coast Stations and Marine Utility Stations	
80 Subpart S - Compulsory Radiotelephone Installations for Small Passenger Boats	
80 Subpart T - Radiotelephone Installation Required for Vessels on the Great Lakes	
80 Subpart U - Radiotelephone Installations Required by the Bridge-to-Bridge Act	
80 Subpart V - Emergency Position Indicating Radiobeacons (EPIRB'S)	
80 Subpart W - Global Maritime Distress and Safety System (GMDSS)	
80 Subpart X - Voluntary Radio Installations	
87 - Aviation Services	
90 - Private Land Mobile Radio Services	x
94 - Private Operational-Fixed Microwave Service	
95 Subpart A - General Mobile Radio Service (GMR)	
95 Subpart C - Radio Control (R/C) Radio Service	
95 Subpart D - Citizens Band (CB) Radio Service	
95 Subpart E - Family Radio Service	
95 Subpart F - Interactive Video and Data Service (IVDS)	
101 - Fixed Microwave Services	

PAGE NO.

5 of 36.

STANDARD TEST CONDITIONS
and
ENGINEERING PRACTICES

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.4-1992, section 6.1.9, and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104 °F) unless the particular equipment requirements specify testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Prior to testing, the EUT was tuned up in accordance with the manufacturer's alignment procedures. All external gain controls were maintained at the position of maximum and/or optimum gain throughout the testing.

Measurement results, unless otherwise noted, are worst case measurements.

PAGE NO. 6 of 36.
NAME OF TEST: Carrier Output Power (Conducted)
SPECIFICATION: 47 CFR 2.1046(a)
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.1
TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The EUT was connected to a resistive coaxial attenuator of normal load impedance, and the unmodulated output power was measured by means of an R. F. Power Meter.
2. Measurement accuracy is $\pm 3\%$.

MEASUREMENT RESULTS
(Worst case)

FREQUENCY OF CARRIER, MHz = 498.6, 485.1, 511.9

POWER SETTING	R. F. POWER, WATTS
High	25

SUPERVISED BY:

Morton Flom P. Eng.


Morton Flom, P. Eng.

PAGE NO.

7 of 36.

TRANSMITTER POWER CONDUCTED MEASUREMENTS

TEST 1: R. F. POWER OUTPUT
 TEST 2: FREQUENCY STABILITY



Asset Description

s/n

(1) COAXIAL ATTENUATOR

—	i00122	Narda 766-10	7802
—	i00123	Narda 766-10	7802A
—	i00069	Bird 8329 (30 dB)	1006
x	i00113	Sierra 661A-3D	1059

(2) POWER METERS

—	i00014	HP 435A	1733A05836
x	i00039	HP 436A	2709A26776
x	i00020	HP 8901A POWER MODE	2105A01087

(3) FREQUENCY COUNTER

—	i00042	HP 5383A	1628A00959
x	i00019	HP 5334B	2704A00347
x	i00020	HP 8901A FREQUENCY MODE	2105A01087

PAGE NO. 8 of 36.
NAME OF TEST: Unwanted Emissions (Transmitter Conducted)
SPECIFICATION: 47 CFR 2.1051
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.13
TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The emissions were measured for the worst case as follows:
(a): within a band of frequencies defined by the carrier frequency plus and minus one channel.
(b): from the lowest frequency generated in the EUT and to at least the 10th harmonic of the carrier frequency, or 40 GHz, whichever is lower.
2. The magnitude of spurious emissions that are attenuated more than 20 dB below the permissible value need not be specified.
3. MEASUREMENT RESULTS: ATTACHED FOR WORST CASE

FREQUENCY OF CARRIER, MHz = 498.6, 485.1, 511.9
SPECTRUM SEARCHED, GHz = 0 to 10 x Fc
MAXIMUM RESPONSE, Hz = 3160
ALL OTHER EMISSIONS = ≥ 20 dB BELOW LIMIT
LIMIT(S), dBc
 $-(43+10 \times \log P) = -57$ (25 Watts)

SUPERVISED BY:

Morton Flom P. Eng.


Morton Flom, P. Eng.

PAGE NO.

9 of 36.

TRANSMITTER SPURIOUS EMISSION

TEST A. OCCUPIED BANDWIDTH (IN-BAND SPURIOUS)
 TEST B. OUT-OF-BAND SPURIOUS



Asset	Description	s/n
(1)	<u>AUDIO OSCILLATOR/GENERATOR</u>	
—	i00010 HP 204D	1105A04683
—	i00017 HP 8903A	2216A01753
x	i00012 HP 3312A	1432A11250
(2)	<u>COAXIAL ATTENUATOR</u>	
—	i00122 Narda 766-10	7802
—	i00123 Narda 766-10	7802A
x	i00069 Bird 8329 (30 dB)	1006
x	i00113 Sierra 661A-3D	1059
(3)	<u>FILTERS; NOTCH, HP, LP, BP</u>	
x	i00126 Eagle TNF-1	100-250
x	i00125 Eagle TNF-1	50-60
x	i00124 Eagle TNF-1	250-850
(4)	<u>SPECTRUM ANALYZER</u>	
x	i00048 HP 8566B	2511A01467
—	i00029 HP 8563E	3213A00104
(5)	<u>SCOPE</u>	
—	i00058 HP 1741A	2251A09356
—	i00030 HP 54502A	2927A00209
—	i00071 Tektronix 935	1935-B011343

NAME OF TEST: Unwanted Emissions (Transmitter Conducted)
g98b0433: 1998-Nov-16 Mon 12:18:00
STATE: 2:High Power

FREQUENCY TUNED, MHZ	FREQUENCY LEVEL, dbm	LEVEL, dbc	MARGIN, db
498.600000	997.195000	-19.2	-63.1
498.600000	1495.479000	-23.3	-67.2
498.600000	1994.397000	-20.2	-64.1
498.600000	2492.990000	-19.7	-63.6
498.600000	2991.808000	-23.8	-67.7
498.600000	3490.609000	-24.6	-68.5
498.600000	3988.582000	-24.2	-68.1
498.600000	4487.813000	-24.9	-68.8
498.600000	4985.698000	-24.9	-68.8
498.600000	5484.435000	-23.5	-67.4
498.600000	5982.973000	-18.2	-62.1
498.600000	6481.923000	-18.4	-62.3
498.600000	6980.620000	-19.1	-63
498.600000	7478.616000	-18.8	-62.7

PAGE NO. 11 of 36.
NAME OF TEST: Field Strength of Spurious Radiation
SPECIFICATION: 47 CFR 2.1053(a)
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.12
TEST EQUIPMENT: As per attached page


MEASUREMENT PROCEDURE

1. A description of the measurement facilities was filed with the FCC and was found to be in compliance with the requirements of Section 15.38, by letter from the FCC dated March 3, 1997, FILE 31040/SIT. All pertinent changes will be reported to the Commission by up-date prior to March 2000.
2. At first, in order to locate all spurious frequencies and approximate amplitudes, and to determine proper equipment functioning, the test sample was set up at a distance of three meters from the test instrument. Valid spurious signals were determined by switching the power on and off.
3. In the field, the test sample was placed on a wooden turntable above ground at three (or thirty) meters away from the search antenna. Excess power leads were coiled near the power supply.

The cables were oriented in order to obtain the maximum response. At each emission frequency, the turntable was rotated and the search antennas were raised and lowered vertically.
4. The emission was observed with both a vertically polarized and a horizontally polarized search antenna and the worst case was used.
6. The field strength of each emission within 20 dB of the limit was recorded and corrected with the appropriate cable and transducer factors.
7. The worst case for all channels is shown.
8. Measurement results: ATTACHED FOR WORST CASE

PAGE NO.

12 of 36.

RADIATED TEST SETUP

NOTES:

- (a) Search Antenna - Rotatable on boom
 (b) Non-metallic boom
 (c) Non-metallic mast
 (d) Adjustable horizontally
 (e) Equipment Under Test
 (f) Turntable
 (g) Boom adjustable in height.
 (h) External control cables routed horizontally at least one wavelength.
 (i) Rotatable
 (j) Cables routed through hollow turntable center
 (k) 30 cm or less
 (l) External power source
 (m) 10 cm diameter coil of excess cable
 (n) 25 cm (V), 1 m-7 m (V, H)
 (o) 25 cm from bottom end of 'V', 1m normally
 (p) Calibrated Cable at least 10m in length
 (q) Amplifier (optional)
 (r) Spectrum Analyzer

Asset	Description	s/n	Cycle	Last Cal
-------	-------------	-----	-------	----------

Per ANSI C63.4-1992, 10.1.4

TRANSDUCER

___	i00065	EMCO 3109B 100Hz-50MHz	2336	12 mo.	
___	i00033	Singer 94593-1 10kHz-32MHz	0219	12 mo.	
x	i00088	EMCO 3109-B 25MHz-300MHz	2336	12 mo.	Oct-98
x	i00089	Apriel 2001 200MHz-1GHz	001500	12 mo.	Oct-98
x	i00103	EMCO 3115 1GHz-18GHz	9208-3925	12 mo.	Oct-98
___	i00085	EMCO 3116 10GHz-40GHz	2076	12 mo.	

AMPLIFIER

___	i00028	HP 8449A	2749A00121	12 mo.	Mar-98
-----	--------	----------	------------	--------	--------

SPECTRUM ANALYZER

___	i00029	HP 8563E	3213A00104	12 mo.	
x	i00033	HP 85462A	3625A00357	12 mo.	Dec-97
___	i00048	HP 8566B	2511AD1467	6 mo.	Mar-98

PAGE NO. 13 of 36.

NAME OF TEST: Field Strength of Spurious Radiation

ALL OTHER EMISSIONS = $\geq$ 20 dB BELOW LIMIT

<u>EMISSION, MHz/HARMONIC</u>	<u>SPURIOUS LEVEL, dBc</u>
-------------------------------	----------------------------

2nd to 10th	<-60
-------------	------

SUPERVISED BY:



Morton Flom, P. Eng.

PAGE NO. 14 of 36.
NAME OF TEST: Emission Masks (Occupied Bandwidth)
SPECIFICATION: 47 CFR 2.1049(c)(1)
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.11
TEST EQUIPMENT: As per previous page


MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page, with the Spectrum Analyzer connected.
2. For EUTs supporting audio modulation, the audio signal generator was adjusted to the frequency of maximum response and with output level set for ± 2.5 kHz deviation (or 50% modulation). With level constant, the signal level was increased 16 dB.
3. For EUTs supporting digital modulation, the digital modulation mode was operated to its maximum extent.
4. The Occupied Bandwidth was measured with the Spectrum Analyzer controls set as shown on the test results.
5. MEASUREMENT RESULTS: ATTACHED

PAGE NO.

15 of 36.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
g98b0430: 1998-Nov-16 Mon 11:57:00
STATE: 2:High Power



POWER:
MODULATION:

HIGH
NONE


SUPERVISED BY:

Morton Flom P. Eng.
Morton Flom, P. Eng.

PAGE NO.

16 of 36.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
g98b0431: 1998-Nov-16 Mon 12:00:00
STATE: 2:High Power



POWER:
MODULATION:

HIGH
VOICE: 2500 Hz SINE WAVE
MASK: B, VHF/UHF 25kHz,
w/LPF


SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO.

17 of 36.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
g98b0432: 1998-Nov-16 Mon 12:04:00
STATE: 2:High Power



POWER:
MODULATION:

HIGH
VOICE: 2500 Hz SINE WAVE
MASK: D, VHF/UHF 12.5kHz BW

SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO. 18 of 36.
NAME OF TEST: Transient Frequency Behavior
SPECIFICATION: 47 CFR 90.214
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.19
TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The EUT was setup as shown on the attached page, following TIA/EIA-603 steps a, b, and c as a guide.
2. The transmitter was turned on.
3. Sufficient attenuation was provided so that the transmitter carrier level measured at the output of the combiner was 40 dB below the maximum input level of the test receiver. This level was recorded as step f.
4. The transmitter was turned off.
5. An RF signal generator (1) modulated with a 1 kHz tone at either 25, 12.5, or 6.25 kHz deviation, and set to the same frequency as the assigned transmitter frequency, (2) was adjusted to a level -20 dB below the level recorded for step f, as measured at the output of the combiner. This level was then fixed for the remainder of the test and is recorded at step h.
6. The oscilloscope was setup using TIA/EIA-603 steps j and k as a guide, and to either 10 ms/div (UHF) or 5 ms/div (VHF).
7. The 30 dB attenuator was removed, the transmitter was turned on, and the level of the carrier at the output of the combiner was recorded as step l.
8. The carrier on-time as referenced in TIA/EIA-603 steps m, n, and o was captured and plotted. The carrier off-time as referenced in TIA/EIA-603 steps p, q, r, and s was captured and plotted.

LEVELS MEASURED:

step f, dBm	= -6.7
step h, dBm	= -28.4
step l, dBm	= 22.1




SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO.

19 of 36.

TRANSIENT FREQUENCY BEHAVIOR

Asset Description

s/n

(1) ATTENUATOR (Removed after 1st step)x i00112 Philco 30 dB 989(2) ATTENUATOR

i00112 Philco 30 dB 989

i00172 Bird 30 dB 989

x i00122 Narda 10 dB 7802

i00123 Narda 10 dB 7802A

i00110 Kay Variable 145-387

(3) COMBINERx i00154 4 x 25 Ω COMBINER 154(4) CRYSTAL DETECTORx i00159 HP 8470B 1822A10054(5) RF SIGNAL GENERATOR

i00018 HP 8656A 2228A03472


i00031 HP 8656A 2402A06180

x i00067 HP 8920A 3345U01242(6) MODULATION ANALYZERx i00020 HP 8901A 2105A01087(7) SCOPEx i00030 HP 54502A 2927A00209

PAGE NO.

20 of 36.

NAME OF TEST: Transient Frequency Behavior
 g98b0425: 1998-Nov-16 Mon 11:27:00
 STATE: 0:General



Main	Timebase	Delay/Pos	Reference	Mode
	10.0 ms/div	40.0000 ms	Center	Repetitive
Channel 1	Sensitivity	Offset	Probe	Coupling
	275 mV/div	0.00000 V	1.000 :1	dc (1M ohm)

Trigger mode : Edge
 On Negative Edge Of Chan2
 Trigger Level
 Chan2 = -225.000 mV (noise reject ON)
 Holdoff = 40.000 ns

POWER:
 MODULATION:
 DESCRIPTION:

n/a
 Ref Gen=25 kHz Deviation
 CARRIER ON TIME


SUPERVISED BY:

Morton Flom P. Eng.
 Morton Flom, P. Eng.

PAGE NO.

21 of 36.

NAME OF TEST: Transient Frequency Behavior
 g98b0429: 1998-Nov-16 Mon 11:45:00
 STATE: 0:General



POWER:
 MODULATION:
 DESCRIPTION:

n/a
 Ref Gen=25 kHz Deviation
 CARRIER OFF TIME


SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO.

22 of 36.

NAME OF TEST: Transient Frequency Behavior
 g98b0427: 1998-Nov-16 Mon 11:32:00
 STATE: 0:General



Main Timebase 10.0 ms/div Delay/Pos 40.0000 ms Reference Center Mode Repetitive
 Channel 1 Sensitivity 275 mV/div Offset 0.00000 V Probe 1.000 :1 Coupling dc (1M ohm)
 Trigger mode : Edge
 On Negative Edge Of Chan2
 Trigger Level
 Chan2 = -225.000 mV (noise reject ON)
 Holdoff = 40.000 ns

POWER:
 MODULATION:
 DESCRIPTION:

n/a
 Ref Gen=12.5 kHz Deviation
 CARRIER ON TIME


SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO.

23 of 36.

NAME OF TEST: Transient Frequency Behavior
 g98b0428: 1998-Nov-16 Mon 11:33:00
 STATE: 0:General



Main	Timebase	Delay/Pos	Reference	Mode
	10.0 ms/div	-30.0000 ms	Center	Repetitive
Channel 1	Sensitivity	Offset	Probe	Coupling
	275 mV/div	0.00000 V	1.000 :1	dc (1M ohm)

Trigger mode : Edge
 On Positive Edge Of Chan2
 Trigger Level
 Chan2 = -600.000 mV (noise reject ON)
 Holdoff = 40.000 ns

POWER:
 MODULATION:
 DESCRIPTION:

n/a
 Ref Gen=12.5 kHz Deviation
 CARRIER OFF TIME

SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO. 24 of 36.
NAME OF TEST: Audio Low Pass Filter (Voice Input)
SPECIFICATION: 47 CFR 2.1047(a)
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.15
TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE


1. The EUT and test equipment were set up such that the audio input was connected at the input to the modulation limiter, and the modulated stage.
2. The audio output was connected at the output to the modulated stage.
3. MEASUREMENT RESULTS: ATTACHED

PAGE NO.

25 of 36.


TRANSMITTER TEST SET-UP

TEST A. MODULATION CAPABILITY/DISTORTION
 TEST B. AUDIO FREQUENCY RESPONSE
 TEST C. HUM AND NOISE LEVEL
 TEST D. RESPONSE OF LOW PASS FILTER
 TEST E. MODULATION LIMITING



Asset	Description	s/n
(1) <u>LINE IMPEDANCE STABILIZATION NETWORK</u>		
	i00010 HP 204D	1105A04683
<u>x</u>	i00017 HP 8903A	2216A01753
<u>x</u>	i00118 HP 33120A	US36002064
(2) <u>COAXIAL ATTENUATOR</u>		
	i00122 NARDA 766-10	7802
	i00123 NARDA 766-10	7802A
<u>x</u>	i00113 SIERRA 661A-3D	1059
	i00069 BIRD 8329 (30 dB)	10066
(3) <u>MODULATION ANALYZER</u>		
<u>x</u>	i00020 HP 8901A	2105A01087
(4) <u>AUDIO ANALYZER</u>		
<u>x</u>	i00017 HP 8903A	2216A01753
(5) <u>SCOPE</u>		
	i00058 HP 1741A	2215A09356
	i00071 Tektronix 935	1935-B011343

NAME OF TEST: Audio Low Pass Filter (Voice Input)
g98b0136: 1998-Nov-16 Mon 13:27:00
STATE: 0:General



Morton Flom, P. Eng.

M. Flom P. Eng.

SUPERVISED BY:


1. The EUT and test equipment were set up as shown on the following page.
2. The audio signal generator was connected to the audio input circuit/microphone of the EUT.
3. The audio signal input was adjusted to obtain 20% modulation at 1 kHz, and this point was taken as the 0 dB reference level.
4. With input levels held constant and below limiting at all frequencies, the audio signal generator was varied from 100 Hz to 50 kHz.
5. The response in dB relative to 1 kHz was then measured, using the HP 8901A Modulation Analyzer.
6. MEASUREMENT RESULTS: ATTACHED

MEASUREMENT PROCEDURE

NAME OF TEST:	Audio Frequency Response
SPECIFICATION:	47 CFR 2.1047(a)
GUIDE:	ANSI/TIA/EIA-603-1992, Paragraph 2.2.6
TEST EQUIPMENT:	As per previous page

PAGE NO. 27 of 36.

NAME OF TEST: Audio Frequency Response
 g98b0134: 1998-Nov-16 Mon 13:22:00
 STATE: 0:General



Additional points:

FREQUENCY, Hz	LEVEL, dB
300	-12.18
20000	-27.52
30000	-27.68
50000	-27.71

Am. J. Eng.
 Morton Flom, P. Eng.

SUPERVISED BY:

1. The signal generator was connected to the input of the EUT as for "Frequency Response of the Modulating Circuit."
2. The modulation response was measured for each of three frequencies (one of which was the frequency of maximum response), and the input voltage was varied and was observed on an HP 8901A Modulation Analyzer.
3. The input level was varied from 30% modulation (± 1.5 kHz deviation) to at least 20 dB higher than the saturation point.
4. Measurements were performed for both negative and positive modulation and the respective results were recorded.
5. MEASUREMENT RESULTS: ATTACHED


MEASUREMENT PROCEDURE

PAGE NO.	29 of 36.
NAME OF TEST:	Modulation Limiting
SPECIFICATION:	47 CFR 2.1047(b)
GUIDE:	ANSI/TIA/EIA-603-1992, Paragraph 2.2.3
TEST EQUIPMENT:	As per previous page


SUPERVISED BY:

Morton Flom, P. Eng.

M. Flom



Negative Peaks:




Positive Peaks:

NAME OF TEST: Modulation Limiting
STATE: 0:General
g98b0137: 1998-Nov-16 Mon 13:32:00


NAME OF TEST: Modulation Limiting
g98b0138: 1998-Nov-16 Mon 13:37:00
STATE: 0:General

PAGE NO.

Positive
Peaks:



Negative
Peaks:



Morton Flom, P. Eng.

M. Flom

SUPERVISED BY:

Frequency Stability (Temperature Variation)

NAME OF TEST:

47 CFR 2.1055(a)(1)

SPECIFICATION:

ANSI/TIA/EIA-603-1992, Paragraph 2.2.2

GUIDE:

TEST CONDITIONS:

As Indicated

TEST EQUIPMENT:

As per previous page

MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page.

2. With all power removed, the temperature was decreased to -30°C and permitted to stabilize for three hours. Power was applied and the maximum change in frequency was noted within one minute.


3. With power OFF, the temperature was raised in 10°C steps. The sample was permitted to stabilize at each step for at least one-half hour. Power was applied and the maximum frequency change was noted within one minute.

4. The temperature tests were performed for the worst case.

5. MEASUREMENT RESULTS: ATTACHED

TRANSMITTER TEST SET-UP

- TEST A. OPERATIONAL STABILITY
- TEST B. CARRIER FREQUENCY STABILITY
- TEST C. OPERATIONAL PERFORMANCE STABILITY
- TEST D. HUMIDITY
- TEST E. VIBRATION
- TEST F. ENVIRONMENTAL TEMPERATURE
- TEST G. FREQUENCY STABILITY: TEMPERATURE VARIATION
- TEST H. FREQUENCY STABILITY: VOLTAGE VARIATION



Asset	Description	s/n
(1)	TEMPERATURE, HUMIDITY, VIBRATION	
x	100027 Tenny Temp. Chamber	9083-765-234
100	Weber Humidity Chamber	
100	L.A.B. RVH 18-100	

(2)	COAXIAL ATTENUATOR	
100122	NARDA 766-10	7802
100123	NARDA 766-10	7802A
x	100113 SIERRA 661A-3D	1059
100069	BIRD 8329 (30 dB)	10066


(3)	R.F. POWER	
100014	HP 435A POWER METER	1733A05839
x	100039 HP 436A POWER METER	2709A26776
x	100020 HP 8901A POWER METER	2105A01087

(4)	FREQUENCY COUNTER	
100042	HP 5383A	1628A00959
x	100019 HP 5334B	2704A00347
x	100020 HP 8901A	2105A01087

PAGE NO.

34 of 36.

NAME OF TEST: Frequency Stability (Temperature Variation)
 998b0253: 1998-Nov-18 Wed 07:27:00
 STATE: 0:General



Mr. James P. Eng
 Morton Flom, P. Eng.
 SUPERVISED BY:

SUPERVISED BY:

Morton Flom, P. Eng.



% of STV	Voltage	Frequency, MHz	Change, Hz	Change, ppm
85	11.56	498.600010	10	0.02
100	13.6	498.600000	0	0.00
115	15.64	498.600000	0	0.00
76	10.3	498.600010	10	0.02

LIMIT, ppm = 2.5
 LIMIT, Hz = 1247
 BATTERY END POINT (Voltage) = 10.3

RESULTS: 998b0434: 1998-Nov-16 Mon 12:31:58
 STATE: 0:General

1. The EUT was placed in a temperature chamber at 25±5°C and connected as for "Frequency Stability - Temperature Variation" test.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

MEASUREMENT PROCEDURE

PAGE NO. 35 of 36.

NAME OF TEST: Frequency Stability (Voltage Variation)

SPECIFICATION: 47 CFR 2.1055(b) (1)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.2

TEST EQUIPMENT: As per previous page

PAGE NO. NAME OF TEST: Necessary Bandwidth and Emission Bandwidth
SPECIFICATION: 47 CFR 2.202(g)

MODULATION = 16K0F3E
NECESSARY BANDWIDTH CALCULATION:
MAXIMUM MODULATION (M), KHz
MAXIMUM DEVIATION (D), KHz
CONSTANT FACTOR (K)
NECESSARY BANDWIDTH (B_N), KHz
= 3
= 5
= 1
= (2 x M) + (2 x D x K)
= 16.0

MODULATION = 11K0F3E
NECESSARY BANDWIDTH CALCULATION:
MAXIMUM MODULATION (M), KHz
MAXIMUM DEVIATION (D), KHz
CONSTANT FACTOR (K)
NECESSARY BANDWIDTH (B_N), KHz
= 3
= 2.5
= 1
= (2 x M) + (2 x D x K)
= 11.0

Supervised By: *Al. J. Eng.*
Morton Flom, P. Eng.

CERTIFYING ENGINEER:

Morton Flom, P. Eng.

M. Flom

1. THAT the application was prepared either by, or under the direct supervision of, the undersigned.
2. THAT the technical data supplied with the application was taken under my direction and supervision.
3. THAT the data was obtained on representative units, randomly selected.
4. THAT, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.

THIS IS TO CERTIFY THAT:

TESTIMONIAL
AND
STATEMENT OF CERTIFICATION

STATEMENT OF QUALIFICATIONS

EDUCATION:

1. B. ENG. in ENGINEERING PHYSICS, 1949, McGill University, Montreal. Canada.
2. Post Graduate Studies, McGill University & Sir George Williams University, Montreal.

PROFESSIONAL AFFILIATIONS:

1. ARIZONA SOCIETY OF PROFESSIONAL ENGINEERS (NSPE), #026 031 821.
2. ORDER OF ENGINEERS (QUEBEC) 1949. #45 34.
3. ASSOCIATION OF PROFESSIONAL ENGINEERS, GEOPHYSICISTS & GEOLOGISTS OF ALBERIA #5916.
4. REGISTERED ENGINEERING CONSULTANT - GOVERNMENT OF CANADA, DEPARTMENT OF COMMUNICATIONS. Radio Equipment approvals.
5. IEEE, Lifetime member no. 041/204 (Member since 1947).

EXPERIENCE:

1. Research/Development/Senior Project Engineer. R.C.A. LIMITED (4 years).
2. Owner/Chief Engineer of Electronics. Design/Manufacturing & Cable TV Companies (10 years)
3. CONSULTING ENGINEER (over 25 years).



MORTON FLOM, P. Eng.