



M. Flom Associates, Inc. - Global Compliance Center

3356 North San Marcos Place, Suite 107, Chandler, Arizona 85225-7176

www.mflom.com general@mflom.com (480) 926-3100, FAX: 926-3598

Date: December 17, 2001

Federal Communications Commission
Via: Electronic Filing

Attention: Authorization & Evaluation Division

Applicant: Kenwood Communications Corporation
Equipment: TK-8102H-2
FCC ID: ALH32943220
FCC Rules: 74, 90, 90.210, 95

Gentlemen:

On behalf of the Applicant, enclosed please find Application Form 731, Engineering Test Report and all pertinent documentation, the whole for approval of the referenced equipment as shown.

Filing fees are attached.

We trust the same is in order. Should you need any further information, kindly contact the writer who is authorized to act as agent.

Sincerely yours,

A handwritten signature in black ink, appearing to read 'M. Flom P. Eng.' The signature is written in a cursive style with a horizontal line underneath the name.

Morton Flom, P. Eng.

enclosure(s)
cc: Applicant
MF/cvr

LIST OF EXHIBITS
(FCC **CERTIFICATION** (TRANSMITTERS) - REVISED 9/28/98)

APPLICANT: Kenwood Communications Corporation

FCC ID: ALH32943220

BY APPLICANT:

1. LETTER OF AUTHORIZATION	x
2. IDENTIFICATION DRAWINGS, 2.1033(c)(11)	
<input checked="" type="checkbox"/> LABEL	
<input checked="" type="checkbox"/> LOCATION OF LABEL	
<input checked="" type="checkbox"/> COMPLIANCE STATEMENT	
<input checked="" type="checkbox"/> LOCATION OF COMPLIANCE STATEMENT	
3. PHOTOGRAPHS, 2.1033(c)(12)	x
4. DOCUMENTATION: 2.1033(c)	
(3) USER MANUAL	x
(9) TUNE UP INFO	x
(10) SCHEMATIC DIAGRAM	x
(10) CIRCUIT DESCRIPTION	x
BLOCK DIAGRAM	x
PARTS LIST	x
ACTIVE DEVICES	x
5. PART 90.203(e) & (g) ATTESTATION	x
6. MPE Report	x

BY M.F.A. INC.

A. TESTIMONIAL & STATEMENT OF CERTIFICATION
B. STATEMENT OF QUALIFICATIONS



M. Flom Associates, Inc. - Global Compliance Center

3356 North San Marcos Place, Suite 107, Chandler, Arizona 85225-7176

www.mflom.com general@mflom.com (480) 926-3100, FAX: 926-3598

T R A N S M I T T E R C E R T I F I C A T I O N

of

FCC ID: ALH32943220

MODEL: TK-8102H-2

to

FEDERAL COMMUNICATIONS COMMISSION

Rule Part(s) 74, 90, 90.210, 95

DATE OF REPORT: December 17, 2001

ON THE BEHALF OF THE APPLICANT:

Kenwood Communications Corporation

AT THE REQUEST OF:

P.O. 41640

Kenwood Communications Corporation
Technology Park at Johns Creek
3975 Johns Creek Court #300
Suwanee, GA 30024

Attention of:

Joel E. Berger, Research & Development
JBerger@kenwoodusa.com
(678) 474-4722; FAX: -4731

SUPERVISED BY:



Morton Flom, P. Eng.

THE APPLICANT HAS BEEN CAUTIONED AS TO THE FOLLOWING:

15.21 INFORMATION TO USER.

The users manual or instruction manual for an intentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

15.27(a) SPECIAL ACCESSORIES.

Equipment marketed to a consumer must be capable of complying with the necessary regulations in the configuration in which the equipment is marketed. Where special accessories, such as shielded cables and/or special connectors are required to enable an unintentional or intentional radiator to comply with the emission limits in this part, the equipment must be marketed with, i.e. shipped and sold with, those special accessories. However, in lieu of shipping or packaging the special accessories with the unintentional or intentional radiator, the responsible party may employ other methods of ensuring that the special accessories are provided to the consumer, without additional charge.

Information detailing any alternative method used to supply the special accessories for a grant of equipment authorization or retained in the verification records, as appropriate. The party responsible for the equipment, as detailed in § 2.909 of this chapter, shall ensure that these special accessories are provided with the equipment. The instruction manual for such devices shall include appropriate instructions on the first page of text concerned with the installation of the device that these special accessories must be used with the device. It is the responsibility of the user to use the needed special accessories supplied with the equipment.

TABLE OF CONTENTS

<u>RULE</u>	<u>DESCRIPTION</u>	<u>PAGE</u>
	Test Report	1
2.1033(c)	General Information Required	2
2.1033(c)(14)	Rule Summary	5
	Standard Test Conditions and Engineering Practices	6
2.1046(a)	Carrier Output Power (Conducted)	7
2.1046(a)	ERP Carrier Power (Radiated)	9
2.1051	Unwanted Emissions (Transmitter Conducted)	10
2.1053(a)	Field Strength of Spurious Radiation	14
2.1049(c)(1)	Emission Masks (Occupied Bandwidth)	18
90.214	Transient Frequency Behavior	25
2.1047(a)	Audio Low Pass Filter (Voice Input)	31
2.1047(a)	Audio Frequency Response	34
2.1047(b)	Modulation Limiting	36
2.1055(a)(1)	Frequency Stability (Temperature Variation)	39
2.1055(b)(1)	Frequency Stability (Voltage Variation)	42
2.202(g)	Necessary Bandwidth and Emission Bandwidth	43

PAGE NO.

1 of 43.

Required information per ISO/IEC Guide 25-1990, paragraph 13.2:

a)

TEST REPORT

b) Laboratory: M. Flom Associates, Inc.
(FCC: 31040/SIT) 3356 N. San Marcos Place, Suite 107
(Canada: IC 2044) Chandler, AZ 85225

c) Report Number: d01c0031

d) Client: Kenwood Communications Corporation
Technology Park at Johns Creek
3975 Johns Creek Court #300
Suwanee, GA 30024

e) Identification: TK-8102H-2
EUT Description: FCC ID: ALH32943220
UHF FM Transceiver

f) EUT Condition: Not required unless specified in individual tests.

g) Report Date: December 17, 2001
EUT Received: December 7, 2001

h, j, k): As indicated in individual tests.

i) Sampling method: No sampling procedure used.

l) Uncertainty: In accordance with MFA internal quality manual.

m) Supervised by:

n) Results: The results presented in this report relate only to the item tested.

o) Reproduction: This report must not be reproduced, except in full, without written permission from this laboratory.



Morton Flom, P. Eng.

PAGE NO.

2 of 43.

LIST OF GENERAL INFORMATION REQUIRED FOR CERTIFICATIONIN ACCORDANCE WITH FCC RULES AND REGULATIONS,
VOLUME II, PART 2 AND TO

74, 90, 90.210, 95

Sub-part 2.1033

(c)(1): NAME AND ADDRESS OF APPLICANT:Kenwood Communications Corporation
Technology Park at Johns Creek
3975 Johns Creek Court #300
Suwanee, GA 30024MANUFACTURER:Kenwood Electronics Technologies PTE Ltd.
1 Ang Mo Kio Street 63
Singapore 569110(c)(2): FCC ID: ALH32943220MODEL NO: TK-8102H-2(c)(3): INSTRUCTION MANUAL(S):

PLEASE SEE ATTACHED EXHIBITS

(c)(4): TYPE OF EMISSION: 16K0F3E, 11K0F3E(c)(5): FREQUENCY RANGE, MHz: 485 to 512(c)(6): POWER RATING, Watts: 25 to 45
 Switchable Variable N/A


FCC GRANT NOTE: BM - The output power is continuously variable from the value listed in this entry to 50%-55% of the value listed.

(c)(7): MAXIMUM POWER RATING, Watts: 300DUT RESULTS: Passes Fails

PAGE NO.

3 of 43.

M. Flom Associates, Inc. is accredited by the American Association for Laboratory Association (A2LA) as shown in the scope below.



"This laboratory is accredited by the American Association for Laboratory Accreditation (A2LA) and the results shown in this report have been determined in accordance with the laboratory's terms of accreditation unless stated otherwise in the report."

Should this report contain any data for tests for which we are not accredited, or which have been undertaken by a subcontractor that is not A2LA accredited, such data would not be covered by this laboratory's A2LA accreditation.

PAGE NO. 4 of 43.

Subpart 2.1033 (continued)

(c)(8): VOLTAGES & CURRENTS IN ALL ELEMENTS IN FINAL R. F. STAGE, INCLUDING FINAL TRANSISTOR OR SOLID STATE DEVICE:

COLLECTOR CURRENT, A = per manual
COLLECTOR VOLTAGE, Vdc = per manual
SUPPLY VOLTAGE, Vdc = 13.6

(c)(9): TUNE-UP PROCEDURE:

PLEASE SEE ATTACHED EXHIBITS

(c)(10): CIRCUIT DIAGRAM/CIRCUIT DESCRIPTION:

Including description of circuitry & devices provided for determining and stabilizing frequency, for suppression of spurious radiation, for limiting modulation and limiting power.

PLEASE SEE ATTACHED EXHIBITS

(c)(11): LABEL INFORMATION:

PLEASE SEE ATTACHED EXHIBITS

(c)(12): PHOTOGRAPHS:

PLEASE SEE ATTACHED EXHIBITS

(c)(13): DIGITAL MODULATION DESCRIPTION:

 ATTACHED EXHIBITS
 x N/A

(c)(14): TEST AND MEASUREMENT DATA:

FOLLOWS

PAGE NO.

5 of 43.

Sub-part

2.1033(c)(14):TEST AND MEASUREMENT DATA

All tests and measurement data shown were performed in accordance with FCC Rules and Regulations, Volume II; Part 2, Sub-part J, Sections 2.947, 2.1033(c), 2.1041, 2.1046, 2.1047, 2.1079, 2.1051, 2.1053, 2.1055, 2.1057 and the following individual Parts:

- x 21 - Domestic Public Fixed Radio Services
- 22 - Public Mobile Services
- 22 Subpart H - Cellular Radiotelephone Service
- 22.901(d) - Alternative technologies and auxiliary services
- 23 - International Fixed Public Radiocommunication services
- 24 - Personal Communications Services
- x 74 Subpart H - Low Power Auxiliary Stations
- 80 - Stations in the Maritime Services
- 80 Subpart E - General Technical Standards
- 80 Subpart F - Equipment Authorization for Compulsory Ships
- 80 Subpart K - Private Coast Stations and Marine Utility Stations
- 80 Subpart S - Compulsory Radiotelephone Installations for Small Passenger Boats
- 80 Subpart T - Radiotelephone Installation Required for Vessels on the Great Lakes
- 80 Subpart U - Radiotelephone Installations Required by the Bridge-to-Bridge Act
- 80 Subpart V - Emergency Position Indicating Radiobeacons (EPIRB'S)
- 80 Subpart W - Global Maritime Distress and Safety System (GMDSS)
- 80 Subpart X - Voluntary Radio Installations
- 87 - Aviation Services
- x 90 - Private Land Mobile Radio Services
- 94 - Private Operational-Fixed Microwave Service
- 95 Subpart A - General Mobile Radio Service (GMRS)
- 95 Subpart C - Radio Control (R/C) Radio Service
- 95 Subpart D - Citizens Band (CB) Radio Service
- 95 Subpart E - Family Radio Service
- 95 Subpart F - Interactive Video and Data Service (IVDS)
- 97 - Amateur Radio Service
- 101 - Fixed Microwave Services

PAGE NO.

6 of 43.

STANDARD TEST CONDITIONS
and
ENGINEERING PRACTICES

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.4-1992/2000 Draft, section 6.1.9, and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104 °F) unless the particular equipment requirements specify testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Prior to testing, the EUT was tuned up in accordance with the manufacturer's alignment procedures. All external gain controls were maintained at the position of maximum and/or optimum gain throughout the testing.

Measurement results, unless otherwise noted, are worst case measurements.

PAGE NO. 7 of 43.
NAME OF TEST: Carrier Output Power (Conducted)
SPECIFICATION: 47 CFR 2.1046(a)
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.1
TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The EUT was connected to a resistive coaxial attenuator of normal load impedance, and the unmodulated output power was measured by means of an R. F. Power Meter.
2. Measurement accuracy is $\pm 3\%$.

MEASUREMENT RESULTS
(Worst case)

FREQUENCY OF CARRIER, MHz = 498.75, 511.75, 485.25

POWER SETTING	R. F. POWER, WATTS
Low	25
High	45


PERFORMED BY:  Doug Noble, B.A.S. E.E.T.

PAGE NO.

8 of 43.

TRANSMITTER POWER CONDUCTED MEASUREMENTS

TEST 1: R. F. POWER OUTPUT
 TEST 2: FREQUENCY STABILITY



Asset Description (as applicable)	s/n
(1) COAXIAL ATTENUATOR	
i00122 Narda 766-10	7802
i00123 Narda 766-10	7802A
i00069 Bird 8329 (30 dB)	1006
i00113 Sierra 661A-3D	1059
(2) POWER METERS	
i00014 HP 435A	1733A05836
i00039 HP 436A	2709A26776
i00020 HP 8901A POWER MODE	2105A01087
(3) FREQUENCY COUNTER	
i00042 HP 5383A	1628A00959
i00019 HP 5334B	2704A00347
i00020 HP 8901A FREQUENCY MODE	2105A01087

PAGE NO.

9 of 43.

NAME OF TEST:

ERP Carrier Power (Radiated)


SPECIFICATION:

TIA/EIA 603A (Substitution Method)

2.2.17.1 Definition: The average radiated power of a licensed device is the equivalent power required, when delivered to a half-wave dipole or horn antenna, to produce at a distant point the same average received power as produced by the licensed device.

2.2.17.2 Method of Measurement:

a) Connect the equipment as illustrated. Place the transmitter to be tested on the turntable in the standard test site.



b) Raise and lower the test antenna from 1m to 6 m with the transmitter facing the antenna and record the highest received signal in dB as LVL.

c) Repeat step b) for seven additional readings at 45° interval positions of the turntable.

d) Replace the transmitter under test with a half-wave or horn vertically polarized antenna. The center of the antenna should be at the same location as the transmitter under test. Connect the antenna to a signal generator with a known output power and record the path loss in dB or LOSS.

e) Calculate the average radiated output power from the readings in step c) and d) by the following:

$$\text{average radiated power} = 10 \log_{10} \sum 10(\text{LVL} - \text{LOSS})/10 \text{ (dBm)}$$

RESULTS				
	485.25 MHz LVL, dbm	498.25 MHz LVL, dbm	511.75 MHz LVL, dbm	Path Loss, db
0°	45.6	44.7	42.5	0.7
45°	42.2	39.4	38.2	0.7
90°	42.9	37.0	33.4	0.7
135°	41.3	38.7	39.0	0.7
180°	42.8	38.8	33.7	0.7
225°	43.4	39.6	36.7	0.7
270°	42.3	35.9	37.2	0.7
315°	45.3	35.1	39.4	0.7
Av. Radiated Power:				
		485.25 MHz 43.89 dbm	498.25 MHz 39.35 dbm	511.75 MHz 38.21 dbm

PAGE NO. 10 of 43.

NAME OF TEST: Unwanted Emissions (Transmitter Conducted)

SPECIFICATION: 47 CFR 2.1051

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.13

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The emissions were measured for the worst case as follows:
 - (a): within a band of frequencies defined by the carrier frequency plus and minus one channel.
 - (b): from the lowest frequency generated in the EUT and to at least the 10th harmonic of the carrier frequency, or 40 GHz, whichever is lower.
2. The magnitude of spurious emissions that are attenuated more than 20 dB below the permissible value need not be specified.
3. MEASUREMENT RESULTS: ATTACHED FOR WORST CASE

FREQUENCY OF CARRIER, MHz = 498.75, 511.75, 485.25
SPECTRUM SEARCHED, GHz = 0 to $10 \times F_c$
MAXIMUM RESPONSE, Hz = 2820
ALL OTHER EMISSIONS = ≥ 20 dB BELOW LIMIT

PERFORMED BY:



Doug Noble, B.A.S. E.E.T.

PAGE NO.

11 of 43.

TRANSMITTER SPURIOUS EMISSION

TEST A. OCCUPIED BANDWIDTH (IN-BAND SPURIOUS)
 TEST B. OUT-OF-BAND SPURIOUS



Asset Description (as applicable)	s/n
(1) <u>AUDIO OSCILLATOR/GENERATOR</u>	
i00010 HP 204D	1105A04683
i00017 HP 8903A	2216A01753
i00012 HP 3312A	1432A11250
(2) <u>COAXIAL ATTENUATOR</u>	
i00122 Narda 766-10	7802
i00123 Narda 766-10	7802A
i00069 Bird 8329 (30 dB)	1006
i00113 Sierra 661A-3D	1059
(3) <u>FILTERS; NOTCH, HP, LP, BP</u>	
i00126 Eagle TNF-1	100-250
i00125 Eagle TNF-1	50-60
i00124 Eagle TNF-1	250-850
(4) <u>SPECTRUM ANALYZER</u>	
i00048 HP 8566B	2511A01467
i00029 HP 8563E	3213A00104

PAGE NO.

12 of 43.

NAME OF TEST:

Unwanted Emissions (Transmitter Conducted)

LIMIT(S), dBc: $-(43+10\log P) = -57$ (25 Watts)
 $-(43+10\log P) = -59.5$ (45 Watts)

Low Power g01c0164: 2001-Dec-12 Wed 16:04:00

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	LEVEL, dBm	LEVEL, dBc	MARGIN, dB
485.250000	970.501000	-21.9	-65.8	-8.9
498.250000	996.493000	-27.4	-71.3	-14.4
511.750000	1023.505000	-29.8	-73.7	-16.8
485.250000	1455.678000	-32.6	-76.5	-19.6
498.250000	1494.693000	-32.3	-76.2	-19.3
511.750000	1535.268000	-32.7	-76.6	-19.7
485.250000	1940.525000	-31.9	-75.8	-18.9
498.250000	1992.981000	-30.6	-74.5	-17.6
511.750000	2046.680000	-32.1	-76	-19.1
485.250000	2426.604000	-31	-74.9	-18
498.250000	2491.349000	-30.5	-74.4	-17.5
511.750000	2558.882000	-33.1	-77	-20.1
485.250000	2911.384000	-33.1	-77	-20.1
498.250000	2989.297000	-34.3	-78.2	-21.3
511.750000	3070.602000	-32.8	-76.7	-19.8
485.250000	3396.552000	-34.1	-78	-21.1
498.250000	3487.674000	-33.3	-77.2	-20.3
511.750000	3582.061000	-33.5	-77.4	-20.5
485.250000	3881.919000	-34.4	-78.3	-21.4
498.250000	3985.553000	-33.3	-77.2	-20.3
511.750000	4094.262000	-33.6	-77.5	-20.6
485.250000	4367.164000	-34.3	-78.2	-21.3
498.250000	4484.214000	-33.6	-77.5	-20.6
511.750000	4606.083000	-33	-76.9	-20
485.250000	4852.817000	-33.4	-77.3	-20.4
498.250000	4982.437000	-33.2	-77.1	-20.2
511.750000	5117.373000	-34.3	-78.2	-21.3
485.250000	5338.075000	-31.6	-75.5	-18.6
498.250000	5480.639000	-32.7	-76.6	-19.7
511.750000	5629.055000	-32.9	-76.8	-19.9
485.250000	5823.004000	-27.8	-71.7	-14.8
498.250000	5978.927000	-28.1	-72	-15.1
511.750000	6140.708000	-27.1	-71	-14.1
485.250000	6308.477000	-27.6	-71.5	-14.6
498.250000	6477.149000	-28.2	-72.1	-15.2
511.750000	6652.812000	-28.8	-72.7	-15.8
485.250000	6793.202000	-28.2	-72.1	-15.2
498.250000	6975.486000	-27.9	-71.8	-14.9
511.750000	7164.042000	-28	-71.9	-15
485.250000	7278.563000	-27.5	-71.4	-14.5
498.250000	7474.087000	-28.3	-72.2	-15.3
511.750000	7676.001000	-27.5	-71.4	-14.5

PERFORMED BY:

Doug Noble, B.A.S. E.E.T.

PAGE NO.

13 of 43.

NAME OF TEST:

Unwanted Emissions (Transmitter Conducted)

LIMIT(S), dBc: $-(43+10\log P) = -57$ (25 Watts)
 $-(43+10\log P) = -59.5$ (45 Watts)

High Power g01c0163: 2001-Dec-12 Wed 15:40:00

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	LEVEL, dBm	LEVEL, dBc	MARGIN, dB
485.250000	970.566000	-32.1	-78.6	-19.1
498.250000	996.526000	-33	-79.5	-20
511.750000	1023.498000	-31.7	-78.2	-18.7
485.250000	1455.930000	-31.7	-78.2	-18.7
498.250000	1494.496000	-32.8	-79.3	-19.8
511.750000	1535.569000	-32.1	-78.6	-19.1
485.250000	1941.150000	-31.9	-78.4	-18.9
498.250000	1992.799000	-31.6	-78.1	-18.6
511.750000	2046.849000	-31.8	-78.3	-18.8
485.250000	2425.955000	-30.6	-77.1	-17.6
498.250000	2491.449000	-30.6	-77.1	-17.6
511.750000	2558.795000	-32.7	-79.2	-19.7
485.250000	2911.299000	-34.1	-80.6	-21.1
498.250000	2989.683000	-33.5	-80	-20.5
511.750000	3070.648000	-33.5	-80	-20.5
485.250000	3396.858000	-33.3	-79.8	-20.3
498.250000	3487.387000	-33.3	-79.8	-20.3
511.750000	3582.344000	-33.6	-80.1	-20.6
485.250000	3882.093000	-33.9	-80.4	-20.9
498.250000	3985.845000	-34.1	-80.6	-21.1
511.750000	4094.098000	-33.6	-80.1	-20.6
485.250000	4367.488000	-34	-80.5	-21
498.250000	4484.597000	-32.9	-79.4	-19.9
511.750000	4605.920000	-33.5	-80	-20.5
485.250000	4852.574000	-32.7	-79.2	-19.7
498.250000	4982.970000	-33.1	-79.6	-20.1
511.750000	5117.155000	-34	-80.5	-21
485.250000	5338.132000	-33	-79.5	-20
498.250000	5480.378000	-31.9	-78.4	-18.9
511.750000	5628.768000	-33.6	-80.1	-20.6
485.250000	5822.745000	-27	-73.5	-14
498.250000	5978.676000	-27.2	-73.7	-14.2
511.750000	6141.394000	-27.7	-74.2	-14.7
485.250000	6308.148000	-27.3	-73.8	-14.3
498.250000	6477.718000	-27.3	-73.8	-14.3
511.750000	6652.588000	-27.8	-74.3	-14.8
485.250000	6793.045000	-27.3	-73.8	-14.3
498.250000	6975.290000	-27.8	-74.3	-14.8
511.750000	7164.853000	-27.9	-74.4	-14.9
485.250000	7279.022000	-27.8	-74.3	-14.8
498.250000	7473.303000	-28	-74.5	-15
511.750000	7676.624000	-27.2	-73.7	-14.2

PERFORMED BY:

Doug Noble, B.A.S. E.E.T.

PAGE NO. 14 of 43.

NAME OF TEST: Field Strength of Spurious Radiation

SPECIFICATION: 47 CFR 2.1053(a)


GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 1.2.12

MEASUREMENT PROCEDURE

1.2.12.1 Definition: Radiated spurious emissions are emissions from the equipment when transmitting into a non-radiating load on a frequency or frequencies which are outside an occupied band sufficient to ensure transmission of information of required quality for the class of communications desired.

1.2.12.2 Method of Measurement

- A) Connect the equipment as illustrated
- B) Adjust the spectrum analyzer for the following settings:
 - 1) Resolution Bandwidth ≤ 3 kHz.
 - 2) Video Bandwidth ≥ 10 kHz
 - 3) Sweep Speed ≤ 2000 Hz/second
 - 4) Detector Mode = Positive Peak
- C) Place the transmitter to be tested on the turntable in the standard test site. The transmitter is transmitting into a non-radiating load which is placed on the turntable. The RF cable to this load should be of minimum length.



PAGE NO.


15 of 43.

NAME OF TEST: Field Strength of Spurious Radiation (Cont.)

D) For each spurious measurement the test antenna should be adjusted to the correct length for the frequency involved. This length may be determined from a calibration ruler supplied with the equipment. Measurements shall be made from the lowest radio frequency generated in the equipment to the tenth harmonic of the carrier, except for the region close to the carrier equal to \pm the test bandwidth (see section 1.3.4.4).

E) For each spurious frequency, raise and lower the test antenna from 1 m to 4 m to obtain a maximum reading on the spectrum analyzer with the test antenna at horizontal polarity. Repeat this procedure to obtain the highest possible reading. Record this maximum reading.

F) Repeat step E) for each spurious frequency with the test antenna polarized vertically.



G) Reconnect the equipment as illustrated.

H) Keep the spectrum analyzer adjusted as in step B).

I) Remove the transmitter and replace it with a substitution antenna (the antenna should be half-wavelength for each frequency involved). The center of the substitution antenna should be approximately at the same location as the center of the transmitter. At lower frequencies, where the substitution antenna is very long, this will be impossible to achieve when the antenna is polarized vertically. In such case the lower end of the antenna should be 0.3 m above the ground.

PAGE NO.

16 of 43.

NAME OF TEST: Field Strength of Spurious Radiation (Cont.)

J) Feed the substitution antenna at the transmitter end with a signal generator connected to the antenna by means of a non-radiating cable. With the antennas at both ends horizontally polarized and with the signal generator tuned to a particular spurious frequency, raise and lower the test antenna to obtain a maximum reading at the spectrum analyzer. Adjust the level of the signal generator output until the previously recorded maximum reading for this set of conditions is obtained. This should be done carefully repeating the adjustment of the test antenna and generator output.

K) Repeat step J) with both antennas vertically polarized for each spurious frequency.

L) Calculate power in dBm into a reference ideal half-wave dipole antenna by reducing the readings obtained in steps J) and K) by the power loss in the cable between the generator and the antenna and further corrected for the gain of the substitution antenna used relative to an ideal half-wave dipole antenna.

M) The levels recorded in step L) are absolute levels of radiated spurious emissions in dBm. The radiated spurious emissions in dB can be calculated by the following:

Radiated spurious emissions dB =
 $10\log_{10}(\text{TX power in watts}/0.001) - \text{the levels in step 1}$

NOTE: It is permissible that other antennas provided can be referenced to a dipole.

Test Equipment:

Asset	Description (as applicable)	s/n	Cycle	Last Cal
Per ANSI C63.4-1992/2000 Draft, 10.1.4				
<u>TRANSDUCER</u>				
i00088	EMCO 3109-B 25MHz-300MHz	2336	12 mo.	Sep-01
i00065	EMCO 3301-B Active Monopole	2635	12 mo.	Sep-01
i00089	Aprel 2001 200MHz-1GHz	001500	12 mo.	Sep-01
i00103	EMCO 3115 1GHz-18GHz	9208-3925	12 mo.	Sep-01
<u>AMPLIFIER</u>				
i00028	HP 8449A	2749A00121	12 mo.	Mar-01
SPECTRUM ANALYZER				
i00029	HP 8563E	3213A00104	12 mo.	Aug-01
i00033	HP 85462A	3625A00357	12 mo.	May-01
i00048	HP 8566B	2511AD1467	6 mo.	Nov-01
<u>MICROPHONE, ANTENNA PORT, AND CABLING</u>				
Microphone	Yes/No	<u>Y</u>	Cable Length	<u>1.0</u> Meter
Antenna Port Terminated	Yes/No	<u>Y</u>	Load	Antenna Gain <u>0</u> dbd

PAGE NO. 17 of 43.

NAME OF TEST: Field Strength of Spurious Radiation

g01c0151: 2001-Dec-11 Tue 11:38:00
STATE: 2:High Power

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	ERP, dBm	ERP, dbc
498.250000	996.503800	-17.7	≤ -64.2
498.250000	1494.752300	-40.3	≤ -64.2
498.250000	1993.008600	-41.9	≤ -64.2
498.250000	2491.252300	-42.2	≤ -64.2
498.250000	2989.516000	-54.2	≤ -64.2
498.250000	3487.742667	-50	≤ -64.2
498.250000	3986.005750	-50.1	≤ -64.2
498.250000	4484.257750	-51.2	≤ -64.2
498.250000	4982.535091	-52.3	≤ -64.2

SUPERVISED BY:



Doug Noble, B.A.S. E.E.T.

PAGE NO. 18 of 43.

NAME OF TEST: Emission Masks (Occupied Bandwidth)

SPECIFICATION: 47 CFR 2.1049(c)(1)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.11

TEST EQUIPMENT: As per previous page


MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page, with the Spectrum Analyzer connected.
2. For EUTs supporting audio modulation, the audio signal generator was adjusted to the frequency of maximum response and with output level set for $\pm 2.5/\pm 1.25$ kHz deviation (or 50% modulation). With level constant, the signal level was increased 16 dB.
3. For EUTs supporting digital modulation, the digital modulation mode was operated to its maximum extent.
4. The Occupied Bandwidth was measured with the Spectrum Analyzer controls set as shown on the test results.
5. MEASUREMENT RESULTS: ATTACHED

PAGE NO.

19 of 43.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g01c0157: 2001-Dec-12 Wed 14:42:00
 STATE: 1:Low Power



POWER: LOW
 MODULATION: NONE

PERFORMED BY:




Doug Noble, B.A.S. E.E.T.

PAGE NO.

20 of 43.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g01c0158: 2001-Dec-12 Wed 14:44:00
 STATE: 1:Low Power



POWER:
 MODULATION:

LOW
 VOICE: 2500 Hz SINE WAVE
 MASK: B, VHF/UHF 25kHz,
 w/ LPF


PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO.

21 of 43.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g01c0160: 2001-Dec-12 Wed 15:22:00
 STATE: 1:Low Power



POWER:
 MODULATION:

LOW
 VOICE: 2500 Hz SINE WAVE
 MASK: D, VHF/UHF 12.5kHz BW


PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO.

22 of 43.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g01c0156: 2001-Dec-12 Wed 14:37:00
 STATE: 2:High Power



POWER: HIGH
 MODULATION: NONE


PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO.

23 of 43.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g01c0159: 2001-Dec-12 Wed 15:06:00
 STATE: 2:High Power



POWER:
 MODULATION:

HIGH
 VOICE: 2500 Hz SINE WAVE
 MASK: D, VHF/UHF 12.5kHz BW

PERFORMED BY:




Doug Noble, B.A.S. E.E.T.

PAGE NO.

24 of 43.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g01c0161: 2001-Dec-12 Wed 15:26:00
 STATE: 2:High Power



POWER:
 MODULATION:

HIGH
 VOICE: 2500 Hz SINE WAVE
 MASK: B, VHF/UHF 25kHz,
 w/ LPF

PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO. 25 of 43.

NAME OF TEST: Transient Frequency Behavior

SPECIFICATION: 47 CFR 90.214

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.19

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The EUT was setup as shown on the attached page, following TIA/EIA-603 steps a, b, and c as a *guide*.

2. The transmitter was turned on.

3. Sufficient attenuation was provided so that the transmitter carrier level measured at the output of the combiner was 40 dB below the maximum input level of the test receiver. This level was recorded as step f.

4. The transmitter was turned off.

5. An RF signal generator (1) modulated with a 1 kHz tone at either 25, 12.5, or 6.25 kHz deviation, and set to the same frequency as the assigned transmitter frequency, (2) was adjusted to a level -20 dB below the level recorded for step f, as measured at the output of the combiner. This level was then fixed for the remainder of the test and is recorded at step h.

6. The oscilloscope was setup using TIA/EIA-603 steps j and k as a guide, and to either 10 ms/div (UHF) or 5 ms/div (VHF).


7. The 30 dB attenuator was removed, the transmitter was turned on, and the level of the carrier at the output of the combiner was recorded as step l.

8. The carrier on-time as referenced in TIA/EIA-603 steps m, n, and o was captured and plotted. The carrier off-time as referenced in TIA/EIA-603 steps p, q, r, and s was captured and plotted.


LEVELS MEASURED:

<u>step f</u> , dBm	= -12.3
<u>step h</u> , dBm	= -45.6
<u>step l</u> , dBm	= 4.6

PERFORMED BY:


Doug Noble, B.A.S. E.E.T.

TRANSIENT FREQUENCY BEHAVIOR




Asset Description (as applicable)	s/n
(1) <u>ATTENUATOR</u> (Removed after 1st step) i00112 Philco 30 dB	989
(2) <u>ATTENUATOR</u> i00112 Philco 30 dB i00172 Bird 30 dB i00122 Narda 10 dB i00123 Narda 10 dB i00110 Kay Variable	989 989 7802 7802A 145-387
(3) <u>COMBINER</u> i00154 4 x 25 Ω COMBINER	154
(4) <u>CRYSTAL DETECTOR</u> i00159 HP 8470B	1822A10054
(5) <u>RF SIGNAL GENERATOR</u> i00018 HP 8656A i00031 HP 8656A i00067 HP 8920A	2228A03472 2402A06180 3345U01242
(6) <u>MODULATION ANALYZER</u> i00020 HP 8901A	2105A01087
(7) <u>SCOPE</u> i00030 HP 54502A	2927A00209

PAGE NO.

27 of 43.

NAME OF TEST: Transient Frequency Behavior
 g01c0198: 2001-Dec-19 Wed 11:21:00
 STATE: 2:High Power



Main Timebase Delay/Pos
 -10.0 ms/div 40.0000 ms Center

 Channel 1 Sensitivity Offset Probe
 550 mV/div 0.00000 V 1.000 :1

 Trigger mode :
 on Negative Edge Of
 Trigger
 - Chan2 = -1.500 mV (noise
 Holdoff ~ 40.000

POWER: HIGH
 MODULATION: Ref Gen=25 kHz Deviation
 DESCRIPTION: CARRIER ON TIME


PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO.

28 of 43.

NAME OF TEST: Transient Frequency Behavior
 g01c0199: 2001-Dec-19 Wed 11:22:00
 STATE: 2:High Power



```

Main      Timebase      Delay/Pos
- ....      -10.0 ms/div      -30.0000 ms      Center
-          Sensitivity      Offset      Probe
Channel 1      550 mV/div      0.00000 V      1.000 :1
-          (MHz)
-          Trigger mode :
-          On Positive Edge Of
-          Trigger
-          Chan2 = -175.000 mV (noise
-          Holdoff=40.000

```

POWER:	HIGH
MODULATION:	Ref Gen=25 kHz Deviation
DESCRIPTION:	CARRIER OFF TIME

PERFORMED BY:




Doug Noble, B.A.S. E.E.T.

PAGE NO.

29 of 43.

NAME OF TEST: Transient Frequency Behavior
g01c0200: 2001-Dec-19 Wed 11:25:00
STATE: 2:High Power



```

Main           Timebase      Delay/Pos
              -10.0 ms/div   40.0000 ms  Center
                                      Sensitivity  Offset  Probe
Channel 1     275  mV/div    0.00000  V  1.000  :1
                                      Trigger mode :
On Negative Edge Of
Trigger
- Chan2 = -1.500  mV (noise
Holdoff = 40.000

```

POWER:
MODULATION:
DESCRIPTION:

HIGH
Ref Gen=12.5 kHz Deviation
CARRIER ON TIME


PERFORMED BY:

Doug Noble, B.A.S. E.E.T.

PAGE NO.

30 of 43.

NAME OF TEST: Transient Frequency Behavior
 g01c0201: 2001-Dec-19 Wed 11:25:00
 STATE: 2:High Power



Main Timebase -10.0 ms/div Delay/Pos -30.0000 ms Center
 -
 Channel 1 Sensitivity 275 mV/div Offset 0.00000 V Probe 1.000 :1
 -
 Trigger mode :
 On Positive Edge Of
 Trigger
 - Chan2 = -175.000 mV (noise
 Holdoff - 40.000

POWER:
 MODULATION:
 DESCRIPTION:

HIGH
 Ref Gen=12.5 kHz Deviation
 CARRIER OFF TIME

PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO. 31 of 43.

NAME OF TEST: Audio Low Pass Filter (Voice Input)

SPECIFICATION: 47 CFR 2.1047(a)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.15

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE


1. The EUT and test equipment were set up such that the audio input was connected at the input to the modulation limiter, and the modulated stage.
2. The audio output was connected at the output to the modulated stage.
3. MEASUREMENT RESULTS: ATTACHED

PAGE NO.

32 of 43.

TRANSMITTER TEST SET-UP

TEST A. MODULATION CAPABILITY/DISTORTION
 TEST B. AUDIO FREQUENCY RESPONSE
 TEST C. HUM AND NOISE LEVEL
 TEST D. RESPONSE OF LOW PASS FILTER
 TEST E. MODULATION LIMITING




Asset (as applicable)	Description	s/n
(1) <u>Audio Oscillator</u>		
i00010	HP 204D	1105A04683
i00017	HP 8903A	2216A01753
i00118	HP 33120A	US36002064
(2) <u>COAXIAL ATTENUATOR</u>		
i00122	NARDA 766-10	7802
i00123	NARDA 766-10	7802A
i00113	SIERRA 661A-3D	1059
i00069	BIRD 8329 (30 dB)	10066
(3) <u>MODULATION ANALYZER</u>		
i00020	HP 8901A	2105A01087
(4) <u>AUDIO ANALYZER</u>		
i00017	HP 8903A	2216A01753

PAGE NO.

33 of 43.

NAME OF TEST: Audio Low Pass Filter (Voice Input)
g01c0128: 2001-Dec-12 Wed 11:49:00
STATE: 0:General



PERFORMED BY:



Doug Noble, B.A.S. E.E.T.

PAGE NO. 34 of 43.

NAME OF TEST: Audio Frequency Response

SPECIFICATION: 47 CFR 2.1047(a)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.6

TEST EQUIPMENT: As per previous page


MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page.
2. The audio signal generator was connected to the audio input circuit/microphone of the EUT.
3. The audio signal input was adjusted to obtain 20% modulation at 1 kHz, and this point was taken as the 0 dB reference level.
4. With input levels held constant and below limiting at all frequencies, the audio signal generator was varied from 100 Hz to 50 kHz.
5. The response in dB relative to 1 kHz was then measured, using the HP 8901A Modulation Analyzer.
6. MEASUREMENT RESULTS: ATTACHED

PAGE NO.

35 of 43.

NAME OF TEST: Audio Frequency Response
 g01c0123: 2001-Dec-12 Wed 11:31:00
 STATE: 0:General



Frequency of Maximum Audio Response, Hz = 2820

Additional points:

FREQUENCY, Hz	LEVEL, dB
300	-13.68
20000	-30.22
30000	-33.34
50000	-33.90

PERFORMED BY:

Doug Noble, B.A.S. E.E.T.

PAGE NO. 36 of 43.

NAME OF TEST: Modulation Limiting

SPECIFICATION: 47 CFR 2.1047(b)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.3

TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE

1. The signal generator was connected to the input of the EUT as for "Frequency Response of the Modulating Circuit."
2. The modulation response was measured for each of three frequencies (one of which was the frequency of maximum response), and the input voltage was varied and was observed on an HP 8901A Modulation Analyzer.
3. The input level was varied from 30% modulation (± 1.5 kHz deviation) to at least 20 dB higher than the saturation point.
4. Measurements were performed for both negative and positive modulation and the respective results were recorded.


5. MEASUREMENT RESULTS: ATTACHED

PAGE NO.


37 of 43.

NAME OF TEST: Modulation Limiting
 g01c0129: 2001-Dec-12 Wed 11:53:00
 STATE: 0:General

Positive
Peaks:



Negative
Peaks:



PERFORMED BY:



 Doug Noble, B.A.S. E.E.T.

PAGE NO.


38 of 43.

NAME OF TEST: Modulation Limiting
 g01c0130: 2001-Dec-12 Wed 12:03:00
 STATE: 0:General

Positive
Peaks:



Negative
Peaks:



PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO. 39 of 43.

NAME OF TEST: Frequency Stability (Temperature Variation)

SPECIFICATION: 47 CFR 2.1055(a)(1)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.2

TEST CONDITIONS: As Indicated

TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE


1. The EUT and test equipment were set up as shown on the following page.
2. With all power removed, the temperature was decreased to -30°C and permitted to stabilize for three hours. Power was applied and the maximum change in frequency was noted within one minute.
3. With power OFF, the temperature was raised in 10°C steps. The sample was permitted to stabilize at each step for at least one-half hour. Power was applied and the maximum frequency change was noted within one minute.
4. The temperature tests were performed for the worst case.
5. MEASUREMENT RESULTS: ATTACHED

PAGE NO.

40 of 43.

TRANSMITTER TEST SET-UP

TEST A. OPERATIONAL STABILITY
 TEST B. CARRIER FREQUENCY STABILITY
 TEST C. OPERATIONAL PERFORMANCE STABILITY
 TEST D. HUMIDITY
 TEST E. VIBRATION
 TEST F. ENVIRONMENTAL TEMPERATURE
 TEST G. FREQUENCY STABILITY: TEMPERATURE VARIATION
 TEST H. FREQUENCY STABILITY: VOLTAGE VARIATION




Transmitter Test Set Up

Asset Description (as applicable)		s/n
(1) TEMPERATURE, HUMIDITY, VIBRATION		
i00027 Tenney Temp. Chamber	9083-765-234	
i00 Weber Humidity Chamber		
i00 L.A.B. RVH 18-100		
(2) COAXIAL ATTENUATOR		
i00122 NARDA 766-10	7802	
i00123 NARDA 766-10	7802A	
i00113 SIERRA 661A-3D	1059	
i00069 BIRD 8329 (30 dB)	10066	
(3) R.F. POWER		
i00014 HP 435A POWER METER	1733A05839	
i00039 HP 436A POWER METER	2709A26776	
i00020 HP 8901A POWER MODE	2105A01087	
(4) FREQUENCY COUNTER		
i00042 HP 5383A	1628A00959	
i00019 HP 5334B	2704A00347	
i00020 HP 8901A	2105A01087	

PAGE NO.

41 of 43.

NAME OF TEST: Frequency Stability (Temperature Variation)
g01c0118: 2001-Dec-11 Tue 15:32:55
STATE: 0:General



PERFORMED BY:



Doug Noble, B.A.S. E.E.T.

PAGE NO. 42 of 43.

NAME OF TEST: Frequency Stability (Voltage Variation)

SPECIFICATION: 47 CFR 2.1055(d)(1)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.2

TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE

1. The EUT was placed in a temperature chamber at $25\pm5^{\circ}\text{C}$ and connected as for "Frequency Stability - Temperature Variation" test.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

RESULTS: Frequency Stability (Voltage Variation)

g01c0152: 2001-Dec-12 Wed 13:02:18

STATE: 0:General

LIMIT, ppm	= 2.5
LIMIT, Hz	= 1246
BATTERY END POINT (Voltage)	= 11.2

% of STV	Voltage	Frequency, MHz	Change, Hz	Change, ppm
85	11.56	498.250010	10	0.02
100	13.6	498.250000	0	0.00
115	15.64	498.250020	20	0.04
82	11.2	498.250010	10	0.02

PERFORMED BY:


Doug Noble, B.A.S. E.E.T.

PAGE NO. 43 of 43.

NAME OF TEST: Necessary Bandwidth and Emission Bandwidth

SPECIFICATION: 47 CFR 2.202(g)

MODULATION = 16K0F3E

NECESSARY BANDWIDTH CALCULATION:

MAXIMUM MODULATION (M), kHz	= 3
MAXIMUM DEVIATION (D), kHz	= 5
CONSTANT FACTOR (K)	= 1
NECESSARY BANDWIDTH (B _N), kHz	= (2xM)+(2xDxK)
	= 16.0

MODULATION = 11K0F3E

NECESSARY BANDWIDTH CALCULATION:

MAXIMUM MODULATION (M), kHz	= 3
MAXIMUM DEVIATION (D), kHz	= 2.5
CONSTANT FACTOR (K)	= 1
NECESSARY BANDWIDTH (B _N), kHz	= (2xM)+(2xDxK)
	= 11.0

PERFORMED BY:



Doug Noble, B.A.S. E.E.T.

END OF TEST REPORT

TESTIMONIAL
AND
STATEMENT OF CERTIFICATION

THIS IS TO CERTIFY THAT:

1. THAT the application was prepared either by, or under the direct supervision of, the undersigned.
2. THAT the technical data supplied with the application was taken under my direction and supervision.
3. THAT the data was obtained on representative units, randomly selected.
4. THAT, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.

CERTIFYING ENGINEER:



Morton Flom, P. Eng.