

Test Report

TEST PROCEDURES AND TEST SITE DESCRIPTION

FCC ID: AMWUC002R
MODEL: EXI5160(XX)
EQUIPMENT: 5.8GHZ ISM BAND ANALOG TRANSMITTER

MEASUREMENT ITEMS	Section No.
5-1 Field Strength of Radiated Emissions	15.249(a)(b) 15.205 / 15.209
5-2 Power Line Conducted Emissions	15.207
SUPPLEMENT DATA - BAND EDGE EMISSIONS	

5-1 Field Strength of Radiated Emissions

15.249(a)(b)
15.205 / 15.209

The measurements were performed in accordance with the ANSI C63.4-1992. Field Strength measurements of radiated spurious emissions were made at the open test site of a 3 meter range maintained by Uniden Corporation in Japan. Complete description and measurement data of this test site have been placed on file with the Commission.

The radio frequency spectrum was scanned in the range of 30 MHz to the 10th harmonic in accordance with the section 15.33(a) of the FCC Rules. The frequency below 1 GHz, the measurement was carried out by using CISPR quasi-peak detector, AGILENT E7400A the Spectrum Analyzer in accordance with the sections 15.33(a) and 15.35(a). The frequency above 1 GHz, using the AGILENT E7400A Spectrum Analyzer in accordance with the section 15.35(b) carried out the measurement.

A bilog antenna CBL6112A was used to cover the range from 30 MHz to 1000 MHz. Narrowband tuned dipole antennas were used over the entire 30 to 1000 MHz range for precision measurements of field strength. Above 1000 MHz, a horn antenna EMCO 3115 was used.

For each spurious or harmonic frequency, the antenna was raised and lowered to obtain a maximum reading on the Spectrum Analyzer with antenna horizontally polarized. Then the turntable, on which the equipment under test was placed, was rotated a minimum of 360 degrees to further increase the reading on the Spectrum Analyzer.

For testing small and/or handheld product, the measurement was performed in 3 orthogonal planes(X, Y, Z). This procedure was repeated with the antenna vertically polarized. The equipment under test was placed in its normal operating position on a turntable approximately 1 meter in height.

In order to convert the measured emission levels into field strength in dBuV/m, the actual field strength (Ef) is determined by algebraically adding the measured emission level (Em) and the antenna correction factor (ACF) including the cable loss at the appropriate frequency. $E_f [dBuV/m] = E_m [dBuV/m] + ACF [dB]$

FCC Limits:

- a) Fundamental emission: 94 dBuV/m (50,000 uV/m)
- b) Spurious emissions:

30 - 88 MHz	40 dBuV/m	(100 uV/m)
88 - 216 MHz	43.5 dBuV/m	(150 uV/m)
216 - 960 MHz	46 dBuV/m	(200 uV/m)
Above 960 MHz	54 dBuV/m	(500 uV/m)

Test Results: Refer to the attached test reports. All emissions

not reported were more than 20 dB below the limits.

NOTE:

For measurement of the handset, all of the testing were made with the internal battery that is fully charged.

For measurement of base unit, all of the testing were made with the AC Adapter which connected to a standard voltage source.

5-2 Power Line Conducted Emissions

15.207

Test Procedure:

The measurements were performed in accordance with the ANSI C63.4-1992. During the measurements, a standard voltage source is fed into the unit under test through a power line impedance stabilization network.

FCC Limit:

The radio frequency voltage that is conducted back into the AC power line on any frequencies within the band from 150kHz to 30MHz shall not exceed the following limitation.

REQUIREMENTS:

FREQUENCY(MHz)	LEVEL (dBuV)	
0.150-0.50	66 to 56 QP	56 to 46 Ave
0.50-5.0	56 QP	46 Ave
5.0-30.0	60 QP	50 Ave

Test Results: Refer to the attached test reports. All emissions not reported were more than 20 dB below the limits.

NOTE:

Regarding the Handset, this FCC requirement is not applicable to it since the Handset is intended to use the battery only.

SUPPLEMENT DATA - BAND EDGE EMISSION

Attached data show the handset's transmission on lowest channel and base unit's transmission on highest channel.

At the outside of emission bands, those emissions are well reduced against the operational channel frequency of the units.

TEST CONDITIONS:

Modulation : 1000 Hz

5-1 Field Strength of Radiated Emissions (Test Result)

a) Handset: Fundamental Emissions

Emission (MHz)	FSM Reading (dBuV)	Amplifier Gain (dB)	Measured Level		ACF (dB)	Field Strength (dBuV/m)	FCC Limit (dBuV/m)	Margin (dB)
			(dBuV)	(V/H)				
5739.320225	55.6	0.0	55.6	H	35.5	91.1	94.0	2.9
5746.130091	55.6	0.0	55.6	H	35.5	91.1	94.0	2.9

b) Handset: Spurious Emissions

Transmitting Frequency: 5743.772830MHz								
Emission (MHz)	FSM Reading (dBuV)	Amplifier Gain (dB)	Measured Level		ACF (dB)	Field Strength (dBuV/m)	FCC Limit (dBuV/m)	Margin (dB)
			(dBuV)	(V/H)				
1914.5909	47.9	29.0	18.9	H	24.0	42.9	54.0	11.1
3829.1818	40.9	26.5	14.4	V	31.5	45.9	54.0	8.1
5699.7728	37.7	26.0	11.7	H	34.0	45.7	54.0	8.3
5721.7728	38.9	26.0	12.9	H	34.0	46.9	54.0	7.1
5765.7728	37.6	26.0	11.6	H	34.0	45.6	54.0	8.4
7658.3636	38.8	25.6	13.2	H	37.0	50.2	54.0	3.8
9572.9545	32.9	25.0	7.9	V	39.0	46.9	54.0	7.1
11487.5454	33.9	25.0	8.9	H	41.0	49.9	54.0	4.1

NOTE: All emissions not reported were more than 20 dB below the FCC limit.

5-2 Power Line Conducted Emissions

15.207

Test Result

<u>Transmitting frequency</u>	<u>Emissions Frequency</u>	<u>Measured Level</u>
-------------------------------	----------------------------	-----------------------

NOT APPLICABLE

Handset:

The FCC requirement do not apply to the handset
since the handset is designed to operate with internal battery only.


HANDSET 1ch Band Edge Emissions

EXI5160 TX 1ch
MAX Dev.
1kHz ± 100kHz dev.

ATTEN 10dB
RL -4.8dBm

10dB/

MKR -4.84dBm
5.7393GHz



CENTER 5.7250GHz

SPAN 100.0MHz

RBW 1.0MHz *VBW 100kHz


SWP 50.0ms

HANDSET 20ch Band Edge Emissions

EXI5160 TX 20ch

ATTEN 10dB
RL -4.8dBm

MKR -5.01dBm MAX Dev.
5.7467GHz 1kHz±100kHzdev.



CENTER 5.8500GHz

SPAN 500.0MHz

RBW 1.0MHz *VBW 100kHz

SWP 50.0ms