



Ref: FCC ID.: AMWUT401

05-Jun-2014

This Device is a Hand Held CB transceiver operating in the 27MHz CB Radio Band.
 As such SAR testing is not required because it operates below 100MHz.
 However SAR evaluation is still required. The SAR evaluation report has been included in this submission.

This document provides some Uniden accessories that can be used with this device.
 Similar accessories of typical design will also work with this device.

Type	Model	Brand	Feature/Spec	Image
Speaker	BC7	Uniden	Maximum 7 Watts Input Power 3.5 mm Right Angle Plug 2.2" Speaker Frequency Response 300 Hz - 5 kHz Works with CBs, Scanners, and other communications receivers	
Speaker	BC15	Uniden	Maximum 15 Watts Input Power Noise Blanker for Clear Audio 3.5 mm Right Angle Plug 3" Speaker Frequency Response 500 Hz - 5 kHz	
Speaker	BC20	Uniden	Maximum 20 Watts Input Power 3.5 mm Right Angle Plug Noise Blanker for Clear Audio 4" Speaker Frequency Response 300 Hz - 5 kHz	
Speaker	BC23A	Uniden	Maximum 15 Watts Input Power 3.5 mm Right Angle Plug 8 Watt Amplifier Noise Blanker for Clear Audio 3" Speaker Frequency Response 500 Hz - 5 kHz	
Speaker - Mic	SPM-G	Uniden	Speaker Plug: 3.5mm Mic with PTT button Mic Plug: 2.5mm	
Speaker - Mic	MS800	Diamond	Speaker: 500mW Speaker Plug: 3.5mm Mic with PTT button Mic Plug: 2.5mm	