## SHEN ZHEN ZHIKE COMMUNICATION CO., LTD

**GSM Mobile Phone** 

Model: i3 Pro Serial Model: i3

Feb 12th 2012

Report No.: 12070016-SAR (FCC)

(This report supersedes NONE)



Modifications made to the product: None

This Test Report is Issued Under the Authority of:

Chris You

Chris You

Test Engineer

Technical Manager

This test report may be reproduced in full only.
All Test Data Presented in this report is only applicable to presented Test sample.

SIEMIC, INC.
Accessing global markets

## **Laboratory Introduction**

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to <u>testing</u> and <u>certification</u>, SIEMIC provides initial design reviews and <u>compliance</u> <u>management</u> through out a project. Our extensive experience with <u>China</u>, <u>Asia Pacific</u>, <u>North America</u>, <u>European</u>, <u>and international</u> compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the <u>global markets</u>.

**Accreditations for Conformity Assessment** 

Accreditations for comorning Assessment					
Country/Region	Accreditation Body	Scope			
USA	FCC, A2LA	EMC , RF/Wireless , Telecom			
Canada	IC, A2LA, NIST	EMC, RF/Wireless , Telecom			
Taiwan	BSMI , NCC , NIST	EMC, RF, Telecom, Safety			
Hong Kong	OFTA , NIST	RF/Wireless ,Telecom			
Australia	NATA, NIST	EMC, RF, Telecom, Safety			
Korea	KCC/RRA, NIST	EMI, EMS, RF , Telecom, Safety			
Japan	VCCI, JATE, TELEC, RFT	EMI, RF/Wireless, Telecom			
Mexico	NOM, COFETEL, Caniety	Safety, EMC, RF/Wireless, Telecom			
Europe	A2LA, NIST	EMC, RF, Telecom, Safety			

### **Accreditations for Product Certifications**

Country	Accreditation Body	Scope
USA	FCC TCB, NIST	EMC , RF , Telecom
Canada	IC FCB , NIST	EMC , RF , Telecom
Singapore	iDA, NIST	EMC , RF , Telecom
EU	NB, NIST	EMC,RF,Safety,Telecom

This page has been left blank intentionally.

Serial# 12070016-SAR Issue Date Feb 12th 2012 Page 4 of 98 www.siemic.com

### CONTENTS

1	EXECUTIVE SUMMARY & EUT INFORMATION	6
2	TECHNICAL DETAILS	7
3	INTRODUCTION	
4	SAR MEASUREMENT SETUP	
5	ANSI/IEEE C95.1 – 1999 RF EXPOSURE LIMIT	19
6	SYSTEM AND LIQUID VALIDATION	20
7	TYPE A MEASUREMENT UNCERTAINTY	28
8	OUTPUT POWER VERIFICATION	30
9	SAR TEST RESULTS	32
10	SAR MEASUREMENT REFERENCES	35
ANN	IEX A. TEST INSTRUMENT & METHOD	52
ANN	IEX B CALIBRATION REPORTS	54
ANN	IEX C SAR SYSTEM PHOTOGRAPHS	93
ANN	IEX D SETUP PHOTOGRAPHS	94
ANN	IEX E EUT PHOTO	97

This page has been left blank intentionally.

## 1 Executive Summary & EUT information

The purpose of this test programmed was to demonstrate compliance of the SHEN ZHEN ZHIKE COMMUNICATION CO., LTD. Model: i3 Pro against the current Stipulated Standards. The GSM Mobile Phone have demonstrated compliance with the C95.1, IEEE 1528, OET Bulletin 65 Supplement C, IEC62209-2, RSS-102 Issue 4 and Safety Code 6. The test has demonstrated that this unit complies with stipulated standards.

### **EUT Information**

**EUT** : GSM Mobile Phone

Description

Model No : i3 Pro, i3

Input Power : 3.6V-4.2VDC

**Maximum** GSM850(Class 4): 1.871W (32.72dBm)

Output Power GPRS850(Multi-slot Class 10): 1.675W (32.24dBm)

to Antenna GSM1900 (Class 1) : 0.708W (28.50dBm)

GPRS1900 (Multi-slot Class 10): 0.697W (28.43dBm)

1.170W/Kg 1g Head Tissue (Cellular Band)

Max. SAR
Level(s)

0.644W/Kg 1g Body Tissue (Cellular Band)
0.550W/Kg 1g Head Tissue (PCS Band)
Measured
0.511W/Kg 1g Body Tissue (PCS Band)

Classification

Per Stipulated : Mobile Device , Class B

**Test Standard** 

Co-located TX : WWAN can transmit simultaneously with Bluetooth

**Antenna** 

**Separation**: 6.1cm - WWAN antenna-to-Bluetooth antenna

distances

Antenna Type(s) : Internal Antenna

Serial# 12070016-SAR Issue Date Feb 12th 2012 Page 7 of 98 www.siemic.com

## **2 TECHNICAL DETAILS**

	2 TECHNICAL DETAILS
Purpose	Compliance testing of GSM Mobile Phone model i3 Pro with stipulated standard
Applicant / Client	SHEN ZHEN ZHIKE COMMUNICATION CO.,LTD 1805, Tower A , Phase I, Tianan High-Tech Plaza, Futian District, Shenzhen China
Manufacturer	Shenzhen Sky Tango Electronic Technology Co., Ltd B,7/F, Factory Building A, Shenfubao Science and Technology Industrial Park,#3, Huang Huai Road, Futian Trade Zone, Shenzhen P.R
Laboratory performing the tests	SIEMIC Laboratories Suite 311, Building 1, Section 30, No.2 Kefa Road, Science and Technology Park Nan Shan District, Shenzhen 518057, Guangdong, P.R.C Tel: +(86) 0755-26014629 VIP Line:950-4038-0435
Test report reference number	12070016-SAR
Date EUT received	Feb 9 <sup>th</sup> 2012
Standard applied	See Page 9
Dates of test (from – to)	Feb 10th 2012
No of Units:	1
Equipment Category:	PCE
Trade Name:	o iPro
Model Name:	i3 Pro, i3
RF Operating Frequency (ies)	GSM850 : 824.2 ~ 848.8 MHz(TX) / 869.2 ~ 893.8 MHz(RX) GSM1900 : 1850.2 ~ 1909.8 MHz(TX) / 1930.2 ~ 1989.8 MHz(RX) BT:2402~ 2480MHz(TX/RX)
Modulation:	GSM / GPRS : GMSK Bluetooth: GFSK
FCC ID	AODZKTXIPROI3
IC ID:	N/A

## 3 INTRODUCTION

### Introduction

This measurement report shows compliance of the EUT with FCC OET Bulletin 65 Supplement C (Edition 01-01), IEC62209-2 & RSS 102 Issue 4.0.

The test procedures, as described in ANSI C95.1 – 1999 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [2], and ANSI C95.3 – 2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields [3], were employed.

### **SAR Definition**

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (p).

$$SAR = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dV} \right)$$

SAR is expressed in units of watts per kilogram (W/kg). SAR can be related to the electric field at a point by

$$SAR = \frac{\sigma \mid E \mid^2}{\rho}$$

where:

 $\sigma$  = conductivity of the tissue (S/m)

 $\rho$  = mass density of the tissue (kg/m3)

E = rms electric field strength (V/m)


## 4 SAR Measurement Setup

### **Dosimetric Assessment System**

These measurements were performed with the automated near-field scanning system OPENSAR from SATIMO. The system is based on a high precision robot (working range: 850 mm), which positions the probes with a positional repeatability of better than  $\pm$  0.02 mm. Special E- and H-field probes have been developed for measurements close to material discontinuity, the sensors of which are directly loaded with a Schottky diode and connected via highly resistive lines to the data acquisition unit.

The SAR measurements were conducted with dosimetric probe (manufactured by SATIMO), designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe has been calibrated according to the procedure described in SAR standard with accuracy of better than  $\pm 10\%$ . The spherical isotropy was evaluated with the procedure described in SAR starndard and found to be better than  $\pm 0.25$  dB. The phantom used was the SAM Phantom as described in FCC supplement C, IEEE P1528 and CENELEC EN62209-1.

### **Measurement System Diagram**



## The OPENSAR system for performing compliance tests consist of the following items:

- 1. A standard high precision 6-axis robot (KUKA) with controller and software.
- KUKA Control Panel (KCP).
- A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- 4. The functions of the PC plug-in card are to perform the time critical task such as signal filtering, surveillance of the robot operation fast movement interrupts.

- 5. A computer operating Windows XP.
- 6. OPENSAR software.
- 7. Remote control with teaches pendant and additional circuitry for robot safety such as warning lamps, etc.
- 8. The SAM phantom enabling testing left-hand right-hand and body usage.
- 9. The Position device for handheld EUT.
- 10. Tissue simulating liquid mixed according to the given recipes (see Application Note).
- 11. System validation dipoles to validate the proper functioning of the system.

Serial# 12070016-SAR Issue Date Feb 12th 2012 Page 11 of 98 www.siemic.com

### EP100 Probe





Construction Symmetrical design with triangular Core. Built-in shielding against static charges Calibration in air from 100 MHz to 2.5 GHz. In brain and muscle simulating tissue at frequencies from 800 to 6000 MHz (accuracy of 8%).

Frequency 100 MHz to 6 GHz;

Linearity; 0.25 dB (100 MHz to 6 GHz),

Directivity: 0.25 dB in brain tissue (rotation around probe axis) 0.5 dB in brain tissue (rotation normal probe axis)

Dynamic: 0.001W/kg to > 100W/kg;

Range Linearity: 0.25 dB

Surface: 0.2 mm repeatability in air and liquids

Dimensions Overall length: 330 mm

Tip length: 16 mm

Body diameter: 8 mm

Tip diameter: 2.6 mm

Distance from probe tip to dipole centers: <1.5 mm

Application General dosimetric up to 6 GHz

Compliance tests of mobile phones

Fast automatic scanning in arbitrary phantoms

The SAR measurements were conducted with the dosimetric probe designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe is constructed using the thick film technique, with printed resistive lines on ceramic substrates.

It is connected to the KRC box on the robot arm and provides an automatic detection of the phantom surface. The 3D file of the phantom is include in OpenSAR software. The Video Positioning System allow the system to take the automatic reference and to move the probe safely and accurately on the phantom.

### **E-Field Probe Calibration Process**

Each probe is calibrated according to a dosimetric assessment procedure described in SAR standard with accuracy better than +/- 10%. The spherical isotropy was evaluated with the procedure described in SAR standard and found to be better than +/-0.25dB. The sensitivity parameters (NormX, NormY, NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe are tested.

The free space E-field from probe outputs is determined in a test chamber. This is performed in a TEM cell for frequencies bellow 0.8 GHz, and in a waveguide above 0.8 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. E-field correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue.

### **SAM Phantom**

The SAM Phantom SAM29 is constructed of a fiberglass shell ntegrated in a wooden table. The shape of the shell is in compliance with the specification set in IEEE P1528 and CENELEC EN62209-1, IEC62209-2.

The phantom enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region.

A cover prevents the evaporation of the liquid.

Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot.

Shell Thickness: 2 0.2 mm Filling Volume: Approx. 25 liters

Dimensions (H x L x W): 810 x 1000 x 500 mm

Liquid is filled to at least 15mm from the bottom of Phantom.



### **Device Holder**

In combination with the Generic Twin Phantom V3.0, the Mounting Device enables the rotation of the mounted transmitter in spherical coordinates whereby the rotation points is the ear opening. The devices can be easily, accurately, and repeatedly positioned according to the FCC and CENELEC specifications. The device holder can be locked at different phantom locations (left head, right head, flat phantom).



**Note:** A simulating human hand is not used due to the complex anatomical and geometrical structure of the hand that may produced infinite number of configurations [10]. To produce the worst-case condition (the hand absorbs antenna output power), the hand is omitted during the tests.

### **Data Evaluation**

The OPENSAR software automatically executes the following procedure to calculate the field units from the microvolt readings at the probe connector. The parameters used in the valuation are stored in the configuration modules of the software:

Probe Parameters	- Sensitivity	Norm <sub>i</sub>
	- Conversion factor	ConvFi
	- Diode compression point Dcpi	
Device Parameter	- Frequency	f
	- Crest factor	Cf
Media Parametrs	- Conductivity	σ
	- Density	ρ

These parameters must be set correctly in the software. They can either be found in the component documents or be imported into the software from the configuration files issued for the OPENSAR components.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

Where  $V_i$  = Compensated signal of channel i (i = x, y, z)

 $U_i$  = Input signal of channel i (i = x, y, z)

cf = Crest factor of exciting field(DASY parameter)

dcp<sub>i</sub> = Diode compression point (DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

E-field probes:  $E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$ 

H-field probes:  $H_i = \sqrt{Vi} \cdot \frac{a_{00} + a_{01}f + a_{02}f^2}{f}$ 

Where  $V_i$  = Compensated signal of channel i (i = x, y, z)

 $Norm_i$  = Sensor sensitivity of channel i (i = x, y, z)

μV/(V/m)2 for E0field Probes

ConvF= Sensitivity enhancement in solution

a<sub>ij</sub> = Sensor sensitivity factors for H-field probes

f = Carrier frequency (GHz)

E<sub>i</sub> = Electric field strength of channel i in V/m H<sub>i</sub> = Magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_{x}^{2} + E_{x}^{2} + E_{x}^{2}}$$

The primary field data are used to calculate the derived field units.

 $SAR - E_{100}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$ 

where SAR = local specific absorption rate in mW/g

Etot = total field strength in V/m

 $\sigma$  = conductivity in [mho/m] or [siemens/m]

ρ = equivalent tissue density in g/cm3

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid.

The power flow density is calculated assuming the excitation field as a free space field.

 $P_{\text{per}} = \frac{E_{\text{var}}^2}{3770}$  or  $P_{\text{per}} = H_{\text{var}}^2 \cdot 37.7$ 

where Ppwe = Equivalent power density of a plane wave in mW/cm2

 $E_{tot}$  = total electric field strength in V/m  $H_{tot}$  = total magnetic field strength in A/m

### SAR Evaluation – Peak Spatial - Average

The procedure for assessing the peak spatial-average SAR value consists of the following steps

#### · Power Reference Measurement

The reference and drift jobs are useful jobs for monitoring the power drift of the device under test in the batch process. Both jobs measure the field at a specified reference position, at a selectable distance from the phantom surface. The reference position can be either the selected section's grid reference point or a user point in this section. The reference job projects the selected point onto the phantom surface, orients the probe perpendicularly to the surface, and approaches the surface using the selected detection method.

### · Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a finer measurement around the hot spot. The sophisticated interpolation routines implemented in OPENSAR software can find the maximum locations even in relatively coarse grids. The scan area is defined by an editable grid. This grid is anchored at the grid reference point of the selected section in the phantom. When the area scan's property sheet is brought-up, grid was at to 15 mm by 15 mm and can be edited by a user.

#### Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The default zoom scan measures 5 x 5 x 7 points within a cube whose base faces are centered around the maximum found in a preceding area scan job within the same procedure. If the preceding Area Scan job indicates more then one maximum, the number of Zoom Scans has to be enlarged accordingly (The default number inserted is 1).

### · Power Drift measurement

The drift job measures the field at the same location as the most recent reference job within the same procedure, and with the same settings. The drift measurement gives the field difference in dB from the reading conducted within the last reference measurement. Several drift measurements are possible for one reference measurement. This allows a user to monitor the power drift of the device under test within a batch process. In the properties of the Drift job, the user can specify a limit for the drift and have OPENSAR software stop the measurements if this limit is exceeded.

### SAR Evaluation – Peak SAR

The procedure for spatial peak SAR evaluation has been implemented according to the IEEE1529 standard. It can be conducted for 1 g and 10 g. The OPENSAR system allows evaluations that combine measured data and robot positions, such as:

- maximum search
- extrapolation
- · boundary correction
- peak search for averaged SAR

During a maximum search, global and local maximum searches are automatically performed in 2-D after each Area Scan measurement with at least 6 measurement points. It is based on the evaluation of the local SAR gradient calculated by the Quadratic Shepard's method. The algorithm will find the global maximum and all local maxima within -2 dB of the global maxima for all SAR distributions.

### Extrapolation

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. Several measurements at different distances are necessary for the extrapolation.

They are used in the Cube Scan to obtain SAR values between the lowest measurement points and the inner phantom surface. The routine uses the fourth order least square polynomial method for extrapolation. For a grid using 5x5x7 measurement points with 5mm resolution amounting to 343 measurement points, the uncertainty of the extrapolation routines is less than 1% for 1 g and 10 g cubes.

### **Definition of Reference Points**

### Ear Reference Point

Figure 6.2 shows the front, back and side views of the SAM Phantom. The point "M" is the reference point for the center of the mouth, "LE" is the left ear reference point (ERP), and "RE" is the right ERP. The ERPs are 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 6.1. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front) is perpendicular to the reference plane and passing through the RE (or LE) is called the Reference Pivoting Line (see Figure 6.1). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




Figure 6.1 Close-up side view of ERP's



Figure 6.2 Front, back and side view of SAM

### **Device Reference Points**

Two imaginary lines on the device need to be established: the vertical centerline and the horizontal line. The test device is placed in a normal operating position with the "test device reference point" located along the "vertical centerline" on the front of the device aligned to the "ear reference point" (See Fig. 6.3). The "test device reference point" is than located at the same level as the center of the ear reference point. The test device is positioned so that the "vertical centerline" is bisecting the front surface of the device at it's top and bottom edges, positioning the "ear reference point" on the outer surface of both the left and right head phantoms on the ear reference point [5].




Figure 6.3 Handset Vertical Center & Horizontal Line Reference Points

### Test Configuration - Positioning for Cheek / Touch

1. Position the device close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure below), such that the plane defined by the vertical center line and the horizontal line of the device is approximately parallel to the sagittal plane of the phantom



Figure 7.1 Front, Side and Top View of Cheek/Touch Position

- 2. Translate the device towards the phantom along the line passing through RE and LE until the device touches the ear.
- 3. While maintaining the device in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to MB-NF including the line MB (called the reference plane).
- 4. Rotate the device around the vertical centerline until the device (horizontal line) is symmetrical with respect to the line NF.
- 5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE and maintaining the device contact with the ear, rotate the device about the line NF until any point on the device is in contact with a phantom point below the ear (cheek). See Figure below.




Figure 7.2 Side view w/ relevant markings

### Test Configuration - Positioning for Ear / 15° Tilt

With the test device aligned in the Cheek/Touch Position":

- 1. While maintaining the orientation of the device, retracted the device parallel to the reference plane far enough to enable a rotation of the device by 15 degrees.
- 2. Rotate the device around the horizontal line by 15 degrees.
- 3. While maintaining the orientation of the device, move the device parallel to the reference plane until any part of the device touches the head. (In this position, point A is located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact is at any location other than the pinna, the angle of the device shall be reduced. The tilted position is obtained when any part of the device is in contact with the ear as well as a second part of the device is in contact with the head (see Figure below).




Figure 7.3 Front, Side and Top View of Ear/15° Tilt Position

### **Test Position – Body Worn Configurations**

**Body Worn Position** 

- (a) To position the device parallel to the phantom surface with either keypad up or down.
- (b) To adjust the device parallel to the flat phantom.
- (c) To adjust the distance between the device surface and the flat phantom to 1.5 cm or holster surface and the flat phantom to 0 cm.



## ANSI/IEEE C95.1 - 1999 RF Exposure Limit

In order for users to be aware of the body-worn operating requirements for meeting RF exposure compliance, operating instructions and cautions statements are included in the user's manual.

### **Uncontrolled Environment**

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

### **Controlled Environment**

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

**Table 8.1 Human Exposure Limits** 

	UNCONTROLLED ENVIRONMENT General Population (W/kg) or (mW/g)	CONTROLLED ENVIROMENT Professional Population (W/kg) or (mW/g)
SPATIAL PEAK SAR <sup>1</sup> Brain	1.60	8.00
SPATIAL AVERAGE SAR <sup>2</sup> Whole Body	0.08	0.40
SPATIAL PEAK SAR <sup>3</sup> Hands, Feet, Ankles, Wrists	4.00	20.00

<sup>&</sup>lt;sup>1</sup> The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

<sup>2</sup> The Spatial Average value of the SAR averaged over the whole body.

<sup>&</sup>lt;sup>3</sup> The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

## 6 SYSTEM AND LIQUID VALIDATION

### **System Validation**




Fig 8.1 System Setup for System Evaluation

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

In the simplified setup for system evaluation, the DUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:

- 1. Signal Generator
- 2. Amplifier
- 3. Directional Coupler
- 4. Power Meter
- 5. Calibrated Dipole

The output power on dipole port must be calibrated to 30 dBm (1000 mW) before dipole is connected.

## Numerical reference SAR values (W/kg) for reference dipole and flat phantom

Frequency (MHz)	1 g SAR	10 g SAR	Local SAR at surface (above feed-point)	Local SAR at surface (y = 2 cm offset from feed-point) <sup>a</sup>
300	3.0	2.0	4.4	2.1
450	4.9	3.3	7.2	3.2
835	9.5	6.2	4.1	4.9
900	10.8	6.9	16.4	5.4
1450	29.0	16.0	50.2	6.5
1800	38.1	19.8	69.5	6.8
1900	39.7	20.5	72.1	6.6
2000	41.1	21.1	74.6	6.5
2450	52.4	24.0	104.2	7.7
3000	63.8	25.7	140.2	9.5

### Target and measurement SAR after Normalized

Measurement Date	Frequency (MHz)	Liquid Type (head/body)	Target SAR1g (W/kg)	Measured SAR1g (W/kg)	Deviation (%)
Feb 10 <sup>th</sup> ,2012	835	head	9.5	9.2	-3.1
Feb 10 <sup>th</sup> ,2012	835	body	9.5	9.8	+3.1
Feb 10th,2012	1900	head	39.7	38.2	-3.7
Feb 10 <sup>th</sup> ,2012	1900	body	39.7	39.2	-1.2

## **Liquid Validation**

The dielectric parameters were checked prior to assessment using the HP85070C dielectric probe kit. The dielectric parameters measured are reported in each correspondent section.

### IEEE SCC-34/SC-2 P1528 recommended Tissue Dielectric Parameters

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest xpected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations and extrapolated according to the head parameters specified in P1528

Target Frequency	He	ad	Boo	dy
MHz	εr	σ (S/m)	εr	σ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800-2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5800	35.3	5.27	48.2	6.00

**Note:**  $\varepsilon_r = relative\ permittivity, \quad \sigma = conductivity\ and \quad \rho = 1000\ kg/m^3$ 

Serial# 12070016-SAR Issue Date Feb 12th 2012 Page 23 of 98 www.siemic.com

### **Liquid Confirmation Result:**

Temperature: 22°C			Relative humidity: <u>53</u> %			
	Fr	eq(MHz)	Target	Measured	Deviation (%)	Limit (%)
835	Head	Permittivity	41.5	41.84	0.8	5
		Conductivity	0.90	0.92	2.2	5
835	Body	Permittivity	55.2	53.66	-2.7	5
		Conductivity	0.97	0.99	2.06	5
824.2	Head	Permittivity	41.5	41.6	0.24	5
		Conductivity	0.90	0.89	1.1	5
824.2	Body	Permittivity	55.2	54.3	-1.6	5
		Conductivity	0.97	0.98	1.03	5
836.6	Head	Permittivity	41.5	41.53	0.07	5
		Conductivity	0.90	0.90	0.0	5
836.6	Body	Permittivity	55.2	54.1	-1.9	5
		Conductivity	0.97	0.98	1.0	5
848.8	Head	Permittivity	41.5	41.47	0.07	5
		Conductivity	0.90	0.91	1.11	5
848.8	Body	Permittivity	55.2	53.26	-3.5	5
		Conductivity	0.97	0.99	2.06	5

Temperature: <u>22</u> °C			Relative humidity: <u>53</u> %			
	Fr	eq(MHz)	Target	Measured	Deviation (%)	Limit (%)
1900	Head	Permittivity	40.00	40.83	2.07	5
		Conductivity	1.4	1.46	4.2	5
1900	Body	Permittivity	53.3	52.30	-1.87	5
		Conductivity	1.52	1.54	1.31	5
1850.2	Head	Permittivity	40.00	41.94	4.8	5
		Conductivity	1.4	1.38	-1.4	5
1850.2	Body	Permittivity	53.3	54.30	1.87	5
		Conductivity	1.52	1.49	-1.97	5

Note: The liquid validation was performed at Feb 10th, 2012


## System Validation Plots


Product Description: Mobile Phone

Model: i3 Pro


Test Date: Feb 10th, 2012

Frequency (MHz)	835.000000 (Head)
Relative permitivity (real part)	41.84
Conductivity (S/m)	0.92
Input power	10mW
Crest factor	1.0
Conversion Factor	8.78
Variation (%)	-0.020000
SAR 10g (W/Kg)	0.060
SAR 1g (W/Kg)	0.092











**Product Description: Mobile Phone** 

Model: i3 Pro


Test Date: Feb 10th, 2012

Frequency (MHz)	835.000000 (Body)
Relative permitivity (real part)	53.66
Conductivity (S/m)	0.99
Input power	10mW
Crest factor	1.0
Conversion Factor	9.07
Variation (%)	-0.130000
SAR 10g (W/Kg)	0.064
SAR 1g (W/Kg)	0.098











**Product Description: Mobile Phone** 

Model: i3 Pro


Test Date: Feb 10th, 2012

Frequency (MHz)	1900.000000(Head)
Relative permitivity (real part)	40.83
Conductivity (S/m)	1.46
Input power	10mW
Crest factor	1.0
Conversion Factor	9.09
Variation (%)	0.1000000
SAR 10g (W/Kg)	0.201
SAR 1g (W/Kg)	0.382











**Product Description: Mobile Phone** 

Model: i3 Pro


Test Date: Feb 10th, 2012

Frequency (MHz)	1900.000000(Body)
Relative permitivity (real part)	52.30
Conductivity (S/m)	1.54
Input power	10mW
Crest factor	1.0
Conversion Factor	9.32
Variation (%)	0.120
SAR 10g (W/Kg)	0.209
SAR 1g (W/Kg)	0.392





## SAR, Z Axis Scan (X = 1, Y = 0)



## 7 TYPE A MEASUREMENT UNCERTAINTY

The component of uncertainty may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainty by the statistical analysis of a series of observations is termed a Type An evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observation is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience and specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in Table below:

Uncertainty Distribution	Normal	Rectangle	Triangular	U Shape
Multi-plying Factor <sup>(a)</sup>	1/k <sup>(b)</sup>	1 / √3	1/√6	1 / √2

(a) standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity

(b) k is the coverage factor

Standard Uncertainty for Assumed Distribution

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type -sum-by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %.

The COMOSAR Uncertainty Budget is show in below table :

## Uncertainty Budget of COMOSAR for frequency range 300 MHz to 6 GHz

Uncertainty Component	Tolerances %	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Uncertainty 1g(%)	Uncertainty 10g(%)
oomponent	70	Distribution		(19)	(109)	19(70)	109(70)
Measurement System Related	t						
Probe Calibration	6	N	1	1	1	6	6
Axial Isotropy	3	R	√3	√ (1-Cp)	√ (1-Cp)	1.22474	1.22474
Hemispherical Isotropy	4	R	√3	√Cp	√ Cp	1.63299	1.63299
Boundary Effect	1	R	√3	1	1	0.57735	0.57735
Linearity	5	R	√3	1	1	2.88675	2.88675
System Detection Limits	1	R	√3	1	1	0.57735	0.57735
Readout Electronics	0.5	N	1	1	1	0.5	0.5
Response Time	0.2	R	√3	1	1	0.11547	0.11547
Integration Time	2	R	√3	1	1	1.1547	1.1547
RF Ambient Conditions	3	R	√3	1	1	1.73205	1.73205
Probe Positioner Mechanical	2	R	√3	1	1	1.1547	1.1547
Tolerances			V3				
Probe Positioning with	1	R	√3	1	1	0.57735	0.57735
respect to Phantom Shell			V3				
Extrapolation, Interpolation	1.5	R		1	1	0.86603	0.86603
and integration Algorithms for			√3				
Max. SAR Evaluation.							
Test Sample Related							
Test Sample Positioning	1.5	N	1	1	1	1.5	1.5
Device Holder Uncertainty	5	N	1	1	1	5	5
Output Power Variation –	3	R	√3	1	1	1.73205	1.73205
SAR Drift measurement			٧٥				
Phantom and Tissue Paramet	ters Related						
Phantom Uncertainty (Shape	4	R	√3	1	1	2.3094	2.394
and thickness Tolerances)			٧٥				
Liquid Conductivity –	5	R	√3	0.64	0.43	1.84752	1.2413
deviation from target value			٧٥				
Liquid Conductivity –	2.5	N	1	0.64	0.43	1.6	1.075
Measurement Uncertainty							
Liquid Permittivity – deviation	3	R	√3	0.6	0.49	1.03923	0.8487
from target value			٧٥				
Liquid Permittivity –	2.5	N	1	0.6	0.49	1.5	1.225
Measurement Uncertainty			ı				
				Standard L	Incertainty	9.66051 %	9.52428 %
Expanded	Standard Uncert	ainty ( K=2, con	fidence 95%	6)		18.9346 %	18.6676 %

Serial# 12070016-SAR Issue Date Feb 12th 2012 Page 30 of 98 www.siemic.co

## **8 OUTPUT POWER VERIFICATION**

### **Test Condition:**

1. Conducted Measurement

EUT was set for low, mid, high channel with modulated mode and highest RF output power.

The base station simulator was connected to the antenna terminal.

2 Conducted Emissions Measurement Uncertainty

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz - 40GHz is  $\pm 1.5dB$ .

3 Environmental Conditions

Temperature 23°C
Relative Humidity 53%
Atmospheric Pressure 1019mbar

4 Test Date: Feb 10th 2012 Tested By: Chris You

### Test Procedures:

Mobile phone radio output power measurement

- 1. The transmitter output port was connected to base station emulator.
- 2. Establish communication link between emulator and EUT and set EUT to operate at maximum output power all the time.
- 3. Select lowest, middle, and highest channels for each band and different possible test mode.
- 4. Measure the conducted peak burst power and conducted average burst power from EUT antenna port.

### Other radio output power measurement

The output power was measured using power meter at low, mid, and hi channels.

### **Test Configuration:**

EUT supports GSM mode and GPRS multi-slot class 10. The measurement was made under GSM voice call mode, and each possible different uplink configuration, including 1 UL slot, 2 UL slots.

### Source-based Time Averaged Burst Power Calculation:

For TDMA, the following duty cycle factor was used to calculate the source-based time average power

Number of Time slot	1	2	3	4
Duty Cycle	1:8	1:4	1:2.66	1:2
Duty cycle factor	-9.03 dB	-6.02 dB	-4.26 dB	-3.01 dB
Crest Factor	8	4	2.66	2

Remark: <u>Time slot duty cycle factor = 10 \* log (1 / Time Slot Duty Cycle)</u>

Source based time averaged power = Maximum burst averaged power (1 Uplink) – 9.03 dB Source based time averaged power = Maximum burst averaged power (2 Uplink) – 6.02 dB Source based time averaged power = Maximum burst averaged power (4 Uplink) – 3.01 dB Test Result:

### **GSM Mode:**

Burst Average Power (dBm)								
Band		G	SM850			C	SM1900	
Channel	128			Tune up Power tolerant	512	661	810	Tune up Power tolerant
Frequency (MHz)	824.2	836.6	848.8	1	1850.2	1880	1909.8	1
GSM Voice (1 uplink)	32.41	32.55	32.72	32±2	28.50	28.35	28.22	30±2
GPRS Multi-Slot Class 8 (1 uplink)	31.98	32.11	32.28	32±2	28.49	28.33	28.20	30±2
GPRS Multi-Slot Class 10 (2 uplink)	31.94	32.08	32.24	32±2	28.43	28.26	28.14	30±2

Remark:

GPRS, CS1 coding scheme.

Multi-Slot Class 8 , Support Max 4 downlink, 1 uplink , 5 working link

Multi-Slot Class 10, Support Max 4 downlink, 2 uplink, 5 working link

Multi-Slot Class 12, Support Max 4 downlink, 4 uplink, 5 working link

Source Based time Average Power (dBm)								
Band		G	SM850			(	SM1900	
Channel	128	190 251		Time Average factor	512	661	810	Time Average factor
Frequency (MHz)	824.2	836.6	848.8	1	1850.2	1880	1909.8	1
GSM Voice (1 uplink)	23.38	23.52	23.69	-9.03	19.47	19.32	19.19	-9.03
GPRS Multi-Slot Class 8 (1 uplink)	22.95	23.08	23.25	-9.03	19.46	19.30	19.17	-9.03
GPRS Multi-Slot Class 10 (2 uplink)	25.92	22.06	26.22	-6.02	22.41	22.24	22.12	-6.02

### Remark:

Time average factor = 1 uplink , 10\*log(1/8)=-9.03dB , 2 uplink , 10\*log(2/8)=-6.02dB , 4 uplink , 10\*log(4/8)=-3.01dB Source based time average power = Burst Average power + Time Average factor

Note: For GSM/GPRS body SAR testing, the EUT was set in GPRS multi-class 10 with 2 uplink slots due to maximum source-base time-averaged output power.

### **Bluetooth Measurement Result**

Channel number	Frequency (MHz)	Peak Output Power(dBm)	Peak Output Power(mW)
1	2402	-2.33	0.58
6	2441	-0.83	0.83
11	2480	0	1.00

## **SAR TEST RESULTS**

### **Test Condition:**

1. SAR Measurement

> The distance between the EUT and the antenna of the emulator is more than 50 cm and the output power radiated from the emulator antenna is at least 30 dB less than the output power of EUT.

2 Measurement Uncertainty: See page 26 for detail

3 **Environmental Conditions** Temperature 23°C

Relative Humidity 53%

Atmospheric Pressure 1019mbar

4 Test Date: Feb 10th 2012 Tested By: Chris You

### Test Procedures:

1. Establish communication link between EUT and base station emulation by air link.

- 2. Consider the SAR test reduction per FCC KDB guide line. For GSM/GPRS/EGPRS, set EUT into highest output power channel with test mode which has the maximum source-based time-averaged burst power listed in power table. If the source-based time-average output power for each data mode of EGPRS is lower than that in normal GPRS mode, then testing under EGPRS mode is not necessary.
- 3. Place the EUT in the selected test position. (Cheek, tilt or flat)
- 4. Perform SAR testing at highest output power channel under the selected test mode. If the measured 1-q SAR is  $\leq$  0.8 W/kg, then testing for the other channel will not be performed.

SAR measurement system will proceed the following basic steps:

- 1. Initial power reference measurement
- 2. Area Scan
- 3. Zoom Scan
- 4. Power drift measurement

### **Test Configuration:**

1. EUT was tested under GSM voice call mode for head SAR. Testing on GPRS was performed under 2 uplink slots mode body SAR because this mode has greater source-based time averaged power than other uplink slot mode.

Crest factor is 8 for GSM and GPRS multi-slot class 8, 4 for GPRS multi-slot class 10.

# SAR Summary Test Result: GSM850

Date of Measured	: Feb 10th 201	2				Body-Worn	Separation Dist	ance:1.5cm
Position	Channel	Mode	SAR 1g(W/kg)	Limit (W/kg)	Power Drift (%)	Maximum Turn-up Power(dBm)	measured output power (dBm)	Scaled Maximum SAR(W/kg)
Right Head Cheek	Low	GSM voice	0.911	1.6	3.8	34	32.41	1.31
Right Head Cheek	Mid	GSM voice	1.126	1.6	1.77	34	32.55	1.57
Right Head Cheek	High	GSM voice	1.153	1.6	3.12	34	32.72	1.55
Right Head Tilt	High	GSM voice	0.613	1.6	2.51	34	32.72	0.82
Left Head Cheek	Low	GSM voice	1.069	1.6	4.6	34	32.41	1.54
Left Head Cheek	Mid	GSM voice	1.099	1.6	3.56	34	32.55	1.53
Left Head Cheek	High	GSM voice	1.170	1.6	2.88	34	32.72	1.57
Left Head Tilt	High	GSM voice	0.413	1.6	3.25	34	32.72	0.55
Body-worn LCD up	High	GPRS Class 10	0.415	1.6	-1.9	34	32.24	0.62
Body-worn LCD down	High	GPRS Class 10	0.644	1.6	3.34	34	32.24	0.97

### GSM1900

Date of Measured	: Feb 10th 201	Body-Worn S	Separation Dist	ance:1.5cm				
Mode	Channel	Mode	SAR 1g(W/kg)	Limit (W/kg)	Power Drift (%)	Maximum Turn-up Power(dBm)	measured output power (dBm)	Scaled Maximum SAR(W/kg)
Right Head Cheek	Low	GSM voice	0.550	1.6	1.89	32	28.50	1.23
Right Head Tilt	Low	GSM voice	0.105	1.6	2.9	32	28.50	0.24
Left Head Cheek	Low	GSM voice	0.483	1.6	2.21	32	28.50	1.08
Left Head Tilt	Low	GSM voice	0.127	1.6	2.52	32	28.50	0.28
Body-worn LCD up	Low	GPRS Class 10	0.216	1.6	3.01	32	28.43	0.49
Body-worn LCD down	Low	GPRS Class 10	0.511	1.6	2.20	32	28.43	1.16

### KDB648474 & Simultaneous SAR Evaluation.

### **Antenna Separation Information:**



Test Case	TX Ant1	TX Ant2	The shortest distance between Ant & Ant2 (mm)
1	WWAN	BT	61

Antenna Pair	Justification	Simultaneous SAR required ?
BT / WWAN	BT and WWAN Antenna separation is 6.1cm>5cm, and the maximum output power is 1.0mW< Pref(12 mW). So no standalone required for BT	No

## 10 SAR MEASUREMENT REFERENCES

### References

- FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- 2. IEEE Std. C95.1-1991, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3kHz to 300GHz", 1991
- IEEE Std. 1528-2003, "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate(SAR) in the Human Head from Wireless Communication Devices: Measurement Techniques", December 2003
- 4. FCC OET Bulletin 65(Edition 97-01) Supplement C(Edition 01-01), "Evaluation Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields", June 2001
- 5. FCC KDB 447498 D01 v04, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", November 2009
- 6. FCC KDB 648474 D01 v01r05, "SAR Evaluation Considerations for Handsets with Multiple Transmitters and Antennas", September 2008
- 7. FCC KDB 941225 D04 v01, "Evaluation SAR for GSM/(E)GPRS Dual Transfer Mode", January 27 2010
- 8. FCC KDB 941225 D03 v01, "Evaluation SAR Test Reduction Procedures for GSM/GPRS/EDGE", December 2008
- IEC 62209-2, "Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices—Human models, instrumentation, and procedures – Part 2: Procedure to determine the specific absorption rate(SAR) for wireless communication devices used in close proximity to the human body(frequency range of 30MHz to 6GHz)", March 2010

### **SAR** measurement Plots

Test mode: GSM850, low channel (Right Head Cheek)

Product Description: GSM Mobile Phone


Model: i3 Pro


Test Date: Feb 10th, 2012

Frequency (MHz)	824.20000
	(Right Head , Cheek)
Relative permitivity (real part)	41.6
Conductivity (S/m)	0.89
Crest factor	8.0
Conversion Factor	8.78
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	3.80000
SAR 10g (W/Kg)	0.573
SAR 1g (W/Kg)	0.911


## **SURFACE SAR**

## **VOLUME SAR**





## SAR, Z Axis Scan (X = -54, Y = -26)





Test mode: GSM850, middle channel (Right Head Cheek)

Product Description: GSM Mobile Phone

Model: i3 Pro

Z= 0.2

SAVE Concel


Test Date: Feb 10th, 2012

Frequency (MHz)	836.60000 (Right Head , Cheek)
Relative permitivity (real part)	41.53
Conductivity (S/m)	0.90
Crest factor	8.0
Conversion Factor	8.78
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	1.770000
SAR 10g (W/Kg)	0.740
SAR 1g (W/Kg)	1.126


### **SURFACE SAR**

|48 X (mm) | 24 Y (mm)





## SAR, Z Axis Scan (X = -54, Y = -26)





Test mode: GSM850, high channel (Right Head Cheek)

Product Description: GSM Mobile Phone


Model: i3 Pro


Test Date: Feb 10th, 2012

Frequency (MHz)	848.80000 (Right Head, Cheek)
Relative permitivity (real part)	41.47
Conductivity (S/m)	0.91
Crest factor	8.0
Conversion Factor	8.78
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	3.120000
SAR 10g (W/Kg)	0.884
SAR 1g (W/Kg)	1.153

### **SURFACE SAR**







# SAR, Z Axis Scan (X = -33, Y = -16)





Test mode: GSM850, high channel (Right Head Tilt)


Product Description: GSM Mobile Phone

Model: i3 Pro


Test Date: Feb 10th, 2012

Frequency (MHz)	848.80000 (Right Head , Tilt)
Relative permitivity (real part)	41.47
Conductivity (S/m)	0.91
Crest factor	8.0
Conversion Factor	8.78
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	2.510000
SAR 10g (W/Kg)	0.443
SAR 1g (W/Kg)	0.613


### **SURFACE SAR**



|-15 × (mm) |8 Y (mm)



# SAR, Z Axis Scan (X = -18, Y = -8)





Test mode: GSM850, low channel (Left Head Cheek)

Product Description: GSM Mobile Phone


Model: i3 Pro


Test Date: Feb 10th, 2012

Frequency (MHz)	824.20000
	(Left Head, Cheek)
Relative permitivity (real part)	41.6
Conductivity (S/m)	0.89
Crest factor	8.0
Conversion Factor	8.78
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	4.60000
SAR 10g (W/Kg)	0.683
SAR 1q (W/Kq)	1.069


### **SURFACE SAR**

### **VOLUME SAR**





# SAR, Z Axis Scan (X = -50, Y = -26)





Test mode: GSM850, middle channel (Left Head Cheek)

Product Description: GSM Mobile Phone


Model: i3 Pro


Test Date: Feb 10th, 2012

Frequency (MHz)	836.60000
	(Left Head, Cheek)
Relative permitivity (real part)	41.53
Conductivity (S/m)	0.90
Crest factor	8.0
Conversion Factor	8.78
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	3.560000
SAR 10g (W/Kg)	0.754
SAR 1q (W/Kq)	1.099


### **SURFACE SAR**

### **VOLUME SAR**





# SAR, Z Axis Scan (X = -53, Y = -28)





Test mode: GSM850, high channel (Left Head Cheek)

Product Description: GSM Mobile Phone


Model: i3 Pro


Test Date: Feb 10th, 2012

Frequency (MHz)	848.80000
	(Left Head, Cheek)
Relative permitivity (real part)	41.47
Conductivity (S/m)	0.91
Crest factor	8.0
Conversion Factor	8.78
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	2.880000
SAR 10g (W/Kg)	0.787
SAR 1g (W/Kg)	1.170


### SURFACE SAR

### **VOLUME SAR**





# SAR, Z Axis Scan (X = -34, Y = -16)





Test mode: GSM850, high channel (Left Head Tilt)

Product Description: GSM Mobile Phone


Model: i3 Pro


Test Date: Feb 10th, 2012

Frequency (MHz)	848.80000
, , ,	(Left Head , Tilt)
Relative permitivity (real part)	41.47
Conductivity (S/m)	0.91
Crest factor	8.0
Conversion Factor	8.78
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	3.250000
SAR 10g (W/Kg)	0.289
SAR 1a (W/Ka)	0.413


### **SURFACE SAR**

### **VOLUME SAR**





# SAR, Z Axis Scan (X = -32, Y = -23)





Test mode: GPRS850, high channel (Body-LCD UP)

Product Description: GSM Mobile Phone


Model: i3 Pro


Test Date: Feb 10th, 2012

Frequency (MHz)	848.80000
	(Body, LCD UP)
Relative permitivity (real part)	53.26
Conductivity (S/m)	0.99
Crest factor	4.0
Conversion Factor	9.07
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-1.90000
SAR 10g (W/Kg)	0.284
SAR 1g (W/Kg)	0.415


### **SURFACE SAR**

### **VOLUME SAR**





# SAR, Z Axis Scan (X = 0, Y = -41)





Test mode: GPRS850, high channel (Body-LCD DOWN)

Product Description: GSM Mobile Phone


Model: i3 Pro


Test Date: Feb 10th, 2012

Frequency (MHz)	848.80000
	(Body, LCD DOWN)
Relative permitivity (real part)	53.26
Conductivity (S/m)	0.99
Crest factor	4.0
Conversion Factor	9.07
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	3.340000
SAR 10g (W/Kg)	0.420
SAR 1q (W/Kq)	0.644


### **SURFACE SAR**

### **VOLUME SAR**





# SAR, Z Axis Scan (X = 5, Y = -15)





Test mode: GSM1900, Low channel (Right Head Cheek)

Product Description: GSM Mobile Phone


Model: i3 Pro


Test Date: Feb 10th, 2012

Frequency (MHz)	1850.20000
	(Right Head , Cheek)
Relative permitivity (real part)	41.94
Conductivity (S/m)	1.38
Crest factor	8.0
Conversion Factor	9.09
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	1.8900000
SAR 10g (W/Kg)	0.265
SAR 1q (W/Kq)	0.550


### **SURFACE SAR**

### **VOLUME SAR**





# SAR, Z Axis Scan (X = -49, Y = -39)





Test mode: GSM1900, Low channel (Right Head Tilt)

Product Description: GSM Mobile Phone


Model: i3 Pro


Test Date: Feb 10th, 2012

Frequency (MHz)	1850.200000
	(Right Head, Tilt)
Relative permitivity (real part)	41.94
Conductivity (S/m)	1.38
Crest factor	8.0
Conversion Factor	9.09
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	2.90000
SAR 10g (W/Kg)	0.045
SAR 1q (W/Kq)	0.105


### **SURFACE SAR**

### **VOLUME SAR**





# SAR, Z Axis Scan (X = 8, Y = 0)





Test mode: GSM1900, Low channel (Left Head Cheek)

Product Description: GSM Mobile Phone


Model: i3 Pro


Test Date: Feb 10th, 2012

Frequency (MHz)	1850.200000
	(Left Head, Cheek)
Relative permitivity (real part)	41.94
Conductivity (S/m)	1.38
Crest factor	8.0
Conversion Factor	9.09
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	2.210000
SAR 10g (W/Kg)	0.209
SAR 1g (W/Kg)	0.483


### **SURFACE SAR**

### **VOLUME SAR**





# SAR, Z Axis Scan (X = -56, Y = -40)





Test mode: GSM1900, Low channel (left Head Tilt)

Product Description: GSM Mobile Phone


Model: i3 Pro


Test Date: Feb 10th, 2012

Frequency (MHz)	1850.200000 (Left Head, Tilk)
	(Left Head , Tilt)
Relative permitivity (real part)	41.94
Conductivity (S/m)	1.38
Crest factor	8.0
Conversion Factor	9.09
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	2.520000
SAR 10g (W/Kg)	0.057
SAR 1g (W/Kg)	0.127


### **SURFACE SAR**

### **VOLUME SAR**





# SAR, Z Axis Scan (X = -10, Y = 17)





Test mode: GPRS1900, low channel (Body LCD-UP)

Product Description: GSM Mobile Phone


Model: i3 Pro


Test Date: Feb 10th, 2012

Frequency (MHz)	1850.200000 (Pody LCD LID)
	(Body, LCD UP)
Relative permitivity (real part)	54.30
Conductivity (S/m)	1.49
Crest factor	4.0
Conversion Factor	9.32
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	3.010000
SAR 10g (W/Kg)	0.104
SAR 1g (W/Kg)	0.216


### **SURFACE SAR**

### **VOLUME SAR**





# SAR, Z Axis Scan (X = -6, Y = -6)





Test mode: GPRS1900, low channel (Body LCD-DOWN)

Product Description: GSM Mobile Phone


Model: i3 Pro


Test Date: Feb 10th, 2012

Frequencfy (MHz)	1850.200000		
	(Body, LCD DOWN)		
Relative permitivity (real part)	54.30		
Conductivity (S/m)	1.49		
Crest factor	4.0		
Conversion Factor	9.32		
Area Scan	dx=8mm dy=8mm		
Zoom Scan	7x7x7,dx=8mm dy=8mm dz=5mm		
Variation (%)	2.200000		
SAR 10g (W/Kg)	0.243		
SAR 1g (W/Kg)	0.511		


### **SURFACE SAR**

### **VOLUME SAR**





# SAR, Z Axis Scan (X = -7, Y = -14)



# Annex A. TEST INSTRUMENT & METHOD

Annex A.i. TEST INSTRUMENTATION & GENERAL PROCEDURES						
Name of Equipment	Manufacturer	Type/Model	Serial Number	Calibration Date	Calibration Due	
PC	Compaq	PV 3.06GHz	375052-AA1	N/A	N/A	
Signal Generator	Agilent	8665B-008	3744A10293	05/17/2011	05/17/2012	
MultiMeter	Keithley	MiltiMeter 2000	1259033	06/21/2011	06/21/2012	
S-Parameter Network Analyzer	Agilent	8753ES	US39173518	08/04/2011	08/04/2012	
Wireless Communication Test Set	R&S	CMU200	111078	07/22/2011	07/22/2012	
Power Meter	HP	437B	3038A03648	05/17/2011	05/17/2012	
E-field PROBE	SATIMO	SSE2	SN 26/11 EPG122	10/03/2011	10/03/2012	
DIPOLE 835	SATIMO	DIPOLE 835MHz	SN 18/11 DIPC 150	06/01/2011	06/01/2012	
DIPOLE 900	SATIMO	DIPOLE 900MHz	SN 18/11 DIPC 151	06/01/2011	06/01/2012	
DIPOLE 1800	SATIMO	DIPOLE 1800MHz	SN 18/11 DIPC 152	06/01/2011	06/01/2012	
DIPOLE 1900	SATIMO	DIPOLE 1900MHz	SN 18/11 DIPG 153	06/01/2011	06/01/2012	
DIPOLE 2000	SATIMO	DIPOLE 2000MHz	SN 18/11 DIPC 154	06/01/2011	06/01/2012	
DIPOLE 2450	SATIMO	DIPOLE 2450MHz	SN 18/11 DIPJ 155	06/01/2011	06/01/2012	
DIPOLE 3500	SATIMO	DIPOLE 3500MHz	SN 18/11 DIPC 156	06/01/2011	06/01/2012	
WaveGuide 5/6 GHz	SATIMO	Wave Guide 5/6GHz	SN 31/10 DIPWGA13	06/01/2011	06/01/2012	
COMOHAC E-Field Probe	SATIMO	EPH30	SN 24/11 EPH30	06/01/2011	06/01/2012	
COMOHAC H-Field Probe	SATIMO	HPH42	SN 43/10 HPH42	06/01/2011	06/01/2012	
COMOSAR Open Coaxial Probe	SATIMO	OCP43	SN 24/11 OCPG43	06/01/2011	06/01/2012	
T-Coil Probe	SATIMO	TCP21	SN 24/11 TCP21	06/01/2011	06/01/2012	
Communication Antenna	SATIMO	ANTA3	SN 20/11 ANTA 3	06/20/2011	06/20/2012	
Laptop POSITIONING DEVICE	SATIMO	LSH15	SN 24/11 LSH15	N/A	N/A	
Mobile Phone POSITIONING DEVICE	SATIMO	MSH73	SN 24/11 MSH73	N/A	N/A	
COMOHAC Broadband Dipole 800-950	SATIMO	COMOHAC Broadband Dipole 800-950MHz	SN 24/11 DHA31	06/01/2011	06/01/2012	
COMOHAC Broadband Dipole 1700-2000	SATIMO	COMOHAC Broadband Dipole 1700-2000MHz	SN 24/11 DHB32	06/01/2011	06/01/2012	
COMOHAC TELEPHONE MAGNETIC FIELD SIMULATOR	SATIMO	TMFS12		06/01/2011	06/01/2012	
DUMMY PROBE	ANTENNESSA		DP41	N/A	N/A	

 Serial#
 12070016-SAR

 Issue Date
 Feb 12th 2012

 Page
 52 of 98



Serial# 12070016-SAR Issue Date Feb 12th 2012 Page 53 of 98 www.siemic.com

SAM PHANTOM	SATIMO	SAM87	SN 24/11 SAM87	N/A	N/A
Elliptic Phantom	SATIMO	ELLI20	SN 20/11ELLI20	N/A	N/A
PHANTOM TABLE	SATIMO	N/A	N/A	N/A	N/A
6 AXIS ROBOT	KUKA	KR5	949272	N/A	N/A
High Power Solid State Amplifier (80MHz~1000MHz)	Instruments for Industry	CMC150	M631-0408	N/A	N/A
Medium Power Solid State Amplifier (0.8~4.2GHz)	Instruments for Industry	S41-25	M629-0408	N/A	N/A
Wave Tube Amplifier 4- 8 GHz at 20Watt	Hughes Aircraft Company	1277H02F000	81	N/A	N/A

# Annex B CALIBRATION REPORTS



Serial# 12070016-SAR Issue Date Feb 12th 2012 Page 55 of 98 www.siemic.com



### **COMOSAR E-Field Probe Calibration Report**

Ref: ACR.277.1.11.SATU.B

# SIEMIC TESTING AND CERTIFICATION SERVICES

SUITE 311, BUILDING 1, SECTION 30 ,NO.2 KEFA ROAD, SCIENCE AND TECHNOLOGY PARK

NAN SHAN DISTRICT, SHENZHEN 518057, GUANGDONG, P.R.C.

#### SATIMO COMOSAR DOSIMETRIC E-FIELD PROBE

SERIAL NO.: SN 26/11 EPG129

Calibrated at SATIMO US 2105 Barrett Park Dr. - Kennesaw, GA 30144



10/03/2011

#### Summary:

This document presents the method and results from an accredited COMOSAR Dosimetric E-Field Probe calibration performed in SATIMO USA using the CALISAR / CALIBAIR test bench, for use with a SATIMO COMOSAR system only. All calibration results are traceable to national metrology institutions.

 Serial#
 12070016-SAR

 Issue Date
 Feb 12th 2012

 Page
 56 of 98

 www.siemic.com



#### COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref ACR 277.1.11 SATU B

	Name	Function	Date	Signature
Prepared by :	Jérôme LÚC	Product Manager	10/4/2011	15
Checked by :	Jérôme LUC	Product Manager	10/4/2011	13
Approved by:	Km RUTKOWSKI	Quality Manager	10/4/2011	Vim Antipologica

	Customer Name
Distribution (	SIEMIC Testing and Certification Services

Issue	Date	Modifications
A	10/4/2011	Initial release
В	11/30/2011	Add detail about the calibration method

Serial# 12070016-SAR Issue Date Feb 12th 2012 Page 57 of 98 www.siemic.com



#### COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref. ACR 277.1.11 SATUE

#### TABLE OF CONTENTS

1 De	evice Under Test	4
2 Pro	oduct Description	4
2.1	General Information	4
3 Me	easprement Method	4
3.1	Method	4
3.2	Linearity	5
3.3	Sensitivity	6
3.4	Lower Detection Limit	6
3.5	Isotropy	6
3.6	Boundary Effect	6
4 Me	easurement Uncertainty	6
5 Ca	libration Measurement Results	Ť
5.1	Sensitivity in air	
5.2	Lineanty	
5.3	Sensitivity in liquid	
5.4	Isotropy	9
6 Lis	st of Equipment	11



#### COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref ACR 277.1.11 SATUB

#### 1 DEVICE UNDER TEST

Device Under Test			
Device Type	COMOSAR DOSIMETRIC E FIELD PROBE		
Manufacturer	Satimo		
Model	SSE2		
Serial Number	SN 26/11 EPG129		
Product Condition (new / used)	new		
Frequency Range of Probe	0.7 GHz-6GHz		
Resistance of Three Dipoles at Connector	Dipole 1: R1=0.153 MΩ		
As a remain of other transfer of a party of	Dipole 2: R2=0.215 MΩ		
	Dipole 3: R3=0.192 MΩ		

A yearly calibration interval is recommended.

#### 2 PRODUCT DESCRIPTION

#### 2.1 GENERAL INFORMATION

Satimo's COMOSAR E field Probes are built in accordance to the IEEE 1528, OET 65 Bulletin C and CEL/IEC 62209 standards.



Figure 1 - Satimo COMOSAR Dosimetric E field Dipole

Probe Length	330 mm
Length of Individual Dipoles	2 mm
Maximum external diameter	8 mm
Probe Tip External Diameter	2.5 mm
Distance between dipoles / probe extremity	1 mm

#### 3 MEASUREMENT METHOD

The IEEE 1528, OET 65 Bulletin C, CENELEC EN50361 and CEI/IEC 62209 standards provide recommended practices for the probe calibrations, including the performance characteristics of interest and methods by which to assess their affect. All calibrations / measurements performed meet the fore mentioned standards.

#### 3.1 METHOD

Probe calibration is realized, in compliance with CENELEC EN 50361; CEI/IEC 62209 and IEEE 1528 std, with CALISAR, SATIMO proprietary calibration system. The calibration is performed with the technique using reference waveguide.

Page: 4/11




Serial# 12070016-SAR Issue Date Feb 12th 2012 Page 59 of 98 www.siemic.com



#### COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR 277.1.11 SATU B



 $SAR = \frac{4\left(P_{fw} - P_{bw}\right)}{ab\delta} \cos^2\left(\pi \frac{y}{a}\right) e^{-(2z/\delta)}$ 

Where:

P<sub>fw</sub> = Forward Power P<sub>fw</sub> = Backward Power a and b = Waveguide dimensions

= Skin depth

Keithley configuration:

Rate = Medium; Filter =ON; RDGS=10; FILTER TYPE =MOVING AVERAGE; RANGE AUTO

After each calibration, a SAR measurement is performed on a validation dipole and compared with a NPL calibrated probe, to verify it.

#### 3.2 LINEARITY

The evaluation of the linearity was done in free space using the waveguide, performing a power sweep to cover the SAR range  $0.01 \mathrm{W/kg}$  to  $100 \mathrm{W/kg}$ .

Serial# 12070016-SAR Issue Date Feb 12th 2012 Page 60 of 98 www.siemic.com



#### COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR 277.1.11 SATU.B

#### 3.3 SENSITIVITY

The sensitivity factors of the three dipoles were determined using a two step calibration method (air and rissue simulating liquid) using waveguides as outlined in the standards.

#### 3.4 LOWER DETECTION LIMIT

The lower detection limit was assessed using the same measurement set up as used for the linearity measurement. The required lower detection limit is 10 mW/kg.

#### 3.5 ISOTROPY

The axial isotropy was evaluated by exposing the probe to a reference wave from a standard dipole with the dipole mounted under the flat phantom in the test configuration suggested for system validations and checks. The probe was rotated along its main axis from 0 - 360 degrees in 15 degree steps. The hemispherical isotropy is determined by inserting the probe in a thin plastic box filled with tissue-equivalent liquid, with the plastic box illuminated with the fields from a half wave dipole. The dipole is rotated about its axis (0°–180°) in 15° increments. At each step the probe is rotated about its axis (0°–360°).

#### 3.6 BOUNDARY EFFECT

The boundary effect is defined as the deviation between the SAR measured data and the expected exponential decay in the liquid when the probe is oriented normal to the interface. To evaluate this effect, the liquid filled flat phantom is exposed to fields from either a reference dipole or waveguide. With the probe normal to the phantom surface, the peak spatial average SAR is measured and compared to the analytical value at the surface.

#### 4 MEASUREMENT UNCERTAINTY

The guidelines outlined in the IEEE 1528, OET 65 Bulletin C, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty associated with an E-field probe calibration using the waveguide technique. All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

ERROR SOURCES	Uncertainty value (%)	Probability Distribution	Divisor	ci	Standard Uncertainty (%)
Incident or forward power	3.00%	Rectangular	√3	1	1.732%
Reflected power	3.00%	Rectangular	$\sqrt{3}$	1	1.732%
Liquid conductivity	5.00%	Rectangular	$\sqrt{3}$	1	2.887%
Liquid permittivity	4.00%	Rectangular	√3 I	1	2 309%
Field homogeneity	3,00%	Rectangular	$\sqrt{3}$	1	1.732%
Field probe positioning	5.00%	Rectangular	√3	- 1	2,887%
Field probe linearity	3.00%a	Rectangular	√3	Í	1.732%



#### COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR 277.1.11 SATU B

Combined standard uncertainty	5.831%
Expanded uncertainty 95 % confidence level k = 2	11.662%

Issue Date Feb 12th 2012
Page 61 of 98

#### 5 CALIBRATION MEASUREMENT RESULTS

Calibration Parameters			
Liquid Temperature	21 °C		
Lab Temperature	21 °C		
Lab Humidity	45 %		


#### 5.1 SENSITIVITY IN AIR

Normx dipole		
$1 \left( \mu V / (V/m)^2 \right)$	$2 \left( \mu V/(V/m)^2 \right)$	$3 (\mu V/(V/m)^2)$
0.53	0.53	0.58

DCP dipole 1	DCP dipole 2	DCP dipole 3
(mV)	(mV)	(mV)
120	118	123

Calibration curves ei=f(V) (i=1,2,3) allow to obtain H-field value using the formula:

$$E = \sqrt{E_1^2 + E_2^2 + E_3^2}$$



Dipole 1 Dipole 2


Page. 7/11



#### COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref ACR 277.1.11 SATUB

#### 5.2 LINEARITY



Linearity: 11+/-3.51% (+/-0.16dB)

#### 5.3 SENSITIVITY IN LIQUID

Liquid	Frequency (MHz +/- 100MHz)	Permittivity	Epsilon (S/m)	ConvE
HL850	835	42.56	0.88	8.78
BL850	835	55.23	0.98	9.07
HL900	900	42.02	0.96	8.74
BL900	900	55.02	1.03	9.03
HL1800	1750	39.03	1.39	8.60
BL1800	1750	53.78	1.50	8.83
HL1900	1880	39.43	1.42	9.09
BL1900	1880	53.99	1.52	9.32
HL2000	1950	39.43	1.44	8.54
BL2000	1950	54.76	1.54	8.82
HL2450	2450	40.32	1.82	9.02
BL2450	2450	53.67	1.96	9.28
HL3500	3500	36.43	2.86	7.99
BL3500	3500	52.75	3.43	8.31
HL5200	5200	34.57	4.41	6.30
BL5200	5200	48.32	5.01	6.43
HL5500	5500	34.93	4.96	7.27
BL5500	5500	48.99	5.77	7.55
HL5800	5800	33.69	5.42	7.52
BL5800	5800	49.56	6.11	7.79

LOWER DETECTION LIMIT: 7mW/kg

Serial# 12070016-SAR Issue Date Feb 12th 2012 Page 63 of 98 www.siemic.com




#### COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref. ACR 277.1.11 SATU.

#### 5.4 ISOTROPY


#### HL900 MHz

- Axial isotropy: 0.08 dB - Hemispherical isotropy: 0.04 dB



#### HL1800 MHz

- Axial isotropy: 0.09 dB - Hemispherical isotropy: 0.07 dB



 Serial#
 12070016-SAR

 Issue Date
 Feb 12th 2012

 Page
 64 of 98

 www.siemic.com




#### COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref. ACR 277.1.11 SATUB

#### HL5500 MHz

- Axial isotropy: 0.14 dB
- Hemispherical isotropy: 0.08 dB



Serial# 12070016-SAR Issue Date Feb 12th 2012 Page 65 of 98 www.siemic.com



#### COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR 277.1.11 SATU B

#### 6 LIST OF EQUIPMENT

Equipment Summary Sheet				
Equipment Description	Manufacturer/ Madel	Identification No.	Current Calibration Date	Next Calibration Date
Flat Phantom	Satimo	SN-20/09-SAM71	Validated. No cal required	Validated. No cal required.
COMOSAR Test Bench	Version 3	NA	Validated. No cal required.	Validated. No cal required.
Network Analyzer	Rhode & Schwarz ZVA	SN100132	02/2010	02/2013
Reference Probe	Satimo	EP 94 SN 37/08	Characterized prior to test. No cal required.	Characterized prior to test. No cal required,
Multimeter	Keithley 2000	1188656	11/2010	11/2013
Signal Generalor	Agilent E4438C	MY49070581	12/2010	12/2013
Amplifier	Aethercomm	SN 046	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Power Meter	HP E4418A	US38261498	11/2010	11/2013
Power Sensor	HP ECP-E26A	US37181460	11/2010	11/2013
Directional Coupler	Narda 4216-20	01386	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Waveguide	Mega Industries	069Y7-158-13-712	Validated. No cal required.	Validated No cal required.
Waveguide Transition	Mega Industries	069Y7-158-13-701	Validated. No cal required.	Validated. No cal required.
Wayeguide Termination	Mega Industries	069Y7-158-13-701	Validated. No cal required.	Validated. No cal required.
Temperature / Humidity Sensor	Control Company	11-661-9	3/2010	3/2012

Serial# 12070016-SAR Issue Date Feb 12th 2012 Page 66 of 98 www.siemic.com



### SAR Reference Dipole Calibration Report

Ref: ACR.158.4.11.SATU.A

# SIEMIC TESTING AND CERTIFICATION SERVICES

SUITE 311, BUILDING 1, SECTION 30 ,NO.2 KEFA ROAD, SCIENCE AND TECHNOLOGY PARK
NAN SHAN DISTRICT, SHENZHEN 518057, GUANGDONG ,P.R.C.

### SATIMO COMOSAR REFERENCE DIPOLE

Calibrated at SATIMO US 2105 Barrett Park Dr. - Kennesaw, GA 30144



06/01/2011

#### Summary:

This document presents the method and results from an accredited SAR reference dipole calibration performed in SATIMO USA using the COMOSAR test bench. All calibration results are traceable to national metrology institutions.

Serial# 12070016-SAR Issue Date Feb 12th 2012 Page 67 of 98 www.siemic.com



#### SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR, 158, 4.11, SATU. A

	Name	Function	Date	Signature
Prepared by :	Jérôme LUC	Product Manager	6/7/2011	JES
Checked by:	Jérôme LUC	Product Manager	6/7/2011	Jes
Approved by:	Kim RUTKOWSKI	Quality Manager	6/7/2011	sum Putthoust

	Customer Name
Distribution :	SIEMIC Testing and Certification Services

Issue	Date	Modifications	
A	6/7/2011	Initial release	

Serial# 12070016-SAR Issue Date Feb 12th 2012 Page 68 of 98 www.siemic.com



#### SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR. 158.4.11.5ATU.A

#### TABLE OF CONTENTS

1	Intr	oduction4	
2	De	vice Under Test4	
3	Pro	duct Description4	
	3.1		4
4	Me	asurement Method5	
	4.1	Return Loss Requirements	5
	4.2	Mechanical Requirements	5
5	Me	asurement Uncertainty5	
	5.1	Return Loss	5
	5.2	Dimension Measurement	5
	5.3	Validation Measurement	
6	Cal	ibration Measurement Results6	
	6.1	Return Loss_	6
	6.2	Mechanical Dimensions	6
7	Val	idation measurement7	
	7.1	Measurement Condition	7
	7.2	Head Liquid Measurement	,7
	7.3	Measurement Result	8
8	Lis	t of Equipment8	

Serial# 12070016-SAR Issue Date Feb 12th 2012 Page 69 of 98 www.siemic.com



#### SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR, 158.4.1 LSATULA

#### 1 INTRODUCTION

This document contains a summary of the requirements set forth by the IEEE 1528, OET 65 Bulletin C and CEI/IEC 62209 standards for reference dipoles used for SAR measurement system validations and the measurements that were performed to verify that the product complies with the fore mentioned standards.

#### 2 DEVICE UNDER TEST

Device Under Test			
Device Type COMOSAR 835 MHz REFERENCE DIPOLE			
Manufacturer Satimo			
Model	SID835		
Serial Number	SN 18/11 DIPC150		
Product Condition (new / used)	new		

A yearly calibration interval is recommended.

#### 3 PRODUCT DESCRIPTION

#### 3.1 GENERAL INFORMATION

Satimo's COMOSAR Validation Dipoles are built in accordance to the IEEE 1528, OET 65 Bulletin C and CEI/IEC 62209 standards. The product is designed for use with the COMOSAR test bench only.



Figure 1 - Satimo COMOSAR Validation Dipole

Serial# 12070016-SAR Issue Date Feb 12th 2012 Page 70 of 98 www.siemic.com



#### SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR. 158,4,11.SATU,A

#### 4 MEASUREMENT METHOD

The IEEE 1528, OET 65 Bulletin C and CEI/IEC 62209 standards provide requirements for reference dipoles used for system validation measurements. The following measurements were performed to verify that the product complies with the fore mentioned standards.

#### 4.1 RETURN LOSS REQUIREMENTS

The dipole used for SAR system validation measurements and checks must have a return loss of -20 dB or better. The return loss measurement shall be performed against a liquid filled flat phantom, with the phantom constucted as outlined in the fore mentioned standards.

#### 4.2 MECHANICAL REQUIREMENTS

The IEEE Std. 1528 and CEI/IEC 62209 standards specify the mechanical components and dimensions of the validation dipoles, with the dimensions frequency and phantom shell thickness dependent. The COMOSAR test bench employs a 2 mm phantom shell thickness therefore the dipoles sold for use with the COMOSAR test bench comply with the requirements set forth for a 2 mm phantom shell thickness.

#### 5 MEASUREMENT UNCERTAINTY

All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

#### 5.1 RETURN LOSS

The following uncertainties apply to the return loss measurement:

Expanded Uncertainty on Return Loss
0.1 dB

#### 5.2 DIMENSION MEASUREMENT

The following uncertainties apply to the dimension measurements:

Expanded Uncertainty on Length
0.05 mm

#### 5.3 VALIDATION MEASUREMENT

The guidelines outlined in the IEEE 1528, OET 65 Bulletin C, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty for validation measurements.

Scan Volume	Expanded Uncertainty
Tg	16.19 %
10 g	15.86 %

Page: 5/9




#### SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref; ACR. 158.4.11. SATU, A

#### 6 CALIBRATION MEASUREMENT RESULTS

#### 6.1 RETURN LOSS



Frequency (MHz)	Return Loss (dB)	Requirement (dB)
835	-35.8	-20

#### 6.2 MECHANICAL DIMENSIONS

Frequency MH2	L'mm		himm		di	nm
	required	measured	required	measured	required	measured
300	420.0 ±1 %.		250.0 ±1 %.		6.35 ±1 %.	
450	290.0 ±1 %.		166.7 ±1 %.		5.35 ±1 %.	
750	176.0 ±1 %.		100.0 ±1.%.		6.35 ±1 %.	
835	161.0 ±1 %.	PASS	89.8 ±1 %.	PASS	3.6 ±1 %.	PASS
900	149.0 ±1 %.		83,3 ±1 %.		3.6±1%.	
1450	89.1±1%.		51.7±1 %.		3.6 ±1%.	
1500	80.5 ±1 %.		50.0 ±1 %.		3.6 ±1 %.	
1640	79.0 ±1.%		45.7±1%.		3.6 ±1 %.	
1750	75,2 ±1 %.	Ī	42.9 ±1 %.		3.6 ±1.%	
1800	72.0 ±1 %.		41.7±1%.		3.6 ±1 %.	
1900	68.0 ±1.%		39.5±1%.		3.6±1%.	
1950	66.3 ±1%.		38,5 ±1 %.		3.6 ±1.%	
2000	54.5 ±1 %.		37.9 ±1 %.		3.6 ±1 %.	
2100	61.0 ±1.%		35.7±1%.		3.6 ±1 %.	
2300	55.5 ±1%.	7	32.6 ±1 %.		3.6 ±1%	
2450	51.5±1%.		30.4±1%.		3.6 ±1 %.	
2600	48.5 ±1.%		28.8 ±1 %.		3.6 ±1 %.	
3000	41.5 ±1 %.	7	25.0 ±1 %.		3.6 ±1%	
3500	37.0±1 %.		26.4±1%.		3.6 ±1 %	
3700	34,7±1 %.		26.4±1 %.		3.6 ±1 %	

Page: 6/9

Serial# 12070016-SAR Issue Date Feb 12th 2012 Page 72 of 98 www.siemic.com



#### SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR, 158.4.1 LSATULA

#### 7 VALIDATION MEASUREMENT

The IEEE Std. 1528, OET 65 Bulletin C and CEI/IEC 62209 standards state that the system validation measurements must be performed using a reference dipole meeting the fore mentioned return loss and mechanical dimension requirements. The validation measurement must be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. Per the standards, the dipole shall be positioned below the bottom of the phantom, with the dipole length centered and parallel to the longest dimension of the flat phantom, with the top surface of the dipole at the described distance from the bottom surface of the phantom.

#### 7.1 MEASUREMENT CONDITION

Software	OPENSAR V4	
Phantom	SN 20/09 SAM71	
Probe	SN 18/11 EPG122	
Liquid	Head Liquid Values: eps' : 43.0 sigma : 0.88	
Distance between dipole center and liquid	15,0 mm	
A rea scan resolution	dx=8mm/dy=8mm	
Zoon Scan Resolution	dx=8mm/dy=8m/dz=5mm	
Frequency	835 MHz	
Input power	20 dBm	
Liquid Temperature	21 °C	
Lab Temperature	21 °C	
Lab Humidity	45 %	

#### 7.2 HEAD LIQUID MEASUREMENT

Frequency MHz	Relative normittivity (g.)		Conductiv	rity (a) 5/m
	required	measured	required	measured
300	45.3 ±5 %		0.87 ±5 %	
450	43.5±5%	1	0.87 ±5 %	
750	41.9 ±5 %		0.89 ±5 %	
835	A1.5 ±5 %	PASS	0.90 ±5 %	PASS
900	41,5 ±5 %		0.97 ±5 16	
1450	40.5 ±5 %		1.20 ±5 %	
1500	40.4±5%		1.23 ±5 16	
1640	40,2 ±5 %		1.31 ±5 %	
1750	40.1 ±5 %		1.37 ±5 %	
1800	40.0 ±5 %		1.40 ±5 %	
1900	40,0 ±5 %	, -	1.40 ±5 %	
1950	40.0±5.%		1.40 ±5 %	
2000	40.0 ±5 %		1.40 ±5 %	
2100	39.8 ±5 %		1.49 ±5 %	
2300	39.5 ±5.%		1.67 ±5 %	
2450	39.2 ±5 %	-	1.80 ±5 %	
2600	39.0 ±5 %		1.96 ±5 %	
3000	38.5 ±5.%		2.40.±5%	
3500	37.9 ±5 %	b	2.91 ±5 %	

Page: 7/9




#### SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR, 158.4.11.SATU.A

#### 7.3 MEASUREMENT RESULT

The IEEE Std. 1528 and CEI/IEC 62209 standards state that the system validation measurements should produce the SAR values shown below (for phantom thickness of 2 mm), within the uncertainty for the system validation. All SAR values are normalized to 1 W forward power. In bracket, the measured SAR is given with the used input power.

Frequency MHz	1 g SAR	(W/kg/W)	10 g SAR	(W/kg/W)
	required	measured	required	measured
300	2.85		1.94	
45Q	4.58		3,06	
750	8.49		5.55	
835	9.56	9.59 (0.96)	6,22	6.25 (0.62
900	10.9		6.99	
1450	29		16	
1500	30.5		16.8	
1640	34,2		18.4	
1750	35.4		19.3	
1800	38.4		20,1	
1900	39.7		20.5	
1950	40.5		20.9	
2000	41.1		21,1	
2100	43.6		21.9	
2300	48.7		23.3	
2450	52.4	1	24	
2600	55:3		24.6	
3000	63.8		25.7	
3500	67.1	7	25	



Page: 8/9

Serial# 12070016-SAR Issue Date Feb 12th 2012 Page 74 of 98 www.siemic.com



#### SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR, 158, 4.11, SATU.A

#### 8 LIST OF EQUIPMENT

	Equi	pment Summary S	Sheet			
Equipment Description	Manufacturer / Model	Identification No.	Current Calibration Date	Next Calibration Date		
Flat Phantom	Satimo	SN-20/09-SAM71	Validated. No cal required.	Validated. No ca required.		
COMOSAR Test Bench	Version 3	NA	Validated. No cal required.	Validated. No ca required.		
Network Analyzer	Rhode & Schwarz ZVA	SN100132	02/2010	02/2013		
Calipers	Carrera	CALIPER-01	12/2010	12/2013		
Reference Probe	Satimo	EPG122 SN 18/11	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.		
Multimeter	Keithley 2000	1188656	11/2010	11/2013		
Signal Generator	Agilent E4438C	MY49070581	12/2010	12/2013		
Amplifier	Aethercomm	SN 046	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.		
Power Meter	HP E4418A	US38261498	11/2010	11/2013		
Power Sensor	HP ECP-E26A	US37181460	11/2010	11/2013		
Directional Coupler	Narda 4216-20	01386	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.		
Temperature and Humidity Sensor	Control Company	11-661-9	3/2010	3/2012		

Serial# 12070016-SAR Issue Date Feb 12th 2012 Page 75 of 98 www.siemic.cor



# SAR Reference Dipole Calibration Report

Ref: ACR.158.7.11.SATU.A

# SIEMIC TESTING AND CERTIFICATION SERVICES

SUITE 311, BUILDING 1, SECTION 30 ,NO.2 KEFA ROAD, SCIENCE AND TECHNOLOGY PARK
NAN SHAN DISTRICT, SHENZHEN 518057, GUANGDONG ,P.R.C.

## SATIMO COMOSAR REFERENCE DIPOLE

Calibrated at SATIMO US 2105 Barrett Park Dr. - Kennesaw, GA 30144



06/01/2011

#### Summary:

This document presents the method and results from an accredited SAR reference dipole calibration performed in SATIMO USA using the COMOSAR test bench. All calibration results are traceable to national metrology institutions.

Serial# 12070016-SAR Issue Date Feb 12th 2012 Page 76 of 98 www.siemic.com



#### SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR. 158.7.11. SATU.A

	Name	Function	Date	Signature
Prepared by :	Jérôme LUC	Product Manager	6/7/2011	JES
Checked by:	Jérôme LUC	Product Manager	6/7/2011	JES
Approved by:	Kim RUTKOWSKI	Quality Manager	6/7/2011	from Putthoushi

	Customer Name
Distribution :	SIEMIC Testing and Certification Services

Issue	Date	Modifications	
A	6/7/2011	Initial release	

Serial# 12070016-SAR Issue Date Feb 12th 2012 Page 77 of 98 www.siemic.com



#### SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR 158.7.1 LSATULA

#### TABLE OF CONTENTS

1		roduction4	
2	Des	vice Under Test4	
3	Pro	duct Description	
3	3.1	General Information	- 4
4	Me	asurement Method	
2	1.1	Return Loss Requirements	5
2	4.2	Mechanical Requirements	5
5	Me	asurement Uncertainty	
12	5.1	Return Loss	
2	5.2	Dimension Measurement	5
1	5.3	Validation Measurement_	5
6	Cal	libration Measurement Results	
16	5.1	Return Loss	6
6	5.2	Mechanical Dimensions	6
7	Val	lidation measurement	
7	7.1	Measurement Condition	7
7	7.2	Head Liquid Measurement	7
7	7.3	Measurement Result	- 8
8	Lis	t of Equipment8	

Serial# 12070016-SAR Issue Date Feb 12th 2012 Page 78 of 98 www.siemic.com



#### SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR. 158.7.11.5ATU.A

#### 1 INTRODUCTION

This document contains a summary of the requirements set forth by the IEEE 1528, OET 65 Bulletin C and CEI/IEC 62209 standards for reference dipoles used for SAR measurement system validations and the measurements that were performed to verify that the product complies with the fore mentioned standards.

#### 2 DEVICE UNDER TEST

Device Under Test				
Device Type	COMOSAR 1900 MHz REFERENCE DIPOLE			
Manufacturer	Satimo			
Model	SID1900			
Serial Number	SN 18/11 DIPG153			
Product Condition (new / used)	new			

A yearly calibration interval is recommended.

#### 3 PRODUCT DESCRIPTION

#### 3.1 GENERAL INFORMATION

Satimo's COMOSAR Validation Dipoles are built in accordance to the IEEE 1528, OET 65 Bulletin C and CEI/IEC 62209 standards. The product is designed for use with the COMOSAR test bench only.



Figure 1 - Satimo COMOSAR Validation Dipole



#### SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref; ACR, 158.7,11.SATU,A

#### 4 MEASUREMENT METHOD

The IEEE 1528, OET 65 Bulletin C and CEI/IEC 62209 standards provide requirements for reference dipoles used for system validation measurements. The following measurements were performed to verify that the product complies with the fore mentioned standards.

Serial#

12070016-SAR

Issue Date Feb 12th 2012

#### 4.1 RETURN LOSS REQUIREMENTS

The dipole used for SAR system validation measurements and checks must have a return loss of -20 dB or better. The return loss measurement shall be performed against a liquid filled flat phantom, with the phantom constucted as outlined in the fore mentioned standards.

#### 4.2 MECHANICAL REQUIREMENTS

The IEEE Std. 1528 and CEI/IEC 62209 standards specify the mechanical components and dimensions of the validation dipoles, with the dimensions frequency and phantom shell thickness dependent. The COMOSAR test bench employs a 2 mm phantom shell thickness therefore the dipoles sold for use with the COMOSAR test bench comply with the requirements set forth for a 2 mm phantom shell thickness.

#### 5 MEASUREMENT UNCERTAINTY

All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

#### 5.1 RETURN LOSS

The following uncertainties apply to the return loss measurement:

Frequency band	Expanded Uncertainty on Return Los		
400-6000MHz	0.1 dB		

#### 5.2 DIMENSION MEASUREMENT

The following uncertainties apply to the dimension measurements:

Length (mm)	Expanded Uncertainty on Length		
3 - 300	0.05 mm		

#### 5.3 VALIDATION MEASUREMENT

The guidelines outlined in the IEEE 1528, OET 65 Bulletin C, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty for validation measurements.

Scan Volume	Expanded Uncertainty
1 g	16.19 %
10 g	15.86 %

Page: 5/9

Serial# 12070016-SAR Issue Date Feb 12th 2012 Page 80 of 98 www.siemic.com




#### SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR. 158,7,11.SATU,A

#### 6 CALIBRATION MEASUREMENT RESULTS

#### 6.1 RETURN LOSS



Frequency (MHz)	Return Loss (dB)	Requirement (dB)	
1900	-25.9	-20	

#### 6.2 MECHANICAL DIMENSIONS

Frequency MHz	Ln	nm-	h m	no	dr	nor
	required	measured	required	measured	required	measured
300	420.0 ±1 %.		250.0 ±1.%.		6,35 ±1 %.	
450	290:0 ±1 %.		166.7 ±1.%		5.35 ±1 %.	
750	176.0 ±1.%.		100.0 ±1.76.		5,35 ±1 %.	
835	161.0 ±1 %.		89.8 ±1 %.		3.6 ±1%.	
900	149.0 ±1 %.		83.3 ±1 %.		3.6 ±1%	
1450	89.1 ±1%.		51.7 ±1 %.		3.6 ±1 %.	
1500	80.5 ±1 %.		S0.0 ±1 %.		3.6 ±1%.	
1640	79.0 ±1 %.		45.7±1%.		3.6 ±1 %.	
1750	75.2 ±1 %.		42.9 ±1 %.		3.6 ±1 %.	
1800	72.0±1%.		41.7±1%.		3.6 ±1%.	
1900	68.0 ±1 %.	PASS.	39.5 ±1 %.	PASS	3.6 ±1 %.	PASS
1950	66.3 ±1.%.		38.5±1%.		3.6 ±1 %.	
2000	64.5 ±1 %.		37.5 ±1.%.		3.6 ±1%.	
2100	61.0 ±1%.		35.7.±1%.		3.6 ±1 %.	
2300	55.9 ±1 %.		32.6 ±1 %.		3.6 ±1 %.	
2450	51.5 ±1 %.	-	30.4±1.%.		3.6 ±1%.	
2600	48.5 ±1 %.		28.8 ±1 %.		3.6 ±1 %.	
3000	41.5±1%.		25.0 ±1 %.		3.6 ±1 %.	
3500	37.0±1 %.		26.4±1%.		3.6 ±1%.	
3700	34.7±1%.		26,4 ±1 %.		3.6 ±1 %.	

Page: 6/9



#### SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR. 158.7.1 LSATU.A.

#### 7 VALIDATION MEASUREMENT

The IEEE Std. 1528, OET 65 Bulletin C and CEI/IEC 62209 standards state that the system validation measurements must be performed using a reference dipole meeting the fore mentioned return loss and mechanical dimension requirements. The validation measurement must be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. Per the standards, the dipole shall be positioned below the bottom of the phantom, with the dipole length centered and parallel to the longest dimension of the flat phantom, with the top surface of the dipole at the described distance from the bottom surface of the phantom.

Issue Date Feb 12th 2012

#### 7.1 MEASUREMENT CONDITION

Software	OPENSAR V4
Phantom	SN 20/09 SAM7.1
Probe	SN 18/11 EPG122
Liquid	Head Liquid Values: eps' : 38:5 sigma #1.42
Distance between dipole center and liquid	10,0 mm
A rea scan resolution	dx=8mm/dy=8mm
Zoon Scan Resolution	dx=8mm/dy=8m/dz=5mm
Frequency	1900 MHz
Input power	20 dBm
Liquid Temperature	21 °C
Lab Temperature	21.°C
Lab Humidity	45 %

#### 7.2 HEAD LIQUID MEASUREMENT

Frequency MHz	Relative per	mittivity (ɛ,')	Conductiv	ity (a) 5/m
	required	measured	required	measured
300	45.3 ±5 %		0.87 ±5 %	
450	43.5±5%	-	0.87 ±5 %	
750	41,9 ±5 %		0.89 ±5 %	
835	41.5±5%		0:90±5 %	
900	41.5±5%	-	0.97 ±5 %	
1450	40.5 ±5 %		1,20 ±5 %	
1500	40,4 ±5 %		1,23 ±5 %	
1640	40.2 ±5 %		1.31 ±5 %	
1750	40.1 ±5 %		1,37 ±5 %	
1800	40.0±5%		1.40 ±5 %	
1900	40,0±5 %	PASS	1.40 ±5 %	PASS
1950	40.0 ±5 %		1.40 ±5 %	
2000	40.0 ±5 %	-	1.40.25 %	
2100	39.8±5 %		1.49 ±5 %	
2300	39.5 ±5 %		1.67 ±5 %	
2450	39.2 ±5 %	-	1.80 ±5 %	
2600	39.0±5%		1,96 ±5 %	
3000	38.5 ±5 %		2.40 ±5 %	
3500	37,9±5 %	+	2.91 ±5 %	

Page: 7/9




#### SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR, 158.7.1 LSATULA

#### 7.3 MEASUREMENT RESULT

The IEEE Std. 1528 and CEI/IEC 62209 standards state that the system validation measurements should produce the SAR values shown below (for phantom thickness of 2 mm), within the uncertainty for the system validation. All SAR values are normalized to 1 W forward power. In bracket, the measured SAR is given with the used input power.

Frequency	1 g SAR	(W/kg/W)	10 g SAR	(W/kg/W)
	required	measured	required	measured
300	2.85	-	1.94	
450	4,58	1	3.06	
750	8.49		5.55	
835	9.56		6.22	
900	10.9		6.99	
1450	29		16	
1500	30.5		16.8	
1640	34.2		18.4	
1750	36.4		19.3	
1800	38.4		20.1	
1900	39.7	39.92 (3.99)	20.5	20.49 (2.05
1950	40.5		20.9	
2000	41.1		21.1	
2100	43.6		21.9	
2300	48.7		23.3	
2450	52.4		24	
2600	55.3	j.	24.6	
3000	63.8		25.7	
3500	67.1		25	



Page: 8/9

Serial# 12070016-SAR Issue Date Feb 12th 2012 Page 83 of 98 www.siemic.com



#### SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR. 158,7.1 LSATU, A

## 8 LIST OF EQUIPMENT

	Equipment Summary Sheet			
Equipment Description	Manufacturer / Model	Identification No.	Current Calibration Date	Next Calibration Date
Flat Phantom	Satimo	SN-20/09-SAM71	Validated. No cal required.	Validated. No ca required.
COMOSAR Test Bench	Version 3	NA	Validated. No cal required.	Validated. No ca required.
Network Analyzer	Rhode & Schwarz ZVA	SN100132	02/2010	02/2013
Calipers	Carrera	CALIPER-01	12/2010	12/2013
Reference Probe	Satimo	EPG122 SN 18/11	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Multimeter	Keithley 2000	1188656	11/2010	11/2013
Signal Generator	Agilent E4438C	MY49070581	12/2010	12/2013
Amplifier	Aethercomm	SN 046	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Power Meter	HP E4418A	US38261498	11/2010	11/2013
Power Sensor	HP ECP-E26A	US37181460	11/2010	11/2013
Directional Coupler	Narda 4216-20	01386	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Temperature and Humidity Sensor	Control Company	11-661-9	3/2010	3/2012

Serial# 12070016-SAR Issue Date Feb 12th 2012 Page 84 of 98 www.siemic.cor



# SAR Reference Dipole Calibration Report

Ref: ACR.158.9.11.SATU.A

# SIEMIC TESTING AND CERTIFICATION SERVICES

SUITE 311, BUILDING 1, SECTION 30 ,NO.2 KEFA ROAD, SCIENCE AND TECHNOLOGY PARK
NAN SHAN DISTRICT, SHENZHEN 518057, GUANGDONG ,P.R.C.

# SATIMO COMOSAR REFERENCE DIPOLE

Calibrated at SATIMO US 2105 Barrett Park Dr. - Kennesaw, GA 30144



#### 06/01/2011

#### Summary:

This document presents the method and results from an accredited SAR reference dipole calibration performed in SATIMO USA using the COMOSAR test bench. All calibration results are traceable to national metrology institutions.

Serial# 12070016-SAR Issue Date Feb 12th 2012 Page 85 of 98 www.siemic.com



#### SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR. 158.9.11. SATU.A.

	Name	Function	Date	Signature
Prepared by:	Jérôme LUC	Product Manager	6/7/2011	Jes
Checked by:	Jérôme LUC	Product Manager	6/7/2011	25
Approved by:	Kim RUTKOWSKI	Quality Manager	6/7/2011	Min. Puthoust

	Customer Name
Distribution :	SIEMIC Testing and Certification Services

Issue	Date	Modifications
A	6/7/2011	Initial release

Serial# 12070016-SAR Issue Date Feb 12th 2012 Page 86 of 98 www.siemic.com



#### SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR. 158.9.1 LSATULA

#### TABLE OF CONTENTS

1	Inte	oduction4	
2	Des	vice Under Test4	
3	Pro	duct Description4	
	3.1	General Information	
4	Me	asurement Method5	
	4.1	Return Loss Requirements	5
	4.2	Mechanical Requirements	5
5	Me	asurement Uncertainty5	
	5.1	Return Loss	5
	5.2	Dimension Measurement	5
	5.3	Validation Measurement_	5
6	Cal	ibration Measurement Results6	
	6.1	Return Loss_	6
	6.2	Mechanical Dimensions	6
7	Val	idation measurement	
9	7.1	Measurement Condition	7
	7.2	Head Liquid Measurement	7
	7.3	Measurement Result	- 8
8	Lis	t of Equipment	

 Serial#
 12070016-SAR

 Issue Date
 Feb 12th 2012

 Page
 87 of 98

 www.siemic.com



#### SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR. 158.9.11, SATU.A.

#### 1 INTRODUCTION

This document contains a summary of the requirements set forth by the IEEE 1528, OET 65 Bulletin C and CEI/IEC 62209 standards for reference dipoles used for SAR measurement system validations and the measurements that were performed to verify that the product complies with the forementioned standards.

#### 2 DEVICE UNDER TEST

Device Under Test		
Device Type	COMOSAR 2450 MHz REFERENCE DIPOLE	
Manufacturer	Satimo	
Model	SID2450	
Serial Number	SN 18/11 DIPJ155	
Product Condition (new / used)	new	

A yearly calibration interval is recommended.

#### 3 PRODUCT DESCRIPTION

#### 3.1 GENERAL INFORMATION

Satimo's COMOSAR Validation Dipoles are built in accordance to the IEEE 1528, OET 65 Bulletin C and CEI/IEC 62209 standards. The product is designed for use with the COMOSAR test bench only.



Figure 1 - Satimo COMOSAR Validation Dipole



Ref: ACR, 158.9.11, SATU.A.

#### 4 MEASUREMENT METHOD

OMITAE

The IEEE 1528, OET 65 Bulletin C and CEI/IEC 62209 standards provide requirements for reference dipoles used for system validation measurements. The following measurements were performed to verify that the product complies with the fore mentioned standards.

Serial#

Page

12070016-SAR

Issue Date Feb 12th 2012 88 of 98

#### 4.1 RETURN LOSS REQUIREMENTS

The dipole used for SAR system validation measurements and checks must have a return loss of -20 dB or better. The return loss measurement shall be performed against a liquid filled flat phantom, with the phantom constucted as outlined in the fore mentioned standards.

#### 4.2 MECHANICAL REQUIREMENTS

The IEEE Std. 1528 and CEI/IEC 62209 standards specify the mechanical components and dimensions of the validation dipoles, with the dimensions frequency and phantom shell thickness dependent. The COMOSAR test bench employs a 2 mm phantom shell thickness therefore the dipoles sold for use with the COMOSAR test bench comply with the requirements set forth for a 2 mm phantom shell thickness.

#### MEASUREMENT UNCERTAINTY 5

All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

#### 5.1 RETURN LOSS

The following uncertainties apply to the return loss measurement:

Frequency band	Expanded Uncertainty on Return Loss
400-6000MHz	0.1 dB

#### 5.2 DIMENSION MEASUREMENT

The following uncertainties apply to the dimension measurements:

Expanded Uncertainty on Length
0.05 mm

#### 5.3 VALIDATION MEASUREMENT

The guidelines outlined in the IEEE 1528. OET 65 Bulletin C, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty for validation measurements.

Expanded Uncertainty
16.19 %
15.86 %

Page: 5/9

Serial# 12070016-SAR Issue Date Feb 12th 2012 Page 89 of 98 www.siemic.com




#### SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR. 158.9.11.SATU.A

#### 6. CALIBRATION MEASUREMENT RESULTS

#### 6.1 RETURN LOSS



Frequency (MHz)	Return Loss (dB)	Requirement (dB)
2450	-32.00	-20

#### 6.2 MECHANICAL DIMENSIONS

Frequency MHz	Lmm		h roza		d mm	
	required	measured	required	measured	required	measured
300	-420.0±1 %.		250.0 ±1 %.		6.35 ±1 %.	
450.	290.0 ±1 %.		166.7 ±1 %.		6.35 ±1%.	
750	176:0 ±1 %.		100:0 ±1 %.		5.35 ±1.%.	
835	161.0±1%.		89.8 ±1.%.		3.6 ±1 %.	
900	149.0 ±1 %.		83.3 ±1.%		3.6 ±1%.	
1450	89.1 ±1 %.		51.7±1 %.		3.5 ±1 %	
1500	80.5 ±1 %.		50.0 ±1.%.		3.5±1%.	
1640	79.0 ±1 %.		45.7±1:%		3.6 ±1 %.	
1750	75,2 ±1 %.		42.9 ±1.%		3.6±1%.	
1800	72.0 ±1 %.		41.7±1%		3.5 ±1 %.	
1900	68.0 ±1 %.	7	39.5 ±1 %.		3.6 ±1%.	
1950	66.3 ±1 %.		38.5 ±1.%.		3.6±1%.	
2000	64.5 ±1%.		37.5 ±1 %.		3.6 ±1 %.	
2100	61.0 ±1 %.		35.7±1%.		3.6 ±1%.	
2300	S5.5 ±1 %.		32.6 £1.%.		3.6±1%.	
2450	51.5 ±1%.	PASS	30.4±1 %.	PASS	3.6 ±1 %.	PASS
2600	48.5 ±1 %.		28.8 ±1 %.		3.6 ±1%.	
3000	41.5 ±1%.		25.0 ±1.%.	1	3.6 ±1 %.	
3500	37.0±1 %		26.4 ±1 %.		3.6 ±1 %.	
3700	34.7±1 %.		26.4 ±1.%.		3.6 ±1 %.	

Page: 6/9

Serial# 12070016-SAR Issue Date Feb 12th 2012 Page 90 of 98 www.siemic.com



#### SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref, ACR. 158,9,11.SATU,A

#### 7 VALIDATION MEASUREMENT

The IEEE Std. 1528, OET 65 Bulletin C and CEI/IEC 62209 standards state that the system validation measurements must be performed using a reference dipole meeting the fore mentioned return loss and mechanical dimension requirements. The validation measurement must be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. Per the standards, the dipole shall be positioned below the bottom of the phantom, with the dipole length centered and parallel to the longest dimension of the flat phantom, with the top surface of the dipole at the described distance from the bottom surface of the phantom.

#### 7.1 MEASUREMENT CONDITION

OPENSAR V4		
SN 20/09 SAM71		
SN 18/11 EPG122		
Head Liquid Values: eps' : 38.8 sigma : 1.88		
10.0 mm		
dx=8mm/dy=8mm		
dx=8mm/dy=8m/dz=5mm		
2450 MHz		
20 dBm		
21 °C		
21 °C		
45 %		

### 7.2 HEAD LIQUID MEASUREMENT

Frequency	Relative permittivity ( $\epsilon_{\rm c}'$ )		Conductivity (a) S/m	
	required	measured	required	measured
300	45.3 ±5 %		0.87 ±5 %	
450	43.5 ±5 %		0.87 ±5 %	
750	41.9±5%		0.89 ±5 %	
835	41.5 ±5 %		0.90±5%	
900	41.5 ±5%		0.97 ±5 %	
1450	40.5 ±5 %		1.20±5 %	
1500	40.4 ±5 %		1,23 ±5 %	
1640	40.2 ±5 %		1.31±5%	
1750	40.1 15 %		1.37 ±5 %	
1800	40.0 ±5 %		1.40 ±5 %	
1900	40.0 ±5 %		1.40 ±5 %	
1950	40.0±5%		1.40 ±5 %	
2000	40.0±5%		1.40 ±5 %	
2100	39.8 ±5 %		1.49 ±5 %	
2300	39,5 ±5 %		1.67 ±5 %	
2450	39.2 ±5%	PASS	1.60 ±5 %	PASS
2600	39.0 ±5 %		1.96±5%	
3000	38,5 ±5 %		2.40 ±5 %	
3500	37.9 ±5 %		2,91±5%	

Page: 7/9




#### SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR. 158.9.11. SATU, A

#### 7.3 MEASUREMENT RESULT

The IEEE Std. 1528 and CEI/IEC 62209 standards state that the system validation measurements should produce the SAR values shown below (for phantom thickness of 2 mm), within the uncertainty for the system validation. All SAR values are normalized to 1 W forward power. In bracket, the measured SAR is given with the used input power.

Frequency MHz	1 g SAR (W/kg/W)		10 g SAR (W/kg/W)	
	required	measured	required	measured
300	2.85		1,94	
450	4.58		3.06	
750	8.49		5.55	
835	9.56		6.22	
900	10.9		6,99	
1,450	29		16	
1500	30,5		16.8	
1640	34.2		18.4	
1750	36,4		19.3	
1800	38.4		20.1	
1900	39.7		20.5	
1950	40.5		20.9	
2000	41.1		21.1	
2100	43.6		21.9	
2300	48.7		23,3	
2450	52.4	53.82 (5,38)	24	24.12 (2.41
2600	55.3		24.6	
3000	63.8		25.7	
3500	57,1		25.	



Page: 8/9

Serial# 12070016-SAR Issue Date Feb 12th 2012 Page 92 of 98 www.siemic.com



#### SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref; ACR. 158,9,11.SATU,A

## 8 LIST OF EQUIPMENT

Equipment Summary Sheet					
Equipment Description	Manufacturer / Model	Identification No.	Current Calibration Date	Next Calibration Date	
Flat Phantom	Satimo	SN-20/09-SAM71	Validated. No cal required.	Validated. No ca required.	
COMOSAR Test Bench	Version 3	NA	Validated. No cal required.	Validated. No ca required.	
Network Analyzer	Rhode & Schwarz ZVA	SN100132	02/2010	02/2013	
Calipers	Carrera	CALIPER-01	12/2010	12/2013	
Reference Probe	Satimo	EPG122 SN 18/11	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.	
Multimeter	Keithley 2000	1188656	11/2010	11/2013	
Signal Generator	Agilent E4438C	MY49070581	12/2010	12/2013	
Amplifier	Aethercomm	SN 046	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.	
Power Meter	HP E4418A	US38261498	11/2010	11/2013	
Power Sensor	HP ECP-E26A	US37181460	11/2010	11/2013	
Directional Coupler	Narda 4216-20	01386	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.	
Temperature and Humidity Sensor	Control Company	11-661-9	3/2010	3/2012	

# Annex C SAR System PHOTOGRAPHS




Liquid depth ≥ 15cm



# Annex D SETUP PHOTOGRAPHS

## Right Head Touch View




Right Head Tilt View




Serial# 12070016-SAR Issue Date Feb 12th 2012 Page 95 of 98 www.siemic.com


## **Left Head Touch View**



Left Head Tilt View



# Body Setup Photo (LCD UP)



Body Setup Photo (LCD DOWN)



## Annex E EUT PHOTO

## **EUT-Front Side View**



**EUT-Back Side View** 



## **EUT-Battery Uncover View**



## **EUT-Top Side View**

