

SPECIFICATION



深圳市大显科技有限公司

Shenzhen Daxian Technology Co., Ltd.

通力 Bar300 WIFI 1 天线组件

Tonly Bar300 WIFI 1 Antenna assembly

产品规格书

Product Specification

客户 connection	通力 Tonly	频段 frequency range	2400 ~ 2500MHz、5150~5850MHz
项目名称 entry name	Bar300	版本 edition	V1.2
物料编号 Material No	1B-ar500-068	颜色 Color	黑色+白色 Black+White
客户料号 Customer Item Number	290000-019573		
环保要求 environmental requirement	<input checked="" type="checkbox"/> RoHS <input checked="" type="checkbox"/> REACH <input checked="" type="checkbox"/> HF		
R F 设计 R F Design	沈川 Chuan.Shen	结构设计 Structural Design	周锐斌 Rui Bin.Zhou
品质经理 Quality Manager	杨进 Jin.Yang	技术总监 Technical Director	张磊 Lei.Zhang
日期 Date	2024-10-14		



客户确认:

Customer confirmation:

装配是否符合贵司要求: OK NG

Whether the assembly meets your company's requirements: OK NG

深圳市大显科技有限公司

Shenzhen Daxian Technology Co., Ltd.

深圳市龙岗区布吉镇吉华路 513 号上水径村(国防培训基地
对面) 达成工业园综合楼 7 楼

TEL: 0755-28576002

FAX: 0755-84276383

Buji Town, Longgang District, Shenzhen, China Jihua Road 513,
Shangshuijing Village (opposite the national defense
training base) Dacheng Industrial Park, Building 7.

TEL: 0755-28576002

FAX: 0755-84276383

上海分部: 上海市张江高科技园区集成电路产业区龙东大道
3000 号 8 号楼 201 室

TEL: 021-61630552

FAX: 755-84276383

Room201, Building8, LongDongRoad3000#, Semiconductor Industry
Park, ZhangJiang Hitech Zone, Shanghai

TEL: 021-61630552

FAX: 755-84276383

索引 Indexes

一、项目说明 Project Description.....	4
二、 WIFI 1 天线 antenna.....	4
1、 规格 specifications.....	4
1.1 电气规格标准 Electrical specifications and standards.....	5
1.1.1 电性能指标 Electrical performance index.....	5
1.1.2 天线位置图片 Antenna position picture.....	5
1.2 结构规格标准 Structural specifications and standards.....	5
1.2.1 天线组成 Antenna composition..	5
2、 测试环境 testing environment.....	6
3、 测试 test.	7
3.1 驻波(VSWR)的测试 Test of standing wave (VSWR).....	7
3.1.1 测试连接 Test connection.....	7
3.2 效率、功率 (TRP)、灵敏度 (TIS) 的测试 Testing of efficiency, power (TRP), sensitivity (TIS).....	7
3.2.1 测试的场地 Test site.....	7
3.2.2 测试的仪表 Tested Instruments.....	7
3.2.3 测试数据 test data.....	7-8
4、 VSWR 参数图 Parameter diagram.....	8
5、 无源场型图 Passive field pattern diagram.....	9-10
6、 天线测试结果：整机数据–隔离度 Antenna Test Results: Whole Unit Data - Isolation	11
7、 拉距测试 Pull distance test:.....	12
8、 天线装机注意事项： Antenna mounting notes:.....	13
9、 结论 conclusion.....	13
三、 工程图 schedule drawing.....	14

www.Topant.com.cn
Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

一 项目说明 Project Description


客户名: Customer Name:	通力 Tonly
整机类型: Type of complete machine:	音箱 loudspeaker box
天线频段: Antenna band:	2400 ~ 2500MHz、5150~5850MHz
天线形式: Antenna form:	FPC+同轴线+EVA FPC+coaxial line+EVA
馈电形式: Feed form:	焊接 weld
硬件版本: Hardware version:	/

二 WIFI 1 天线组件 Antenna assembly

1 规格 specifications

本报告主要提供 **Bar300** 项目天线的各项电气和结构性能参数的测试状况。下图为大显设计的天线图片。

This report mainly provides the testing status of various electrical and structural performance parameters of the antenna for the **Bar300** project. The following image shows an antenna with a large display design.



天线外观图

antenna appearing diagram

www.Topant.com.cn
Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

1.1 电气规格标准 Electrical specifications and standards

1.1.1 电性能指标 Electrical performance index

天线工作频段在 2400 ~ 2500 MHz、5150~5850MHz。 下表是大显设计和量产天线的电性能指标。

The operating frequency band of the antenna is between 2400 and 2500 MHz、5150and 5850 MHz. The following table shows the electrical performance indicators of large display design and mass production antennas.

Frequency Range	Frequency (MHz)	VSWR
WIFI-1	2400 ~ 2500	≤ 2
WIFI-1	5150~5850	≤ 2

1.1.2 天线位置图片 Antenna position picture



WIFI 1

2 结构规格标准 Structural specifications and standards

1.2.1 天线组成 Antenna composition

天线主要是由 FPC+同轴线+EVA 组成。

The antenna is mainly composed of FPC+coaxial line+EVA.

www.Topant.com.cn
Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

2、测试设备 The Equipment of Active Test

Satimo 3D Chamber 6×4×4(m)

Agilent 8960 E5515c

Network analyzer-R&S ZVL



图 2

Figure 2

www.Topant.com.cn
Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

3 测试 test

3.1 驻波(VSWR)的测试 Test of standing wave (VSWR)

3.1.1 测试连接: VSWR 测试装置依次连接为: R&S ZVL 网络分析仪 → 测试线 → 测试治

Test connection: The VSWR test device is sequentially connected as follows: R&S ZVL network analyzer → test line → test fixture

实测(附图)Actual measurement (attached drawing)

3.2 增益及效率、功率 (TRP)、灵敏度 (TIS) 的测试

Gain and efficiency, power (TRP), sensitivity (TIS) testing

3.2.1 测试的场地 Test site:

大显微波暗室。测试频率范围为 400MHz—6GHz, 静区范围为 50cm 圆周, 反射率小于-50 dB。

Large display microwave anechoic chamber. The test frequency range is 400MHz - 6GHz, the static zone range is 50cm circumferential, and the reflectivity is less than - 50dB.

3.2.2 测试的仪表 Tested Instruments:

R&S ZVL 网络分析仪、Agilent8960 E5515C、标准喇叭天线、法国 SATIMO-SG24SYSTEM 系统、打印机等。

R&S ZVL network analyzer, Agilent 8960 E5515C, standard horn antenna, French SATIMO-SG24SYSTEM system, printer, etc.

3.2.3 测试数据 : 在微波暗室中, 测试的功率和灵敏度相关的数值如下表

Test data: In a microwave anechoic chamber, the values related to the power and sensitivity tested are shown in the table bel

无源效率&增益 Passive efficiency&gain:

WIFI-1 天线:


Freq (MHz)	Effi (%)	Effi (dB)	Gain (dBi)
2400	48.97	-3.10	1.59
2450	49.19	-3.08	1.64
2500	48.76	-3.12	1.45
5150	45.87	-3.38	2.39
5350	46.22	-3.35	2.45
5500	46.65	-3.34	2.62
5650	46.32	-3.31	2.37
5750	45.81	-3.39	2.48
5850	45.56	-3.41	2.57

www.Topant.com.cn
Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

4、VSWR 参数图 VSWR parameter diagram


WIFI-1 天线:



www.Topant.com.cn
Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd







5、无源场型图 Passive Field Pattern Diagram--- WiFi-1 天线: 2450MHz:



www.Topant.com.cn
Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd


5500MHz:




www.Topant.com.cn
Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

6、天线测试结果：整机数据--隔离度 Antenna Test Results: Whole Unit Data - Isolation WIFI1--BT




WIFI0-WIFI1



www.Topant.com.cn
Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

7、拉距测试 Pull distance test



测试时间 Testing time: 2024/10/08

测试场地 Test site: 深圳鹤洲劲拓股份公司附近

Near Shenzhen Hezhou Jintuo Co.

测试手机 Test Cell Phones: Iphone 14 Pro

测试路由器 Test Router: 华硕-RT-AC86UA SUS-RT-AC86U

后 empress



左 Left

右 Right

前 ahead

测试方向 Test direction	前 ahead	后 empress	左 Left	右 Right
	测试距离 Test Distance			
BT	100M	100M	100M	100M
WIFI 2.4G	200M	200M	200M	200M
WIFI 5.8G	255M	255M	255M	255M


www.Topant.com.cn

Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

8、天线装机注意事项 Antenna mounting precautions

WiFi1 出线方式如下，先安装 WiFi1 天线使用胶带固定同轴线置于最底层
WiFi1 out as follows, first install the WiFi1 antenna using tape to fix the coaxial cable on the bottom layer



9、结论 conclusion

此天线是在客户提供样机基础上设计，电参数和结构性能已达到技术要求，请确认！



This antenna is designed based on the prototype provided by the customer. The electrical parameters and structural performance have met the technical requirements, please confirm!

www.Topant.com.cn
Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

第三视角		比例 1:1		2		3		4		5		6					
单位	mm	0~10	10~30	30~50	50~	角度	◎	⊥	∠	0.05	0.10	0.15	0.20	0.02	0.02	0.03	0.05

Dot UV glue (点UV胶水)



注:
 1. "*"为重点尺寸;
 2. 未标注尺寸请依图纸;
 3. 不可有虚焊、漏焊、短线、断线等操作不良;
 4. 符合 RoHS 要求.

C	线材海绵	PU海绵	T=1.5mm	黑色
B	端子线	Cable线		白色
A	FPC(带补强)	电解铜 PI		黑色
序号	零件名称	材质		颜色

深圳大显科技有限公司
 Shenzhen Daxian Technology Co., Ltd.

机型	Bar500	产品颜色	黑色	日期	2024/09/04
项目编码	BB-ar500-068	模面处理		结构设计	周锐斌
零件名称	Bar-WIFI1天线			射频设计	沈川
零件编码	1B-ar500-068			审核	周康
材质	FPC+线材海绵+同轴线			批准	张磊
保存路径					当前版本

版本	A	首次绘制	日期	备注
描述				