

## FCC AND IC CERTIFICATION TEST REPORT

### FOR

<b>Applicant</b>	:	Harman International Industries, Incorporated
<b>Address</b>	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES
<b>Equipment under Test</b>	:	2.0 Soundbar with Bluetooth
<b>Model No.</b>	:	BAR STUDIO
<b>Trade Mark</b>	:	JBL
<b>FCC ID</b>	:	APIBARSTUDIO
<b>IC</b>	:	6132A-BARSTUDIO
<b>Manufacturer</b>	:	Harman International Industries, Incorporated
<b>Address</b>	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES

**Issued By: Dongguan Dongdian Testing Service Co., Ltd.**

**Add:** No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City,  
Guangdong Province, China, 523808

**Tel:** +86-0769-89201699 [Http://www.dgddt.com](http://www.dgddt.com)

## TABLE OF CONTENTS

	Test report declares.....	4
1.	Summary of test results .....	5
2.	General test information.....	6
2.1.	Description of EUT .....	6
2.2.	Accessories of EUT.....	6
2.3.	Assistant equipment used for test.....	6
2.4.	Block diagram of EUT configuration for test.....	6
2.5.	Test environment conditions .....	7
2.6.	Deviations of test standard .....	7
2.7.	Test laboratory.....	7
2.8.	Measurement uncertainty .....	7
3.	Equipment used during test .....	8
4.	6dB Bandwidth and 99% Bandwidth .....	9
4.1.	Block diagram of test setup .....	9
4.2.	Limits.....	9
4.3.	Test Procedure.....	9
4.4.	Test Result.....	9
4.5.	Original test data .....	10
5.	Maximum Peak Output Power .....	11
5.1.	Block diagram of test setup .....	11
5.2.	Limits.....	11
5.3.	Test Procedure.....	11
5.4.	Test Result.....	11
5.5.	Original test data .....	11
6.	Power Spectral Density .....	13
6.1.	Block diagram of test setup .....	13
6.2.	Limits.....	13
6.3.	Test Procedure.....	13
6.4.	Test Result.....	13
6.5.	Original test data .....	14
7.	Emissions in non-restricted frequency bands .....	15
7.1.	Block diagram of test setup .....	15
7.2.	Limits.....	15
7.3.	Test Procedure.....	15
7.4.	Test Result.....	16

7.5.	Original test data .....	16
8.	Emissions in restricted frequency bands .....	17
8.1.	Block diagram of test setup .....	17
8.2.	Limit .....	18
8.3.	Test Procedure.....	19
8.4.	Test result .....	20
9.	RF Conducted Spurious Emissions .....	24
9.1.	Block diagram of test setup .....	24
9.2.	Limits.....	24
9.3.	Test Procedure.....	24
9.4.	Test Result.....	25
9.5.	Original test data .....	25
10.	Band Edge Compliance.....	31
10.1.	Block diagram of test setup .....	31
10.2.	Limit .....	31
10.3.	Test Procedure.....	31
10.4.	Test result .....	31
11.	Power Line Conducted Emission .....	36
11.1.	Block diagram of test setup .....	36
11.2.	Power Line Conducted Emission Limits .....	36
11.3.	Test Procedure.....	36
11.4.	Test Result.....	37
12.	Antenna Requirements .....	40
12.1.	Limit .....	40
12.2.	Result.....	40
13.	Test setup photograph .....	41
14.	Photos of the EUT .....	43

## TEST REPORT DECLARE

<b>Applicant</b>	:	Harman International Industries, Incorporated
<b>Address</b>	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES
<b>Equipment under Test</b>	:	2.0 Soundbar with Bluetooth
<b>Model No.</b>	:	BAR STUDIO
<b>Trade mark</b>	:	JBL
<b>Manufacturer</b>	:	Harman International Industries, Incorporated
<b>Address</b>	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES

**Test Standard Used:**

FCC Rules and Regulations Part 15 Subpart C, RSS-247 Issue 2 February 2017.

**Test procedure used:**

ANSI C63.10:2013, RSS-Gen Issue 4, Nov. 2014, KDB558074 D01 DTS Meas Guidance V04

**We Declare:**

The equipment described above is tested by Dongguan Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Dongguan Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

**After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above FCC&IC standards.**

<b>Report No:</b>	DDT-R17Q0705-9E3		
<b>Date of Receipt:</b>	Jul. 5, 2017	<b>Date of Test:</b>	Jul. 5, 2017 ~ Jul. 18, 2017

*Prepared By:*

*Damon Hu*

**Damon Hu/Engineer**

*Approved By:*



**Kevin Feng/EMC Manager**

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

## 1. Summary of test results

The EUT have been tested according to the applicable standards as referenced below.		
Description of Test Item	Standard	Results
6dB Bandwidth and 99% Bandwidth	FCC Part 15: 15.247 ANSI C63.10:2013 RSS-247 Issue 2 KDB558074	PASS
Peak Output Power	FCC Part 15: 15.247 ANSI C63.10:2013 RSS-247 Issue 2 KDB558074	PASS
Power Spectral Density	FCC Part 15:15.247 ANSI C63.10:2013 RSS-247 Issue 2 KDB558074	PASS
Emissions in non-restricted frequency bands	FCC Part 15: 15.247 ANSI C63.10:2013 RSS-247 Issue 2 RSS-Gen Issue 4 KDB558074	PASS
Transmitter spurious emission	FCC Part 15: 15.209 FCC Part 15: 15.247 ANSI C63.10: 2013 RSS-247 Issue 2 RSS-Gen Issue 4 KDB558074	PASS
Band Edge Compliance	FCC Part 15: 15.209 FCC Part 15: 15.247 ANSI C63.10: 2013 RSS-247 Issue 2 RSS-Gen Issue 4 KDB558074	PASS
Power Line Conducted Emission	FCC Part 15: 15.207 ANSI C63.10: 2013 RSS-Gen Issue 4	PASS
Antenna requirement	FCC Part 15: 15.203 RSS-Gen Issue 4	PASS

## 2. General test information

### 2.1. Description of EUT

EUT* Name	: 2.0 Soundbar with Bluetooth
Model Number	: BAR STUDIO
EUT function description	: Please reference user manual of this device
Power supply	: DC 19V from adapter AC 120V/60Hz
Radio Specification	: Bluetooth V4.2 (BLE)
Operation frequency	: 2402MHz -2480MHz
Modulation	: GFSK,
Data rate	: 1Mbps
Antenna Type	: Integrated antenna, maximum PK gain: 3.40dBi
Sample Type	: Series production

Note 1: EUT is the ab. of equipment under test.

Note 2: This report only for Bluetooth LE mode of EUT, for Bluetooth BDR and EDR mode was reported in another test report.

Note 3: AC mains: AC 120V/60Hz, AC 240V/50Hz.

After the preliminary scan, AC 120V/60Hz power supply will have highest emission, was selected and recorded in this report.

### 2.2. Accessories of EUT

Description of Accessories	Manufacturer	Model number	Serial No.	Other
Aux in cable	JBL	N/A	N/A	Length: 1.2m without core
Optical cable	JBL	N/A	N/A	Length: 1.2m without core
AC cable	JBL	N/A	N/A	Length: 1.5m without core
AC Adapter	Harman/Kardon	NSA40ED-190200	N/A	Input: 100-240V, 1.0A Output: DC 19V, 2.0A DC cable: 1.2m without core

### 2.3. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Serial No.	Other
/	/	/	/	/

### 2.4. Block diagram of EUT configuration for test



Test software: FCC Test tools v1.06

The test software was used to control EUT work in Continuous TX mode, and select test channel, wireless mode as blow table.

Tested mode, channel, information		
Mode	Channel	Frequency (MHz)
GFSK	CH0	2402
	CH19	2440
	CH39	2480
Note: According exploratory test, EUT will have maximum output power in those data rate, so those data rate were used for all test.		

## 2.5. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	21-25°C
Humidity range:	40-75%
Pressure range:	86-106kPa

## 2.6. Deviations of test standard

No Deviation.

## 2.7. Test laboratory

Dongguan Dongdian Testing Service Co., Ltd

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808 Tel: +86-0769-89201699 <http://www.dgddt.com>

FCC Registration Number: 270092; Industry Canada site registration number: 10288A-1

CNAS Accreditation No. L6451; A2LA Accreditation No. 3870.01

## 2.8. Measurement uncertainty

Test Item	Uncertainty
Bandwidth	1.1%
Peak Output Power(Conducted)( Spectrum analyzer)	0.86dB(10 MHz ≤ f < 3.6GHz);
	1.38dB(3.6GHz ≤ f < 8GHz)
Peak Output Power(Conducted)(Power Sensor)	0.74dB
Power Spectral Density	0.74dB(10 MHz ≤ f < 3.6GHz);
	1.38dB(3.6GHz ≤ f < 8GHz)
Conducted spurious emissions	0.86dB(10 MHz ≤ f < 3.6GHz);
	1.40dB(3.6GHz ≤ f < 8GHz)
	1.66dB(8GHz ≤ f < 22GHz)
Uncertainty for radio frequency (RBW<20KHz)	3×10 <sup>-8</sup>


Temperature	0.4°C
Humidity	2%
Uncertainty for Radiation Emission test (30MHz-1GHz)	4.70 dB (Antenna Polarize: V)
	4.84 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1GHz-18GHz)	4.10dB(1-6GHz)
	4.40dB (6GHz-18Gz)
Uncertainty for Power line conduction emission test	3.32dB (150KHz-30MHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95%	

### 3. Equipment used during test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
<b>RF Connected Test</b>					
Spectrum analyzer	R&S	FSU26	1166.1660.26	Oct. 16, 2016	1Year
Vector Signal Generator	Agilent	E8267D	MY52098743	Oct. 20, 2016	1Year
Vector Signal Generator	Agilent	N5182A	MY48180737	Jul. 05, 2017	1Year
Power Sensor	Agilent	U2021XA	MY55150010	Apr. 18, 2017	1Year
Power Sensor	Agilent	U2021XA	MY55150011	Apr. 19, 2017	1Year
DC Power Source	MATRIS	MPS-3005L-3	D813058W	Oct. 24, 2016	1Year
Attenuator	Mini-Circuits	BW-S10W2	101109	Aug. 18, 2016	1Year
RF Cable	Micable	C10-01-01-1	100309	Aug. 18, 2016	1Year
Test Software	JS Tonscend	JS1120-2	Ver.2.5	N/A	N/A
USB Data acquisition	Agilent	U2531A	TW55043503	N/A	N/A
Auto control Unit	JS Tonscend	JS0806-2	158060010	N/A	N/A
<b>Radiated Emission Test</b>					
EMI Test Receiver	R&S	ESU8	100316	Oct. 16, 2016	1Year
Spectrum analyzer	R&S	FSU26	1166.1660.26	Oct. 16, 2016	1Year
Trilog Broadband Antenna	Schwarzbeck	VULB9163	9163-462	Oct. 27, 2016	1 Year
Active Loop antenna	Schwarzbeck	FMZB-1519	1519-038	Oct. 16, 2016	1 Year
Double Ridged Horn Antenna	R&S	HF907	100276	Oct. 12, 2016	1 Year
Pre-amplifier	A.H.	PAM-0118	360	Oct. 16, 2016	1 Year
RF Cable	HUBSER	CP-X2	W11.03	Oct. 16, 2016	1Year
RF Cable	HUBSER	CP-X1	W12.02	Oct. 16, 2016	1 Year
MI Cable	HUBSER	C10-01-01-1M	1091629	Oct. 16, 2016	1 Year
Test software	Audix	E3	V 6.11111b	/	/
<b>Power Line Conducted Emissions Test</b>					
Test Receiver	R&S	ESU8	100316	Oct. 16, 2016	1 Year
LISN 1	R&S	ENV216	101109	Oct. 16, 2016	1 Year
LISN 2	R&S	ESH2-Z5	100309	Oct. 16, 2016	1 Year
Pulse Limiter	R&S	ESH3-Z2	101242	Oct. 16, 2016	1 Year
CE Cable 1	HUBSER	ESU8/RF2	W10.01	Oct. 16, 2016	1 Year
Test software	Audix	E3	V 6.11111b	/	/

## 4. 6dB Bandwidth and 99% Bandwidth

### 4.1. Block diagram of test setup



### 4.2. Limits

For direct sequence systems, the minimum 6dB bandwidth shall be at least 500 KHz

### 4.3. Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Set the spectrum analyzer as follows:

RBW:	100KHz
VBW:	300KHz
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, measure the 6dB and 99% bandwidth of signal.

### 4.4. Test Result

Mode	Channel	6dB bandwidth Result (MHz)	99% bandwidth Result (MHz)	6 dB width Limit (MHz)	Conclusion
GFSK	CH0	0.516	0.956	>0.5	PASS
	CH19	0.516	0.956	>0.5	PASS
	CH39	0.520	0.956	>0.5	PASS



## 5. Maximum Peak Output Power

### 5.1. Block diagram of test setup

Same with 4.1

### 5.2. Limits

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### 5.3. Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Set the spectrum analyzer as follows:

RBW:	1MHz
VBW:	3MHz
Span	>1.5x 6dB bandwidth
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges measure out the PK output power.

### 5.4. Test Result

Mode	Freq (MHz)	Peak Output Power (dBm)	Limit (dBm)	Conclusion
GFSK	2402	0.100	30	PASS
	2440	1.990	30	PASS
	2480	2.240	30	PASS

### 5.5. Original test data

Graphs

<p>LCH</p>	<p>Ref 20 dBm -Att 30 dB -RBW 3 MHz -VBW 10 MHz -SWT 100 ms Marker 1 [T1] 0.10 dBm 2.401892000 GHz</p> <p>20 Offset 9.9 dB</p> <p>Center 2.402 GHz 400 kHz/ Span 4 MHz</p> <p>Date: 19.JUL.2017 13:47:39</p>
<p>MCH</p>	<p>Ref 20 dBm -Att 30 dB -RBW 3 MHz -VBW 10 MHz -SWT 100 ms Marker 1 [T1] 1.99 dBm 2.439740000 GHz</p> <p>20 Offset 10 dB</p> <p>Center 2.44 GHz 400 kHz/ Span 4 MHz</p> <p>Date: 19.JUL.2017 13:50:24</p>
<p>HCH</p>	<p>Ref 20 dBm -Att 30 dB -RBW 3 MHz -VBW 10 MHz -SWT 100 ms Marker 1 [T1] 2.24 dBm 2.479700000 GHz</p> <p>20 Offset 10.2 dB</p> <p>Center 2.48 GHz 400 kHz/ Span 4 MHz</p> <p>Date: 19.JUL.2017 13:53:02</p>

## 6. Power Spectral Density

### 6.1. Block diagram of test setup

Same with 4.1

### 6.2. Limits

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

### 6.3. Test Procedure


- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) Set the spectrum analyzer as follows:
 

Center frequency	DTS Channel center frequency
RBW:	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW:	$\geq 3\text{RBW}$
Span	1.5times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold
- (3) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.
- (4) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### 6.4. Test Result

EUT Set Mode	Channel	Result (dBm)
GFSK	CH0	-0.740
	CH19	1.090
	CH39	1.370
Limit: <8dBm/3KHz		Conclusion: PASS

### 6.5. Original test data



## 7. Emissions in non-restricted frequency bands

### 7.1. Block diagram of test setup

Same with 4.1

### 7.2. Limits

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

### 7.3. Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

Center frequency	DTS Channel center frequency
RBW:	100KHz
VBW:	300KHz
Span	1.5times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.

(4) Set the spectrum analyzer as follows:


RBW:	100KHz
VBW:	300KHz
Span	Encompass frequency range to be measured
Number of measurement points	$\geq \text{span}/\text{RBW}$
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band

7.4. Test Result

EUT Set Mode	CH or Frequency	Measured Range	Result (dBm)
GFSK	CH0	2.375GHz-2.405GHz	PASS
	CH39	2.476GHz-2.506GHz	PASS


7.5. Original test data




## 8. Emissions in restricted frequency bands

### 8.1. Block diagram of test setup


In 3m Anechoic Chamber Test Setup Diagram for 9KHz-30MHz



In 3m Anechoic Chamber Test Setup Diagram for 30MHz-1GHz



In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP.

## 8.2. Limit

### 8.2.1 FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	( <sup>2</sup> )

### 8.2.2 FCC 15.209 Limit.

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
0.009 ~ 0.490	300	2400/F(KHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(KHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0

Above 1000	3	74.0 dB( $\mu$ V)/m (Peak) 54.0 dB( $\mu$ V)/m (Average)
------------	---	---

Note: (1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9-90KHz, 110-490KHz and above 1000MHz. Radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3m}(\text{dBuV/m}) = \text{Limit}_{30m}(\text{dBuV/m}) + 40\text{Log}(30m/3m)$$

### 8.2.3 Limit for this EUT

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

## 8.3. Test Procedure

- (1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a semi-anechoic chamber for above 1G.
- (2) Test antenna was located 3m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used
9KHz-30MHz	Active Loop antenna
30MHz-1GHz	Trilog Broadband Antenna
1GHz-18GHz	Double Ridged Horn Antenna(1GHz-18GHz)
18GHz-40GHz	Horn Antenna(18GHz-40GHz)

According ANSI C63.10:2013 clause 6.4.4.2 and 6.5.3, for measurements below 30 MHz, the loop antenna was positioned with its plane vertical from the EUT and rotated about its vertical axis for maximum response at each azimuth position around the EUT. And the loop antenna also be positioned with its plane horizontal at the specified distance from the EUT. The center of the loop is 1 m above the ground. for measurement above 30MHz, the Trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

- (3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9KHz to 25GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1m to 4m(Except loop antenna, it's fixed 1m above ground.)

- (b) Change work frequency or channel of device if practicable.
- (c) Change modulation type of device if practicable.
- (d) Change power supply range from 85% to 115% of the rated supply voltage
- (e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces

highest emissions.

Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 9KHz to 30MHz and 18GHz to 25GHz so below final test was performed with frequency range from 30MHz to 18GHz.

- (4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10 2013 on Radiated Emission test.
- (5) The emissions from 9KHz to 1GHz were measured based on CISPR QP detector except for the frequency bands 9-90KHz, 110-490KHz, for emissions from 9KHz-90KHz, 110KHz-490KHz and above 1GHz were measured based on average detector, for emissions above 1GHz, peak emissions also be measured and need comply with Peak limit.
- (6) The emissions from 9KHz to 1GHz, QP or average values were measured with EMI receiver with below RBW

Frequency band	RBW
9KHz-150KHz	200Hz
150KHz-30MHz	9KHz
30MHz-1GHz	120KHz

For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 3MHz for Average measure (according ANSI C63.10:2013 clause 4.2.3.2.3 procedure for average measure).

- (8) X axis, Y axis, Z axis are tested, and worse setup X axis is reported.

## 8.4. Test result

### **PASS. (See below detailed test result)**

All the emissions except fundamental emission from 9KHz to 25GHz were comply with 15.209 limit.

Note1: According exploratory test no any obvious emission were detected from 9KHz to 30MHz and 18GHz to 25GHz, so the final test was performed with frequency range from 30MHz to 18GHz and recorded in below.

Note2: For emissions below 1GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1GHz, the final test was only performed with EUT working in GFSK, Tx 2440MHz mode.


Note3: For emissions above 1GHz. If peak results comply with AV limit, AV Result is deemed to comply with AV limit.

Radiated Emission test (below 1GHz)

**TR-4-E-009 Radiated Emission Test Result**

<b>Test Site</b>	: DDT 3m Chamber 2#	E:\2017 RE2# Report Data\17Q0705-9\RE.EM6
<b>Test Date</b>	: 2017-07-12	<b>Tested By</b> : Sunny
<b>EUT</b>	: 2.0 Soundbar with Bluetooth	<b>Model Number</b> : BAR STUDIO
<b>Power Supply</b>	: AC 120V/60Hz	<b>Test Mode</b> : Tx mode
<b>Condition</b>	: Temp:24.5°C,Humi:55%, Press:100.1kPa	<b>Antenna/Distance</b> : 2016 VULB9163 2#/3m/HORIZONTAL
<b>Memo</b>	:	

Data: 27




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	81.67	13.46	6.93	4.16	24.55	40.00	-15.45	QP	HORIZONTAL
2	199.31	16.46	10.00	4.89	31.35	43.50	-12.15	QP	HORIZONTAL
3	225.30	20.12	11.30	5.02	36.44	46.00	-9.56	QP	HORIZONTAL
4	315.47	17.52	13.50	5.44	36.46	46.00	-9.54	QP	HORIZONTAL
5	406.11	14.46	15.58	5.82	35.86	46.00	-10.14	QP	HORIZONTAL
6	478.87	9.55	16.62	6.09	32.26	46.00	-13.74	QP	HORIZONTAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.  
 2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.  
 3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

**Test Site** : DDT 3m Chamber 2# E:\2017 RE2# Report Data\17Q0705-9\RE.EM6  
**Test Date** : 2017-07-12 **Tested By** : Sunny  
**EUT** : 2.0 Soundbar with Bluetooth **Model Number** : BAR STUDIO  
**Power Supply** : AC 120V/60Hz **Test Mode** : Tx mode  
**Condition** : Temp:24.5°C,Humi:55%,  
 Press:100.1kPa **Antenna/Distance** : 2016 VULB9163 2#/3m/VERTICAL  
**Memo** :

Data: 28



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	30.85	16.19	9.85	3.68	29.72	40.00	-10.28	QP	VERTICAL
2	32.52	16.45	10.19	3.71	30.35	40.00	-9.65	QP	VERTICAL
3	42.90	10.07	13.10	3.82	26.99	40.00	-13.01	QP	VERTICAL
4	46.83	11.18	13.25	3.86	28.29	40.00	-11.71	QP	VERTICAL
5	478.85	11.93	16.62	6.09	34.64	46.00	-11.36	QP	VERTICAL
6	511.84	11.50	17.24	6.21	34.95	46.00	-11.05	QP	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.  
 2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.  
 3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

**Radiated Emission test (above 1GHz)**

Freq. (MHz)	Read level (dB $\mu$ V)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Detector type	Polarization
GFSK Tx mode 2402MHz									
3996.00	38.44	33.39	29.05	7.61	50.39	74.00	-23.61	Peak	HORIZONTAL
5088.00	36.94	33.88	29.34	8.78	50.26	74.00	-23.74	Peak	HORIZONTAL
6075.00	36.60	35.12	29.26	9.72	52.18	74.00	-21.82	Peak	HORIZONTAL
7013.00	37.31	36.21	30.39	10.45	53.58	74.00	-20.42	Peak	HORIZONTAL
7328.00	36.81	36.47	30.59	10.71	53.40	74.00	-20.60	Peak	HORIZONTAL
7797.00	36.96	36.66	31.04	11.02	53.60	74.00	-20.40	Peak	HORIZONTAL
3947.00	38.79	33.25	29.07	7.58	50.55	74.00	-23.45	Peak	VERTICAL
4717.00	37.32	33.76	29.30	8.39	50.17	74.00	-23.83	Peak	VERTICAL
5760.00	36.32	34.86	29.21	9.43	51.40	74.00	-22.60	Peak	VERTICAL
6698.00	36.76	35.96	30.14	10.14	52.72	74.00	-21.28	Peak	VERTICAL
7279.00	36.30	36.43	30.55	10.66	52.84	74.00	-21.16	Peak	VERTICAL
7643.00	36.48	36.63	30.94	10.94	53.11	74.00	-20.89	Peak	VERTICAL
GFSK Tx mode 2440MHz									
3758.00	38.39	32.70	29.19	7.45	49.35	74.00	-24.65	Peak	HORIZONTAL
4318.00	37.52	33.66	29.12	7.96	50.02	74.00	-23.98	Peak	HORIZONTAL
5767.00	36.02	34.86	29.21	9.47	51.14	74.00	-22.86	Peak	HORIZONTAL
6796.00	37.04	36.04	30.24	10.24	53.08	74.00	-20.92	Peak	HORIZONTAL
7069.00	36.96	36.26	30.42	10.50	53.30	74.00	-20.70	Peak	HORIZONTAL
7741.00	36.80	36.65	31.00	10.99	53.44	74.00	-20.56	Peak	HORIZONTAL
4451.00	37.97	33.76	29.19	8.10	50.64	74.00	-23.36	Peak	VERTICAL
5417.00	36.16	34.54	29.28	9.11	50.53	74.00	-23.47	Peak	VERTICAL
5998.00	37.06	35.00	29.19	9.68	52.55	74.00	-21.45	Peak	VERTICAL
6677.00	36.84	35.95	30.12	10.12	52.79	74.00	-21.21	Peak	VERTICAL
6992.00	37.45	36.19	30.38	10.44	53.70	74.00	-20.30	Peak	VERTICAL
7279.00	36.75	36.43	30.55	10.66	53.29	74.00	-20.71	Peak	VERTICAL
GFSK Tx mode 2480MHz									
4017.00	38.11	33.41	29.04	7.63	50.11	74.00	-23.89	Peak	HORIZONTAL
4682.00	37.24	33.76	29.29	8.33	50.04	74.00	-23.96	Peak	HORIZONTAL
5683.00	36.06	34.81	29.22	9.36	51.01	74.00	-22.99	Peak	HORIZONTAL
6180.00	37.53	35.30	29.34	9.77	53.26	74.00	-20.74	Peak	HORIZONTAL
6950.00	37.02	36.16	30.34	10.39	53.23	74.00	-20.77	Peak	HORIZONTAL
7699.00	36.87	36.64	30.97	10.97	53.51	74.00	-20.49	Peak	HORIZONTAL
4360.00	38.41	33.69	29.13	7.98	50.95	74.00	-23.05	Peak	VERTICAL
4780.00	38.23	33.74	29.31	8.44	51.10	74.00	-22.90	Peak	VERTICAL
5403.00	36.69	34.51	29.29	9.09	51.00	74.00	-23.00	Peak	VERTICAL
6047.00	37.15	35.08	29.23	9.71	52.71	74.00	-21.29	Peak	VERTICAL
6691.00	36.97	35.96	30.14	10.14	52.93	74.00	-21.07	Peak	VERTICAL
7314.00	36.87	36.45	30.57	10.71	53.46	74.00	-20.54	Peak	VERTICAL
Result: Pass									

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

## 9. RF Conducted Spurious Emissions

### 9.1. Block diagram of test setup

Same as section 4.1

### 9.2. Limits

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

### 9.3. Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

Center frequency	DTS Channel center frequency
RBW:	100KHz
VBW:	300KHz
Span	1.5times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.

(4) Set the spectrum analyzer as follows:


RBW:	100KHz
VBW:	300KHz
Span	Encompass frequency range to be measured
Number of measurement points	$\geq \text{span/RBW}$
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold


(5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band

### 9.4. Test Result

Mode	Freq. (MHz)	Conclusion
GFSK	Hopping off 2402	PASS
	Hopping off 2441	PASS
	Hopping off 2480	PASS


### 9.5. Original test data






BLE\_MCH\_Graphs

<p>MCH</p>	<p>Ref 20 dBm -Att 30 dB -RBW 100 kHz Marker 1 [T1] 1.03 dBm -VSW 300 kHz -SWT 5 ms 2.43996000 GHz</p> <p>30 Offset 10 dB</p> <p>20 10 0 -10 -20 -30 -40 -50 -60 -70 -80</p> <p>1 -18.03 dBm</p> <p>Center 2.44 GHz 400 MHz/ Span 4 MHz</p> <p>Date: 19.JUL.2017 13:50:59</p>
<p>MCH</p>	<p>Ref 30 dBm -Att 30 dB -RBW 100 kHz Marker 1 [T1] -44.02 dBm -VSW 300 kHz -SWT 300 ms 3.273082500 GHz</p> <p>30 Offset 10 dB</p> <p>20 10 0 -10 -20 -30 -40 -50 -60 -70</p> <p>1 -18.03 dBm</p> <p>Start 30 MHz 297 MHz/ Stop 3 GHz</p> <p>Date: 19.JUL.2017 13:51:00</p> <p>Ref 30 dBm -Att 30 dB -RBW 100 kHz Marker 1 [T1] -44.02 dBm -VSW 300 kHz -SWT 200 ms 3.107230000 GHz</p> <p>30 Offset 10 dB</p> <p>20 10 0 -10 -20 -30 -40 -50 -60 -70</p> <p>1 -18.03 dBm</p> <p>Start 3 GHz 200 MHz/ Stop 5 GHz</p> <p>Date: 19.JUL.2017 13:51:06</p>




BLE\_HCH\_Graphs

<p>HCH</p>	<p>Ref 20 dBm -Att 30 dB -RBW 100 kHz Marker 1 [T1] 1.26 dBm -VSW 300 kHz 2.479960000 GHz SWT 5 ms</p> <p>Center 2.48 GHz 400 kHz/ Span 4 MHz</p> <p>Date: 19.JUL.2017 13:59:46</p>
<p>HCH</p>	<p>Ref 30 dBm -Att 30 dB -RBW 100 kHz Marker 1 [T1] -43.76 dBm -VSW 300 kHz 2.853212500 GHz SWT 200 ms</p> <p>Start 30 MHz 297 MHz/ Stop 3 GHz</p> <p>Date: 19.JUL.2017 13:59:59</p> <p>Ref 30 dBm -Att 30 dB -RBW 100 kHz Marker 1 [T1] -44.04 dBm -VSW 300 kHz 3.207000000 GHz SWT 200 ms</p> <p>Start 3 GHz 200 MHz/ Stop 3 GHz</p> <p>Date: 19.JUL.2017 13:59:59</p>



## 10. Band Edge Compliance

### 10.1. Block diagram of test setup



### 10.2. Limit

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz and 5725MHz to 5850MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

### 10.3. Test Procedure

Same with clause 8.3 except change investigated frequency range from 2310MHz to 2415MHz and 2475MHz to 2500MHz.

Remark: All restriction band have been tested, and only the worse case is shown in report.


### 10.4. Test result

**PASS.** (See below detailed test result)

## TR-4-E-009 Radiated Emission Test Result

<b>Test Site</b>	: DDT 3m Chamber 1#	D:\2017 RE1# Report Data\17Q0705-9\RE.EM6
<b>Test Date</b>	: 2017-07-13	<b>Tested By</b> : Jerry
<b>EUT</b>	: 2.0 Soundbar with Bluetooth	<b>Model Number</b> : BAR STUDIO
<b>Power Supply</b>	: AC 120V/60Hz	<b>Test Mode</b> : TX mode CH0
<b>Condition</b>	: Temp:24.5°C,Humi:55%, Press:100.1kPa	<b>Antenna/Distance</b> : 2016 HF907/3m/VERTICAL
<b>Memo</b>	:	

Data: 23




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2390.00	25.23	29.78	29.42	6.03	31.62	54.00	-22.38	Average	VERTICAL
2	2390.00	51.50	29.78	29.42	6.03	57.89	74.00	-16.11	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

**Test Site** : DDT 3m Chamber 1# D:\2017 RE1# Report Data\17Q0705-9\RE.EM6  
**Test Date** : 2017-07-13 **Tested By** : Jerry  
**EUT** : 2.0 Soundbar with Bluetooth **Model Number** : BAR STUDIO  
**Power Supply** : AC 120V/60Hz **Test Mode** : TX mode CH0  
**Condition** : Temp:24.5°C,Humi:55%,  
 Press:100.1kPa **Antenna/Distance** : 2016 HF907/3m/HORIZONTAL  
**Memo** :

Data: 24




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2374.24	44.11	29.71	29.39	6.01	50.44	74.00	-23.56	Peak	HORIZONTAL
2	2390.00	25.06	29.78	29.42	6.03	31.45	54.00	-22.55	Average	HORIZONTAL
3	2390.00	48.78	29.78	29.42	6.03	55.17	74.00	-18.83	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

<b>Test Site</b>	: DDT 3m Chamber 1#	<b>Test Date</b>	: 2017-07-13	<b>Tested By</b>	: Jerry
<b>EUT</b>	: 2.0 Soundbar with Bluetooth	<b>Model Number</b>	: BAR STUDIO	<b>Test Mode</b>	: TX mode CH39
<b>Power Supply</b>	: AC 120V/60Hz	<b>Antenna/Distance</b>	: 2016 HF907/3m/HORIZONTAL		
<b>Condition</b>	: Temp:24.5°C,Humi:55%, Press:100.1kPa	<b>Memo</b>	:		

Data: 29




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	28.04	30.14	29.71	6.13	34.60	54.00	-19.40	Average	HORIZONTAL
2	2483.50	63.59	30.14	29.71	6.13	70.15	74.00	-3.85	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

**Test Site** : DDT 3m Chamber 1# D:\2017 RE1# Report Data\17Q0705-9\RE.EM6  
**Test Date** : 2017-07-13 **Tested By** : Jerry  
**EUT** : 2.0 Soundbar with Bluetooth **Model Number** : BAR STUDIO  
**Power Supply** : AC 120V/60Hz **Test Mode** : TX mode CH39  
**Condition** : Temp:24.5°C,Humi:55%,  
 Press:100.1kPa **Antenna/Distance** : 2016 HF907/3m/VERTICAL  
**Memo** :

Data: 30




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	28.31	30.14	29.71	6.13	34.87	54.00	-19.13	Average	VERTICAL
2	2483.50	64.43	30.14	29.71	6.13	70.99	74.00	-3.01	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## 11. Power Line Conducted Emission

### 11.1. Block diagram of test setup



### 11.2. Power Line Conducted Emission Limits

Frequency	Quasi-Peak Level dB( $\mu$ V)	Average Level dB( $\mu$ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Note 1: \* Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

### 11.3. Test Procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

Configuration EUT to simulate typical usage as described in clause 2.4 and test equipment as described in clause 10.2 of this report.

All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 KHz.

#### **11.4. Test Result**

**PASS. (See below detailed test result)**


Note1: All emissions not reported below are too low against the prescribed limits.

Note2: “----” means Peak detection; “-----” mans Average detection

# TR-4-E-010 Conducted Emission Test Result

**Test Site** : DDT 1# Shield Room E:\2017 CE report data\17Q0705-9\RF.EM6  
**Test Date** : 2017-07-18 **Tested By** : Xian  
**EUT** : 2.0 Soundbar with Bluetooth **Model Number** : BAR STUDIO  
**Power Supply** : AC 120V/60Hz **Test Mode** : TX mode  
**Condition** : Temp:24.5°C,Humi:55%,  
**LISN** : 2016 ENV216/LINE  
 Press:100.1kPa  
**Memo** :

Data: 6




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Over Limit (dB)	Detector	Phase
1	0.16	12.92	9.61	0.02	9.86	32.41	55.43	-23.02	Average	LINE
2	0.16	18.76	9.61	0.02	9.86	38.25	65.43	-27.18	QP	LINE
3	0.21	12.66	9.61	0.02	9.86	32.15	53.23	-21.08	Average	LINE
4	0.21	17.96	9.61	0.02	9.86	37.45	63.23	-25.78	QP	LINE
5	0.48	10.70	9.61	0.02	9.86	30.19	46.27	-16.08	Average	LINE
6	0.48	15.92	9.61	0.02	9.86	35.41	56.27	-20.86	QP	LINE
7	0.78	13.87	9.61	0.03	9.86	33.37	46.00	-12.63	Average	LINE
8	0.78	18.06	9.61	0.03	9.86	37.56	56.00	-18.44	QP	LINE
9	1.22	8.65	9.62	0.03	9.86	28.16	46.00	-17.84	Average	LINE
10	1.22	13.23	9.62	0.03	9.86	32.74	56.00	-23.26	QP	LINE
11	1.44	8.76	9.62	0.03	9.86	28.27	46.00	-17.73	Average	LINE
12	1.44	13.38	9.62	0.03	9.86	32.89	56.00	-23.11	QP	LINE

- Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.  
 2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).  
 4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

# TR-4-E-010 Conducted Emission Test Result

<b>Test Site</b>	: DDT 1# Shield Room	<b>E:\2017 CE report data\17Q0705-9\RF.EM6</b>	
<b>Test Date</b>	: 2017-07-18	<b>Tested By</b>	: Xian
<b>EUT</b>	: 2.0 Soundbar with Bluetooth	<b>Model Number</b>	: BAR STUDIO
<b>Power Supply</b>	: AC 120V/60Hz	<b>Test Mode</b>	: TX mode
<b>Condition</b>	: Temp:24.5°C,Humi:55%, Press:100.1kPa	<b>LISN</b>	: 2016 ENV216/NEUTRAL
<b>Memo</b>	:		

Data: 8



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Over Limit (dB)	Detector	Phase
1	0.15	12.99	9.61	0.02	9.86	32.48	55.82	-23.34	Average	NEUTRAL
2	0.15	19.26	9.61	0.02	9.86	38.75	65.82	-27.07	QP	NEUTRAL
3	0.27	12.64	9.61	0.02	9.86	32.13	51.20	-19.07	Average	NEUTRAL
4	0.27	17.94	9.61	0.02	9.86	37.43	61.20	-23.77	QP	NEUTRAL
5	0.36	11.61	9.61	0.02	9.86	31.10	48.83	-17.73	Average	NEUTRAL
6	0.36	16.73	9.61	0.02	9.86	36.22	58.83	-22.61	QP	NEUTRAL
7	0.45	11.04	9.61	0.02	9.86	30.53	46.80	-16.27	Average	NEUTRAL
8	0.45	16.42	9.61	0.02	9.86	35.91	56.80	-20.89	QP	NEUTRAL
9	0.78	12.95	9.61	0.03	9.86	32.45	46.00	-13.55	Average	NEUTRAL
10	0.78	17.26	9.61	0.03	9.86	36.76	56.00	-19.24	QP	NEUTRAL
11	1.45	8.64	9.62	0.03	9.86	28.15	46.00	-17.85	Average	NEUTRAL
12	1.45	13.38	9.62	0.03	9.86	32.89	56.00	-23.11	QP	NEUTRAL

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

## **12. Antenna Requirements**


### **12.1. Limit**

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### **12.2. Result**

The antennas used for this product is integrated antenna and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is only 3.40dBi.

13. Test setup photograph





## **14. Photos of the EUT**

Refer to section 7-Photos of the EUT for report “DDT-R17Q0705-9E1”.

**END OF REPORT**