



TECH SPEC

Transducers:	189 x 114 mm Subwoofer, 2 x 80.9 x 80.9 mm Midrange / 2 x 27.5 inch, 2 x 6.02 mm Tweeter / 2 x 6.75 inch	Bluetooth® profile:	A2DP 1.3, AVRCP 1.6
Output power:	1 x 80 W RMS-subwoofer + 2 x 40 W RMS-midrange + 2 x 10 W RMS-tweeter (AC mode) / 1 x 80 W RMS-subwoofer + 2 x 30 W RMS-midrange + 2 x 8 W RMS-tweeter (Battery mode)	Bluetooth® transmitter:	2.4 GHz - 2.4835 GHz
Power input:	100 - 240 VAC, 50/60 Hz	Bluetooth® transmitter power:	≤ 9 dBm (EIRP)
Frequency response:	> 30 Hz	Bluetooth® transmitter modulation:	GFSK, π/4 DQPSK, EDPSK
Signal-to-noise ratio:	> 95 dB	Product dimensions (W x H x D):	482.4 x 256.9 x 199.2 mm / 19.0 x 10.1 x 7.9"
Battery type:	Li-ion polymer 69.696kWh (equivalent to 7.2kVh / 9,600 mAh)	Packaging dimensions (W x H x D):	6.7 kg / 14.7 lbs
Battery charge time:	6.5 hours	Net weight:	565 x 324 x 256.5 mm / 22.2 x 12.8 x 10.1"
Music play time:	up to 24 hours (dependent on volume level and audio content)	Gross weight:	9.74 kg / 21.47 lbs
Connection ports:	AC, USB-A, Aux-In	Maximum operation temperature:	65 °C
Cable type:	AC Power Cable	Bluetooth® transmitter power:	2,400 GHz - 2,475 GHz
Cable length:	2000 mm / 78.7"	Bluetooth® transmitter modulation:	≤ 15 dBm (EIRP)
USB charge rate:	1.8 A (maximum)		
Bluetooth® version:	5.3		

