



No. 1 Workshop, M-10, Middle section, Science & Technology Park,
Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM170700736502
Page: 1 of 8

RF Exposure Evaluation Report

Application No.: SZEM1707007365CR (GZEM1707004198CR)

Applicant: Harman International Industries, Inc.

Address of Applicant: 8500 Balboa Boulevard, Northridge, California, 91329, United States

Manufacturer: Harman International Industries, Inc.

Address of Manufacturer: 8500 Balboa Boulevard, Northridge, California, 91329, United States

Factory: Guoguang Electric Co., Ltd.

Address of Factory: No.8 Jinghu Road, Xinya Street, Huadu Reg, Guangzhou, China

Equipment Under Test (EUT):

Product Name: JBL Wireless Speaker-Secondary

Model No.: CONTROL XSTREAM Secondary

Trade mark: JBL

FCC ID: APICNTRLXSTRMS

Standards: 47 CFR Part 1.1307 (2016)

47 CFR Part 1.1310 (2016)

Date of Receipt: 2017-07-13

Date of Test: 2017-07-28 to 2017-08-11

Date of Issue: 2017-09-14

Test Result :	PASS*
----------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.




Jack Zhang
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2017-09-14		Original

Authorized for issue by:			
			
	Benson Wang /Project Engineer		
			
	Eric Fu /Reviewer		

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 GENERAL INFORMATION.....	4
4.1 GENERAL DESCRIPTION OF EUT	4
4.2 TEST LOCATION.....	5
4.3 TEST FACILITY.....	5
4.4 DEVIATION FROM STANDARDS.....	6
4.5 ABNORMALITIES FROM STANDARD CONDITIONS.....	6
4.6 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	6
5 RF EXPOSURE EVALUATION	7
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT	7
5.1.1 <i>Limits</i>	7
5.1.2 <i>Test Procedure</i>	7
4.1.3 EUT RF EXPOSURE EVALUATION	8

4 General Information

4.1 General Description of EUT

Power supply: AC 100-240V 50/60Hz

Cable: AC cable: 153cm unshielded

For 5.2G property:

Operation Frequency: 5180MHz~5240MHz

Modulation Type: QPSK

Sample Type: Fixed production

Antenna Type: Integral

Antenna Gain: Antenna A: 3.0dBi
Antenna B: 3.0dBi

The two antennas and match circuit are the identical and only one antenna is selected for use at any one time, through the on-board Transmit-receive/Diversity RF switch.

For 5.8G property:

Operation Frequency: 5736MHz~5814MHz

Modulation Type: QPSK

Sample Type: Fixed production

Antenna Type: Integral

Antenna Gain: Antenna A: 3.2dBi
Antenna B: 3.2dBi

The two antennas and match circuit are the identical and only one antenna is selected for use at any one time, through the on-board Transmit-receive/Diversity RF switch.

4.2 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China
518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

4.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

4.4 Deviation from Standards

None.

4.5 Abnormalities from Standard Conditions

None.

4.6 Other Information Requested by the Customer

None.

5 RF Exposure Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	f/300	6
1500–100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	f/1500	30
1500–100,000	1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.1.3 EUT RF Exposure Evaluation

5.2g property

Antenna A/B: 3.0dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.0 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

The normal conducted output power is 9dBm (tolerance: +/- 2dB).

Max Conducted Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm²)	Limit	Result
11	12.59	0.005	1.0	PASS

5.8g property

Antenna A/B: 3.2dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.09 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

The normal conducted output power is 8dBm (tolerance: +/- 2dB).

Max Conducted Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm²)	Limit	Result
10	10	0.004	1.0	PASS

The distance r (3rd column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.