

# Appendix B

## Highest Test Plots

# Table of Contents

1. 2.4G Body-worn 0mm SAR ..... 3

## 1. 2.4G Body-worn 0mm SAR

Date: 26.06.2025

Test Laboratory: Guangdong Dongdian Testing Service Co., Ltd.

Q24112615-2E

Serial: S24112615-010

Communication System: UID 0, Bluetooth (0); Communication System Band: Bluetooth; Frequency: 2480 MHz; Communication System PAR: 0 dB; PMF: 1.12202e-005

Medium parameters used:  $f = 2480$  MHz;  $\sigma = 1.846$  S/m;  $\epsilon_r = 39.234$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3906; ComF(7.9, 7.9) @ 2480 MHz; Calibrated: 28.05.2025
- Sensor-Surface: 1.4mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 Sn1366; Calibrated: 28.05.2025
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP-1197
- DASY52 52.10.4(1535); SEMCAD X 14.6.14(7501)

**Configuration/Left side 3DHS 2480 MHz/Area Scan (7x19x1):** Measurement grid:  $dx=10$ mm,  $dy=10$ mm  
Maximum value of SAR (measured) = 0.311 W/kg

**Configuration/Left side 3DHS 2480 MHz/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5$ mm,  $dy=5$ mm,  $dz=5$ mm  
Reference Value = 7.512 V/m; Power Drift = 0.19 dB  
Peak SAR (extrapolated) = 0.396 W/kg  
**SAR(1 g) = 0.181 W/kg; SAR(10 g) = 0.080 W/kg**  
Smallest distance from peaks to all points 3 dB below = 8 mm  
Ratio of SAR at M2 to SAR at M1 = 47.7%  
Maximum value of SAR (measured) = 0.310 W/kg

