

FCC AND ISED CERTIFICATION TEST REPORT

FOR

Applicant	:	Harman International Industries, Inc.
Address	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES
Equipment under Test	:	Portable Bluetooth Speaker
Model No.	:	BOOMBOX 3
Trade Mark	:	JBL
FCC ID	:	APIJBLBOOMBOX3
IC	:	6132A-JBLBOOMBOX3
Manufacturer	:	Harman International Industries, Inc.
Address	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park,
Dongguan City, Guangdong Province, China, 523808

Tel.: +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

REPORT

Table of Contents

	Test report declares.....	3
1.	Summary of Test Results.....	5
2.	General Test Information	6
2.1.	Description of EUT	6
2.2.	Accessories of EUT.....	7
2.3.	Assistant equipment used for test.....	7
2.4.	Block diagram of EUT configuration for test.....	7
2.5.	Deviations of test standard.....	7
2.6.	Test environment conditions	8
2.7.	Test laboratory	8
2.8.	Measurement uncertainty.....	9
3.	Equipment Used During Test.....	10
4.	Radiated Emission	11
4.1.	Block diagram of test setup.....	11
4.2.	Limit.....	12
4.3.	Test procedure	14
4.4.	Test result.....	15
5.	Power Line Conducted Emission.....	22
5.1.	Block diagram of test setup.....	22
5.2.	Power line conducted emission limits	22
5.3.	Test procedure	22
5.4.	Test result.....	23
6.	Test Setup Photograph	30
7.	Photos of the EUT	31

Test Report Declare

Applicant	:	Harman International Industries, Inc.
Address	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES
Equipment under Test	:	Portable Bluetooth Speaker
Model No.	:	BOOMBOX 3
Trade Mark	:	JBL
Manufacturer	:	Harman International Industries, Inc.
Address	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES

Test Standard Used:

FCC Rules and Regulations Part 15 Subpart C, RSS-247 Issue 2 February 2017.

Test Procedure Used:

ANSI C63.10:2013, RSS-Gen Issue 5, Apr. 2018, Amendment 2 (February 2021).

We Declare:

The equipment described above is tested by Dongguan Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Dongguan Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above FCC&ISED standards.

Report No.:	DDT-R22071424-2E03		
Date of Receipt:	Jul. 25, 2022	Date of Test:	Jul. 25, 2022 ~ Aug. 15, 2022

Prepared By:

Ella Gong

Ella Gong/Engineer

Approved By:



Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Aug. 15, 2022	

1. Summary of Test Results

Description of Test Item	Standard	Verdict
Radiated Emission	FCC Part 15: 15.209 FCC Part 15: 15.247(d) ANSI C63.10:2013 RSS-247 Issue 2 RSS-Gen Issue 5	Pass
Power Line Conducted Emissions	FCC Part 15: 15.207 ANSI C63.10:2013 RSS-Gen Issue 5	Pass

Note:

1. This report adds IC and battery for alternative use with solution A, B, C on the basis of the report DDT-R22012417-2E03, this change based on engineering judgment that only Radiated Emission (below 1GHz) and Power Line Conducted Emission need to test.
2. Please refer to report DDT-R22012417-2E03 for the other original data.

Solution	Chip Replacement Specifications	Battery model/specification configuration
A	Battery Charging IC changed from SYV651 to SY6961	Original: ICA068GA Added battery IDA109GA: GP+SINO WEALTH (SH366003) chip
B	1. Battery Charging IC changed from SYV651 to SY6961; 2. BOOST DC-DC IC changed from TPS43061 to MP3910; 3. Stepdown DC-DC changed from DIO54302 to SGM61230; 4. OVP&OCP IC changed from SY6874 to SGM2526; 5. OP AMP IC changed from TLV9062IPWR to GS8722; 6. LDO IC changed from LP3980-33B5F to AW37050D330STR	Add battery IDA109GA: GP+SINO WEALTH(SH366003) chip
C	Based on the Solution B, Charger chip U8 is changed from SY6961 to SC1896; and DC-DC chip U2 is changed from SGM61230 to DIO54302	IDA109GA: GP+TI(BQ28Z610DRZR) chip Add battery IDA109GA: GP+SINO WEALTH(SH366003) chip

2. General Test Information

2.1. Description of EUT

EUT* Name	: Portable Bluetooth Speaker
Model Number	: BOOMBOX 3
EUT Function Description	: Please reference user manual of this device
Power Supply	: AC 100-240V-50/60Hz 80W DC 7.26V built-in battery
Radio Specification	: 2.4G SRD
Operation Frequency	: 2407 MHz - 2475 MHz
Modulation	: GFSK, $\pi/4$ -DQPSK, 8DPSK
Data Rate	: 1 Mbps, 2 Mbps, 3 Mbps
Antenna Gain	: 2.26 dBi
Sample Type	: Series production
Sample Number	: S22071424-29, S22071424-76, S22071424-78

Note: EUT is the abbreviation of equipment under test.

Channel information					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
5	2407	28	2430	51	2453
6	2408	29	2431	52	2454
7	2409	30	2432	53	2455
8	2410	31	2433	54	2456
9	2411	32	2434	55	2457
10	2412	33	2435	56	2458
11	2413	34	2436	57	2459
12	2414	35	2437	58	2460
13	2415	36	2438	59	2461
14	2416	37	2439	60	2462
15	2417	38	2440	61	2463
16	2418	39	2441	62	2464
17	2419	40	2442	63	2465
18	2420	41	2443	64	2466
19	2421	42	2444	65	2467
20	2422	43	2445	66	2468
21	2423	44	2446	67	2469
22	2424	45	2447	68	2470
23	2425	46	2448	69	2471
24	2426	47	2449	70	2472
25	2427	48	2450	71	2473
26	2428	49	2451	72	2474
27	2429	50	2452	73	2475

2.2. Accessories of EUT

Description of Accessories	Manufacturer	Model number	Description	Remark
AC cable	Harman	N/A	N/A	Length: 1.85m unshielded

2.3. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	EMC Compliance	SN
N/A	N/A	N/A	N/A	N/A

2.4. Block diagram of EUT configuration for test

EUT

Test software: FCC Test Tool V2.3.137.747

The test software was used to control EUT work in Continuous Tx mode, and select test channel, wireless mode as below table.

Tested mode, channel, information			
Mode	Setting Tx Power	Channel	Frequency (MHz)
GFSK hopping on Tx mode	/	CH5 to CH73	2407 to 2475
$\pi/4$ -DQPSK hopping on Tx mode	/	CH5 to CH73	2407 to 2475
8DPSK hopping on Tx mode	/	CH5 to CH73	2407 to 2475
GFSK hopping off Tx mode	/	CH5	2407
	/	CH39	2441
	/	CH73	2475
$\pi/4$ -DQPSK hopping off Tx mode	/	CH5	2407
	/	CH39	2441
	/	CH73	2475
8DPSK hopping off Tx mode	/	CH5	2407
	/	CH39	2441
	/	CH73	2475

2.5. Deviations of test standard

No deviation.

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	21-25 °C
Humidity range:	40-75%
Pressure range:	86-106 kPa

2.7. Test laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City,
Guangdong Province, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, G-20118

2.8. Measurement uncertainty

Test Item	Uncertainty
Bandwidth	1.1%
Peak Output Power (Conducted) (Spectrum Analyzer)	0.86 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$); 1.38 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$)
Peak Output Power (Conducted) (Power Sensor)	0.74 dB
Power Spectral Density	0.74 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$); 1.38 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$)
Frequencies Stability	6.7×10^{-8} (Antenna couple method) 5.5×10^{-8} (Conducted method)
Conducted Spurious Emissions	0.86 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$); 1.40 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$) 1.66 dB ($8 \text{ GHz} \leq f < 22 \text{ GHz}$)
Uncertainty for Radio Frequency (RBW < 20 kHz)	3×10^{-8}
Temperature	0.4 °C
Humidity	2 %
Uncertainty for Radiation Emission Test (9 kHz – 30 MHz)	3.44 dB
Uncertainty for Radiation Emission Test (30 MHz - 1 GHz)	4.70 dB (Antenna Polarize: V) 4.84 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission Test (1 GHz - 40 GHz)	4.10 dB (1 - 6 GHz) 4.40 dB (6 GHz - 18 GHz) 3.54 dB (18 GHz - 26 GHz) 4.30 dB (26 GHz - 40 GHz)
Uncertainty for Power Line Conduction Emission Test	3.32 dB (150 kHz - 30 MHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	


3. Equipment Used During Test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
☒ Radiation 3#chamber					
EMI Test Receiver	R&S	ESU	100472	May 18, 2022	1 Year
Spectrum analyzer	Agilent	E4447A	MY50180031	May 18, 2022	1 Year
Active Loop antenna	Schwarzbeck	FMZB-1519	1519-038	Sep. 19, 2021	1 Year
Trilog Broadband Antenna	Schwarzbeck	VULB 9161	4034	Sep. 19, 2021	1 Year
Double Ridged Horn Antenna	Schwarzbeck	BBHA9120	02468	Nov. 17, 2021	1 Year
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	790	May 06, 2022	1 Year
Pre-amplifier	COM-POWER	PAM-118A	18040084	Sep. 02, 2021	1 Year
Pre-amplifier	COM-POWER	PAM-840A	461369	Apr. 11, 2022	1 Year
Test software	Audix	E3	V 6.1.1.1	N/A	N/A
☒ Power Line Conducted Emissions Test 1#					
Test Receiver	R&S	ESCI	100551	Sep. 02, 2021	1 Year
LISN 1	R&S	ENV216	101109	Sep. 02, 2021	1 Year
LISN 2	R&S	ESH2-Z5	100309	Sep. 02, 2021	1 Year
Pulse Limiter	R&S	ESH3-Z2	101242	Sep. 02, 2021	1 Year
CE Cable 1	HUBSER	N/A	W10.01	Sep. 02, 2021	1 Year
LISN 3	SCHWARZBECK	NSLK 8163	00017	Sep. 02, 2021	1 Year
Test software	Audix	E3	V 6.11111b	N/A	N/A


4. Radiated Emission

4.1. Block diagram of test setup


In 3 m Anechoic Chamber, test setup diagram for 9 kHz - 30 MHz:



In 3 m Anechoic Chamber, test setup diagram for 30 MHz - 1 GHz:



In 3 m Anechoic Chamber, test setup diagram for frequency above 1 GHz:



Note: For harmonic emissions test an appropriate high pass filter was inserted in the input port of AMP.

4.2. Limit

(1) FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6

(2) RSS-GEN Restricted frequency band*

MHz	MHz	MHz	GHz
0.090 - 0.110	13.36 - 13.41	960 - 1427	9.0 - 9.2
0.495 - 0.505	16.42 - 16.423	1435 - 1626.5	9.3 - 9.5
2.1735 - 2.1905	16.69475 - 16.69525	1645.5 - 1646.5	10.6 - 12.7
3.020 - 3.026	16.80425 - 16.80475	1660 - 1710	13.25 - 13.4
4.125 - 4.128	25.5 - 25.67	1718.8 - 1722.2	14.47 - 14.5
4.17725 - 4.17775	37.5 - 38.25	2200 - 2300	15.35 - 16.2
4.20725 - 4.20775	73 - 74.6	2310 - 2390	17.7 - 21.4
5.677 - 5.683	74.8 - 75.2	2483.5 - 2500	22.01 - 23.12
6.215 - 6.218	108 - 138	2655 - 2900	23.6 - 24.0
6.26775 - 6.26825	149.9 - 150.05	3260 - 3267	31.2 - 31.8
6.31175 - 6.31225	156.52475 - 156.52525	3332 - 3339	36.43 - 36.5
8.291 - 8.294	156.7 - 156.9	3345.8 - 3358	Above 38.6
8.362 - 8.366	162.0125 - 167.17	3500 - 4400	
8.37625 - 8.38675	167.72 - 173.2	4500 - 5150	
8.41425 - 8.41475	240 - 285	5350 - 5460	
12.29 - 12.293	322 - 335.4	7250 - 7750	
12.51975 - 12.52025	399.9 - 410	8025 - 8500	
12.57675 - 12.57725	608 - 614	--	

* Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

(2) FCC 15.209 & RSS-GEN Limit.

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

Note: (1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz and above 1000 MHz, radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30 MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3m}(\text{dB}\mu\text{V}/\text{m}) = \text{Limit}_{30m}(\text{dB}\mu\text{V}/\text{m}) + 40\text{Log}(30\text{m}/3\text{m})$$

(3) Limit for this EUT

All the emissions appearing within 15.205 & RSS-GEN restricted frequency bands shall not exceed the limits shown in 15.209 & RSS-GEN, all the other emissions shall be at least 20 dB below the fundamental emissions or comply with 15.209 & RSS-GEN limits.

4.3. Test procedure

- (1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1 GHz and 150 cm above the ground plane inside a fully-anechoic chamber for above 1 GHz.
- (2) Test antenna was located 3 m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9 kHz - 30 MHz	Active Loop antenna	3 m
30 MHz - 1 GHz	Trilog Broadband Antenna	3 m
1 GHz - 18 GHz	Double Ridged Horn Antenna (1 GHz - 18 GHz)	3 m
18 GHz - 40 GHz	Horn Antenna (18 GHz - 40 GHz)	1 m

According ANSI C63.10:2013 clause 6.4.4.2 and 6.5.3, for measurements below 30 MHz, the loop antenna was positioned with its plane vertical from the EUT and rotated about its vertical axis for maximum response at each azimuth position around the EUT. And the loop antenna also is positioned with its plane horizontal at the specified distance from the EUT. The center of the loop is 1 m above the ground. For measurement above 30 MHz, the trilog Broadband Antenna or Horn Antenna was located 3 m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

- (3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9 kHz to 25 GHz:

- (a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1 m to 4 m (Except loop antenna, it's fixed 1 m above ground.)

- (b) Change work frequency or channel of device if practicable.

- (c) Change modulation type of device if practicable.

- (d) Change power supply range from 85% to 115% of the rated supply voltage

- (e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9 kHz to 25 GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18 GHz to 25 GHz, so below final test was performed with frequency range from 9 kHz to 18 GHz.

- (4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipment and all of the interface cables were changed according to ANSI C63.10:2013 on Radiated Emission test.
- (5) The emissions from 9 kHz to 1 GHz were measured based on CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz, for emissions from 9 kHz - 90 kHz, 110 kHz - 490 kHz and above 1 GHz were measured based on average detector, for emissions above 1 GHz, peak emissions also be measured and need comply with Peak limit.
- (6) The emissions from 9 kHz to 1 GHz, QP or average values were measured with EMI receiver with below RBW.

Frequency band	RBW
9 kHz - 150 kHz	200 Hz
150 kHz - 30 MHz	9 kHz
30 MHz - 1 GHz	120 kHz

- (7) For emissions above 1 GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1 MHz, VBW is set at 3 MHz for Peak measure; According ANSI C63.10:2013 clause 4.1.4.2.2 procedure for average measure.
- (8) X axis, Y axis, Z axis are tested, and worse setup X axis is reported.

4.4. Test result

Pass. (See below detailed test result)

All the emissions except fundamental emission from 9 kHz to 25 GHz were comply with 15.209 & RSS-GEN limits.

Note1: According exploratory test, the emission levels are 20 dB below the limit detected from 9 kHz to 30 MHz and 18 GHz to 25 GHz, so the final test was performed with frequency range from 30 MHz to 18 GHz and recorded in below.

Note2: For emissions below 1 GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1 GHz, the final test was only performed with EUT working in GFSK, Tx 2407 MHz mode.

Note3: For emissions above 1 GHz. Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK, the worst case is GFSK mode. If peak results comply with AV limit, AV Result is deemed to comply with AV limit. Other emission levels are attenuated 20 dB below the limit, so it does not record in the report.

Radiated Emission test (below 1 GHz)

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 3#

D:\E3 6.111\2022 Report Data\Q22071424-2E JBL
BOOMBOX3\A\FCC BELOW 1G.EM6

Test Date : 2022-08-02

Tested By : James Gan

EUT : Portable Bluetooth Speaker


Model Number : BOOMBOX 3

Power Supply : Battery

Test Mode : Tx Mode

Condition : Temp:22.7°C,Humi:56.5%,Press:100.3kPa Antenna/Distance : 2022 9161 #3/3m/HORIZONTAL

Memo : SRD (Solution A)

Data:
5

Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	31.84	7.21	11.08	3.56	21.85	40.00	-18.15	QP	HORIZONTAL
2	66.73	11.32	9.33	3.80	24.45	40.00	-15.55	QP	HORIZONTAL
3	169.60	2.25	19.40	4.34	25.99	43.50	-17.51	QP	HORIZONTAL
4	337.22	3.70	13.84	4.95	22.49	46.00	-23.51	QP	HORIZONTAL
5	605.66	2.96	19.23	5.75	27.94	46.00	-18.06	QP	HORIZONTAL
6	965.54	3.07	23.62	6.66	33.35	54.00	-20.65	QP	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 3#

D:\E3 6.111\2022 Report Data\Q22071424-2E JBL BOOMBOX3\A\FCC BELOW 1G.EM6

Test Date : 2022-08-02

Tested By : James Gan

EUT : Portable Bluetooth Speaker

Model Number : BOOMBOX 3

Power Supply : Battery


Test Mode : Tx Mode

Condition : Temp:22.7°C,Humi:56.5%,Press:100.3kPa

Antenna/Distance : 2022 9161 #3/3m/VERTICAL

Memo : SRD (Solution A)

Data:
6



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	35.88	2.98	11.78	3.59	18.35	40.00	-21.65	QP	VERTICAL
2	66.50	8.99	9.45	3.80	22.24	40.00	-17.76	QP	VERTICAL
3	97.12	5.85	12.10	3.97	21.92	43.50	-21.58	QP	VERTICAL
4	169.01	1.75	19.40	4.34	25.49	43.50	-18.01	QP	VERTICAL
5	401.84	3.57	15.70	5.16	24.43	46.00	-21.57	QP	VERTICAL
6	962.16	3.55	23.54	6.64	33.73	54.00	-20.27	QP	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 3#

D:\E3 6.111\2022 Report Data\Q22071424-2E JBL
BOOMBOX3\B\FCC BELOW 1G.EM6

Test Date : 2022-08-09

Tested By : James Gan

EUT : Portable Bluetooth Speaker

Model Number : BOOMBOX 3

Power Supply : Battery


Test Mode : Tx Mode

Condition : Temp:22.8°C,Humi:55.6%,Press:100.3kPa

Antenna/Distance : 2022 9161 #3/3m/HORIZONTAL

Memo : SRD (Solution B)

Data:
5



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	31.96	8.93	11.10	3.56	23.59	40.00	-16.41	QP	HORIZONTAL
2	56.79	4.35	11.48	3.73	19.56	40.00	-20.44	QP	HORIZONTAL
3	167.82	2.96	19.50	4.33	26.79	43.50	-16.71	QP	HORIZONTAL
4	407.51	1.59	15.80	5.18	22.57	46.00	-23.43	QP	HORIZONTAL
5	699.31	2.84	20.10	5.99	28.93	46.00	-17.07	QP	HORIZONTAL
6	982.62	2.40	23.80	6.75	32.95	54.00	-21.05	QP	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 3#

D:\E3 6.111\2022 Report Data\Q22071424-2E JBL
BOOMBOX3\B\FCC BELOW 1G.EM6

Test Date : 2022-08-09

Tested By : James Gan

EUT : Portable Bluetooth Speaker

Model Number : BOOMBOX 3


Power Supply : Battery

Test Mode : Tx Mode

Condition : Temp:22.8°C,Humi:55.6%,Press:100.3kPa Antenna/Distance : 2022 9161 #3/3m/VERTICAL

Memo : SRD (Solution B)

Data:
6



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	32.75	11.72	11.25	3.57	26.54	40.00	-13.46	QP	VERTICAL
2	50.76	14.20	11.77	3.68	29.65	40.00	-10.35	QP	VERTICAL
3	169.60	3.24	19.40	4.34	26.98	43.50	-16.52	QP	VERTICAL
4	462.35	3.19	17.20	5.36	25.75	46.00	-20.25	QP	VERTICAL
5	636.13	3.95	19.82	5.83	29.60	46.00	-16.40	QP	VERTICAL
6	965.54	4.15	23.62	6.66	34.43	54.00	-19.57	QP	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 3#

D:\E3 6.111\2022 Report Data\Q22071424-2E JBL
BOOMBOX3\FCC BELOW 1G.EM6

Test Date : 2022-07-21

Tested By : Bairong

EUT : Portable Bluetooth Speaker

Model Number : BOOMBOX 3

Power Supply : Battery


Test Mode : Tx Mode

Condition : Temp:22.6°C,Humi:62.3%,Press:100.1kPa

Antenna/Distance : 2022 9161 #3/3m/HORIZONTAL

Memo : SRD (Solution C)

Data:
5



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	37.16	3.84	11.92	3.60	19.36	40.00	-20.64	QP	HORIZONTAL
2	58.41	4.20	11.64	3.74	19.58	40.00	-20.42	QP	HORIZONTAL
3	164.33	1.51	19.50	4.32	25.33	43.50	-18.17	QP	HORIZONTAL
4	284.98	1.47	12.80	4.77	19.04	46.00	-26.96	QP	HORIZONTAL
5	642.86	1.94	19.90	5.84	27.68	46.00	-18.32	QP	HORIZONTAL
6	942.13	3.38	23.24	6.56	33.18	46.00	-12.82	QP	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 3#

D:\E3 6.111\2022 Report Data\Q22071424-2E JBL BOOMBOX3\FCC BELOW 1G.EM6

Test Date : 2022-07-21

Tested By : Bairong

EUT : Portable Bluetooth Speaker

Model Number : BOOMBOX 3


Power Supply : Battery

Test Mode : Tx Mode

Condition : Temp:22.6°C,Humi:62.3%,Press:100.1kPa Antenna/Distance : 2022 9161 #3/3m/VERTICAL

Memo : SRD (Solution C)

Data:
6



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	43.97	0.17	12.80	3.64	16.61	40.00	-23.39	QP	VERTICAL
2	141.83	0.66	16.82	4.22	21.70	43.50	-21.80	QP	VERTICAL
3	166.65	2.38	19.50	4.33	26.21	43.50	-17.29	QP	VERTICAL
4	307.83	0.47	13.10	4.85	18.42	46.00	-27.58	QP	VERTICAL
5	640.61	1.46	19.90	5.84	27.20	46.00	-18.80	QP	VERTICAL
6	965.54	1.44	23.62	6.66	31.72	54.00	-22.28	QP	VERTICAL


Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

5. Power Line Conducted Emission

5.1. Block diagram of test setup



5.2. Power line conducted emission limits

Frequency	Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150 kHz ~ 500 kHz	66 ~ 56*	56 ~ 46*
500 kHz ~ 5 MHz	56	46
5 MHz ~ 30 MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

5.3. Test procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

- Configuration EUT to simulate typical usage as described in clause 2.4 and test equipment as described in clause 10.2 of this report.

All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

5.4. Test result

Pass. (See below detailed test result)

Note1: All emissions not reported below are too low against the prescribed limits.


Note2: "----" means Peak detection; "----" means Average detection.

Note3: Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/50Hz, recorded worse case.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room **D:\2022 CE report date\Q22071424-2E BB3\A\FCC.EM6**
Test Date : 2022-08-10 **Tested By** : James Gan
EUT : Portable Bluetooth Speaker **Model Number** : BOOMBOX 3
Power Supply : AC 120V/60Hz **Test Mode** : TX
Condition : TEMP:23.3°C, RH:51.6.0%,
BP:100.3kPa **LISN** : 2021 1# ENV216/LINE
Memo : SRD (Solution A)

Data: 6



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Over Limit (dB)	Detector	Phase
1	0.18	3.58	9.71	0.01	9.92	23.22	64.64	-41.42	QP	LINE
2	0.18	-14.64	9.71	0.01	9.92	5.00	54.64	-49.64	Average	LINE
3	0.24	-0.23	9.76	0.02	9.92	19.47	62.26	-42.79	QP	LINE
4	0.24	-16.30	9.76	0.02	9.92	3.40	52.26	-48.86	Average	LINE
5	0.55	-6.62	9.57	0.02	9.91	12.88	56.00	-43.12	QP	LINE
6	0.55	-14.79	9.57	0.02	9.91	4.71	46.00	-41.29	Average	LINE
7	4.57	-3.70	9.58	0.06	9.92	15.86	56.00	-40.14	QP	LINE
8	4.57	-13.46	9.58	0.06	9.92	6.10	46.00	-39.90	Average	LINE
9	21.72	-4.90	9.62	0.18	9.97	14.87	60.00	-45.13	QP	LINE
10	21.72	-14.08	9.62	0.18	9.97	5.69	50.00	-44.31	Average	LINE
11	27.56	-3.24	9.68	0.20	9.99	16.63	60.00	-43.37	QP	LINE
12	27.56	-10.73	9.68	0.20	9.99	9.14	50.00	-40.86	Average	LINE


Note:

1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room **D:\2022 CE report date\Q22071424-2E BB3\A\FCC.EM6**
Test Date : 2022-08-10 **Tested By** : James Gan
EUT : Portable Bluetooth Speaker **Model Number** : BOOMBOX 3
Power Supply : AC 120V/60Hz **Test Mode** : TX
Condition : TEMP:23.3°C, RH:51.6.0%,
BP:100.3kPa **LISN** : 2021 1# ENV216/NEUTRAL
Memo : SRD (Solution A)

Data: 12



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Over Limit (dB)	Detector	Phase
1	0.15	5.66	9.80	0.01	9.92	25.39	65.74	-40.35	QP	NEUTRAL
2	0.15	-12.11	9.80	0.01	9.92	7.62	55.74	-48.12	Average	NEUTRAL
3	0.23	1.12	9.75	0.02	9.92	20.81	62.35	-41.54	QP	NEUTRAL
4	0.23	-14.00	9.75	0.02	9.92	5.69	52.35	-46.66	Average	NEUTRAL
5	0.55	-6.65	9.59	0.02	9.91	12.87	56.00	-43.13	QP	NEUTRAL
6	0.55	-15.39	9.59	0.02	9.91	4.13	46.00	-41.87	Average	NEUTRAL
7	4.53	-3.67	9.76	0.06	9.92	16.07	56.00	-39.93	QP	NEUTRAL
8	4.53	-14.54	9.76	0.06	9.92	5.20	46.00	-40.80	Average	NEUTRAL
9	8.68	-5.87	9.72	0.10	9.94	13.89	60.00	-46.11	QP	NEUTRAL
10	8.68	-17.73	9.72	0.10	9.94	2.03	50.00	-47.97	Average	NEUTRAL
11	28.00	-3.05	9.88	0.20	9.99	17.02	60.00	-42.98	QP	NEUTRAL
12	28.00	-10.45	9.88	0.20	9.99	9.62	50.00	-40.38	Average	NEUTRAL


Note:

1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room **D:\2022 CE report date\Q22071424-2E BB3\B\FCC.EM6**
Test Date : 2022-08-10 **Tested By** : James Gan
EUT : Portable Bluetooth Speaker **Model Number** : BOOMBOX 3
Power Supply : AC 120V/60Hz **Test Mode** : TX
Condition : TEMP:23.3°C, RH:51.6.0%,
BP:100.3kPa **LISN** : 2021 1# ENV216/NEUTRAL
Memo : SRD (Solution B)

Data: 6



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Over Limit (dB)	Detector	Phase
1	0.18	17.33	9.80	0.01	9.92	37.06	64.33	-27.27	QP	NEUTRAL
2	0.18	1.78	9.80	0.01	9.92	21.51	54.33	-32.82	Average	NEUTRAL
3	0.34	6.98	9.62	0.02	9.91	26.53	59.13	-32.60	QP	NEUTRAL
4	0.34	1.39	9.62	0.02	9.91	20.94	49.13	-28.19	Average	NEUTRAL
5	0.39	13.31	9.59	0.02	9.91	32.83	58.17	-25.34	QP	NEUTRAL
6	0.39	9.25	9.59	0.02	9.91	28.77	48.17	-19.40	Average	NEUTRAL
7	0.76	2.64	9.78	0.03	9.91	22.36	56.00	-33.64	QP	NEUTRAL
8	0.76	-3.77	9.78	0.03	9.91	15.95	46.00	-30.05	Average	NEUTRAL
9	8.68	-4.31	9.72	0.10	9.94	15.45	60.00	-44.55	QP	NEUTRAL
10	8.68	-12.79	9.72	0.10	9.94	6.97	50.00	-43.03	Average	NEUTRAL
11	19.43	2.03	9.78	0.17	9.96	21.94	60.00	-38.06	QP	NEUTRAL
12	19.43	-6.02	9.78	0.17	9.96	13.89	50.00	-36.11	Average	NEUTRAL

Note:

1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room

D:\2022 CE report date\Q22071424-2E BB3\B\FCC.EM6

Test Date : 2022-08-10

Tested By : James Gan

EUT : Portable Bluetooth Speaker

Model Number : BOOMBOX 3

Power Supply : AC 120V/60Hz


Test Mode : TX

Condition : TEMP:23.3°C, RH:51.6.0%,
BP:100.3kPa

LISN : 2021 1# ENV216/LINE

Memo : SRD (Solution B)

Data: 8



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Over Limit (dB)	Detector	Phase
1	0.18	17.49	9.74	0.01	9.92	37.16	64.33	-27.17	QP	LINE
2	0.18	2.79	9.74	0.01	9.92	22.46	54.33	-31.87	Average	LINE
3	0.34	9.47	9.68	0.02	9.91	29.08	59.09	-30.01	QP	LINE
4	0.34	5.50	9.68	0.02	9.91	25.11	49.09	-23.98	Average	LINE
5	0.39	12.75	9.66	0.02	9.91	32.34	58.17	-25.83	QP	LINE
6	0.39	9.55	9.66	0.02	9.91	29.14	48.17	-19.03	Average	LINE
7	2.30	-3.22	9.52	0.05	9.90	16.25	56.00	-39.75	QP	LINE
8	2.30	-6.97	9.52	0.05	9.90	12.50	46.00	-33.50	Average	LINE
9	13.27	-3.32	9.71	0.13	9.93	16.45	60.00	-43.55	QP	LINE
10	13.27	-9.83	9.71	0.13	9.93	9.94	50.00	-40.06	Average	LINE
11	25.86	0.15	9.66	0.19	9.99	19.99	60.00	-40.01	QP	LINE
12	25.86	-6.49	9.66	0.19	9.99	13.35	50.00	-36.65	Average	LINE


Note:

1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room **D:\2022 CE report date\Q22071424-2E BB3\FCC.EM6**
Test Date : 2022-07-27 **Tested By** : Bairong
EUT : Portable Bluetooth Speaker **Model Number** : BOOMBOX 3
Power Supply : AC 120V/60Hz **Test Mode** : TX
Condition : TEMP:23.8°C, RH:62.0%, BP:101.2kPa **LISN** : 2021 1# ENV216/LINE
Memo : SRD (Solution C)

Data: 6



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Over Limit (dB)	Detector	Phase
1	0.17	7.92	9.67	0.01	9.92	27.52	65.21	-37.69	QP	LINE
2	0.17	-13.61	9.67	0.01	9.92	5.99	55.21	-49.22	Average	LINE
3	0.22	5.11	9.78	0.01	9.92	24.82	62.88	-38.06	QP	LINE
4	0.22	-13.95	9.78	0.01	9.92	5.76	52.88	-47.12	Average	LINE
5	0.40	4.07	9.65	0.02	9.91	23.65	57.90	-34.25	QP	LINE
6	0.40	-9.84	9.65	0.02	9.91	9.74	47.90	-38.16	Average	LINE
7	0.55	-2.77	9.57	0.02	9.91	16.73	56.00	-39.27	QP	LINE
8	0.55	-13.52	9.57	0.02	9.91	5.98	46.00	-40.02	Average	LINE
9	4.55	-5.87	9.58	0.06	9.92	13.69	56.00	-42.31	QP	LINE
10	4.55	-15.08	9.58	0.06	9.92	4.48	46.00	-41.52	Average	LINE
11	7.57	-5.73	9.50	0.09	9.94	13.80	60.00	-46.20	QP	LINE
12	7.57	-17.14	9.50	0.09	9.94	2.39	50.00	-47.61	Average	LINE


Note:

1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room **D:\2022 CE report date\Q22071424-2E BB3\FCC.EM6**
Test Date : 2022-07-27 **Tested By** : Bairong
EUT : Portable Bluetooth Speaker **Model Number** : BOOMBOX 3
Power Supply : AC 120V/60Hz **Test Mode** : TX
Condition : TEMP:23.8°C, RH:62.0%, BP:101.2kPa **LISN** : 2021 1# ENV216/NEUTRAL
Memo : SRD (Solution C)

Data: 12



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Over Limit (dB)	Detector	Phase
1	0.17	8.29	9.80	0.01	9.92	28.02	64.81	-36.79	QP	NEUTRAL
2	0.17	-13.80	9.80	0.01	9.92	5.93	54.81	-48.88	Average	NEUTRAL
3	0.40	1.26	9.58	0.02	9.91	20.77	57.95	-37.18	QP	NEUTRAL
4	0.40	-13.41	9.58	0.02	9.91	6.10	47.95	-41.85	Average	NEUTRAL
5	0.54	-5.30	9.57	0.02	9.91	14.20	56.00	-41.80	QP	NEUTRAL
6	0.54	-14.59	9.57	0.02	9.91	4.91	46.00	-41.09	Average	NEUTRAL
7	2.99	-10.50	9.72	0.05	9.91	9.18	56.00	-46.82	QP	NEUTRAL
8	2.99	-18.34	9.72	0.05	9.91	1.34	46.00	-44.66	Average	NEUTRAL
9	4.38	-8.27	9.77	0.06	9.92	11.48	56.00	-44.52	QP	NEUTRAL
10	4.38	-16.62	9.77	0.06	9.92	3.13	46.00	-42.87	Average	NEUTRAL
11	8.68	-9.55	9.72	0.10	9.94	10.21	60.00	-49.79	QP	NEUTRAL
12	8.68	-18.91	9.72	0.10	9.94	0.85	50.00	-49.15	Average	NEUTRAL

Note:

1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.