

Left Earphone 2DH5 2441MHz Back side 0mm

Communication System: UID 0, BT(0) (0); Communication System Band: BT; Frequency: 2441 MHz;

Medium parameters used: $f = 2441$ MHz; $\sigma = 1.81$ S/m; $\epsilon_r = 40.78$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- Probe: EX3DV4 - SN7383; ConvF(7.75, 7.75, 7.75); Calibrated: 2020/11/30;
- Sensor-Surface: 3mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE3 Sn427; Calibrated: 2021/4/9
- Phantom: SAM; Type: QD000P40CD; Serial: 1805
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Head/Area Scan (12x12x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 0.0120 W/kg

Configuration/Head/Zoom Scan (8x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm,

$dz=5$ mm

Reference Value = 1.748 V/m; Power Drift = -0.19 dB

Peak SAR (extrapolated) = 0.0350 W/kg

SAR(1 g) = 0.00952 W/kg; SAR(10 g) = 0.00553 W/kg

Maximum value of SAR (measured) = 0.0131 W/kg

