






## TEST REPORT

<b>Report No.:</b>	<b>EM201400094-5</b>	<b>Application No.:</b>	<b>ZJ00040895</b>
<b>Client:</b>	Harman International Industries, Incorporated		
<b>Address:</b>	8500 Balboa Blvd, Northridge, CA 91329, United States		
<b>Sample Description:</b>	Bluetooth headset		
<b>Model:</b>	REFLECT BT		
<b>Adding Model:</b>	/		
<b>FCC ID</b>	APIREFLECTBT		
<b>Test Specification:</b>	FCC Part 15,Subpart C:2012		
<b>Test Date:</b>	2014-02-25 to 2014-03-10		
<b>Issue Date:</b>	2014-03-11		
<b>Test Result:</b>	<i>Pass.</i>		
<b>Prepared By:</b>	<b>Reviewed By:</b>	<b>Approved By:</b>	
Lynn Xiao / Test Engineer	Jane Cao / Technical Manager	Gavin Wu / Manager	
			
Date:2014-03-11	Date:2014-03-11	Date:2014-03-11	
<b>Other Aspects:</b>			
/			
<b>Abbreviations:</b> ok / P = passed; fail / F = failed; n.a. / N = not applicable			
The test result in this test report refers exclusively to the presented test sample. This report shall not be reproduced except in full, without the written approval of GRGT.			

## **DIRECTIONS OF TEST**

1. This station carries out test task according to the national regulation of verifications which can be traced to National Primary Standards and BIPM.
2. The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test result without the written permission of the test laboratory.
3. If there is any objection concerning the test, the client should inform the laboratory within 15 days from the date of receiving the test report.

## Table of Contents

<b>1. TEST RESULT SUMMARY .....</b>	<b>5</b>
<b>2. GENERAL DESCRIPTION OF EUT .....</b>	<b>6</b>
2.1 APPLICANT .....	6
2.2 MANUFACTURER .....	6
2.3 BASIC DESCRIPTION OF EQUIPMENT UNDER TEST .....	6
<b>3. LABORATORY AND ACCREDITATIONS .....</b>	<b>7</b>
3.1 LABORATORY .....	7
3.2 ACCREDITATIONS .....	7
3.3 MEASUREMENT UNCERTAINTY .....	7
3.4 LIST OF USED TEST EQUIPMENT AT GRGT .....	8
<b>4. TEST RESULTS .....</b>	<b>9</b>
4.1 E.U.T. TEST CONDITIONS .....	9
4.2 ANTENNA REQUIREMENT .....	11
4.3 OCCUPIED BANDWIDTH .....	12
4.3.1 LIMITS .....	12
4.3.2 TEST PROCEDURES .....	12
4.3.3 TEST SETUP .....	12
4.3.4 TEST RESULTS .....	12
4.4 CARRIER FREQUENCIES SEPARATED .....	16
4.4.1 LIMITS .....	16
4.4.2 TEST PROCEDURES .....	16
4.4.3 TEST SETUP .....	16
4.4.4 TEST RESULTS .....	16
4.5 HOPPING CHANNEL NUMBER .....	20
4.5.1 LIMITS .....	20
4.5.2 TEST PROCEDURES .....	20
4.5.3 TEST SETUP .....	20
4.5.4 TEST RESULTS .....	20
4.6 DWELL TIME .....	22
4.6.1 LIMITS .....	22
4.6.2 TEST PROCEDURES .....	22
4.6.3 TEST SETUP .....	22
4.6.4 TEST RESULTS .....	22
4.7 CONDUCTED EMISSION MEASUREMENT .....	39
4.7.1 LIMITS .....	39
4.7.2 TEST PROCEDURES .....	39
4.7.3 TEST SETUP .....	39
4.7.4 TEST RESULTS .....	41
4.8 MAXIMUM PEAK OUTPUT POWER .....	43
4.8.1 LIMITS .....	43
4.8.2 TEST PROCEDURES .....	43
4.8.3 TEST SETUP .....	43
4.8.4 TEST RESULTS .....	43
4.9 CONDUCTED SPURIOUS EMISSIONS .....	47
4.9.1 LIMITS .....	47
4.9.2 TEST PROCEDURES .....	47
4.9.3 TEST SETUP .....	47
4.9.4 TEST RESULTS .....	47
4.10 RADIATED SPURIOUS EMISSIONS .....	57
4.10.1 LIMITS .....	57
4.10.2 TEST PROCEDURES .....	57
4.10.3 TEST SETUP .....	58
4.10.4 TEST RESULTS .....	60
4.11 BAND EDGES REQUIREMENT .....	66
4.11.1 LIMITS .....	66
4.11.2 TEST PROCEDURES .....	66
4.11.3 TEST SETUP .....	66

4.11.4 TEST RESULTS .....66  
4.11.5 Radiated Emissions which fall in the restricted bands .....70

**1. TEST RESULT SUMMARY**

<b>FCC Part 15.247:2012</b>			
<b>Standard</b>	<b>Item</b>	<b>Limit / Severity</b>	<b>Result</b>
FCC Part 15,Subpart C (15.247)	Antenna Requirement	Section 15.247 (c)	PASS
	Occupied Bandwidth	Section 15.247 (a1)	PASS
	Carrier Frequencies Separated	Section 15.247(a)(1)	PASS
	Hopping Channel Number	Section 15.247(a)(1)(iii)	PASS
	Dwell Time	Section 15.247(a)(1)(iii)	PASS
	Maximum Peak Output Power	Section 15.247(b)(1)	PASS
	Conducted Emission	Section 15.207	PASS
	Conducted Spurious Emission (30MHz to 25GHz)	Section 15.209 &15.247(d)	PASS
	Radiated Spurious Emission (30MHz to 25GHz)	Section 15.209 &15.247(d)	PASS
	Band Edges Measurement	Section 15.247 (d) &15.205	PASS

## 2. GENERAL DESCRIPTION OF EUT

### 2.1 APPLICANT

Name: Harman International Industries, Incorporated  
Address: 8500 Balboa Blvd, Northridge, CA 91329, United States

### 2.2 MANUFACTURER

Name: Harman International Industries, Incorporated  
Address: 8500 Balboa Blvd, Northridge, CA 91329, United States

### 2.3 BASIC DESCRIPTION OF EQUIPMENT UNDER TEST

Equipment: Bluetooth headset  
Model No.: REFLECT BT  
Trade Name: JBL  
Power supply: B 1S1P/70mAh/4.2+/-0.05V  
Frequency Range 2402MHz~2480MHz  
Type of Modulation GFSK, 8DPSK, Pi/4 QPSK  
Channels: Channels with 1MHz step  
Antenna Type PCB antenna  
Antenna gain 5dBi

### 3. LABORATORY AND ACCREDITATIONS

#### 3.1 LABORATORY

The tests and measurements refer to this report were performed by Guangzhou GRG Metrology and Test CO., LTD.

Add. : 163 Pingyun Rd, West of Huangpu Ave, Guangzhou, 510656, P. R. China

Telephone: +86-20-38699959, 38699960, 38699961

Fax : +86-20-38695185

#### 3.2 ACCREDITATIONS

Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

<b>USA</b>	FCC Listed Lab (No. 688188)
<b>China</b>	CNAS (No.L0446)
<b>China</b>	DILAC (No.DL175)
<b>Canada</b>	Registration No.:8355A-1

#### 3.3 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement		Frequency	Uncertainty
Radiated Emission	Horizontal	30MHz~1000MHz	4.2dB
		1GHz~26.5GHz	4.2dB
	Vertical	30MHz~1000MHz	4.4dB
		1GHz~26.5GHz	4.4dB
Conducted Emission		9kHz~30MHz	3.1 dB

This uncertainty represents an expanded uncertainty factor of  $k=2$ .

**3.4 LIST OF USED TEST EQUIPMENT AT GRGT**

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
<b>Conducted Emissions</b>				
EMI Receiver	R&S	ESCI	100529	2014-07-21
L.I.S.N	SCHWARZBECK	NSLK 8127	8127450	2014-08-05
<b>Spurious Emissions at Antenna Port</b>				
Receiver	R&S	ESU40	100106	2015-01-26
<b>Restricted Bands</b>				
Receiver	R&S	ESU40	100106	2015-01-26
<b>Spurious Emissions</b>				
Receiver	R&S	ESU40	100106	2015-01-26
Signal Generator	R&S	SML03	103002	2014-11-13
Biconical Log-periodic Antenna	ETS.LINDGREN	3142C	00075971	2014-05-26
Horn antenna	SCHWARZBECK	BBHA9120D	D752	2014-10-14
<b>6 dB Bandwidth</b>				
Receiver	R&S	ESU40	100106	2015-01-26
<b>Maximum Peak Output Power</b>				
Receiver	R&S	ESU40	100106	2015-01-26
<b>100kHz Bandwidth of Frequency Band Edge</b>				
Receiver	R&S	ESU40	100106	2015-01-26
<b>Power Spectral Density</b>				
Receiver	R&S	ESU40	100106	2015-01-26

## 4. TEST RESULTS

### 4.1 E.U.T. TEST CONDITIONS

**Type of antenna:** Integral

**Temperature:** 22.0 °C

**Humidity:** 54 % RH

**Atmospheric Pressure:** 1011 mbar

**Test frequencies:** According to the 15.31(m) Measurements on intentional radiators or receivers, other than TV broadcast receivers, shall be performed and, if required, reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table:

Frequency range over which device operates	Number of frequencies	Location in the range of operation
1 MHz or less	1	Middle
1 to 10 MHz	2	1 near top and 1 near bottom
More than 10 MHz	3	1 near top, 1 near middle and 1 near bottom

#### EUT channels and frequencies list:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	14	2416	28	2430
1	2403	15	2417	29	2431
2	2404	16	2418	30	2432
3	2405	17	2419	31	2433
4	2406	18	2420	32	2434
5	2407	19	2421	33	2435
6	2408	20	2422	34	2436
7	2409	21	2423	35	2437
8	2410	22	2424	36	2438
9	2411	23	2425	37	2439
10	2412	24	2426	38	2440
11	2413	25	2427	39	2441
12	2414	26	2428	40	2442
13	2415	27	2429	41	2443

<b>Channel</b>	<b>Frequency (MHz)</b>	<b>Channel</b>	<b>Frequency (MHz)</b>	<b>Channel</b>	<b>Frequency (MHz)</b>
42	2444	55	2457	68	2470
43	2445	56	2458	69	2471
44	2446	57	2459	70	2472
45	2447	58	2460	71	2473
46	2448	59	2461	72	2474
47	2449	60	2462	73	2475
48	2450	61	2463	74	2476
49	2451	62	2464	75	2477
50	2452	63	2465	76	2478
51	2453	64	2466	77	2479
52	2454	65	2467	78	2480
53	2455	66	2468		
54	2456	67	2469		

Test frequency is the lowest channel: 0 channel(2402MHz), middle channel: 39 channel(2441MHz) and highest channel: 78 channel(2480MHz)

## **4.2 ANTENNA REQUIREMENT**

The EUT antenna is PCB antenna. Max Antenna gain is 5dBi .which accordance 15.203.is considered sufficient to comply with the provisions of this section

### 4.3 OCCUPIED BANDWIDTH

#### 4.3.1 LIMITS

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.


#### 4.3.2 TEST PROCEDURES

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: Span = approximately 2 to 3 times the 20dB bandwidth, centre on a hopping channel;
3. Set the spectrum analyzer: RBW  $\geq$  1% of the 20dB bandwidth (set 100 kHz). VBW  $\geq$  RBW. Sweep = auto; Detector Function = Peak. Trace = Max Hold.
4. Mark the peak frequency and -20dB bandwidth.
5. Bandwidth value is OBW value.

**Remark:**

Pre-test the 3 modulation to find GFSK and 8DPSK is worse case, so only record GFSK and 8DPSK test data.

#### 4.3.3 TEST SETUP



#### 4.3.4 TEST RESULTS

**For GFSK**


Frequency (GHz)	Test Channel	bandwidth
2.402	Lowest	1.14MHz
2.441	Middle	1.13MHz
2.480	Highest	1.13MHz

**For 8DPSK**


Frequency (GHz)	Test Channel	bandwidth
2.402	Lowest	1.34MHz
2.441	Middle	1.35MHz
2.480	Highest	1.36MHz

Result plot as follows:


### GFSK Lowest Channel:




### GFSK Middle Channel:




### GFSK Highest Channel:




### 8DPSK Lowest Channel:



### 8DPSK Middle Channel:



### 8DPSK Highest Channel:



## 4.4 CARRIER FREQUENCIES SEPARATED

### 4.4.1 LIMITS

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.


### 4.4.2 TEST PROCEDURES

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW  $\geq$  1% of the span (set 100 kHz). VBW  $\geq$  RBW, Span = 3MHz. Sweep = auto; Detector Function = Peak. Trace = Max, hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.

**Remark :**

Pre-test the 3 modulation to find GFSK and 8DPSK is worse case, so only record GFSK and 8DPSK test data.

### 4.4.3 TEST SETUP




### 4.4.4 TEST RESULTS


Mode	Test Channel	Carrier Frequencies Separated	2/3 20 dB bandwidth	PASS/FAIL
GFSK	Lower Channels (channel 0 and channel 1)	1.005MHz	0.76MHz	Pass
	Middle Channels (channel 39 and channel 40)	1.005MHz	0.75MHz	Pass
	Upper Channels (channel 77 and channel 78)	1.005MHz	0.75MHz	Pass
8DPSK	Lower Channels (channel 0 and channel 1)	1.005MHz	0.89MHz	Pass
	Middle Channels (channel 39 and channel 40)	1.005MHz	0.90MHz	Pass
	Upper Channels (channel 77 and channel 78)	1.005MHz	0.91MHz	Pass

Result plot as follows:


GFSK Lowest Channels:




GFSK Middle Channels:




GFSK Highest Channels:




8DPSK Lowest Channels:



8DPSK Middle Channels:



8DPSK Highest Channels:



Test result: The unit does meet the FCC requirements.

## 4.5 HOPPING CHANNEL NUMBER


### 4.5.1 LIMITS

Regulation 15.247 (a) (1)(iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

### 4.5.2 TEST PROCEDURES

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 100 kHz. VBW = 100 kHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. It may prove necessary to break the span up to sections. in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section.
4. Set the spectrum analyzer: start frequency = 2400MHz. stop frequency = 2483.5MHz. Submit the test result graph.



### 4.5.3 TEST SETUP



### 4.5.4 TEST RESULTS

**Test result:** Total channels are 79 channels.

Result plot as follows:



**Test result: The unit does meet the FCC requirements.**

## 4.6 DWELL TIME


### 4.6.1 LIMITS

Regulation 15.247(a)(1)(iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

### 4.6.2 TEST PROCEDURES

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set spectrum analyzer span = 0. centered on a hopping channel;
3. Set RBW = 1MHz and VBW = 3MHz.Sweep = as necessary to capture the entire dwell time per hopping channel. Detector Function = Peak. Trace = Max hold;
4. Use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g.. data rate. modulation format. etc.). Repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s). An oscilloscope may be used instead of a spectrum analyzer.

### 4.6.3 TEST SETUP



### 4.6.4 TEST RESULTS

The test period:  $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

#### 1. Channel 0: 2.402GHz

DH1	time slot=	0.389	(ms)*	$(1600/(2*79))$	*	31.6	=	124.5	ms
DH3	time slot=	1.660	(ms)*	$(1600/(4*79))$	*	31.6	=	265.6	ms
DH5	time slot=	2.904	(ms)*	$(1600/(6*79))$	*	31.6	=	309.8	ms
2DH1	time slot=	0.404	(ms)*	$(1600/(2*79))$	*	31.6	=	129.3	ms
2DH3	time slot=	1.660	(ms)*	$(1600/(4*79))$	*	31.6	=	265.6	ms
2DH5	time slot=	2.917	(ms)*	$(1600/(6*79))$	*	31.6	=	311.1	ms
3DH1	time slot=	0.404	(ms)*	$(1600/(2*79))$	*	31.6	=	129.3	ms
3DH3	time slot=	1.660	(ms)*	$(1600/(4*79))$	*	31.6	=	265.6	ms
3DH5	time slot=	2.917	(ms)*	$(1600/(6*79))$	*	31.6	=	311.1	ms

**2. Channel 39: 2.441GHz**

DH1	time slot=	0.390	(ms)*	(1600/(2*79))	*	31.6	=	124.8	ms
DH3	time slot=	1.648	(ms)*	(1600/(4*79))	*	31.6	=	263.7	ms
DH5	time slot=	2.892	(ms)*	(1600/(6*79))	*	31.6	=	308.5	ms

2DH1	time slot=	0.405	(ms)*	(1600/(2*79))	*	31.6	=	129.6	ms
2DH3	time slot=	1.648	(ms)*	(1600/(4*79))	*	31.6	=	263.7	ms
2DH5	time slot=	2.917	(ms)*	(1600/(6*79))	*	31.6	=	311.1	ms

3DH1	time slot=	0.405	(ms)*	(1600/(2*79))	*	31.6	=	129.6	ms
3DH3	time slot=	1.667	(ms)*	(1600/(4*79))	*	31.6	=	266.7	ms
3DH5	time slot=	2.910	(ms)*	(1600/(6*79))	*	31.6	=	310.4	ms

**3. Channel 78: 2.480GHz**

DH1	time slot=	0.393	(ms)*	(1600/(2*79))	*	31.6	=	125.8	ms
DH3	time slot=	1.653	(ms)*	(1600/(4*79))	*	31.6	=	264.5	ms
DH5	time slot=	2.897	(ms)*	(1600/(6*79))	*	31.6	=	309.0	ms

2DH1	time slot=	0.401	(ms)*	(1600/(2*79))	*	31.6	=	128.3	ms
2DH3	time slot=	1.666	(ms)*	(1600/(4*79))	*	31.6	=	266.6	ms
2DH5	time slot=	2.909	(ms)*	(1600/(6*79))	*	31.6	=	310.3	ms


3DH1	time slot=	0.409	(ms)*	(1600/(2*79))	*	31.6	=	130.9	ms
3DH3	time slot=	1.667	(ms)*	(1600/(4*79))	*	31.6	=	266.7	ms
3DH5	time slot=	2.922	(ms)*	(1600/(6*79))	*	31.6	=	311.7	ms

**The results are not greater than 0.4 seconds.  
The unit does meet the requirements.**


Please refer the graph as below:

1. Lowest channel (2.402 GHz):


DH1




DH3:



DH5:




2DH1



2DH3




1 PK  
MAXH




2DH5




1 PK  
MAXH




3DH1



3DH3




3DH5




2. Middle Channel (2.441GHz)


DH1




DH3




DH5




2DH1



2DH3



2DH5






3DH5




RBW 1 MHz      Delta 3 [T1 ]  
\*V BW 3 MHz      -0.01 dB  
SWT 8 ms      3.769231 ms

Ref 20 dBm      \*Att 40 dB




3. Highest channel (2.480GHz)


DH1




DH3




DH5




2DH1




2DH3




2DH5




3DH1



3DH3



3DH5



## 4.7 CONDUCTED EMISSION MEASUREMENT

### 4.7.1 LIMITS

Frequency range	Limits (dB $\mu$ V)	
	Quasi-peak	Average
150kHz ~ 0.5MHz	66~56	56~46
0.5 MHz ~ 5 MHz	56	46
5 MHz ~ 30 MHz	60	50

### 4.7.2 TEST PROCEDURES

#### Procedure of Preliminary Test

For measurement of the disturbance voltage the equipment under test (EUT) is connected to the power supply mains and any other extended network via one or more artificial network(s). An EUT, whether intended to be grounded or not, and which is to be used on a table is configured as follows:


- Either the bottom or the rear of the EUT shall be at a controlled distance of 40 cm from a reference ground plane. This ground plane is normally the wall or floor of a shielded room. It may also be a grounded metal plane of at least 2 m by 2 m. This is physically accomplished as follows:
  - 1) Place the EUT on a table of non-conducting material which is at least 80 cm high. Place the EUT so that it is 40 cm from the wall of the shielded room, or
  - 2) place the EUT on a table of non-conducting material which is 40 cm high so that the bottom of the EUT is 40 cm above the ground plane;
- All other conductive surfaces of the EUT shall be at least 80 cm from the reference ground plane;
- The EUT are placed on the floor that one side of the housings is 40 cm from the vertical reference ground plane and other metallic parts;
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth forming a bundle 30 cm to 40 cm long, hanging approximately in the middle between the ground plane and the table.
- I/O cables that are connected to a peripheral shall be bundled in the centre. The end of the cable may be terminated if required using correct terminating impedance. The total length shall not exceed 1 m.

The test mode(s) described in Item 2.4 were scanned during the preliminary test. After the preliminary scan, we found the test mode described in Item 2.4 producing the highest emission level. The EUT configuration and cable configuration of the above highest emission levels were recorded for reference of the final test.

#### Procedure of Final Test


EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test. A scan was taken on both power lines, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. The test data of the worst-case condition(s) was recorded.

### 4.7.3 TEST SETUP




### 4.7.4 TEST RESULTS

<b>Project No.:</b>	<b>ZJ00040895</b>	<b>Probe:</b>	<b>L1</b>
<b>Standard:</b>	<b>(CE)FCC PART 15 class B_QP</b>	<b>Power Source:</b>	<b>AC 120V/60Hz</b>
<b>Test item:</b>	<b>Conduction Test</b>	<b>Date:</b>	<b>2014-2-26</b>
<b>Temp./Hum.(%RH):</b>	<b>23/57%RH</b>	<b>Time:</b>	<b>9:14:33</b>
<b>EUT:</b>	<b>Bluetooth headset</b>	<b>Test Result:</b>	<b>Pass</b>
<b>Model:</b>	<b>REFLECT BT</b>		
<b>Note:</b>			



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.3700	37.29	6.51	43.80	58.50	-14.70	QP
2	0.3700	29.39	6.51	35.90	48.50	-12.60	AVG
3	0.6100	24.71	6.49	31.20	56.00	-24.80	QP
4	0.6100	14.41	6.49	20.90	46.00	-25.10	AVG
5	1.0420	21.84	6.46	28.30	56.00	-27.70	QP
6	1.0420	11.64	6.46	18.10	46.00	-27.90	AVG
7	1.5980	22.02	6.58	28.60	56.00	-27.40	QP
8	1.5980	12.02	6.58	18.60	46.00	-27.40	AVG
9	11.8940	19.38	6.82	26.20	60.00	-33.80	QP
10	11.8940	12.58	6.82	19.40	50.00	-30.60	AVG
11	24.0020	12.37	6.93	19.30	60.00	-40.70	QP
12	24.0020	8.87	6.93	15.80	50.00	-34.20	AVG

<b>Project No.:</b>	<b>ZJ00040895</b>	<b>Probe:</b>	<b>N</b>
<b>Standard:</b>	<b>(CE)FCC PART 15 class B_QP</b>	<b>Power Source:</b>	<b>AC 120V/60Hz</b>
<b>Test item:</b>	<b>Conduction Test</b>	<b>Date:</b>	<b>2014-2-26</b>
<b>Temp./Hum.(%RH):</b>	<b>23/57%RH</b>	<b>Time:</b>	<b>9:07:33</b>
<b>EUT:</b>	<b>Bluetooth headset</b>	<b>Test Result:</b>	<b>Pass</b>
<b>Model:</b>	<b>REFLECT BT</b>		
<b>Note:</b>			



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.3700	35.19	6.51	41.70	58.50	-16.80	QP
2	0.3700	29.39	6.51	35.90	48.50	-12.60	AVG
3	0.6060	22.71	6.49	29.20	56.00	-26.80	QP
4	0.6060	14.81	6.49	21.30	46.00	-24.70	AVG
5	0.6700	22.82	6.48	29.30	56.00	-26.70	QP
6	0.6700	16.62	6.48	23.10	46.00	-22.90	AVG
7	1.5740	20.02	6.58	26.60	56.00	-29.40	QP
8	1.5740	11.62	6.58	18.20	46.00	-27.80	AVG
9	11.5540	23.14	6.76	29.90	60.00	-30.10	QP
10	11.5540	15.44	6.76	22.20	50.00	-27.80	AVG
11	24.0020	15.17	6.93	22.10	60.00	-37.90	QP
12	24.0020	12.57	6.93	19.50	50.00	-30.50	AVG

## 4.8 MAXIMUM PEAK OUTPUT POWER

### 4.8.1 LIMITS

Regulation 15.247 (b)(1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts. Refer to the result "Hopping channel number" of this document. The 1 watt (30.0dBm) limit applies.


### 4.8.2 TEST PROCEDURES

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3 MHz. VBW = 3 MHz. Sweep = auto; Detector Function = Peak.
3. Keep the EUT in transmitting at lowest, medium and highest channel individually. Record the max value.

#### Remark:

1. Pre-test the 3 modulation to find GFSK and 8DPSK is worse case, so only record GFSK and 8DPSK test data.
2. Cable loss = 1.5dB, the receiver offset loss 1.5dB

### 4.8.3 TEST SETUP



### 4.8.4 TEST RESULTS

For GFSK:

Test Channel	Fundamental Frequency (GHz)	Max Output Power(dBm)	Limit (dBm)	Pass/Fail
Lowest	2.402	4.38	30.0	Pass
Middle	2.441	4.44	30.0	Pass
Highest	2.480	4.93	30.0	Pass


For 8DPSK:

Test Channel	Fundamental Frequency (GHz)	Max Output Power(dBm)	Limit (dBm)	Pass/Fail
Lowest	2.402	3.62	30.0	Pass
Middle	2.441	4.01	30.0	Pass
Highest	2.480	4.56	30.0	Pass


Test result: The unit does meet the FCC requirements.

Test result plot as follows:


GFSK Lowest Channel:




GFSK Middle Channel:




GFSK Highest Channel:




8DPSK Lowest Channel:



8DPSK Middle Channel:



8DPSK Highest Channel:



## 4.9 CONDUCTED SPURIOUS EMISSIONS

### 4.9.1 LIMITS

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating. The radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. based on either an RF conducted or a radiated measurement. Provided the transmitter demonstrates compliance with the peak conducted power limits.


### 4.9.2 TEST PROCEDURES

Remove the antenna from the EUT and then connect a low attenuation cable from the antenna port to the spectrum.

Below 1GHz Set the spectrum analyzer: RBW =100KHz VBW  $\geq$  RBW, Span = enough to catch the trace. Sweep = auto; Detector Function = Peak. Trace = Max, hold.

Above 1GHz Set the spectrum analyzer: RBW =1MHz VBW  $\geq$  RBW, Span = enough to catch the trace. Sweep = auto; Detector Function = Peak. Trace = Max, hold.

### 4.9.3 TEST SETUP



### 4.9.4 TEST RESULTS


**The unit does meet the FCC requirements.**

Test result plot as follows:


For GFSK

Lowest Channel:


30M to 1GHz



1G to 10GHz




10G to 25GHz




Middle Channel:


30M to 1GHz



1G to 10GHz




10G to 25GHz




Highest Channel:


30M to 1GHz



1G to 10GHz




10G to 25GHz




For 8DPSK

Lowest Channel:


30M to 1GHz



1G to 10GHz




10G to 25GHz




Middle Channel:


30M to 1GHz



1G to 10GHz




10G to 25GHz




Highest Channel


30M to 1GHz



1G to 10GHz



10G to 25GHz



## 4.10 RADIATED SPURIOUS EMISSIONS

### 4.10.1 LIMITS

Frequency (MHz)	Quasi-peak( $\mu\text{V}/\text{m}$ )	Measurement distance(m)	Quasi-peak( $\text{dB}\mu\text{V}/\text{m}$ )@distance 3m
0.009-0.490	2400/F(kHz)	300	53.8~88.5
0.490-1.705	24000/F(kHz)	30	43~53.8
1.705-30.0	30	30	49.5
30 ~ 88	100	3	40
88~216	150	3	43.5
216 ~ 960	200	3	46
Above 960	500	3	54

NOTE: (1) The lower limit shall apply at the transition frequencies.

Frequency (GHz)	Quasi-peak( $\text{dB}\mu\text{V}/\text{m}$ )
1 ~ 26.5	74
1~ 26.5	54

### 4.10.2 TEST PROCEDURES

#### Procedure of Preliminary Test

According to ANSI C63.10:2009, a calibrated, linearly polarized antenna shall be positioned at the specified distance from the periphery of the EUT. The specified distance is the distance between the horizontal projection onto the ground plane of the closest periphery of the EUT and the projection onto the ground plane of the center of the axis of the elements of the receiving antenna.

Measurements shall be made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna shall be varied in height above the reference ground plane to obtain the maximum signal strength. Unless otherwise specified, the measurement distance shall be 3 m. At any measurement distance, the antenna height shall be varied from 1 m to 4 m. These height scans apply for both horizontal and vertical polarizations, except that for vertical polarization, the minimum height of the center of the antenna shall be increased so that the lowest point of the bottom of the lowest antenna element clears the site reference ground plane by at least 25 cm. For a tuned dipole, the minimum heights as measured from the center of the antenna are those specified in the NSA measurement requirements.

For tabletop systems, cables or wires should be manipulated within the range of likely arrangements. For floor-standing equipment, the cables or wires should be located in the same manner as the user would install them and no further manipulation is made. For combination EUTs, the tabletop and floor-standing portions of the EUT shall follow the procedures for their respective setups and cable manipulation.

Table-top equipment is placed on a non-conductive set-up table with height  $0,8\text{ m} \pm 0,01\text{ m}$ , ANSI C63.10:2009 specifies the method to determine the impact of the non-conductive set-up table on test results. If the manner of cable installation is not known, or if it changes with each installation, cables or wires for floor-standing equipment shall be manipulated to the extent possible to produce the maximum level of emissions. For each mode of operation required to be tested, the frequency spectrum shall be monitored. Variations in antenna height between 1 m and 4 m, antenna polarization, EUT azimuth, and cable or wire placement shall be explored to produce the emission that has the highest amplitude relative to the limit.

#### Procedure of Final Test

EUT and support equipment were set up on the turntable as per the configuration with highest emission level in the preliminary test. The Analyzer / Receiver scanned from 30MHz to 1000MHz. Emissions were scanned and measured rotating the EUT to 360 degrees, varying cable placement and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level. Record at least six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit and only QP reading is presented. The test data of the worst-case condition(s) was recorded.

#### Procedure of Final Test

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test. A scan was taken on both power lines, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. The test data of the worst-case condition(s) was recorded.

Below 1GHz Set the spectrum analyzer: RBW =100KHz VBW  $\geq$  RBW , Span = enough to catch the trace. Sweep = auto; Detector Function = Peak. Trace = Max,hold.

Above 1GHz Set the spectrum analyzer: RBW =1MHz VBW  $\geq$  RBW , Span = enough to catch the trace. Sweep = auto; Detector Function = Peak. Trace = Max,hold.

Pre-test for normal mode and EDR mode, to find the EDR is the worst case. Pre-test for EUT in three axes and find the X axe is the worst case.

The worst case emissions were reported.

### 4.10.3 TEST SETUP




Figure 1. 9 KHz to 30MHz radiated emissions test configuration




Figure 2. 30MHz to 1GHz radiated emissions test configuration




Figure 3. Above 1GHz radiated emissions test configuration

#### 4.10.4 TEST RESULTS

##### 1. Low Frequency 2402MHz

##### 30MHz~1GHz Spurious Emissions .Quasi-Peak Measurement

No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Antenna polarization
1	72.0843	9.47	7.83	17.30	40.00	-22.70	Vertical
2	96.0986	12.83	9.87	22.70	43.50	-20.80	Vertical
3	129.9226	12.22	8.68	20.90	43.50	-22.60	Vertical
4	193.7728	18.87	11.43	30.30	43.50	-13.20	Vertical
5	225.3080	14.04	12.76	26.80	46.00	-19.20	Vertical
6	397.6334	8.26	18.14	26.40	46.00	-19.60	Vertical
7	96.0986	15.93	9.87	25.80	43.50	-17.70	Horizontal
8	183.8440	21.48	11.22	32.70	43.50	-10.80	Horizontal
9	224.5193	17.47	12.73	30.20	46.00	-15.80	Horizontal
10	271.3246	16.51	14.19	30.70	46.00	-15.30	Horizontal
11	366.8231	12.94	17.56	30.50	46.00	-15.50	Horizontal
12	432.5457	11.09	18.51	29.60	46.00	-16.40	Horizontal

##### 1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

##### Peak Measurement:

No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Antenna polarization
1	2028.925	27.18	3.95	31.13	74.00	-42.87	Vertical
2	2793.241	32.99	9.12	42.11	74.00	-31.89	Vertical
3	2925.146	29.75	10.74	40.49	74.00	-33.51	Vertical
4	4794.727	34.69	16.07	50.76	74.00	-23.24	Vertical
5	10194.427	30.13	25.28	55.41	74.00	-18.59	Vertical
6	23437.013	30.94	30.59	61.53	74.00	-12.47	Vertical
7	1618.002	25.44	3.35	28.79	74.00	-45.21	Horizontal
8	2110.778	27.73	4.25	31.98	74.00	-42.02	Horizontal
9	2777.939	28.26	8.92	37.18	74.00	-36.82	Horizontal
10	4794.727	32.75	16.07	48.82	74.00	-25.18	Horizontal
11	10159.847	30.79	25.35	56.14	74.00	-17.86	Horizontal
12	17617.565	32.15	30.44	62.59	74.00	-11.41	Horizontal

## AV Measurement:

No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Antenna polarization
1	2028.925	14.65	3.95	18.60	54.00	-41.40	Vertical
2	2793.241	16.08	9.12	25.20	54.00	-34.80	Vertical
3	2925.146	15.36	10.74	26.10	54.00	-33.90	Vertical
4	4794.727	19.33	16.07	35.40	54.00	-18.60	Vertical
5	10194.427	17.92	25.28	43.20	54.00	-10.80	Vertical
6	23437.013	16.91	30.59	47.50	54.00	-6.50	Vertical
7	1618.002	12.95	3.35	16.30	54.00	-43.70	Horizontal
8	2110.778	14.15	4.25	18.40	54.00	-41.60	Horizontal
9	2777.939	15.58	8.92	24.50	54.00	-35.50	Horizontal
10	4794.727	19.43	16.07	35.50	54.00	-18.50	Horizontal
11	10159.847	17.75	25.35	43.10	54.00	-10.90	Horizontal
12	17617.565	17.36	30.44	47.80	54.00	-6.20	Horizontal

The field strength is calculated by adding the Antenna Factor. Correct Factor.

The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Correct Factor

## 2. Middle Frequency 2441MHz

## 30MHz~1GHz Spurious Emissions .Quasi-Peak Measurement

No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Antenna polarization
1	72.0843	9.47	7.83	17.30	40.00	-22.70	Vertical
2	96.0986	12.53	9.87	22.40	43.50	-21.10	Vertical
3	185.7882	19.50	11.30	30.80	43.50	-12.70	Vertical
4	225.3080	13.14	12.76	25.90	46.00	-20.10	Vertical
5	261.9753	10.14	13.96	24.10	46.00	-21.90	Vertical
6	399.0302	8.54	18.16	26.70	46.00	-19.30	Vertical
7	72.0843	12.97	7.83	20.80	40.00	-19.20	Horizontal
8	96.0986	15.53	9.87	25.40	43.50	-18.10	Horizontal
9	183.8440	22.68	11.22	33.90	43.50	-9.60	Horizontal
10	226.0994	19.01	12.79	31.80	46.00	-14.20	Horizontal
11	261.9753	16.44	13.96	30.40	46.00	-15.60	Horizontal
12	366.8231	14.14	17.56	31.70	46.00	-14.30	Horizontal

## 1~25 GHz Harmonics &amp; Spurious Emissions. Peak &amp; Average Measurement

## Peak Measurement:

No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Antenna polarization
1	1751.184	25.95	3.68	29.63	74.00	-44.37	Vertical
2	2491.654	32.63	5.62	38.25	74.00	-35.75	Vertical
3	2790.174	30.57	9.09	39.66	74.00	-34.34	Vertical
4	4876.882	35.26	16.35	51.61	74.00	-22.39	Vertical
5	9654.996	30.75	25.11	55.86	74.00	-18.14	Vertical
6	18226.471	31.04	30.87	61.91	74.00	-12.09	Vertical
7	1308.865	26.06	0.60	26.66	74.00	-47.34	Horizontal
8	2143.493	28.10	4.36	32.46	74.00	-41.54	Horizontal
9	2954.211	28.56	11.10	39.66	74.00	-34.34	Horizontal
10	4876.882	32.07	16.35	48.42	74.00	-25.58	Horizontal
11	9524.659	30.95	24.89	55.84	74.00	-18.16	Horizontal
12	13424.317	30.65	28.82	59.47	74.00	-14.53	Horizontal

## AV Measurement:

No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Antenna polarization
1	1751.184	12.92	3.68	16.60	54.00	-43.40	Vertical
2	2491.654	17.48	5.62	23.10	54.00	-36.90	Vertical
3	2790.174	16.21	9.09	25.30	54.00	-34.70	Vertical
4	4876.882	18.95	16.35	35.30	54.00	-18.70	Vertical
5	9654.996	17.39	25.11	42.50	54.00	-11.50	Vertical
6	18226.471	17.73	30.87	48.60	54.00	-5.40	Vertical
7	1308.865	13.10	0.60	13.70	54.00	-46.30	Horizontal
8	2143.493	14.94	4.36	19.30	54.00	-40.70	Horizontal
9	2954.211	16.00	11.10	27.10	54.00	-32.90	Horizontal
10	4876.882	19.35	16.35	35.70	54.00	-18.30	Horizontal
11	9524.659	17.61	24.89	42.50	54.00	-11.50	Horizontal
12	13424.317	17.38	28.82	46.20	54.00	-7.80	Horizontal

The field strength is calculated by adding the Antenna Factor. Correct Factor.

The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Correct Factor

## 3. High Frequency 2480MHz

## 30MHz~1GHz Spurious Emissions .Quasi-Peak Measurement

No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Antenna polarization
1	72.0843	10.47	7.83	18.30	40.00	-21.70	Vertical
2	96.0986	12.53	9.87	22.40	43.50	-21.10	Vertical
3	180.0165	19.83	11.07	30.90	43.50	-12.60	Vertical
4	188.4125	20.20	11.40	31.60	43.50	-11.90	Vertical
5	399.0300	7.54	18.16	25.70	46.00	-20.30	Vertical
6	482.2156	6.33	19.97	26.30	46.00	-19.70	Vertical
7	72.0843	12.07	7.83	19.90	40.00	-20.10	Horizontal
8	96.0986	13.83	9.87	23.70	43.50	-19.80	Horizontal
9	173.8135	24.39	10.71	35.10	43.50	-8.40	Horizontal
10	185.7882	23.70	11.30	35.00	43.50	-8.50	Horizontal
11	271.3246	14.11	14.19	28.30	46.00	-17.70	Horizontal
12	287.9904	13.41	14.69	28.10	46.00	-17.90	Horizontal

## 1~25 GHz Harmonics &amp; Spurious Emissions. Peak &amp; Average Measurement

## Peak Measurement:

No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Antenna polarization
1	1443.306	26.59	2.10	28.69	74.00	-45.31	Vertical
2	2257.079	27.61	4.78	32.39	74.00	-41.61	Vertical
3	2796.311	31.65	9.16	40.81	74.00	-33.19	Vertical
4	4960.444	34.55	16.64	51.19	74.00	-22.81	Vertical
5	8485.484	30.62	24.20	54.82	74.00	-19.18	Vertical
6	13654.335	31.09	29.30	60.39	74.00	-13.61	Vertical
7	1619.781	25.36	3.35	28.71	74.00	-45.29	Horizontal
8	2024.472	26.44	3.93	30.37	74.00	-43.63	Horizontal
9	2726.539	29.48	8.25	37.73	74.00	-36.27	Horizontal
10	4960.444	32.09	16.64	48.73	74.00	-25.27	Horizontal
11	9654.996	30.12	25.11	55.23	74.00	-18.77	Horizontal
12	13747.442	30.37	29.51	59.88	74.00	-14.12	Horizontal

## AV Measurement:

No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Antenna polarization
1	1443.306	12.80	2.10	14.90	54.00	-45.10	Vertical
2	2257.079	14.32	4.78	19.10	54.00	-40.90	Vertical
3	2796.311	15.34	9.16	24.50	54.00	-35.50	Vertical
4	4960.444	19.46	16.64	36.10	54.00	-17.90	Vertical
5	8485.484	18.10	24.20	42.30	54.00	-11.70	Vertical
6	13654.335	17.30	29.30	46.60	54.00	-7.40	Vertical
7	1619.781	13.15	3.35	16.50	54.00	-43.50	Horizontal
8	2024.472	13.97	3.93	17.90	54.00	-42.10	Horizontal
9	2726.539	15.85	8.25	24.10	54.00	-35.90	Horizontal
10	4960.444	19.16	16.64	35.80	54.00	-18.20	Horizontal
11	9654.996	17.79	25.11	42.90	54.00	-11.10	Horizontal
12	13747.442	16.99	29.51	46.50	54.00	-7.50	Horizontal

## Remark:

- 1). No any other emissions level which are attenuated less than 20dB below the limit.  
According to 15.31(o), The amplitude of spurious emissions from intentional radiators and emissions from unintentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this Part.  
Hence there no other emissions have been reported.
- 2). As shown in Section, for frequencies above 1000 MHz. the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.
- 3). The test only perform the EUT in transmitting status since the test frequencies were over 1GHz only required transmitting status.

**Test result: The unit does meet the requirements.**

## 4.11 BAND EDGES REQUIREMENT


### 4.11.1 LIMITS

Section 15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required.

### 4.11.2 TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Fixing frequency mode:  
Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency. Repeat above procedures until all measured frequencies were complete.
4. Frequency Hopping mode:  
Span = wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products which fall outside of the authorized band of operation.  
RBW  $\geq$  1 % of spectrum analyzer display span(set 100kHz), VBW  $\geq$  RBW(set 100kHz),  
Sweep = auto, Detector function = peak, Trace = max hold.  
Allow the trace to stabilize. Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge.

### 4.11.3 TEST SETUP



### 4.11.4 TEST RESULTS


**The unit does meet the FCC requirements.**

Test result plot as follows:


**Fixing frequency mode:**

For GFSK

**Lowest Channel**




**Highest Channel**




For 8DPSK


Lowest Channel




Highest Channel



**Frequency Hopping mode:  
FOR GFSK:**



**FOR 8DPSK**



**4.11.5 Radiated Emissions which fall in the restricted bands**

Section 15.247(d) In addition, radiated emissions which fall in the restricted bands. as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

Section 15.205 Restricted bands of operation.

(a) Except as shown in paragraph (d) of this section. only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 -	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.69525	960 - 1240	7.25 - 7.75
4.125 - 4.128	16.80425 -	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	16.80475	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	25.5 - 25.67	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	37.5 - 38.25	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	73 - 74.6	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	74.8 - 75.2	2200 - 2300	14.47 - 14.5
8.291 - 8.294	108 - 121.94	2310 - 2390	15.35 - 16.2
8.362 - 8.366	123 - 138	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	149.9 - 150.05	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.52475 -	3260 - 3267	23.6 - 24.0
12.29 - 12.293	156.52525	3332 - 3339	31.2 - 31.8
12.51975 -	156.7 - 156.9	3345.8 - 3358	36.43 - 36.5
12.52025	162.0125 - 167.17	3600 - 4400	
12.57675 -	167.72 - 173.2		
12.57725	240 - 285		
13.36 - 13.41	322 - 335.4		

Pretest the Bluetooth normal mode and EDR mode, record normal mode data  
 The field strength was measured with an EMI measuring receiver and 1 MHz RBW / VBW for peak and with 1MHz RBW / 10Hz VBW for average at a distance of 3m.

**Test Result:**

**Channel Low**

No.	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark	Pol V/H
1	2390.000	26.86	5.25	32.11	74.00	-41.89	peak	VERTICAL
2	2400.000	29.54	5.29	34.83	74.00	-39.17	peak	VERTICAL
3	2390.000	13.91	16.32	30.23	54.00	-23.77	AVG	VERTICAL
4	2400.000	14.64	16.38	31.02	54.00	-22.98	AVG	VERTICAL
1	2390.000	26.52	5.25	31.77	74.00	-42.23	peak	HORIZONTAL
2	2400.000	27.06	5.29	32.35	74.00	-41.65	peak	HORIZONTAL
3	2390.000	13.79	16.32	30.11	54.00	-23.89	AVG	HORIZONTAL
4	2400.000	15.50	16.38	31.88	54.00	-22.12	AVG	HORIZONTAL

**Channel High**

No.	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark	Pol V/H
1	2483.500	27.86	5.60	33.46	74.00	-40.54	peak	VERTICAL
2	2500.000	27.74	5.66	33.40	74.00	-40.60	peak	VERTICAL
3	2483.500	16.28	5.60	21.88	54.00	-32.12	AVG	VERTICAL
4	2500.000	16.07	5.66	21.73	54.00	-32.27	AVG	VERTICAL
1	2483.500	28.38	5.60	33.98	74.00	-40.02	peak	HORIZONTAL
2	2500.000	28.22	5.66	33.88	74.00	-40.12	peak	HORIZONTAL
3	2483.500	16.35	5.60	21.95	54.00	-32.05	AVG	HORIZONTAL
4	2500.000	16.14	5.66	21.80	54.00	-32.20	AVG	HORIZONTAL

Remark: Max field strength in 3m distance. No any other emission which falls in restricted bands can be detected and be reported.

-----**This is the last page of the report.**-----