



# EMI TEST REPORT

Test Report No. : 10946202H-B

**Applicant** : Sharp Corporation, Communication Systems Division  
**Type of Equipment** : Smart Phone  
**Model No.** : SH-02H  
**FCC ID** : APYHRO00228  
**Test standard** : FCC Part 15 Subpart B 2015 Class B  
**Test Result** : Complied

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the above regulation.
4. The test results in this report are traceable to the national or international standards.
5. This test report must not be used by the customer product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.
6. This test report covers EMC technical requirements. It does not cover administrative issues such as Manual or non-EMC test related Requirements. (if applicable)

**Date of test:** September 28, 2015

**Representative  
test engineer:**

*Koji Yamamoto*

Koji Yamamoto

Engineer

Consumer Technology Division

**Approved by :**

*T. Hatahara*

Takahiro Hatakeda

Leader

Consumer Technology Division



NVLAP LAB CODE: 200572-0

This laboratory is accredited by the NVLAP LAB CODE 200572-0, U.S.A. The tests reported herein have been performed in accordance with its terms of accreditation.  
\*As for the range of Accreditation in NVLAP, you may refer to the WEB address,  
<http://www.ul.com/japan/jpn/pages/services/emc/about/mark1/index.jsp#nvlap>

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

13-EM-F0429



---

| <b>CONTENTS</b>                                                      | <b>PAGE</b> |
|----------------------------------------------------------------------|-------------|
| <b>SECTION 1: Customer information .....</b>                         | <b>4</b>    |
| <b>SECTION 2: Equipment under test (E.U.T.) .....</b>                | <b>4</b>    |
| <b>SECTION 3: Test specification, procedures &amp; results .....</b> | <b>5</b>    |
| <b>SECTION 4: Operation of E.U.T. during testing .....</b>           | <b>7</b>    |
| <b>SECTION 5: Conducted Emission .....</b>                           | <b>8</b>    |
| <b>SECTION 6: Radiated Emission .....</b>                            | <b>9</b>    |
| <b>APPENDIX 1: Data of EMI test .....</b>                            | <b>10</b>   |
| Conducted Emission .....                                             | 10          |
| Radiated Emission .....                                              | 12          |
| <b>APPENDIX 2: Test instruments .....</b>                            | <b>16</b>   |
| <b>APPENDIX 3: Photographs of test setup.....</b>                    | <b>17</b>   |
| Conducted Emission .....                                             | 17          |
| Radiated Emission .....                                              | 18          |
| Worst Case Position (Horizontal: X-axis/ Vertical:X-axis) .....      | 20          |

## **SECTION 1: Customer information**

Company Name : Sharp Corporation, Communication Systems Division  
Address : 2-13-1 Iida Hachihonmatsu HigashiHiroshima-City, Hiroshima, 739-0192  
Japan  
Telephone Number : +81-82-420-1552  
Facsimile Number : +81-82-420-1555  
Contact Person : Hachiro Hidaka

## **SECTION 2: Equipment under test (E.U.T.)**

### **2.1 Identification of E.U.T.**

Type of Equipment : Smart Phone  
Model No. : SH-02H  
Serial No. : Refer to Section 4, Clause 4.2  
Receipt Date of Sample : September 28, 2015  
Country of Mass-production : Japan  
Condition of EUT : Production prototype  
(Not for Sale: This sample is equivalent to mass-produced items.)  
Modification of EUT : No Modification by the test lab

### **2.2 Product description**

Feature of EUT : SH-02H is Tri-band LTE(Band 1 / 3 / 19), Quad-band WCDMA  
(FDD I / V / VI/ X IX) & Quad-band GSM(850 / 900 / 1800 / 1900)  
Multi-mode Smart Phone.  
The EUT has the function that NFC, Bluetooth and Wireless-LAN technology  
interface for establishing contact and transmitting data with certain device.  
Clock frequencies in the system : CPU: 1.824 GHz (max)  
Source oscillation: 19.2 MHz, 27.12 MHz(NFC), 48.0 MHz(WLAN/BT),  
32.0 MHz(DTV)

---

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

## SECTION 3: Test specification, procedures & results

### 3.1 Test specification

Test specification: Test specification: FCC Part 15 Subpart B: 2015, final revised on September 8, 2015

Title : FCC 47CFR Part15 Radio Frequency Device  
Subpart B Unintentional Radiators

### 3.2 Procedures and results

| Item               | Test Procedure                                                            | Limits  | Deviation | Worst margin                                                           | Result   |
|--------------------|---------------------------------------------------------------------------|---------|-----------|------------------------------------------------------------------------|----------|
| Conducted emission | ANSI C63.4: 2009<br>7. AC powerline<br>conducted emission<br>measurements | Class B | N/A       | [QP]<br>15.0 dB<br>0.17095 MHz, L<br>[AV]<br>12.9 dB<br>0.17095 MHz, L | Complied |
| Radiated emission  | ANSI C63.4: 2009<br>8. Radiated<br>emission measurements                  | Class B | N/A       | 7.0 dB<br>31.957 MHz,<br>Vertical, QP                                  | Complied |

\*Note: UL Japan, Inc's EMI Work Procedure 13-EM-W0420.

### 3.3 Addition to standard

No addition, exclusion nor deviation has been made from the standard.

### 3.4 Uncertainty

#### EMI

The following uncertainties have been calculated to provide a confidence level of 95% using a coverage factor k=2.

| Test room<br>(semi-anechoic chamber) | Conducted emission<br>(+dB) |
|--------------------------------------|-----------------------------|
|                                      | 150kHz-30MHz                |
| No.1                                 | 3.5dB                       |
| No.2                                 | 3.5dB                       |
| No.3                                 | 3.4dB                       |
| No.4                                 | 3.5dB                       |

| Test room<br>(semi-anechoic chamber) | Radiated emission |                     |                    |                   |                    |                      |                      |
|--------------------------------------|-------------------|---------------------|--------------------|-------------------|--------------------|----------------------|----------------------|
|                                      | (3 m*)(+dB)       |                     |                    |                   | (1 m*)(+dB)        |                      | (0.5 m*)(+dB)        |
|                                      | 9 kHz<br>- 30 MHz | 30 MHz<br>- 300 MHz | 300 MHz<br>- 1 GHz | 1 GHz<br>- 10 GHz | 10 GHz<br>- 18 GHz | 18 GHz<br>- 26.5 GHz | 26.5 GHz<br>- 40 GHz |
| No.1                                 | 4.3 dB            | 5.1 dB              | 6.2 dB             | 5.5 dB            | 5.8 dB             | 5.8 dB               | 4.3 dB               |
| No.2                                 | 4.2 dB            | 5.1 dB              | 6.2 dB             | 5.4 dB            | 5.7 dB             | 5.9 dB               | 5.6 dB               |
| No.3                                 | 4.4 dB            | 5.1 dB              | 6.3 dB             | 5.2 dB            | 5.5 dB             | 5.8 dB               | 5.5 dB               |
| No.4                                 | 4.7 dB            | 5.3 dB              | 6.3 dB             | 5.3 dB            | 5.7 dB             | 5.9 dB               | 5.5 dB               |

\*3m/1m/0.5m = Measurement distance

#### Conducted emission test

The data listed in this test report has enough margin, more than the site margin.

#### Radiated emission test(3m)

The data listed in this test report has enough margin, more than the site margin.

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

### 3.5 Test Location

UL Japan, Inc. Ise EMC Lab. \*NVLAP Lab. code: 200572-0  
4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN  
Telephone : +81 596 24 8999 Facsimile : +81 596 24 8124

|                            | IC Registration Number | Width x Depth x Height (m) | Size of reference ground plane (m) / horizontal conducting plane | Other rooms            |
|----------------------------|------------------------|----------------------------|------------------------------------------------------------------|------------------------|
| No.1 semi-anechoic chamber | 2973C-1                | 19.2 x 11.2 x 7.7m         | 7.0 x 6.0m                                                       | No.1 Power source room |
| No.2 semi-anechoic chamber | 2973C-2                | 7.5 x 5.8 x 5.2m           | 4.0 x 4.0m                                                       | -                      |
| No.3 semi-anechoic chamber | 2973C-3                | 12.0 x 8.5 x 5.9m          | 6.8 x 5.75m                                                      | No.3 Preparation room  |
| No.3 shielded room         | -                      | 4.0 x 6.0 x 2.7m           | N/A                                                              | -                      |
| No.4 semi-anechoic chamber | 2973C-4                | 12.0 x 8.5 x 5.9m          | 6.8 x 5.75m                                                      | No.4 Preparation room  |
| No.4 shielded room         | -                      | 4.0 x 6.0 x 2.7m           | N/A                                                              | -                      |
| No.5 semi-anechoic chamber | -                      | 6.0 x 6.0 x 3.9m           | 6.0 x 6.0m                                                       | -                      |
| No.6 shielded room         | -                      | 4.0 x 4.5 x 2.7m           | 4.0 x 4.5 m                                                      | -                      |
| No.6 measurement room      | -                      | 4.75 x 5.4 x 3.0m          | 4.75 x 4.15 m                                                    | -                      |
| No.7 shielded room         | -                      | 4.7 x 7.5 x 2.7m           | 4.7 x 7.5m                                                       | -                      |
| No.8 measurement room      | -                      | 3.1 x 5.0 x 2.7m           | N/A                                                              | -                      |
| No.9 measurement room      | -                      | 8.8 x 4.6 x 2.8m           | 2.4 x 2.4m                                                       | -                      |
| No.11 measurement room     | -                      | 6.2 x 4.7 x 3.0m           | 4.8 x 4.6m                                                       | -                      |

\* Size of vertical conducting plane (for Conducted Emission test) : 2.0 x 2.0m for No.1, No.2, No.3, and No.4 semi-anechoic chambers and No.3 and No.4 shielded rooms.

### 3.6 Test data, Test instruments, and Test set up


Refer to APPENDIX.

## SECTION 4: Operation of E.U.T. during testing

### 4.1 Operating modes

The mode(s) : 1) USB Data Com Mode  
The USB data is communicated between EUT and Personal computer (Pair of EUT).  
2) Standby Mode  
Standby state for USB communication.

### 4.2 Configuration and peripherals



■ : Ferrite core which has been standard on support equipment.

\*Cabling and setup were taken into consideration and test data was taken under worse case conditions.

#### Description of EUT and Support equipment

| No. | Item                | Model number | Serial number            | Manufacturer      | Remarks |
|-----|---------------------|--------------|--------------------------|-------------------|---------|
| A   | Smart Phone         | SH-02H       | 004401/11/559033/9       | Sharp Corporation | EUT     |
| B   | microSD Memory Card | SD-MD008GA   | None                     | TOSHIBA           | -       |
| C   | Personal Computer   | PP11L        | CN-0D4571-48643-55V-1651 | Dell              | -       |
| D   | Mouse               | M-BE55       | LZE21450232              | LOGITEC           | -       |
| E   | AC Adapter(PC)      | PA-1650-05D2 | CN-0F7970-71615-561-14A1 | Dell              | -       |
| F   | Printer             | 895Cxi       | SG8BL1W16V               | Hewlett Packard   | -       |
| G   | AC Adapter(Printer) | C4557-60004  | C8K28B                   | Hewlett Packard   | -       |

#### List of cables used

| No. | Name                       | Length (m) | Shield     |            | Remarks |
|-----|----------------------------|------------|------------|------------|---------|
|     |                            |            | Cable      | Connector  |         |
| 1   | USB Data Cable             | 0.95       | Shielded   | Shielded   | -       |
| 2   | Mouse Cable                | 0.72       | Unshielded | Unshielded | -       |
| 3   | AC Adaptor Cable (PC)      | 1.76       | Unshielded | Unshielded | -       |
| 4   | AC Power Cable (PC)        | 0.85       | Unshielded | Unshielded | -       |
| 5   | Parallel Cable             | 1.65       | Shielded   | Shielded   | -       |
| 6   | AC Adapter Cable (printer) | 2.00       | Unshielded | Unshielded | -       |
| 7   | AC Power Cable (printer)   | 1.75       | Unshielded | Unshielded | -       |

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

## **SECTION 5: Conducted Emission**

### **5.1 Operating environment**

|             |                               |
|-------------|-------------------------------|
| Test place  | : No. 1 semi anechoic chamber |
| Temperature | : See data                    |
| Humidity    | : See data                    |

### **5.2 Test configuration**

EUT was placed on a urethane platform of nominal size, 1.0 m by 1.5 m, raised 0.8 m above the conducting ground plane.

The rear of tabletop was located 40 cm to the vertical conducting plane. The rear of EUT and its peripherals was aligned and flushed with rear of tabletop. All other surfaces of tabletop were at least 80 cm from any other grounded conducting surface. EUT was located 80 cm from the LISN/AMN. I/O cables that were connected to the other peripherals were bundled in center. They were folded back and forth forming a bundle 30 cm to 40 cm long and were hanged at a 40 cm height to the ground plane. Each EUT current-carrying power lead, except the ground (safety) lead, was individually connected through a LISN/AMN to the input power source. All unused 50 ohm connectors of the LISN/AMN were resistivity terminated in 50 ohm when not connected to the measuring equipment.

Photographs of the set up are shown in Appendix 3.

|                    |                     |
|--------------------|---------------------|
| Frequency range    | : 0.15 MHz - 30 MHz |
| EUT position       | : Table top         |
| EUT operation mode | : See Clause 4.1    |

### **5.3 Test procedure**

The AC Mains Terminal Continuous disturbance Voltage has been measured with the EUT within a semi anechoic chamber. The EUT was connected to a Line Impedance Stabilization Network (LISN)/ Artificial Mains network (AMN). An overview sweep with peak detection has been performed. The measurements have been performed with a quasi-peak detector and if required, with an average detector.

The conducted emission measurements were made with the following detector function of the test receiver.

|               |                           |
|---------------|---------------------------|
| Detector Type | : Quasi-Peak and CISPR AV |
| IF Bandwidth  | : 9 kHz                   |

### **5.4 Test result**

Summary of the test results: Pass

Date: September 28, 2015                      Test engineer: Koji Yamamoto

## **SECTION 6: Radiated Emission**

### **6.1 Operating environment**

Test place : No. 1 semi anechoic chamber  
Temperature : See data  
Humidity : See data

### **6.2 Test configuration**

EUT was placed on a urethane platform of nominal size, 1.0m by 1.5m, raised 0.8m above the conducting ground plane. The EUT was set on the edge of the tabletop.  
Test was made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna was varied in height above the conducting ground plane to obtain the maximum signal strength. Photographs of the set up are shown in Appendix 3.

### **6.3 Test conditions**

Frequency range : 30 MHz - 300 MHz (Biconical antenna) / 300 MHz - 1000 MHz (Logperiodic antenna)  
1000 MHz - 10000 MHz (Horn antenna)  
Test distance : 3 m  
EUT position : Table top  
EUT operation mode : See Clause 4.1

### **6.4 Test procedure**

The height of the measuring antenna varied between 1 m and 4 m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.  
The measurements were performed for both vertical and horizontal antenna polarization with the Test Receiver. The radiated emission measurements were made with the following detector function of the Test Receiver.

|                 |               |                                |
|-----------------|---------------|--------------------------------|
| Frequency       | Below 1GHz    | Above 1GHz                     |
| Instrument used | Test Receiver | Test Receiver                  |
| IF Bandwidth    | QP: BW 120kHz | PK: BW 1MHz, CISPR AV: BW 1MHz |

- The carrier level and noise levels were confirmed at each position of X, Y and Z axes of EUT to see the position of maximum noise, and the test was made at the position that has the maximum noise.

### **6.5 Test result**

Summary of the test results: Pass

Date: September 28, 2015      Test engineer: Koji Yamamoto





## Radiated Emission (Below 1GHz)

### DATA OF RADIATED EMISSION TEST


UL Japan, Inc. Ise EMC Lab. No.1 Semi Anechoic Chamber  
Date : 2015/09/28

Report No. : 10946202H

Temp./Humi. : 23deg. C / 63% RH  
Engineer : Koji Yamamoto

Mode / Remarks : USB Data Com Mode Axis(Hori: X / Vert: X)

LIMIT : FCC15.109(a) 3m, below 1GHz:QP, above 1GHz:PK  
Except for the data below : adequate margin data below the limits.



| Frequency | Reading | DET | Antenna | Loss& | Level    | Angle | Height | Polar. | Limit    | Margin | Comment |
|-----------|---------|-----|---------|-------|----------|-------|--------|--------|----------|--------|---------|
|           |         |     | Factor  | Gain  |          |       |        |        |          |        |         |
| [MHz]     | [dBuV]  |     | [dB/m]  | [dB]  | [dBuV/m] | [Deg] | [cm]   |        | [dBuV/m] | [dB]   |         |
| 31.957    | 47.7    | QP  | 16.7    | -31.4 | 33.0     | 125   | 100    | Vert.  | 40.0     | 7.0    |         |
| 60.338    | 54.2    | QP  | 7.3     | -31.0 | 30.5     | 277   | 300    | Hori.  | 40.0     | 9.5    |         |
| 72.400    | 54.4    | QP  | 6.3     | -30.8 | 29.9     | 307   | 300    | Hori.  | 40.0     | 10.1   |         |
| 72.402    | 51.2    | QP  | 6.3     | -30.8 | 26.7     | 262   | 100    | Vert.  | 40.0     | 13.3   |         |
| 78.429    | 53.6    | QP  | 6.7     | -30.7 | 29.6     | 290   | 300    | Hori.  | 40.0     | 10.4   |         |
| 159.774   | 44.5    | QP  | 15.4    | -29.7 | 30.2     | 110   | 232    | Hori.  | 43.5     | 13.3   |         |
| 159.775   | 46.1    | QP  | 15.4    | -29.7 | 31.8     | 172   | 100    | Vert.  | 43.5     | 11.7   |         |
| 199.717   | 40.3    | QP  | 16.3    | -29.4 | 27.2     | 15    | 100    | Vert.  | 43.5     | 16.3   |         |
| 447.357   | 42.3    | QP  | 17.8    | -26.9 | 33.2     | 135   | 195    | Hori.  | 46.0     | 12.8   |         |
| 479.314   | 41.5    | QP  | 17.9    | -26.5 | 32.9     | 137   | 145    | Hori.  | 46.0     | 13.1   |         |
| 500.426   | 42.9    | QP  | 18.0    | -26.2 | 34.7     | 348   | 209    | Hori.  | 46.0     | 11.3   |         |
| 511.263   | 39.6    | QP  | 18.2    | -26.1 | 31.7     | 336   | 100    | Vert.  | 46.0     | 14.3   |         |
| 543.219   | 40.2    | QP  | 18.7    | -25.9 | 33.0     | 341   | 118    | Vert.  | 46.0     | 13.0   |         |

CHART:WITH FACTOR ANT TYPE: -30MHz:LOOP, 30-300MHz:BICONICAL, 300MHz-1000MHz:LOGPERIODIC, 1000MHz-:HORN  
CALCULATION : RESULT = READING + ANT FACTOR + LOSS & GAIN(CABLE + ATTEN - GAIN(AMP))

\*The limit is rounded down to one decimal place.

\*The test result is rounded off to one or two decimal places, so some differences might be observed.

## Radiated Emission (Below 1GHz)

### DATA OF RADIATED EMISSION TEST


UL Japan, Inc. Ise EMC Lab. No.1 Semi Anechoic Chamber  
Date : 2015/09/28

Report No. : 10946202H

Temp./Humi. : 23deg. C / 63% RH  
Engineer : Koji Yamamoto

Mode / Remarks : Standby Mode Axis(Hori: X / Vert: X)

LIMIT : FCC15.109(a) 3m, below 1GHz:QP, above 1GHz:PK  
Except for the data below : adequate margin data below the limits.



| Frequency | Reading | DET | Antenna |       | Level    | Angle | Height | Polar. | Limit    | Margin | Comment |
|-----------|---------|-----|---------|-------|----------|-------|--------|--------|----------|--------|---------|
|           |         |     | Factor  | Gain  |          |       |        |        |          |        |         |
| [MHz]     | [dBuV]  |     | [dB/m]  | [dB]  | [dBuV/m] | [Deg] | [cm]   |        | [dBuV/m] | [dB]   |         |
| 31.957    | 47.3    | QP  | 16.7    | -31.4 | 32.6     | 83    | 100    | Vert.  | 40.0     | 7.4    |         |
| 60.337    | 54.3    | QP  | 7.3     | -31.0 | 30.6     | 257   | 300    | Hori.  | 40.0     | 9.4    |         |
| 72.400    | 54.2    | QP  | 6.3     | -30.8 | 29.7     | 299   | 300    | Hori.  | 40.0     | 10.3   |         |
| 72.400    | 50.9    | QP  | 6.3     | -30.8 | 26.4     | 270   | 100    | Vert.  | 40.0     | 13.6   |         |
| 78.434    | 53.4    | QP  | 6.7     | -30.7 | 29.4     | 295   | 300    | Hori.  | 40.0     | 10.6   |         |
| 159.775   | 43.9    | QP  | 15.4    | -29.7 | 29.6     | 105   | 247    | Hori.  | 43.5     | 13.9   |         |
| 159.775   | 46.7    | QP  | 15.4    | -29.7 | 32.4     | 159   | 100    | Vert.  | 43.5     | 11.1   |         |
| 199.718   | 40.3    | QP  | 16.3    | -29.4 | 27.2     | 0     | 100    | Vert.  | 43.5     | 16.3   |         |
| 479.314   | 41.2    | QP  | 17.9    | -26.5 | 32.6     | 141   | 145    | Hori.  | 46.0     | 13.4   |         |
| 479.314   | 39.2    | QP  | 17.9    | -26.5 | 30.6     | 172   | 156    | Vert.  | 46.0     | 15.4   |         |
| 500.397   | 42.7    | QP  | 18.0    | -26.2 | 34.5     | 0     | 195    | Hori.  | 46.0     | 11.5   |         |
| 543.219   | 39.9    | QP  | 18.7    | -25.9 | 32.7     | 340   | 115    | Vert.  | 46.0     | 13.3   |         |

CHART:WITH FACTOR ANT TYPE:-30MHz:LOOP, 30-300MHz:BICONICAL, 300MHz-1000MHz:LOGPERIODIC, 1000MHz-:HORN  
CALCULATION : RESULT = READING + ANT FACTOR + LOSS & GAIN(CABLE + ATTEN - GAIN(AMP))

\*The limit is rounded down to one decimal place.

\*The test result is rounded off to one or two decimal places, so some differences might be observed.

**Radiated Emission**  
**(Above 1GHz)**

**DATA OF RADIATED EMISSION TEST**


UL Japan, Inc. Ise EMC Lab. No.1 Semi Anechoic Chamber  
Date : 2015/09/28

Report No. : 10946202H

Temp./Humi. : 23deg. C / 63% RH  
Engineer : Koji Yamamoto

Mode / Remarks : USB Data Com Mode Axis(Hori: X / Vert: X)

LIMIT : FCC15.109(a) 3m, below 1GHz:QP, above 1GHz:PK  
FCC15.109(a) 3m, below 1GHz:QP, above 1GHz:AV



| Frequency | Reading | DET | Antenna | Loss& | Level    | Angle | Height | Polar. | Limit    | Margin | Comment |
|-----------|---------|-----|---------|-------|----------|-------|--------|--------|----------|--------|---------|
|           |         |     | Factor  | Gain  |          |       |        |        |          |        |         |
| [MHz]     | [dBuV]  |     | [dB/m]  | [dB]  | [dBuV/m] | [Deg] | [cm]   |        | [dBuV/m] | [dB]   |         |
| 1595.846  | 60.0    | PK  | 25.6    | -34.1 | 51.5     | 282   | 100    | Hori.  | 73.9     | 22.4   |         |
| 1595.846  | 60.6    | PK  | 25.6    | -34.1 | 52.1     | 245   | 100    | Vert.  | 73.9     | 21.8   |         |
| 1595.846  | 36.3    | AV  | 25.6    | -34.1 | 27.8     | 282   | 100    | Hori.  | 53.9     | 26.1   |         |
| 1595.846  | 35.0    | AV  | 25.6    | -34.1 | 26.5     | 245   | 100    | Vert.  | 53.9     | 27.4   |         |

CHART:WITH FACTOR ANT TYPE: -30MHz:LOOP, 30-300MHz:BICONICAL, 300MHz-1000MHz:LOGPERIODIC, 1000MHz-:HORN  
CALCULATION : RESULT = READING + ANT FACTOR + LOSS & GAIN (CABLE - GAIN(AMP))

\*The limit is rounded down to one decimal place.

\*The test result is rounded off to one or two decimal places, so some differences might be observed.

## Radiated Emission (Above 1GHz)

### DATA OF RADIATED EMISSION TEST


UL Japan, Inc. Ise EMC Lab. No.1 Semi Anechoic Chamber  
Date : 2015/09/28

Report No. : 10946202H

Temp./Humi. : 23deg. C / 63% RH  
Engineer : Koji Yamamoto

Mode / Remarks : Standby Mode Axis(Hori: X / Vert: X)

LIMIT : FCC15.109(a) 3m, below 1GHz:QP, above 1GHz:PK  
FCC15.109(a) 3m, below 1GHz:QP, above 1GHz:AV



| Frequency | Reading | DET | Antenna | Loss& | Level    | Angle | Height | Polar. | Limit    | Margin | Comment |
|-----------|---------|-----|---------|-------|----------|-------|--------|--------|----------|--------|---------|
|           |         |     | Factor  | Gain  |          |       |        |        |          |        |         |
| [MHz]     | [dBuV]  |     | [dB/m]  | [dB]  | [dBuV/m] | [Deg] | [cm]   |        | [dBuV/m] | [dB]   |         |
| 1595.846  | 55.6    | PK  | 25.6    | -34.1 | 47.1     | 298   | 100    | Hori.  | 73.9     | 26.8   |         |
| 1595.846  | 60.2    | PK  | 25.6    | -34.1 | 51.7     | 257   | 100    | Vert.  | 73.9     | 22.2   |         |
| 1595.846  | 34.5    | AV  | 25.6    | -34.1 | 26.0     | 298   | 100    | Hori.  | 53.9     | 27.9   |         |
| 1595.846  | 34.7    | AV  | 25.6    | -34.1 | 26.2     | 257   | 100    | Vert.  | 53.9     | 27.7   |         |

CHART:WITH FACTOR ANT TYPE: -30MHz:LOOP, 30-300MHz:BICONICAL, 300MHz-1000MHz:LOGPERIODIC, 1000MHz-:HORN  
CALCULATION : RESULT = READING + ANT FACTOR + LOSS & GAIN(CABLE - GAIN(AMP))

\*The limit is rounded down to one decimal place.

\*The test result is rounded off to one or two decimal places, so some differences might be observed.

## APPENDIX 2: Test instruments

### EMI Test Instruments

| Control No. | Instrument                 | Manufacturer             | Model No                                               | Serial No                      | Test Item | Calibration Date *<br>Interval(month) |
|-------------|----------------------------|--------------------------|--------------------------------------------------------|--------------------------------|-----------|---------------------------------------|
| MAEC-01     | Semi Anechoic Chamber(NSA) | TDK                      | Semi Anechoic Chamber 10m                              | DA-06881                       | RE/CE     | 2014/09/01 * 12                       |
| MOS-27      | Thermo-Hygrometer          | CUSTOM                   | CTH-201                                                | A08Q26                         | RE/CE     | 2015/01/13 * 12                       |
| MJM-21      | Measure                    | KOMELON                  | KMC-36                                                 | -                              | RE/CE     | -                                     |
| COTS-MEMI   | EMI measurement program    | TSJ                      | TEPTO-DV                                               | -                              | RE/CE     | -                                     |
| MTR-09      | EMI Test Receiver          | Rohde & Schwarz          | ESU26                                                  | 100412                         | RE/CE     | 2015/06/08 * 12                       |
| KBA-05      | Biconical Antenna          | Schwarzbeck              | BBA9106                                                | 2513                           | RE        | 2014/11/22 * 12                       |
| KLA-04      | Logperiodic Antenna        | Schwarzbeck              | USLP9143                                               | 361                            | RE        | 2014/11/22 * 12                       |
| MAT-08      | Attenuator(6dB)            | Weinschel Corp           | 2                                                      | BK7971                         | RE        | 2014/11/20 * 12                       |
| MCC-02      | Coaxial Cable              | Suhner/storm/Agilent/TSJ | -                                                      | -                              | RE        | 2014/09/12 * 12                       |
| MPA-19      | Pre Amplifier              | MITEQ                    | MLA-10K01-B01-35                                       | 1237616                        | RE        | 2015/02/03 * 12                       |
| MMM-03      | Digital Tester             | Fluke                    | FLUKE 26-3                                             | 78030621                       | RE/CE     | 2015/08/19 * 12                       |
| MLS-24      | LISN(AMN)                  | Schwarzbeck              | NSLK8127                                               | 8127-730                       | CE(EUT)   | 2015/07/10 * 12                       |
| MLS-26      | LISN(AMN)                  | Schwarzbeck              | NSLK8127                                               | 8127-732                       | CE(AE)    | 2015/07/17 * 12                       |
| MTA-30      | Terminator                 | TME                      | CT-01                                                  | -                              | CE        | 2015/01/19 * 12                       |
| MCC-03      | Coaxial Cable              | Fujikura/Suhner/TSJ      | 5D-2W(20m)/3D-2W(7.5m)/RG400u(1.5m)/RFM-E421(Switcher) | -<br>/01068(Switcher)          | CE        | 2014/09/12 * 12                       |
| MAT-64      | Attenuator(13dB)           | JFW Industries, Inc.     | 50FP-013H2 N                                           | -                              | CE        | 2015/01/29 * 12                       |
| MHA-05      | Horn Antenna 1-18GHz       | Schwarzbeck              | BBHA9120D                                              | 253                            | RE        | 2015/05/18 * 12                       |
| MPA-01      | Pre Amplifier              | Agilent                  | 8449B                                                  | 3008A01671                     | RE        | 2015/02/04 * 12                       |
| MCC-165     | Microwave Cable            | Junkosha                 | MWX221                                                 | 1203S213(1m) /<br>1311S166(5m) | RE        | 2014/11/11 * 12                       |

The expiration date of the calibration is the end of the expired month.

All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.

As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.

#### Test Item:

CE: Conducted Emissions

RE: Radiated Emissions

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124