

# TEST REPORT

## CERTIFICATE OF CONFORMITY

**Standard:** 47 CFR FCC Part 15, Subpart C (Section 15.247)  
47 CFR FCC Part 15, Subpart E (Section 15.407)

**Report No.:** RFBEFM-WTW-P24110678-5

**FCC ID:** ARS-CRD29

**Product:** Wi-Fi module

**Brand:** Philips

**Model No.:** CRD29

**Received Date:** 2024/11/28

**Test Date:** 2025/1/9 ~ 2025/1/10

**Issued Date:** 2025/1/22

**Applicant:** TOP VICTORY ELECTRONICS (TAIWAN) CO., LTD.

**Address:** 10F., No 230, Liancheng Rd., Zhonghe Dist., New Taipei City 23553, Taiwan

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Lin Kou Laboratories

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

**Test Location:** No. 70, Wenming Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)

**FCC Registration /** 281270 / TW0032

**Designation Number:**

**Approved by:** \_\_\_\_\_

*Jeremy Lin*

**Date:** \_\_\_\_\_

2025/1/22

Jeremy Lin / Project Engineer

This test report consists of 29 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.



Prepared by : Annie Chang / Senior Specialist

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

## Table of Contents

|                                                                     |           |
|---------------------------------------------------------------------|-----------|
| <b>Release Control Record .....</b>                                 | <b>3</b>  |
| <b>1 Certificate.....</b>                                           | <b>4</b>  |
| <b>2 Summary of Test Results .....</b>                              | <b>5</b>  |
| 2.1 Measurement Uncertainty .....                                   | 5         |
| 2.2 Supplementary Information .....                                 | 5         |
| <b>3 General Information .....</b>                                  | <b>6</b>  |
| 3.1 General Description of EUT .....                                | 6         |
| 3.2 Antenna Description of EUT .....                                | 6         |
| 3.3 Test Mode Applicability and Tested Channel Detail.....          | 7         |
| 3.4 Test Program Used and Operation Descriptions .....              | 8         |
| 3.5 Connection Diagram of EUT and Peripheral Devices .....          | 8         |
| 3.6 Configuration of Peripheral Devices and Cable Connections ..... | 8         |
| <b>4 Test Instruments .....</b>                                     | <b>9</b>  |
| 4.1 Unwanted Emissions below 1 GHz .....                            | 9         |
| 4.2 Unwanted Emissions above 1 GHz.....                             | 10        |
| <b>5 Limits of Test Items.....</b>                                  | <b>11</b> |
| 5.1 Unwanted Emissions below 1 GHz .....                            | 11        |
| 5.2 Unwanted Emissions above 1 GHz.....                             | 12        |
| <b>6 Test Arrangements.....</b>                                     | <b>13</b> |
| 6.1 Unwanted Emissions below 1 GHz .....                            | 13        |
| 6.1.1 Test Setup .....                                              | 13        |
| 6.1.2 Test Procedure.....                                           | 14        |
| 6.2 Unwanted Emissions above 1 GHz.....                             | 15        |
| 6.2.1 Test Setup .....                                              | 15        |
| 6.2.2 Test Procedure.....                                           | 15        |
| <b>7 Test Results of Test Item .....</b>                            | <b>16</b> |
| 7.1 Unwanted Emissions below 1 GHz .....                            | 16        |
| 7.2 Unwanted Emissions above 1 GHz.....                             | 24        |
| <b>8 Pictures of Test Arrangements .....</b>                        | <b>28</b> |
| <b>9 Information of the Testing Laboratories .....</b>              | <b>29</b> |

## Release Control Record

| Issue No.              | Description       | Date Issued |
|------------------------|-------------------|-------------|
| RFBEFM-WTW-P24110678-5 | Original release. | 2025/1/22   |

## 1 Certificate

**Product:** Wi-Fi module

**Brand:** Philips

**Test Model:** CRD29

**Sample Status:** Engineering sample

**Applicant:** TOP VICTORY ELECTRONICS (TAIWAN) CO., LTD.

**Test Date:** 2025/1/9 ~ 2025/1/10

**Standard:** 47 CFR FCC Part 15, Subpart C (Section 15.247)  
47 CFR FCC Part 15, Subpart E (Section 15.407)

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

## 2 Summary of Test Results

| Standard / Clause                                      | Test Item                      | Result | Remark                         |
|--------------------------------------------------------|--------------------------------|--------|--------------------------------|
| 15.205 /15.209 /15.247(d)<br>15.407(b)(9)              | Unwanted Emissions below 1 GHz | Pass   | Meet the requirement of limit. |
| 15.205 /15.209 /15.247(d)<br>15.407(b) (1/2/3/4(i)/10) | Unwanted Emissions above 1 GHz | Pass   | Meet the requirement of limit. |

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| Parameter                      | Specification   | Uncertainty (±) |
|--------------------------------|-----------------|-----------------|
| Unwanted Emissions below 1 GHz | 9 kHz ~ 30 MHz  | 3 dB            |
|                                | 30 MHz ~ 1 GHz  | 2.93 dB         |
| Unwanted Emissions above 1 GHz | 1 GHz ~ 18 GHz  | 1.76 dB         |
|                                | 18 GHz ~ 40 GHz | 1.77 dB         |

The other instruments specified are routine verified to remain within the calibrated levels, no measurement uncertainty is required to be calculated.

### 2.2 Supplementary Information

There is not any deviation from the test standards for the test method, and no modifications required for compliance.

### 3 General Information

#### 3.1 General Description of EUT

|                       |              |                                                                                              |
|-----------------------|--------------|----------------------------------------------------------------------------------------------|
| Product               | Wi-Fi module |                                                                                              |
| Brand                 | Philips      |                                                                                              |
| Test Model            | CRD29        |                                                                                              |
| Modulation Technology | BT-EDR       | FHSS                                                                                         |
|                       | BT-LE        | DTS                                                                                          |
|                       | WLAN         | DSSS, OFDM, OFDMA                                                                            |
| Operating Frequency   | BT-EDR       | 2.402 GHz ~ 2.48 GHz                                                                         |
|                       | BT-LE        | 2.402 GHz ~ 2.48 GHz                                                                         |
|                       | WLAN         | 2.412 GHz ~ 2.462 GHz<br>5.18 ~ 5.24 GHz, 5.26 ~ 5.32 GHz, 5.5 ~ 5.72 GHz, 5.745 ~ 5.825 GHz |

Note:

1. There are Bluetooth and WLAN (2.4 GHz & 5 GHz) technology used for the EUT.
2. Simultaneously transmission combination.

| Combination | Technology     |           |
|-------------|----------------|-----------|
| 1           | WLAN (2.4 GHz) | Bluetooth |
| 2           | WLAN (5 GHz)   | Bluetooth |

Note: The emission of the simultaneous operation has been evaluated and no non-compliance was found.

3. The EUT does not support Partial RU technology.
4. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.

#### 3.2 Antenna Description of EUT

The antenna information is listed as below.

| Antenna NO. | RF Chain NO. | Brand | Model                  | Gain (dBi) | Frequency range (GHz) | Antenna Type | Connector Type | Cable Length |
|-------------|--------------|-------|------------------------|------------|-----------------------|--------------|----------------|--------------|
| 1(WIFI)     | 0/1          | TPV   | 368GAAWA1950YL         | 2.99       | 2.4~2.5               | Dipole       | ipex(MHF)      | 70mm         |
|             |              |       |                        | 3.73       | 5.15~5.85             | Dipole       | ipex(MHF)      | 70mm         |
| 2(WIFI)     | 0/1          | TPV   | SLK-GJ-P2808A-L-200I-B | 2.01       | 2.4~2.5               | PIFA         | ipex(MHF)      | 200mm        |
|             |              |       |                        | 2.74       | 5.15~5.85             | PIFA         | ipex(MHF)      | 200mm        |
| 3(WIFI)     | 0/1          | TPV   | SLK-GJ-P2808B-R-550I-G | 2.9        | 2.4~2.5               | PIFA         | ipex(MHF)      | 550mm        |
|             |              |       |                        | 2.79       | 5.15~5.85             | PIFA         | ipex(MHF)      | 550mm        |
| 4(WIFI)     | 0/1          | TPV   | SLK-GJ-T3018-R-507I-G  | 1.99       | 2.4~2.5               | PIFA         | ipex(MHF)      | 507mm        |
|             |              |       |                        | 1.72       | 5.15~5.85             | PIFA         | ipex(MHF)      | 507mm        |
| 5(BT)       | 2            | TPV   | 368GAAWA1920YL         | 2.22       | 2.4~2.5               | PIFA         | ipex(MHF)      | 35mm         |

\* Detail antenna specification please refer to antenna datasheet and/or antenna measurement report.

### 3.3 Test Mode Applicability and Tested Channel Detail

|                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|--------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Pre-Scan:</b>   | 1. The PIFA BT antenna can be used in the following ways: X / Y / Z axis. Pre-scan in these ways and find the worst case as a representative test condition.<br>2. The PIFA(SLK-GJ-P2808A-L-200I-B)/ PIFA(SLK-GJ-P2808B-R-550I-G)/ PIFA(SLK-GJ-T3018-R-507I-G) WIFI antenna can be used in the following ways: X / Y / Z axis. Pre-scan in these ways and find the worst case as a representative test condition.<br>3. The Dipole(368GAAWA1950YL) WIFI antenna can be used in the following ways: X / Z axis. Pre-scan in these ways and find the worst case as a representative test condition. |
| <b>Worst Case:</b> | 1. The PIFA BT antenna the worst condition: Z axis.<br>2. The PIFA WIFI antenna the worst condition: PIFA(SLK-GJ-P2808B-R-550I-G) on Z axis.<br>3. The Dipole WIFI antenna the worst condition: Dipole(368GAAWA1950YL) on Z axis.                                                                                                                                                                                                                                                                                                                                                                 |

Following channel(s) was (were) selected for the final test as listed below:


| Test Item                      | EUT Configure Mode | Combination                                | Mode            | Tested Channel |
|--------------------------------|--------------------|--------------------------------------------|-----------------|----------------|
| Unwanted Emissions below 1 GHz | A                  | 1                                          | GFSK            | 39             |
|                                |                    |                                            | 802.11ax (HE40) | 6              |
|                                |                    | 2                                          | GFSK            | 39             |
|                                |                    |                                            | 802.11ax (HE40) | 54             |
|                                | B                  | 1                                          | GFSK            | 39             |
|                                |                    |                                            | 802.11ax (HE40) | 6              |
|                                |                    | 2                                          | GFSK            | 39             |
|                                |                    |                                            | 802.11ax (HE40) | 54             |
| Unwanted Emissions above 1 GHz | A                  | 1                                          | GFSK            | 39             |
|                                |                    |                                            | 802.11ax (HE40) | 6              |
|                                |                    | 2                                          | GFSK            | 39             |
|                                |                    |                                            | 802.11ax (HE40) | 54             |
|                                | B                  | 1                                          | GFSK            | 39             |
|                                |                    |                                            | 802.11ax (HE40) | 6              |
|                                |                    | 2                                          | GFSK            | 39             |
|                                |                    |                                            | 802.11ax (HE40) | 54             |
| EUT Configure Mode:            | A                  | EUT with (WIFI 2.4G/ 5G) Dipole Antenna+BT |                 |                |
|                                | B                  | EUT with (WIFI 2.4G/ 5G) PIFA Antenna+BT   |                 |                |

### 3.4 Test Program Used and Operation Descriptions


Controlling software (RTL8852B\_USB\_MP\_Package\_ALPHA\_v1.0.52) has been activated to set the EUT under transmission condition continuously at specific channel frequency.

### 3.5 Connection Diagram of EUT and Peripheral Devices

Mode A



Mode B



### 3.6 Configuration of Peripheral Devices and Cable Connections

| ID | Product    | Brand  | Model No.         | Serial No. | FCC ID | Remarks         |
|----|------------|--------|-------------------|------------|--------|-----------------|
| A  | NB         | Lenovo | IdeaPad 5 15ITL05 | N/A        | N/A    | Provided by Lab |
| B  | NB Adapter | Lenovo | ADLX65CLGC2A      | N/A        | N/A    | Provided by Lab |

| ID | Cable Descriptions | Qty. | Length (m) | Shielding (Yes/No) | Cores (Qty.) | Remarks         |
|----|--------------------|------|------------|--------------------|--------------|-----------------|
| 1  | USB Cable          | 1    | 1          | Y                  | 0            | Provided by Lab |
| 2  | DC cable           | 1    | 1.9        | N                  | 0            | Provided by Lab |

## 4 Test Instruments

The calibration interval of the all test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.1 Unwanted Emissions below 1 GHz

| Description<br>Manufacturer       | Model No.                    | Serial No.       | Calibrated<br>Date | Calibrated<br>Until |
|-----------------------------------|------------------------------|------------------|--------------------|---------------------|
| Antenna Tower<br>Max-Full         | MFA-515BSN                   | N/A              | N/A                | N/A                 |
| Bi_Log Antenna<br>Schwarzbeck     | VULB 9168                    | 9168-1214        | 2024/10/15         | 2025/10/14          |
| EXA Signal Analyzer<br>Agilent    | N9010A                       | MY52220207       | 2024/12/30         | 2025/12/29          |
| Loop Antenna<br>TESEQ             | HLA 6121                     | 45745            | 2024/8/21          | 2025/8/20           |
| MXE EMI Receiver<br>Agilent       | N9038A                       | MY52260177       | 2024/9/19          | 2025/9/18           |
| Preamplifier<br>EMCI              | EMC330N                      | 980798           | 2024/1/15          | 2025/1/14           |
| RF Coaxial Cable<br>EMCI          | EMCCFD400-NM-NM-500          | 201248           | 2024/1/15          | 2025/1/14           |
|                                   | EMCCFD400-NM-NM-3000         | 201249           | 2024/1/15          | 2025/1/14           |
|                                   | EMCCFD400-NM-NM-9000         | 201251(with PAD) | 2024/1/15          | 2025/1/14           |
| Software<br>BV ADT                | ADT_Radiated_<br>V7.6.15.9.5 | N/A              | N/A                | N/A                 |
| Turn Table<br>Max-Full            | MFT-201SS                    | N/A              | N/A                | N/A                 |
| Turn Table Controller<br>Max-Full | MF-7802BS                    | MF780208676      | N/A                | N/A                 |

Notes:

1. The test was performed in WM - 966 chamber 9.
2. Tested Date: 2025/1/9 ~ 2025/1/10

## 4.2 Unwanted Emissions above 1 GHz

| Description<br>Manufacturer       | Model No.                    | Serial No.  | Calibrated<br>Date | Calibrated<br>Until |
|-----------------------------------|------------------------------|-------------|--------------------|---------------------|
| Antenna Tower<br>Max-Full         | MFA-515BSN                   | N/A         | N/A                | N/A                 |
| EXA Signal Analyzer<br>Agilent    | N9010A                       | MY52220207  | 2024/12/30         | 2025/12/29          |
| Horn Antenna<br>RFSPIN            | DRH18-E                      | 210104A18E  | 2024/11/10         | 2025/11/9           |
| Horn Antenna<br>Schwarzbeck       | BBHA 9170                    | 9170-1049   | 2024/11/10         | 2025/11/9           |
| MXE EMI Receiver<br>Agilent       | N9038A                       | MY52260177  | 2024/9/19          | 2025/9/18           |
| Preamplifier<br>Agilent           | 83017A                       | MY39501357  | 2024/6/12          | 2025/6/11           |
| Preamplifier<br>EMCI              | EMC184045SE                  | 980788      | 2024/1/15          | 2025/1/14           |
| RF Coaxial Cable<br>EMCI          | EMC101G-KM-KM-2000           | 201254      | 2024/1/15          | 2025/1/14           |
|                                   | EMC101G-KM-KM-3000           | 201258      | 2024/1/15          | 2025/1/14           |
|                                   | EMC101G-KM-KM-5000           | 201261      | 2024/1/15          | 2025/1/14           |
|                                   | EMC104-SM-SM-1000            | 210103      | 2024/1/15          | 2025/1/14           |
|                                   | EMC104-SM-SM-3000            | 201241      | 2024/1/15          | 2025/1/14           |
|                                   | EMC104-SM-SM-9000            | 201244      | 2024/1/15          | 2025/1/14           |
| Software<br>BV ADT                | ADT_Radiated_<br>V7.6.15.9.5 | N/A         | N/A                | N/A                 |
| Turn Table<br>Max-Full            | MFT-201SS                    | N/A         | N/A                | N/A                 |
| Turn Table Controller<br>Max-Full | MF-7802BS                    | MF780208676 | N/A                | N/A                 |

### Notes:

1. The test was performed in WM - 966 chamber 9.
2. Tested Date: 2025/1/9 ~ 2025/1/10

## 5 Limits of Test Items

### 5.1 Unwanted Emissions below 1 GHz

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table.

For FCC 15.247:

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009 ~ 0.490     | 2400/F(kHz)                       | 300                           |
| 0.490 ~ 1.705     | 24000/F(kHz)                      | 30                            |
| 1.705 ~ 30.0      | 30                                | 30                            |
| 30 ~ 88           | 100                               | 3                             |
| 88 ~ 216          | 150                               | 3                             |
| 216 ~ 960         | 200                               | 3                             |
| Above 960         | 500                               | 3                             |

Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).

For FCC 15.407:

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009 ~ 0.490     | 2400/F(kHz)                       | 300                           |
| 0.490 ~ 1.705     | 24000/F(kHz)                      | 30                            |
| 1.705 ~ 30.0      | 30                                | 30                            |
| 30 ~ 88           | 100                               | 3                             |
| 88 ~ 216          | 150                               | 3                             |
| 216 ~ 960         | 200                               | 3                             |
| Above 960         | 500                               | 3                             |

Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).

## 5.2 Unwanted Emissions above 1 GHz

For FCC 15.247:

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| Above 960         | 500                               | 3                             |

Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

For FCC 15.407 transmitters operating in the 5.150-5.850 GHz band:

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table.

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| Above 960         | 500                               | 3                             |

Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

Limits of unwanted emission out of the restricted bands

| Applicable To                                           | Limit                 |                 |
|---------------------------------------------------------|-----------------------|-----------------|
| 789033 D02 General UNII Test Procedure New Rules v02r01 | Field Strength at 3 m |                 |
|                                                         | PK: 74 (dBμV/m)       | AV: 54 (dBμV/m) |

| Applicable To   | EIRP Limit                                                                                                                              | Equivalent Field Strength at 3 m                                                                                                            |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| 15.407(b)(1)    | PK: -27 (dBm/MHz)                                                                                                                       | PK: 68.2 (dBμV/m) *                                                                                                                         |
| 15.407(b)(2)    | PK: -27 (dBm/MHz)                                                                                                                       | PK: 68.2 (dBμV/m) *                                                                                                                         |
| 15.407(b)(3)    | PK: -27 (dBm/MHz)                                                                                                                       | PK: 68.2 (dBμV/m) *                                                                                                                         |
| 15.407(b)(4)(i) | PK: -27 (dBm/MHz) <sup>*1</sup><br>PK: 10 (dBm/MHz) <sup>*2</sup><br>PK: 15.6 (dBm/MHz) <sup>*3</sup><br>PK: 27 (dBm/MHz) <sup>*4</sup> | PK: 68.2 (dBμV/m) <sup>*1</sup><br>PK: 105.2 (dBμV/m) <sup>*2</sup><br>PK: 110.8 (dBμV/m) <sup>*3</sup><br>PK: 122.2 (dBμV/m) <sup>*4</sup> |

<sup>\*1</sup> beyond 75 MHz or more above of the band edge.

<sup>\*2</sup> below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above.

<sup>\*3</sup> below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above.

<sup>\*4</sup> from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Note: The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:


$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where } P \text{ is the eirp (Watts).}$$

## 6 Test Arrangements


### 6.1 Unwanted Emissions below 1 GHz

#### 6.1.1 Test Setup

##### For Radiated emission below 30 MHz



##### For Radiated emission above 30 MHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

### 6.1.2 Test Procedure

#### For Radiated emission below 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode, except for the frequency band (9 kHz to 90 kHz and 110 kHz to 490 kHz) set to average detect function and peak detect function.

#### Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 200 Hz at frequency below 150 kHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz or 10 kHz at frequency (150 kHz to 30 MHz).
3. All modes of operation were investigated and the worst-case emissions are reported.

#### For Radiated emission above 30 MHz


- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

#### Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
2. All modes of operation were investigated and the worst-case emissions are reported.

## 6.2 Unwanted Emissions above 1 GHz

### 6.2.1 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

### 6.2.2 Test Procedure

- The EUT was placed on the top of a rotating table 1.5 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

#### Notes:

- The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) and Average detection (AV) at frequency above 1 GHz.
- All modes of operation were investigated and the worst-case emissions are reported.

## 7 Test Results of Test Item

### 7.1 Unwanted Emissions below 1 GHz


#### Mode A (Combination 1)

|                 |                           |                               |                                    |
|-----------------|---------------------------|-------------------------------|------------------------------------|
| RF Mode         | BT GFSK + 802.11ax (HE40) | Channel                       | CH 39 : 2441 MHz + CH 6 : 2437 MHz |
| Frequency Range | 30 MHz ~ 1 GHz            | Detector Function & Bandwidth | QP: RB=120kHz, DET=Quasi-Peak      |
| Input Power     | 120 Vac, 60 Hz            | Environmental Conditions      | 25.9 °C, 74.3 % RH                 |
| Tested By       | Ian Chang                 |                               |                                    |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 53.74           | 34.0 QP                 | 40.0           | -6.0        | 1.00 H             | 1                    | 47.2             | -13.2                    |
| 2                                                    | 156.46          | 25.3 QP                 | 43.5           | -18.2       | 1.26 H             | 54                   | 38.2             | -12.9                    |
| 3                                                    | 254.33          | 29.5 QP                 | 46.0           | -16.5       | 1.80 H             | 118                  | 43.4             | -13.9                    |
| 4                                                    | 337.67          | 30.6 QP                 | 46.0           | -15.4       | 2.13 H             | 159                  | 41.9             | -11.3                    |
| 5                                                    | 426.82          | 31.0 QP                 | 46.0           | -15.0       | 2.81 H             | 239                  | 40.1             | -9.1                     |
| 6                                                    | 540.19          | 25.2 QP                 | 46.0           | -20.8       | 3.39 H             | 305                  | 31.9             | -6.7                     |

#### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




|                 |                           |                               |                                    |
|-----------------|---------------------------|-------------------------------|------------------------------------|
| RF Mode         | BT GFSK + 802.11ax (HE40) | Channel                       | CH 39 : 2441 MHz + CH 6 : 2437 MHz |
| Frequency Range | 30 MHz ~ 1 GHz            | Detector Function & Bandwidth | QP: RB=120kHz, DET=Quasi-Peak      |
| Input Power     | 120 Vac, 60 Hz            | Environmental Conditions      | 25.9 °C, 74.3 % RH                 |
| Tested By       | Ian Chang                 |                               |                                    |

| Antenna Polarity & Test Distance : Vertical at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|----------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                 | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                  | 33.39           | 33.7 QP                 | 40.0           | -6.3        | 2.95 V             | 227                  | 47.9             | -14.2                    |
| 2                                                  | 54.71           | 30.9 QP                 | 40.0           | -9.1        | 3.37 V             | 274                  | 44.2             | -13.3                    |
| 3                                                  | 83.78           | 26.0 QP                 | 40.0           | -14.0       | 3.72 V             | 314                  | 44.6             | -18.6                    |
| 4                                                  | 238.83          | 33.9 QP                 | 46.0           | -12.1       | 2.24 V             | 144                  | 48.4             | -14.5                    |
| 5                                                  | 337.67          | 28.1 QP                 | 46.0           | -17.9       | 1.53 V             | 59                   | 39.4             | -11.3                    |
| 6                                                  | 426.82          | 29.3 QP                 | 46.0           | -16.7       | 4.00 V             | 5                    | 38.4             | -9.1                     |

#### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




### Mode A (Combination 2)

|                        |                           |                                          |                                     |
|------------------------|---------------------------|------------------------------------------|-------------------------------------|
| <b>RF Mode</b>         | BT GFSK + 802.11ax (HE40) | <b>Channel</b>                           | CH 39 : 2441 MHz + CH 54 : 5270 MHz |
| <b>Frequency Range</b> | 30 MHz ~ 1 GHz            | <b>Detector Function &amp; Bandwidth</b> | QP: RB=120kHz, DET=Quasi-Peak       |
| <b>Input Power</b>     | 120 Vac, 60 Hz            | <b>Environmental Conditions</b>          | 25.9 °C, 74.3 % RH                  |
| <b>Tested By</b>       | Ian Chang                 |                                          |                                     |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 33.39           | 31.5 QP                 | 40.0           | -8.5        | 1.53 H             | 57                   | 45.7             | -14.2                    |
| 2                                                    | 53.74           | 31.2 QP                 | 40.0           | -8.8        | 4.00 H             | 354                  | 44.4             | -13.2                    |
| 3                                                    | 83.78           | 25.6 QP                 | 40.0           | -14.4       | 2.02 H             | 116                  | 44.2             | -18.6                    |
| 4                                                    | 139.02          | 27.5 QP                 | 43.5           | -16.0       | 4.00 H             | 5                    | 40.9             | -13.4                    |
| 5                                                    | 345.42          | 29.1 QP                 | 46.0           | -16.9       | 3.41 H             | 278                  | 40.4             | -11.3                    |
| 6                                                    | 433.60          | 35.4 QP                 | 46.0           | -10.6       | 2.84 H             | 213                  | 44.2             | -8.8                     |

### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




|                 |                           |                               |                                     |
|-----------------|---------------------------|-------------------------------|-------------------------------------|
| RF Mode         | BT GFSK + 802.11ax (HE40) | Channel                       | CH 39 : 2441 MHz + CH 54 : 5270 MHz |
| Frequency Range | 30 MHz ~ 1 GHz            | Detector Function & Bandwidth | QP: RB=120kHz, DET=Quasi-Peak       |
| Input Power     | 120 Vac, 60 Hz            | Environmental Conditions      | 25.9 °C, 74.3 % RH                  |
| Tested By       | Ian Chang                 |                               |                                     |

| Antenna Polarity & Test Distance : Vertical at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|----------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                 | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                  | 32.42           | 32.4 QP                 | 40.0           | -7.6        | 1.70 V             | 95                   | 46.6             | -14.2                    |
| 2                                                  | 53.74           | 28.0 QP                 | 40.0           | -12.0       | 2.42 V             | 215                  | 41.2             | -13.2                    |
| 3                                                  | 253.36          | 30.3 QP                 | 46.0           | -15.7       | 1.88 V             | 151                  | 44.3             | -14.0                    |
| 4                                                  | 344.45          | 31.2 QP                 | 46.0           | -14.8       | 1.45 V             | 99                   | 42.5             | -11.3                    |
| 5                                                  | 425.85          | 31.6 QP                 | 46.0           | -14.4       | 1.06 V             | 52                   | 40.7             | -9.1                     |
| 6                                                  | 787.30          | 30.9 QP                 | 46.0           | -15.1       | 1.00 V             | 0                    | 32.9             | -2.0                     |

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




### Mode B (Combination 1)

|                 |                           |                               |                                    |
|-----------------|---------------------------|-------------------------------|------------------------------------|
| RF Mode         | BT GFSK + 802.11ax (HE40) | Channel                       | CH 39 : 2441 MHz + CH 6 : 2437 MHz |
| Frequency Range | 30 MHz ~ 1 GHz            | Detector Function & Bandwidth | QP: RB=120kHz, DET=Quasi-Peak      |
| Input Power     | 120 Vac, 60 Hz            | Environmental Conditions      | 25.9 °C, 74.3 % RH                 |
| Tested By       | Ian Chang                 |                               |                                    |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 32.94           | 32.3 QP                 | 40.0           | -7.7        | 1.00 H             | 0                    | 46.6             | -14.3                    |
| 2                                                    | 53.74           | 27.9 QP                 | 40.0           | -12.1       | 1.93 H             | 140                  | 41.1             | -13.2                    |
| 3                                                    | 157.43          | 27.3 QP                 | 43.5           | -16.2       | 1.52 H             | 90                   | 40.2             | -12.9                    |
| 4                                                    | 237.86          | 31.8 QP                 | 46.0           | -14.2       | 1.13 H             | 43                   | 46.4             | -14.6                    |
| 5                                                    | 337.67          | 32.3 QP                 | 46.0           | -13.7       | 3.10 H             | 277                  | 43.6             | -11.3                    |
| 6                                                    | 428.76          | 31.3 QP                 | 46.0           | -14.7       | 2.62 H             | 222                  | 40.3             | -9.0                     |

#### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




|                 |                           |                               |                                    |
|-----------------|---------------------------|-------------------------------|------------------------------------|
| RF Mode         | BT GFSK + 802.11ax (HE40) | Channel                       | CH 39 : 2441 MHz + CH 6 : 2437 MHz |
| Frequency Range | 30 MHz ~ 1 GHz            | Detector Function & Bandwidth | QP: RB=120kHz, DET=Quasi-Peak      |
| Input Power     | 120 Vac, 60 Hz            | Environmental Conditions      | 25.9 °C, 74.3 % RH                 |
| Tested By       | Ian Chang                 |                               |                                    |

| Antenna Polarity & Test Distance : Vertical at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|----------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                 | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                  | 53.74           | 28.0 QP                 | 40.0           | -12.0       | 2.05 V             | 122                  | 41.2             | -13.2                    |
| 2                                                  | 84.75           | 24.5 QP                 | 40.0           | -15.5       | 2.46 V             | 169                  | 43.2             | -18.7                    |
| 3                                                  | 139.02          | 24.1 QP                 | 43.5           | -19.4       | 2.89 V             | 221                  | 37.5             | -13.4                    |
| 4                                                  | 253.36          | 28.1 QP                 | 46.0           | -17.9       | 3.31 V             | 268                  | 42.1             | -14.0                    |
| 5                                                  | 345.42          | 28.7 QP                 | 46.0           | -17.3       | 3.79 V             | 322                  | 40.0             | -11.3                    |
| 6                                                  | 431.66          | 30.2 QP                 | 46.0           | -15.8       | 4.00 V             | 4                    | 39.1             | -8.9                     |

#### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




## Mode B (Combination 2)

|                        |                           |                                          |                                     |
|------------------------|---------------------------|------------------------------------------|-------------------------------------|
| <b>RF Mode</b>         | BT GFSK + 802.11ax (HE40) | <b>Channel</b>                           | CH 39 : 2441 MHz + CH 54 : 5270 MHz |
| <b>Frequency Range</b> | 30 MHz ~ 1 GHz            | <b>Detector Function &amp; Bandwidth</b> | QP: RB=120kHz, DET=Quasi-Peak       |
| <b>Input Power</b>     | 120 Vac, 60 Hz            | <b>Environmental Conditions</b>          | 25.9 °C, 74.3 % RH                  |
| <b>Tested By</b>       | Ian Chang                 |                                          |                                     |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 33.39           | 30.9 QP                 | 40.0           | -9.1        | 1.47 H             | 46                   | 45.1             | -14.2                    |
| 2                                                    | 54.71           | 28.8 QP                 | 40.0           | -11.2       | 2.33 H             | 149                  | 42.1             | -13.3                    |
| 3                                                    | 83.78           | 25.5 QP                 | 40.0           | -14.5       | 1.89 H             | 97                   | 44.1             | -18.6                    |
| 4                                                    | 257.24          | 27.7 QP                 | 46.0           | -18.3       | 2.82 H             | 207                  | 41.5             | -13.8                    |
| 5                                                    | 349.30          | 28.2 QP                 | 46.0           | -17.8       | 3.26 H             | 258                  | 39.5             | -11.3                    |
| 6                                                    | 429.73          | 30.4 QP                 | 46.0           | -15.6       | 3.64 H             | 300                  | 39.4             | -9.0                     |
| 7                                                    | 635.16          | 26.3 QP                 | 46.0           | -19.7       | 4.00 H             | 4                    | 30.8             | -4.5                     |

### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




|                 |                           |                               |                                     |
|-----------------|---------------------------|-------------------------------|-------------------------------------|
| RF Mode         | BT GFSK + 802.11ax (HE40) | Channel                       | CH 39 : 2441 MHz + CH 54 : 5270 MHz |
| Frequency Range | 30 MHz ~ 1 GHz            | Detector Function & Bandwidth | QP: RB=120kHz, DET=Quasi-Peak       |
| Input Power     | 120 Vac, 60 Hz            | Environmental Conditions      | 25.9 °C, 74.3 % RH                  |
| Tested By       | Ian Chang                 |                               |                                     |

| Antenna Polarity & Test Distance : Vertical at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|----------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                 | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                  | 33.39           | 32.8 QP                 | 40.0           | -7.2        | 1.17 V             | 43                   | 47.0             | -14.2                    |
| 2                                                  | 53.74           | 30.5 QP                 | 40.0           | -9.5        | 1.63 V             | 98                   | 43.7             | -13.2                    |
| 3                                                  | 156.46          | 24.3 QP                 | 43.5           | -19.2       | 2.25 V             | 140                  | 37.2             | -12.9                    |
| 4                                                  | 254.33          | 30.3 QP                 | 46.0           | -15.7       | 2.12 V             | 159                  | 44.2             | -13.9                    |
| 5                                                  | 337.67          | 28.3 QP                 | 46.0           | -17.7       | 3.01 V             | 262                  | 39.6             | -11.3                    |
| 6                                                  | 430.69          | 30.3 QP                 | 46.0           | -15.7       | 2.58 V             | 212                  | 39.3             | -9.0                     |

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.



## 7.2 Unwanted Emissions above 1 GHz

### Mode A (Combination 1)

|                        |                           |                                          |                                                                                                         |
|------------------------|---------------------------|------------------------------------------|---------------------------------------------------------------------------------------------------------|
| <b>RF Mode</b>         | BT GFSK + 802.11ax (HE40) | <b>Channel</b>                           | CH 39 : 2441 MHz + CH 6 : 2437 MHz                                                                      |
| <b>Frequency Range</b> | 1 GHz ~ 25 GHz            | <b>Detector Function &amp; Bandwidth</b> | PK: RB=1 MHz, VB=3 MHz, DET=Peak<br>AV: RB=1 MHz, VB=3 MHz, DET=RMS<br>AV: RB=1 MHz, VB=10 Hz, DET=Peak |
| <b>Input Power</b>     | 120 Vac, 60 Hz            | <b>Environmental Conditions</b>          | 25.9 °C, 74.3 % RH                                                                                      |
| <b>Tested By</b>       | Ian Chang                 |                                          |                                                                                                         |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 4874.00         | 47.2 PK                 | 74.0           | -26.8       | 2.21 H             | 151                  | 43.7             | 3.5                      |
| 2                                                    | 4874.00         | 35.6 AV                 | 54.0           | -18.4       | 2.21 H             | 151                  | 32.1             | 3.5                      |
| 3                                                    | 4882.00         | 48.9 PK                 | 74.0           | -25.1       | 1.42 H             | 270                  | 45.3             | 3.6                      |
| 4                                                    | 4882.00         | 18.1 AV                 | 54.0           | -35.9       | 1.42 H             | 270                  | 14.5             | 3.6                      |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 4874.00         | 49.5 PK                 | 74.0           | -24.5       | 1.66 V             | 42                   | 46.0             | 3.5                      |
| 2                                                    | 4874.00         | 36.1 AV                 | 54.0           | -17.9       | 1.66 V             | 42                   | 32.6             | 3.5                      |
| 3                                                    | 4882.00         | 47.2 PK                 | 74.0           | -26.8       | 1.92 V             | 163                  | 43.6             | 3.6                      |
| 4                                                    | 4882.00         | 16.4 AV                 | 54.0           | -37.6       | 1.92 V             | 163                  | 12.8             | 3.6                      |

#### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.

## Mode A (Combination 2)

|                        |                           |                                          |                                                                                                         |
|------------------------|---------------------------|------------------------------------------|---------------------------------------------------------------------------------------------------------|
| <b>RF Mode</b>         | BT GFSK + 802.11ax (HE40) | <b>Channel</b>                           | CH 39 : 2441 MHz + CH 54 : 5270 MHz                                                                     |
| <b>Frequency Range</b> | 1 GHz ~ 40 GHz            | <b>Detector Function &amp; Bandwidth</b> | PK: RB=1 MHz, VB=3 MHz, DET=Peak<br>AV: RB=1 MHz, VB=3 MHz, DET=RMS<br>AV: RB=1 MHz, VB=10 Hz, DET=Peak |
| <b>Input Power</b>     | 120 Vac, 60 Hz            | <b>Environmental Conditions</b>          | 25.9 °C, 74.3 % RH                                                                                      |
| <b>Tested By</b>       | Ian Chang                 |                                          |                                                                                                         |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 4882.00         | 48.9 PK                 | 74.0           | -25.1       | 1.42 H             | 270                  | 45.3             | 3.6                      |
| 2                                                    | 4882.00         | 18.1 AV                 | 54.0           | -35.9       | 1.42 H             | 270                  | 14.5             | 3.6                      |
| 3                                                    | 5150.00         | 51.8 PK                 | 74.0           | -22.2       | 1.74 H             | 340                  | 47.9             | 3.9                      |
| 4                                                    | 5150.00         | 40.1 AV                 | 54.0           | -13.9       | 1.74 H             | 340                  | 36.2             | 3.9                      |
| 5                                                    | #10540.00       | 55.9 PK                 | 68.2           | -12.3       | 1.11 H             | 302                  | 47.0             | 8.9                      |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 4882.00         | 47.2 PK                 | 74.0           | -26.8       | 1.92 V             | 163                  | 43.6             | 3.6                      |
| 2                                                    | 4882.00         | 16.4 AV                 | 54.0           | -37.6       | 1.92 V             | 163                  | 12.8             | 3.6                      |
| 3                                                    | 5150.00         | 52.6 PK                 | 74.0           | -21.4       | 1.42 V             | 182                  | 48.7             | 3.9                      |
| 4                                                    | 5150.00         | 40.3 AV                 | 54.0           | -13.7       | 1.42 V             | 182                  | 36.4             | 3.9                      |
| 5                                                    | #10540.00       | 57.0 PK                 | 68.2           | -11.2       | 1.91 V             | 152                  | 48.1             | 8.9                      |

### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " # ": The radiated frequency is out of the restricted band, the limit was restricted at the Conducted Out of Band Emissions.

### Mode B (Combination 1)

|                        |                           |                                          |                                                                                                         |
|------------------------|---------------------------|------------------------------------------|---------------------------------------------------------------------------------------------------------|
| <b>RF Mode</b>         | BT GFSK + 802.11ax (HE40) | <b>Channel</b>                           | CH 39 : 2441 MHz + CH 6 : 2437 MHz                                                                      |
| <b>Frequency Range</b> | 1 GHz ~ 25 GHz            | <b>Detector Function &amp; Bandwidth</b> | PK: RB=1 MHz, VB=3 MHz, DET=Peak<br>AV: RB=1 MHz, VB=3 MHz, DET=RMS<br>AV: RB=1 MHz, VB=10 Hz, DET=Peak |
| <b>Input Power</b>     | 120 Vac, 60 Hz            | <b>Environmental Conditions</b>          | 25.9 °C, 74.3 % RH                                                                                      |
| <b>Tested By</b>       | Ian Chang                 |                                          |                                                                                                         |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 4874.00         | 49.3 PK                 | 74.0           | -24.7       | 2.16 H             | 190                  | 45.8             | 3.5                      |
| 2                                                    | 4874.00         | 37.9 AV                 | 54.0           | -16.1       | 2.16 H             | 190                  | 34.4             | 3.5                      |
| 3                                                    | 4882.00         | 47.2 PK                 | 74.0           | -26.8       | 1.92 H             | 163                  | 43.6             | 3.6                      |
| 4                                                    | 4882.00         | 16.4 AV                 | 54.0           | -37.6       | 1.92 H             | 163                  | 12.8             | 3.6                      |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 4874.00         | 50.3 PK                 | 74.0           | -23.7       | 2.02 V             | 250                  | 46.8             | 3.5                      |
| 2                                                    | 4874.00         | 38.7 AV                 | 54.0           | -15.3       | 2.02 V             | 250                  | 35.2             | 3.5                      |
| 3                                                    | 4882.00         | 47.2 PK                 | 74.0           | -26.8       | 1.92 V             | 163                  | 43.6             | 3.6                      |
| 4                                                    | 4882.00         | 16.4 AV                 | 54.0           | -37.6       | 1.92 V             | 163                  | 12.8             | 3.6                      |

### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.

## Mode B (Combination 2)

|                        |                           |                                          |                                                                                                         |
|------------------------|---------------------------|------------------------------------------|---------------------------------------------------------------------------------------------------------|
| <b>RF Mode</b>         | BT GFSK + 802.11ax (HE40) | <b>Channel</b>                           | CH 39 : 2441 MHz + CH 54 : 5270 MHz                                                                     |
| <b>Frequency Range</b> | 1 GHz ~ 40 GHz            | <b>Detector Function &amp; Bandwidth</b> | PK: RB=1 MHz, VB=3 MHz, DET=Peak<br>AV: RB=1 MHz, VB=3 MHz, DET=RMS<br>AV: RB=1 MHz, VB=10 Hz, DET=Peak |
| <b>Input Power</b>     | 120 Vac, 60 Hz            | <b>Environmental Conditions</b>          | 25.9 °C, 74.3 % RH                                                                                      |
| <b>Tested By</b>       | Ian Chang                 |                                          |                                                                                                         |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 4882.00         | 48.9 PK                 | 74.0           | -25.1       | 1.42 H             | 270                  | 45.3             | 3.6                      |
| 2                                                    | 4882.00         | 18.1 AV                 | 54.0           | -35.9       | 1.42 H             | 270                  | 14.5             | 3.6                      |
| 3                                                    | 5150.00         | 54.6 PK                 | 74.0           | -19.4       | 1.00 H             | 280                  | 50.7             | 3.9                      |
| 4                                                    | 5150.00         | 41.5 AV                 | 54.0           | -12.5       | 1.00 H             | 280                  | 37.6             | 3.9                      |
| 5                                                    | #10540.00       | 58.2 PK                 | 68.2           | -10.0       | 1.59 H             | 236                  | 49.3             | 8.9                      |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 4882.00         | 47.2 PK                 | 74.0           | -26.8       | 1.92 V             | 163                  | 43.6             | 3.6                      |
| 2                                                    | 4882.00         | 16.4 AV                 | 54.0           | -37.6       | 1.92 V             | 163                  | 12.8             | 3.6                      |
| 3                                                    | 5150.00         | 53.7 PK                 | 74.0           | -20.3       | 2.23 V             | 171                  | 49.8             | 3.9                      |
| 4                                                    | 5150.00         | 40.2 AV                 | 54.0           | -13.8       | 2.23 V             | 171                  | 36.3             | 3.9                      |
| 5                                                    | #10540.00       | 57.0 PK                 | 68.2           | -11.2       | 2.41 V             | 255                  | 48.1             | 8.9                      |

### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " # ": The radiated frequency is out of the restricted band, the limit was restricted at the Conducted Out of Band Emissions.

## 8 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo)

## 9 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Lin Kou EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

**Hwa Ya EMC/RF/Safety Lab**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@bureauveritas.com](mailto:service.adt@bureauveritas.com)

**Web Site:** <http://ee.bureauveritas.com.tw>

The address and road map of all our labs can be found in our web site also.

--- END ---