



Alcatel-Lucent USA
Rm. 28-114H
600-700 Mountain Ave.
PO Box 636
Murray Hill, NJ 07974

July 14, 2013

Timco Engineering Inc.
Telecommunication Certification Bodies
849 NW State Road 45
Newberry, Florida 32669

Subject: Application for Class II Permissive Change under FCC ID: AS5ONEBTS-27 for 1900 RRH 2x60W Base Station with Modification in RF Amplifier, Operating in the PCS Wireless Services, 1930-1990MHz, with LTE Technology

Dear Examiner:

The Alcatel-Lucent 1900 RRH (Remote Radio Head) 2x60W Base Station has been authorized and granted under FCC ID: AS5ONEBTS-27, effective December 10, 2012, for operating in the PCS (1930-1990MHz) with Long Term Evolution (LTE) technology. Now a new RF amplifier, 1900A, has been designed for the above RRH. The purpose of this Class II Permissive Change Application is to get authorization for installing the 1900A amplifier in the above RRH under AS5ONEBTS-27.

The distributed wireless RRH base station system is comprised of two separate modules 1) the digital Base Band Unit (BBU) and 2) the RRH. These two modules are interconnected by Common Public Radio Interface (CPRI) though optic fiber or metallic coax cables when the separation is less than 3m for indoor deployment. The RRH contains all RF (radio frequency) functionality, including transceiver, power amplifier and transmitting and receiving (Tx/Rx) filters. The BBU provides the digital baseband signals, plus the timing reference signal to the RRH. The BBU can be a unit specially designed for the distributed application or utilize the digital baseband shelf of a non-distributed base station system. The BBU and RRH units can be co-located or remotely located.

The existing Alcatel-Lucent 1900 RRH 2x60W LTE Distributed Base Station, henceforth RRH 2x60 1900, supports both 5MHz and 10MHz LTE carriers. It has 2 antenna ports. It can provide up to 60 Watts (47.8dBm) per carrier and per port and 120 Watts (50.8dBm) per RRH at the base station transmitting antenna terminals. The RRH 2x60 1900 also supports transmit diversity and/or 2x2 MIMO (Multiple Input Multiple Output) operation for LTE.

The modified 1900 LTE RRH, henceforth RRH 2x60 1900A, is equipped with the new RF amplifier 1900A and a new RF Tx/Rx filter. The RRH 2x60 1900A has 4 antenna ports, where two additional ports are for receiving only. There are no modifications in the RF transceiver, the maximum output power and transmitting and receiving frequency ranges. The 1900 LTE RRH 2x60W, which includes both RRH 2x60 1900 and RRH 2x60 1900A, is powered by -48VDC and currently is available in indoor and outdoor versions.

Per CFR 47 Part 2.1043, a Class II permissive authorization is requested to authorize the RRH 2x60 1900A distributed base station under the existing FCCID AS5ONEBTS-27.

In accordance with CFR 47 Parts 2 and 24 of the Commission's Rules and Regulations, we are submitting herewith statements and supporting data to show compliance with the requirements of the Commission for the Class II permissive change certification of the Alcatel-Lucent RRH 2x60 1900A Distributed Base Station System under FCC ID AS5ONEBTS-27, for operation in the domestic PCS Wireless Services A, B, C, D, E and F bands

(1930-1990 MHz), E-UTRAN band II, with LTE technology. Only the documents, photos and testing data, which are affected by this Class II permissive change, are being submitted. Those documents and responses submitted to the FCC in the previous certification applications under AS5ONEBTS-27, which are still valid for this application, are not being resubmitted.


The data summarized below is in the form presently used by the Commission's Radio Equipment List.

Manufacturer	Alcatel-Lucent, Inc.
Equipment Identification	AS5ONEBTS-27
Rules Part Number	Part 24
Frequency Range	Transmit: 1930-1990MHz, Receive: 1850-1910 MHz
Output Power	0-60W per LTE carrier and 0-60W per Tx Port.
Frequency Tolerance	± 0.05 ppm
Emission Designator	5M00F9W, 10M0F9W

Enclosed in this application package are the FCC Application Form 731, Table of Contents and the required exhibits. These exhibits contain the technical data and the required statements and documents for equipment certification. The technical contact at Alcatel-Lucent will comply with any request for additional information should the need arise.

The fees are submitted as required for radio equipment certification filing.

Sincerely,



R.J. Pillmeier
Technical Manager
FCC Compliance Test Group