

**MOTOROLA SOLUTIONS**

TESTING CERT # 2518.01

DECLARATION OF COMPLIANCE: MPE ASSESSMENT**EME Test Laboratory**8000 West Sunrise Blvd
Fort Lauderdale, FL. 33322**Date of Report:** August 15, 2012**Report Revision:** O**Report ID:** SR10192 MPE Auto rpt APX4500 VHF
Rev O 120815

Responsible Engineer: Kim Uong (Principal Staff EME Test Engineer)
Report author: Kim Uong (Principal Staff EME Test Engineer)
Date(s) Tested: 6/27/2012 - 7/11/2012, 7/25/2012, 8/2/2012
Manufacturer/Location: Motorola Solutions, Penang
Date submitted for test: 06/25/2012
DUT Description: APX4500 VHF 50W Band, 136 - 174 MHz
Test TX mode(s): CW
Max. Power output: 60W
TX Frequency Bands: VHF: 136 - 174 MHz
Signaling type: Analog, APCO 25, and TDMA 1:2 (F2)
Model(s) Tested: M22KSS9PW1AN (MUD3222)
Model(s) Certified: M22KSS9PW1AN (MUD3222)
Serial Number(s): WKE0NK03JZ
Classification: Occupational/Controlled Environment
FCC ID: AZ492FT3826
IC: Part 22 & 90: 150.8-173.4 MHz
109U-92FT3826
(138-174 MHz)

Based on the information and the testing results provided herein, the undersigned certifies that when used as stated in the operating instructions supplied, said product complies with the national and international reference standards and guidelines listed in section 3.0 of this report. This report shall not be reproduced without written approval from an officially designated representative of the Motorola Solutions Inc. EME Laboratory.

I attest to the accuracy of the data and assume full responsibility for the completeness of these measurements.

This reporting format is consistent with the suggested guidelines of the TIA TSB-159 April 2006

The results and statements contained in this report pertain only to the device(s) evaluated herein.

Deanna Zakharia
EME Lab Senior Resource Manager and
Laboratory Director

Approval Date: 8/15/2012

Certification Date: 8/16/2012

Certification No.: L1120802P

Document Revision History

Date	Revision	Comments
8/15/2012	O	Initial release

Table of Contents

1.0	Introduction.....	4
2.0	Abbreviations / Definitions.....	4
3.0	Referenced Standards and Guidelines.....	4
4.0	Power Density Limits.....	5
5.0	N _c Test Channels.....	6
6.0	Measurement Equipment	6
7.0	Measurement System Uncertainty Levels.....	6
8.0	Product and System Description	7
9.0	Additional Options and Accessories	7
10.0	Test Set-Up Description.....	7
11.0	Method of Measurement with trunk mounted antenna(s).....	8
11.1	External/Bystander vehicle MPE measurements.....	8
11.2	Internal/Passenger vehicle MPE measurements	8
12.0	Method of Measurement with roof mounted antenna(s).....	9
12.1	External/Bystander vehicle MPE measurements.....	9
12.2	Internal/Passenger vehicle MPE measurements	9
13.0	MPE Calculations	10
14.0	Antenna Summary.....	11
15.0	Test Results Summary	11
16.0	Conclusion	22
	Appendix A - Illustration of Antenna Locations and Test Distances	23
	Appendix B - Probe Calibration Certificates	26
	Appendix C - Photos of Assessed Antennas.....	33
	Appendix D – MPE Measurement Results	34
	Appendix E – SAR Simulation Results	59

1.0 Introduction

This report details the test setup, test equipment and test results of Maximum Permissible Exposure (MPE) performed at Motorola Solutions' outside test site for product model M22KSS9PW1AN (MUD3222).

2.0 Abbreviations / Definitions

APCO: Association of Public-Safety Communications Officials

BS: Bystander

C4FM: Compatible 4-Level Frequency Modulation

CNR: Calibration Not Required

CQPSK: Compatible Quadrature Phase Shift Keying

CW: Continuous Wave

DUT: Device Under Test

EME: Electromagnetic Energy

F2: 2 slot Time Division Multiple Access

FM: Frequency Modulation

MPE: Maximum Permissible Exposure

NA: Not Applicable

PB: Passenger Backseat

PF: Passenger Front seat

PTT: Push to Talk

TDMA: Time Division Multiple Access

3.0 Referenced Standards and Guidelines

This product is designed to comply with the following applicable national and international standards and guidelines.

- United States Federal Communications Commission, Code of Federal Regulations; Rule Part 47CFR § 1.1310, § 2.1091 (d) and § 2.1093 for RF Exposure, where applicable.
- Federal Communications Commission, "Evaluating Compliance with FCC Guidelines for Human Exposure to Radio frequency Electromagnetic Fields", OET Bulletin 65, Supplement C (Edition 01-01), FCC, Washington, D.C.: June 2001.
- American National Standards Institute (ANSI) / Institute of Electrical and Electronics Engineers (IEEE) C95. 1-1999
- American National Standards Institute (ANSI) / Institute of Electrical and Electronics Engineers (IEEE) C95. 1-1992. Specific to FCC rules and regulations.
- Institute of Electrical and Electronics Engineers (IEEE) C95.3-2002
- International Commission on Non-Ionizing Radiation Protection (ICNIRP) 1998
- Ministry of Health (Canada) Safety Code 6 (2009), Limits of Human Exposure to Radio frequency Electromagnetic Fields in the Frequency Range from 3 kHz to 300 GHz

4.0 Power Density Limits

Table 1 – Occupational / Controlled Exposure Limits

Frequency Range (MHz)	FCC OET Bulletin 65 Supplement C	ICNIRP	IEEE C95.1 1992/1999	IEEE C95.1 2005	RSS 102 issue 4 - 2010
	mW/cm ²	W/m ²	mW/cm ²	W/m ²	W/m ²
30 - 300	1.0				*10.0
10 - 400		10.0			
100 - 300			1.0	10.0	
300 - 1,500	f/300				f/30
300 - 3,000			f/300	f/30	
400 - 2,000		f/40			
1,500 - 15,000					50.0
1,500 - 100,000	5.0				
2,000 – 300,000		50.0			
3,000 - 300,000			10.0	100.0	

*Power density limit is applicable at frequencies greater than 100MHz

Table 2 – General Population / Uncontrolled Exposure Limits

Frequency Range (MHz)	FCC OET Bulletin 65 Supplement C	ICNIRP	IEEE C95.1 1992/1999	IEEE C95.1 2005	RSS 102 issue 4 – 2010
	mW/cm ²	W/m ²	mW/cm ²	W/m ²	W/m ²
30 – 300	0.2				*2.0
10 – 400		2.0			
100 – 300			0.2		
100 – 400				2.0	
300 – 1,500	f/1,500				f/150
400 – 2,000		f/200		f/200	
300 – 15,000			f/1,500		
1,500 – 15,000					10.0
1,500 – 100,000	1.0				
2,000 – 100,000				10.0	
2,000 – 300,000		10.0			

*Power density limit is applicable at frequencies greater than 100MHz

5.0 N_c Test Channels

The number of test channels are determined by using Equation 1 below. This equation is available in FCC's KDB 447498. The test channels are appropriately spaced across the antenna's frequency range.

Equation 1 – Number of test channels

$$N_c = \text{Round} \{ [100(f_{\text{high}} - f_{\text{low}})/f_c]^{0.5} \times (f_c / 100)^{0.2} \}$$

where N_c is the number of test channels, f_{high} and f_{low} are the highest and lowest frequencies within the transmission band, f_c is the mid-band frequency, and frequencies are in MHz.

6.0 Measurement Equipment

Table 3 - Equipment

Equipment Type	Model #	SN	Calibration Date	Calibration Due Date
Motorcycle	2005 Kawasaki KZ1000	NA	NA	NA
Survey Meter Probe – E-Field	ETS Model HI-2200 ETS Model E100	00086887 00126277	06/11/2012	06/11/2013
Survey Meter Probe – H-Field	ETS Model HI-2200 ETS Model H200	00086887 84225	06/11/2012	06/11/2013

E-field measurements are in mW/cm².

H-field measurements are in A/m.

7.0 Measurement System Uncertainty Levels

Table 4 - Uncertainty Budget for Near Field Probe Measurements

	Tol. (± %)	Prob. Dist.	Divisor	u_i (± %)	v_i
Measurement System					
Probe Calibration	6.0	N	1.00	6.0	∞
Survey Meter Calibration	3.0	N	1.00	3.0	∞
Hemispherical Isotropy	8.0	R	1.73	4.6	∞
Linearity	5.0	R	1.73	2.9	∞
Pulse Response	1.0	R	1.73	0.6	∞
RF Ambient Noise	3.0	R	1.73	1.7	∞
RF Reflections	8.0	R	1.73	4.6	∞
Probe Positioning	10.0	R	1.73	5.8	∞
Test sample Related					
Antenna Positioning	3.0	N	1.00	3.0	∞
Power drift	5.0	R	1.73	2.9	∞
Combined Standard Uncertainty		RSS		12.2	∞
Expanded Uncertainty (95% CONFIDENCE LEVEL)		$k=2$		24	

8.0 Product and System Description

Model M22KSS9PW1AN (MUD3222) is a mobile transceiver that utilizes analog, APCO 25 & F2 digital two-way radio communications. The analog modulation scheme uses Frequency Modulation (FM). APCO 25 & F2 digital modes use C4FM of CQPSK family of modulation (Compatible 4-Level Frequency Modulation of Compatible Quadrature Phase Shift Keying). F2 is a TDMA 1:2 protocol that allocates portions of the RF signal by dividing time into two slots (2 slots TDMA). Transmission from a unit or base station is accommodated in time-slot lengths of 30 milliseconds and frame lengths of 60 milliseconds. This product supports voice in analog mode, and both voice and data modes in digital mode.

The maximum duty cycle for TDMA is 1:2 (50%) and is controlled by software. The FM signal is continuous. However, because of hand shaking or Push-To-Talk (PTT) between users and/or base stations a conservative 50% duty cycle is applied. The TDMA mode was not tested because its duty cycle is inherently 50% and would include an additional 50% duty cycle for PTT.

The intended use of the radio is PTT while the device is properly installed in a vehicle with an external antenna mounted at the roof or trunk.

This device will be marketed to and used by employees solely for work-related operations, such as public safety agencies, e.g. police, fire and emergency medical. User training is the responsibility of these agencies which can be expected to employ the usage instructions, safety information and operational cautions set forth in the user's manual, instructional sessions or other means.

Accordingly this product is classified as Occupational/Controlled Exposure. However, in accordance with FCC requirements, the passengers inside the vehicle and the bystanders external to the vehicle are evaluated to the General Population/Uncontrolled Exposure Limits.

(Note that "Bystanders" as used herein are people other than operator)

9.0 Additional Options and Accessories

Refer to Table 5 for complete list of tested antennas.

10.0 Test Set-Up Description

Assessments were performed with mobile radio installed in the test vehicle while engine was at idle, at the specified distances and test locations indicated in sections 11.0, 12.0 and Appendix A.

All antennas described in Table 5 were considered in order to develop the test plan for this product. Antennas were installed and tested per their appropriate mount locations (Roof / Trunk) and defined test channels.

11.0 Method of Measurement with trunk mounted antenna(s)

11.1 External/Bystander vehicle MPE measurements

Antenna is located at the center of the trunk. Refer to Appendix A for antenna location and distance.

MPE measurements for bystander (BS) conditions are determined by taking the average of (10) measurements in a 2 m vertical line for each of the (3) bystander test locations indicated in Appendix A with 20 cm height increments, with antenna to probe sensor separation distances of 90 cm directly behind the vehicle, 104 cm (45 degree radial) and 110.5 cm (90 degree radial). The separation distance used for testing is defined from the antenna where as the RF safety booklet defines the same distance from the vehicle body to ensure that the assessment is applicable to other vehicles. The measurement probe is positioned orthogonal to antenna (typically parallel to ground with a vertically mounted antenna) and aimed directly at the antenna's axis. These measurements are representative of persons other than the operator standing next to the vehicle.

Each of the offered antennas mounted at the center of the trunk were assessed at the rear of the vehicle while maintaining a minimum of twenty (20) centimeter separation distance between the probe sensor and vehicle body. The antenna/frequency for each of the antenna types (1/2 wave, 5/8 wave) with highest MPE result was then tested at a 45° radial at the corner of the trunk, and 90° radial at the side of the trunk.

Note: The 90cm includes the distance from the centered trunk-mounted antenna to the rear edge of the vehicle is 42cm, and the distance from the rear edge of the vehicle to the survey probe sensor is 48cm.

11.2 Internal/Passenger vehicle MPE measurements

Antenna is located toward the center of the trunk at a minimum 85cm from backseat passenger. Users are instructed, per installation manual, to mount antennas on the roof only if a minimum 85cm cannot be achieved. Refer to Appendix A for antenna location and distance.

MPE measurements for passenger front seat (PF) and backseat (PB) conditions are determined by taking the average of the (3) measurements (Head, Chest, and Lower Trunk) inside the vehicle for both the front and back seats.

The backseat is a bench seat and therefore each position (Head, Chest & Lower Trunk) were scanned across (horizontally) the seat starting from the middle of the seat to the edge of the seat stopping 20 cm from the vehicle door. Similar process was used in the front bucket seat.

The probe handle is oriented parallel (horizontal) to the ground and pointed towards the back of the vehicle. The probe handle is not oriented normal to the seat surface. The probe head (incorporating the field sensors) is scanned continuously (using the max-hold function available in the meter) along three test axes which are parallel to the seat angle (intended as the line determined by the intersection of the plane of the seat and the plane of the backrest) and are 20 cm from the seat surface. One test axis is at the Head height, another is at the Chest height, and another is at the Lower Trunk height. The maximum field level value recorded for each test axis is logged. The MPE is determined by averaging these three maximum values regardless of the geometrical location where they were observed.

For instance, the locations of the three maxima may lie on different vertical (relative to ground) lines.

This approach leads to results that are representative of the exposure of vehicle occupants since it is based on an average across the body portions closest to the antenna for both trunk and roof mount positions, and is conservatively biased because the highest results for each test axis are combined, e.g. the highest head exposure could be in the middle of the seat while the highest lower trunk exposure could be closer to the door.

12.0 Method of Measurement with roof mounted antenna(s)

12.1 External/Bystander vehicle MPE measurements

Antenna is located at the center of the roof. Refer to Appendix A for antenna location and distance.

MPE measurements for bystander (BS) conditions are determined by taking the average of (10) measurements in a 2m vertical line for the test location indicated in Appendix A with 20cm increments at the test distance of 117cm from the antenna under test. The measurement probe is positioned orthogonal to antenna (typically parallel to ground with a vertically mounted antenna) and aimed directly at the antenna's axis. These measurements are representative of persons other than the operator standing next to the vehicle.

Note: Actual test distance was approximately 117cm from centered roof-mounted antenna to the probe element (97cm from antenna to edge of car door and 20cm from the edge of the car door to the survey probe sensor); this is the closest distance that can be achieved to a centered roof-mounted antenna used for MPE compliance assessment herein.

12.2 Internal/Passenger vehicle MPE measurements

Antenna is located at the center of the roof. Refer to Appendix A for antenna location and distance.

MPE measurements for passenger front seat (PF) and backseat (PB) conditions are determined by taking the average of the (3) measurements (Head, Chest, and Lower Trunk) inside the vehicle for both the front and back seats.

The backseat is a bench seat and therefore each position (Head, Chest & Lower Trunk) were scanned across (horizontally) the seat starting from the middle of the seat to the edge of the seat stopping 20 cm from the vehicle door. Similar process was used in the front bucket seat.

The probe handle is oriented parallel (horizontal) to the ground and pointed towards the back of the vehicle. The probe handle is not oriented normal to the seat surface. The probe head (incorporating the field sensors) is scanned continuously (using the max-hold function available in the meter) along three test axes which are parallel to the seat angle (intended as the line determined by the intersection of the plane of the seat and the plane of the backrest) and are 20 cm from the seat surface. One test axis is at the Head height, another is at the Chest height, and another is at the Lower Trunk height. The maximum field level value recorded for each test axis is logged. The MPE is determined by averaging these three maximum values regardless of the geometrical location where they were observed. For instance, the locations of the three maxima may lie on different vertical (relative to ground) lines.

This approach leads to results that are representative of the exposure of vehicle occupants since it is based on an average across the body portions closest to the antenna for both trunk and roof mount positions, and is conservatively biased because the highest results for each test axis are combined, e.g. the highest head exposure could be in the middle of the seat while the highest lower trunk exposure could be closer to the door.

13.0 MPE Calculations

The final MPE results for this mobile radio are presented in section 15.0 Tables 6 - 9. These results are based on 50% duty cycle for PTT.

Below is an explanation of how the MPE results are calculated. Refer to Appendix D for MPE measurement results and calculations.

External to vehicle (Bystander) - 10 measurements are averaged over the body (*Avg_over_body*).
Internal to vehicle (Passengers) - 3 measurements are averaged over the body (*Avg_over_body*).

The Average over Body test methodology is consistent with IEEE/ANSI C95.3-2002 guidelines.

Therefore;

Equation 2 – Power Density Calculation (*Calc._P.D.*)

$$\text{Calc._P.D.} = (\text{Avg_over_body}) * (\text{probe_frequency_cal_factor}) * (\text{duty_cycle})$$

Note 1: The highest “average” cal factors from the calibration certificates were selected for the applicable frequency range. Linear interpretation was used to determine “probe_frequency_cal_factor” for the specific test frequencies.

Note 2: The E-field probe calibration certificate’s frequency cal factors were determined by measuring V/m. The survey meter’s results were measured in power density (mW/cm²) and therefore the “probe_frequency_cal_factor” was squared in equation 2 to account for these results.

Note 3: The H-field probe calibration certificate’s frequency cal factors were determined by measuring A/m. The survey meter’s results were measured in A/m and therefore the “Avg_over_body” A/m results were converted to power density (mW/cm²) using the equation 3. H-field measurements are only applicable to frequencies below 300MHz.

Equation 3 – Converting A/m to mW/cm²

$$\text{mW/cm}^2 = (\text{A/m})^2 * 37.699$$

Equation 4 – Power Density Maximum Calculation

$$\text{Max_Calc._P.D.} = \text{P.D._calc} * \frac{\text{max_output_power}}{\text{initial_output_power}}$$

Note 4: For initial output power > max_output_power; max_output_power / initial output power = 1

14.0 Antenna Summary

Table 5 below summarizes the tested antennas and their descriptions, mount location (roof/trunk), overlap of FCC bands, number of test channels per FCC KDB 447498 (FCC N_c) and actual number of tested channels (Actual N_c). This information was used to determine the test configurations presented in this report.

Table 5

#	Antenna Model	Frequency Range (MHz)	Physical Length (cm)	Gain (dBi)	Remarks	Mount Location (Roof/Trunk)	Overlap FCC Bands	FCC N_c	Actual N_c
1	HAD4006A	136-144	52.0	2.15	1/4 wave, wire	R	NA	3	3
2	HAD4007A	144-150.8	49.0	2.15	1/4 wave, wire	R	150.8	2	3
3	HAD4008A	150.8-162	45.5	2.15	1/4 wave, wire	R	150.8-162	3	3
4	HAD4009A	162-174	43.0	2.15	1/4 wave, wire	R	162-174	3	3
5	*RAD4010ARB	136-174	143.5 137.5 130.5 126.8 116.5 112.5 103.5	5.15	1/2 wave, wire	R/T	150.8-173.4	5	7
6	HAD4016A	136-162	51.0	2.15	1/4 wave, wire	R	150.8-162	5	5
7	HAD4017A	146-174	47.5	2.15	1/4 wave, wire	R	150.8-173.4	5	5
8	HAD4021A	136-174	51.7	2.15	1/4 wave, wire	R	150.8-173.4	5	7
9	*HAD4022A	132-174	130 127.5 118.3 113.8 102.7 96.5 89.9	5.15	5/8 wave, wire	R/T	150.8-173.4	5	7

* Antennas trimmed per test frequency.

15.0 Test Results Summary

The following tables below summarize the MPE results for each test configuration: antenna location, test positions (BS-Bystander, PB-Passenger Backseat, PF-Passenger Front seat), E/H field measurements, angle, antenna model & freq. range, maximum output power, initial power, TX frequency, max calculated power density results, applicable FCC/IEEE/ICNIRP specification limits and % of the applicable specification limits.

Table 6
Bystander MPE assessment for trunk mounted antennas

Trunk/ Roof	Test Position	E/H Field	Angle (Degree)	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ICNIRP Limit	% To ICNIRP Spec Limit
E- Field Measurement Data												
Trunk	BS	E	0	RAD4010ARB (136-174 MHz)	60	59.1	136.000	0.10	0.20	52.1	0.20	52.1
						60.1	140.000	0.11	0.20	52.7	0.20	52.7
						60.6	144.000	0.12	0.20	57.5	0.20	57.5
						60.8	150.800	0.10	0.20	49.6	0.20	49.6
						61.5	158.300	0.12	0.20	59.2	0.20	59.2
						61.4	165.900	0.09	0.20	44.6	0.20	44.6
						61.8	173.400	0.15	0.20	77.1	0.20	77.1
Trunk	BS	E	45	RAD4010ARB (136-174 MHz)	60	61.8	173.400	0.11	0.20	56.7	0.20	56.7
			90			61.8	173.400	0.11	0.20	56.3	0.20	56.3
Trunk	BS	E	0	HAD4022A (132-174 MHz)	60	59.1	136.000	0.11	0.20	56.1	0.20	56.1
						60.1	140.000	0.12	0.20	57.8	0.20	57.8
						60.6	144.000	0.13	0.20	66.3	0.20	66.3
						60.8	150.800	0.11	0.20	56.1	0.20	56.1
						61.5	158.300	0.13	0.20	62.6	0.20	62.6
						61.4	165.900	0.13	0.20	66.7	0.20	66.7
						61.8	173.400	0.14	0.20	71.3	0.20	71.3
Trunk	BS	E	45	HAD4022A (132-174 MHz)	60	61.8	173.400	0.16	0.20	77.8	0.20	77.8
			90			61.8	173.400	0.13	0.20	67.2	0.20	67.2

Table 6 (continued)
Bystander MPE assessment for trunk mounted antennas

Trunk/ Roof	Test Position	E/H Field	Angle (Degree)	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm^2)	FCC Limit	% To FCC Spec Limit	ICNIRP Limit	% To ICNIRP Spec Limit
H- Field Measurement Data												
Trunk	BS	H	0	RAD4010ARB (136-174 MHz)	60	59.1	136.000	0.08	0.20	38.8	0.20	38.8
						60.1	140.000	0.08	0.20	40.2	0.20	40.2
						60.6	144.000	0.10	0.20	51.1	0.20	51.1
						60.8	150.800	0.09	0.20	43.2	0.20	43.2
						61.5	158.300	0.12	0.20	58.5	0.20	58.5
						61.4	165.900	0.09	0.20	43.4	0.20	43.4
						61.8	173.400	0.17	0.20	83.7	0.20	83.7
Trunk	BS	H	45	RAD4010ARB (136-174 MHz)	60	61.8	173.400	0.13	0.20	66.2	0.20	66.2
			90			61.8	173.400	0.13	0.20	66.1	0.20	66.1
Trunk	BS	H	0	HAD4022A (132 -174 MHz)	60	59.1	136.000	0.11	0.20	54.0	0.20	54.0
						60.1	140.000	0.10	0.20	52.4	0.20	52.4
						60.6	144.000	0.13	0.20	63.3	0.20	63.3
						60.8	150.800	0.11	0.20	54.8	0.20	54.8
						61.5	158.300	0.13	0.20	65.1	0.20	65.1
						61.4	165.900	0.14	0.20	68.8	0.20	68.8
						61.8	173.400	0.15	0.20	77.4	0.20	77.4
Trunk	BS	H	45	HAD4022A (132 -174 MHz)	60	61.8	173.400	0.18	0.20	89.5	0.20	89.5
			90			61.8	173.400	0.17	0.20	82.8	0.20	82.8

Table 7

Passenger MPE assessment for trunk mounted antennas

Trunk/ Roof	Test Position	E/H Field	Angle (Degree)	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm^2)	FCC Limit	% To FCC Spec Limit	ICNIRP Limit	% To ICNIRP Spec Limit
E - Field Measurement Data												
Trunk	PB	E	NA	RAD4010ARB (136-174 MHz)	60	59.1	136.000	0.03	0.20	16.9	0.20	16.9
						60.1	140.000	0.00	0.20	1.3	0.20	1.3
						60.6	144.000	0.01	0.20	4.5	0.20	4.5
						60.8	150.800	0.02	0.20	9.1	0.20	9.1
						61.5	158.300	0.04	0.20	20.3	0.20	20.3
						61.4	165.900	0.13	0.20	64.3	0.20	64.3
						61.8	173.400*	0.23	0.20	112.8	0.20	112.8
Trunk	PB	E	NA	HAD4022A (132-174 MHz)	60	59.1	136.000	0.02	0.20	10.0	0.20	10.0
						60.1	140.000	0.09	0.20	42.6	0.20	42.6
						60.6	144.000	0.13	0.20	66.2	0.20	66.2
						60.8	150.800	0.16	0.20	79.2	0.20	79.2
						61.5	158.300*	0.35	0.20	172.5	0.20	172.5
						61.4	165.900*	0.56	0.20	281.7	0.20	281.7
						61.8	173.400*	0.26	0.20	131.3	0.20	131.3
Trunk	PF	E	NA	RAD4010ARB (136-174 MHz)	60	59.1	136.000	0.01	0.20	4.6	0.20	4.6
						60.1	140.000	0.01	0.20	4.1	0.20	4.1
						60.6	144.000	0.01	0.20	3.1	0.20	3.1
						60.8	150.800	0.01	0.20	3.8	0.20	3.8
						61.5	158.300	0.01	0.20	7.1	0.20	7.1
						61.4	165.900	0.02	0.20	9.8	0.20	9.8
						61.8	173.400	0.07	0.20	36.1	0.20	36.1
Trunk	PF	E	NA	HAD4022A (132-174 MHz)	60	59.1	136.000	0.01	0.20	3.3	0.20	3.3
						60.1	140.000	0.01	0.20	5.9	0.20	5.9
						60.6	144.000	0.02	0.20	11.8	0.20	11.8
						60.8	150.800	0.03	0.20	16.4	0.20	16.4
						61.5	158.300	0.05	0.20	25.8	0.20	25.8
						61.4	165.900	0.10	0.20	48.2	0.20	48.2
						61.8	173.400	0.08	0.20	38.3	0.20	38.3

*Test configuration exceeds MPE FCC (General Population/Uncontrolled) spec limit.

Table 7 (continued)

Passenger MPE assessment for trunk mounted antennas

Trunk/ Roof	Test Position	E/H Field	Angle (Degree)	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm^2)	FCC Limit	% To FCC Spec Limit	ICNIRP Limit	% To ICNIRP Spec Limit
H - Field Measurement Data												
Trunk	PB	H	NA	RAD4010ARB (136-174 MHz)	60	59.1	136.000	0.02	0.20	12.5	0.20	12.5
						60.1	140.000	0.00	0.20	1.5	0.20	1.5
						60.6	144.000	0.00	0.20	1.6	0.20	1.6
						60.8	150.800	0.01	0.20	4.1	0.20	4.1
						61.5	158.300	0.03	0.20	12.8	0.20	12.8
						61.4	165.900	0.08	0.20	37.6	0.20	37.6
						61.8	173.400	0.11	0.20	54.3	0.20	54.3
Trunk	PB	H	NA	HAD4022A (132 -174 MHz)	60	59.1	136.000	0.01	0.20	6.8	0.20	6.8
						60.1	140.000	0.03	0.20	17.1	0.20	17.1
						60.6	144.000	0.06	0.20	28.9	0.20	28.9
						60.8	150.800	0.07	0.20	35.8	0.20	35.8
						61.5	158.300	0.17	0.20	83.4	0.20	83.4
						61.4	165.900*	0.33	0.20	167.1	0.20	167.1
						61.8	173.400	0.15	0.20	76.6	0.20	76.6
Trunk	PF	H	NA	RAD4010ARB (136-174 MHz)	60	59.1	136.000	0.01	0.20	6.8	0.20	6.8
						60.1	140.000	0.01	0.20	3.7	0.20	3.7
						60.6	144.000	0.01	0.20	2.9	0.20	2.9
						60.8	150.800	0.01	0.20	3.6	0.20	3.6
						61.5	158.300	0.01	0.20	3.9	0.20	3.9
						61.4	165.900	0.01	0.20	3.8	0.20	3.8
						61.8	173.400	0.03	0.20	16.8	0.20	16.8
Trunk	PF	H	NA	HAD4022A (132 -174 MHz)	60	59.1	136.000	0.00	0.20	2.5	0.20	2.5
						60.1	140.000	0.01	0.20	5.7	0.20	5.7
						60.6	144.000	0.02	0.20	11.8	0.20	11.8
						60.8	150.800	0.03	0.20	14.7	0.20	14.7
						61.5	158.300	0.03	0.20	12.6	0.20	12.6
						61.4	165.900	0.04	0.20	19.4	0.20	19.4
						61.8	173.400	0.04	0.20	18.2	0.20	18.2

*Test configuration exceeds MPE FCC (General Population/Uncontrolled) spec limit.

Table 8
Bystander MPE assessment for roof mounted antennas

Trunk/ Roof	Test Position	E/H Field	Angle (Degree)	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ICNIRP Limit	% To ICNIRP Spec Limit
E - Field Measurement Data												
Roof	BS	E	0	HAD4021A (136 -174MHz)	60	59.1	136.000	0.05	0.20	25.7	0.20	25.7
						60.1	140.000	0.06	0.20	30.6	0.20	30.6
						60.6	144.000	0.06	0.20	30.2	0.20	30.2
						60.8	150.800	0.06	0.20	27.8	0.20	27.8
						61.5	158.300	0.06	0.20	31.3	0.20	31.3
						61.4	165.900	0.06	0.20	27.7	0.20	27.7
						61.8	173.400	0.06	0.20	29.0	0.20	29.0
				HAD4006A (136-144 MHz)	60	59.1	136.000	0.08	0.20	39.7	0.20	39.7
						60.1	140.000	0.08	0.20	37.7	0.20	37.7
						60.6	144.000	0.07	0.20	34.7	0.20	34.7
				HAD4007A (144-150.8 MHz)	60	60.6	144.000	0.07	0.20	33.2	0.20	33.2
						60.7	148.000	0.06	0.20	31.5	0.20	31.5
						60.8	150.800	0.06	0.20	29.9	0.20	29.9
				HAD4008A (150.8-162 MHz)	60	60.8	150.800	0.06	0.20	30.7	0.20	30.7
						61.3	156.200	0.08	0.20	37.9	0.20	37.9
						61.3	162.000	0.08	0.20	40.1	0.20	40.1
				HAD4009A (162-174 MHz)	60	61.3	162.000	0.07	0.20	35.2	0.20	35.2
						61.5	167.700	0.08	0.20	39.2	0.20	39.2
						61.8	173.400	0.08	0.20	40.0	0.20	40.0
				HAD4016A (136-162 MHz)	60	59.1	136.000	0.07	0.20	32.6	0.20	32.6
						60.6	144.000	0.06	0.20	31.9	0.20	31.9
						60.8	150.800	0.06	0.20	28.2	0.20	28.2
						61.3	156.200	0.08	0.20	40.4	0.20	40.4
						61.3	162.000	0.06	0.20	30.9	0.20	30.9
				HAD4017A (146-174 MHz)	60	60.7	146.000	0.04	0.20	17.6	0.20	17.6
						60.8	150.800	0.06	0.20	29.8	0.20	29.8
						61.5	158.300	0.08	0.20	38.3	0.20	38.3
						61.4	165.900	0.07	0.20	35.8	0.20	35.8
						61.8	173.400	0.07	0.20	36.7	0.20	36.7
				RAD4010ARB (136-174 MHz)	60	59.1	136.000	0.03	0.20	17.4	0.20	17.4
						60.1	140.000	0.03	0.20	17.2	0.20	17.2
						60.6	144.000	0.04	0.20	19.9	0.20	19.9
						60.8	150.800	0.03	0.20	16.9	0.20	16.9
						61.5	158.300	0.04	0.20	22.3	0.20	22.3
						61.4	165.900	0.04	0.20	17.7	0.20	17.7
						61.8	173.400	0.06	0.20	30.8	0.20	30.8
				HAD4022A (132-174 MHz)	60	59.1	136.000	0.04	0.20	21.4	0.20	21.4
						60.1	140.000	0.04	0.20	20.2	0.20	20.2
						60.6	144.000	0.04	0.20	20.1	0.20	20.1
						60.8	150.800	0.04	0.20	21.0	0.20	21.0
						61.5	158.300	0.06	0.20	31.5	0.20	31.5
						61.4	165.900	0.06	0.20	28.0	0.20	28.0
						61.8	173.400	0.07	0.20	33.4	0.20	33.4

Table 8 (continued)
Bystander MPE assessment for roof mounted antennas

Trunk/ Roof	Test Position	E/H Field	Angle (Degree)	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm^2)	FCC Limit	% To FCC Spec Limit	ICNIRP Limit	% To ICNIRP Spec Limit
H - Field Measurement Data												
Roof	BS	H	0	HAD4021A (136 -174MHz)	60	59.1	136.000	0.05	0.20	25.8	0.20	25.8
						60.1	140.000	0.06	0.20	29.7	0.20	29.7
						60.6	144.000	0.06	0.20	31.6	0.20	31.6
						60.8	150.800	0.05	0.20	27.1	0.20	27.1
						61.5	158.300	0.06	0.20	28.9	0.20	28.9
						61.4	165.900	0.05	0.20	27.5	0.20	27.5
						61.8	173.400	0.06	0.20	28.1	0.20	28.1
				HAD4006A (136-144 MHz)	60	59.1	136.000	0.07	0.20	37.5	0.20	37.5
						60.1	140.000	0.07	0.20	37.0	0.20	37.0
						60.6	144.000	0.07	0.20	36.5	0.20	36.5
				HAD4007A (144-150.8 MHz)	60	60.6	144.000	0.07	0.20	34.0	0.20	34.0
						60.7	148.000	0.07	0.20	32.9	0.20	32.9
						60.8	150.800	0.06	0.20	32.2	0.20	32.2
				HAD4008A (150.8-162 MHz)	60	60.8	150.800	0.07	0.20	32.6	0.20	32.6
						61.3	156.200	0.08	0.20	38.8	0.20	38.8
						61.3	162.000	0.07	0.20	36.1	0.20	36.1
				HAD4009A (162-174 MHz)	60	61.3	162.000	0.07	0.20	35.1	0.20	35.1
						61.5	167.700	0.07	0.20	36.4	0.20	36.4
						61.8	173.400	0.08	0.20	40.6	0.20	40.6
				HAD4016A (136-162 MHz)	60	59.1	136.000	0.07	0.20	32.6	0.20	32.6
						60.6	144.000	0.07	0.20	33.5	0.20	33.5
						60.8	150.800	0.06	0.20	29.3	0.20	29.3
						61.3	156.200	0.08	0.20	38.8	0.20	38.8
						61.3	162.000	0.06	0.20	30.0	0.20	30.0
				HAD4017A (146-174 MHz)	60	60.7	146.000	0.04	0.20	20.9	0.20	20.9
						60.8	150.800	0.06	0.20	31.5	0.20	31.5
						61.5	158.300	0.07	0.20	35.8	0.20	35.8
						61.4	165.900	0.07	0.20	34.6	0.20	34.6
						61.8	173.400	0.07	0.20	36.5	0.20	36.5
				RAD4010ARB (136-174 MHz)	60	59.1	136.000	0.02	0.20	11.2	0.20	11.2
						60.1	140.000	0.02	0.20	11.2	0.20	11.2
						60.6	144.000	0.03	0.20	15.4	0.20	15.4
						60.8	150.800	0.02	0.20	11.3	0.20	11.3
						61.5	158.300	0.03	0.20	16.8	0.20	16.8
						61.4	165.900	0.03	0.20	14.5	0.20	14.5
						61.8	173.400	0.06	0.20	28.8	0.20	28.8
				HAD4022A (132-174 MHz)	60	59.1	136.000	0.04	0.20	17.6	0.20	17.6
						60.1	140.000	0.03	0.20	16.4	0.20	16.4
						60.6	144.000	0.08	0.20	40.0	0.20	40.0
						60.8	150.800	0.04	0.20	17.9	0.20	17.9
						61.5	158.300	0.05	0.20	26.8	0.20	26.8
						61.4	165.900	0.05	0.20	26.2	0.20	26.2
						61.8	173.400	0.07	0.20	33.3	0.20	33.3

Table 9

Passenger MPE assessment for roof mounted antennas

Trunk/ Roof	Test Position	E/H Field	Angle (Degree)	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm^2)	FCC Limit	% To FCC Spec Limit	ICNIRP Limit	% To ICNIRP Spec Limit
Roof	PB	E	NA	HAD4021A (136 -174MHz)	60	59.1	136.000	0.09	0.20	44.1	0.20	44.1
						60.1	140.000	0.15	0.20	76.8	0.20	76.8
						60.6	144.000	0.14	0.20	69.6	0.20	69.6
						60.8	150.800	0.07	0.20	35.0	0.20	35.0
						61.5	158.300	0.02	0.20	9.1	0.20	9.1
						61.4	165.900	0.07	0.20	35.8	0.20	35.8
						61.8	173.400	0.03	0.20	17.0	0.20	17.0
				HAD4006A (136-144 MHz)	60	59.1	136.000	0.19	0.20	94.7	0.20	94.7
						60.1	140.000	0.20	0.20	98.5	0.20	98.5
						60.6	144.000	0.14	0.20	68.9	0.20	68.9
				HAD4007A (144-150.8 MHz)	60	60.6	144.000	0.13	0.20	64.8	0.20	64.8
						60.7	148.000	0.05	0.20	26.4	0.20	26.4
						60.8	150.800	0.07	0.20	32.9	0.20	32.9
				HAD4008A (150.8-162 MHz)	60	60.8	150.800	0.07	0.20	35.6	0.20	35.6
						61.3	156.200	0.05	0.20	27.1	0.20	27.1
						61.3	162.000	0.07	0.20	34.1	0.20	34.1
				HAD4009A (162-174 MHz)	60	61.3	162.000	0.06	0.20	30.9	0.20	30.9
						61.5	167.700	0.07	0.20	34.6	0.20	34.6
						61.8	173.400	0.05	0.20	24.3	0.20	24.3
				HAD4016A (136-162 MHz)	60	59.1	136.000	0.08	0.20	42.1	0.20	42.1
						60.6	144.000	0.11	0.20	54.9	0.20	54.9
						60.8	150.800	0.06	0.20	32.3	0.20	32.3
						61.3	156.200	0.06	0.20	27.9	0.20	27.9
						61.3	162.000	0.06	0.20	29.9	0.20	29.9
				HAD4017A (146-174 MHz)	60	60.7	146.000	0.04	0.20	21.2	0.20	21.2
						60.8	150.800	0.07	0.20	35.8	0.20	35.8
						61.5	158.300	0.02	0.20	9.5	0.20	9.5
						61.4	165.900	0.09	0.20	46.6	0.20	46.6
						61.8	173.400	0.06	0.20	28.5	0.20	28.5
				RAD4010ARB (136-174 MHz)	60	59.1	136.000	0.05	0.20	22.9	0.20	22.9
						60.1	140.000	0.02	0.20	9.8	0.20	9.8
						60.6	144.000	0.03	0.20	12.7	0.20	12.7
						60.8	150.800	0.04	0.20	17.9	0.20	17.9
						61.5	158.300	0.02	0.20	11.5	0.20	11.5
						61.4	165.900	0.02	0.20	8.9	0.20	8.9
						61.8	173.400	0.03	0.20	12.9	0.20	12.9
				HAD4022A (132-174 MHz)	60	59.1	136.000	0.02	0.20	9.5	0.20	9.5
						60.1	140.000	0.02	0.20	10.3	0.20	10.3
						60.6	144.000	0.04	0.20	17.9	0.20	17.9
						60.8	150.800	0.02	0.20	9.2	0.20	9.2
						61.5	158.300	0.01	0.20	5.4	0.20	5.4
						61.4	165.900	0.06	0.20	28.8	0.20	28.8
						61.8	173.400	0.03	0.20	16.3	0.20	16.3

Table 9 (continued)

Passenger MPE assessment for roof mounted antennas

Trunk/ Roof	Test Position	E/H Field	Angle (Degree)	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm^2)	FCC Limit	% To FCC Spec Limit	ICNIRP Limit	% To ICNIRP Spec Limit
Roof	PF	E	NA	HAD4021A (136 -174MHz)	60	59.1	136.000	0.03	0.20	13.7	0.20	13.7
						60.1	140.000	0.08	0.20	39.9	0.20	39.9
						60.6	144.000	0.08	0.20	39.8	0.20	39.8
						60.8	150.800	0.05	0.20	24.0	0.20	24.0
						61.5	158.300	0.03	0.20	15.7	0.20	15.7
						61.4	165.900	0.01	0.20	7.3	0.20	7.3
						61.8	173.400	0.01	0.20	3.9	0.20	3.9
				HAD4006A (136-144 MHz)	60	59.1	136.000	0.05	0.20	22.8	0.20	22.8
						60.1	140.000	0.05	0.20	27.4	0.20	27.4
						60.6	144.000	0.05	0.20	24.2	0.20	24.2
				HAD4007A (144-150.8 MHz)	60	60.6	144.000	0.04	0.20	21.0	0.20	21.0
						60.7	148.000	0.06	0.20	28.1	0.20	28.1
						60.8	150.800	0.03	0.20	16.1	0.20	16.1
				HAD4008A (150.8-162 MHz)	60	60.8	150.800	0.04	0.20	18.3	0.20	18.3
						61.3	156.200	0.02	0.20	12.2	0.20	12.2
						61.3	162.000	0.04	0.20	19.0	0.20	19.0
				HAD4009A (162-174 MHz)	60	61.3	162.000	0.03	0.20	17.0	0.20	17.0
						61.5	167.700	0.03	0.20	17.2	0.20	17.2
						61.8	173.400	0.02	0.20	9.0	0.20	9.0
				HAD4016A (136-162 MHz)	60	59.1	136.000	0.03	0.20	15.2	0.20	15.2
						60.6	144.000	0.07	0.20	32.9	0.20	32.9
						60.8	150.800	0.03	0.20	15.7	0.20	15.7
						61.3	156.200	0.03	0.20	12.9	0.20	12.9
						61.3	162.000	0.03	0.20	14.4	0.20	14.4
				HAD4017A (146-174 MHz)	60	60.7	146.000	0.04	0.20	18.7	0.20	18.7
						60.8	150.800	0.03	0.20	17.4	0.20	17.4
						61.5	158.300	0.03	0.20	16.5	0.20	16.5
						61.4	165.900	0.04	0.20	21.8	0.20	21.8
						61.8	173.400	0.02	0.20	9.3	0.20	9.3
				RAD4010ARB (136-174 MHz)	60	59.1	136.000	0.01	0.20	5.0	0.20	5.0
						60.1	140.000	0.01	0.20	3.6	0.20	3.6
						60.6	144.000	0.01	0.20	4.7	0.20	4.7
						60.8	150.800	0.01	0.20	6.3	0.20	6.3
						61.5	158.300	0.00	0.20	2.3	0.20	2.3
						61.4	165.900	0.01	0.20	5.1	0.20	5.1
						61.8	173.400	0.02	0.20	9.6	0.20	9.6
				HAD4022A (132-174 MHz)	60	59.1	136.000	0.01	0.20	4.1	0.20	4.1
						60.1	140.000	0.01	0.20	3.3	0.20	3.3
						60.6	144.000	0.01	0.20	6.1	0.20	6.1
						60.8	150.800	0.01	0.20	4.9	0.20	4.9
						61.5	158.300	0.01	0.20	5.5	0.20	5.5
						61.4	165.900	0.01	0.20	7.2	0.20	7.2
						61.8	173.400	0.01	0.20	6.3	0.20	6.3

Table 9 (continued)

Passenger MPE assessment for roof mounted antennas

Trunk/ Roof	Test Position	E/H Field	Angle (Degree)	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm^2)	FCC Limit	% To FCC Spec Limit	ICNIRP Limit	% To ICNIRP Spec Limit
Roof	PB	H	NA	HAD4021A (136 -174MHz)	60	59.1	136.000	0.03	0.20	12.8	0.20	12.8
						60.1	140.000	0.03	0.20	15.3	0.20	15.3
						60.6	144.000	0.03	0.20	15.0	0.20	15.0
						60.8	150.800	0.03	0.20	15.1	0.20	15.1
						61.5	158.300	0.02	0.20	8.1	0.20	8.1
						61.4	165.900	0.03	0.20	13.2	0.20	13.2
						61.8	173.400	0.02	0.20	9.9	0.20	9.9
				HAD4006A (136-144 MHz)	60	59.1	136.000	0.05	0.20	24.4	0.20	24.4
						60.1	140.000	0.08	0.20	38.7	0.20	38.7
						60.6	144.000	0.08	0.20	38.4	0.20	38.4
				HAD4007A (144-150.8 MHz)	60	60.6	144.000	0.07	0.20	36.6	0.20	36.6
						60.7	148.000	0.03	0.20	16.7	0.20	16.7
						60.8	150.800	0.04	0.20	20.1	0.20	20.1
				HAD4008A (150.8-162 MHz)	60	60.8	150.800	0.04	0.20	20.1	0.20	20.1
						61.3	156.200	0.02	0.20	12.3	0.20	12.3
						61.3	162.000	0.04	0.20	18.4	0.20	18.4
				HAD4009A (162-174 MHz)	60	61.3	162.000	0.03	0.20	16.3	0.20	16.3
						61.5	167.700	0.07	0.20	32.7	0.20	32.7
						61.8	173.400	0.04	0.20	18.9	0.20	18.9
				HAD4016A (136-162 MHz)	60	59.1	136.000	0.05	0.20	23.5	0.20	23.5
						60.6	144.000	0.07	0.20	35.6	0.20	35.6
						60.8	150.800	0.04	0.20	19.8	0.20	19.8
						61.3	156.200	0.03	0.20	14.3	0.20	14.3
						61.3	162.000	0.04	0.20	22.4	0.20	22.4
				HAD4017A (146-174 MHz)	60	60.7	146.000	0.04	0.20	17.8	0.20	17.8
						60.8	150.800	0.05	0.20	26.8	0.20	26.8
						61.5	158.300	0.02	0.20	8.8	0.20	8.8
						61.4	165.900	0.05	0.20	25.3	0.20	25.3
						61.8	173.400	0.03	0.20	12.9	0.20	12.9
				RAD4010ARB (136-174 MHz)	60	59.1	136.000	0.02	0.20	12.5	0.20	12.5
						60.1	140.000	0.01	0.20	5.6	0.20	5.6
						60.6	144.000	0.01	0.20	6.9	0.20	6.9
						60.8	150.800	0.02	0.20	9.0	0.20	9.0
						61.5	158.300	0.01	0.20	7.4	0.20	7.4
						61.4	165.900	0.02	0.20	8.0	0.20	8.0
						61.8	173.400	0.02	0.20	9.8	0.20	9.8
				HAD4022A (132-174 MHz)	60	59.1	136.000	0.02	0.20	9.4	0.20	9.4
						60.1	140.000	0.02	0.20	8.9	0.20	8.9
						60.6	144.000	0.03	0.20	13.4	0.20	13.4
						60.8	150.800	0.02	0.20	8.7	0.20	8.7
						61.5	158.300	0.01	0.20	7.1	0.20	7.1
						61.4	165.900	0.04	0.20	21.9	0.20	21.9
						61.8	173.400	0.02	0.20	11.5	0.20	11.5

Table 9 (continued)

Passenger MPE assessment for roof mounted antennas

Trunk/ Roof	Test Position	E/H Field	Angle (Degree)	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm^2)	FCC Limit	% To FCC Spec Limit	ICNIRP Limit	% To ICNIRP Spec Limit
Roof	PF	H	NA	HAD4021A (136 -174MHz)	60	59.1	136.000	0.02	0.20	11.9	0.20	11.9
						60.1	140.000	0.04	0.20	20.8	0.20	20.8
						60.6	144.000	0.05	0.20	23.4	0.20	23.4
						60.8	150.800	0.05	0.20	24.3	0.20	24.3
						61.5	158.300	0.03	0.20	15.7	0.20	15.7
						61.4	165.900	0.01	0.20	4.6	0.20	4.6
						61.8	173.400	0.01	0.20	6.0	0.20	6.0
				HAD4006A (136-144 MHz)	60	59.1	136.000	0.04	0.20	22.1	0.20	22.1
						60.1	140.000	0.05	0.20	24.8	0.20	24.8
						60.6	144.000	0.08	0.20	38.0	0.20	38.0
				HAD4007A (144-150.8 MHz)	60	60.6	144.000	0.07	0.20	35.3	0.20	35.3
						60.7	148.000	0.08	0.20	39.6	0.20	39.6
						60.8	150.800	0.06	0.20	29.1	0.20	29.1
				HAD4008A (150.8-162 MHz)	60	60.8	150.800	0.07	0.20	34.2	0.20	34.2
						61.3	156.200	0.02	0.20	10.2	0.20	10.2
						61.3	162.000	0.02	0.20	8.7	0.20	8.7
				HAD4009A (162-174 MHz)	60	61.3	162.000	0.02	0.20	8.3	0.20	8.3
						61.5	167.700	0.01	0.20	6.4	0.20	6.4
						61.8	173.400	0.02	0.20	8.5	0.20	8.5
				HAD4016A (136-162 MHz)	60	59.1	136.000	0.04	0.20	18.5	0.20	18.5
						60.6	144.000	0.06	0.20	31.4	0.20	31.4
						60.8	150.800	0.05	0.20	26.2	0.20	26.2
						61.3	156.200	0.02	0.20	11.9	0.20	11.9
						61.3	162.000	0.02	0.20	7.9	0.20	7.9
				HAD4017A (146-174 MHz)	60	60.7	146.000	0.03	0.20	15.8	0.20	15.8
						60.8	150.800	0.05	0.20	26.2	0.20	26.2
						61.5	158.300	0.03	0.20	13.6	0.20	13.6
						61.4	165.900	0.01	0.20	5.7	0.20	5.7
						61.8	173.400	0.02	0.20	8.8	0.20	8.8
				RAD4010ARB (136-174 MHz)	60	59.1	136.000	0.00	0.20	2.2	0.20	2.2
						60.1	140.000	0.01	0.20	2.8	0.20	2.8
						60.6	144.000	0.01	0.20	4.9	0.20	4.9
						60.8	150.800	0.01	0.20	2.9	0.20	2.9
						61.5	158.300	0.01	0.20	2.6	0.20	2.6
						61.4	165.900	0.00	0.20	2.3	0.20	2.3
						61.8	173.400	0.01	0.20	5.2	0.20	5.2
				HAD4022A (132-174 MHz)	60	59.1	136.000	0.01	0.20	5.4	0.20	5.4
						60.1	140.000	0.01	0.20	4.7	0.20	4.7
						60.6	144.000	0.02	0.20	8.1	0.20	8.1
						60.8	150.800	0.01	0.20	5.7	0.20	5.7
						61.5	158.300	0.01	0.20	5.5	0.20	5.5
						61.4	165.900	0.01	0.20	3.9	0.20	3.9
						61.8	173.400	0.01	0.20	5.3	0.20	5.3

16.0 Conclusion

The assessments for this device were performed with an output power range as indicated in section 15.0 Tables 6 - 9. The maximum allowable output power is equal to the upper limit of the final test factory transmit power specification of 60W (136 – 174 MHz). The highest power density results for the mobile device scaled to the maximum allowable power output are indicated in the Table 10 for internal/passenger to the vehicle, and external/bystander to the vehicle.

Table 10: Maximum MPE RF Exposure Summary

Designator	Frequency (MHz)	Passenger (mW/cm ²)	Bystander (mW/cm ²)
Overall	136-174	0.56	0.18
FCC	150.8 – 173.4	0.56	0.18
IC	138-174	0.56	0.18


These MPE results herein demonstrate compliance to the FCC/IEEE/ICNIRP Occupational/Controlled Exposure limit. FCC rules require compliance for Passengers and Bystanders to the FCC General Population/Uncontrolled limits. Although MPE is a convenient method of demonstrating compliance, SAR is recognized as the "basic restriction". For those configurations exceeding the MPE limit noted * in section 15 Tables 6 thru 9, compliance to the FCC SAR General Population/ Uncontrolled limit of 1.6mW/g is demonstrated in Appendix E via SAR computational analysis.

The computational results show that this device, when used with the offered antennas in accordance with the user manual instructions, exhibits the maximum peak 1-g average SAR values as indicated in the Table 11.


Table 11: Highest SAR Results Summary

Designator	Frequency (MHz)	Maximum peak average SAR (W/kg)	
		1g-SAR	10g-SAR
Overall	136-174	0.67	0.40
FCC	150.8 – 173.4	0.67	0.40
IC	138-174	0.67	0.40

Appendix A - Illustration of Antenna Locations and Test Distances



- 1 - Roof (center)
 2 - Trunk (center)
 3 - Trunk (85cm from back of the back seat)



By-Stander Test Locations


- Roof Mount
 ● Trunk Mount

Note: The distance from the centered trunk-mounted antenna to the edge of the vehicle is 42cm and the distance from the edge of the vehicle to the survey probe sensor is 48cm.

Seat scan areas
(Applicable to both front and back seats)

Meter - Probe

 Probe diameter is 5.5cm



Appendix B - Probe Calibration Certificates

Service Test Report

QAF 1126, 03/11

Report ID: 91614



An ESCO Technologies Company

1301 Arrow Point Drive
Cedar Park, Texas 78613
(512) 531-6498



An ESCO Technologies Company

Tracking # S000025288

Equipment Check

Attested by TDO Date: 11-Jun-12
www.ets-lindgren.com

Certificate of Test Conformance

Page 1 of 1

Reference: S 000025288**Customer:** AGILENT/MOTOROLA (FL)

The instrument listed below has been tested and verified to Internal Quality Standards. Test data is Not Applicable. Equipment used during instrument testing is controlled by laboratory compliance with ISO/IEC 17025-2005 and ANSI/NCSL Z540-1-1994 using ETS-Lindgren Quality Management System internal procedures.

Manufacturer ETS-Lindgren**Instrument Type** RF Survey Meter**Model** HI-2200**Serial Number/ID** 00086887**Status In**

In Tolerance

Date Completed

11-Jun-12

Status Out

Compliant with Internal Quality Standards

Remarks

Functional test performed.

I would like to take this opportunity to express our appreciation for using ETS-Lindgren for your EMI test equipment services and I am looking forward to continued business with your organization. Please feel free to contact our offices at (512) 531-6400, if you have any questions regarding this report.

Sincerely,

A handwritten signature in black ink, appearing to read "Terry D. O'Neill".

Terry D. O'Neill

Calibration Manager

Date Attested: 11-Jun-12



1301 Arrow Point Drive
Cedar Park, Texas 78613
(512) 531-6498

Cert I.D.: 91609

Certificate of Calibration Conformance

Page 1 of 3

The instrument identified below has been individually calibrated in compliance with the following standard(s):

IEEE 1309 - 2005, Institute of Electrical and Electronics Engineers, Standard for Calibration of Electromagnetic Field Sensors and Probes, Excluding Antennas from 9 kHz to 40 GHz

Environment: Laboratory MTE is maintained in a temperature controlled environment with ambient conditions from 18 to 28 C, relative humidity less than 90%. The instrument under test has been calibrated in a suitable environment using an EMCO TEM Cell 5101C, GTEM! 5305 and an RF Shielded EMC Chamber which is conducive to maintaining accurate and reliable measurement quality.

Manufacturer:	ETS-Lindgren	Operating Range:	100kHz - 5GHz
Model Number:	E100	Instrument Type:	Isotropic Probe > 1 GHz
Serial Number/ ID:	00126277	Date Code:	
Tracking Number:	S 000025288	Alternate ID:	
Date Completed:	11-Jun-12	Customer:	AGILENT/MOTOROLA (FL)
Test Type:	Standard Field, Field Strength		

Calibration Uncertainty: Std Field Method 10kHz - 18000 MHz, +/-0.7 dB, 26.5GHz - 40GHz, +/- 0.95 dB
k=2, (95% Confidence Level)

Test Remarks: Probe tested with HI-2200 s/n 00086887. Special Calibration - Additional frequency points added per customer request.

Calibration Traceability: All Measuring and Test Equipment (M/TE) identified below are traceable to the SI units through the National Institute for Standards and Technology (NIST) or other recognized National Metrology Institute. Calibration Laboratory and Quality System controls are compliant with ISO/IEC 17025-2005 and ANSI/NCSL Z540-1-1994.

Standards and Equipment Used:

Make / Model / Name / S/N / Recall Date


Agilent/HP	8648C	Signal Generator	3623A03573	01-Feb-13
Agilent	E4419B	Power Meter	MY45104171	29-Sep-12
Agilent/HP	8648C	Signal Generator	3847A04406	01-Feb-13
Agilent	E4419B	Power Meter	MY45103242	01-Feb-13
Rohde & Schwarz	857.8008.02	Power Meter NRVD	100451	28-Mar-13
Hewlett Packard	83620B	Signal Generator	3722A00541	01-Feb-13
Fluke	6060B	RF Signal Generator	5690204	28-Jun-12


Condition of Instrument Upon Receipt:

In Tolerance to Internal Quality Standards

On Release:

In Tolerance to Internal Quality Standards


Calibration Completed By
George Cisneros, Calibration Technician


Attested and Issued on 11-Jun-12
Terry D. O'Neill, Calibration Manager

This document provides traceability of measurements to recognized national standards using controlled processes at the ETS-Lindgren Calibration Laboratory. Uncertainties listed are derived from the methods described by NIST Tech Note 1297. This certificate and report may not be reproduced, except in full, without the written approval of ETS-Lindgren Calibration Laboratory in accordance with ISO/IEC 17025-2005 and ANSI/NCSL Z540-1-1994. QAF 1127 (03/11)

CALIBRATION REPORT

Electric Field Sensor

Model	S/N
E100	00126277
HI-2200	86887

Date: 11 June 2012

☐ New Instrument
☐ Other
☐ Out of Tolerance
☒ Within Tolerance

Frequency Response

Frequency Response		Nominal Field	Cal Factor*	Deviation
	MHz	V/m	(Eapplied/Eindicated)	dB
1	1	20	1.40	-2.93
2	15	20	1.10	-0.80
3	30	20	1.02	-0.21
4	75	20	0.98	0.14
5	100	20	0.99	0.05
6	150	20	1.00	0.00
7	200	20	1.00	0.00
8	250	20	0.98	0.15
9	300	20	0.99	0.05
10	400	20	1.00	0.00
11	500	20	1.00	-0.04
12	600	20	1.01	-0.06
13	700	20	1.01	-0.10
14	800	20	1.02	-0.15
15	900	20	1.02	-0.15
16	1000	20	0.98	0.21
17	2000	20	0.95	0.48
18	2450	20	1.01	-0.09
19	3000	20	1.02	-0.17
20	3500	20	0.97	0.30
21	4000	20	1.01	-0.11
22	5000	20	1.37	-2.76
23	5500	20	1.41	-2.95
24	6000	20	1.43	-3.10

* Corrected electric field values (V/m) can be obtained by multiplying the Cal Factor with the indicated E field readings.

Linearity

maximum linearity deviation is 0.1 dB
 (measurements taken from 0.3 V/m to 800 V/m at 27.12 MHz)

Test Conditions

Calibration performed at ambient room temperature: 23 ±3°C



PROBE ROTATIONAL RESPONSE

Model E100
 S/N 00126277
 Date Date of Calibration 11 June 2012
 Time 12:55:30 PM
 Isotropy * $+ 0.304 \text{ dB} / -0.304 \text{ dB}$




Figure 1: Probe Isotropic Response Chart.

Isotropic response is measured in a 20 V/m field at 400 MHz

*Isotropy is the maximum deviation from the geometric mean as defined by IEEE 1309-2005.



ETS-LINDGREN
An ESCO Technologies Company
1301 Arrow Point Drive
Cedar Park, Texas 78613
(512) 531-6498

ETS-LINDGREN
An ESCO Technologies Company
Track# S000025288 Ltd Cal ☐
By GC Date 11-Jun-12
Next Cal Due
www.ets-lindgren.com

Cert I.D.: 91613

Certificate of Calibration Conformance

Page 1 of 2

The instrument identified below has been individually calibrated in compliance with the following standard(s):

IEEE 1309 - 2005, Institute of Electrical and Electronics Engineers, Standard for Calibration of Electromagnetic Field Sensors and Probes, Excluding Antennas from 9 kHz to 40 GHz

Environment: Laboratory MTE is maintained in a temperature controlled environment with ambient conditions from 18 to 28 C, relative humidity less than 90%. The instrument under test has been calibrated in a suitable environment using an EMCO TEM Cell 5101C, GTEM! 5305 and an RF Shielded EMC Chamber which is conducive to maintaining accurate and reliable measurement quality.

Manufacturer:	ETS-Lindgren	Operating Range:	5-300MHz / 30mA/m-10A/m
Model Number:	H200	Instrument Type:	Isotropic Magnetic Field Probe (2)
Serial Number/ ID:	00084225	Date Code:	
Tracking Number:	S 000025288	Alternate ID:	
Date Completed:	11-Jun-12	Customer:	AGILENT/MOTOROLA (FL)
Test Type:	Standard Field, Field Strength		

Calibration Uncertainty: Direct Field Method 1.15dB
k=2, (95% Confidence Level)

Test Remarks: Probe tested with HI-2200 s/n 00086887.

Calibration Traceability: All Measuring and Test Equipment (MTE) identified below are traceable to the SI units through the National Institute for Standards and Technology (NIST) or other recognized National Metrology Institute. Calibration Laboratory and Quality System controls are compliant with ISO/IEC 17025-2005 and ANSI/NCCL Z540-1-1994.

Standards and Equipment Used:

Make / Model / Name / S/N / Recall Date

HP	8648C	Sig Gen	3836A04299	01-Feb-13
Hewlett Packard	E4419B	Power Meter	US39250717	01-Feb-13

Condition of Instrument Upon Receipt:

In Tolerance to Internal Quality Standards

On Release:

In Tolerance to Internal Quality Standards


Calibration Completed By
George Cisneros, Calibration Technician


Attested and Issued on 11-Jun-12
Terry D. O'Neill, Calibration Manager

This document provides traceability of measurements to recognized national standards using controlled processes at the ETS-Lindgren Calibration Laboratory. Uncertainties listed are derived from the methods described by NIST Tech Note 1297. This certificate and report may not be reproduced, except in full, without the written approval of ETS-Lindgren Calibration Laboratory in accordance with ISO/IEC 17025-2005 and ANSI/NCCL Z540-1-1994. QAF 1127 (03/11)

CALIBRATION REPORT

Magnetic Field Sensor

Model	S/N
H200	00084225
HI-2200	86887

Date: 11 Jun 2012

As received, the instrument was found: X Within Tolerance
 Out of Tolerance
 (New Instrument)

Frequency Response

Frequency		Nominal		
Response		Field	Cal Factor*	Deviation
	MHz	A/m	(Applied/Indicated)	dB
1	10	0.08	1.04	-0.32
2	15	0.08	1.00	0.00
3	30	0.08	1.00	0.00
4	50	0.08	0.98	0.18
5	75	0.08	0.96	0.34
6	100	0.08	0.93	0.61
7	150	0.08	0.86	1.28
8	175	0.08	0.84	1.53
9	200	0.08	0.82	1.97
10	250	0.08	0.72	3.28
11	300	0.08	0.60	4.56

* Corrected magnetic field values (A/m) can be obtained by multiplying the Cal Factor with the indicated H field readings.

Linearity

Maximum linearity deviation is 0.03 dB

(measurements taken from 30 mA/m to 9 A/m at 27.12 MHz)

Test Conditions

Calibration performed at ambient room temperature: 23 ±3°C

Appendix C - Photos of Assessed Antennas

(Refer to Exhibit 7B)

Appendix D – MPE Measurement Results

MPE measurement data for Bystander - Trunk mounted antennas

D.U.T. Info.							Probe Info.		Test Position	MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Location	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor		Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Trunk	RAD4010ARB (136-174 MHz)	5.15	136.000	60	59.1	CW	E	0.99	BS	0.03	0.05	0.07	0.09	0.14	0.25	0.37	0.42	0.34	0.32	0.50	0.207	0.103	0.10
Trunk	RAD4010ARB (136-174 MHz)	5.15	140.000	60	60.1	CW	E	1.00	BS	0.03	0.05	0.07	0.09	0.15	0.26	0.37	0.41	0.35	0.34	0.50	0.211	0.105	0.11
Trunk	RAD4010ARB (136-174 MHz)	5.15	144.000	60	60.6	CW	E	1.00	BS	0.03	0.06	0.08	0.11	0.16	0.28	0.4	0.43	0.37	0.38	0.50	0.230	0.115	0.12
Trunk	RAD4010ARB (136-174 MHz)	5.15	150.800	60	60.8	CW	E	1.00	BS	0.03	0.05	0.07	0.09	0.12	0.23	0.35	0.35	0.34	0.34	0.50	0.198	0.099	0.10
Trunk	RAD4010ARB (136-174 MHz)	5.15	158.300	60	61.5	CW	E	1.00	BS	0.04	0.08	0.1	0.1	0.14	0.26	0.39	0.42	0.42	0.41	0.50	0.237	0.118	0.12
Trunk	RAD4010ARB (136-174 MHz)	5.15	165.900	60	61.4	CW	E	1.00	BS	0.04	0.06	0.06	0.05	0.07	0.2	0.32	0.33	0.32	0.34	0.50	0.178	0.089	0.09
Trunk	RAD4010ARB (136-174 MHz)	5.15	173.400	60	61.8	CW	E	1.00	BS	0.04	0.05	0.07	0.08	0.2	0.42	0.58	0.53	0.55	0.57	0.50	0.308	0.154	0.15
45 degree																							
Trunk	RAD4010ARB (136-174 MHz)	5.15	173.400	60	61.8	CW	E	1.00	BS	0.09	0.16	0.16	0.15	0.21	0.28	0.32	0.31	0.3	0.3	0.50	0.227	0.113	0.11
90 degree																							
Trunk	RAD4010ARB (136-174 MHz)	5.15	173.400	60	61.8	CW	E	1.00	BS	0.07	0.11	0.1	0.15	0.27	0.33	0.33	0.31	0.31	0.29	0.50	0.225	0.113	0.11
Trunk	HAD4022A (132-174 MHz)	5.15	136.000	60	59.1	CW	E	0.99	BS	0.03	0.05	0.08	0.12	0.19	0.29	0.37	0.38	0.36	0.37	0.50	0.223	0.110	0.11
Trunk	HAD4022A (132-174 MHz)	5.15	140.000	60	60.1	CW	E	1.00	BS	0.03	0.06	0.08	0.12	0.19	0.3	0.39	0.39	0.38	0.37	0.50	0.231	0.116	0.12
Trunk	HAD4022A (132-174 MHz)	5.15	144.000	60	60.6	CW	E	1.00	BS	0.05	0.09	0.14	0.18	0.24	0.31	0.41	0.41	0.41	0.41	0.50	0.265	0.133	0.13
Trunk	HAD4022A (132-174 MHz)	5.15	150.800	60	60.8	CW	E	1.00	BS	0.04	0.08	0.12	0.12	0.18	0.27	0.36	0.39	0.35	0.34	0.50	0.224	0.112	0.11
Trunk	HAD4022A (132-174 MHz)	5.15	158.300	60	61.5	CW	E	1.00	BS	0.05	0.09	0.12	0.18	0.23	0.34	0.41	0.37	0.37	0.36	0.50	0.250	0.125	0.13
Trunk	HAD4022A (132-174 MHz)	5.15	165.900	60	61.4	CW	E	1.00	BS	0.05	0.07	0.09	0.14	0.25	0.42	0.48	0.4	0.41	0.36	0.50	0.267	0.133	0.13
Trunk	HAD4022A (132-174 MHz)	5.15	173.400	60	61.8	CW	E	1.00	BS	0.04	0.07	0.1	0.18	0.29	0.43	0.48	0.46	0.43	0.38	0.50	0.285	0.143	0.14
45 degree																							
Trunk	HAD4022A (132-174 MHz)	5.15	173.400	60	61.8	CW	E	1.00	BS	0.16	0.31	0.3	0.29	0.4	0.41	0.37	0.33	0.29	0.26	0.50	0.311	0.156	0.16
90 degree																							
Trunk	HAD4022A (132-174 MHz)	5.15	173.400	60	61.8	CW	E	1.00	BS	0.11	0.19	0.17	0.23	0.36	0.41	0.37	0.32	0.29	0.25	0.50	0.269	0.134	0.13

MPE calculations are defined in section 13.0.

MPE measurement data for Bystander - Trunk mounted antennas

D.U.T. Info.							Probe Info.		Test Position	MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Location	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor		Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Trunk	RAD4010ARB (136-174 MHz)	5.15	136.000	60	59.1	CW	H	0.88	BS	0.04	0.03	0.03	0.04	0.05	0.06	0.08	0.11	0.14	0.15	0.50	0.072	0.077	0.08
Trunk	RAD4010ARB (136-174 MHz)	5.15	140.000	60	60.1	CW	H	0.87	BS	0.04	0.03	0.03	0.04	0.05	0.07	0.09	0.12	0.14	0.15	0.50	0.075	0.080	0.08
Trunk	RAD4010ARB (136-174 MHz)	5.15	144.000	60	60.6	CW	H	0.87	BS	0.04	0.03	0.03	0.05	0.06	0.08	0.11	0.14	0.15	0.16	0.50	0.085	0.102	0.10
Trunk	RAD4010ARB (136-174 MHz)	5.15	150.800	60	60.8	CW	H	0.86	BS	0.03	0.03	0.04	0.05	0.06	0.07	0.1	0.12	0.14	0.15	0.50	0.079	0.086	0.09
Trunk	RAD4010ARB (136-174 MHz)	5.15	158.300	60	61.5	CW	H	0.85	BS	0.03	0.03	0.05	0.06	0.08	0.09	0.12	0.15	0.16	0.16	0.50	0.093	0.117	0.12
Trunk	RAD4010ARB (136-174 MHz)	5.15	165.900	60	61.4	CW	H	0.85	BS	0.03	0.03	0.04	0.05	0.05	0.07	0.1	0.13	0.14	0.15	0.50	0.080	0.087	0.09
Trunk	RAD4010ARB (136-174 MHz)	5.15	173.400	60	61.8	CW	H	0.84	BS	0.04	0.04	0.06	0.07	0.09	0.12	0.16	0.18	0.19	0.18	0.50	0.112	0.167	0.17
45 degree																							
Trunk	RAD4010ARB (136-174 MHz)	5.15	173.400	60	61.8	CW	H	0.84	BS	0.05	0.07	0.08	0.09	0.09	0.1	0.11	0.13	0.14	0.14	0.50	0.100	0.132	0.13
90 degree																							
Trunk	RAD4010ARB (136-174 MHz)	5.15	173.400	60	61.8	CW	H	0.84	BS	0.05	0.07	0.08	0.1	0.1	0.11	0.12	0.12	0.12	0.13	0.50	0.100	0.132	0.13
Trunk	HAD4022A (132-174 MHz)	5.15	136.000	60	59.1	CW	H	0.88	BS	0.03	0.03	0.03	0.05	0.07	0.1	0.12	0.14	0.15	0.14	0.50	0.085	0.106	0.11
Trunk	HAD4022A (132-174 MHz)	5.15	140.000	60	60.1	CW	H	0.87	BS	0.03	0.03	0.04	0.05	0.07	0.1	0.12	0.14	0.14	0.14	0.50	0.086	0.105	0.10
Trunk	HAD4022A (132-174 MHz)	5.15	144.000	60	60.6	CW	H	0.87	BS	0.04	0.03	0.05	0.07	0.09	0.11	0.13	0.14	0.14	0.13	0.50	0.094	0.127	0.13
Trunk	HAD4022A (132-174 MHz)	5.15	150.800	60	60.8	CW	H	0.86	BS	0.03	0.03	0.05	0.07	0.09	0.1	0.12	0.13	0.14	0.13	0.50	0.089	0.110	0.11
Trunk	HAD4022A (132-174 MHz)	5.15	158.300	60	61.5	CW	H	0.85	BS	0.04	0.04	0.06	0.08	0.1	0.12	0.14	0.14	0.14	0.12	0.50	0.098	0.130	0.13
Trunk	HAD4022A (132-174 MHz)	5.15	165.900	60	61.4	CW	H	0.85	BS	0.04	0.04	0.06	0.09	0.11	0.13	0.14	0.15	0.14	0.12	0.50	0.101	0.138	0.14
Trunk	HAD4022A (132-174 MHz)	5.15	173.400	60	61.8	CW	H	0.84	BS	0.04	0.04	0.07	0.09	0.12	0.14	0.15	0.15	0.15	0.13	0.50	0.108	0.155	0.15
45 degree																							
Trunk	HAD4022A (132-174 MHz)	5.15	173.400	60	61.8	CW	H	0.84	BS	0.07	0.09	0.11	0.12	0.13	0.13	0.14	0.13	0.13	0.11	0.50	0.116	0.179	0.18
90 degree																							
Trunk	HAD4022A (132-174 MHz)	5.15	173.400	60	61.8	CW	H	0.84	BS	0.06	0.09	0.11	0.12	0.12	0.13	0.13	0.12	0.12	0.11	0.50	0.112	0.166	0.17

MPE calculations are defined in section 13.0.

MPE measurement data for Passenger - Trunk mounted antennas

D.U.T. Info.							Probe Info.		Test Position	MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Location	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor		Passenger						
										Head	Chest	Lower Trunk				
Trunk	RAD4010ARB (136-174 MHz)	5.15	136.000	60	59.1	CW	E	0.99	PB	0.078	0.068	0.056	0.50	0.067	0.033	0.03
Trunk	RAD4010ARB (136-174 MHz)	5.15	140.000	60	60.1	CW	E	1.00	PB	0.004	0.006	0.005	0.50	0.005	0.003	0.00
Trunk	RAD4010ARB (136-174 MHz)	5.15	144.000	60	60.6	CW	E	1.00	PB	0.021	0.02	0.013	0.50	0.018	0.009	0.01
Trunk	RAD4010ARB (136-174 MHz)	5.15	150.800	60	60.8	CW	E	1.00	PB	0.039	0.045	0.025	0.50	0.036	0.018	0.02
Trunk	RAD4010ARB (136-174 MHz)	5.15	158.300	60	61.5	CW	E	1.00	PB	0.095	0.078	0.071	0.50	0.081	0.041	0.04
Trunk	RAD4010ARB (136-174 MHz)	5.15	165.900	60	61.4	CW	E	1.00	PB	0.167	0.29	0.315	0.50	0.257	0.129	0.13
Trunk	RAD4010ARB (136-174 MHz)	5.15	173.400	60	61.8	CW	E	1.00	PB	0.436	0.395	0.523	0.50	0.451	0.226	0.23
Trunk	HAD4022A (132-174 MHz)	5.15	136.000	60	59.1	CW	E	0.99	PB	0.05	0.043	0.026	0.50	0.040	0.020	0.02
Trunk	HAD4022A (132-174 MHz)	5.15	140.000	60	60.1	CW	E	1.00	PB	0.198	0.185	0.128	0.50	0.170	0.085	0.09
Trunk	HAD4022A (132-174 MHz)	5.15	144.000	60	60.6	CW	E	1.00	PB	0.237	0.3	0.257	0.50	0.265	0.132	0.13
Trunk	HAD4022A (132-174 MHz)	5.15	150.800	60	60.8	CW	E	1.00	PB	0.355	0.335	0.26	0.50	0.317	0.158	0.16
Trunk	HAD4022A (132-174 MHz)	5.15	158.300	60	61.5	CW	E	1.00	PB	0.667	0.83	0.573	0.50	0.690	0.345	0.35
Trunk	HAD4022A (132-174 MHz)	5.15	165.900	60	61.4	CW	E	1.00	PB	0.756	1.269	1.355	0.50	1.127	0.563	0.56
Trunk	HAD4022A (132-174 MHz)	5.15	173.400	60	61.8	CW	E	1.00	PB	0.668	0.413	0.495	0.50	0.525	0.263	0.26

MPE calculations are defined in section 13.0.

MPE measurement data for Passenger - Trunk mounted antennas

D.U.T. Info.							Probe Info.		Test Position	MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Location	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor		Passenger						
										Head	Chest	Lower Trunk				
Trunk	RAD4010ARB (136-174 MHz)	5.15	136.000	60	59.1	CW	E	0.99	PF	0.016	0.018	0.021	0.50	0.018	0.009	0.01
Trunk	RAD4010ARB (136-174 MHz)	5.15	140.000	60	60.1	CW	E	1.00	PF	0.008	0.02	0.021	0.50	0.016	0.008	0.01
Trunk	RAD4010ARB (136-174 MHz)	5.15	144.000	60	60.6	CW	E	1.00	PF	0.008	0.016	0.013	0.50	0.012	0.006	0.01
Trunk	RAD4010ARB (136-174 MHz)	5.15	150.800	60	60.8	CW	E	1.00	PF	0.006	0.018	0.021	0.50	0.015	0.008	0.01
Trunk	RAD4010ARB (136-174 MHz)	5.15	158.300	60	61.5	CW	E	1.00	PF	0.038	0.029	0.018	0.50	0.028	0.014	0.01
Trunk	RAD4010ARB (136-174 MHz)	5.15	165.900	60	61.4	CW	E	1.00	PF	0.029	0.048	0.041	0.50	0.039	0.020	0.02
Trunk	RAD4010ARB (136-174 MHz)	5.15	173.400	60	61.8	CW	E	1.00	PF	0.101	0.172	0.16	0.50	0.144	0.072	0.07
Trunk	HAD4022A (132-174 MHz)	5.15	136.000	60	59.1	CW	E	0.99	PF	0.009	0.017	0.013	0.50	0.013	0.006	0.01
Trunk	HAD4022A (132-174 MHz)	5.15	140.000	60	60.1	CW	E	1.00	PF	0.025	0.028	0.018	0.50	0.024	0.012	0.01
Trunk	HAD4022A (132-174 MHz)	5.15	144.000	60	60.6	CW	E	1.00	PF	0.07	0.047	0.025	0.50	0.047	0.024	0.02
Trunk	HAD4022A (132-174 MHz)	5.15	150.800	60	60.8	CW	E	1.00	PF	0.095	0.07	0.032	0.50	0.066	0.033	0.03
Trunk	HAD4022A (132-174 MHz)	5.15	158.300	60	61.5	CW	E	1.00	PF	0.149	0.094	0.067	0.50	0.103	0.052	0.05
Trunk	HAD4022A (132-174 MHz)	5.15	165.900	60	61.4	CW	E	1.00	PF	0.184	0.189	0.205	0.50	0.193	0.096	0.10
Trunk	HAD4022A (132-174 MHz)	5.15	173.400	60	61.8	CW	E	1.00	PF	0.121	0.173	0.166	0.50	0.153	0.077	0.08

MPE calculations are defined in section 13.0.

MPE measurement data for Passenger - Trunk mounted antennas

D.U.T. Info.							Probe Info.		Test Position	MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Location	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor		Passenger						
										Head	Chest	Lower Trunk				
Trunk	RAD4010ARB (136-174 MHz)	5.15	136.000	60	59.1	CW	H	0.88	PB	0.055	0.038	0.03	0.50	0.041	0.025	0.02
Trunk	RAD4010ARB (136-174 MHz)	5.15	140.000	60	60.1	CW	H	0.87	PB	0.015	0.013	0.016	0.50	0.015	0.003	0.00
Trunk	RAD4010ARB (136-174 MHz)	5.15	144.000	60	60.6	CW	H	0.87	PB	0.014	0.015	0.016	0.50	0.015	0.003	0.00
Trunk	RAD4010ARB (136-174 MHz)	5.15	150.800	60	60.8	CW	H	0.86	PB	0.031	0.023	0.019	0.50	0.024	0.008	0.01
Trunk	RAD4010ARB (136-174 MHz)	5.15	158.300	60	61.5	CW	H	0.85	PB	0.055	0.041	0.034	0.50	0.043	0.026	0.03
Trunk	RAD4010ARB (136-174 MHz)	5.15	165.900	60	61.4	CW	H	0.85	PB	0.099	0.074	0.05	0.50	0.074	0.075	0.08
Trunk	RAD4010ARB (136-174 MHz)	5.15	173.400	60	61.8	CW	H	0.84	PB	0.116	0.096	0.059	0.50	0.090	0.109	0.11
Trunk	HAD4022A (132-174 MHz)	5.15	136.000	60	59.1	CW	H	0.88	PB	0.034	0.033	0.024	0.50	0.030	0.013	0.01
Trunk	HAD4022A (132-174 MHz)	5.15	140.000	60	60.1	CW	H	0.87	PB	0.06	0.051	0.036	0.50	0.049	0.034	0.03
Trunk	HAD4022A (132-174 MHz)	5.15	144.000	60	60.6	CW	H	0.87	PB	0.081	0.062	0.048	0.50	0.064	0.058	0.06
Trunk	HAD4022A (132-174 MHz)	5.15	150.800	60	60.8	CW	H	0.86	PB	0.08	0.068	0.067	0.50	0.072	0.072	0.07
Trunk	HAD4022A (132-174 MHz)	5.15	158.300	60	61.5	CW	H	0.85	PB	0.134	0.102	0.096	0.50	0.111	0.167	0.17
Trunk	HAD4022A (132-174 MHz)	5.15	165.900	60	61.4	CW	H	0.85	PB	0.206	0.161	0.103	0.50	0.157	0.334	0.33
Trunk	HAD4022A (132-174 MHz)	5.15	173.400	60	61.8	CW	H	0.84	PB	0.128	0.116	0.078	0.50	0.107	0.153	0.15

MPE calculations are defined in section 13.0.

MPE measurement data for Passenger - Trunk mounted antennas

D.U.T. Info.							Probe Info.		Test Position	MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Location	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor		Passenger						
										Head	Chest	Lower Trunk				
Trunk	RAD4010ARB (136-174 MHz)	5.15	136.000	60	59.1	CW	H	0.88	PF	0.036	0.034	0.021	0.50	0.030	0.013	0.01
Trunk	RAD4010ARB (136-174 MHz)	5.15	140.000	60	60.1	CW	H	0.87	PF	0.023	0.026	0.019	0.50	0.023	0.007	0.01
Trunk	RAD4010ARB (136-174 MHz)	5.15	144.000	60	60.6	CW	H	0.87	PF	0.02	0.022	0.018	0.50	0.020	0.006	0.01
Trunk	RAD4010ARB (136-174 MHz)	5.15	150.800	60	60.8	CW	H	0.86	PF	0.025	0.026	0.017	0.50	0.023	0.007	0.01
Trunk	RAD4010ARB (136-174 MHz)	5.15	158.300	60	61.5	CW	H	0.85	PF	0.023	0.025	0.024	0.50	0.024	0.008	0.01
Trunk	RAD4010ARB (136-174 MHz)	5.15	165.900	60	61.4	CW	H	0.85	PF	0.025	0.022	0.024	0.50	0.024	0.008	0.01
Trunk	RAD4010ARB (136-174 MHz)	5.15	173.400	60	61.8	CW	H	0.84	PF	0.053	0.049	0.049	0.50	0.050	0.034	0.03
Trunk	HAD4022A (132-174 MHz)	5.15	136.000	60	59.1	CW	H	0.88	PF	0.018	0.019	0.018	0.50	0.018	0.005	0.00
Trunk	HAD4022A (132-174 MHz)	5.15	140.000	60	60.1	CW	H	0.87	PF	0.028	0.029	0.028	0.50	0.028	0.011	0.01
Trunk	HAD4022A (132-174 MHz)	5.15	144.000	60	60.6	CW	H	0.87	PF	0.042	0.042	0.038	0.50	0.041	0.024	0.02
Trunk	HAD4022A (132-174 MHz)	5.15	150.800	60	60.8	CW	H	0.86	PF	0.049	0.047	0.042	0.50	0.046	0.029	0.03
Trunk	HAD4022A (132-174 MHz)	5.15	158.300	60	61.5	CW	H	0.85	PF	0.04	0.042	0.047	0.50	0.043	0.025	0.03
Trunk	HAD4022A (132-174 MHz)	5.15	165.900	60	61.4	CW	H	0.85	PF	0.049	0.054	0.057	0.50	0.053	0.039	0.04
Trunk	HAD4022A (132-174 MHz)	5.15	173.400	60	61.8	CW	H	0.84	PF	0.05	0.05	0.057	0.50	0.052	0.036	0.04

MPE calculations are defined in section 13.0.

MPE measurement data for Bystander - Roof mounted antennas

D.U.T. Info.							Probe Info.		Test Position	MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Location	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor		Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAD4021A (136-174MHz)	2.15	136.000	60	59.1	CW	E	0.99	BS	0.04	0.08	0.09	0.07	0.07	0.09	0.13	0.15	0.16	0.15	0.50	0.102	0.051	0.05
Roof	HAD4021A (136-174MHz)	2.15	140.000	60	60.1	CW	E	1.00	BS	0.05	0.1	0.11	0.09	0.08	0.1	0.15	0.18	0.19	0.19	0.50	0.122	0.061	0.06
Roof	HAD4021A (136-174MHz)	2.15	144.000	60	60.6	CW	E	1.00	BS	0.05	0.11	0.12	0.09	0.06	0.08	0.14	0.18	0.19	0.18	0.50	0.121	0.060	0.06
Roof	HAD4021A (136-174MHz)	2.15	150.800	60	60.8	CW	E	1.00	BS	0.02	0.04	0.03	0.02	0.05	0.12	0.18	0.21	0.22	0.22	0.50	0.111	0.056	0.06
Roof	HAD4021A (136-174MHz)	2.15	158.300	60	61.5	CW	E	1.00	BS	0.03	0.04	0.03	0.04	0.09	0.16	0.22	0.23	0.22	0.21	0.50	0.125	0.063	0.06
Roof	HAD4021A (136-174MHz)	2.15	165.900	60	61.4	CW	E	1.00	BS	0.02	0.03	0.02	0.04	0.1	0.15	0.18	0.2	0.19	0.19	0.50	0.111	0.055	0.06
Roof	HAD4021A (136-174MHz)	2.15	173.400	60	61.8	CW	E	1.00	BS	0.01	0.02	0.02	0.06	0.13	0.16	0.18	0.19	0.19	0.2	0.50	0.116	0.058	0.06
Roof	HAD4006A (136-144 MHz)	2.15	136.000	60	59.1	CW	E	0.99	BS	0.06	0.11	0.13	0.11	0.1	0.13	0.18	0.24	0.24	0.29	0.50	0.158	0.078	0.08
Roof	HAD4006A (136-144 MHz)	2.15	140.000	60	60.1	CW	E	1.00	BS	0.05	0.12	0.13	0.11	0.09	0.13	0.18	0.23	0.24	0.23	0.50	0.151	0.075	0.08
Roof	HAD4006A (136-144 MHz)	2.15	144.000	60	60.6	CW	E	1.00	BS	0.05	0.11	0.12	0.07	0.06	0.11	0.18	0.22	0.24	0.22	0.50	0.139	0.069	0.07
Roof	HAD4007A (144-150.8 MHz)	2.15	144.000	60	60.6	CW	E	1.00	BS	0.05	0.11	0.12	0.07	0.06	0.1	0.17	0.22	0.22	0.21	0.50	0.133	0.066	0.07
Roof	HAD4007A (144-150.8 MHz)	2.15	148.000	60	60.7	CW	E	1.00	BS	0.04	0.08	0.07	0.04	0.04	0.12	0.18	0.22	0.24	0.23	0.50	0.126	0.063	0.06
Roof	HAD4007A (144-150.8 MHz)	2.15	150.800	60	60.8	CW	E	1.00	BS	0.03	0.07	0.05	0.03	0.06	0.13	0.18	0.22	0.24	0.19	0.50	0.120	0.060	0.06
Roof	HAD4008A (150.8-162 MHz)	2.15	150.800	60	60.8	CW	E	1.00	BS	0.04	0.07	0.05	0.03	0.06	0.13	0.19	0.24	0.21	0.21	0.50	0.123	0.061	0.06
Roof	HAD4008A (150.8-162 MHz)	2.15	156.200	60	61.3	CW	E	1.00	BS	0.04	0.07	0.05	0.03	0.11	0.18	0.27	0.27	0.25	0.23	0.50	0.152	0.076	0.08
Roof	HAD4008A (150.8-162 MHz)	2.15	162.000	60	61.3	CW	E	1.00	BS	0.04	0.06	0.04	0.05	0.14	0.22	0.27	0.28	0.27	0.24	0.50	0.161	0.080	0.08

MPE calculations are defined in section 13.0.

MPE measurement data for Bystander - Roof mounted antennas

D.U.T. Info.							Probe Info.		Test Position	MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Location	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor		Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAD4009A (162-174 MHz)	2.15	162.000	60	61.3	CW	E	1.00	BS	0.03	0.05	0.04	0.04	0.12	0.19	0.24	0.25	0.23	0.21	0.50	0.141	0.070	0.07
Roof	HAD4009A (162-174 MHz)	2.15	167.700	60	61.5	CW	E	1.00	BS	0.02	0.03	0.02	0.05	0.15	0.23	0.25	0.27	0.28	0.27	0.50	0.157	0.078	0.08
Roof	HAD4009A (162-174 MHz)	2.15	173.400	60	61.8	CW	E	1.00	BS	0.02	0.02	0.03	0.09	0.17	0.21	0.24	0.26	0.27	0.3	0.50	0.160	0.080	0.08
Roof	HAD4016A (136-162 MHz)	2.15	136.000	60	59.1	CW	E	0.99	BS	0.05	0.09	0.12	0.1	0.07	0.1	0.16	0.21	0.21	0.19	0.50	0.130	0.064	0.07
Roof	HAD4016A (136-162 MHz)	2.15	144.000	60	60.6	CW	E	1.00	BS	0.05	0.11	0.12	0.07	0.05	0.09	0.16	0.21	0.21	0.2	0.50	0.127	0.064	0.06
Roof	HAD4016A (136-162 MHz)	2.15	150.800	60	60.8	CW	E	1.00	BS	0.03	0.05	0.05	0.02	0.05	0.12	0.18	0.21	0.21	0.2	0.50	0.113	0.056	0.06
Roof	HAD4016A (136-162 MHz)	2.15	156.200	60	61.3	CW	E	1.00	BS	0.05	0.07	0.05	0.04	0.1	0.19	0.28	0.32	0.28	0.24	0.50	0.162	0.081	0.08
Roof	HAD4016A (136-162 MHz)	2.15	162.000	60	61.3	CW	E	1.00	BS	0.03	0.04	0.03	0.04	0.11	0.18	0.22	0.22	0.19	0.18	0.50	0.124	0.062	0.06
Roof	HAD4017A (146-174 MHz)	2.15	146.000	60	60.7	CW	E	1.00	BS	0.02	0.05	0.05	0.02	0.03	0.06	0.1	0.12	0.13	0.13	0.50	0.070	0.035	0.04
Roof	HAD4017A (146-174 MHz)	2.15	150.800	60	60.8	CW	E	1.00	BS	0.04	0.05	0.04	0.02	0.06	0.13	0.19	0.22	0.23	0.2	0.50	0.119	0.060	0.06
Roof	HAD4017A (146-174 MHz)	2.15	158.300	60	61.5	CW	E	1.00	BS	0.04	0.06	0.04	0.05	0.13	0.21	0.26	0.27	0.25	0.23	0.50	0.153	0.077	0.08
Roof	HAD4017A (146-174 MHz)	2.15	165.900	60	61.4	CW	E	1.00	BS	0.04	0.05	0.04	0.05	0.12	0.19	0.23	0.26	0.23	0.23	0.50	0.143	0.072	0.07
Roof	HAD4017A (146-174 MHz)	2.15	173.400	60	61.8	CW	E	1.00	BS	0.02	0.02	0.03	0.08	0.16	0.2	0.22	0.24	0.25	0.26	0.50	0.147	0.073	0.07

MPE calculations are defined in section 13.0.

MPE measurement data for Bystander - Roof mounted antennas

D.U.T. Info.							Probe Info.		Test Position	MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Location	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor		Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	RAD4010ARB (136-174 MHz)	5.15	136.000	60	59.1	CW	E	0.99	BS	0.02	0.03	0.04	0.03	0.03	0.04	0.07	0.11	0.15	0.19	0.50	0.069	0.034	0.03
Roof	RAD4010ARB (136-174 MHz)	5.15	140.000	60	60.1	CW	E	1.00	BS	0.01	0.04	0.04	0.03	0.02	0.04	0.06	0.1	0.15	0.19	0.50	0.069	0.034	0.03
Roof	RAD4010ARB (136-174 MHz)	5.15	144.000	60	60.6	CW	E	1.00	BS	0.02	0.04	0.05	0.04	0.03	0.03	0.07	0.12	0.18	0.22	0.50	0.079	0.040	0.04
Roof	RAD4010ARB (136-174 MHz)	5.15	150.800	60	60.8	CW	E	1.00	BS	0.02	0.04	0.04	0.02	0.01	0.03	0.06	0.11	0.16	0.18	0.50	0.067	0.034	0.03
Roof	RAD4010ARB (136-174 MHz)	5.15	158.300	60	61.5	CW	E	1.00	BS	0.02	0.03	0.02	0.01	0.03	0.07	0.12	0.17	0.2	0.23	0.50	0.089	0.045	0.04
Roof	RAD4010ARB (136-174 MHz)	5.15	165.900	60	61.4	CW	E	1.00	BS	0.01	0.02	0.01	0.01	0.03	0.07	0.1	0.13	0.15	0.17	0.50	0.071	0.035	0.04
Roof	RAD4010ARB (136-174 MHz)	5.15	173.400	60	61.8	CW	E	1.00	BS	0.01	0.02	0.01	0.04	0.1	0.15	0.18	0.21	0.24	0.27	0.50	0.123	0.062	0.06
Roof	HAD4022A (132-174 MHz)	5.15	136.000	60	59.1	CW	E	0.99	BS	0.02	0.05	0.07	0.06	0.03	0.04	0.08	0.13	0.18	0.21	0.50	0.085	0.042	0.04
Roof	HAD4022A (132-174 MHz)	5.15	140.000	60	60.1	CW	E	1.00	BS	0.02	0.05	0.05	0.04	0.02	0.04	0.07	0.13	0.18	0.21	0.50	0.081	0.040	0.04
Roof	HAD4022A (132-174 MHz)	5.15	144.000	60	60.6	CW	E	1.00	BS	0.02	0.05	0.05	0.03	0.02	0.04	0.08	0.13	0.18	0.21	0.50	0.080	0.040	0.04
Roof	HAD4022A (132-174 MHz)	5.15	150.800	60	60.8	CW	E	1.00	BS	0.02	0.03	0.02	0.02	0.03	0.06	0.11	0.15	0.2	0.22	0.50	0.084	0.042	0.04
Roof	HAD4022A (132-174 MHz)	5.15	158.300	60	61.5	CW	E	1.00	BS	0.02	0.04	0.03	0.03	0.06	0.13	0.19	0.23	0.25	0.28	0.50	0.126	0.063	0.06
Roof	HAD4022A (132-174 MHz)	5.15	165.900	60	61.4	CW	E	1.00	BS	0.02	0.03	0.02	0.02	0.05	0.1	0.16	0.21	0.24	0.27	0.50	0.112	0.056	0.06
Roof	HAD4022A (132-174 MHz)	5.15	173.400	60	61.8	CW	E	1.00	BS	0.01	0.01	0.01	0.05	0.11	0.16	0.21	0.23	0.26	0.29	0.50	0.134	0.067	0.07

MPE calculations are defined in section 13.0.

MPE measurement data for Bystander - Roof mounted antennas

D.U.T. Info.							Probe Info.		Test Position	MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Location	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor		Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAD4021A (136-174MHz)	2.15	136.000	60	59.1	CW	H	0.88	BS	0.02	0.03	0.04	0.06	0.07	0.07	0.07	0.07	0.08	0.07	0.50	0.059	0.051	0.05
Roof	HAD4021A (136-174MHz)	2.15	140.000	60	60.1	CW	H	0.87	BS	0.03	0.03	0.05	0.06	0.07	0.08	0.08	0.09	0.09	0.08	0.50	0.065	0.059	0.06
Roof	HAD4021A (136-174MHz)	2.15	144.000	60	60.6	CW	H	0.87	BS	0.03	0.04	0.06	0.07	0.07	0.08	0.08	0.08	0.08	0.08	0.50	0.067	0.063	0.06
Roof	HAD4021A (136-174MHz)	2.15	150.800	60	60.8	CW	H	0.86	BS	0.03	0.03	0.04	0.05	0.07	0.07	0.08	0.08	0.09	0.09	0.50	0.062	0.054	0.05
Roof	HAD4021A (136-174MHz)	2.15	158.300	60	61.5	CW	H	0.85	BS	0.03	0.04	0.05	0.06	0.07	0.08	0.08	0.08	0.09	0.09	0.50	0.065	0.058	0.06
Roof	HAD4021A (136-174MHz)	2.15	165.900	60	61.4	CW	H	0.85	BS	0.02	0.03	0.04	0.06	0.07	0.07	0.07	0.08	0.09	0.1	0.50	0.064	0.055	0.05
Roof	HAD4021A (136-174MHz)	2.15	173.400	60	61.8	CW	H	0.84	BS	0.02	0.03	0.04	0.06	0.07	0.07	0.08	0.09	0.1	0.1	0.50	0.065	0.056	0.06
Roof	HAD4006A (136-144 MHz)	2.15	136.000	60	59.1	CW	H	0.88	BS	0.04	0.04	0.05	0.07	0.08	0.08	0.09	0.09	0.09	0.09	0.50	0.071	0.074	0.07
Roof	HAD4006A (136-144 MHz)	2.15	140.000	60	60.1	CW	H	0.87	BS	0.03	0.04	0.06	0.07	0.08	0.09	0.09	0.09	0.09	0.09	0.50	0.072	0.074	0.07
Roof	HAD4006A (136-144 MHz)	2.15	144.000	60	60.6	CW	H	0.87	BS	0.03	0.04	0.05	0.07	0.08	0.08	0.09	0.09	0.09	0.09	0.50	0.072	0.073	0.07
Roof	HAD4007A (144-150.8 MHz)	2.15	144.000	60	60.6	CW	H	0.87	BS	0.03	0.04	0.05	0.07	0.07	0.08	0.08	0.09	0.09	0.09	0.50	0.069	0.068	0.07
Roof	HAD4007A (144-150.8 MHz)	2.15	148.000	60	60.7	CW	H	0.86	BS	0.03	0.04	0.05	0.06	0.07	0.08	0.09	0.09	0.09	0.09	0.50	0.069	0.066	0.07
Roof	HAD4007A (144-150.8 MHz)	2.15	150.800	60	60.8	CW	H	0.86	BS	0.03	0.04	0.05	0.06	0.07	0.08	0.08	0.09	0.09	0.09	0.50	0.068	0.064	0.06
Roof	HAD4008A (150.8-162 MHz)	2.15	150.800	60	60.8	CW	H	0.86	BS	0.03	0.04	0.05	0.06	0.07	0.08	0.08	0.09	0.09	0.09	0.50	0.068	0.065	0.07
Roof	HAD4008A (150.8-162 MHz)	2.15	156.200	60	61.3	CW	H	0.86	BS	0.03	0.04	0.06	0.07	0.08	0.08	0.09	0.09	0.1	0.1	0.50	0.075	0.078	0.08
Roof	HAD4008A (150.8-162 MHz)	2.15	162.000	60	61.3	CW	H	0.85	BS	0.03	0.04	0.05	0.07	0.08	0.08	0.08	0.09	0.1	0.1	0.50	0.073	0.072	0.07

MPE calculations are defined in section 13.0.

MPE measurement data for Bystander - Roof mounted antennas

D.U.T. Info.							Probe Info.		Test Position	MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Location	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor		Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAD4009A (162-174 MHz)	2.15	162.000	60	61.3	CW	H	0.85	BS	0.03	0.04	0.06	0.07	0.08	0.08	0.08	0.09	0.1	0.1	0.50	0.072	0.070	0.07
Roof	HAD4009A (162-174 MHz)	2.15	167.700	60	61.5	CW	H	0.85	BS	0.03	0.03	0.05	0.07	0.08	0.08	0.09	0.1	0.11	0.11	0.50	0.073	0.073	0.07
Roof	HAD4009A (162-174 MHz)	2.15	173.400	60	61.8	CW	H	0.84	BS	0.03	0.04	0.06	0.07	0.08	0.08	0.09	0.1	0.11	0.12	0.50	0.078	0.081	0.08
Roof	HAD4016A (136-162 MHz)	2.15	136.000	60	59.1	CW	H	0.88	BS	0.03	0.04	0.05	0.06	0.07	0.08	0.08	0.08	0.09	0.08	0.50	0.066	0.064	0.07
Roof	HAD4016A (136-162 MHz)	2.15	144.000	60	60.6	CW	H	0.87	BS	0.03	0.04	0.05	0.06	0.07	0.08	0.08	0.09	0.09	0.09	0.50	0.069	0.067	0.07
Roof	HAD4016A (136-162 MHz)	2.15	150.800	60	60.8	CW	H	0.86	BS	0.03	0.03	0.05	0.06	0.07	0.08	0.08	0.08	0.09	0.09	0.50	0.065	0.059	0.06
Roof	HAD4016A (136-162 MHz)	2.15	156.200	60	61.3	CW	H	0.86	BS	0.03	0.04	0.06	0.07	0.08	0.09	0.08	0.09	0.1	0.1	0.50	0.075	0.078	0.08
Roof	HAD4016A (136-162 MHz)	2.15	162.000	60	61.3	CW	H	0.85	BS	0.03	0.04	0.05	0.06	0.07	0.08	0.08	0.08	0.09	0.09	0.50	0.066	0.060	0.06
Roof	HAD4017A (146-174 MHz)	2.15	146.000	60	60.7	CW	H	0.87	BS	0.02	0.03	0.04	0.05	0.06	0.06	0.07	0.07	0.07	0.07	0.50	0.054	0.042	0.04
Roof	HAD4017A (146-174 MHz)	2.15	150.800	60	60.8	CW	H	0.86	BS	0.03	0.03	0.05	0.06	0.07	0.08	0.08	0.09	0.09	0.09	0.50	0.067	0.063	0.06
Roof	HAD4017A (146-174 MHz)	2.15	158.300	60	61.5	CW	H	0.85	BS	0.03	0.04	0.06	0.07	0.08	0.08	0.09	0.09	0.09	0.09	0.50	0.073	0.072	0.07
Roof	HAD4017A (146-174 MHz)	2.15	165.900	60	61.4	CW	H	0.85	BS	0.03	0.04	0.06	0.07	0.08	0.08	0.08	0.09	0.1	0.1	0.50	0.071	0.069	0.07
Roof	HAD4017A (146-174 MHz)	2.15	173.400	60	61.8	CW	H	0.84	BS	0.03	0.04	0.05	0.06	0.07	0.08	0.09	0.1	0.11	0.12	0.50	0.074	0.073	0.07

MPE calculations are defined in section 13.0.

MPE measurement data for Bystander - Roof mounted antennas

D.U.T. Info.							Probe Info.		Test Position	MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Location	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor		Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	RAD4010ARB (136-174 MHz)	5.15	136.000	60	59.1	CW	H	0.88	BS	0.02	0.02	0.03	0.04	0.04	0.04	0.04	0.04	0.05	0.07	0.50	0.039	0.022	0.02
Roof	RAD4010ARB (136-174 MHz)	5.15	140.000	60	60.1	CW	H	0.87	BS	0.02	0.02	0.03	0.04	0.04	0.04	0.04	0.04	0.05	0.08	0.50	0.040	0.022	0.02
Roof	RAD4010ARB (136-174 MHz)	5.15	144.000	60	60.6	CW	H	0.87	BS	0.02	0.03	0.03	0.04	0.04	0.05	0.05	0.05	0.07	0.09	0.50	0.046	0.031	0.03
Roof	RAD4010ARB (136-174 MHz)	5.15	150.800	60	60.8	CW	H	0.86	BS	0.02	0.02	0.03	0.04	0.04	0.04	0.04	0.04	0.06	0.08	0.50	0.040	0.023	0.02
Roof	RAD4010ARB (136-174 MHz)	5.15	158.300	60	61.5	CW	H	0.85	BS	0.02	0.03	0.03	0.04	0.04	0.04	0.05	0.06	0.08	0.1	0.50	0.050	0.034	0.03
Roof	RAD4010ARB (136-174 MHz)	5.15	165.900	60	61.4	CW	H	0.85	BS	0.02	0.02	0.03	0.04	0.04	0.04	0.05	0.06	0.08	0.09	0.50	0.046	0.029	0.03
Roof	RAD4010ARB (136-174 MHz)	5.15	173.400	60	61.8	CW	H	0.84	BS	0.02	0.03	0.04	0.05	0.06	0.06	0.07	0.09	0.11	0.12	0.50	0.066	0.058	0.06
Roof	HAD4022A (132-174 MHz)	5.15	136.000	60	59.1	CW	H	0.88	BS	0.02	0.02	0.03	0.04	0.05	0.05	0.05	0.06	0.07	0.09	0.50	0.049	0.035	0.04
Roof	HAD4022A (132-174 MHz)	5.15	140.000	60	60.1	CW	H	0.87	BS	0.02	0.02	0.03	0.04	0.04	0.05	0.05	0.06	0.08	0.09	0.50	0.048	0.033	0.03
Roof	HAD4022A (132-174 MHz)	5.15	144.000	60	60.6	CW	H	0.87	BS	0.02	0.26	0.03	0.04	0.05	0.05	0.06	0.07	0.08	0.09	0.50	0.075	0.080	0.08
Roof	HAD4022A (132-174 MHz)	5.15	150.800	60	60.8	CW	H	0.86	BS	0.02	0.03	0.03	0.04	0.05	0.05	0.05	0.07	0.08	0.1	0.50	0.051	0.036	0.04
Roof	HAD4022A (132-174 MHz)	5.15	158.300	60	61.5	CW	H	0.85	BS	0.03	0.04	0.04	0.05	0.06	0.06	0.07	0.08	0.1	0.11	0.50	0.063	0.054	0.05
Roof	HAD4022A (132-174 MHz)	5.15	165.900	60	61.4	CW	H	0.85	BS	0.03	0.03	0.04	0.05	0.06	0.06	0.07	0.08	0.1	0.12	0.50	0.062	0.052	0.05
Roof	HAD4022A (132-174 MHz)	5.15	173.400	60	61.8	CW	H	0.84	BS	0.02	0.03	0.04	0.06	0.07	0.07	0.09	0.1	0.12	0.13	0.50	0.071	0.067	0.07

MPE calculations are defined in section 13.0.

MPE measurement data for Passenger - Roof mounted antennas

D.U.T. Info.							Probe Info.		Test Position	MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Location	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor		Passenger						
										Head	Chest	Lower Trunk				
Roof	HAD4021A (136-174MHz)	2.15	136.000	60	59.1	CW	E	0.99	PB	0.197	0.196	0.134	0.50	0.176	0.087	0.09
Roof	HAD4021A (136-174MHz)	2.15	140.000	60	60.1	CW	E	1.00	PB	0.328	0.345	0.248	0.50	0.307	0.154	0.15
Roof	HAD4021A (136-174MHz)	2.15	144.000	60	60.6	CW	E	1.00	PB	0.285	0.306	0.244	0.50	0.278	0.139	0.14
Roof	HAD4021A (136-174MHz)	2.15	150.800	60	60.8	CW	E	1.00	PB	0.036	0.175	0.209	0.50	0.140	0.070	0.07
Roof	HAD4021A (136-174MHz)	2.15	158.300	60	61.5	CW	E	1.00	PB	0.076	0.013	0.02	0.50	0.036	0.018	0.02
Roof	HAD4021A (136-174MHz)	2.15	165.900	60	61.4	CW	E	1.00	PB	0.094	0.123	0.213	0.50	0.143	0.072	0.07
Roof	HAD4021A (136-174MHz)	2.15	173.400	60	61.8	CW	E	1.00	PB	0.075	0.044	0.085	0.50	0.068	0.034	0.03
Roof	HAD4006A (136-144 MHz)	2.15	136.000	60	59.1	CW	E	0.99	PB	0.356	0.402	0.373	0.50	0.377	0.187	0.19
Roof	HAD4006A (136-144 MHz)	2.15	140.000	60	60.1	CW	E	1.00	PB	0.426	0.414	0.342	0.50	0.394	0.197	0.20
Roof	HAD4006A (136-144 MHz)	2.15	144.000	60	60.6	CW	E	1.00	PB	0.317	0.291	0.219	0.50	0.276	0.138	0.14
Roof	HAD4007A (144-150.8 MHz)	2.15	144.000	60	60.6	CW	E	1.00	PB	0.313	0.263	0.202	0.50	0.259	0.130	0.13
Roof	HAD4007A (144-150.8 MHz)	2.15	148.000	60	60.7	CW	E	1.00	PB	0.058	0.13	0.129	0.50	0.106	0.053	0.05
Roof	HAD4007A (144-150.8 MHz)	2.15	150.800	60	60.8	CW	E	1.00	PB	0.121	0.148	0.126	0.50	0.132	0.066	0.07
Roof	HAD4008A (150.8-162 MHz)	2.15	150.800	60	60.8	CW	E	1.00	PB	0.124	0.156	0.147	0.50	0.142	0.071	0.07
Roof	HAD4008A (150.8-162 MHz)	2.15	156.200	60	61.3	CW	E	1.00	PB	0.11	0.131	0.084	0.50	0.108	0.054	0.05
Roof	HAD4008A (150.8-162 MHz)	2.15	162.000	60	61.3	CW	E	1.00	PB	0.173	0.117	0.119	0.50	0.136	0.068	0.07

MPE calculations are defined in section 13.0.

MPE measurement data for Passenger - Roof mounted antennas

D.U.T. Info.							Probe Info.		Test Position	MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Location	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor		Passenger						
										Head	Chest	Lower Trunk				
Roof	HAD4009A (162-174 MHz)	2.15	162.000	60	61.3	CW	E	1.00	PB	0.156	0.115	0.1	0.50	0.124	0.062	0.06
Roof	HAD4009A (162-174 MHz)	2.15	167.700	60	61.5	CW	E	1.00	PB	0.118	0.126	0.171	0.50	0.138	0.069	0.07
Roof	HAD4009A (162-174 MHz)	2.15	173.400	60	61.8	CW	E	1.00	PB	0.117	0.063	0.111	0.50	0.097	0.049	0.05
Roof	HAD4016A (136-162 MHz)	2.15	136.000	60	59.1	CW	E	0.99	PB	0.199	0.185	0.119	0.50	0.168	0.083	0.08
Roof	HAD4016A (136-162 MHz)	2.15	144.000	60	60.6	CW	E	1.00	PB	0.174	0.253	0.232	0.50	0.220	0.110	0.11
Roof	HAD4016A (136-162 MHz)	2.15	150.800	60	60.8	CW	E	1.00	PB	0.098	0.14	0.149	0.50	0.129	0.065	0.06
Roof	HAD4016A (136-162 MHz)	2.15	156.200	60	61.3	CW	E	1.00	PB	0.074	0.155	0.106	0.50	0.112	0.056	0.06
Roof	HAD4016A (136-162 MHz)	2.15	162.000	60	61.3	CW	E	1.00	PB	0.126	0.11	0.123	0.50	0.120	0.060	0.06
Roof	HAD4017A (146-174 MHz)	2.15	146.000	60	60.7	CW	E	1.00	PB	0.075	0.086	0.093	0.50	0.085	0.042	0.04
Roof	HAD4017A (146-174 MHz)	2.15	150.800	60	60.8	CW	E	1.00	PB	0.121	0.156	0.152	0.50	0.143	0.072	0.07
Roof	HAD4017A (146-174 MHz)	2.15	158.300	60	61.5	CW	E	1.00	PB	0.064	0.02	0.03	0.50	0.038	0.019	0.02
Roof	HAD4017A (146-174 MHz)	2.15	165.900	60	61.4	CW	E	1.00	PB	0.161	0.21	0.188	0.50	0.186	0.093	0.09
Roof	HAD4017A (146-174 MHz)	2.15	173.400	60	61.8	CW	E	1.00	PB	0.07	0.098	0.174	0.50	0.114	0.057	0.06

MPE calculations are defined in section 13.0.

MPE measurement data for Passenger - Roof mounted antennas

D.U.T. Info.							Probe Info.		Test Position	MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Location	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor		Passenger						
										Head	Chest	Lower Trunk				
Roof	RAD4010ARB (136-174 MHz)	5.15	136.000	60	59.1	CW	E	0.99	PB	0.062	0.103	0.109	0.50	0.091	0.045	0.05
Roof	RAD4010ARB (136-174 MHz)	5.15	140.000	60	60.1	CW	E	1.00	PB	0.016	0.047	0.055	0.50	0.039	0.020	0.02
Roof	RAD4010ARB (136-174 MHz)	5.15	144.000	60	60.6	CW	E	1.00	PB	0.021	0.062	0.069	0.50	0.051	0.025	0.03
Roof	RAD4010ARB (136-174 MHz)	5.15	150.800	60	60.8	CW	E	1.00	PB	0.012	0.08	0.123	0.50	0.072	0.036	0.04
Roof	RAD4010ARB (136-174 MHz)	5.15	158.300	60	61.5	CW	E	1.00	PB	0.035	0.058	0.045	0.50	0.046	0.023	0.02
Roof	RAD4010ARB (136-174 MHz)	5.15	165.900	60	61.4	CW	E	1.00	PB	0.026	0.032	0.049	0.50	0.036	0.018	0.02
Roof	RAD4010ARB (136-174 MHz)	5.15	173.400	60	61.8	CW	E	1.00	PB	0.046	0.045	0.064	0.50	0.052	0.026	0.03
Roof	HAD4022A (132-174 MHz)	5.15	136.000	60	59.1	CW	E	0.99	PB	0.037	0.041	0.035	0.50	0.038	0.019	0.02
Roof	HAD4022A (132-174 MHz)	5.15	140.000	60	60.1	CW	E	1.00	PB	0.034	0.047	0.043	0.50	0.041	0.021	0.02
Roof	HAD4022A (132-174 MHz)	5.15	144.000	60	60.6	CW	E	1.00	PB	0.042	0.081	0.092	0.50	0.072	0.036	0.04
Roof	HAD4022A (132-174 MHz)	5.15	150.800	60	60.8	CW	E	1.00	PB	0.008	0.043	0.059	0.50	0.037	0.018	0.02
Roof	HAD4022A (132-174 MHz)	5.15	158.300	60	61.5	CW	E	1.00	PB	0.048	0.01	0.007	0.50	0.022	0.011	0.01
Roof	HAD4022A (132-174 MHz)	5.15	165.900	60	61.4	CW	E	1.00	PB	0.065	0.104	0.177	0.50	0.115	0.058	0.06
Roof	HAD4022A (132-174 MHz)	5.15	173.400	60	61.8	CW	E	1.00	PB	0.075	0.04	0.081	0.50	0.065	0.033	0.03

MPE calculations are defined in section 13.0.

MPE measurement data for Passenger - Roof mounted antennas

D.U.T. Info.							Probe Info.		Test Position	MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Location	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor		Passenger						
										Head	Chest	Lower Trunk				
Roof	HAD4021A (136-174MHz)	2.15	136.000	60	59.1	CW	E	0.99	PF	0.054	0.057	0.052	0.50	0.054	0.027	0.03
Roof	HAD4021A (136-174MHz)	2.15	140.000	60	60.1	CW	E	1.00	PF	0.164	0.161	0.154	0.50	0.160	0.080	0.08
Roof	HAD4021A (136-174MHz)	2.15	144.000	60	60.6	CW	E	1.00	PF	0.161	0.166	0.15	0.50	0.159	0.080	0.08
Roof	HAD4021A (136-174MHz)	2.15	150.800	60	60.8	CW	E	1.00	PF	0.086	0.083	0.119	0.50	0.096	0.048	0.05
Roof	HAD4021A (136-174MHz)	2.15	158.300	60	61.5	CW	E	1.00	PF	0.049	0.071	0.068	0.50	0.063	0.031	0.03
Roof	HAD4021A (136-174MHz)	2.15	165.900	60	61.4	CW	E	1.00	PF	0.029	0.023	0.035	0.50	0.029	0.015	0.01
Roof	HAD4021A (136-174MHz)	2.15	173.400	60	61.8	CW	E	1.00	PF	0.014	0.016	0.017	0.50	0.016	0.008	0.01
Roof	HAD4006A (136-144 MHz)	2.15	136.000	60	59.1	CW	E	0.99	PF	0.075	0.095	0.102	0.50	0.091	0.045	0.05
Roof	HAD4006A (136-144 MHz)	2.15	140.000	60	60.1	CW	E	1.00	PF	0.098	0.113	0.118	0.50	0.110	0.055	0.05
Roof	HAD4006A (136-144 MHz)	2.15	144.000	60	60.6	CW	E	1.00	PF	0.078	0.07	0.142	0.50	0.097	0.048	0.05
Roof	HAD4007A (144-150.8 MHz)	2.15	144.000	60	60.6	CW	E	1.00	PF	0.071	0.057	0.124	0.50	0.084	0.042	0.04
Roof	HAD4007A (144-150.8 MHz)	2.15	148.000	60	60.7	CW	E	1.00	PF	0.07	0.13	0.137	0.50	0.112	0.056	0.06
Roof	HAD4007A (144-150.8 MHz)	2.15	150.800	60	60.8	CW	E	1.00	PF	0.089	0.055	0.049	0.50	0.064	0.032	0.03
Roof	HAD4008A (150.8-162 MHz)	2.15	150.800	60	60.8	CW	E	1.00	PF	0.091	0.065	0.063	0.50	0.073	0.037	0.04
Roof	HAD4008A (150.8-162 MHz)	2.15	156.200	60	61.3	CW	E	1.00	PF	0.02	0.047	0.079	0.50	0.049	0.024	0.02
Roof	HAD4008A (150.8-162 MHz)	2.15	162.000	60	61.3	CW	E	1.00	PF	0.033	0.067	0.128	0.50	0.076	0.038	0.04

MPE calculations are defined in section 13.0.

MPE measurement data for Passenger - Roof mounted antennas

D.U.T. Info.							Probe Info.		Test Position	MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Location	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor		Passenger						
										Head	Chest	Lower Trunk				
Roof	HAD4009A (162-174 MHz)	2.15	162.000	60	61.3	CW	E	1.00	PF	0.025	0.057	0.122	0.50	0.068	0.034	0.03
Roof	HAD4009A (162-174 MHz)	2.15	167.700	60	61.5	CW	E	1.00	PF	0.033	0.053	0.12	0.50	0.069	0.034	0.03
Roof	HAD4009A (162-174 MHz)	2.15	173.400	60	61.8	CW	E	1.00	PF	0.032	0.025	0.051	0.50	0.036	0.018	0.02
Roof	HAD4016A (136-162 MHz)	2.15	136.000	60	59.1	CW	E	0.99	PF	0.075	0.061	0.046	0.50	0.061	0.030	0.03
Roof	HAD4016A (136-162 MHz)	2.15	144.000	60	60.6	CW	E	1.00	PF	0.085	0.138	0.172	0.50	0.132	0.066	0.07
Roof	HAD4016A (136-162 MHz)	2.15	150.800	60	60.8	CW	E	1.00	PF	0.079	0.044	0.065	0.50	0.063	0.031	0.03
Roof	HAD4016A (136-162 MHz)	2.15	156.200	60	61.3	CW	E	1.00	PF	0.023	0.053	0.079	0.50	0.052	0.026	0.03
Roof	HAD4016A (136-162 MHz)	2.15	162.000	60	61.3	CW	E	1.00	PF	0.024	0.055	0.094	0.50	0.058	0.029	0.03
Roof	HAD4017A (146-174 MHz)	2.15	146.000	60	60.7	CW	E	1.00	PF	0.041	0.085	0.098	0.50	0.075	0.037	0.04
Roof	HAD4017A (146-174 MHz)	2.15	150.800	60	60.8	CW	E	1.00	PF	0.083	0.054	0.072	0.50	0.070	0.035	0.03
Roof	HAD4017A (146-174 MHz)	2.15	158.300	60	61.5	CW	E	1.00	PF	0.032	0.069	0.097	0.50	0.066	0.033	0.03
Roof	HAD4017A (146-174 MHz)	2.15	165.900	60	61.4	CW	E	1.00	PF	0.032	0.057	0.172	0.50	0.087	0.044	0.04
Roof	HAD4017A (146-174 MHz)	2.15	173.400	60	61.8	CW	E	1.00	PF	0.025	0.035	0.051	0.50	0.037	0.019	0.02

MPE calculations are defined in section 13.0.

MPE measurement data for Passenger - Roof mounted antennas

D.U.T. Info.							Probe Info.		Test Position	MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Location	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor		Passenger						
										Head	Chest	Lower Trunk				
Roof	RAD4010ARB (136-174 MHz)	5.15	136.000	60	59.1	CW	E	0.99	PF	0.031	0.018	0.011	0.50	0.020	0.010	0.01
Roof	RAD4010ARB (136-174 MHz)	5.15	140.000	60	60.1	CW	E	1.00	PF	0.022	0.013	0.008	0.50	0.014	0.007	0.01
Roof	RAD4010ARB (136-174 MHz)	5.15	144.000	60	60.6	CW	E	1.00	PF	0.021	0.02	0.015	0.50	0.019	0.009	0.01
Roof	RAD4010ARB (136-174 MHz)	5.15	150.800	60	60.8	CW	E	1.00	PF	0.036	0.031	0.008	0.50	0.025	0.013	0.01
Roof	RAD4010ARB (136-174 MHz)	5.15	158.300	60	61.5	CW	E	1.00	PF	0.008	0.01	0.009	0.50	0.009	0.005	0.00
Roof	RAD4010ARB (136-174 MHz)	5.15	165.900	60	61.4	CW	E	1.00	PF	0.014	0.023	0.024	0.50	0.020	0.010	0.01
Roof	RAD4010ARB (136-174 MHz)	5.15	173.400	60	61.8	CW	E	1.00	PF	0.03	0.036	0.049	0.50	0.038	0.019	0.02
Roof	HAD4022A (132-174 MHz)	5.15	136.000	60	59.1	CW	E	0.99	PF	0.016	0.016	0.017	0.50	0.016	0.008	0.01
Roof	HAD4022A (132-174 MHz)	5.15	140.000	60	60.1	CW	E	1.00	PF	0.015	0.011	0.014	0.50	0.013	0.007	0.01
Roof	HAD4022A (132-174 MHz)	5.15	144.000	60	60.6	CW	E	1.00	PF	0.024	0.02	0.029	0.50	0.024	0.012	0.01
Roof	HAD4022A (132-174 MHz)	5.15	150.800	60	60.8	CW	E	1.00	PF	0.007	0.014	0.038	0.50	0.020	0.010	0.01
Roof	HAD4022A (132-174 MHz)	5.15	158.300	60	61.5	CW	E	1.00	PF	0.009	0.024	0.033	0.50	0.022	0.011	0.01
Roof	HAD4022A (132-174 MHz)	5.15	165.900	60	61.4	CW	E	1.00	PF	0.017	0.025	0.044	0.50	0.029	0.014	0.01
Roof	HAD4022A (132-174 MHz)	5.15	173.400	60	61.8	CW	E	1.00	PF	0.02	0.026	0.029	0.50	0.025	0.013	0.01

MPE calculations are defined in section 13.0.

MPE measurement data for Passenger - Roof mounted antennas

D.U.T. Info.							Probe Info.		Test Position	MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Location	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor		Passenger						
										Head	Chest	Lower Trunk				
Roof	HAD4021A (136-174MHz)	2.15	136.000	60	59.1	CW	H	0.88	PB	0.055	0.053	0.064	0.50	0.057	0.025	0.03
Roof	HAD4021A (136-174MHz)	2.15	140.000	60	60.1	CW	H	0.87	PB	0.07	0.07	0.071	0.50	0.070	0.031	0.03
Roof	HAD4021A (136-174MHz)	2.15	144.000	60	60.6	CW	H	0.87	PB	0.066	0.069	0.072	0.50	0.069	0.030	0.03
Roof	HAD4021A (136-174MHz)	2.15	150.800	60	60.8	CW	H	0.86	PB	0.081	0.069	0.061	0.50	0.070	0.030	0.03
Roof	HAD4021A (136-174MHz)	2.15	158.300	60	61.5	CW	H	0.85	PB	0.045	0.032	0.037	0.50	0.038	0.016	0.02
Roof	HAD4021A (136-174MHz)	2.15	165.900	60	61.4	CW	H	0.85	PB	0.073	0.068	0.046	0.50	0.062	0.026	0.03
Roof	HAD4021A (136-174MHz)	2.15	173.400	60	61.8	CW	H	0.84	PB	0.051	0.053	0.037	0.50	0.047	0.020	0.02
Roof	HAD4006A (136-144 MHz)	2.15	136.000	60	59.1	CW	H	0.88	PB	0.064	0.057	0.051	0.50	0.057	0.048	0.05
Roof	HAD4006A (136-144 MHz)	2.15	140.000	60	60.1	CW	H	0.87	PB	0.074	0.077	0.07	0.50	0.074	0.077	0.08
Roof	HAD4006A (136-144 MHz)	2.15	144.000	60	60.6	CW	H	0.87	PB	0.073	0.076	0.071	0.50	0.073	0.077	0.08
Roof	HAD4007A (144-150.8 MHz)	2.15	144.000	60	60.6	CW	H	0.87	PB	0.074	0.069	0.072	0.50	0.072	0.073	0.07
Roof	HAD4007A (144-150.8 MHz)	2.15	148.000	60	60.7	CW	H	0.86	PB	0.057	0.045	0.045	0.50	0.049	0.033	0.03
Roof	HAD4007A (144-150.8 MHz)	2.15	150.800	60	60.8	CW	H	0.86	PB	0.064	0.051	0.046	0.50	0.054	0.040	0.04
Roof	HAD4008A (150.8-162 MHz)	2.15	150.800	60	60.8	CW	H	0.86	PB	0.064	0.052	0.045	0.50	0.054	0.040	0.04
Roof	HAD4008A (150.8-162 MHz)	2.15	156.200	60	61.3	CW	H	0.86	PB	0.051	0.042	0.033	0.50	0.042	0.025	0.02
Roof	HAD4008A (150.8-162 MHz)	2.15	162.000	60	61.3	CW	H	0.85	PB	0.063	0.053	0.04	0.50	0.052	0.037	0.04

MPE calculations are defined in section 13.0.

MPE measurement data for Passenger - Roof mounted antennas

D.U.T. Info.							Probe Info.		Test Position	MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Location	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor		Passenger						
										Head	Chest	Lower Trunk				
Roof	HAD4009A (162-174 MHz)	2.15	162.000	60	61.3	CW	H	0.85	PB	0.057	0.049	0.041	0.50	0.049	0.033	0.03
Roof	HAD4009A (162-174 MHz)	2.15	167.700	60	61.5	CW	H	0.85	PB	0.078	0.077	0.053	0.50	0.069	0.065	0.07
Roof	HAD4009A (162-174 MHz)	2.15	173.400	60	61.8	CW	H	0.84	PB	0.056	0.063	0.041	0.50	0.053	0.038	0.04
Roof	HAD4016A (136-162 MHz)	2.15	136.000	60	59.1	CW	H	0.88	PB	0.06	0.057	0.052	0.50	0.056	0.046	0.05
Roof	HAD4016A (136-162 MHz)	2.15	144.000	60	60.6	CW	H	0.87	PB	0.072	0.068	0.072	0.50	0.071	0.071	0.07
Roof	HAD4016A (136-162 MHz)	2.15	150.800	60	60.8	CW	H	0.86	PB	0.065	0.052	0.043	0.50	0.053	0.040	0.04
Roof	HAD4016A (136-162 MHz)	2.15	156.200	60	61.3	CW	H	0.86	PB	0.057	0.046	0.033	0.50	0.045	0.029	0.03
Roof	HAD4016A (136-162 MHz)	2.15	162.000	60	61.3	CW	H	0.85	PB	0.057	0.077	0.038	0.50	0.057	0.045	0.04
Roof	HAD4017A (146-174 MHz)	2.15	146.000	60	60.7	CW	H	0.87	PB	0.052	0.048	0.05	0.50	0.050	0.036	0.04
Roof	HAD4017A (146-174 MHz)	2.15	150.800	60	60.8	CW	H	0.86	PB	0.073	0.062	0.051	0.50	0.062	0.054	0.05
Roof	HAD4017A (146-174 MHz)	2.15	158.300	60	61.5	CW	H	0.85	PB	0.049	0.031	0.028	0.50	0.036	0.018	0.02
Roof	HAD4017A (146-174 MHz)	2.15	165.900	60	61.4	CW	H	0.85	PB	0.075	0.064	0.044	0.50	0.061	0.051	0.05
Roof	HAD4017A (146-174 MHz)	2.15	173.400	60	61.8	CW	H	0.84	PB	0.048	0.047	0.037	0.50	0.044	0.026	0.03

MPE calculations are defined in section 13.0.

MPE measurement data for Passenger - Roof mounted antennas

D.U.T. Info.							Probe Info.		Test Position	MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Location	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor		Passenger						
										Head	Chest	Lower Trunk				
Roof	RAD4010ARB (136-174 MHz)	5.15	136.000	60	59.1	CW	H	0.88	PB	0.038	0.051	0.034	0.50	0.041	0.025	0.02
Roof	RAD4010ARB (136-174 MHz)	5.15	140.000	60	60.1	CW	H	0.87	PB	0.03	0.029	0.025	0.50	0.028	0.011	0.01
Roof	RAD4010ARB (136-174 MHz)	5.15	144.000	60	60.6	CW	H	0.87	PB	0.037	0.031	0.025	0.50	0.031	0.014	0.01
Roof	RAD4010ARB (136-174 MHz)	5.15	150.800	60	60.8	CW	H	0.86	PB	0.042	0.038	0.028	0.50	0.036	0.018	0.02
Roof	RAD4010ARB (136-174 MHz)	5.15	158.300	60	61.5	CW	H	0.85	PB	0.037	0.033	0.029	0.50	0.033	0.015	0.01
Roof	RAD4010ARB (136-174 MHz)	5.15	165.900	60	61.4	CW	H	0.85	PB	0.039	0.038	0.026	0.50	0.034	0.016	0.02
Roof	RAD4010ARB (136-174 MHz)	5.15	173.400	60	61.8	CW	H	0.84	PB	0.038	0.043	0.034	0.50	0.038	0.020	0.02
Roof	HAD4022A (132-174 MHz)	5.15	136.000	60	59.1	CW	H	0.88	PB	0.032	0.047	0.028	0.50	0.036	0.019	0.02
Roof	HAD4022A (132-174 MHz)	5.15	140.000	60	60.1	CW	H	0.87	PB	0.039	0.034	0.033	0.50	0.035	0.018	0.02
Roof	HAD4022A (132-174 MHz)	5.15	144.000	60	60.6	CW	H	0.87	PB	0.048	0.04	0.042	0.50	0.043	0.027	0.03
Roof	HAD4022A (132-174 MHz)	5.15	150.800	60	60.8	CW	H	0.86	PB	0.04	0.036	0.03	0.50	0.035	0.017	0.02
Roof	HAD4022A (132-174 MHz)	5.15	158.300	60	61.5	CW	H	0.85	PB	0.042	0.023	0.032	0.50	0.032	0.014	0.01
Roof	HAD4022A (132-174 MHz)	5.15	165.900	60	61.4	CW	H	0.85	PB	0.07	0.062	0.038	0.50	0.057	0.044	0.04
Roof	HAD4022A (132-174 MHz)	5.15	173.400	60	61.8	CW	H	0.84	PB	0.043	0.047	0.035	0.50	0.042	0.023	0.02

MPE calculations are defined in section 13.0.

MPE measurement data for Passenger - Roof mounted antennas

D.U.T. Info.							Probe Info.		Test Position	MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Location	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor		Passenger						
										Head	Chest	Lower Trunk				
Roof	HAD4021A (136-174MHz)	2.15	136.000	60	59.1	CW	H	0.88	PF	0.048	0.038	0.034	0.50	0.040	0.023	0.02
Roof	HAD4021A (136-174MHz)	2.15	140.000	60	60.1	CW	H	0.87	PF	0.045	0.051	0.066	0.50	0.054	0.042	0.04
Roof	HAD4021A (136-174MHz)	2.15	144.000	60	60.6	CW	H	0.87	PF	0.045	0.059	0.068	0.50	0.057	0.047	0.05
Roof	HAD4021A (136-174MHz)	2.15	150.800	60	60.8	CW	H	0.86	PF	0.06	0.065	0.052	0.50	0.059	0.049	0.05
Roof	HAD4021A (136-174MHz)	2.15	158.300	60	61.5	CW	H	0.85	PF	0.051	0.055	0.038	0.50	0.048	0.031	0.03
Roof	HAD4021A (136-174MHz)	2.15	165.900	60	61.4	CW	H	0.85	PF	0.032	0.026	0.02	0.50	0.026	0.009	0.01
Roof	HAD4021A (136-174MHz)	2.15	173.400	60	61.8	CW	H	0.84	PF	0.039	0.028	0.023	0.50	0.030	0.012	0.01
Roof	HAD4006A (136-144 MHz)	2.15	136.000	60	59.1	CW	H	0.88	PF	0.055	0.063	0.046	0.50	0.055	0.044	0.04
Roof	HAD4006A (136-144 MHz)	2.15	140.000	60	60.1	CW	H	0.87	PF	0.06	0.061	0.056	0.50	0.059	0.050	0.05
Roof	HAD4006A (136-144 MHz)	2.15	144.000	60	60.6	CW	H	0.87	PF	0.064	0.079	0.076	0.50	0.073	0.076	0.08
Roof	HAD4007A (144-150.8 MHz)	2.15	144.000	60	60.6	CW	H	0.87	PF	0.063	0.077	0.071	0.50	0.070	0.071	0.07
Roof	HAD4007A (144-150.8 MHz)	2.15	148.000	60	60.7	CW	H	0.86	PF	0.068	0.09	0.068	0.50	0.075	0.079	0.08
Roof	HAD4007A (144-150.8 MHz)	2.15	150.800	60	60.8	CW	H	0.86	PF	0.061	0.075	0.058	0.50	0.065	0.058	0.06
Roof	HAD4008A (150.8-162 MHz)	2.15	150.800	60	60.8	CW	H	0.86	PF	0.068	0.077	0.065	0.50	0.070	0.068	0.07
Roof	HAD4008A (150.8-162 MHz)	2.15	156.200	60	61.3	CW	H	0.86	PF	0.037	0.041	0.037	0.50	0.038	0.020	0.02
Roof	HAD4008A (150.8-162 MHz)	2.15	162.000	60	61.3	CW	H	0.85	PF	0.034	0.036	0.037	0.50	0.036	0.017	0.02

MPE calculations are defined in section 13.0.

MPE measurement data for Passenger - Roof mounted antennas

D.U.T. Info.							Probe Info.		Test Position	MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/ cm2)	Calc. P.D. (mW/ cm2)	Max Calc. P.D. (mW/ cm2)
Ant Location	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor		Passenger						
										Head	Chest	Lower Trunk				
Roof	HAD4009A (162-174 MHz)	2.15	162.000	60	61.3	CW	H	0.85	PF	0.031	0.036	0.038	0.50	0.035	0.017	0.02
Roof	HAD4009A (162-174 MHz)	2.15	167.700	60	61.5	CW	H	0.85	PF	0.033	0.029	0.03	0.50	0.031	0.013	0.01
Roof	HAD4009A (162-174 MHz)	2.15	173.400	60	61.8	CW	H	0.84	PF	0.042	0.035	0.03	0.50	0.036	0.017	0.02
Roof	HAD4016A (136-162 MHz)	2.15	136.000	60	59.1	CW	H	0.88	PF	0.053	0.054	0.043	0.50	0.050	0.036	0.04
Roof	HAD4016A (136-162 MHz)	2.15	144.000	60	60.6	CW	H	0.87	PF	0.056	0.072	0.071	0.50	0.066	0.063	0.06
Roof	HAD4016A (136-162 MHz)	2.15	150.800	60	60.8	CW	H	0.86	PF	0.058	0.068	0.058	0.50	0.061	0.052	0.05
Roof	HAD4016A (136-162 MHz)	2.15	156.200	60	61.3	CW	H	0.86	PF	0.04	0.046	0.038	0.50	0.041	0.024	0.02
Roof	HAD4016A (136-162 MHz)	2.15	162.000	60	61.3	CW	H	0.85	PF	0.032	0.032	0.038	0.50	0.034	0.016	0.02
Roof	HAD4017A (146-174 MHz)	2.15	146.000	60	60.7	CW	H	0.87	PF	0.041	0.054	0.046	0.50	0.047	0.032	0.03
Roof	HAD4017A (146-174 MHz)	2.15	150.800	60	60.8	CW	H	0.86	PF	0.06	0.074	0.05	0.50	0.061	0.052	0.05
Roof	HAD4017A (146-174 MHz)	2.15	158.300	60	61.5	CW	H	0.85	PF	0.046	0.05	0.038	0.50	0.045	0.027	0.03
Roof	HAD4017A (146-174 MHz)	2.15	165.900	60	61.4	CW	H	0.85	PF	0.028	0.027	0.032	0.50	0.029	0.011	0.01
Roof	HAD4017A (146-174 MHz)	2.15	173.400	60	61.8	CW	H	0.84	PF	0.041	0.042	0.026	0.50	0.036	0.018	0.02

MPE calculations are defined in section 13.0.

MPE measurement data for Passenger - Roof mounted antennas

D.U.T. Info.							Probe Info.		Test Position	MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Location	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor		Passenger						
										Head	Chest	Lower Trunk				
Roof	RAD4010ARB (136-174 MHz)	5.15	136.000	60	59.1	CW	H	0.88	PF	0.018	0.018	0.016	0.50	0.017	0.004	0.00
Roof	RAD4010ARB (136-174 MHz)	5.15	140.000	60	60.1	CW	H	0.87	PF	0.02	0.02	0.019	0.50	0.020	0.006	0.01
Roof	RAD4010ARB (136-174 MHz)	5.15	144.000	60	60.6	CW	H	0.87	PF	0.028	0.027	0.024	0.50	0.026	0.010	0.01
Roof	RAD4010ARB (136-174 MHz)	5.15	150.800	60	60.8	CW	H	0.86	PF	0.023	0.022	0.016	0.50	0.020	0.006	0.01
Roof	RAD4010ARB (136-174 MHz)	5.15	158.300	60	61.5	CW	H	0.85	PF	0.024	0.02	0.015	0.50	0.020	0.005	0.01
Roof	RAD4010ARB (136-174 MHz)	5.15	165.900	60	61.4	CW	H	0.85	PF	0.021	0.016	0.018	0.50	0.018	0.005	0.00
Roof	RAD4010ARB (136-174 MHz)	5.15	173.400	60	61.8	CW	H	0.84	PF	0.032	0.028	0.024	0.50	0.028	0.010	0.01
Roof	HAD4022A (132-174 MHz)	5.15	136.000	60	59.1	CW	H	0.88	PF	0.029	0.029	0.023	0.50	0.027	0.011	0.01
Roof	HAD4022A (132-174 MHz)	5.15	140.000	60	60.1	CW	H	0.87	PF	0.025	0.028	0.024	0.50	0.026	0.009	0.01
Roof	HAD4022A (132-174 MHz)	5.15	144.000	60	60.6	CW	H	0.87	PF	0.032	0.035	0.034	0.50	0.034	0.016	0.02
Roof	HAD4022A (132-174 MHz)	5.15	150.800	60	60.8	CW	H	0.86	PF	0.028	0.033	0.025	0.50	0.029	0.011	0.01
Roof	HAD4022A (132-174 MHz)	5.15	158.300	60	61.5	CW	H	0.85	PF	0.029	0.031	0.025	0.50	0.028	0.011	0.01
Roof	HAD4022A (132-174 MHz)	5.15	165.900	60	61.4	CW	H	0.85	PF	0.025	0.023	0.024	0.50	0.024	0.008	0.01
Roof	HAD4022A (132-174 MHz)	5.15	173.400	60	61.8	CW	H	0.84	PF	0.032	0.029	0.024	0.50	0.028	0.011	0.01

MPE calculations are defined in section 13.0.

Appendix E – SAR Simulation Results