



## MEASUREMENT REPORT

### FCC PART 15.247 / ISED RSS-247 WLAN 802.11b/g/n

**Applicant Name:**

Apple Inc.  
One Apple Park Way  
Cupertino, CA 95014  
United States

**Date of Testing:**

05/01/2019 - 07/24/2019

**Test Site/Location:**

PCTEST Lab. Morgan Hill, CA, USA

**Test Report Serial No.:**

1C1905130010-05.BCG

|                   |                   |
|-------------------|-------------------|
| <b>FCC ID:</b>    | <b>BCG-A2095</b>  |
| <b>IC:</b>        | <b>579C-A2095</b> |
| <b>APPLICANT:</b> | <b>Apple Inc.</b> |

**Application Type:**

Certification

**Model/HVIN:**

A2095

**EUT Type:**

Watch

**Frequency Range:**

2412 – 2472MHz

**FCC Classification:**

Digital Transmission System (DTS)

**FCC Rule Part(s):**

Part 15 Subpart C (15.247)

**ISED Specification:**

RSS-247 Issue 2

**Test Procedure(s):**

ANSI C63.10-2013, KDB 558074 D01 v05r02

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013 and KDB 558074 D01 v05r02. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.




---

Randy Ortanez  
President



|   |  |                    |   |                                 |
|---|--|--------------------|---|---------------------------------|
| FCC ID: BCG-A2095                       |  <b>PCTEST</b><br><small>ENGINEERING LABORATORY, INC.</small> |                    | <b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019   | EUT Type:<br>Watch | Page 1 of 62                                  |                                 |

## T A B L E   O F   C O N T E N T S


---

|       |   |    |
|-------|---|----|
| 1.0   | INTRODUCTION.....   | 4  |
| 1.1   | Scope .....   | 4  |
| 1.2   | PCTEST Test Location.....                                   | 4  |
| 1.3   | Test Facility / Accreditations.....                         | 4  |
| 2.0   | PRODUCT INFORMATION .....                                   | 5  |
| 2.1   | Equipment Description .....                                 | 5  |
| 2.2   | Device Capabilities.....                                    | 5  |
| 2.3   | Antenna Description .....                                   | 6  |
| 2.4   | Test Support Equipment.....                                 | 6  |
| 2.5   | Test Configuration .....                                    | 7  |
| 2.6   | Software and Firmware .....                                 | 7  |
| 2.7   | EMI Suppression Device(s)/Modifications .....               | 7  |
| 3.0   | DESCRIPTION OF TESTS .....                                  | 8  |
| 3.1   | Evaluation Procedure .....                                  | 8  |
| 3.2   | AC Line Conducted Emissions .....                           | 8  |
| 3.3   | Radiated Emissions.....                                     | 9  |
| 3.4   | Environmental Conditions.....                               | 9  |
| 4.0   | ANTENNA REQUIREMENTS .....                                  | 10 |
| 5.0   | MEASUREMENT UNCERTAINTY.....                                | 11 |
| 6.0   | TEST EQUIPMENT CALIBRATION DATA.....                        | 12 |
| 7.0   | TEST RESULTS.....   | 13 |
| 7.1   | Summary .....   | 13 |
| 7.2   | 6dB Bandwidth Measurement .....                             | 14 |
| 7.3   | Output Power Measurement.....                               | 21 |
| 7.3.1 | Peak Output Power Measurement.....                          | 22 |
| 7.3.2 | Average Output Power Measurement.....                       | 23 |
| 7.4   | Power Spectral Density .....                                | 24 |
| 7.5   | Conducted Emissions at the Band Edge .....                  | 30 |
| 7.6   | Conducted Spurious Emissions.....                           | 37 |
| 7.7   | Radiated Spurious Emission Measurements – Above 1 GHz.....  | 42 |
| 7.8   | Radiated Restricted Band Edge Measurements.....             | 49 |
| 7.9   | Radiated Spurious Emissions Measurements – Below 1GHz ..... | 54 |
| 7.10  | AC Line-Conducted Test Data.....                            | 58 |
| 8.0   | CONCLUSION .....  | 62 |

|   |   |                    |                                       |                                 |
|---|---|--------------------|---------------------------------------|---------------------------------|
| FCC ID: BCG-A2095                       | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. |                    | MEASUREMENT REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019        | EUT Type:<br>Watch |                                       | Page 2 of 62                    |



# MEASUREMENT REPORT



| Mode    | Tx Frequency<br>(MHz) | Avg Conducted         |                        | Peak Conducted        |                        |
|---------|-----------------------|-----------------------|------------------------|-----------------------|------------------------|
|         |                       | Max.<br>Power<br>(mW) | Max.<br>Power<br>(dBm) | Max.<br>Power<br>(mW) | Max.<br>Power<br>(dBm) |
| 802.11b | 2412 - 2472           | 79.433                | 19.00                  | 138.357               | 21.41                  |
| 802.11g | 2412 - 2472           | 70.795                | 18.50                  | 208.449               | 23.19                  |
| 802.11n | 2412 - 2472           | 70.795                | 18.50                  | 206.538               | 23.15                  |

## EUT Overview

|   |   |                    |              |                                 |
|---|---|--------------------|--------------|---------------------------------|
| FCC ID: BCG-A2095                       |  <b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                    |              | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019  | EUT Type:<br>Watch | Page 3 of 62 |                                 |

## 1.0 INTRODUCTION

### 1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

### 1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 18855 Adams Court, Morgan Hill, CA 95037. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014 and KDB 414788 D01 v01r01.

### 1.3 Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Morgan Hill, CA 95037, U.S.A.

- PCTEST is an ISO 17025-2005 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.02 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- PCTEST facility is a registered (22831) test laboratory with the site description on file with ISED.

|   |  |                    |                                 |
|---|--|--------------------|---------------------------------|
| FCC ID: BCG-A2095                       | <br><b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                    | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019   | EUT Type:<br>Watch | Page 4 of 62                    |

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **Apple Watch FCC ID: BCG-A2095**. The test data contained in this report pertains only to the emissions due to the EUT's WLAN (DTS) transmitter.

**Test Device Serial No.:** D92D02NM95M, D92YD057M95J, FN690770041KTRG5V

### 2.2 Device Capabilities

This device contains the following capabilities:

850/1700/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n WLAN, Bluetooth (1x, EDR, HDR4, HDR8, LE), NFC

| Ch. | Frequency (MHz) | Ch. | Frequency (MHz) |
|-----|-----------------|-----|-----------------|
| 1   | 2412            | 8   | 2447            |
| 2   | 2417            | 9   | 2452            |
| 3   | 2422            | 10  | 2457            |
| 4   | 2427            | 11  | 2462            |
| 5   | 2432            | 12  | 2467            |
| 6   | 2437            | 13  | 2472            |
| 7   | 2442            |     |                 |

**Table 2-1. Frequency/ Channel Operations**

**Note:**

1. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = peak per the guidance of Section 6.0 b) of KDB 558074 D01 v05r02 and ANSI C63.10-2013. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

| 802.11 Mode/Band |   | Duty Cycle [%] |
|------------------|---|----------------|
| 2.4GHz           | b | 100.0          |
|                  | g | 98.0           |
|                  | n | 98.5           |

**Table 2-2. Measured Duty Cycles**

|   |  |                    |                                       |                                 |
|---|--|--------------------|---------------------------------------|---------------------------------|
| FCC ID: BCG-A2095                       | PCTEST<br>Engineering Laboratory, Inc. |                    | MEASUREMENT REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019 | EUT Type:<br>Watch |                                       |                                 |

2. This device supports simultaneous transmission operation, which allows for two transmitters to transmit simultaneously on the same antenna. The table below shows all configurations possible.

| Simultaneous Tx Configurations | Antenna         |                 |                 |                 |
|--------------------------------|-----------------|-----------------|-----------------|-----------------|
|                                | FCM             |                 |                 |                 |
|                                | Configuration 1 | Configuration 2 | Configuration 3 | Configuration 4 |
| WIFI 2.4GHz                    | ✓               | ✓               | ✗               | ✗               |
| Bluetooth                      | ✗               | ✗               | ✓               | ✓               |
| LTE Mid Bands                  | ✓               | ✗               | ✓               | ✗               |
| LTE High Bands                 | ✗               | ✓               | ✗               | ✓               |

**Table 2-3. Simultaneous Tx Configurations**

✓ = Support ; ✗ = NOT Support

a. The worst simultaneous Tx configuration was found to be Bluetooth and LTE Mid Band transmitting on antenna FCM. These results can be found in the RF Bluetooth and RF LTE FCC reports.

Data Rates Supported: 1Mbps, 2Mbps, 5.5Mbps, 11Mbps (b)  
6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps (g)  
6.5/7.2Mbps, 13/14.4Mbps, 19.5/21.7Mbps, 26/28.9Mbps, 39/43.3Mbps,  
52/57.8Mbps, 58.5/65Mbps, 65/72.2Mbps (n)

## 2.3 Antenna Description

Following antenna was used for the testing.

| Frequency [GHz] | Antenna Gain [dBi] |
|-----------------|--------------------|
| 2.4             | -8.90              |

**Table 2-4. Highest Antenna Gain**

## 2.4 Test Support Equipment

|   |  |  |   |
|---|--|--|---|
| 1 | Apple MacBook<br>w/AC/DC Adapter                           | Model: A1398<br>Model: A1435                 | S/N: C2QKP008F6F3<br>S/N: N/A                       |
| 2 | Apple USB Cable<br>w/ Charging Dock<br>w/ Dock             | Model: Kanzi<br>Model: FAPS73<br>Model: X241 | S/N: 311C81<br>S/N: 17481001022<br>S/N: GW17F01ST22 |
| 3 | USB Lightning Cable<br>w/ AC Adapter                       | Model: N/A<br>Model: A1385                   | S/N: N/A<br>S/N: N/A                                |
| 4 | Wireless Charging Pad (WCP)<br>Wireless Charging Pad (WCP) | Model: EVT<br>Model: EVT                     | S/N: DLC915600ECLNW3K<br>S/N: DLC9156006TLNW3V      |
| 5 | Test Pathfinder Sinsa Board<br>w/ SiP Cradle               | Model: X1456<br>Model: P1 X1454S             | S/N: 920-062535-01<br>S/N: 920-06373-02             |
| 6 | DC Power Supply  | Model: KPS3010D                              | S/N: N/A  |
| 7 | Mobile Comm DC Source                                      | Model: 66321D                                | S/N: MY52000555                                     |

**Table 2-5. Test Support Equipment Used**

|   |  |                    |  |                                 |
|---|--|--------------------|--|---------------------------------|
| FCC ID: BCG-A2095                       | MEASUREMENT REPORT (CERTIFICATION)     |                    |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019 | EUT Type:<br>Watch |  |                                 |

## 2.5 Test Configuration

The EUT was tested per the guidance of ANSI C63.10-2013 and KDB 558074 D01 v05r02. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See Sections 3.2 for AC line conducted emissions test setups, 3.3 for radiated emissions test setups, and 7.2, 7.3, 7.4, 7.5, and 7.6 for antenna port conducted emissions test setups.

The worst case configuration was investigated for various types of wristbands, metal and non-metal wristbands. The store display sample was investigated and determined as not the worst case. The EUT was also investigated with and without wireless charger. The worst case configuration found was used for all testing.

For emissions from 1GHz – 18GHz, low, mid, and high channels were tested with highest power and worst case configuration. The emissions below 1GHz and above 18GHz were tested with the highest transmitting power channel and the worst case configuration.

The EUT was manipulated through three orthogonal planes of X-orientation (flatbed), Y-orientation (landscape), and Z-orientation (portrait) during the testing. Only the worst case emissions were reported in this test report.

For AC line conducted and radiated test below 1GHz, following configuration were investigated and worst case was reported.

- EUT powered by AC/DC adaptor via USB cable with wireless charger
- EUT powered by host PC via USB cable with wireless charger

## 2.6 Software and Firmware

The test was conducted with firmware version wOS 6.0 installed on the EUT.

## 2.7 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

|   |  |                    |                                 |
|---|--|--------------------|---------------------------------|
| FCC ID: BCG-A2095                       | <br><b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                    | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019   | EUT Type:<br>Watch | Page 7 of 62                    |

## 3.0 DESCRIPTION OF TESTS

### 3.1 Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013) and the guidance provided in KDB 558074 D01 v05r02 were used in the measurement of the EUT.

**Deviation from measurement procedure.....**None

### 3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 7m x 3.66m x 2.7m shielded enclosure. The shielded enclosure is manufactured by AP Americas. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50µH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is EPCOS 2X60A Power Line Filter (100dB Attenuation, 14kHz-18GHz) and the two EPCOs 2X48A filters (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 7.10. Automated test software was used to perform the AC line conducted emissions testing. Automated measurement software utilized is Rohde & Schwarz EMC32, Version 10.35.04.

|   |   |                    |                                 |
|---|---|--------------------|---------------------------------|
| FCC ID: BCG-A2095                       |  <b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                    | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019  | EUT Type:<br>Watch | Page 8 of 62                    |

### 3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

Per KDB 414788, radiated emission test sites other than open-field test sites (e.g., shielded anechoic chambers), may be employed for emission measurements below 30MHz if characterized so that the measurements correspond to those obtained at an open-field test site. To determine test site equivalency, a reference sample transmitting at 149kHz was measured on an open field test site (asphalt with no ground plane) and then measured in the 3m semi-anechoic chamber. A calibrated 60cm loop antenna was rotated about its vertical axis while the reference device was rotated through the X, Y and Z axis in order to capture the worst case level. A maximum deviation of 2.77dB at 149kHz was measured when comparing the 3 meter semi-anechoic chamber to the open field site.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33 depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

### 3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

| FCC ID: BCG-A2095                       | PCTEST<br>ENGINEERING LABORATORY, INC. |                    | MEASUREMENT REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
|---|--|--------------------|---------------------------------------|---------------------------------|
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019 | EUT Type:<br>Watch |                                       | Page 9 of 62                    |

## 4.0 ANTENNA REQUIREMENTS

### Excerpt from §15.203 of the FCC Rules/Regulations:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

- The antennas of the EUT are **permanently attached**.
- There are no provisions for connections to an external antenna.

### Conclusion:

The EUT unit complies with the requirement of §15.203.

|   |  |                    |                                 |
|---|--|--------------------|---------------------------------|
| FCC ID: BCG-A2095                       | <br><b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                    | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019   | EUT Type:<br>Watch | Page 10 of 62                   |

## 5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the  $U_{CISPR}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

| Contribution                     | Expanded Uncertainty ( $\pm$ dB) |
|----------------------------------|----------------------------------|
| Conducted Bench Top Measurements | 1.29                             |
| Line Conducted Disturbance       | 2.48                             |
| Radiated Disturbance (<1GHz)     | 4.15                             |
| Radiated Disturbance (>1GHz)     | 4.70                             |
| Radiated Disturbance (>18GHz)    | 5.01                             |

|   |   |                    |                                       |                                 |
|---|---|--------------------|---------------------------------------|---------------------------------|
| FCC ID: BCG-A2095                       |  <b>PCTEST®</b><br><small>ENGINEERING LABORATORY, INC.</small> |                    | MEASUREMENT REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019  | EUT Type:<br>Watch |                                       |                                 |

## 6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

| Manufacturer         | Model       | Description                                    | Cal Date   | Cal Interval | Cal Due    | Serial Number |
|----------------------|-------------|--|------------|--------------|------------|---------------|
| Agilent Technologies | N9030A      | 3Hz-44GHz PXA Signal Analyzer                  | 3/13/2019  | Annual       | 3/13/2020  | MY49430244    |
| Anritsu              | ML2496A     | Power Meter                                    | 10/22/2018 | Annual       | 10/22/2019 | 184005        |
| Anritsu              | MA2411B     | Pulse Power Sensor                             | 10/22/2018 | Annual       | 10/22/2019 | 1726261       |
| Anritsu              | MA2411B     | Pulse Power Sensor                             | 10/22/2018 | Annual       | 10/22/2019 | 1726262       |
| ATM                  | 180-442A-KF | 20dB Nominal Gain Horn Antenna                 | 9/10/2018  | Annual       | 9/10/2019  | T058701-03    |
| COM-POWER            | LIN-120A    | LISN   | 3/13/2019  | Annual       | 3/13/2020  | 241297        |
| ETS-Lindgren         | 118490      | Pre-Amplifier (30MHz - 6GHz)                   | 8/31/2018  | Annual       | 8/31/2019  | 213236        |
| ETS-Lindgren         | 3142E       | BiConiLog Antenna (30MHz - 6GHz)               | 12/11/2018 | Annual       | 12/11/2019 | 224569        |
| Rohde & Schwarz      | ESW26       | EMI Test Receiver                              | 5/21/2019  | Annual       | 5/21/2020  | 101299        |
| Rohde & Schwarz      | ESW44       | EMI Test Receiver                              | 11/20/2018 | Annual       | 11/20/2019 | 101570        |
| Rohde & Schwarz      | TS-PR1840   | Pre-Amplifier (18GHz - 40GHz)                  | 9/5/2018   | Annual       | 9/5/2019   | 100050        |
| Rohde & Schwarz      | TC-TA18     | Cross Polarized Vivaldi Antenna (400MHz-18GHz) | 11/21/2018 | Annual       | 11/21/2019 | 101057        |
| Rohde & Schwarz      | TC-TA18     | Cross Polarized Vivaldi Antenna (400MHz-18GHz) | 12/7/2018  | Annual       | 12/7/2019  | 101063        |
| Rohde & Schwarz      | HFH2-Z2     | Loop Antenna                                   | 3/21/2019  | Annual       | 3/21/2020  | 100519        |

**Table 6-1. Annual Test Equipment Calibration Schedule**

**Note:**

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

|   |  |                    |               |                                 |
|---|--|--------------------|---------------|---------------------------------|
| FCC ID: BCG-A2095                       | MEASUREMENT REPORT<br>(CERTIFICATION)  |                    |               | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019 | EUT Type:<br>Watch | Page 12 of 62 |                                 |

## 7.0 TEST RESULTS

### 7.1 Summary

Company Name: Apple Inc.

FCC ID: BCG-A2095

FCC Classification: Digital Transmission System (DTS)

| FCC Part Section(s) | RSS Section(s) | Test Description  | Test Limit   | Test Condition | Test Result | Reference              |
|---------------------|----------------|---|--|----------------|-------------|------------------------|
| 15.247(a)(2)        | RSS-247 [5.2]  | 6dB Bandwidth   | > 500kHz   | CONDUCTED      | PASS        | Section 7.2            |
| 15.247(b)(3)        | RSS-247 [5.4]  | Transmitter Output Power  | < 1 Watt   |                | PASS        | Sections 7.3           |
| 15.247(e)           | RSS-247 [5.2]  | Transmitter Power Spectral Density  | < 8dBm / 3kHz Band   |                | PASS        | Section 7.4            |
| 15.247(d)           | RSS-247 [5.5]  | Band Edge / Out-of-Band Emissions   | ≥ 20dBc  |                | PASS        | Sections 7.5, 7.6      |
| 15.205<br>15.209    | RSS-Gen [8.9]  | General Field Strength Limits (Restricted Bands and Radiated Emission Limits) | Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-Gen [8.9]) | RADIATED       | PASS        | Sections 7.7, 7.8, 7.9 |
| 15.207              | RSS-Gen [8.8]  | AC Conducted Emissions 150kHz – 30MHz   | < FCC 15.207 limits (RSS-Gen[8.8])   | LINE CONDUCTED | PASS        | Section 7.10           |

**Table 7-1. Summary of Test Results**

**Notes:**

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "WLAN Automation," Version 3.5.
- 5) For radiated band edge, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "Chamber Automation," Version 1.3.1.

|   |  |                    |               |                                 |
|---|--|--------------------|---------------|---------------------------------|
| FCC ID: BCG-A2095                       | <br><b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                    |               | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019   | EUT Type:<br>Watch | Page 13 of 62 |                                 |

## 7.2 6dB Bandwidth Measurement

§15.247(a.2); RSS-247 [5.2]

### Test Overview and Limit

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the transmitter antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated and the worst case configuration results are reported in this section.

***The minimum permissible 6dB bandwidth is 500 kHz.***

### Test Procedure Used

ANSI C63.10-2013 – Section 11.8.2 Option 2  
 KDB 558074 D01 v05r02 – Section 8.2

### Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to X = 6. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 100kHz
3. VBW  $\geq 3 \times$  RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-1. Test Instrument & Measurement Setup**

### Test Notes


None

|   |   |                    |                                       |                                 |
|---|---|--------------------|---------------------------------------|---------------------------------|
| FCC ID: BCG-A2095                       |  <b>PCTEST®</b><br><small>ENGINEERING LABORATORY, INC.</small> |                    | MEASUREMENT REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019  | EUT Type:<br>Watch |                                       | Page 14 of 62                   |


| Frequency [MHz] | Channel No. | 802.11 Mode | Data Rate [Mbps] | Measured Bandwidth [MHz] | Minimum Bandwidth [MHz] |
|-----------------|-------------|-------------|------------------|--------------------------|-------------------------|
| 2412            | 1           | b           | 1                | 9.116                    | 0.500                   |
| 2437            | 6           | b           | 1                | 9.124                    | 0.500                   |
| 2462            | 11          | b           | 1                | 9.102                    | 0.500                   |
| 2412            | 1           | g           | 6                | 18.44                    | 0.500                   |
| 2437            | 6           | g           | 6                | 18.62                    | 0.500                   |
| 2462            | 11          | g           | 6                | 18.61                    | 0.500                   |
| 2412            | 1           | n           | 6.5/7.2 (MCS0)   | 18.63                    | 0.500                   |
| 2437            | 6           | n           | 6.5/7.2 (MCS0)   | 18.63                    | 0.500                   |
| 2462            | 11          | n           | 6.5/7.2 (MCS0)   | 18.59                    | 0.500                   |

**Table 7-2. Conducted Bandwidth Measurements**

|   |   |                    |  |                                 |
|---|---|--------------------|--|---------------------------------|
| FCC ID: BCG-A2095                       |  <b>MEASUREMENT REPORT (CERTIFICATION)</b> |                    |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019  | EUT Type:<br>Watch |  |                                 |





Plot 7-1. 6dB Bandwidth Plot (802.11b – Ch. 1)




Plot 7-2. 6dB Bandwidth Plot (802.11b – Ch. 6)


|   |  |                    |               |                                 |
|---|--|--------------------|---------------|---------------------------------|
| FCC ID: BCG-A2095                       | <br><b>MEASUREMENT REPORT (CERTIFICATION)</b> |                    |               | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019   | EUT Type:<br>Watch | Page 16 of 62 |                                 |


**Plot 7-3. 6dB Bandwidth Plot (802.11b – Ch. 11)**

**Plot 7-4. 6dB Bandwidth Plot (802.11g – Ch. 1)**

|   |   |                    |               |                                 |
|---|---|--------------------|---------------|---------------------------------|
| FCC ID: BCG-A2095                       |  <b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                    |               | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019  | EUT Type:<br>Watch | Page 17 of 62 |                                 |




Plot 7-5. 6dB Bandwidth Plot (802.11g – Ch. 6)




Plot 7-6. 6dB Bandwidth Plot (802.11g – Ch. 11)

|   |   |                    |               |                                 |
|---|---|--------------------|---------------|---------------------------------|
| FCC ID: BCG-A2095                       |  <b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                    |               | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019  | EUT Type:<br>Watch | Page 18 of 62 |                                 |




Plot 7-7. 6dB Bandwidth Plot (802.11n (2.4GHz) – Ch. 1)



Plot 7-8. 6dB Bandwidth Plot (802.11n (2.4GHz) – Ch. 6)

|   |   |                    |               |                                 |
|---|---|--------------------|---------------|---------------------------------|
| FCC ID: BCG-A2095                       |  <b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                    |               | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019  | EUT Type:<br>Watch | Page 19 of 62 |                                 |



Plot 7-9. 6dB Bandwidth Plot (802.11n (2.4GHz) – Ch. 11)

|   |   |                    |                                 |
|---|---|--------------------|---------------------------------|
| FCC ID: BCG-A2095                       |  <b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                    | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019  | EUT Type:<br>Watch | Page 20 of 62                   |

## 7.3 Output Power Measurement

§15.247(b.3); RSS-247 [5.4]

### Test Overview and Limits

A transmitter antenna terminal of EUT is connected to the input of an RF power sensor. Measurement is made using a broadband power meter capable of making peak and average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

***The maximum permissible conducted output power is 1 Watt.***

### Test Procedure Used

ANSI C63.10-2013 – Section 11.9.1.3 PKPM1 Peak Power Method

KDB 558074 D01 v05r02 – Section 8.3.1.3 PKPM1 Peak-reading Power Meter Method

ANSI C63.10-2013 – Section 11.9.2.3.2 Method AVGPM-G

KDB 558074 D01 v05r02 – Section 8.3.2.3 Measurement using a Power Meter (PM)

### Test Settings

#### Method PKPM1 (Peak Power Measurement)

Peak power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The pulse sensor employs a VBW = 50MHz so this method was only used for signals whose DTS bandwidth was less than or equal to 50MHz.

#### Method AVGPM-G (Average Power Measurement)

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

### Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.



**Figure 7-2. Test Instrument & Measurement Setup for Power Meter Measurements**

### Test Notes

None

| FCC ID: BCG-A2095                       | PCTEST<br>Engineering Laboratory, Inc. |                    | MEASUREMENT REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
|---|--|--------------------|---------------------------------------|---------------------------------|
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019 | EUT Type:<br>Watch |                                       | Page 21 of 62                   |

### 7.3.1 Peak Output Power Measurement

§15.247(b.3); RSS-247 [5.4]

| Freq [MHz] | Channel | Detector | IEEE Transmission Mode |         |         | Conducted Power Limit [dBm] | Conducted Power Margin [dB] | Ant. Gain [dBi] | Max e.i.r.p. [dBm] | Max e.i.r.p. Limit [dBm] | e.i.r.p. Margin [dB] |
|------------|---------|----------|------------------------|---------|---------|-----------------------------|-----------------------------|-----------------|--------------------|--------------------------|----------------------|
|            |         |          | 802.11b                | 802.11g | 802.11n |                             |                             |                 |                    |                          |                      |
| 2412       | 1       | PEAK     | 21.33                  | 22.21   | 22.15   | 30.00                       | -7.79                       | -8.90           | 13.31              | 36.02                    | -22.71               |
| 2417       | 2       | PEAK     | 21.41                  | 23.19   | 23.15   | 30.00                       | -6.81                       | -8.90           | 14.29              | 36.02                    | -21.73               |
| 2437       | 6       | PEAK     | 21.37                  | 22.80   | 22.98   | 30.00                       | -7.02                       | -8.90           | 14.08              | 36.02                    | -21.94               |
| 2457       | 10      | PEAK     | 21.17                  | 23.00   | 22.97   | 30.00                       | -7.00                       | -8.90           | 14.10              | 36.02                    | -21.92               |
| 2462       | 11      | PEAK     | 21.09                  | 21.60   | 21.55   | 30.00                       | -8.40                       | -8.90           | 12.70              | 36.02                    | -23.32               |
| 2467       | 12      | PEAK     | 21.19                  | 19.82   | 19.76   | 30.00                       | -8.81                       | -8.90           | 12.29              | 36.02                    | -23.73               |
| 2472       | 13      | PEAK     | 20.40                  | 17.84   | 17.70   | 30.00                       | -9.60                       | -8.90           | 11.50              | 36.02                    | -24.52               |

**Table 7-3. Peak Conducted Output Power Measurements**

|   |  |                    |  |                                 |
|---|--|--------------------|--|---------------------------------|
| FCC ID: BCG-A2095                       | MEASUREMENT REPORT (CERTIFICATION)     |                    |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019 | EUT Type:<br>Watch |  |                                 |

### 7.3.2 Average Output Power Measurement

§15.247(b.3); RSS-247 [5.4]

| Freq [MHz] | Channel | Detector | IEEE Transmission Mode |         |         | Conducted Power Limit [dBm] | Conducted Power Margin [dB] | Ant. Gain [dBi] | Max e.i.r.p. [dBm] | Max e.i.r.p. Limit [dBm] | e.i.r.p. Margin [dB] |
|------------|---------|----------|------------------------|---------|---------|-----------------------------|-----------------------------|-----------------|--------------------|--------------------------|----------------------|
|            |         |          | 802.11b                | 802.11g | 802.11n |                             |                             |                 |                    |                          |                      |
| 2412       | 1       | AVG      | 19.00                  | 17.50   | 17.47   | 30.00                       | -11.00                      | -8.90           | 10.10              | 36.02                    | -25.92               |
| 2417       | 2       | AVG      | 19.00                  | 18.50   | 18.50   | 30.00                       | -11.00                      | -8.90           | 10.10              | 36.02                    | -25.92               |
| 2437       | 6       | AVG      | 19.00                  | 18.36   | 18.50   | 30.00                       | -11.00                      | -8.90           | 10.10              | 36.02                    | -25.92               |
| 2457       | 10      | AVG      | 18.92                  | 18.47   | 18.44   | 30.00                       | -11.08                      | -8.90           | 10.02              | 36.02                    | -26.00               |
| 2462       | 11      | AVG      | 18.83                  | 16.94   | 16.90   | 30.00                       | -11.17                      | -8.90           | 9.93               | 36.02                    | -26.09               |
| 2467       | 12      | AVG      | 18.91                  | 15.00   | 15.00   | 30.00                       | -11.09                      | -8.90           | 10.01              | 36.02                    | -26.01               |
| 2472       | 13      | AVG      | 18.00                  | 7.00    | 7.00    | 30.00                       | -12.00                      | -8.90           | 9.10               | 36.02                    | -26.92               |

Table 7-4. Average Conducted Output Power Measurements

|   |  |                    |  |                                 |
|---|--|--------------------|--|---------------------------------|
| FCC ID: BCG-A2095                       | MEASUREMENT REPORT (CERTIFICATION)     |                    |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019 | EUT Type:<br>Watch |  |                                 |

## 7.4 Power Spectral Density

§15.247(e); RSS-247 [5.2]

### Test Overview and Limit

The peak power density is measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated and the worst case configuration results are reported in this section.

***The maximum permissible power spectral density is 8 dBm in any 3 kHz band.***

### Test Procedure Used

ANSI C63.10-2013 – Section 11.10.2 Method PKPSD

KDB 558074 D01 v05r02 – Section 8.4 DTS Maximum Power Spectral Density level in the fundamental emission

### Test Settings

1. Analyzer was set to the center frequency of the DTS channel under investigation
2. Span = 1.5 times the DTS channel bandwidth
3. RBW = 3kHz
4. VBW = 1MHz
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Trace was allowed to stabilize

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-3. Test Instrument & Measurement Setup**

### Test Notes


Lowest and highest channel that can transmit at maximum power for each mode has been reported.

|   |   |                    |                                 |
|---|---|--------------------|---------------------------------|
| FCC ID: BCG-A2095                       |  <b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                    | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019  | EUT Type:<br>Watch | Page 24 of 62                   |

| Frequency [MHz] | Channel No. | 802.11 Mode | Data Rate [Mbps] | Measured Power Spectral Density [dBm/3KHz] | Maximum Permissible Power Density [dBm / 3kHz] | Margin [dB] | Pass / Fail |
|-----------------|-------------|-------------|------------------|--|--|-------------|-------------|
| 2412            | 1           | b           | 1                | 0.68                                       | 8.00   | -7.32       | Pass        |
| 2437            | 6           | b           | 1                | 0.84                                       | 8.00   | -7.16       | Pass        |
| 2462            | 11          | b           | 1                | -0.17                                      | 8.00   | -8.17       | Pass        |
| 2412            | 1           | g           | 6                | -3.21                                      | 8.00   | -11.21      | Pass        |
| 2437            | 6           | g           | 6                | -2.67                                      | 8.00   | -10.67      | Pass        |
| 2462            | 11          | g           | 6                | -2.55                                      | 8.00   | -10.55      | Pass        |
| 2412            | 1           | n           | 6.5/7.2 (MCS0)   | -3.20                                      | 8.00   | -11.20      | Pass        |
| 2437            | 6           | n           | 6.5/7.2 (MCS0)   | -3.50                                      | 8.00   | -11.50      | Pass        |
| 2462            | 11          | n           | 6.5/7.2 (MCS0)   | -3.69                                      | 8.00   | -11.69      | Pass        |

**Table 7-5. Conducted Power Density Measurements**

**Plot 7-10. Power Spectral Density Plot (802.11b – Ch. 1)**

|   |   |                    |               |                                 |
|---|---|--------------------|---------------|---------------------------------|
| FCC ID: BCG-A2095                       |  <b>MEASUREMENT REPORT (CERTIFICATION)</b> |                    |               | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019  | EUT Type:<br>Watch | Page 25 of 62 |                                 |




Plot 7-11. Power Spectral Density Plot (802.11b – Ch. 6)




Plot 7-12. Power Spectral Density Plot (802.11b – Ch. 11)

|   |   |                    |               |                                 |
|---|---|--------------------|---------------|---------------------------------|
| FCC ID: BCG-A2095                       |  <b>MEASUREMENT REPORT (CERTIFICATION)</b> |                    |               | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019  | EUT Type:<br>Watch | Page 26 of 62 |                                 |




Plot 7-13. Power Spectral Density Plot (802.11g – Ch. 1)




Plot 7-14. Power Spectral Density Plot (802.11g – Ch. 6)

|   |   |                    |  |                                 |
|---|---|--------------------|--|---------------------------------|
| FCC ID: BCG-A2095                       |  <b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                    |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019  | EUT Type:<br>Watch |  | Page 27 of 62                   |




Plot 7-15. Power Spectral Density Plot (802.11g – Ch. 11)




Plot 7-16. Power Spectral Density Plot (802.11n (2.4GHz) – Ch. 1)

|   |   |                    |                                       |                                 |
|---|---|--------------------|---------------------------------------|---------------------------------|
| FCC ID: BCG-A2095                       | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. |                    | MEASUREMENT REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019        | EUT Type:<br>Watch | Page 28 of 62                         |                                 |



Plot 7-17. Power Spectral Density Plot (802.11n (2.4GHz) – Ch. 6)



Plot 7-18. Power Spectral Density Plot (802.11n (2.4GHz) – Ch. 11)

|   |   |                    |  |                                 |
|---|---|--------------------|--|---------------------------------|
| FCC ID: BCG-A2095                       |  <b>MEASUREMENT REPORT (CERTIFICATION)</b> |                    |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019  | EUT Type:<br>Watch |  | Page 29 of 62                   |

## 7.5 Conducted Emissions at the Band Edge

§15.247(d); RSS-247 [5.5]

### Test Overview and Limit

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. For the following out of band conducted spurious emissions plots at the band edge, the EUT was set at a data rate of 1Mbps for "b" mode, 6 Mbps for "g" mode, and 6.5/7.2Mbps for "n" mode as these settings produced the worst-case emissions.

***The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the PSD procedure (Section 7.4).***

### Test Procedure Used

ANSI C63.10-2013 – Section 11.11.3  
 KDB 558074 D01 v05r02 – Section 8.7.2

### Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW = 100kHz
4. VBW = 1MHz
5. Detector = Peak
6. Number of sweep points  $\geq 2 \times \text{Span}/\text{RBW}$
7. Trace mode = max hold
8. Sweep time = auto couple
9. The trace was allowed to stabilize

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-4. Test Instrument & Measurement Setup**


### Test Notes

Lowest and highest channel that can transmit at maximum power for each mode has been reported.

| FCC ID: BCG-A2095                       |  <b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                    | Approved by:<br>Quality Manager |
|---|---|--------------------|---------------------------------|
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019  | EUT Type:<br>Watch | Page 30 of 62                   |




Plot 7-19. Band Edge Plot (802.11b – Ch. 1)



Plot 7-20. Band Edge Plot (802.11b – Ch. 11)

|   |   |                    |  |                                 |
|---|---|--------------------|--|---------------------------------|
| FCC ID: BCG-A2095                       |  <b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                    |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019  | EUT Type:<br>Watch |  | Page 31 of 62                   |




Plot 7-21. Band Edge Plot (802.11b – Ch. 12)




Plot 7-22. Band Edge Plot (802.11b – Ch. 13)

|   |   |                    |                                 |
|---|---|--------------------|---------------------------------|
| FCC ID: BCG-A2095                       |  <b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                    | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019  | EUT Type:<br>Watch | Page 32 of 62                   |



Plot 7-23. Band Edge Plot (802.11g- Ch. 1)



Plot 7-24. Band Edge Plot (802.11g – Ch. 11)

|   |   |                    |  |                                 |
|---|---|--------------------|--|---------------------------------|
| FCC ID: BCG-A2095                       |  <b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                    |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019  | EUT Type:<br>Watch |  | Page 33 of 62                   |




Plot 7-25. Band Edge Plot (802.11g – Ch. 12)




Plot 7-26. Band Edge Plot (802.11g – Ch. 13)

|   |  |                    |                                 |
|---|--|--------------------|---------------------------------|
| FCC ID: BCG-A2095                       |  <b>MEASUREMENT REPORT</b><br>(CERTIFICATION) |                    | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019   | EUT Type:<br>Watch | Page 34 of 62                   |




Plot 7-27. Band Edge Plot (802.11n (2.4GHz) – Ch. 1)



Plot 7-28. Band Edge Plot (802.11n (2.4GHz) – Ch. 11)

|   |   |                    |  |                                 |
|---|---|--------------------|--|---------------------------------|
| FCC ID: BCG-A2095                       |  <b>MEASUREMENT REPORT (CERTIFICATION)</b> |                    |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019  | EUT Type:<br>Watch |  | Page 35 of 62                   |



Plot 7-29. Band Edge Plot (802.11n (2.4GHz) – Ch. 12)



Plot 7-30. Band Edge Plot (802.11n (2.4GHz) – Ch. 13)

|   |   |                                       |                                 |
|---|---|---------------------------------------|---------------------------------|
| FCC ID: BCG-A2095                       |  | MEASUREMENT REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019  | EUT Type:<br>Watch                    | Page 36 of 62                   |

## 7.6 Conducted Spurious Emissions

§15.247(d); RSS-247 [5.5]

### Test Overview and Limit

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. For the following out of band conducted spurious emissions plots, the EUT was investigated in all available data rates for "b", "g", and "n" modes. The worst case spurious emissions for the 2.4GHz band were found while transmitting in "b" mode at 1 Mbps and are shown in the plots below.

***The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the procedure in Section 11.1 of ANSI C63.10-2013 and KDB 558074 D01 v05r02.***

### Test Procedure Used

ANSI C63.10-2013 – Section 11.11.3  
 KDB 558074 D01 v05r02 – Section 8.5

### Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 25GHz (separated into two plots per channel)
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-5. Test Instrument & Measurement Setup**

|   |  |                    |                                       |                                 |
|---|--|--------------------|---------------------------------------|---------------------------------|
| FCC ID: BCG-A2095                       |  <b>PCTEST</b><br><small>ENGINEERING LABORATORY, INC.</small> |                    | MEASUREMENT REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019   | EUT Type:<br>Watch |                                       | Page 37 of 62                   |


## Test Notes

1. RBW was set to 1MHz rather than 100kHz in order to increase the measurement speed.
2. The display line shown in the following plots denotes the limit at 20dB below the fundamental emission level measured in a 100kHz bandwidth. However, since the traces in the following plots are measured with a 1MHz RBW, the display line may not necessarily appear to be 20dB below the level of the fundamental in a 1MHz bandwidth.
3. For plots showing conducted spurious emissions near the limit, the frequencies were investigated with a reduced RBW to ensure that no emissions were present.
4. The unit was tested with all possible modes and only the highest emission is reported.

|   |  |                    |                                 |
|---|--|--------------------|---------------------------------|
| FCC ID: BCG-A2095                       | <br><b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                    | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019   | EUT Type:<br>Watch | Page 38 of 62                   |




Plot 7-31. Conducted Spurious Plot (802.11b – Ch. 1)




Plot 7-32. Conducted Spurious Plot (802.11b – Ch. 1)

|   |   |                    |               |                                 |
|---|---|--------------------|---------------|---------------------------------|
| FCC ID: BCG-A2095                       |  <b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                    |               | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019  | EUT Type:<br>Watch | Page 39 of 62 |                                 |




Plot 7-33. Conducted Spurious Plot (802.11b – Ch. 6)



Plot 7-34. Conducted Spurious Plot (802.11b – Ch. 6)

|   |   |                    |  |                                 |
|---|---|--------------------|--|---------------------------------|
| FCC ID: BCG-A2095                       |  <b>MEASUREMENT REPORT (CERTIFICATION)</b> |                    |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019  | EUT Type:<br>Watch |  | Page 40 of 62                   |



Plot 7-35. Conducted Spurious Plot (802.11b – Ch. 11)



Plot 7-36. Conducted Spurious Plot (802.11b – Ch. 11)

|   |   |                    |  |                                 |
|---|---|--------------------|--|---------------------------------|
| FCC ID: BCG-A2095                       |  <b>MEASUREMENT REPORT (CERTIFICATION)</b> |                    |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019  | EUT Type:<br>Watch |  | Page 41 of 62                   |

## 7.7 Radiated Spurious Emission Measurements – Above 1 GHz

§15.247(d) §15.205 & §15.209; RSS-Gen [8.9]

### Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

***All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 7 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-6 per Section 15.209 and RSS-Gen (8.9).***

| Frequency       | Field Strength<br>[ $\mu$ V/m] | Measured Distance<br>[Meters] |
|-----------------|--------------------------------|-------------------------------|
| Above 960.0 MHz | 500                            | 3                             |

**Table 7-6. Radiated Limits**

### Test Procedures Used

ANSI C63.10-2013 – Section 6.6.4.3

KDB 558074 D01 v05r02 – Sections 8.6, 8.7

### Test Settings

#### Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be  $\geq 2 \times$  span/RBW)
6. Sweep time = auto
7. Trace (RMS) averaging was performed over at least 100 traces


#### Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

|   |   |                    |                                       |                                 |
|---|---|--------------------|---------------------------------------|---------------------------------|
| FCC ID: BCG-A2095                       |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. |                    | MEASUREMENT REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019  | EUT Type:<br>Watch |                                       | Page 42 of 62                   |

## Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-6. Test Instrument & Measurement Setup**

## Test Notes

1. The optional test procedures for antenna port conducted measurements of unwanted emissions per the guidance of KDB 558074 D01 v05r02 were not used to evaluate this device for compliance to radiated limits. All radiated spurious emissions levels were measured in a radiated test setup.
2. All emissions lying in restricted bands specified in Section 15.205 and Section 8.10 of RSS-Gen are below the limit shown in Table 7-6.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery.
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
6. Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
7. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section.
8. The "-" shown in the following RSE tables are used to denote a noise floor measurement.
9. The unit was tested with all possible modes and only the highest emission is reported.

| FCC ID: BCG-A2095                       |  <b>PCTEST®</b><br>ENGINEERING LABORATORY, INC. |                    | MEASUREMENT REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
|---|--|--------------------|---------------------------------------|---------------------------------|
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019   | EUT Type:<br>Watch | Page 43 of 62                         |                                 |

## Sample Calculations

### Determining Spurious Emissions Levels

- Field Strength Level [ $\text{dB}_{\mu\text{V/m}}$ ] = Analyzer Level [ $\text{dBm}$ ] + 107 + AFCL [ $\text{dB/m}$ ]
- AFCL [ $\text{dB/m}$ ] = Antenna Factor [ $\text{dB/m}$ ] + Cable Loss [ $\text{dB}$ ]
- Margin [ $\text{dB}$ ] = Field Strength Level [ $\text{dB}_{\mu\text{V/m}}$ ] – Limit [ $\text{dB}_{\mu\text{V/m}}$ ]


### Radiated Band Edge Measurement Offset

- The amplitude offset shown in the radiated restricted band edge plots in Section 7.7 was calculated using the formula:  
Offset (dB) = (Antenna Factor + Cable Loss + Attenuator) – Preamplifier Gain


|   |  |                    |                                 |
|---|--|--------------------|---------------------------------|
| FCC ID: BCG-A2095                       | <br><b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                    | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019   | EUT Type:<br>Watch | Page 44 of 62                   |

## Radiated Spurious Emission Measurements


§15.247(d) §15.205 & §15.209; RSS-Gen [8.9]



Plot 7-37. Radiated Spurious Plot above 1GHz (802.11b – Ch. 1)



Plot 7-38. Radiated Spurious Plot above 1GHz (802.11b – Ch. 6)




Plot 7-39. Radiated Spurious Plot above 1GHz (802.11b – Ch. 11)


|   |  |                    |  |                                 |
|---|--|--------------------|--|---------------------------------|
| FCC ID: BCG-A2095                       | <br><b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                    |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019   | EUT Type:<br>Watch |  | Page 45 of 62                   |

## Radiated Spurious Emissions Measurements (Above 18GHz)

§15.209; RSS-Gen [8.9]



Plot 7-40. Radiated Spurious Plot above 18GHz (802.11b – Ch. 6, Ant. Pol. H)



Plot 7-41. Radiated Spurious Plot above 18GHz (802.11b – Ch. 6, Ant. Pol. V)

|   |   |                    |                                 |
|---|---|--------------------|---------------------------------|
| FCC ID: BCG-A2095                       |  <b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                    | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019  | EUT Type:<br>Watch | Page 46 of 62                   |

## Radiated Spurious Emission Measurements

§15.247(d) §15.205 & §15.209; RSS-Gen [8.9]

Worst Case Mode: 802.11b  
 Worst Case Transfer Rate: 1 Mbps  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2412MHz  
 Channel: 01

| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dB $\mu$ V/m] | Limit [dB $\mu$ V/m] | Margin [dB] |
|-----------------|----------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------------|----------------------|-------------|
| 4824.00         | Avg      | H               | -                   | -                          | -79.20               | 5.64        | 33.44                         | 53.98                | -20.54      |
| 4824.00         | Peak     | H               | -                   | -                          | -67.09               | 5.64        | 45.55                         | 73.98                | -28.43      |
| 12060.00        | Avg      | H               | -                   | -                          | -82.52               | 15.28       | 39.76                         | 53.98                | -14.22      |
| 12060.00        | Peak     | H               | -                   | -                          | -71.07               | 15.28       | 51.21                         | 73.98                | -22.77      |

**Table 7-7. Radiated Measurements**

Worst Case Mode: 802.11b  
 Worst Case Transfer Rate: 1 Mbps  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2437MHz  
 Channel: 06

| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dB $\mu$ V/m] | Limit [dB $\mu$ V/m] | Margin [dB] |
|-----------------|----------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------------|----------------------|-------------|
| 4874.00         | Avg      | H               | -                   | -                          | -78.96               | 5.72        | 33.76                         | 53.98                | -20.22      |
| 4874.00         | Peak     | H               | -                   | -                          | -67.01               | 5.72        | 45.71                         | 73.98                | -28.27      |
| 7311.00         | Avg      | H               | 285                 | 16                         | -78.25               | 8.58        | 37.33                         | 53.98                | -16.65      |
| 7311.00         | Peak     | H               | 285                 | 16                         | -67.85               | 8.58        | 47.73                         | 73.98                | -26.25      |
| 12185.00        | Avg      | H               | -                   | -                          | -82.04               | 15.15       | 40.11                         | 53.98                | -13.87      |
| 12185.00        | Peak     | H               | -                   | -                          | -70.72               | 15.15       | 51.43                         | 73.98                | -22.55      |

**Table 7-8. Radiated Measurements**

|  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|
| FCC ID: BCG-A2095                                      |  <b>PCTEST</b><br><small>ENGINEERING LABORATORY, INC.</small> | MEASUREMENT REPORT<br><small>(CERTIFICATION)</small> |  |  |  | Approved by:<br><small>Quality Manager</small> |
| Test Report S/N:<br><small>1C1905130010-05.BCG</small> | Test Dates:<br><small>05/01/2019 - 07/24/2019</small>  | EUT Type:<br><small>Watch</small>                    |  |  |  |  |

Worst Case Mode: 802.11b  
 Worst Case Transfer Rate: 1 Mbps  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2462MHz  
 Channel: 11

| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dB $\mu$ V/m] | Limit [dB $\mu$ V/m] | Margin [dB] |
|-----------------|----------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------------|----------------------|-------------|
| 4924.00         | Avg      | H               | -                   | -                          | -79.00               | 5.71        | 33.71                         | 53.98                | -20.27      |
| 4924.00         | Peak     | H               | -                   | -                          | -68.09               | 5.71        | 44.62                         | 73.98                | -29.36      |
| 7386.00         | Avg      | H               | -                   | -                          | -79.58               | 8.67        | 36.09                         | 53.98                | -17.89      |
| 7386.00         | Peak     | H               | -                   | -                          | -68.01               | 8.67        | 47.66                         | 73.98                | -26.32      |
| 12310.00        | Avg      | H               | -                   | -                          | -82.37               | 15.62       | 40.25                         | 53.98                | -13.73      |
| 12310.00        | Peak     | H               | -                   | -                          | -71.18               | 15.62       | 51.44                         | 73.98                | -22.54      |

**Table 7-9. Radiated Measurements**


|   |   |                    |               |                                 |
|---|---|--------------------|---------------|---------------------------------|
| FCC ID: BCG-A2095                       |  <b>MEASUREMENT REPORT (CERTIFICATION)</b> |                    |               | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019  | EUT Type:<br>Watch | Page 48 of 62 |                                 |

## 7.8 Radiated Restricted Band Edge Measurements

### §15.205 §15.209; RSS-Gen [8.9]

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting.

Worst Case Mode: 802.11b  
 Worst Case Transfer Rate: 1Mbps  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2412MHz  
 Channel: 1



**Plot 7-42. Radiated Restricted Lower Band Edge Measurement**


|   |   |                    |  |                                 |
|---|---|--------------------|--|---------------------------------|
| FCC ID: BCG-A2095                       |  <b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                    |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019  | EUT Type:<br>Watch |  | Page 49 of 62                   |

Worst Case Mode: 802.11b  
 Worst Case Transfer Rate: 1Mbps  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2467MHz  
 Channel: 12

**PASS**

Average Trace      RBW: 1 MHz  
 Peak Trace      VBW: 3 MHz  
 Avg. Offset: 11.2dB      SWT: 1.01ms  
 Peak Offset: 11.2dB

Peak: 2484.94 MHz, 54.06 dB $\mu$ V/m  
 Avg: 2483.99 MHz, 42.98 dB $\mu$ V/m




**Plot 7-43. Radiated Restricted Upper Band Edge Measurement**

Worst Case Mode: 802.11b  
 Worst Case Transfer Rate: 1Mbps  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2472MHz  
 Channel: 13

**PASS**

Average Trace      RBW: 1 MHz  
 Peak Trace      VBW: 3 MHz  
 Avg. Offset: 11.2dB      SWT: 1.01ms  
 Peak Offset: 11.2dB

Peak: 2484.19 MHz, 54.41 dB $\mu$ V/m  
 Avg: 2485.04 MHz, 44.38 dB $\mu$ V/m



**Plot 7-44. Radiated Restricted Upper Band Edge Measurement**


|   |  |                    |  |                                 |
|---|--|--------------------|--|---------------------------------|
| FCC ID: BCG-A2095                       | <br><b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                    |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019   | EUT Type:<br>Watch |  | Page 50 of 62                   |

Worst Case Mode: 802.11n  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2412MHz  
 Channel: 1

**PASS**

Average Trace RBW: 1 MHz  
Peak Trace VBW: 3 MHz  
 Avg. Offset: 12.1dB SWT: 1.01ms  
 Peak Offset: 12.1dB

Peak: 2389.66 MHz, 66.10 dB $\mu$ V/m  
 Avg: 2389.90 MHz, 50.89 dB $\mu$ V/m




**Plot 7-45. Radiated Restricted Lower Band Edge Measurement**

Worst Case Mode: 802.11n  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2417MHz  
 Channel: 2

**PASS**

Average Trace RBW: 1 MHz  
Peak Trace VBW: 3 MHz  
 Avg. Offset: 12.1dB SWT: 1.01ms  
 Peak Offset: 12.1dB

Peak: 2389.54 MHz, 65.17 dB $\mu$ V/m  
 Avg: 2389.90 MHz, 47.57 dB $\mu$ V/m




**Plot 7-46. Radiated Restricted Lower Band Edge Measurement**

|   |  |                    |                                 |
|---|--|--------------------|---------------------------------|
| FCC ID: BCG-A2095                       | <br><b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                    | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019   | EUT Type:<br>Watch | Page 51 of 62                   |

Worst Case Mode: 802.11n  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2457MHz  
 Channel: 10

**PASS**

Average Trace      RBW: 1 MHz  
 Peak Trace      VBW: 3 MHz  
 Avg. Offset: 11.2dB      SWT: 1.01ms  
 Peak Offset: 11.2dB      Peak: 2486.04 MHz, 58.18 dB $\mu$ V/m  
 Avg: 2487.59 MHz, 46.45 dB $\mu$ V/m




**Plot 7-47. Radiated Restricted Upper Band Edge Measurement**

Worst Case Mode: 802.11n  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2462MHz  
 Channel: 11

**PASS**

Average Trace      RBW: 1 MHz  
 Peak Trace      VBW: 3 MHz  
 Avg. Offset: 12.5dB      SWT: 1.01ms  
 Peak Offset: 12.5dB      Peak: 2484.89 MHz, 61.15 dB $\mu$ V/m  
 Avg: 2483.79 MHz, 46.86 dB $\mu$ V/m




**Plot 7-48. Radiated Restricted Upper Band Edge Measurement**

|   |  |                    |  |                                 |
|---|--|--------------------|--|---------------------------------|
| FCC ID: BCG-A2095                       | <br><b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                    |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019   | EUT Type:<br>Watch |  | Page 52 of 62                   |

Worst Case Mode: 802.11n  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2467MHz  
 Channel: 12

**PASS**

Average Trace      RBW: 1 MHz  
 Peak Trace      VBW: 3 MHz  
 Avg. Offset: 11.2dB      SWT: 1.01ms  
 Peak Offset: 11.2dB      Peak: 2483.59 MHz, 62.88 dB $\mu$ V/m  
 Avg: 2483.74 MHz, 43.58 dB $\mu$ V/m




**Plot 7-49. Radiated Restricted Upper Band Edge Measurement**

Worst Case Mode: 802.11n  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2472MHz  
 Channel: 13

**PASS**

Average Trace      RBW: 1 MHz  
 Peak Trace      VBW: 3 MHz  
 Avg. Offset: 11.2dB      SWT: 1.01ms  
 Peak Offset: 11.2dB      Peak: 2483.74 MHz, 64.85 dB $\mu$ V/m  
 Avg: 2483.54 MHz, 46.47 dB $\mu$ V/m



**Plot 7-50. Radiated Restricted Upper Band Edge Measurement**

|   |  |                    |                                 |
|---|--|--------------------|---------------------------------|
| FCC ID: BCG-A2095                       | <br><b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                    | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019   | EUT Type:<br>Watch | Page 53 of 62                   |

## 7.9 Radiated Spurious Emissions Measurements – Below 1GHz

§15.209; RSS-Gen [8.9]

### Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

***All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 7 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-10 per Section 15.209 and RSS-Gen (8.9).***

| Frequency         | Field Strength<br>[ $\mu$ V/m] | Measured Distance<br>[Meters] |
|-------------------|--------------------------------|-------------------------------|
| 0.009 – 0.490 MHz | 2400/F (kHz)                   | 300                           |
| 0.490 – 1.705 MHz | 24000/F (kHz)                  | 30                            |
| 1.705 – 30.00 MHz | 30                             | 30                            |
| 30.00 – 88.00 MHz | 100                            | 3                             |
| 88.00 – 216.0 MHz | 150                            | 3                             |
| 216.0 – 960.0 MHz | 200                            | 3                             |
| Above 960.0 MHz   | 500                            | 3                             |

**Table 7-10. Radiated Limits**

### Test Procedures Used

ANSI C63.10-2013

### Test Settings

#### Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize


#### Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. VBW = 300kHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize


|   |  |                    |                                       |                                 |
|---|--|--------------------|---------------------------------------|---------------------------------|
| FCC ID: BCG-A2095                       |  <b>PCTEST®</b><br>ENGINEERING LABORATORY, INC. |                    | MEASUREMENT REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019   | EUT Type:<br>Watch |                                       | Page 54 of 62                   |

## Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.



**Figure 7-7. Radiated Test Setup < 30Mhz**



**Figure 7-8. Radiated Test Setup < 1GHz**

|   |   |                    |                                 |
|---|---|--------------------|---------------------------------|
| FCC ID: BCG-A2095                       |  <b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                    | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019  | EUT Type:<br>Watch | Page 55 of 62                   |


## Test Notes

1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen(8.10) are below the limit shown in Table 7-10.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector on emissions within 6dB of the limit. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. There were no emissions detected in the 30MHz – 1GHz frequency range, as shown in the subsequent plots.
10. The unit was tested with all possible modes and only the highest emission is reported.

|   |   |                    |                                       |                                 |
|---|---|--------------------|---------------------------------------|---------------------------------|
| FCC ID: BCG-A2095                       |  <b>PCTEST®</b><br><small>ENGINEERING LABORATORY, INC.</small> |                    | MEASUREMENT REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019  | EUT Type:<br>Watch |                                       | Page 56 of 62                   |

## Radiated Spurious Emissions Measurements (Below 1GHz)

§15.209; RSS-Gen [8.9]



**Plot 7-51. Radiated Spurious Plot Below 1GHz (802.11b – Ch.6, with WCP + AC/DC Adapter)**

| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dBμV/m] | Limit [dBμV/m] | Margin [dB] |
|-----------------|----------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------|----------------|-------------|
| 30.29           | Max-Peak | V               | 100                 | 9                          | -72.38               | -9.55       | 25.07                   | 40.00          | -14.93      |
| 32.33           | Max-Peak | V               | 100                 | 247                        | -73.05               | -10.64      | 23.31                   | 40.00          | -16.69      |
| 35.00           | Max-Peak | V               | 100                 | 285                        | -72.65               | -11.80      | 22.55                   | 40.00          | -17.45      |
| 954.65          | Max-Peak | V               | 250                 | 15                         | -79.06               | -3.70       | 24.24                   | 46.02          | -21.78      |
| 978.71          | Max-Peak | V               | 250                 | 12                         | -79.79               | -3.38       | 23.83                   | 53.98          | -30.15      |
| 994.03          | Max-Peak | V               | 250                 | 58                         | -79.42               | -3.06       | 24.52                   | 53.98          | -29.46      |

**Table 7-11. Radiated Spurious Emissions Below 1GHz (802.11b – Ch.6, with WCP + AC/DC Adapter)**

|   |   |                    |  |                                 |
|---|---|--------------------|--|---------------------------------|
| FCC ID: BCG-A2095                       |  <b>MEASUREMENT REPORT (CERTIFICATION)</b> |                    |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019  | EUT Type:<br>Watch |  |                                 |

## 7.10 AC Line-Conducted Test Data

§15.207; RSS-Gen [8.8]

### Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

***All conducted emissions must not exceed the limits shown in the table below, per Section 15.207 and RSS-Gen (8.8).***

| Frequency of emission<br>(MHz) | Conducted Limit (dB $\mu$ V) |           |
|--------------------------------|------------------------------|-----------|
|                                | Quasi-peak                   | Average   |
| 0.15 – 0.5                     | 66 to 56*                    | 56 to 46* |
| 0.5 – 5                        | 56                           | 46        |
| 5 – 30                         | 60                           | 50        |

**Table 7-12. Conducted Limits**

\*Decreases with the logarithm of the frequency.

### Test Procedures Used

ANSI C63.10-2013, Section 6.2

### Test Settings

#### Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize


#### Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

|   |  |                    |                                       |                                 |
|---|--|--------------------|---------------------------------------|---------------------------------|
| FCC ID: BCG-A2095                       |  <b>PCTEST</b><br><small>ENGINEERING LABORATORY, INC.</small> |                    | MEASUREMENT REPORT<br>(CERTIFICATION) | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019   | EUT Type:<br>Watch |                                       | Page 58 of 62                   |

## Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-9. Test Instrument & Measurement Setup**

## Test Notes

1. All modes of operation were investigated and the worst-case emissions are reported. The emissions found were not affected by the choice of channel used during testing.
2. The limit for an intentional radiator from 150kHz to 30MHz are specified in Part 15.207 and RSS-Gen(8.8).
3. Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
4. QP/AV Level (dB $\mu$ V) = QP/AV Analyzer/Receiver Level (dB $\mu$ V) + Corr. (dB)
5. Margin (dB) = QP/AV Limit (dB $\mu$ V) - QP/AV Level (dB $\mu$ V)
6. Traces shown in plot are made using Quasi-peak and Average detectors.
7. Deviations to the Specifications: None.

|   |   |                    |                                 |
|---|---|--------------------|---------------------------------|
| FCC ID: BCG-A2095                       |  <b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                    | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019  | EUT Type:<br>Watch | Page 59 of 62                   |




**Plot 7-52. Line Conducted Plot with 802.11b Ch.6 (L1, with WCP + AC/DC Adapter)**

| Frequency [MHz] | Process State | QuasiPeak [dBμV] | Average [dBμV] | Limit [dBμV] | Margin [dB] | Line | PE  |
|-----------------|---------------|------------------|----------------|--------------|-------------|------|-----|
| 0.168           | FINAL         | —                | 35.69          | 55.06        | -19.37      | L1   | GND |
| 0.168           | FINAL         | 49.8             | —              | 65.06        | -15.23      | L1   | GND |
| 0.251           | FINAL         | —                | 26.07          | 51.72        | -25.65      | L1   | GND |
| 0.251           | FINAL         | 41.6             | —              | 61.72        | -20.13      | L1   | GND |
| 0.499           | FINAL         | 37.0             | —              | 56.02        | -18.99      | L1   | GND |
| 0.503           | FINAL         | —                | 22.99          | 46.00        | -23.01      | L1   | GND |
| 0.582           | FINAL         | 40.1             | —              | 56.00        | -15.91      | L1   | GND |
| 0.582           | FINAL         | —                | 24.48          | 46.00        | -21.52      | L1   | GND |
| 0.665           | FINAL         | —                | 23.79          | 46.00        | -22.21      | L1   | GND |
| 0.677           | FINAL         | 39.1             | —              | 56.00        | -16.90      | L1   | GND |
| 0.814           | FINAL         | 40.6             | —              | 56.00        | -15.37      | L1   | GND |
| 0.830           | FINAL         | —                | 26.58          | 46.00        | -19.42      | L1   | GND |

**Table 7-13. Line Conducted Data with 802.11b Ch.6 (L1, with WCP + AC/DC Adapter)**

|   |  |                    |  |                                 |
|---|--|--------------------|--|---------------------------------|
| FCC ID: BCG-A2095                       | MEASUREMENT REPORT (CERTIFICATION)     |                    |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019 | EUT Type:<br>Watch |  | Page 60 of 62                   |



**Plot 7-53. Line Conducted Plot with 802.11b Ch.6 (N, with WCP + AC/DC Adapter)**

| Frequency [MHz] | Process State | QuasiPeak [dBμV] | Average [dBμV] | Limit [dBμV] | Margin [dB] | Line | PE  |
|-----------------|---------------|------------------|----------------|--------------|-------------|------|-----|
| 0.166           | FINAL         | —                | 34.33          | 55.17        | -20.84      | N    | GND |
| 0.166           | FINAL         | 48.4             | —              | 65.17        | -16.74      | N    | GND |
| 0.247           | FINAL         | 42.2             | —              | 61.87        | -19.72      | N    | GND |
| 0.249           | FINAL         | —                | 27.69          | 51.79        | -24.10      | N    | GND |
| 0.494           | FINAL         | —                | 23.48          | 46.10        | -22.62      | N    | GND |
| 0.501           | FINAL         | 36.8             | —              | 56.00        | -19.22      | N    | GND |
| 0.575           | FINAL         | 39.7             | —              | 56.00        | -16.35      | N    | GND |
| 0.587           | FINAL         | —                | 23.89          | 46.00        | -22.11      | N    | GND |
| 0.661           | FINAL         | —                | 22.93          | 46.00        | -23.07      | N    | GND |
| 0.670           | FINAL         | 38.6             | —              | 56.00        | -17.45      | N    | GND |
| 0.821           | FINAL         | 39.7             | —              | 56.00        | -16.29      | N    | GND |
| 0.827           | FINAL         | —                | 25.79          | 46.00        | -20.21      | N    | GND |

**Table 7-14. Line Conducted Data with 802.11b Ch.6 (N, with WCP + AC/DC Adapter)**

|   |  |                    |  |                                 |
|---|--|--------------------|--|---------------------------------|
| FCC ID: BCG-A2095                       | MEASUREMENT REPORT (CERTIFICATION)     |                    |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019 | EUT Type:<br>Watch |  |                                 |

## 8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Apple Watch**

**FCC ID: BCG-A2095** is in compliance with Part 15 Subpart C (15.247) of the FCC Rules and RSS-247 of the Innovation, Science and Economic Development Canada Rules.

|   |  |                    |                                 |
|---|--|--------------------|---------------------------------|
| FCC ID: BCG-A2095                       | <br><b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                    | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1C1905130010-05.BCG | Test Dates:<br>05/01/2019 - 07/24/2019   | EUT Type:<br>Watch | Page 62 of 62                   |