

MEASUREMENT REPORT

FCC PART 15.247 / ISSED RSS-247 WLAN 802.11b/g/n

Applicant Name:

Apple Inc.
One Apple Park Way
Cupertino, CA 95014
United States

Date of Testing:

06/12/2020 - 08/21/2020

Test Site/Location:

PCTEST Lab. Morgan Hill, CA, USA

Test Report Serial No.:

1C2004270017-05.BCG

FCC ID:

BCG-A2293

IC:

579C-A2293

APPLICANT:

Apple Inc.

Application Type:

Certification

Model/HVIN:

A2293

EUT Type:

Watch

Frequency Range:

2412 – 2472MHz

FCC Classification:

Digital Transmission System (DTS)

FCC Rule Part(s):

Part 15 Subpart C (15.247)

ISED Specification:

RSS-247 Issue 2

Test Procedure(s):

ANSI C63.10-2013, KDB 558074 D01 v05r02

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013 and KDB 558074 D01 v05r02. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Randy Ortanez
President

FCC ID: BCG-A2293	 MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch
Page 1 of 72		


TABLE OF CONTENTS

1.0	INTRODUCTION.....	4
1.1	Scope	4
1.2	PCTEST Test Location.....	4
1.3	Test Facility / Accreditations.....	4
2.0	PRODUCT INFORMATION	5
2.1	Equipment Description	5
2.2	Device Capabilities	5
2.3	Antenna Description	6
2.4	Test Support Equipment.....	7
2.5	Test Configuration	8
2.6	Software and Firmware	8
2.7	EMI Suppression Device(s)/Modifications	8
3.0	DESCRIPTION OF TESTS	9
3.1	Evaluation Procedure	9
3.2	AC Line Conducted Emissions	9
3.3	Radiated Emissions.....	10
3.4	Environmental Conditions.....	10
4.0	ANTENNA REQUIREMENTS	11
5.0	MEASUREMENT UNCERTAINTY.....	12
6.0	TEST EQUIPMENT CALIBRATION DATA.....	13
7.0	TEST RESULTS.....	14
7.1	Summary	14
7.2	6dB Bandwidth Measurement	15
7.3	Output Power Measurement.....	22
7.3.1	Peak Output Power Measurement	23
7.3.2	Average Output Power Measurements	24
7.4	Power Spectral Density	25
7.5	Conducted Authorized Band Edge	32
7.6	Conducted Spurious Emissions.....	43
7.7	Radiated Spurious Emissions – Above 1 GHz	48
7.7.1	Radiated Spurious Emissions – Above 1GHz	51
7.7.2	Simultaneous Tx Radiated Spurious Emissions – Above 1GHz	55
7.8	Radiated Restricted Band Edge Measurements.....	57
7.9	Radiated Spurious Emissions – Below 1GHz.....	63
7.9.1	Radiated Spurious Emissions – Below 1GHz.....	66
7.9.2	Simultaneous Tx Radiated Spurious Emissions – Below 1GHz.....	67
7.10	AC Line-Conducted Emission Measurements	68
8.0	CONCLUSION	72

FCC ID: BCG-A2293	 MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch
		Page 2 of 72



MEASUREMENT REPORT



Mode	Tx Frequency (MHz)	Avg Conducted		Peak Conducted	
		Max. Power (mW)	Max. Power (dBm)	Max. Power (mW)	Max. Power (dBm)
802.11b	2412 - 2472	79.433	19.00	140.281	21.47
802.11g	2412 - 2472	70.795	18.50	199.067	22.99
802.11n	2412 - 2472	70.795	18.50	213.304	23.29

EUT Overview

FCC ID: BCG-A2293	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 3 of 72

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST facility located at 18855 Adams Court, Morgan Hill, CA 95037. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014 and KDB 414788 D01 v01r01.

1.3 Test Facility / Accreditations

Measurements were performed at PCTEST located in Morgan Hill, CA 95037, U.S.A.

- PCTEST is an ISO 17025-2005 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.02 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISSED Standards (RSS).
- PCTEST facility is a registered (22831) test laboratory with the site description on file with ISSED.

FCC ID: BCG-A2293	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 4 of 72

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Apple Watch FCC ID: BCG-A2293**. The test data contained in this report pertains only to the emissions due to the EUT's WLAN (DTS) transmitter.

Test Device Serial No.: GY6CN013Q60T, FN60018410NUMLH946

2.2 Device Capabilities

This device contains the following capabilities:

850/1700/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n WLAN, 802.11a/n UNII, Bluetooth (1x, EDR, HDR4, HDR8, LE), NFC, UWB

Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	12	2467
6	2437	13	2472
7	2442		

Table 2-1. WLAN Frequency/ Channel Operations

- The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = peak per the guidance of Section 6.0 b) of KDB 558074 D01 v05r02 and ANSIC63.10-2013. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Measured Duty Cycles		
802.11 Mode/Band	Duty Cycle (%)	
2.4 GHz	b	100.0
	g	98.6
	n (MCS0)	98.3
	n (MCS7)	86.2

Table 2-2. Measured Duty Cycles

- Data Rates Supported: 1Mbps, 2Mbps, 5.5Mbps, 11Mbps (b)
6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps (g)
6.5/7.2Mbps, 13/14.4Mbps, 19.5/21.7Mbps, 26/28.9Mbps, 39/43.3Mbps,
52/57.8Mbps, 58.5/65Mbps, 65/72.2Mbps (n)

FCC ID: BCG-A2293	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 5 of 72

3. This device supports simultaneous multi radio transmission feature, which allows multiple radios to transmit simultaneously at the same antenna. The table below shows all the possible multi radio TX combinations:

Simultaneous Tx Config	Antenna FCM				
	WLAN	Bluetooth	LTE/WCDMA	UNII	UWB
	802.11 b/g/n	BDR, EDR, HDR4/8, LE	Mid band/ High band	802.11 a/n	Ch.5, Ch.9
Config 1	✓	✗	✗	✗	✓
Config 2	✗	✓	✗	✗	✓
Config 3	✗	✗	✓	✗	✓
Config 4	✗	✓	✓	✗	✗
Config 5	✓	✗	✓	✗	✗
Config 6	✗	✗	✓	✓	✗
Config 7	✗	✓	✗	✓	✗
Config 8	✓	✗	✓	✗	✓
Config 9	✗	✓	✓	✗	✓
Config 10	✗	✓	✓	✓	✗

Table 2-3. Simultaneous Transmission Configurations

✓ = Support; ✗ = NOT Support

2.3 Antenna Description

Following antenna was used for the testing.

Frequency [GHz]	Antenna Gain [dBi]
2.4	-11.10

Table 2-4. Highest Antenna Gain

FCC ID: BCG-A2293	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 6 of 72

2.4 Test Support Equipment

1	Apple MacBook	Model:	A1398	S/N:	C02QT94WG8WP
	w/AC/DC Adapter	Model:	A1435	S/N:	N/A
2	Apple USB Cable	Model:	Kanzi	S/N:	325316
	w/ Charging Dock	Model:	FAPS73	S/N:	17481001022
	w/ Dock	Model:	X241	S/N:	GW17F01ST22
3	USB Lightning Cable	Model:	N/A	S/N:	N/A
	w/ AC Adapter	Model:	A1385	S/N:	N/A
4	Wireless Charging Pad (WCP)	Model:	EVT	S/N:	DLC9223004YLNWL43
	Wireless Charging Pad (WCP)	Model:	EVT	S/N:	DLC9104001JLNWK18
5	Test Pathfinder CANMORE Board	Model:	X1658	S/N:	920-08295-03
	w/ Test Socket BANKSY	Model:	EVT X1658	S/N:	920-08658-03
6	DC Power Supply	Model:	KPS3010D	S/N:	N/A

Table 2-5. Test Support Equipment List

FCC ID: BCG-A2293	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 7 of 72

2.5 Test Configuration

The EUT was tested per the guidance of ANSI C63.10-2013 and KDB 558074 D01 v05r02r02. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See Sections 3.2 for AC line conducted emissions test setups, 3.3 for radiated emissions test setups, and 7.2, 7.3, 7.4, 7.5, and 7.6 for antenna port conducted emissions test setups.

The worst case configuration was investigated for all combinations of the three materials, aluminum, stainless steel, and titanium and various types of wristbands, metal and non-metal wristbands. The store display sample was investigated and determined as not the worst case. The EUT was also investigated with and without wireless charger. The worst case configuration found was used for all testing.

For emissions from 1GHz – 18GHz, low, mid, and high channels were tested with highest power and worst case configuration. The emissions below 1GHz and above 18GHz were tested with the highest transmitting power and the worst case channel.

The EUT was manipulated through three orthogonal planes of X-orientation (flatbed), Y-orientation (landscape), and Z-orientation (portrait) during the testing. Only the worst case emissions were reported in this test report.

For AC line conducted emissions and radiated emissions below 1GHz, the following configurations were investigated and worst case was reported.

- EUT powered by AC/DC adapter via USB cable with wireless charger
- EUT powered by host PC via USB cable with wireless charger

Higher and lower data rates were investigated for different test cases and the worst case data is reported in section 7.0.

All possible Simultaneous Transmission configurations have been investigated and the worst case config has been reported.

Description	WLAN	LTE (Band 41)	UWB
Antenna	FCM	FCM	FCM
Channel	6	39750	5
Operating Frequency (MHz)	2437	2506	6500
Mode/Modulation	802.11 b	QPSK/1RB/20MHz	Config3/Payload 125

Table 2-6. Worst Case Simultaneous Transmission Configuration

2.6 Software and Firmware

The test was conducted with firmware version wOS 7.0. installed on the EUT.

2.7 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

FCC ID: BCG-A2293	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 8 of 72

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013) and the guidance provided in KDB 558074 D01 v05r02 were used in the measurement of the EUT.

Deviation from measurement procedure.....None

3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 7m x 3.66m x 2.7m shielded enclosure. The shielded enclosure is manufactured by AP Americas. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is EPCOS 2X60A Power Line Filter (100dB Attenuation, 14kHz-18GHz) and the two EPCOS 2X48A filters (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 7.10. Automated test software was used to perform the AC line conducted emissions testing. Automated measurement software utilized is Rohde & Schwarz EMC32, Version 10.50.40.

FCC ID: BCG-A2293		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 9 of 72

3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

Per KDB 414788, radiated emission test sites other than open-field test sites (e.g., shielded anechoic chambers), may be employed for emission measurements below 30MHz if characterized so that the measurements correspond to those obtained at an open-field test site. To determine test site equivalency, a reference sample transmitting at 149kHz was measured on an open field test site (asphalt with no ground plane) and then measured in the 3m semi-anechoic chamber. A calibrated 60cm loop antenna was rotated about its vertical axis while the reference device was rotated through the X, Y and Z axis in order to capture the worst case level. A maximum deviation of 2.77dB at 149kHz was measured when comparing the 3 meter semi-anechoic chamber to the open field site.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33 depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: BCG-A2293	 PCTEST® Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 10 of 72

4.0 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antennas of the EUT are **permanently attached**.
- There are no provisions for connections to an external antenna.

Conclusion:

The EUT unit complies with the requirement of §15.203.

FCC ID: BCG-A2293	 PCTEST Proud to be part of  element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 11 of 72

5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ($\pm$ dB)
Conducted Bench Top Measurements	1.30
Line Conducted Disturbance	2.34
Radiated Disturbance (<1GHz)	4.15
Radiated Disturbance (>1GHz)	4.59
Radiated Disturbance (>18GHz)	4.96

FCC ID: BCG-A2293	 MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch
		Page 12 of 72

6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated according to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent Technologies	N9030A	3Hz-44GHz PXA Signal Analyzer	3/4/2020	Annual	3/4/2021	MY49430244
Anritsu	ML2496A	Power Meter	10/29/2019	Annual	10/29/2020	184005
Anritsu	MA2411B	Pulse Power Sensor	10/29/2019	Annual	10/29/2020	1726261
Anritsu	MA2411B	Pulse Power Sensor	10/29/2019	Annual	10/29/2020	1726262
ATM	180-442A-KF	20dB Nominal Gain Horn Antenna	10/29/2019	Annual	10/29/2020	T058701-02
COM-POWER	LIN-120A	LISN	3/4/2020	Annual	3/4/2021	241297
ETS-Lindgren	3142E-PA	Pre-Amplifier (30MHz - 6GHz)	9/19/2019	Annual	9/19/2020	213236
ETS-Lindgren	3142E	BiConiLog Antenna (30MHz - 6GHz)	1/6/2020	Annual	1/6/2021	224569
ETS-Lindgren	3117	Double Ridged Guide Antenna (1-18 GHz)	4/21/2020	Annual	4/21/2021	205956
Rohde & Schwarz	ESW26	EMI Test Receiver	6/1/2020	Annual	6/1/2021	101299
Rohde & Schwarz	ESW44	EMI Test Receiver	9/13/2019	Annual	9/13/2020	101570
Rohde & Schwarz	TS-PR1840	Pre-Amplifier (18GHz - 40GHz)	9/19/2019	Annual	9/19/2020	100051
Rohde & Schwarz	TC-TA18	Cross Polarized Vivaldi Antenna (400MHz-18GHz)	11/14/2019	Annual	11/14/2020	101057
Rohde & Schwarz	HFH2-Z2	Loop Antenna	3/12/2020	Annual	3/12/2021	100546

Table 6-1. Test Equipment List

Note:

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

FCC ID: BCG-A2293	 MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch
Page 13 of 72		

7.0 TEST RESULTS

7.1 Summary

Company Name: Apple Inc.

FCC ID: BCG-A2293

FCC Classification: Digital Transmission System (DTS)

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.247(a)(2)	RSS-247 [5.2]	6dB Bandwidth	> 500kHz	CONDUCTED	PASS	Section 7.2
15.247(b)(3)	RSS-247 [5.4]	Transmitter Output Power	< 1 Watt		PASS	Sections 7.3
15.247(e)	RSS-247 [5.2]	Transmitter Power Spectral Density	< 8dBm / 3kHz Band		PASS	Section 7.4
15.247(d)	RSS-247 [5.5]	Band Edge / Out-of-Band Emissions	≥ 20dBc		PASS	Sections 7.5, 7.6
15.205 15.209	RSS-Gen [8.9]	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-Gen [8.9])	RADIATED	PASS	Sections 7.7, 7.8, 7.9
15.207	RSS-Gen [8.8]	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 limits (RSS-Gen[8.8])	LINE CONDUCTED	PASS	Section 7.10

Table 7-1. Summary of Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "WLAN Automation," Version 3.5.
- 5) For radiated band edge, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "Chamber Automation," Version 1.3.1.

FCC ID: BCG-A2293		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 14 of 72

7.2 6dB Bandwidth Measurement

§15.247(a.2); RSS-247 [5.2]

Test Overview and Limit

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the transmitter antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated, and the worst case configuration results are reported in this section.

The minimum permissible 6dB bandwidth is 500 kHz.

Test Procedure Used

ANSI C63.10-2013 – Section 11.8.2 Option 2
KDB 558074 D01 v05r02 – Section 8.2

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 6$. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 100kHz
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-1. Test Instrument & Measurement Setup

Test Notes


Different data rates have been investigated and the worst case data rate is reported in this section.

FCC ID: BCG-A2293	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 15 of 72


Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]	Pass / Fail
2412	1	b	1	9.096	0.500	Pass
2437	6	b	1	9.093	0.500	Pass
2462	11	b	1	9.107	0.500	Pass
2412	1	g	6	18.390	0.500	Pass
2437	6	g	6	18.360	0.500	Pass
2462	11	g	6	18.570	0.500	Pass
2412	1	n	65/72.2 (MCS7)	18.870	0.500	Pass
2437	6	n	65/72.2 (MCS7)	18.710	0.500	Pass
2462	11	n	65/72.2 (MCS7)	18.390	0.500	Pass

Table 7-2. Conducted Bandwidth Measurements

FCC ID: BCG-A2293	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 16 of 72




Plot 7-1. 6dB Bandwidth Plot (802.11b – Ch. 1)




Plot 7-2. 6dB Bandwidth Plot (802.11b – Ch. 6)

FCC ID: BCG-A2293		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 17 of 72




Plot 7-3. 6dB Bandwidth Plot (802.11b – Ch. 11)




Plot 7-4. 6dB Bandwidth Plot (802.11g – Ch. 1)

FCC ID: BCG-A2293	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 18 of 72




Plot 7-5. 6dB Bandwidth Plot (802.11g – Ch. 6)




Plot 7-6. 6dB Bandwidth Plot (802.11g – Ch. 11)

FCC ID: BCG-A2293	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 19 of 72




Plot 7-7. 6dB Bandwidth Plot (802.11n (2.4GHz) – Ch. 1)



Plot 7-8. 6dB Bandwidth Plot (802.11n (2.4GHz) – Ch. 6)

FCC ID: BCG-A2293	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 20 of 72



Plot 7-9. 6dB Bandwidth Plot (802.11n (2.4GHz) – Ch. 11)

FCC ID: BCG-A2293		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 21 of 72

7.3 Output Power Measurement

§15.247(b.3); RSS-247 [5.4]

Test Overview and Limits

A transmitter antenna terminal of EUT is connected to the input of an RF power sensor. Measurement is made using a broadband power meter capable of making peak and average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

The maximum peak conducted output power of digital modulation systems operating in the 2400-2483.5 MHz band is 1 Watt.

The conducted output power limit on paragraph above is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For DTSSs employing digital modulation techniques operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1 W. The e.i.r.p. shall not exceed 4 W.

Test Procedure Used

ANSI C63.10-2013 – Section 11.9.1.3 PKPM1 Peak Power Method
KDB 558074 D01 v05r02 – Section 8.3.1.3 PKPM1 Peak-reading Power Meter Method
ANSI C63.10-2013 – Section 11.9.2.3.2 Method AVGPM-G
KDB 558074 D01 v05r02 – Section 8.3.2.3 Measurement using a Power Meter (PM)

Test Settings

Method PKPM1 (Peak Power Measurement)

Peak power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The pulse sensor employs a VBW = 50MHz so this method was only used for signals whose DTS bandwidth was less than or equal to 50MHz.

Method AVGPM-G (Average Power Measurement)

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.



Figure 7-2. Test Instrument & Measurement Setup for Power Meter Measurements

Test Notes

None

FCC ID: BCG-A2293	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 22 of 72

© 2020 PCTEST

V 10.1 02/01/2020

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

7.3.1 Peak Output Power Measurement

§15.247(b.3); RSS-247 [5.4]

Freq [MHz]	Channel	Detector	Conducted Power [dBm]				Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	Max e.i.r.p. [dBm]	Max e.i.r.p. Limit [dBm]	e.i.r.p. Margin [dB]
			802.11b	802.11g	802.11n (MCS0)	802.11n (MCS7)						
2412	1	PEAK	21.29	21.77	21.69	22.76	30.00	-7.24	-11.10	11.66	36.02	-24.36
2417	2	PEAK	21.28	22.93	23.01	22.59	30.00	-6.99	-11.10	11.91	36.02	-24.11
2437	6	PEAK	21.46	22.94	22.92	22.57	30.00	-7.06	-11.10	11.84	36.02	-24.18
2452	9	PEAK	21.43	22.99	23.00	22.77	30.00	-7.00	-11.10	11.90	36.02	-24.12
2457	10	PEAK	21.47	22.74	22.81	22.63	30.00	-7.19	-11.10	11.71	36.02	-24.31
2462	11	PEAK	21.31	22.69	22.68	23.29	30.00	-6.71	-11.10	12.19	36.02	-23.83
2467	12	PEAK	19.97	22.40	22.41	23.26	30.00	-6.74	-11.10	12.16	36.02	-23.86
2472	13	PEAK	16.48	16.32	16.06	14.50	30.00	-13.52	-11.10	5.38	36.02	-30.64

Table 7-3. Peak Conducted Output Power Measurements

FCC ID: BCG-A2293	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 23 of 72

7.3.2 Average Output Power Measurements

§15.247(b.3); RSS-247 [5.4]

Freq [MHz]	Channel	Detector	Conducted Power [dBm]				Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	Max e.i.r.p. [dBm]	Max e.i.r.p. Limit [dBm]	e.i.r.p. Margin [dB]
			802.11b	802.11g	802.11n (MCS0)	802.11n (MCS7)						
2412	1	AVG	18.82	17.00	16.96	16.48	30.00	-11.18	-11.10	7.72	36.02	-28.30
2417	2	AVG	18.81	18.29	18.50	16.44	30.00	-11.19	-11.10	7.71	36.02	-28.31
2437	6	AVG	18.99	18.50	18.29	16.44	30.00	-11.01	-11.10	7.89	36.02	-28.13
2452	9	AVG	18.98	18.50	18.50	16.50	30.00	-11.02	-11.10	7.88	36.02	-28.14
2457	10	AVG	19.00	17.92	18.00	16.50	30.00	-11.00	-11.10	7.90	36.02	-28.12
2462	11	AVG	18.87	16.46	16.47	16.46	30.00	-11.13	-11.10	7.77	36.02	-28.25
2467	12	AVG	17.49	15.47	15.47	15.50	30.00	-12.51	-11.10	6.39	36.02	-29.63
2472	13	AVG	14.00	5.50	5.50	5.35	30.00	-16.00	-11.10	2.90	36.02	-33.12

Table 7-4. Average Conducted Output Power Measurements

FCC ID: BCG-A2293	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 24 of 72

7.4 Power Spectral Density

§15.247(e); RSS-247 [5.2]

Test Overview and Limit

The peak power density is measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated and the worst case configuration results are reported in this section.

The maximum permissible power spectral density is 8 dBm in any 3 kHz band.

Test Procedure Used

ANSI C63.10-2013 – Section 11.10.2 Method PKPSD

KDB 558074 D01 v05r02 – Section 8.4 DTS Maximum Power Spectral Density level in the fundamental emission

Test Settings

1. Analyzer was set to the center frequency of the DTS channel under investigation
2. Span = 1.5 times the DTS channel bandwidth
3. RBW = 3kHz
4. VBW = 1MHz
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-3. Test Instrument & Measurement Setup

Test Notes


None

FCC ID: BCG-A2293	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch		Page 25 of 72


Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured Power Spectral Density [dBm / 3kHz]	Maximum Permissible Power Density [dBm / 3kHz]	Margin [dB]	Pass / Fail
2412	1	b	1	-2.71	8.00	-10.71	Pass
2437	6	b	1	-3.19	8.00	-11.19	Pass
2462	11	b	1	-2.49	8.00	-10.49	Pass
2412	1	g	6	-7.90	8.00	-15.90	Pass
2437	6	g	6	-8.75	8.00	-16.75	Pass
2462	11	g	6	-8.81	8.00	-16.81	Pass
2412	1	n	65/72.2 (MCS7)	-7.84	8.00	-15.84	Pass
2437	6	n	65/72.2 (MCS7)	-6.92	8.00	-14.92	Pass
2462	11	n	65/72.2 (MCS7)	-7.49	8.00	-15.49	Pass

Table 7-5. Conducted Power Density Measurements

FCC ID: BCG-A2293	 PCTEST Proud to be part of  element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 26 of 72




Plot 7-10. Power Spectral Density Plot (802.11b – Ch. 1)




Plot 7-11. Power Spectral Density Plot (802.11b – Ch. 6)

FCC ID: BCG-A2293	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 27 of 72




Plot 7-12. Power Spectral Density Plot (802.11b – Ch. 11)




Plot 7-13. Power Spectral Density Plot (802.11g – Ch. 1)

FCC ID: BCG-A2293	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 28 of 72




Plot 7-14. Power Spectral Density Plot (802.11g – Ch. 6)



Plot 7-15. Power Spectral Density Plot (802.11g – Ch. 11)

FCC ID: BCG-A2293	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 29 of 72



Plot 7-18. Power Spectral Density Plot (802.11n (2.4GHz) – Ch. 11)

FCC ID: BCG-A2293	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 31 of 72

7.5 Conducted Authorized Band Edge

§15.247(d); RSS-247 [5.5]

Test Overview and Limit

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. For the following out of band conducted spurious emissions plots at the band edge, the EUT was set at a data rate that produced the worst-case emissions.

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the PSD procedure (Section 7.4).

Test Procedure Used

ANSI C63.10-2013 – Section 11.11.3
KDB 558074 D01 v05r02 – Section 8.7.2

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW = 100kHz
4. VBW = 1MHz
5. Detector = Peak
6. Number of sweep points $\geq 2 \times \text{Span/RBW}$
7. Trace mode = max hold
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-4. Test Instrument & Measurement Setup

Test Notes


None

FCC ID: BCG-A2293	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 32 of 72


© 2020 PCTEST

V 10.1 02/01/2020

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.




Plot 7-19. Band Edge Plot (802.11b – Ch. 1)




Plot 7-20. Band Edge Plot (802.11b – Ch. 11)

FCC ID: BCG-A2293	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 33 of 72




Plot 7-21: Band Edge Plot (802.11b – Ch. 12)




Plot 7-22: Band Edge Plot (802.11b – Ch. 13)

FCC ID: BCG-A2293	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 34 of 72



Plot 7-23. Band Edge Plot (802.11g– Ch. 1)




Plot 7-24. Band Edge Plot (802.11g– Ch. 2)

FCC ID: BCG-A2293	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 35 of 72




Plot 7-25. Band Edge Plot (802.11g- Ch. 9)




Plot 7-26. Band Edge Plot (802.11g - Ch. 10)

FCC ID: BCG-A2293	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 36 of 72




Plot 7-27. Band Edge Plot (802.11g - Ch. 11)




Plot 7-28. Band Edge Plot (802.11g - Ch. 12)

FCC ID: BCG-A2293		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 37 of 72




Plot 7-29. Band Edge Plot (802.11g – Ch. 13)

FCC ID: BCG-A2293	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 38 of 72




Plot 7-30. Band Edge Plot (802.11n (2.4GHz) – Ch. 1)




Plot 7-31. Band Edge Plot (802.11n (2.4GHz) – Ch. 2)

FCC ID: BCG-A2293	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 39 of 72




Plot 7-32. Band Edge Plot (802.11n (2.4GHz) – Ch. 9)



Plot 7-33. Band Edge Plot (802.11n (2.4GHz) – Ch. 10)

FCC ID: BCG-A2293	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 40 of 72



7.6 Conducted Spurious Emissions

§15.247(d); RSS-247 [5.5]

Test Overview and Limit

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. For the following out of band conducted spurious emissions plots, the EUT was investigated in all available data rates for “b”, “g”, and “n” modes. The worst case spurious emissions for the 2.4GHz band were found while transmitting in “b” mode at 1 Mbps and are shown in the plots below.

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the procedure in Section 11.1 of ANSI C63.10-2013 and KDB 558074 D01 v0502.

Test Procedure Used

ANSI C63.10-2013 – Section 11.11.3
KDB 558074 D01 v05r02 – Section 8.5

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 25GHz (separated into two plots per channel)
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-5. Test Instrument & Measurement Setup

FCC ID: BCG-A2293	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 43 of 72

© 2020 PCTEST


V 10.1 02/01/2020

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.


Test Notes

1. RBW was set to 1MHz rather than 100kHz in order to increase the measurement speed.
2. The display line shown in the following plots denotes the limit at 20dB below the fundamental emission level measured in a 100kHz bandwidth. However, since the traces in the following plots are measured with a 1MHz RBW, the display line may not necessarily appear to be 20dB below the level of the fundamental in a 1MHz bandwidth.
3. For plots showing conducted spurious emissions near the limit, the frequencies were investigated with a reduced RBW to ensure that no emissions were present.
4. The unit was tested with all possible modes and only the highest emission is reported.

FCC ID: BCG-A2293	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 44 of 72




Plot 7-37. Conducted Spurious Plot (802.11b – Ch. 1)




Plot 7-38. Conducted Spurious Plot (802.11b – Ch. 1)

FCC ID: BCG-A2293	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 45 of 72




Plot 7-39. Conducted Spurious Plot (802.11b – Ch. 6)




Plot 7-40. Conducted Spurious Plot (802.11b – Ch. 6)

FCC ID: BCG-A2293	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 46 of 72



Plot 7-41. Conducted Spurious Plot (802.11b – Ch. 11)



Plot 7-42. Conducted Spurious Plot (802.11b – Ch. 11)

FCC ID: BCG-A2293	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 47 of 72

7.7 Radiated Spurious Emissions – Above 1 GHz

§15.247(d) §15.205 & §15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 7 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-6 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
Above 960.0 MHz	500	3

Table 7-6. Radiated Limits

Test Procedures Used

ANSI C63.10-2013 – Section 6.6.4.3

KDB 558074 D01 v05r02 – Sections 8.6, 8.7

Test Settings

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be $\geq 2 \times \text{span/RBW}$)
6. Sweep time = auto
7. Trace (RMS) averaging was performed over at least 100 traces

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: BCG-A2293		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 48 of 72

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-6. Radiated Measurement Setup

FCC ID: BCG-A2293	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 49 of 72

Test Notes

1. The optional test procedures for antenna port conducted measurements of unwanted emissions per the guidance of KDB 558074 D01 v05r02 were not used to evaluate this device for compliance to radiated limits. All radiated spurious emissions levels were measured in a radiated test setup.
2. All emissions lying in restricted bands specified in Section 15.205 and Section 8.10 of RSS-Gen are below the limit shown in Table 7-6.
3. The antenna is manipulated through typical positions, polarity and height during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery.
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas.
6. Emissions below 18GHz were measured at a 3 meter test distance ($D = 3m$) while emissions above 18GHz were measured at a 1 meter test distance ($D = 1m$) with the application of a distance correction factor.
7. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section.
8. The "-" shown in the following RSE tables are used to denote a noise floor measurement.
9. The unit was tested with all possible modes and only the highest emissions is reported.
10. The intermodulation emissions were tested against the less stringent limit across all rule parts applicable to simultaneous transmitters.
11. For simultaneous transmission measurements, Trace mode = Max Hold was used for pulsed emissions.
12. All harmonics have been measured with the worst case simultaneous configuration and no emissions have been found at UWB and WLAN 2.4GHz harmonic frequencies.

Sample Calculations

Determining Spurious Emissions Levels

- Field Strength Level $_{[dB\mu V/m]} = \text{Analyzer Level}_{[dBm]} + 107 + \text{AFCL}_{[dB/m]}$
- $\text{AFCL}_{[dB/m]} = \text{Antenna Factor}_{[dB/m]} + \text{Cable Loss}_{[dB]} - \text{Preamplifier Gain}_{[dB]}$
- $\text{Margin}_{[dB]} = \text{Field Strength Level}_{[dB\mu V/m]} - \text{Limit}_{[dB\mu V/m]}$

Radiated Band Edge Measurement Offset


- The amplitude offset shown in the radiated restricted band edge plots in Section 7.8 was calculated using the formula:

$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + \text{Attenuator}) - \text{Preamplifier Gain}$$


FCC ID: BCG-A2293	 MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch
		Page 50 of 72

Radiated Spurious Emissions – Above 1GHz


§15.247(d) §15.205 & §15.209; RSS-Gen [8.9]



Plot 7-43. Radiated Spurious Emissions 1-18GHz (802.11b – Ch. 1)



Plot 7-44. Radiated Spurious Emissions 1-18GHz (802.11b – Ch. 6)




Plot 7-45. Radiated Spurious Emissions 1-18GHz (802.11b – Ch. 11)

FCC ID: BCG-A2293	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 51 of 72


Radiated Spurious Emissions – Above 18GHz

§15.209; RSS-Gen [8.9]



13:45:35 14.07.2020

Plot 7-46. Radiated Spurious Emissions 18-26.5GHz (802.11b – Ch. 6, Ant. Pol. H)



13:46:42 14.07.2020

Plot 7-47. Radiated Spurious Emissions 18-26.5GHz (802.11b – Ch. 6, Ant. Pol. V)

FCC ID: BCG-A2293	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 52 of 72

© 2020 PCTEST

V 10.1 02/01/2020

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Radiated Spurious Emission Measurements – Above 1GHz

§15.247(d) §15.205 & §15.209; RSS-Gen [8.9]

Worst Case Mode: 802.11b
Worst Case Transfer Rate: 1 Mbps
Distance of Measurements: 3 Meters
Operating Frequency: 2412MHz
Channel: 01

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4824.00	Avg	V	109	155	-79.06	8.40	36.34	53.98	-17.64
4824.00	Peak	V	109	155	-68.56	8.40	46.84	73.98	-27.14
12060.00	Avg	V	-	-	-85.35	20.28	41.93	53.98	-12.05
12060.00	Peak	V	-	-	-73.52	20.28	53.76	73.98	-20.22

Table 7-7. Radiated Spurious Emission Measurements

Worst Case Mode: 802.11b
Worst Case Transfer Rate: 1 Mbps
Distance of Measurements: 3 Meters
Operating Frequency: 2437MHz
Channel: 06

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4874.00	Avg	V	105	158	-80.02	8.58	35.56	53.98	-18.42
4874.00	Peak	V	105	158	-69.69	8.58	45.89	73.98	-28.09
7311.00	Avg	V	105	204	-81.90	12.94	38.04	53.98	-15.94
7311.00	Peak	V	105	204	-70.80	12.94	49.14	73.98	-24.84
12185.00	Avg	V	-	-	-85.05	19.94	41.89	53.98	-12.09
12185.00	Peak	V	-	-	-73.84	19.94	53.10	73.98	-20.88

Table 7-8. Radiated Spurious Emission Measurements

FCC ID: BCG-A2293	 MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch
		Page 53 of 72

Radiated Spurious Emission Measurements – Above 1GHz

§15.247(d) §15.205 & §15.209; RSS-Gen [8.9]

Worst Case Mode: 802.11b

Worst Case Transfer Rate: 1 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 2462MHz

Channel: 11

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4924.00	Avg	V	105	195	-80.59	9.49	35.90	53.98	-18.08
4924.00	Peak	V	105	195	-70.80	9.49	45.69	73.98	-28.29
7386.00	Avg	V	-	-	-83.20	14.11	37.91	53.98	-16.07
7386.00	Peak	V	-	-	-71.47	14.11	49.64	73.98	-24.34
12310.00	Avg	V	-	-	-85.72	20.67	41.95	53.98	-12.03
12310.00	Peak	V	-	-	-74.50	20.67	53.17	73.98	-20.81

Table 7-9. Radiated Spurious Emission Measurements


FCC ID: BCG-A2293	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 54 of 72

7.7.1 Simultaneous Tx Radiated Spurious Emissions – Above 1GHz

§15.519(c) §15.247 §15.205 §15.209 & §27.53(m); RSS-220 [5.3.1(d)] RSS-Gen [8.9] & RSS-199[4.5]


Description	WLAN	LTE (Band 41)	UWB
Antenna	FCM	FCM	FCM
Channel	6	39750	5
Operating Frequency (MHz)	2437	2506	6500
Mode/Modulation	802.11 b	QPSK/1RB/20MHz	Config3/Payload 125

Table 7-10. Worst Case Simultaneous Transmission Configuration




Plot 7-48. Radiated Spurious Emissions 1-18GHz (Simultaneous Transmission)

Note: Only the LTE B41 limit was shown in the plot above. The 2 other fundamentals are WLAN and UWB.



Plot 7-49. Radiated Spurious Emissions 18-40GHz (Simultaneous Transmission, Ant. Pol. H)

FCC ID: BCG-A2293	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 55 of 72



Plot 7-50. Radiated Spurious Emissions 18-40GHz (Simultaneous Transmission, Ant. Pol. V)

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	EIRP Level at Sub Ant Port [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
5012.00	Avg	H	101	219.00	-61.54	10.15	-51.39	-25.0	-26.39
7518.00	Avg	H	249	115.00	-60.59	12.11	-48.49	-25.0	-23.49
10024.00	Avg	V	-	-	-63.04	13.33	-49.71	-25.0	-24.71
12530.00	Avg	V	-	-	-61.12	13.36	-47.76	-25.0	-22.76
2387.00	Avg	V	139	189.00	-44.88	6.16	-38.71	-25.0	-13.71

Table 7-11. LTE Harmonics and Intermodulation Emission Measurements in Simultaneous Transmission Mode


FCC ID: BCG-A2293	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 56 of 72

7.8 Radiated Restricted Band Edge Measurements

§15.205 §15.209; RSS-Gen [8.9]

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting.


Worst Case Mode:	802.11b
Worst Case Transfer Rate:	1Mbps
Distance of Measurements:	3 Meters
Operating Frequency:	2412MHz
Channel:	1



Plot 7-51. Radiated Restricted Lower Band Edge Measurement


FCC ID: BCG-A2293	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 57 of 72

Worst Case Mode: 802.11b
Worst Case Transfer Rate: 1Mbps
Distance of Measurements: 3 Meters
Operating Frequency: 2462MHz
Channel: 11



Plot 7-52. Radiated Restricted Upper Band Edge Measurement


Worst Case Mode: 802.11b
Worst Case Transfer Rate: 1Mbps
Distance of Measurements: 3 Meters
Operating Frequency: 2467MHz
Channel: 12



Plot 7-53. Radiated Restricted Upper Band Edge Measurement


FCC ID: BCG-A2293	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 58 of 72

Worst Case Mode: 802.11b
Worst Case Transfer Rate: 1Mbps
Distance of Measurements: 3 Meters
Operating Frequency: 2472MHz
Channel: 13



Plot 7-54. Radiated Restricted Upper Band Edge Measurement


Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 2412MHz
Channel: 1



Plot 7-55. Radiated Restricted Lower Band Edge Measurement


FCC ID: BCG-A2293	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 59 of 72

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 2417MHz
Channel: 2



Plot 7-56. Radiated Restricted Lower Band Edge Measurement


Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 2452MHz
Channel: 9



Plot 7-57. Radiated Restricted Upper Band Edge Measurement


FCC ID: BCG-A2293	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 60 of 72

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 2457MHz
Channel: 10



Plot 7-58. Radiated Restricted Upper Band Edge Measurement


Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS7
Distance of Measurements: 3 Meters
Operating Frequency: 2462MHz
Channel: 11



Plot 7-59. Radiated Restricted Upper Band Edge Measurement


FCC ID: BCG-A2293		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 61 of 72

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS7
Distance of Measurements: 3 Meters
Operating Frequency: 2467MHz
Channel: 12



Plot 7-60. Radiated Restricted Upper Band Edge Measurement

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS7
Distance of Measurements: 3 Meters
Operating Frequency: 2472MHz
Channel: 13



Plot 7-61. Radiated Restricted Upper Band Edge Measurement

FCC ID: BCG-A2293	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 62 of 72

7.9 Radiated Spurious Emissions – Below 1GHz

§15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 7 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-12 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [μV/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-12. Radiated Limits

Test Procedures Used

ANSI C63.10-2013

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. VBW = 300kHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: BCG-A2293	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 63 of 72

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.




Figure 7-7. Radiated Test Setup < 30Mhz




Figure 7-8. Radiated Test Setup < 1GHz

FCC ID: BCG-A2293	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 64 of 72

Test Notes

1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen(8.10) are below the limit shown in Table 7-12.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes. For below 30MHz measurements, the loop antenna was positioned in three orthogonal planes (X front, Y side, Z top) to determine the orientation resulting in the worst case emissions.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector for emissions within 6dB of the limit.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the worst channel, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. There were no emissions detected in the 30MHz – 1GHz frequency range, as shown in the subsequent plots.
10. The unit was tested with all possible modes, and only the highest emission is reported.
11. Both configurations below were investigated, and the worst case has been reported.
 - a. EUT powered by AC/DC adapter via USB cable with wireless charger
 - b. EUT powered by host PC via USB cable with wireless charger

Sample Calculation


Determining Spurious Emissions Levels

- Field Strength Level $[\text{dB}\mu\text{V/m}] = \text{Analyzer Level} [\text{dBm}] + 107 + \text{AFCL} [\text{dB/m}]$
- $\text{AFCL} [\text{dB/m}] = \text{Antenna Factor} [\text{dB/m}] + \text{Cable Loss} [\text{dB}] - \text{Preamplifier Gain} [\text{dB}]$
- $\text{Margin} [\text{dB}] = \text{Field Strength Level} [\text{dB}\mu\text{V/m}] - \text{Limit} [\text{dB}\mu\text{V/m}]$

FCC ID: BCG-A2293	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 65 of 72

7.9.1 Radiated Spurious Emissions – Below 1GHz

§15.209; RSS-Gen [8.9]



Plot 7-62. Radiated Spurious Emissions 30MHz-1GHz (802.11b – Ch.6, with WCP + AC/DC Adapter)

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
30.15	Max-Peak	H	250	93	-77.37	-17.44	12.19	40.00	-27.81
36.55	Max-Peak	H	250	347	-76.31	-21.18	9.51	40.00	-30.49
127.39	Max-Peak	H	250	22	-63.90	-25.83	17.27	43.52	-26.25
199.31	Max-Peak	H	100	160	-71.73	-22.39	12.88	43.52	-30.64
401.95	Max-Peak	H	100	352	-77.78	-14.17	15.05	46.02	-30.97
938.11	Max-Peak	H	100	325	-79.40	-5.19	22.41	46.02	-23.61

Table 7-13. Radiated Spurious Measurements 30MHz-1GHz (802.11b – Ch.6, with WCP + AC/DC Adapter)


FCC ID: BCG-A2293		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 66 of 72

7.9.2 Simultaneous Tx Radiated Spurious Emissions – Below 1GHz

§15.209 & §27.53(m); RSS-Gen [8.9] & RSS-199 [4.5]

Description	WLAN	LTE	UWB
Antenna	FCM	FCM	FCM
Channel	6	39750	5
Operating Frequency (MHz)	2437	2506	6500
Mode/Modulation	802.11 b	QPSK/1RB/20MHz	Config3/Payload 125

Table 7-14. Worst Case Simultaneous Transmission Configuration



Plot 7-63. Radiated Spurious Emissions 30MHz-1GHz (Simultaneous Transmission, with WCP + AC/DC adapter)

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
112.55	Max-Peak	V	100	286	-71.31	-25.16	10.53	43.52	-32.99
135.88	Max-Peak	V	250	15	-69.96	-25.10	11.94	43.52	-31.58
176.47	Max-Peak	H	100	151	-67.13	-22.21	17.66	43.52	-25.86
213.04	Max-Peak	V	100	151	-67.90	-21.87	17.23	43.52	-26.29
251.16	Max-Peak	H	100	309	-74.34	-19.94	12.72	46.02	-33.30
272.84	Max-Peak	V	100	270	-72.97	-19.14	14.89	46.02	-31.13

Table 7-15. Radiated Spurious Measurements 30MHz-1GHz (Simultaneous Transmission, with WCP + AC/DC adapter)

FCC ID: BCG-A2293	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch		Page 67 of 72

7.10 AC Line-Conducted Emission Measurements

§15.207; RSS-Gen [8.8]

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for AC Line conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.207 and RSS-Gen (8.8).

Frequency of emission (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-16. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10-2013, Section 6.2

Test Settings

Quasi-Peak Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Average Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: BCG-A2293	 PCTEST® Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 68 of 72

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-9. Test Instrument & Measurement Setup

Test Notes

1. All modes of operation were investigated for AC line conducted spurious emissions, and the worst-case emissions were reported. The emissions found were not affected by the choice of channel used during testing.
2. The limit for an intentional radiator from 150kHz to 30MHz are specified in Part 15.207 and RSS-Gen(8.8).
3. $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
4. $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Corr. (dB)}$
5. $\text{Margin (dB)} = \text{QP/AV Level (dB}\mu\text{V)} - \text{QP/AV Limit (dB}\mu\text{V)}$
6. Traces shown in plot are made using quasi-peak and average detectors.
7. Deviations to the Specifications: none.
8. Both configurations below were investigated, and the worst case has been reported.
 - a. EUT powered by AC/DC adapter via USB cable with wireless charger
 - b. EUT powered by host PC via USB cable with wireless charger

FCC ID: BCG-A2293	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 69 of 72




Plot 7-64. AC Line Conducted Plot with 802.11b Ch.6 (L1, with WCP + AC/DC Adapter)

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.168	FINAL	52.2	—	65.06	-12.86	L1	GND
0.168	FINAL	—	37.08	55.06	-17.98	L1	GND
0.249	FINAL	46.3	—	61.79	-15.51	L1	GND
0.251	FINAL	—	30.72	51.72	-20.99	L1	GND
0.501	FINAL	—	20.64	46.00	-25.36	L1	GND
0.508	FINAL	39.1	—	56.00	-16.95	L1	GND
0.677	FINAL	—	22.14	46.00	-23.86	L1	GND
0.677	FINAL	40.6	—	56.00	-15.41	L1	GND
0.762	FINAL	—	24.19	46.00	-21.81	L1	GND
0.762	FINAL	40.0	—	56.00	-15.96	L1	GND
0.830	FINAL	42.8	—	56.00	-13.19	L1	GND
0.832	FINAL	—	25.86	46.00	-20.14	L1	GND

Table 7-17. AC Line Conducted Data with 802.11b Ch.6 (L1, with WCP + AC/DC Adapter)

FCC ID: BCG-A2293	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 70 of 72



Plot 7-65. AC Line Conducted Plot with 802.11b Ch.6 (N, with WCP + AC/DC Adapter)

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.166	FINAL	47.0	—	65.17	-18.21	N	GND
0.166	FINAL	—	31.19	55.17	-23.98	N	GND
0.247	FINAL	41.5	—	61.87	-20.41	N	GND
0.249	FINAL	—	26.06	51.79	-25.73	N	GND
0.578	FINAL	—	20.30	46.00	-25.70	N	GND
0.587	FINAL	32.9	—	56.00	-23.13	N	GND
0.755	FINAL	37.0	—	56.00	-18.96	N	GND
0.780	FINAL	—	28.16	46.00	-17.84	N	GND
2.751	FINAL	—	23.00	46.00	-23.00	N	GND
2.753	FINAL	32.0	—	56.00	-24.05	N	GND
4.385	FINAL	—	25.61	46.00	-20.39	N	GND
4.387	FINAL	32.1	—	56.00	-23.90	N	GND

Table 7-18. AC Line Conducted Data with 802.11b Ch.6 (N, with WCP + AC/DC Adapter)

FCC ID: BCG-A2293	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 71 of 72

8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Apple Watch FCC ID: BCG-A2293** is in compliance with Part 15 Subpart C (15.247) of the FCC Rules and RSS-247 of the Innovation, Science and Economic Development Canada Rules.

FCC ID: BCG-A2293	 Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270017-05.BCG	Test Dates: 06/12/2020 - 08/21/2020	EUT Type: Watch	Page 72 of 72