



MEASUREMENT REPORT

FCC Part 15.247 / ISED RSS-247 Bluetooth (HDR)

Applicant Name:

Apple Inc.
One Apple Park Way
Cupertino, CA 95014
United States

Date of Testing:

06/08/2021 - 08/06/2021

Test Site/Location:

PCTEST Lab. Morgan Hill, CA, USA

Test Report Serial No.:

1C2106070043-07.BCG

FCC ID:	BCG-A2475
IC:	579C-A2475
APPLICANT:	Apple Inc.

Application Type:	Certification
Model/HVIN:	A2475
EUT Type:	Watch
Max. RF Output Power:	36.392 mW (15.61 dBm) Peak Conducted
Frequency Range:	2404 – 2478MHz
FCC Classification:	Digital Transmission System (DTS)
FCC Rule Part(s):	Part 15 Subpart C (15.247)
ISED Specification:	RSS-247 Issue 2
Test Procedure(s):	ANSI C63.10-2013, KDB 558074 D01 v05r02

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013 and KDB 558074 D01 v05r02. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Randy Ortanez
President



FCC ID: BCG-A2475 IC: 579C-A2475	PCTEST Proud to be part of element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021		EUT Type: Watch	Page 1 of 59

T A B L E O F C O N T E N T S

1.0	INTRODUCTION	3
1.1	Scope	3
1.2	PCTEST Test Location.....	3
1.3	Test Facility / Accreditations.....	3
2.0	PRODUCT INFORMATION.....	4
2.1	Equipment Description	4
2.2	Device Capabilities.....	4
2.3	Antenna Description	5
2.4	Test Support Equipment.....	6
2.5	Test Configuration	6
2.6	Software and Firmware	6
2.7	EMI Suppression Device(s)/Modifications	6
3.0	DESCRIPTION OF TESTS	7
3.1	Evaluation Procedure	7
3.2	AC Line Conducted Emissions	7
3.3	Radiated Emissions.....	8
3.4	Environmental Conditions.....	8
4.0	ANTENNA REQUIREMENTS	9
5.0	MEASUREMENT UNCERTAINTY	10
6.0	TEST EQUIPMENT CALIBRATION DATA	11
7.0	TEST RESULTS.....	12
7.1	Summary	12
7.2	Bandwidth Measurement – Bluetooth (HDR).....	13
7.3	Output Power Measurement – Bluetooth (HDR)	19
7.3.1	Peak Output Power Measurement – Bluetooth (HDR)	21
7.3.2	Average Output Power Measurement – Bluetooth (HDR)	22
7.4	Power Spectral Density – Bluetooth (HDR)	23
7.5	Conducted Authorized Band Edge	31
7.6	Conducted Spurious Emissions.....	35
7.7	Radiated Spurious Emission Measurements.....	40
7.8	Radiated Spurious Emissions Measurements – Below 1GHz	51
7.9	AC Line Conducted Emissions Measurement	55
8.0	CONCLUSION.....	59

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST® Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 2 of 59	

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.


1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST facility located at 18855 Adams Court, Morgan Hill, CA 95037. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014 and KDB 414788 D01 v01r01.

1.3 Test Facility / Accreditations

Measurements were performed at PCTEST located in Morgan Hill, CA 95037, U.S.A.

- PCTEST is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.02 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- PCTEST facility is a registered (22831) test laboratory with the site description on file with ISED.

FCC ID: BCG-A2475 IC: 579C-A2475	 Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 3 of 59

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Apple Watch FCC ID: BCG-A2475, IC: 579C-A2475**. The data found in this test report was taken with the EUT operating in Bluetooth HDR mode. While in HDR mode, the Bluetooth transmitter hops pseudo-randomly between 75 channels.

Note: This device is capable of operating in hopping and non-hopping mode. The EUT can hop between 75 different channels in the 2400 – 2483.5MHz band

Test Device Serial No.: CQ756HJ54Y, T2GPRG7752, MJ2XR422FG

2.2 Device Capabilities

This device contains the following capabilities:

850/1700/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n WLAN, 802.11a/n UNII, Bluetooth (1x, EDR, HDR4, HDR8, LE1M, LE2M), NFC, UWB, 60.5GHz Transmitter.

Ch.	Frequency (MHz)
1	2404
:	:
38	2440
:	:
75	2478

Table 2-1. Frequency / Channel Operations

Maximum Achievable Duty Cycles		
HDR Mode		Duty Cycle (%)
HDR4	ePA	100.0
	iPA	100.0
HDR8	ePA	100.0
	iPA	100.0

Table 2-2. Measured Duty Cycles

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST[®] Proud to be part of element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021		EUT Type: Watch	Page 4 of 59

1. This device supports simultaneous transmission operations, which allows for multiple transmitters to transmit simultaneously on the same antenna. The table below shows all configurations possible.

Simultaneous Tx Config	Antenna FCM				
	WLAN	Bluetooth	LTE/WCDMA	UNII	UWB
	802.11 b/g/n	BDR, EDR, HDR4/8, LE	Mid band/ High band	802.11 a/n	Ch.5, Ch.9
Config 1	✓	✗	✗	✗	✓
Config 2	✗	✓	✗	✗	✓
Config 3	✗	✗	✓	✗	✓
Config 4	✗	✓	✓	✗	✗
Config 5	✓	✗	✓	✗	✗
Config 6	✗	✗	✓	✓	✗
Config 7	✗	✓	✗	✓	✗
Config 8	✓	✗	✓	✗	✓
Config 9	✗	✓	✓	✗	✓
Config 10	✗	✓	✓	✓	✗

Table 2-3. Simultaneous Transmission Configurations

✓ = Support; ✗ = NOT Support

2. All above simultaneous transmission configurations have been tested and the worst case configuration was found to be configuration 10 (BT, LTE, and UNII). These results can be found in the RF Bluetooth, RF UNII, and RF Part 27b reports.

2.3 Antenna Description

Following antenna gain provided by manufacturer was used for the test.

Frequency [GHz]	Antenna Gain (dBi)
	FCM
2.4	-6.40

Table 2-4. Highest Antenna Gain

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST® Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch		

2.4 Test Support Equipment

1	Apple Macbook w/ AC/DC Adapter	Model: A1398	S/N: C2QKP008F6F3	
		Model: A1435	S/N: N/A	
2	Apple USB-C cable w/ Charging Dock w/ Dock	Model: N/A A2687 X241	S/N: N/A FV411420544MW6M4H N/A	
3	Apple Magnetic Charger Apple Magnetic Charger	Model: A2515 A2515	S/N: DLC035200UJMFR0AJ DLC035202KRMFR0A2	
4	Pathfinder Falcon SiP Socket	Model: 920-098626-01 P2 X2011S PF 212	S/N: DLC034200APQ6PM1E DLC048500BP0KPG2N	
5	Store Bracelet Assy	Model: N/A	S/N: DLC1197001R19G21N	

Table 2-5. Test Support Equipment Used

2.5 Test Configuration

The EUT was tested per the guidance of ANSI C63.10-2013 and KDB 558074 D01 v05r02. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See Sections 3.2 for AC line conducted emissions test setups, 3.3 for radiated emissions test setups, and 7.2, 7.3, 7.4, 7.5, and 7.6 for antenna port conducted emissions test setups.

The worst case configuration was investigated for all combinations of the three materials, aluminum, stainless steel, and titanium and various types of wristbands, metal and non-metal wristbands. The worst case configuration found was used for all testing.

For emissions from 1GHz – 18GHz, low, mid, and high channels were tested with highest power and worst case configuration. The emissions below 1GHz and above 18GHz were tested with the highest transmitting power channel and the worst case configuration.

The EUT was manipulated through three orthogonal planes of X-orientation (flatbed), Y-orientation (landscape), and Z-orientation (portrait) during the testing. Only the worst case emissions were reported in this test report.

For AC line conducted and radiated test below 1GHz, following configuration were investigated and EUT powered by AC/DC was the worst case.

- EUT powered by AC/DC adapter via USB-C cable with magnetic charger
- EUT powered by host PC via USB-C cable with magnetic charger

2.6 Software and Firmware

The test was conducted with firmware version watchOS 8.0 installed on the EUT.

2.7 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST® Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 6 of 59	

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013) and the guidance provided in KDB 558074 D01 v05r01 were used in the measurement of the EUT.

Deviation from measurement procedure.....None

3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 7m x 3.66m x 2.7m shielded enclosure. The shielded enclosure is manufactured by AP Americas. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50µH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is an ETS Lindgren Model LPRX-4X30 (100dB Attenuation, 14kHz-18GHz) and the two EMI/RFI filters are ETS Lindgren Model LRW-2030-S1 (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 0. Automated test software was used to perform the AC line conducted emissions testing. Automated measurement software utilized is Rohde & Schwarz EMC32, Version 10.50.40.

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST[®] Proud to be part of element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 7 of 59	

3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

Per KDB 414788, radiated emission test sites other than open-field test sites (e.g., shielded anechoic chambers), may be employed for emission measurements below 30MHz if characterized so that the measurements correspond to those obtained at an open-field test site. To determine test site equivalency, a reference sample transmitting at 149kHz was measured on an open field test site (asphalt with no ground plane) and then measured in the 3m semi-anechoic chamber. A calibrated 60cm loop antenna was rotated about its vertical axis while the reference device was rotated through the X, Y and Z axis in order to capture the worst case level. A maximum deviation of 2.77dB at 149kHz was measured when comparing the 3 meter semi-anechoic chamber to the open field site.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33 depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: BCG-A2475 IC: 579C-A2475	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 8 of 59

4.0 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna(s) of the EUT are **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The EUT complies with the requirement of §15.203.

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST® Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 9 of 59	

5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.23-2012. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (\pm dB)
Conducted Bench Top Measurements	1.65
Line Conducted Disturbance	2.75
Radiated Disturbance (<30MHz)	4.06
Radiated Disturbance (30MHz - 1GHz)	4.30
Radiated Disturbance (1 - 18GHz)	4.78
Radiated Disturbance (>18GHz)	4.79

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST [®] Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 10 of 59

6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent Technologies	N9030A	3Hz-44GHz PXA Signal Analyzer	3/31/2021	Annual	3/31/2022	MY49430244
Anritsu	ML2496A	Power Meter	11/3/2020	Annual	11/3/2021	184005
Anritsu	MA2411B	Pulse Power Sensor	11/10/2020	Annual	11/10/2021	1726261
Anritsu	MA2411B	Pulse Power Sensor	12/9/2020	Annual	12/9/2021	1726262
ATM	180-442-KF	20dB Nominal Gain Horn Antenna	12/9/2020	Annual	12/9/2021	T058701-01
ETS-Lindgren	3142E	BiConiLog Antenna (30MHz - 6GHz)	9/15/2020	Annual	9/15/2021	208204
ETS-Lindgren	3117	Double Ridged Guide Antenna (1-18 GHz)	5/3/2021	Annual	5/3/2022	205956
Keysight Technology	N9040B	UXA Signal Analyzer	12/19/2020	Annual	12/19/2021	MY57212015
Rohde & Schwarz	TS-PR8	Pre-Amplifier (30MHz - 8GHz)	12/3/2020	Annual	12/3/2021	102327
Rohde & Schwarz	TS-PR18	Pre-Amplifier (1GHz - 18GHz)	12/3/2020	Annual	12/3/2021	101648
Rohde & Schwarz	FSV40	Signal Analyzer (10Hz-40GHz)	3/16/2021	Annual	3/16/2022	101619
Rohde & Schwarz	ESW26	EMI Test Receiver	6/11/2021	Annual	6/11/2022	101299
Rohde & Schwarz	ESW44	EMI Test Receiver	11/9/2020	Annual	11/9/2021	101570
Rohde & Schwarz	TS-PR1840	Pre-Amplifier (18GHz - 40GHz)	4/29/2021	Annual	4/29/2022	100051
Rohde & Schwarz	TC-TA18	Cross Polarized Vivaldi Antenna (400MHz-18GHz)	10/2/2020	Annual	10/2/2021	101063
Rohde & Schwarz	HFH2-Z2	Loop Antenna	4/5/2021	Annual	4/5/2022	101063
Rohde & Schwarz	ENV216	Two-Line-V-Network (LiSN)	12/7/2020	Annual	12/7/2021	101364

Table 6-1. Test Equipment List

Note:

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST[®] Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 11 of 59

7.0 TEST RESULTS

7.1 Summary

Company Name: Apple Inc.
 FCC ID: BCG-A2475
 IC: 579C-A2475
 FCC Classification: Digital Transmission System (DTS)
 Number of Channels: 75

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.247(a)(2)	RSS-247 [5.2]	6dB Bandwidth	> 500kHz	CONDUCTED	PASS	Section 7.2
2.1049	RSS-Gen [6.7]	Occupied Bandwidth	N/A		N/A	Section 7.2
15.247(b)(3)	RSS-247 [5.4(d)]	Transmitter Output Power	< 1 Watt		PASS	Section 7.3
15.247(e)	RSS-247 [5.2]	Transmitter Power Spectral Density	< 8dBm / 3kHz Band		PASS	Section 7.4
15.247(d)	RSS-247 [5.5]	Band Edge / Out-of-Band Emissions	≥ 20dBc		PASS	Section 7.5, Section 7.6
15.205 15.209	RSS-Gen [8.9]	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-Gen [8.9])	RADIATED	PASS	Sections 7.7, Section 7.8
15.207	RSS-Gen [8.8]	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 limits (RSS-Gen[8.8])	AC LINE CONDUCTED	PASS	Section 7.9

Table 7-1. Summary of Test Results

Notes:

1. All modes of operation were investigated. The test results shown in the following sections represent the worst case emissions.
2. The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
3. All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
4. For radiated band edge, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "Chamber Automation," Version 1.3.2.

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST [®] Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 12 of 59

7.2 Bandwidth Measurement – Bluetooth (HDR)

§15.247(a.2); RSS-247 [5.2]; RSS-Gen [6.7]

Test Overview and Limit

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the transmitter antenna terminal of the EUT while the EUT is operating at maximum power and at the appropriate frequencies. All modes of operation were investigated and the worst case configuration results are reported in this section.

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible 6dB bandwidth is 500 kHz.

Test Procedure Used

ANSI C63.10-2013 – Section 11.8.2 Option 2

KDB 558074 D01 v05r02 – Section 8.2

RSS-Gen [6.7]

Test Settings

1. The signal analyzers' automatic bandwidth measurement capability of the spectrum analyzer was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to X = 6. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 100kHz
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2-7 were repeated after changing the RBW such that it would be within 1-5% of the 99% occupied bandwidth observed in Step 7

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST® <small>Proud to be part of element</small>		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 13 of 59	

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-1. Test Instrument & Measurement Setup

Test Notes


All supported modulation and power schemes have been tested on the unit and only worst-case configuration is reported

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch		Page 14 of 59


Frequency [MHz]	Data Rate [Mbps]	Power Scheme	Channel No.	Measured 99% Occupied Bandwidth [kHz]	Measured 6dB Bandwidth [kHz]	Minimum 6dB Bandwidth [kHz]	Pass / Fail
2404	4.0	ePA	1	2414.8	2158.5	500	Pass
2441	4.0	ePA	38	2417.0	2156.2	500	Pass
2478	4.0	ePA	75	2418.6	2162.1	500	Pass
2404	8.0	ePA	1	4818.3	4290.5	500	Pass
2441	8.0	ePA	38	4820.5	4291.8	500	Pass
2478	8.0	ePA	75	4832.4	4286.9	500	Pass

Table 7-2. Conducted 6dB and 99% OBW Measurements

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST[®] Proud to be part of element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch		




Plot 7-1. 6dB Bandwidth & 99% OBW Plot (Bluetooth (HDR4), 4Mbps, ePA – Ch. 1)



Plot 7-2. 6dB Bandwidth & 99% OBW Plot (Bluetooth (HDR4), 4Mbps, ePA – Ch. 38)

FCC ID: BCG-A2475 IC: 579C-A2475	PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 16 of 59



Plot 7-3. 6dB Bandwidth & 99% OBW Plot (Bluetooth (HDR4), 4Mbps, ePA – Ch. 75)



Plot 7-4. 6dB Bandwidth & 99% OBW Plot (Bluetooth (HDR8), 8Mbps, ePA – Ch. 1)

FCC ID: BCG-A2475 IC: 579C-A2475	PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 17 of 59



Plot 7-5. 6dB Bandwidth & 99% OBW Plot (Bluetooth (HDR8), 8Mbps, ePA – Ch. 38)



Plot 7-6. 6dB Bandwidth & 99% OBW Plot (Bluetooth (HDR8), 8Mbps, ePA – Ch. 75)

FCC ID: BCG-A2475 IC: 579C-A2475	PCTEST® Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 18 of 59

7.3 Output Power Measurement – Bluetooth (HDR)

§15.247(b.3); RSS-247 [5.4(d)]

Test Overview and Limits

The transmitter antenna terminal of the EUT is connected to the input of a spectrum analyzer. Measurements are made while the EUT is operating at maximum power and at the appropriate frequencies.

The maximum peak conducted output power of digital modulation systems operating in the 2400-2483.5 MHz band is 1 Watt.

The conducted output power limit on paragraph above is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of antenna exceeds 6 dBi.

For DTSs employing digital modulation techniques operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1 W. The e.i.r.p. shall not exceed 4 W

Test Procedure Used

ANSI C63.10-2013 – Section 11.9.1.3

ANSI C63.10-2013 – Section 11.9.2.3.2

KDB 558074 D01 v05r02 – Section 8.3.1.3, 8.3.2.3

Test Settings

Method PKPM1 (Peak Power Measurement)

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

Method AVGPM-G (Average Power Measurement)

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST[®] Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch		Page 19 of 59

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-2. Test Instrument & Measurement Setup for Peak and Average Power Measurement

Test Notes

None

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST Proud to be part of element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch		Page 20 of 59

7.3.1 Peak Output Power Measurement – Bluetooth (HDR)

Frequency [MHz]	Data Rate [Mbps]	Power Scheme	Channel No.	Peak Conducted Power		Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	EIRP Margin [dB]
				[dBm]	[mW]						
2404	4.0	ePA	1	15.27	33.651	30.00	-14.73	-6.40	8.87	36.02	-27.15
2441	4.0	ePA	38	15.51	35.563	30.00	-14.49	-6.40	9.11	36.02	-26.91
2478	4.0	ePA	75	15.54	35.810	30.00	-14.46	-6.40	9.14	36.02	-26.88
2404	4.0	iPA	1	12.67	18.493	30.00	-17.33	-6.40	6.27	36.02	-29.75
2441	4.0	iPA	38	12.83	19.187	30.00	-17.17	-6.40	6.43	36.02	-29.59
2478	4.0	iPA	75	11.79	15.101	30.00	-18.21	-6.40	5.39	36.02	-30.63
2404	8.0	ePA	1	15.24	33.420	30.00	-14.76	-6.40	8.84	36.02	-27.18
2441	8.0	ePA	38	15.50	35.481	30.00	-14.50	-6.40	9.10	36.02	-26.92
2478	8.0	ePA	75	15.61	36.392	30.00	-14.39	-6.40	9.21	36.02	-26.81
2404	8.0	iPA	1	12.61	18.239	30.00	-17.39	-6.40	6.21	36.02	-29.81
2441	8.0	iPA	38	12.78	18.967	30.00	-17.22	-6.40	6.38	36.02	-29.64
2478	8.0	iPA	75	11.86	15.346	30.00	-18.14	-6.40	5.46	36.02	-30.56

Table 7-3. Conducted Peak Output Power Measurements (Bluetooth HDR)

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 21 of 59

7.3.2 Average Output Power Measurement – Bluetooth (HDR)

Frequency [MHz]	Data Rate [Mbps]	Power Scheme	Channel No.	Average Conducted Power		Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	EIRP Margin [dB]
				[dBm]	[mW]						
2404	4.0	ePA	1	12.65	18.408	30.00	-17.35	-6.40	6.25	36.02	-29.77
2441	4.0	ePA	38	12.86	19.320	30.00	-17.14	-6.40	6.46	36.02	-29.56
2478	4.0	ePA	75	12.86	19.320	30.00	-17.14	-6.40	6.46	36.02	-29.56
2404	4.0	iPA	1	10.10	10.233	30.00	-19.90	-6.40	3.70	36.02	-32.32
2441	4.0	iPA	38	10.20	10.471	30.00	-19.80	-6.40	3.80	36.02	-32.22
2478	4.0	iPA	75	10.20	10.471	30.00	-19.80	-6.40	3.80	36.02	-32.22
2404	8.0	ePA	1	12.62	18.281	30.00	-17.38	-6.40	6.22	36.02	-29.80
2441	8.0	ePA	38	12.83	19.187	30.00	-17.17	-6.40	6.43	36.02	-29.59
2478	8.0	ePA	75	12.88	19.409	30.00	-17.12	-6.40	6.48	36.02	-29.54
2404	8.0	iPA	1	10.09	10.209	30.00	-19.91	-6.40	3.69	36.02	-32.33
2441	8.0	iPA	38	10.20	10.471	30.00	-19.80	-6.40	3.80	36.02	-32.22
2478	8.0	iPA	75	10.10	10.233	30.00	-19.90	-6.40	3.70	36.02	-32.32

Table 7-4. Conducted Average Output Power Measurements (Bluetooth HDR)

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST[®] Proud to be part of element			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch			

7.4 Power Spectral Density – Bluetooth (HDR)

§15.247(e); RSS-247 [5.2]

Test Overview and Limit

The peak power density is measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power and at the appropriate frequencies.

The maximum permissible power spectral density is 8 dBm in any 3 kHz band.

Test Procedure Used

ANSI C63.10-2013 – Section 11.10.2 Method PKPSD

KDB 558074 D01 v05r02 – Section 8.4 DTS Maximum Power Spectral Density level in the fundamental emission

Test Settings

1. Analyzer was set to the center frequency of the DTS channel under investigation
2. Span = 1.5 times the DTS channel bandwidth
3. RBW = 3kHz
4. VBW = 1MHz
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-3. Test Instrument & Measurement Setup

Test Notes


None.

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST® Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch		Page 23 of 59


Frequency [MHz]	Data Rate [Mbps]	Power Scheme	Channel No.	Measured Power Spectral Density [dBm / 3kHz]	Maximum Permissible Power Density [dBm / 3kHz]	Margin [dB]
2404	4.0	ePA	1	-2.86	8.0	-10.86
2441	4.0	ePA	38	-2.51	8.0	-10.51
2478	4.0	ePA	75	-3.79	8.0	-11.79
2404	4.0	iPA	1	-6.95	8.0	-14.95
2441	4.0	iPA	38	-6.66	8.0	-14.66
2478	4.0	iPA	75	-7.82	8.0	-15.82
2404	8.0	ePA	1	-3.29	8.0	-11.29
2441	8.0	ePA	38	-3.02	8.0	-11.02
2478	8.0	ePA	75	-4.00	8.0	-12.00
2404	8.0	iPA	1	-7.37	8.0	-15.37
2441	8.0	iPA	38	-8.37	8.0	-16.37
2478	8.0	iPA	75	-8.03	8.0	-16.03

Table 7-5. Conducted Power Density Measurements

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST® <small>Proud to be part of element</small>		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021		EUT Type: Watch	Page 24 of 59




Plot 7-7. Power Spectral Density Plot (Bluetooth (HDR4), 4Mbps, ePA – Ch. 1)




Plot 7-8. Power Spectral Density Plot (Bluetooth (HDR4), 4Mbps, ePA – Ch. 38)

FCC ID: BCG-A2475 IC: 579C-A2475	PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 25 of 59




Plot 7-9. Power Spectral Density Plot (Bluetooth (HDR4), 4Mbps, ePA – Ch. 75)




Plot 7-10. Power Spectral Density Plot (Bluetooth (HDR4), 4Mbps, iPA – Ch. 1)

FCC ID: BCG-A2475 IC: 579C-A2475	PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 26 of 59




Plot 7-11. Power Spectral Density Plot (Bluetooth (HDR4), 4Mbps, iPA – Ch. 38)




Plot 7-12. Power Spectral Density Plot (Bluetooth (HDR4), 4Mbps, iPA – Ch. 75)

FCC ID: BCG-A2475 IC: 579C-A2475	PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 27 of 59




Plot 7-13. Power Spectral Density Plot (Bluetooth (HDR8), 8Mbps, ePA – Ch. 1)




Plot 7-14. Power Spectral Density Plot (Bluetooth (HDR8), 8Mbps, ePA – Ch. 38)

FCC ID: BCG-A2475 IC: 579C-A2475	PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 28 of 59




Plot 7-15. Power Spectral Density Plot (Bluetooth (HDR8), 8Mbps, ePA – Ch. 75)




Plot 7-16. Power Spectral Density Plot (Bluetooth (HDR8), 8Mbps, iPA – Ch. 1)

FCC ID: BCG-A2475 IC: 579C-A2475	PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 29 of 59



Plot 7-17. Power Spectral Density Plot (Bluetooth (HDR8), 8Mbps, iPA – Ch. 38)



Plot 7-18. Power Spectral Density Plot (Bluetooth (HDR8), 8Mbps, iPA – Ch. 75)

FCC ID: BCG-A2475 IC: 579C-A2475	PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 30 of 59

7.5 Conducted Authorized Band Edge (HDR)

§15.247(d); RSS-247 [5.5]

Test Overview and Limit

For the following out of band conducted spurious emissions plots at the band edge, the EUT was set to transmit at maximum power with the largest packet size available. These settings produced the worst-case emissions.

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth.

Test Procedure Used

ANSI C63.10-2013 – Section 11.11.3
 KDB 558074 D01 v05r02 – Section 8.7.2

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW = 100kHz
4. VBW = 300kHz
5. Detector = Peak
6. Number of sweep points $\geq 2 \times$ Span/RBW
7. Trace mode = max hold
8. Sweep time = auto couple
9. The trace was allowed to stabilize

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST® <small>Proud to be part of element</small>		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 31 of 59	

Test Setup


The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-4. Test Instrument & Measurement Setup


Test Notes

All supported modulation and power schemes have been tested on the unit and only worst-case configuration is reported

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 32 of 59	




Plot 7-19. Band Edge Plot (Bluetooth (HDR4), ePA – Ch. 1)




Plot 7-20. Band Edge Plot (Bluetooth (HDR4), ePA – Ch. 75)

FCC ID: BCG-A2475 IC: 579C-A2475	PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 33 of 59



Plot 7-21. Band Edge Plot (Bluetooth (HDR8), ePA – Ch. 1)



Plot 7-22. Band Edge Plot (Bluetooth (HDR8), ePA – Ch. 75)

FCC ID: BCG-A2475 IC: 579C-A2475	PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 34 of 59

7.6 Conducted Spurious Emissions (HDR)

§15.247(d); RSS-247 [5.5]

Test Overview and Limit

For the following out of band conducted spurious emissions plots, the EUT was set to transmit at maximum power with the largest packet size available. The worst case spurious emissions were found in this configuration.

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the procedure in Section 8.5 of KDB 558074 D01 v05r02 and Section 11.11.3 of ANSI C63.10-2013.

Test Procedure Used

ANSI C63.10-2013 – Section 11.11.3
 KDB 558074 D01 v05r02 – Section 8.5

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 25GHz (separated into two plots per channel)
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-5. Test Instrument & Measurement Setup

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST® Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch		Page 35 of 59


Test Notes

1. RBW was set to 1MHz rather than 100kHz in order to increase the measurement speed.
2. The display line shown in the following plots denotes the limit at 20dB below the fundamental emission level measured in a 100kHz bandwidth. However, since the traces in the following plots are measured with a 1MHz RBW, the display line may not necessarily appear to be 20dB below the level of the fundamental in a 1MHz bandwidth.
3. For plots showing conducted spurious emissions near the limit, the frequencies were investigated with a reduced RBW to ensure that no emissions were present.
4. All supported modulation and power schemes have been tested on the unit and only worst-case configuration is reported.

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST® Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch		Page 36 of 59




Plot 7-23. Conducted Spurious Plot (Bluetooth (HDR4), 4 Mbps, ePA – Ch. 1)




Plot 7-24. Conducted Spurious Plot (Bluetooth (HDR4), 4 Mbps, ePA – Ch. 1)

FCC ID: BCG-A2475 IC: 579C-A2475	PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 37 of 59




Plot 7-25. Conducted Spurious Plot (Bluetooth (HDR4), 4 Mbps, ePA – Ch. 38)




Plot 7-26. Conducted Spurious Plot (Bluetooth (HDR4), 4 Mbps, ePA – Ch. 38)

FCC ID: BCG-A2475 IC: 579C-A2475	PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 38 of 59



Plot 7-27. Conducted Spurious Plot (Bluetooth (HDR4), 4 Mbps, ePA – Ch. 75)



Plot 7-28. Conducted Spurious Plot (Bluetooth (HDR4), 4 Mbps, ePA – Ch. 75)

FCC ID: BCG-A2475 IC: 579C-A2475	PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 39 of 59

7.7 Radiated Spurious Emission Measurements

§15.205 §15.209 §15.247(d); RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at maximum power and at the appropriate frequencies. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 7 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-6 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [μ V/m]	Measured Distance [Meters]
Above 960.0 MHz	500	3

Table 7-6. Radiated Limits

Test Procedures Used

ANSI C63.10-2013 – Section 6.6.4.3

KDB 558074 D01 v05r02 – Section 8.6, 8.7


Test Settings

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be $\geq 2 \times$ span/RBW)
6. Sweep time = auto
7. Trace (RMS) averaging was performed over at least 100 traces

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST® Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 40 of 59	

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-6. Radiated Test Setup >1GHz

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST® <small>Proud to be part of element</small>		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch		Page 41 of 59

Test Notes

1. The optional test procedures for antenna port conducted measurements of unwanted emissions per the guidance of KDB 558074 D01 v05r02 were not used to evaluate this device for compliance to radiated limits. All radiated spurious emissions levels were measured in a radiated test setup.
2. All emissions lying in restricted bands specified in §15.205 and Section 8.10 of RSS-Gen are below the limit shown in Table 7-6.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery.
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas.
6. D is the measurement test distance and emissions 1-18GHz were measured at a 3 meters test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
7. The "-" shown in the following RSE tables are used to denote a noise floor measurement.
8. All supported modulation and power schemes have been tested on the unit and only worst case configuration is reported.

Sample Calculations

Determining Spurious Emissions Levels

- Field Strength Level [$\text{dB}_{\mu\text{V/m}}$] = Analyzer Level [dBm] + 107 + AFCL [dB/m]
- AFCL [dB/m] = Antenna Factor [dB/m] + Cable Loss [dB] – Preamplifier Gain [dB]
- Margin [dB] = Field Strength Level [$\text{dB}_{\mu\text{V/m}}$] – Limit [$\text{dB}_{\mu\text{V/m}}$]

Radiated Band Edge Measurement Offset


- The amplitude offset shown in the radiated restricted band edge plots in Section 7.7 was calculated using the formula:

$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + \text{Attenuator}) - \text{Preamplifier Gain}$$

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST Proud to be part of element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 42 of 59	

Radiated Spurious Emission Measurements (1 – 18GHz)

§15.205 §15.209 §15.247(d); RSS-Gen [8.91]




Plot 7-29. Radiated Spurious Plot Above 1GHz (4Mbps, HDR4, ePA – Ch. 1, Ant. Pol. H & V)

Bluetooth Mode:	HDR4
Power Scheme	ePA
Distance of Measurements:	3 Meters
Operating Frequency:	2404MHz
Channel:	1

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
4808.00	Avg	V	-	-	-82.08	7.97	32.89	53.98	-21.09
4808.00	Peak	V	-	-	-71.05	7.97	43.92	73.98	-30.06
12020.00	Avg	V	-	-	-84.54	17.91	40.37	53.98	-13.61
12020.00	Peak	V	-	-	-73.71	17.91	51.20	73.98	-22.78

Table 7-7. Radiated Measurements

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST® Proud to be part of 			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch			




Plot 7-30. Radiated Spurious Plot Above 1GHz (4Mbps, HDR4, ePA – Ch. 38, Ant. Pol. H & V)

Bluetooth Mode: HDR4
Power Scheme ePA
Distance of Measurements: 3 Meters
Operating Frequency: 2441MHz
Channel: 38

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
4882.00	Avg	V	-	-	-82.30	8.16	32.86	53.98	-21.12
4882.00	Peak	V	-	-	-71.27	8.16	43.89	73.98	-30.09
7323.00	Avg	V	-	-	-80.60	11.64	38.04	53.98	-15.94
7323.00	Peak	V	-	-	-71.15	11.64	47.49	73.98	-26.49
12205.00	Avg	V	-	-	-84.97	17.91	39.94	53.98	-14.04
12205.00	Peak	V	-	-	-73.14	17.91	51.77	73.98	-22.21

Table 7-8. Radiated Measurements

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST® Proud to be part of  MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 44 of 59	



Plot 7-31. Radiated Spurious Plot Above 1GHz (4Mbps, HDR4, ePA – Ch. 75, Ant. Pol. H & V)

Bluetooth Mode: HDR4
Power Scheme ePA
Distance of Measurements: 3 Meters
Operating Frequency: 2478MHz
Channel: 75


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
4956.00	Avg	V	-	-	-82.04	8.16	33.12	53.98	-20.86
4956.00	Peak	V	-	-	-71.13	8.16	44.03	73.98	-29.95
7434.00	Avg	V	-	-	-80.24	12.38	39.14	53.98	-14.84
7434.00	Peak	V	-	-	-71.03	12.38	48.35	73.98	-25.63
12390.00	Avg	V	-	-	-84.57	18.50	40.93	53.98	-13.05
12390.00	Peak	V	-	-	-72.77	18.50	52.73	73.98	-21.25

Table 7-9. Radiated Measurements


FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST® Proud to be part of 			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch			

Radiated Spurious Emission Measurements (Above 18GHz)


§15.209; RSS-Gen [8.9]



Plot 7-32. Radiated Spurious Plot Above 18GHz (4Mbps, HDR4, ePA – Ch.38, Ant. Pol. H)



Plot 7-33. Radiated Spurious Plot Above 18GHz (4Mbps, HDR4, ePA – Ch.38, Ant. Pol. V)

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST® Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 46 of 59


Radiated Restricted Band Edge Measurements
§15.205 §15.209; RSS-Gen [8.9]

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting.

The amplitude offset shown in the following plots for average measurements was calculated using the formula:

$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + \text{Attenuator}) - \text{Preamplifier Gain}$$


Bluetooth Mode:	HDR4
Power Scheme:	ePA
Measurement Distance:	3 Meters
Operating Frequency:	2404MHz
Channel:	1



Plot 7-34. Radiated Restricted Lower Band Edge Measurement (Average & Peak)

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST® Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 47 of 59	


Bluetooth Mode:	HDR4
Power Scheme:	ePA
Measurement Distance:	3 Meters
Operating Frequency:	2478MHz
Channel:	75



Plot 7-35. Radiated Restricted Upper Band Edge Measurement (Average & Peak)

FCC ID: BCG-A2475 IC: 579C-A2475	PCTEST Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021		EUT Type: Watch	Page 48 of 59


Bluetooth Mode: HDR8
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 2404MHz
 Channel: 1



Plot 7-36. Radiated Restricted Lower Band Edge Measurement (Average & Peak)

FCC ID: BCG-A2475 IC: 579C-A2475	PCTEST® Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 49 of 59	

Bluetooth Mode:	HDR8
Power Scheme:	ePA
Measurement Distance:	3 Meters
Operating Frequency:	2478MHz
Channel:	75



Plot 7-37. Radiated Restricted Upper Band Edge Measurement (Average & Peak)

FCC ID: BCG-A2475 IC: 579C-A2475	PCTEST Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 50 of 59	

7.8 Radiated Spurious Emissions Measurements – Below 1GHz

§15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 7 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-10 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [μ V/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-10. Radiated Limits

Test Procedures Used

ANSI C63.10-2013

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. VBW = 300kHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST [®] Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 51 of 59

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.




Figure 7-7. Radiated Test Setup < 30Mhz




Figure 7-8. Radiated Test Setup < 1GHz

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST® Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch		Page 52 of 59

Test Notes

1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen(8.10) are below the limit shown in Table 7-10.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes. For below 30MHz the loop antenna was positioned in 3 orthogonal planes (X front, Y side, Z top) to determine the orientation resulting in the worst case emissions.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector on emissions that were within 6dB of the limit.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. All supported modulations and power schemes have been tested on the unit and only the worst case configuration is reported.
10. Both configurations below were investigated, and the worst case has been reported.
 - a. EUT powered by AC/DC adaptor via USB-C cable with magnetic charger
 - b. EUT powered by host PC via USB-C cable with magnetic charger

Sample Calculations


Determining Spurious Emissions Levels

- Field Strength Level $[\text{dB}_{\mu\text{V/m}}]$ = Analyzer Level $[\text{dBm}]$ + 107 + AFCL $[\text{dB/m}]$
- AFCL $[\text{dB/m}]$ = Antenna Factor $[\text{dB/m}]$ + Cable Loss $[\text{dB}]$ – Preamplifier Gain $[\text{dB}]$
- Margin $[\text{dB}]$ = Field Strength Level $[\text{dB}_{\mu\text{V/m}}]$ – Limit $[\text{dB}_{\mu\text{V/m}}]$

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST[®] <small>Proud to be part of element</small>		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 53 of 59	

Radiated Spurious Emissions Measurements (Below 1GHz)


§15.209; RSS-Gen [8.9]



Plot 7-38. Radiated Spurious Plot Below 1GHz (4Mbps, ePA – Ch. 38, Pol. H & V, with (AC/DC Adapter + Magnetic Charger))

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
34.17	Max-Peak	H	100	64	-70.81	-14.00	22.19	40.00	-17.81
65.74	Max-Peak	V	250	302	-65.25	-21.00	20.75	40.00	-19.25
114.63	Max-Peak	H	100	194	-63.63	-20.00	23.37	43.52	-20.15
302.18	Max-Peak	V	100	223	-69.68	-14.00	23.32	46.02	-22.70
379.10	Max-Peak	V	100	332	-69.75	-11.00	26.25	46.02	-19.77
943.59	Max-Peak	H	250	358	-78.45	0.00	28.55	46.02	-17.47

Table 7-11. Radiated Spurious Emissions Below 1GHz (4Mbps, ePA – Ch.38, Pol. H & V, with AC/DC Adapter + Magnetic Charger)

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST® Proud to be part of  MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 54 of 59	

7.9 AC Line Conducted Emissions Measurement

§15.207; RSS-Gen [8.8]

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for AC line conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.207 and RSS-Gen (8.8).

Frequency of emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-12. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10-2013, Section 6.2

Test Settings

Quasi-Peak Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Average Field Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST [®] Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 55 of 59

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-9. Test Instrument & Measurement Setup

Test Notes

1. All modes of operation were investigated and the worst-case emissions are reported using mid channel. The emissions found were not affected by the choice of channel used during testing.
2. Both configurations below were investigated, and the worst case had been reported.
 - a. EUT powered by AC/DC adaptor via USB-C cable with magnetic charger
 - b. EUT powered by host PC via USB-C cable with magnetic charger
3. The limit for an intentional radiator from 150kHz to 30MHz are specified in Part 15.207 and RSS-Gen (8.8).
4. Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
5. QP/AV Level (dB μ V) = QP/AV Analyzer/Receiver Level (dB μ V) + Corr. (dB)
6. Margin (dB) = QP/AV Level (dB μ V) - QP/AV Limit (dB μ V)
7. Traces shown in plot are made using quasi-peak and average detectors.
8. Deviations to the Specifications: None.

FCC ID: BCG-A2475 IC: 579C-A2475	PCTEST® Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 56 of 59




Plot 7-39. AC Line Conducted Plot with Bluetooth HDR (4Mbps, ePA – Ch.38, L1, with AC/DC Adapter + Magnetic Charger)

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.157	FINAL	49.3	—	65.63	-16.30	L1	GND
0.157	FINAL	—	16.06	55.63	-39.57	L1	GND
0.485	FINAL	30.6	—	56.25	-25.66	L1	GND
0.485	FINAL	—	12.13	46.25	-34.12	L1	GND
1.777	FINAL	26.1	—	56.00	-29.90	L1	GND
1.777	FINAL	—	24.68	46.00	-21.32	L1	GND
5.334	FINAL	—	18.80	50.00	-31.20	L1	GND
5.334	FINAL	21.6	—	60.00	-38.38	L1	GND
11.112	FINAL	26.7	—	60.00	-33.32	L1	GND
11.119	FINAL	—	16.63	50.00	-33.37	L1	GND
17.777	FINAL	29.2	—	60.00	-30.80	L1	GND
17.777	FINAL	—	27.23	50.00	-22.77	L1	GND

Table 7-13. AC Line Conducted Data with Bluetooth HDR (4Mbps, ePA – Ch.38, L1, with AC/DC Adapter + Magnetic Charger)

FCC ID: BCG-A2475 IC: 579C-A2475	 MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch	Page 57 of 59	



Plot 7-40. AC Line Conducted Plot with Bluetooth HDR (4Mbps, ePA – Ch.38, N, with AC/DC Adapter + Magnetic Charger)

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.159	FINAL	37.7	—	65.52	-27.81	N	GND
0.159	FINAL	—	23.62	55.52	-31.89	N	GND
0.371	FINAL	25.2	—	58.49	-33.25	N	GND
0.371	FINAL	—	22.06	48.49	-26.43	N	GND
1.777	FINAL	—	26.05	46.00	-19.95	N	GND
1.777	FINAL	27.4	—	56.00	-28.60	N	GND
5.334	FINAL	—	17.56	50.00	-32.44	N	GND
5.334	FINAL	20.7	—	60.00	-39.27	N	GND
11.362	FINAL	—	15.64	50.00	-34.36	N	GND
11.364	FINAL	26.2	—	60.00	-33.84	N	GND
25.332	FINAL	27.1	—	60.00	-32.92	N	GND
25.332	FINAL	—	25.77	50.00	-24.23	N	GND

Table 7-14. AC Line Conducted Data with Bluetooth HDR (4Mbps, ePA – Ch.38, N, with AC/DC Adapter + Magnetic Charger)

FCC ID: BCG-A2475 IC: 579C-A2475	PCTEST® Proud to be part of 			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021	EUT Type: Watch			

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Apple Watch FCC ID: BCG-A2475 and IC: 579C-A2475** is in compliance with Part 15 Subpart C (15.247) of the FCC Rules and RSS-247 of the Innovation, Science and Economic Development Canada Rules.

FCC ID: BCG-A2475 IC: 579C-A2475	 PCTEST [®] Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2106070043-07.BCG	Test Dates: 06/08/2021 - 08/06/2021		EUT Type: Watch	Page 59 of 59