



Element Washington DC LLC

18855 Adams Court, Morgan Hill, CA 95037 USA

Tel. 410.290.6652 / Fax 410.290.6654

<http://www.element.com>



DATA REFERENCE REPORT

PART 24

Applicant Name:

Apple Inc.
One Apple Park Way
Cupertino, CA 95014
United States

Date of Testing:

4/6/2022 - 8/25/2022

Test Site/Location:

Element Washington DC LLC, Morgan Hill, CA, USA

Test Report Serial No.:

1C2205090033-02.BCG

FCC ID:	BCG-A2725
Applicant Name:	Apple Inc.

Reference Model: A2726

Variant Model: A2725 (A2855)

EUT Type: Watch

FCC Classification: PCS Licensed Transmitter Worn on Body (PCT)

FCC Rule Part: 24

Test Procedure(s): ANSI C63.26-2015, TIA-603-E-2016, KDB 971168 D01 v03r01

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

RJ Ortanez
Executive Vice President



FCC ID: BCG-A2725		PART 24 DATA REFERENCE REPORT		Approved by: Technical Manager
Test Report S/N: 1C2205090033-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 1 of 15

Version 2.1 11/9/2021

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Washington DC LLC. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

T A B L E O F C O N T E N T S

1.0	INTRODUCTION	3
1.1	Scope	3
1.2	Element Washington DC LLC Test Location	3
1.3	Test Facility / Accreditations	3
2.0	PRODUCT INFORMATION.....	4
2.1	Equipment Description	4
2.2	Device Capabilities.....	4
2.3	Antenna Description	4
2.4	Test Support Equipment.....	4
2.5	Test Configuration.....	5
2.6	Software and Firmware	5
2.7	EMI Suppression Device(s)/Modifications	5
3.0	DESCRIPTION OF TESTS	6
3.1	Measurement Procedure	6
3.2	Radiated Spurious Emissions	6
4.0	MEASUREMENT UNCERTAINTY	7
5.0	TEST EQUIPMENT CALIBRATION DATA	8
6.0	SAMPLE CALCULATIONS	9
7.0	TEST RESULTS (SPOT-CHECK DATA)	10
7.1	Summary	10
7.2	Radiated Spurious Emissions	11
7.3	Antenna BCM – EIRP.....	13
8.0	CONCLUSION.....	14
9.0	APPENDIX A: REFERENCE MODEL TEST REPORT.....	15

FCC ID: BCG-A2725	 element	PART 24 DATA REFERENCE REPORT	Approved by: Technical Manager
Test Report S/N: 1C2205090033-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch	Page 2 of 15

1.0 INTRODUCTION

1.1 Scope

Per manufacturer declaration, there are two watch device models, A2726 and A2725 (A2855), with high degree of similarity, reference model FCC ID: BCG-A2726 and variant model **FCC ID: BCG-A2725**. Both models share the same material, form factor, circuit design, and components, including antennas and their locations. The reference and variant models use the same power tables and have same tune-up tolerances.

Per FCC approved Data Referencing Test Plan, testing was done fully on the reference model FCC ID: BCG-A2726, while radiated and conducted spot-check verification has been performed on variant model FCC ID: BCG-A2725. Spot-check measurements were conducted, all measurements were investigated and found to be within acceptable tolerance.

Equipment Class	Reference Model FCC ID	Reference Report	Report Title
PCT	BCG-A2726	1C2205090032-02.BCG	RF Part 24 Test Report

Table 1-1. Reference Model Details

Reference model FCC ID: BCG-A2726 test report has been included in Appendix A

1.2 Element Washington DC LLC Test Location

These measurement tests were conducted at the Element Washington DC LLC facility located at 18855 Adams Court, Morgan Hill, CA 95037. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014 and KDB 414788 D01 v01r01.

1.3 Test Facility / Accreditations

- Element Washington DC LLC is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.02 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Washington DC LLC TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- Element Washington DC LLC facility is a registered (22831) test laboratory with the site description on file with ISED.

FCC ID: BCG-A2725	 element	PART 24 DATA REFERENCE REPORT		Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch	Page 3 of 15	



2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Apple Watch FCC ID: BCG-A2725**. The test data contained in this report pertains only to the emissions due to the EUT's licensed transmitters that operate under the provisions of Part 24.

Test Device Serial No.: DVJTX575K2, Y41RW2LYPH, LL9659703K

2.2 Device Capabilities

This device contains the following capabilities:

850/1700/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n WLAN, Bluetooth (1x, EDR, HDR4, HDR8, LE1M, LE2M), NFC.

2.3 Antenna Description

Following antenna gains provided by manufacturer were used for testing.

Band	Antenna Gain (dB)
	Antenna FCM
LTE Band 25/2	-10.2
WCDMA 1900	-10.2

Table 2-1. Highest Antenna Gain

2.4 Test Support Equipment

Test Support Equipment					
1	Apple Macbook	Model:	A1398	S/N:	C2QKP008F6F3
	w/ AC/DC Adapter	Model:	A1435	S/N:	N/A
2	Apple SPAM Cable	Model:	N/A	S/N:	N/A
	w/ Charging Dock	Model:	N/A	S/N:	CYV001700087SWK01WMP8
	w/ Cradle	Model:		S/N:	FAPS7319394000064
3	Apple Magnetic Charger	Model:	N/A	S/N:	DLC9223004YLNWL43
3	Apple Magnetic Charger	Model:	N/A	S/N:	DLC824401XHJLW04U
4	Pathfinder Swiss	Model:	920-11361-01	S/N:	DLC1212005Q18H71Y
	SiP Socket	Model:	N/A	S/N:	P1 X2339S PF 198
5	Sugar Cube Power Supply	Model:	A1365	S/N:	D292066H2NLDHLHAE
6	Store Sample Wristband	Model:	N/A	S/N:	DLC219400361YDQ2W

Table 2-2. Test Support Equipment

FCC ID: BCG-A2725		PART 24 DATA REFERENCE REPORT	Approved by: Technical Manager
Test Report S/N: 1C2205090033-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch	Page 4 of 15

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Washington DC LLC. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Version 2.1 11/9/2021

2.5 Test Configuration

The EUT was tested per the guidance of ANSI C63.26 2015, TIA-603-E-2016 and KDB 971168 D01 v03r01. See Section 7.0 of this test report for a description of the radiated emissions tests.

The worst case configuration was investigated for all combinations the various types of wristbands, metal and non-metal wristbands. The EUT was also investigated with and without wireless charger. The worst case configuration found was used for all testing.

For emissions from 1GHz – 18GHz, low, mid, and high channels were tested with highest power and worst case configuration.

The EUT was manipulated through three orthogonal planes of X-orientation (flatbed), Y-orientation (landscape), and Z-orientation (portrait) during the testing. Only the worst case emissions were reported in this test report.

This device only supports 27RBs or less for 16-QAM uplink.

Per FCC Approved Data Referencing Test Plan, Antennas BCM and FCM spot-check measurements have been conducted and reported. Spot-check Test Plan can be referred to below Table 2-3.

Technology	Test Case	FCC ID: BCG-A2725	
		Mode	Channel
WCDMA, LTE	Radiated Spurious Emissions (>1GHz)	LTE Band 5, 2, 7 Max BW, 1RB, QPSK	Low, Mid, High
WCDMA, LTE	Conducted Power	All Certified Bands: Highest BW only, 1 RB, Modulation with the highest power	Mid

Table 2-3. FCC Approved Spot-Check Test Plan

Output powers were measured and confirmed to be consistent between Reference and Variant models prior to testing.

2.6 Software and Firmware

The test was conducted with firmware version watchOS watchOS 9.0 installed on the EUT.

2.7 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: BCG-A2725	 element	PART 24 DATA REFERENCE REPORT		Approved by: Technical Manager
Test Report S/N: 1C2205090033-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch	Page 5 of 15	

3.0 DESCRIPTION OF TESTS

3.1 Measurement Procedure

The measurement procedures described in the document titled “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI C63.26-2015/TIA-603-E-2016) and “Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems” (KDB 971168 D01 v03r01) were used in the measurement of the EUT.

3.2 Radiated Spurious Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm tall test table made of Styrodur is placed on top of the turn table. A Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

The equipment under test was transmitting while connected to its integral antenna and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer.

For radiated spurious emissions measurements and calculations, conversion method is used per the formulas in KDB 971168 Section 5.8.4. Field Strength (EIRP) is calculated using the following formulas:

$$E_{[\text{dB}\mu\text{V}/\text{m}]} = \text{Measured amplitude level}_{[\text{dBm}]} + 107 + \text{Cable Loss}_{[\text{dB}]} + \text{Antenna Factor}_{[\text{dB}/\text{m}]} \\ \text{And} \\ \text{EIRP}_{[\text{dBm}]} = E_{[\text{dB}\mu\text{V}/\text{m}]} + 20\log D - 104.8;$$

Where D is the measurement distance in meters.

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014.

Per KDB 414788 D01 v01r01, radiated emission test sites other than open-field test sites (e.g., shielded anechoic chambers), may be employed for emission measurements below 30MHz if characterized so that the measurements correspond to those obtained at an open-field test site. To determine test site equivalency, a reference sample transmitting at 149kHz was measured on an open field test site (asphalt with no ground plane) and then measured in the 3m semi-anechoic chamber. A calibrated 60cm loop antenna was used while the reference device was rotated through the X, Y and Z axis in order to capture the worst case level. A maximum deviation of 2.77dB at 149kHz was measured when comparing the 3 meter semi-anechoic chamber to the open field site.

Radiated spurious emission levels are investigated with the receive antenna horizontally and vertically polarized per ANSI C63.26-2015 and TIA-603-E-2016.

FCC ID: BCG-A2725	 element	PART 24 DATA REFERENCE REPORT		Approved by: Technical Manager
Test Report S/N: 1C2205090033-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 6 of 15

4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.23-2012. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (\pm dB)
Conducted Bench Top Measurements	1.77
Radiated Disturbance (<30MHz)	4.38
Radiated Disturbance (30MHz-1GHz)	4.75
Radiated Disturbance (1-18GHz)	5.20
Radiated Disturbance (>18GHz)	4.72

FCC ID: BCG-A2725	 element	PART 24 DATA REFERENCE REPORT		Approved by: Technical Manager
Test Report S/N: 1C2205090033-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch	Page 7 of 15	

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent Technologies	N9030A	3Hz-44GHz PXA Signal Analyzer	6/10/2022	Annual	6/10/2023	MY49430244
ATM	180-442A-KF	20dB Nominal Gain Horn Antenna	8/13/2021	Annual	8/13/2022	T058701-01
ESPEC	SU-241	Tabletop Temperature Chamber	10/26/2021	Annual	10/26/2022	92009574
ETS-Lindgren	3142E	BiConiLog Antenna (30MHz - 6GHz)	10/21/2021	Annual	10/21/2022	208204
ETS-Lindgren	3117	Double Ridged Guide Antenna (1-18 GHz)	5/11/2022	Annual	5/11/2023	205956
Keysight Technology	N9040B	UXA Signal Analyzer	2/8/2022	Annual	2/8/2023	MY57212015
Rohde & Schwarz	TS-PR18	Pre-Amplifier (1GHz - 18GHz)	1/6/2022	Annual	1/6/2023	101639
Rohde & Schwarz	FSV40	Signal Analyzer (10Hz-40GHz)	3/4/2022	Annual	3/4/2023	101619
Rohde & Schwarz	ESW26	EMI Test Receiver	5/19/2022	Annual	5/19/2023	101299
Rohde & Schwarz	TS-PR8	Pre-Amplifier (30MHz - 8GHz)	1/6/2022	Annual	1/6/2023	102327
Rohde & Schwarz	ESW44	EMI Test Receiver	12/2/2021	Annual	12/2/2022	101570
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	10/11/2021	Annual	10/11/2022	161616
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	11/4/2021	Annual	11/4/2022	151888
Rohde & Schwarz	TS-PR1840	Pre-Amplifier (18GHz - 40GHz)	4/18/2022	Annual	4/18/2023	100050
Rohde & Schwarz	TC-TA18	Cross Polarized Vivaldi Antenna (400MHz-18GHz)	1/25/2022	Annual	1/25/2023	101063
Rohde & Schwarz	HFH2-Z2	Loop Antenna	4/3/2022	Annual	4/3/2023	100546

Table 5-1. Test Equipment

Notes:

1. For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

FCC ID: BCG-A2725	 element	PART 24 DATA REFERENCE REPORT		Approved by: Technical Manager
Test Report S/N: 1C2205090033-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch	Page 8 of 15	

6.0 SAMPLE CALCULATIONS

Spurious Radiated Emission

Example: Spurious emission at 3700.40 MHz

The receive spectrum analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3700.40 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.50 dBm so this harmonic was 25.50 dBm $- (-24.80) = 50.3$ dBc.

FCC ID: BCG-A2725	 element	PART 24 DATA REFERENCE REPORT		Approved by: Technical Manager
Test Report S/N: 1C2205090033-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 9 of 15

7.0 TEST RESULTS (SPOT-CHECK DATA)

7.1 Summary

Company Name: Apple Inc.
 FCC ID: BCG-A2725
 FCC Classification: PCS Licensed Transmitter Worn on Body (PCT)
 Mode(s): WCDMA/LTE

Technology	Test Configurations					Reference Model	Variant Model	Delta
	Test Description	Modulation	BW / RB Config	Channel	Measurement Frequency [MHz]	FCC ID: BCG-A2726	FCC ID: BCG-A2725	
						Average [dBm]	Average [dBm]	Average [dB]
LTE Band 2	Radiated Spurious Emissions	QPSK	20MHz / 1/50 RB	L	3720.0	-62.45	-62.03	0.42
LTE Band 2	Radiated Spurious Emissions	QPSK	20MHz / 1/50 RB	M	3760.0	-60.77	-59.90	0.87
LTE Band 2	Radiated Spurious Emissions	QPSK	20MHz / 1/50 RB	H	3800.0	-60.24	-60.83	0.59
LTE Band 2	Conducted Powers	QPSK	20MHz / 1/0 RB	M	1882.5	24.00	24.36	0.36
LTE Band 25	Conducted Powers	QPSK	20MHz / 1/0 RB	M	1882.5	24.02	24.13	0.11
WCDMA B2	Conducted Powers	QPSK	5MHz	M	1880.0	23.91	23.68	0.23

Table 7-1. Worst Case Spot-Check Results


Spot-checks were conducted, all measurements were investigated and found to be within acceptable tolerance in accordance with FCC Approved Data Referencing Test Plan.

FCC ID: BCG-A2725	 element	PART 24 DATA REFERENCE REPORT	Approved by: Technical Manager
Test Report S/N: 1C2205090033-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch	Page 10 of 15

7.2 Radiated Spurious Emissions

§2.1053, 24.238(a)

LTE Band 2



Plot 7-1. Radiated Spurious Emission above 1GHz (LTE Band 2)

Bandwidth (MHz):	20
Frequency (MHz):	1860.0
RB / Offset:	1 / 50

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB μ V/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
3720.0	H	150	206	-77.12	3.35	33.23	-62.03	-13.00	-49.03
5580.0	H	-	-	-80.42	6.97	33.55	-61.70	-13.00	-48.70
7440.0	H	-	-	-80.87	8.15	34.28	-60.98	-13.00	-47.98
9300.0	H	-	-	-82.96	10.70	34.74	-60.51	-13.00	-47.51

Table 7-2. Radiated Spurious Data (LTE Band 2 – Low Channel)

Bandwidth (MHz):	20
Frequency (MHz):	1880.0
RB / Offset:	1 / 50

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB μ V/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
3760.0	H	141	203	-75.26	3.62	35.36	-59.90	-13.00	-46.90
5640.0	H	-	-	-81.31	7.51	33.20	-62.05	-13.00	-49.05
7520.0	H	-	-	-80.54	8.68	35.14	-60.12	-13.00	-47.12
9400.0	H	-	-	-80.23	10.03	36.80	-58.45	-13.00	-45.45

Table 7-3. Radiated Spurious Data (LTE Band 2 – Mid Channel)

FCC ID: BCG-A2725	 element	PART 24 DATA REFERENCE REPORT				Approved by: Technical Manager
Test Report S/N: 1C2205090033-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch				

Bandwidth (MHz):	20
Frequency (MHz):	1900.0
RB / Offset:	1 / 50

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB μ V/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
3800.00	H	137	195	-76.30	3.73	34.43	-60.83	-13.00	-47.83
5700.00	H	117	161	-78.63	6.82	35.19	-60.07	-13.00	-47.07
7600.00	H	-	-	-80.72	9.27	35.55	-59.71	-13.00	-46.71
9500.00	H	-	-	-81.05	11.41	37.36	-57.89	-13.00	-44.89

Table 7-4. Radiated Spurious Data (LTE Band 2 – High Channel)

FCC ID: BCG-A2725	 element	PART 24 DATA REFERENCE REPORT		Approved by: Technical Manager
Test Report S/N: 1C2205090033-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 12 of 15

7.3 Antenna FCM – EIRP

LTE-B2

Bandwidth	Mod.	Frequency [MHz]	Ant. Gain [dBi]	RB Size/Offset	Conducted Power [dBm]	EIRP [dBm]	EIRP [mW]	EIRP Limit [dBm]	Margin [dB]
20 MHz	QPSK	1880.0	-10.20	1 / 0	24.36	14.16	26.062	33.01	-18.85

Table 7-5. Antenna FCM EIRP Data (LTE Band 2)

LTE-B25

Bandwidth	Mod.	Frequency [MHz]	Ant. Gain [dBi]	RB Size/Offset	Conducted Power [dBm]	EIRP [dBm]	EIRP [mW]	EIRP Limit [dBm]	Margin [dB]
20 MHz	QPSK	1882.5	-10.20	1 / 0	24.13	13.93	24.717	33.01	-19.08

Table 7-6. Antenna FCM EIRP Data (LTE Band 25)

WCDMA B2

Frequency [MHz]	Mode	Conducted Power [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [mW]	EIRP Limit [dBm]	Margin [dB]
1880.00	WCDMA1900	23.68	-10.20	13.48	22.284	33.01	-19.53

Table 7-7. Antenna FCM EIRP Data (WCDMA Band 2)

FCC ID: BCG-A2725	 element	PART 24 DATA REFERENCE REPORT			Approved by: Technical Manager
Test Report S/N: 1C2205090033-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch			

Version 2.1 11/9/2021

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Washington DC LLC. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

8.0 CONCLUSION

The spot-check data measured for variant model **FCC ID: BCG-A2725** is in tolerance with reference model FCC ID: BCG-A2726 per FCC Approved Data Referencing Test Plan.

FCC ID: BCG-A2725	 element	PART 24 DATA REFERENCE REPORT		Approved by: Technical Manager
Test Report S/N: 1C2205090033-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 14 of 15

9.0 APPENDIX A: REFERENCE MODEL TEST REPORT

Attached is the test report (1C2205090032-02.BCG) from reference model FCC ID: BCG-A2726, which includes referenced data results.

FCC ID: BCG-A2725	 element	PART 24 DATA REFERENCE REPORT		Approved by: Technical Manager
Test Report S/N: 1C2205090033-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 15 of 15



Element Washington DC LLC

18855 Adams Court, Morgan Hill, CA 95037 USA

Tel. 410.290.6652 / Fax 410.290.6654

<http://www.element.com>



PART 24 MEASUREMENT REPORT

Applicant Name:

Apple Inc.
One Apple Park Way
Cupertino, CA 95014
United States

Date of Testing:

4/6/2022 - 8/25/2022

Test Site/Location:

Element Washington DC LLC.
Morgan Hill, CA, USA

Test Report Serial No.:

1C2205090032-02.BCG

FCC ID:	BCG-A2726
Applicant Name:	Apple Inc.

Application Type:

Certification

Model:

A2726

EUT Type:

Watch

FCC Classification:

PCS Licensed Transmitter Worn on Body (PCT)

FCC Rule Part:

24

Test Procedure(s):

ANSI C63.26-2015, TIA-603-E-2016, KDB 971168 D01 v03r01

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

RJ Ortanez
Executive Vice President



CERT #2041.02

FCC ID: BCG-A2726	element	PART 24 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 1 of 90


V2.1 11/9/2021

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Washington DC LLC. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


T A B L E O F C O N T E N T S

1.0	INTRODUCTION	4
1.1	Scope	4
1.2	Element Washington DC LLC Test Location	4
1.3	Test Facility / Accreditations	4
2.0	PRODUCT INFORMATION	5
2.1	Equipment Description	5
2.2	Device Capabilities	5
2.3	Antenna Description	6
2.4	Test Support Equipment	6
2.5	Test Configuration	7
2.6	Software and Firmware	7
2.7	EMI Suppression Device(s)/Modifications	7
3.0	DESCRIPTION OF TESTS	8
3.1	Evaluation Procedure	8
3.2	Radiated Spurious Emissions	8
4.0	MEASUREMENT UNCERTAINTY	9
5.0	TEST EQUIPMENT CALIBRATION DATA	10
6.0	SAMPLE CALCULATIONS	11
7.0	TEST RESULTS	12
7.1	Summary	12
7.2	Occupied Bandwidth	13
7.3	Spurious and Harmonic Emissions at Antenna Terminal	21
7.4	Band Edge Emissions at Antenna Terminal	33
7.5	Peak-Average Ratio	61
7.6	Radiated Power (EIRP)	75
7.7	Radiated Spurious Emissions	79
7.8	Frequency Stability / Temperature Variation	86
8.0	CONCLUSION	89
9.0	APPENDIX A	90

FCC ID: BCG-A2726	PART 24 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch	Page 2 of 90



PART 24 MEASUREMENT REPORT



Mode	Bandwidth	Modulation	Tx Frequency Range [MHz]	OBW [MHz]	PAR at 0.1% [dB]	EIRP		Emission Designator
						Max. Power [W]	Max. Power [dBm]	
WCDMA1900	5 MHz	Spread Spectrum	1852.4 - 1907.6	4.0946	3.25	23.496	13.71	4M09F9W
Band 2	1.4 MHz	QPSK	1850.7 - 1909.3	1.1090	5.77	25.586	14.08	1M11G7W
		16QAM	1850.7 - 1909.3	1.1137	6.54	21.380	13.30	1M11D7W
	3 MHz	QPSK	1851.5 - 1908.5	2.7374	5.78	24.717	13.93	2M74G7W
		16QAM	1851.5 - 1908.5	2.7331	6.48	21.380	13.30	2M73D7W
	5 MHz	QPSK	1852.5 - 1907.5	4.5735	5.85	25.119	14.00	4M57G7W
		16QAM	1852.5 - 1907.5	4.5720	6.45	21.979	13.42	4M57D7W
	10MHz	QPSK	1855 - 1905	9.1282	5.76	25.468	14.06	9M13G7W
		16QAM	1855 - 1905	5.4862	6.37	22.131	13.45	5M49D7W
	15 MHz	QPSK	1857.5 - 1902.5	13.6902	5.97	25.061	13.99	13M7G7W
		16QAM	1857.5 - 1902.5	6.4140	6.34	21.478	13.32	6M41D7W
Band 25	20 MHz	QPSK	1860 - 1900	18.3140	5.66	25.003	13.98	18M3G7W
		16QAM	1860 - 1900	8.1037	6.34	21.878	13.40	8M10D7W
	1.4 MHz	QPSK	1850.7 - 1914.3	1.1090	5.72	25.293	14.03	1M11G7W
		16QAM	1850.7 - 1914.3	1.1137	6.49	21.232	13.27	1M11D7W
	3 MHz	QPSK	1851.5 - 1913.5	2.7374	5.71	24.155	13.83	2M74G7W
		16QAM	1851.5 - 1913.5	2.7331	6.45	21.281	13.28	2M73D7W
	5 MHz	QPSK	1852.5 - 1912.5	4.5735	5.80	24.660	13.92	4M57G7W
		16QAM	1852.5 - 1912.5	4.5720	6.46	21.878	13.40	4M57D7W
	10 MHz	QPSK	1855 - 1910	9.1282	5.75	24.547	13.90	9M13G7W
		16QAM	1855 - 1910	5.4862	6.40	21.827	13.39	5M49D7W
	15 MHz	QPSK	1857.5 - 1907.5	13.6902	6.06	24.774	13.94	13M7G7W
		16QAM	1857.5 - 1907.5	6.4140	6.39	21.878	13.40	6M41D7W
	20 MHz	QPSK	1860 - 1905	18.3140	5.71	25.119	14.00	18M3G7W
		16QAM	1860 - 1905	8.1037	6.35	21.627	13.35	8M10D7W

EUT Overview

FCC ID: BCG-A2726	PART 24 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch	Page 3 of 90	

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 Element Washington DC LLC Test Location

These measurement tests were conducted at the Element Washington DC LLC facility located at 18855 Adams Court, Morgan Hill, CA 95037. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014 and KDB 414788 D01 v01r01.

1.3 Test Facility / Accreditations

Measurements were performed at Element Washington DC LLC located in Morgan Hill, CA 95037, U.S.A.

- Element Washington DC LLC is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.02 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Washington DC LLC TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- Element Washington DC LLC facility is a registered (22831) test laboratory with the site description on file with ISED.

FCC ID: BCG-A2726	 element	PART 24 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 4 of 90

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Apple Watch FCC ID:BCG-A2726**. The test data contained in this report pertains only to the emissions due to the EUT's licensed transmitters that operate under the provisions of Part 24.

Test Device Serial No.: J0JHQYCM6X, N215GQLWGK, FN622060J2416TT4E

2.2 Device Capabilities

This device contains the following capabilities:

850/1700/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n WLAN, Bluetooth (1x, EDR, HDR4, HDR8, LE1M, LE2M), NFC.

This device supports simultaneous transmission operations, which allows for multiple transmitters to transmit simultaneously on the same antenna. The table below shows all configurations possible.

Simultaneous Tx Config	Antenna FCM		
	WLAN	Bluetooth	LTE
	802.11 b/g/n	BDR, EDR, HDR4/8, LE1/2M	Mid/High Band
Config 1	✓	✗	✓
Config 2	✗	✓	✓

Table 2-1. Simultaneous Transmission Configurations

✓ = Support; ✗ = Not Support

Note:

All the above simultaneous transmission configurations have been tested and the worst case configuration was found to be config 1 and reported in RF WLAN and RF Part 27b test reports.

FCC ID: BCG-A2726	 element	PART 24 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 5 of 90

2.3 Antenna Description

Following antenna gains provided by manufacturer were used for testing.

Band	Antenna Gain [dBi]
	Antenna FCM
LTE Band 25/2	-10.2
WCDMA 1900	-10.2

Table 2-2. Highest Antenna Gain

Note: Antenna Specifications has been attached to Appendix A

2.4 Test Support Equipment

1	Apple Macbook w/ AC/DC Adapter	Model: Model:	A1398 A1435	S/N: S/N:	C2QKP008F6F3 N/A
2	SPAM 2.3-Diags Cable w/ Charging Dock w/ Cradle	Model: Model: Model:	N/A N/A S/N:	S/N: S/N: S/N:	F0571702CMN0000326 CYV001700087SWK01WMP8 FAPS7319394000064
3	Apple Magnetic Charger	Model:	N/A	S/N:	DLC9223004YLNWL43
3	Apple Magnetic Charger	Model:	N/A	S/N:	DLC824401XHJLW04U
4	Pathfinder Swiss SiP Socket	Model: Model:	920-11361-01 N/A	S/N: S/N:	DLC1212005Q18H71Y P1 X2339S PF 198
5	Sugar Cube Power Supply	Model:	A1365	S/N:	D292066H2NLDHLHAE
6	Store Sample Wristband	Model:	N/A	S/N:	DLC219400361YDQ2W

Table 2-3. Test Support Equipment

FCC ID: BCG-A2726	PART 24 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 6 of 90

2.5 Test Configuration

The EUT was tested per the guidance of ANSI C63.26-2015, TIA-603-E-2016 and KDB 971168 D01 v03r01. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

The worst case configuration was investigated for all combinations of the various types of wristbands, metal and non-metal wristbands. The EUT was also investigated with and without wireless charger. The worst case configuration found was used for all testing.

For emissions from 1GHz – 18GHz, low, mid, and high channels were tested with highest power and worst case configuration. The emissions below 1GHz and above 18GHz were tested with the highest transmitting power and the worst case channel.

This device only supports 27RBs or less for 16-QAM uplink.

The EUT was manipulated through three orthogonal planes of X-orientation (flatbed), Y-orientation (landscape), and Z-orientation (portrait) during the testing. Only the worst case emissions were reported in this test report.

2.6 Software and Firmware

The test was conducted with firmware version watchOS 9.0 installed on the EUT.

2.7 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: BCG-A2726	PART 24 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch	Page 7 of 90

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the document titled “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI C63.26-2015/TIA-603-E-2016) and “Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems” (KDB 971168 D01 v03r01) were used in the measurement of the EUT.

Deviation from Measurement Procedure.....None

3.2 Radiated Spurious Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm tall test table made of Styrodur is placed on top of the turn table. A Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

The equipment under test was transmitting while connected to its integral antenna and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer.

For radiated spurious emissions measurements and calculations, conversion method is used per the formulas in KDB 971168 Section 5.8.4. Field Strength (EIRP) is calculated using the following formulas:

$$E_{[\text{dB}\mu\text{V}/\text{m}]} = \text{Measured amplitude level}_{[\text{dBm}]} + 107 + \text{Cable Loss}_{[\text{dB}]} + \text{Antenna Factor}_{[\text{dB}/\text{m}]} \\ \text{And}$$

$$\text{EIRP}_{[\text{dBm}]} = E_{[\text{dB}\mu\text{V}/\text{m}]} + 20\log D - 104.8; \text{ where } D \text{ is the measurement distance in meters.}$$

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014.

Per KDB 414788 D01 v01r01, radiated emission test sites other than open-field test sites (e.g., shielded anechoic chambers), may be employed for emission measurements below 30MHz if characterized so that the measurements correspond to those obtained at an open-field test site. To determine test site equivalency, a reference sample transmitting at 149kHz was measured on an open field test site (asphalt with no ground plane) and then measured in the 3m semi-anechoic chamber. A calibrated 60cm loop antenna was used while the reference device was rotated through the X, Y and Z axis in order to capture the worst case level. A maximum deviation of 2.77dB at 149kHz was measured when comparing the 3 meter semi-anechoic chamber to the open field site.

Radiated spurious emission levels are investigated with the receive antenna horizontally and vertically polarized per ANSI C63.26-2015 and TIA-603-E-2016.

FCC ID: BCG-A2726	PART 24 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch	Page 8 of 90

4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.23-2012. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (\pm dB)
Conducted Bench Top Measurements	1.77
Radiated Disturbance (<30MHz)	4.38
Radiated Disturbance (30MHz-1GHz)	4.75
Radiated Disturbance (1-18GHz)	5.20
Radiated Disturbance (>18GHz)	4.72

FCC ID: BCG-A2726	PART 24 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch	Page 9 of 90

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent Technologies	N9030A	3Hz-44GHz PXA Signal Analyzer	6/10/2022	Annual	6/10/2023	MY49430244
ATM	180-442A-KF	20dB Nominal Gain Horn Antenna	8/13/2021	Annual	8/13/2022	T058701-01
ESPEC	SU-241	Tabletop Temperature Chamber	10/26/2021	Annual	10/26/2022	92009574
ETS-Lindgren	3142E	BiConiLog Antenna (30MHz - 6GHz)	10/21/2021	Annual	10/21/2022	208204
ETS-Lindgren	3117	Double Ridged Guide Antenna (1-18 GHz)	5/11/2022	Annual	5/11/2023	205956
Keysight Technology	N9040B	UXA Signal Analyzer	2/8/2022	Annual	2/8/2023	MY57212015
Rohde & Schwarz	TS-PR18	Pre-Amplifier (1GHz - 18GHz)	1/6/2022	Annual	1/6/2023	101639
Rohde & Schwarz	FSV40	Signal Analyzer (10Hz-40GHz)	3/4/2022	Annual	3/4/2023	101619
Rohde & Schwarz	ESW26	EMI Test Receiver	5/19/2022	Annual	5/19/2023	101299
Rohde & Schwarz	TS-PR8	Pre-Amplifier (30MHz - 8GHz)	1/6/2022	Annual	1/6/2023	102327
Rohde & Schwarz	ESW44	EMI Test Receiver	12/2/2021	Annual	12/2/2022	101570
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	10/11/2021	Annual	10/11/2022	161616
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	11/4/2021	Annual	11/4/2022	151888
Rohde & Schwarz	TS-PR1840	Pre-Amplifier (18GHz - 40GHz)	4/18/2022	Annual	4/18/2023	100050
Rohde & Schwarz	TC-TA18	Cross Polarized Vivaldi Antenna (400MHz-18GHz)	1/25/2022	Annual	1/25/2023	101063
Rohde & Schwarz	HFH2-Z2	Loop Antenna	4/3/2022	Annual	4/3/2023	100546

Table 5-1. Test Equipment

Notes:

1. For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

FCC ID: BCG-A2726	element PART 24 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		

6.0 SAMPLE CALCULATIONS

Emission Designator

Emission Designator = 4M16F9W

WCDMA BW = 4.16 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

QPSK Modulation

Emission Designator = 8M62G7W

BW = 8.62 MHz

G = Phase Modulation

7 = Quantized/Digital Info

W = Combination of Any

QAM Modulation

Emission Designator = 8M45D7W

BW = 8.45 MHz

D = Amplitude/Angle Modulated

7 = Quantized/Digital Info

W = Combination of Any

Spurious Radiated Emission

Example: Spurious emission at 3700.40 MHz

The receive spectrum analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3700.40 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.50 dBm so this harmonic was 25.50 dBm $- (-24.80) = 50.3$ dBc.

FCC ID: BCG-A2726	PART 24 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch	Page 11 of 90

7.0 TEST RESULTS

7.1 Summary

Company Name: Apple Inc.
 FCC ID: BCG-A2726
 FCC Classification: PCS Licensed Transmitter Worn on Body (PCT)
 Mode(s): WCDMA/LTE

Test Condition	Test Description	FCC Part Section(s)	Test Limit	Test Result	Reference
CONDUCTED	Occupied Bandwidth	2.1049	N/A	N/A	Section 7.2
	Conducted Band Edge / Spurious Emissions	2.1051, 24.238(a)	-13 dBm at Band Edge and for all out-of-band emissions	PASS	Sections 7.3, 7.4
	Peak-Average Ratio	24.232(d)	< 13 dB	PASS	Section 7.5
	Transmitter Conducted Output Power	2.1046	N/A	N/A	See RF Exposure Report
	Frequency Stability	2.1055, 24.235	Fundamental emissions stay within authorized frequency block over the temperature and voltage range as tested	PASS	Section 7.8
	Effective Radiated Power / Equivalent Isotropic Radiated Power	24.232(c)	< 2 Watts max. EIRP	PASS	Section 7.6
RADIATED	Radiated Spurious Emissions	2.1053, 24.238(a)	-13 dBm for all out-of-band emissions	PASS	Section 7.7

Table 7-1. Summary of Test Results

Notes:

1. All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
2. The analyzer plots were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
3. All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
4. All conducted emissions measurements are performed with automated test software to capture the corresponding plots necessary to show compliance. The measurement software utilized is Element EMC Software Tool v1.1.

FCC ID: BCG-A2726	 element	PART 24 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch	Page 12 of 90	

7.2 Occupied Bandwidth

§2.1049

Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Procedure Used

KDB 971168 D01 v03r01 – Section 4.2

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW \geq 3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-1. Test Instrument & Measurement Setup

Test Notes


None.

FCC ID: BCG-A2726	PART 24 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch	Page 13 of 90

LTE Band 25/2




Plot 7-1. Occupied Bandwidth Plot (LTE Band 25/2 - 1.4MHz QPSK - Full RB Configuration)



Plot 7-2. Occupied Bandwidth Plot (LTE Band 25/2 - 1.4MHz 16-QAM - Full RB Configuration)

FCC ID: BCG-A2726	 element	PART 24 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 14 of 90




Plot 7-3. Occupied Bandwidth Plot (LTE Band 25/2 - 3MHz QPSK - Full RB Configuration)




Plot 7-4. Occupied Bandwidth Plot (LTE Band 25/2 - 3MHz 16-QAM - Full RB Configuration)

FCC ID: BCG-A2726	PART 24 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 15 of 90




Plot 7-5. Occupied Bandwidth Plot (LTE Band 25/2 - 5MHz QPSK - Full RB Configuration)




Plot 7-6. Occupied Bandwidth Plot (LTE Band 25/2 - 5MHz 16-QAM - Full RB Configuration)

FCC ID: BCG-A2726	PART 24 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 16 of 90



Plot 7-7. Occupied Bandwidth Plot (LTE Band 25/2 - 10MHz QPSK - Full RB Configuration)




Plot 7-8. Occupied Bandwidth Plot (LTE Band 25/2 - 10MHz 16-QAM - Full RB Configuration)

FCC ID: BCG-A2726	PART 24 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 17 of 90




Plot 7-9. Occupied Bandwidth Plot (LTE Band 25/2 - 15MHz QPSK - Full RB Configuration)




Plot 7-10. Occupied Bandwidth Plot (LTE Band 25/2 - 15MHz 16-QAM - Full RB Configuration)

FCC ID: BCG-A2726	PART 24 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 18 of 90




Plot 7-11. Occupied Bandwidth Plot (LTE Band 25/2 - 20MHz QPSK - Full RB Configuration)



Plot 7-12. Occupied Bandwidth Plot (LTE Band 25/2 - 20MHz 16-QAM - Full RB Configuration)

FCC ID: BCG-A2726	PART 24 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 19 of 90

WCDMA PCS



Plot 7-13. Occupied Bandwidth Plot (WCDMA, Ch. 9400)

FCC ID: BCG-A2726	PART 24 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 20 of 90

7.3 Spurious and Harmonic Emissions at Antenna Terminal

§2.1051, §24.238(a)

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + 10 \log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v03r01 – Section 6.0

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 20GHz (separated into at least two plots per channel)
2. Detector = RMS
3. Trace mode = trace average for continuous emissions, max hold for pulse emissions
4. Sweep time = auto couple
5. The trace was allowed to stabilize
6. Please see test notes below for RBW and VBW settings

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-2. Test Instrument & Measurement Setup


FCC ID: BCG-A2726	PART 24 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch	Page 21 of 90

Test Notes


1. Per Part 24, compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth 100 kHz or greater for measurements below 1GHz. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: BCG-A2726	 element			PART 24 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch			Page 22 of 90

LTE Band 25/2




Plot 7-14. Conducted Spurious Plot (LTE Band 25/2 - 20MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)



Plot 7-15. Conducted Spurious Plot (LTE Band 25/2 - 20MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)

FCC ID: BCG-A2726	 element	PART 24 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 23 of 90




Plot 7-16. Conducted Spurious Plot (LTE Band 25/2 - 20MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-17. Conducted Spurious Plot (LTE Band 25/2 - 20MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: BCG-A2726	PART 24 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 24 of 90



Plot 7-18. Conducted Spurious Plot (LTE Band 25/2 - 20MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)




Plot 7-19. Conducted Spurious Plot (LTE Band 25/2 - 20MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: BCG-A2726	PART 24 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 25 of 90




Plot 7-20. Conducted Spurious Plot (LTE Band 25/2 - 20MHz QPSK - RB Size 1, RB Offset 0 - High Channel)



Plot 7-21. Conducted Spurious Plot (LTE Band 25/2 - 20MHz QPSK - RB Size 1, RB Offset 0 - High Channel)


FCC ID: BCG-A2726	PART 24 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 26 of 90




Plot 7-22. Conducted Spurious Plot (LTE Band 25/2 - 20MHz QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: BCG-A2726	PART 24 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 27 of 90

WCDMA PCS




Plot 7-23. Conducted Spurious Plot (WCDMA Ch. 9262)




Plot 7-24. Conducted Spurious Plot (WCDMA Ch. 9262)

FCC ID: BCG-A2726	 element	PART 24 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 28 of 90




Plot 7-25. Conducted Spurious Plot (WCDMA Ch. 9262)




Plot 7-26. Conducted Spurious Plot (WCDMA Ch. 9400)

FCC ID: BCG-A2726	element	PART 24 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch	Page 29 of 90	




Plot 7-27. Conducted Spurious Plot (WCDMA Ch. 9400)




Plot 7-28. Conducted Spurious Plot (WCDMA Ch. 9400)

FCC ID: BCG-A2726	element	PART 24 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch	Page 30 of 90	




Plot 7-29. Conducted Spurious Plot (WCDMA Ch. 9538)



Plot 7-30. Conducted Spurious Plot (WCDMA Ch. 9538)

FCC ID: BCG-A2726	 element	PART 24 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 31 of 90



Plot 7-31. Conducted Spurious Plot (WCDMA Ch. 9538)

FCC ID: BCG-A2726	PART 24 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 32 of 90

7.4 Band Edge Emissions at Antenna Terminal

§2.1051, §24.238(a)

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + 10 \log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v03r01 – Section 6.0

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW \geq 1% of the emission bandwidth
4. VBW \geq 3 x RBW
5. Detector = RMS
6. Number of sweep points \geq 2 x Span/RBW
7. Trace mode = trace average for continuous emissions, max hold for pulse emissions
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-3. Test Instrument & Measurement Setup


FCC ID: BCG-A2726	PART 24 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch	Page 33 of 90

Test Notes

1. Per 24.238(a), in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: BCG-A2726	PART 24 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch	Page 34 of 90


LTE Band 25



FCC ID: BCG-A2726	 element	PART 24 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 35 of 90




Plot 7-34. Upper Band Edge Plot (LTE Band 25 – 1.4MHz QPSK – Full RB Configuration)




Plot 7-35. Extended Upper Band Edge Plot (LTE Band 25 – 1.4MHz QPSK – Full RB Configuration)

FCC ID: BCG-A2726	PART 24 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 36 of 90



Plot 7-36. Lower Band Edge Plot (LTE Band 25 – 3MHz QPSK – Full RB Configuration)




Plot 7-37. Extended Lower Band Edge Plot (LTE Band 25 – 3MHz QPSK – Full RB Configuration)

FCC ID: BCG-A2726	PART 24 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 37 of 90




Plot 7-38. Upper Band Edge Plot (LTE Band 25 – 3MHz QPSK – Full RB Configuration)




Plot 7-39. Extended Upper Band Edge Plot (LTE Band 25 – 3MHz QPSK – Full RB Configuration)

FCC ID: BCG-A2726	PART 24 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 38 of 90



Plot 7-40. Lower Band Edge Plot (LTE Band 25 – 5MHz QPSK – Full RB Configuration)




Plot 7-41. Extended Lower Band Edge Plot (LTE Band 25 – 5MHz QPSK – Full RB Configuration)

FCC ID: BCG-A2726	PART 24 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 39 of 90




Plot 7-42. Upper Band Edge Plot (LTE Band 25 – 5MHz QPSK – Full RB Configuration)




Plot 7-43. Extended Upper Band Edge Plot (LTE Band 25 – 5MHz QPSK – Full RB Configuration)

FCC ID: BCG-A2726	PART 24 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 40 of 90




Plot 7-44. Lower Band Edge Plot (LTE Band 25 – 10MHz QPSK – Full RB Configuration)



Plot 7-45. Extended Lower Band Edge Plot (LTE Band 25 – 10MHz QPSK – Full RB Configuration)

FCC ID: BCG-A2726	PART 24 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 41 of 90




Plot 7-46. Upper Band Edge Plot (LTE Band 25 – 10MHz QPSK – Full RB Configuration)




Plot 7-47. Extended Upper Band Edge Plot (LTE Band 25 – 10MHz QPSK – Full RB Configuration)

FCC ID: BCG-A2726	PART 24 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 42 of 90



Plot 7-48. Lower Band Edge Plot (LTE Band 25 – 15MHz QPSK – Full RB Configuration)



Plot 7-49. Extended Lower Band Edge Plot (LTE Band 25 – 15MHz QPSK – Full RB Configuration)

FCC ID: BCG-A2726	PART 24 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 43 of 90




Plot 7-50. Upper Band Edge Plot (LTE Band 25 – 15MHz QPSK – Full RB Configuration)




Plot 7-51. Extended Upper Band Edge Plot (LTE Band 25 – 15MHz QPSK – Full RB Configuration)

FCC ID: BCG-A2726	PART 24 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 44 of 90



Plot 7-52. Lower Band Edge Plot (LTE Band 25 – 20MHz QPSK – Full RB Configuration)



Plot 7-53. Extended Lower Band Edge Plot (LTE Band 25 – 20MHz QPSK – Full RB Configuration)

FCC ID: BCG-A2726	PART 24 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2205090032-02.BCG	Test Dates: 4/6/2022 - 8/25/2022	EUT Type: Watch		Page 45 of 90