



Element Materials Technology

(formerly PCTEST)

18855 Adams Court, Morgan Hill, CA 95037 USA

Tel. 408.538.5600

<http://www.element.com>



PART 25 MEASUREMENT REPORT

Applicant Name:

Apple Inc.
One Apple Park Way
Cupertino, CA 95014
United States

Date of Testing:

01/17/2025 - 08/03/2025

Test Report Issue Date:

8/3/2025

Test Site/Location:

Element Materials Technology Morgan Hill, CA, USA

Test Report Serial No.:

1C2503270029-04.BCG

FCC ID:

BCG-A3281

Applicant Name:

Apple Inc.

Application Type:

Certification

Model:

A3281, A3282

EUT Type:

Watch

FCC Classification:

Licensed Non-Broadcast Transmitter Worn on Body (TNT)

FCC Rule Part:

25

Test Procedure(s):

ANSI C63.26-2015, KDB 971168 D01 v03r01

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

RJ Ortanez
Executive Vice President




FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 1 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


T A B L E O F C O N T E N T S

1.0	INTRODUCTION.....	4
1.1	Scope.....	4
1.2	Element Test Location	4
1.3	Test Facility / Accreditations.....	4
2.0	PRODUCT INFORMATION.....	5
2.1	Equipment Description.....	5
2.2	Device Capabilities	5
2.3	Antenna Description.....	6
2.4	Test Support Equipment.....	6
2.5	Test Configuration	7
2.6	Software and Firmware.....	7
2.7	EMI Suppression Device(s)/Modifications	7
3.0	DESCRIPTION OF TESTS.....	8
3.1	Evaluation Procedure.....	8
3.2	Radiated Power and Radiated Spurious Emissions.....	8
4.0	MEASUREMENT UNCERTAINTY.....	9
5.0	TEST EQUIPMENT CALIBRATION DATA	10
6.0	SAMPLE Calculations	11
7.0	TEST RESULTS	12
7.1	Summary.....	12
7.2	6dB Bandwidth Measurement.....	13
7.3	Conducted Emissions Mask	22
7.4	Conducted Spurious Emission.....	42
7.5	Maximum Power Spectral Density	54
7.6	Conducted Output Power & EIRP.....	61
7.7	Radiated Spurious Emissions Measurements	65
7.8	Frequency Stability / Temperature Variation.....	72
8.0	CONCLUSION	76

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 2 of 76



PART 25 MEASUREMENT REPORT



Mode	Bandwidth	Modulation	Tx Frequency Range [MHz]	OBW [MHz]	EIRP		Emission Designator
					Max. Power [mW]	Max. Power [dBm]	
LTE Band 53	1.4 MHz	QPSK	2484.2 - 2494.3	1.0777	19.724	12.95	1M08G7W
		16QAM	2484.2 - 2494.3	1.0832	16.255	12.11	1M08D7W
	3 MHz	QPSK	2485.0 - 2493.5	2.6830	18.967	12.78	2M68G7W
		16QAM	2485.0 - 2493.5	2.6844	17.140	12.34	2M68D7W
	5 MHz	QPSK	2486.0 - 2492.5	4.4694	18.923	12.77	4M47G7W
		16QAM	2486.0 - 2492.5	4.4665	17.579	12.45	4M47D7W
	10 MHz	QPSK	2488.5 - 2490.0	8.9405	19.275	12.85	8M94G7W
		16QAM	2488.5 - 2490.0	4.8569	17.701	12.48	4M86D7W
NR Band n53	10 MHz	TT/2 BPSK	2488.5 - 2490.0	8.5744	19.454	12.89	8M57G7W
		QPSK	2488.5 - 2490.0	8.5692	19.055	12.80	8M57G7W
		16QAM	2488.5 - 2490.0	8.6103	16.904	12.28	8M61D7W
		64QAM	2488.5 - 2490.0	8.6374	17.100	12.33	8M64D7W

EUT Overview

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch		Page 3 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.

1.2 Element Test Location

These measurement tests were conducted at the Element Materials Technology facility located at 18855 Adams Court, Morgan Hill, CA 95037. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014 and KDB 414788 D01 v01r01.

1.3 Test Facility / Accreditations

Measurements were performed at Element Materials Technology.

- Element Materials Technology is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.02 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Washington DC LLC TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- Element Materials Technology facility is a registered (22831) test laboratory with the site description on file with ISED.
- Element Washington DC LLC is a Recognized U.S. Certification Assessment Body (CAB # US0110) for ISED Canada as designated by NIST under the U.S. and Canada Mutual Recognition Agreements (MRAs).

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 4 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Apple Watch FCC ID: BCG-A3281**. The test data contained in this report pertains only to the emissions due to the EUT's licensed transmitters that operate under the provisions of Part 25.

Test Device Serial No.: FN6HG1000GN0000VL1, FN6HG1000DF0000VL1, W7Y9YP320W, YMHWMV7H7D, T262Q5T4CQ

2.2 Device Capabilities

This device contains the following capabilities:

Multi-band LTE, 5G NR (FR1), 802.11b/g/n WLAN, 802.11a/n UNII, 802.15.4ab-NB, Bluetooth (1x, EDR, HDR4, HDR8, LE1M, LE2M), NFC, UWB, 60.5GHz Transmitter, Mobile Satellite Service (MSS).

This device supports simultaneous transmission operations, which allows multiple transmitters to transmit simultaneously on the same antenna. The table below shows all configurations possible.

Simultaneous Tx Config	Antenna FCM					
	WLAN	Bluetooth	802.15.4ab - NB	LTE/FR1	UNII	UWB
	802.11b/g/n	BDR, EDR, HDR4/8, LE1/2M	O-QPSK	Mid/High Band	802.11a/n	Ch.5/Ch.9
Config 1	✓	✗	✗	✓	✗	✓
Config 2	✗	✓	✗	✓	✗	✓
Config 3	✗	✓	✓	✓	✗	✗
Config 4	✓	✗	✓	✓	✗	✗
Config 5	✗	✓	✗	✓	✓	✗
Config 6	✗	✓	✗	✓	✗	✓
Config 7	✓	✗	✗	✓	✗	✗
Config 8	✓	✗	✓	✗	✗	✗
Config 9	✓	✗	✗	✗	✗	✓
Config 10	✗	✓	✗	✗	✓	✗
Config 11	✗	✓	✗	✓	✗	✗
Config 12	✗	✓	✓	✗	✗	✗
Config 13	✗	✓	✗	✗	✗	✓
Config 14	✗	✗	✓	✓	✗	✗
Config 15	✗	✗	✗	✓	✓	✗
Config 16	✗	✗	✗	✓	✗	✓

Table 2-1. Simultaneous Transmission Configurations

✓ = Support; ✗ = Not Support

Note:

All the above simultaneous transmission configurations have been tested, and the worst-case configuration was found to be Config 5 and reported in RF Bluetooth, RF UNII, and RF FCC Part 27b test reports.

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch		Page 5 of 76



2.3 Antenna Description

The following antenna gain provided by the manufacturer was used for testing.

Band	Antenna Gain [dBi]
	Antenna BCM
LTE Band 53	-8.20
NR Band n53	

Table 2-2. Highest Antenna Gain

2.4 Test Support Equipment

Test Support Equipment					
1	Apple Macbook w/AC/DC Adapter	Model: A1398 Model: A1435		S/N: FVFDHG8TP3XY S/N: N/A	
2	Apple USB-C cable w/ Charging Dock w/ Cradle	Model: N/A Model: A2921 Model: N/A		S/N: N/A S/N: DQ8137601MY08V22F S/N: CYV142700BEE1EN01MP1P	
3	Apple Magnetic Charger Apple Magnetic Charger	Model: A2515 Model: A2879		S/N: DLC313306ZQ1NR1A7 S/N: DLCH5T0012A00000WB	
4	Pathfinder Davenport SiP Socket	Model: 920-15901-01 Model: P2 N230 PF 238		S/N: DLCH640006H0000QAO S/N: DLCHB60007Q0000Q45	
5	DC Power Supply	Model: KPS3010D		S/N: N/A	

Table 2-3. Test Support Equipment

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch		Page 6 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



2.5 Test Configuration

The EUT was tested per the guidance of ANSI C63.26 2015, and KDB 971168 D01 v03r01. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

The worst case configuration was investigated for the various types of wristbands, metal and non-metal wristbands. The EUT was also investigated with and without wireless charger. The worst case configuration found was used for all testing.

For emissions from 1GHz – 18GHz, low, mid, and high channels were tested with highest power and worst case configuration. The emissions below 1GHz were tested with the highest transmitting power and the worst case channel.

The EUT was manipulated through three orthogonal planes of X-orientation (flatbed), Y-orientation (landscape), and Z-orientation (portrait) during the testing. Only the worst case emissions were reported in this test report.

This device only supports 27RBs or less for LTE 16-QAM uplink.

2.6 Software and Firmware

Testing was performed on device(s) using software/firmware version watchOS 26 installed on the EUT.

2.7 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 7 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the documents titled "American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services" (ANSI C63.26-2015) and "Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems" (KDB 971168 D01 v03r01) were used in the measurement of the EUT.

Deviation from Measurement Procedure.....None

3.2 Radiated Power and Radiated Spurious Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm tall test table made of Styrodur is placed on top of the turn table. A Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

The equipment under test was transmitting while connected to its integral antenna and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer.

For radiated spurious emissions measurements and calculations, conversion method is used per the formulas in KDB 971168 Section 5.8.4. Field Strength (EIRP) is calculated using the following formulas:

$$E_{[\text{dB}\mu\text{V}/\text{m}]} = \text{Measured amplitude level}_{[\text{dBm}]} + 107 + \text{Cable Loss}_{[\text{dB}]} + \text{Antenna Factor}_{[\text{dB}/\text{m}]} \\ \text{And}$$

$$\text{EIRP}_{[\text{dBm}]} = E_{[\text{dB}\mu\text{V}/\text{m}]} + 20\log D - 104.8; \text{ where } D \text{ is the measurement distance in meters.}$$

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014.

Per KDB 414788 D01 v01r01, radiated emission test sites other than open-field test sites (e.g., shielded anechoic chambers), may be employed for emission measurements below 30MHz if characterized so that the measurements correspond to those obtained at an open-field test site. To determine test site equivalency, a reference sample transmitting at 149kHz was measured on an open field test site (asphalt with no ground plane) and then measured in the 3m semi-anechoic chamber. A calibrated 60cm loop antenna was used while the reference device was rotated through the X, Y and Z axis in order to capture the worst case level. A maximum deviation of 2.77dB at 149kHz was measured when comparing the 3 meter semi-anechoic chamber to the open field site.

Radiated power and radiated spurious emission levels are investigated with the receive antenna horizontally and vertically polarized per ANSI C63.26-2015.

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 8 of 76

4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.23-2012. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (\pm dB)
Conducted Bench Top Measurements	2.07
Radiated Disturbance (<30MHz)	4.12
Radiated Disturbance (30MHz-1GHz)	4.85
Radiated Disturbance (1-18GHz)	5.08
Radiated Disturbance (>18GHz)	5.22

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 9 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance with the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent Technologies	N9030A	3Hz-26.5GHz PXA Signal Analyzer	10/31/2024	Annual	10/31/2025	MY55330128
ATM	180-442-KF	20dB Nominal Gain Horn Antenna	3/24/2025	Annual	3/24/2026	T058601-02
ESPEC	SU-241	Tabletop Temperature Chamber	10/24/2024	Annual	10/24/2025	92009574
ETS-Lindgren	3117	Double Ridged Guide Antenna (1-18 GHz)	9/25/2024	Annual	9/25/2025	240109
Fairview Microwave	FMCA1975-36	30MHz-40GHz Conducted Cable *	6/17/2025	Annual	6/17/2026	-
Fairview Microwave	M2CP1122-10	30MHz-40GHz Conducted Coupler *	6/17/2025	Annual	6/17/2026	1946
Keysight Technology	N9040B	UXA Signal Analyzer	6/9/2025	Annual	6/9/2026	MY57212015
MCL	BW-K10-2W44+	Attenuator *	6/17/2025	Annual	6/17/2026	-
Rohde & Schwarz	ESW44	EMI Test Receiver	10/17/2024	Annual	10/17/2025	101668
Rohde & Schwarz	FSV40	Signal Analyzer (10Hz-40GHz)	5/20/2025	Annual	5/20/2026	101619
Rohde & Schwarz	FSW67	Signal and Spectrum Analyzer (2Hz-67GHz)	1/7/2025	Annual	1/7/2026	101366
Rohde & Schwarz	TS-PR18	Pre-Amplifier (1GHz - 18GHz)	8/14/2024	Annual	8/14/2025	101648
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	12/10/2024	Annual	12/10/2025	161616
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	3/4/2025	Annual	3/4/2026	164715
Rohde & Schwarz	HFH2-Z2	Loop Antenna	5/12/2025	Annual	5/12/2026	100546
Rohde & Schwarz	HFH2-Z2	Loop Antenna	6/26/2025	Annual	6/26/2026	100519
Rohde & Schwarz	TS-PR1840	Pre-Amplifier (18GHz - 40GHz)	6/3/2025	Annual	6/3/2026	100052
Rohde & Schwarz	TS-PR8	Pre-Amplifier (30MHz - 8GHz)	11/15/2024	Annual	11/15/2025	102326
Schwarzbeck	VULB 9162	Bilog Antenna (30MHz - 6GHz)	9/18/2024	Annual	9/18/2025	358

Table 5-1. Test Equipment

Notes:

1. For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.
2. * Denotes passive equipment that has been internally verified/calibrated.

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 10 of 76	

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

6.0 SAMPLE CALCULATIONS

Emission Designator

$\pi/2$ BPSK / QPSK Modulation

Emission Designator = 8M62G7W

BW = 8.62 MHz

G = Phase Modulation

7 = Quantized/Digital Info

W = Combination of Any

QAM Modulation

Emission Designator = 8M45D7W

BW = 8.45 MHz

D = Amplitude/Angle Modulated

7 = Quantized/Digital Info

W = Combination of Any

Spurious Radiated Emission

Example: Spurious emission at 3700.40 MHz

The receive spectrum analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3700.40 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.50 dBm so this harmonic was 25.50 dBm $- (-24.80) = 50.3$ dBc.

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 11 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.0 TEST RESULTS

7.1 Summary

Company Name: Apple Inc.

FCC ID: BCG-A3281

FCC Classification: Licensed Non-Broadcast Transmitter Worn on Body (TNT)

Mode(s): LTE/NR

Test Condition	Test Description	FCC Part Section(s)	Test Limit	Test Result	Reference
CONDUCTED	Occupied Bandwidth	2.1049	N/A	N/A	Section 7.2
	6dB Bandwidth	25.149(c)(4)(ii)	≥ 500 kHz	PASS	
	Conducted Emission Mask	2.1051, 25.149(c)(4)(v), (vi)	Must meet the limits specified in 25.149(c)(4)(v) and 25.149(c)(4)(vi)	PASS	Section 7.3
	Conducted Spurious Emissions			PASS	Section 7.4
	Maximum Power Spectral Density	25.149(c)(4)(iv)	< 8dBm/3kHz	PASS	Section 7.5
	Transmitter Conducted Output Power	25.149(c)(4)(iii)	< 1Watt	PASS	Section 7.6
	Equivalent Isotropic Radiated Power		< 6 dBW max. EIRP	PASS	
	Frequency Stability	25.202(d)	< 0.001% of reference frequency	PASS	Section 7.8
RADIATED	Radiated Spurious Emissions	2.1053, 25.149(c)(4)(v), (vi)	Must meet the limits specified in 25.149(c)(4)(v) and 25.149(c)(4)(vi)	PASS	Section 7.7

Table 7-1. Summary of Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For radiated emissions measurements, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element "Chamber Automation," Version 3.4.2.

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 12 of 76

7.2 6dB Bandwidth Measurement

§2.1049; §25.149(c)(4)(ii)

Test Overview and Limit

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the transmitter antenna terminal of the EUT while the EUT is operating at maximum power and at the appropriate frequencies. All modes of operation were investigated and the worst case configuration results are reported in this section.

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

The 6 dB bandwidth is at least 500 kHz.

Test Procedure Used

ANSI C63.26-2015 – Section 5.4.4

Test Settings

1. The signal analyzers' automatic bandwidth measurement capability of the spectrum analyzer was used to perform the 99% occupied bandwidth and the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 6$. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 13 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-1. LTE Test Instrument & Measurement Setup




Figure 7-2. FR1 Test Instrument & Measurement Setup

Test Notes

1. For NR operation, all subcarrier spacings (SCS) and transmission schemes (e.g. CP-OFDM and DFT-s-OFDM) were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 14 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Band	Frequency [MHz]	Mode	RB Allocation/ RB Offset	99% Bandwidth Measurement [MHz]	6dB Bandwidth Measurement [MHz]	Minimum 6dB Bandwidth Measurement Limit [MHz]	Pass/Fail
LTE Band 53	2489.5	1.4MHz, QPSK	6/0	1.078	1.088	0.5	Pass
	2489.5	1.4MHz, 16QAM	6/0	1.083	1.094		Pass
	2489.5	3MHz, QPSK	15/0	2.683	2.721		Pass
	2489.5	3MHz, 16QAM	15/0	2.684	2.721		Pass
	2489.5	5MHz, QPSK	25/0	4.469	4.531		Pass
	2489.5	5MHz, 16QAM	25/0	4.467	4.529		Pass
	2489.5	10MHz, QPSK	50/0	8.941	9.071		Pass
	2489.5	10MHz, 16QAM	50/0	4.857	4.914		Pass

Table 7-2. LTE Band 53 - 6dB BW & 99% OBW Measurements



Band	Frequency [MHz]	Mode	RB Allocation/RB Offset	99% Bandwidth Measurement [MHz]	6dB Bandwidth Measurement [MHz]	Minimum 6dB Bandwidth Measurement Limit [MHz]	Pass/Fail
NR Band n53	2489.3	10MHz DFT-s-OFDM $\pi/2$ BPSK	24/0	8.574	8.581	0.5	Pass
	2489.3	10MHz CP-OFDM QPSK	24/0	8.569	8.540		Pass
	2489.3	10MHz CP-OFDM 16QAM	15/0	8.610	8.659		Pass
	2489.3	10MHz CP-OFDM 64QAM	15/0	8.637	8.672		Pass

Table 7-3. NR Band 53 - 6dB BW & 99% OBW Measurements

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch		



Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

LTE Band 53





FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 16 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.





FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 17 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 18 of 76


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 19 of 76



Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

NR Band n53



FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 20 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 21 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.3 Conducted Emissions Mask

§2.1051; §25.149(c)(4)(v), §25.149(c)(4)(vi)

Test Overview and Limit

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All modes of operation were investigated, and the worst-case configuration results are reported in this section.

Per FCC Part 25.149:

(c) Equipment certification. (4) Applications for equipment authorization of terrestrial low-power system equipment that will operate in the 2483.5-2495 MHz band shall demonstrate the following:

(v) Emissions below 2483.5 MHz are attenuated below the transmitter power (P) measured in watts by a factor of at least $40 + 10 \log (P)$ dB at the channel edge at 2483.5 MHz, $43 + 10 \log (P)$ dB at 5 MHz from the channel edge, and $55 + 10 \log (P)$ dB at X MHz from the channel edge where X is the greater of 6 MHz or the actual emission bandwidth.

(vi) Emissions above 2495 MHz are attenuated below the transmitter power (P) measured in watts by a factor of at least $43 + 10 \log (P)$ dB on all frequencies between the channel edge at 2495 MHz and X MHz from this channel edge and $55 + 10 \log (P)$ dB on all frequencies more than X MHz from this channel edge, where X is the greater of 6 MHz or the actual emission bandwidth.

Test Procedure Used

ANSI C63.26-2015 – Section 5.7

Test Settings

1. EUT is connected to the spectrum analyzer.
2. Highest power within the transmitting signal is measured.
3. Worst case emissions are identified and measured
4. Set span to include the block edge frequency
5. Set resolution bandwidth to at least 1% of emission bandwidth.

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 22 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-3. LTE Test Instrument & Measurement Setup




Figure 7-4. FR1 Test Instrument & Measurement Setup


Test Notes

1. For NR operation, all subcarrier spacings (SCS) and transmission schemes (e.g. CP-OFDM and DFT-s-OFDM) were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.
2. All RB configurations were investigated, only the worst-case RB configuration was reported.


FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 23 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

LTE Band 53




Plot 7-13. Low Channel Conducted Emission Mask (LTE Band 53 – 1.4MHz QPSK – RB Size 6, RB Offset 0)




17:41:02 22.04.2025

PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
FCC ID: BCG-A3281	Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025 EUT Type: Watch





Plot 7-15. Low Channel Conducted Emission Mask (LTE Band 53 – 1.4MHz QPSK – RB Size 6, RB Offset 0)



Plot 7-16. Low Channel Conducted Emission Mask (LTE Band 53 – 1.4MHz QPSK – RB Size 6, RB Offset 0)

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 25 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT				Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch			Page 26 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-19. High Channel Conducted Emission Mask (LTE Band 53 – 1.4MHz QPSK – RB Size 1, RB Offset 5)




Plot 7-20. Low Channel Conducted Emission Mask (LTE Band 53 – 3MHz QPSK – RB Size 15, RB Offset 0)

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 27 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-21. Low Channel Conducted Emission Mask (LTE Band 53 – 3MHz QPSK – RB Size 15, RB Offset 0)




Plot 7-22. Low Channel Conducted Emission Mask (LTE Band 53 – 3MHz QPSK – RB Size 15, RB Offset 0)

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 28 of 76	

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-23. Low Channel Conducted Emission Mask (LTE Band 53 – 3MHz QPSK – RB Size 15, RB Offset 0)




Plot 7-24. High Channel Conducted Emission Mask (LTE Band 53 – 3MHz QPSK – RB Size 1, RB Offset 14)

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 29 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-25. High Channel Conducted Emission Mask (LTE Band 53 – 3MHz QPSK – RB Size 1, RB Offset 14)




Plot 7-26. High Channel Conducted Emission Mask (LTE Band 53 – 3MHz QPSK – RB Size 1, RB Offset 14)

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch		Page 30 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-27. Low Channel Conducted Emission Mask (LTE Band 53 – 5MHz QPSK – RB Size 25, RB Offset 0)




Plot 7-28. Low Channel Conducted Emission Mask (LTE Band 53 – 5MHz QPSK – RB Size 25, RB Offset 0)

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 31 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-29. Low Channel Conducted Emission Mask (LTE Band 53 – 5MHz QPSK – RB Size 25, RB Offset 0)



Plot 7-30. Low Channel Conducted Emission Mask (LTE Band 53 – 5MHz QPSK – RB Size 25, RB Offset 0)

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 32 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-31. High Channel Conducted Emission Mask (LTE Band 53 – 5MHz QPSK – RB Size 1, RB Offset 24)



Plot 7-32. High Channel Conducted Emission Mask (LTE Band 53 – 5MHz QPSK – RB Size 1, RB Offset 24)


FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 33 of 76	

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



19:42:25 22.04.2025

Plot 7-33. High Channel Conducted Emission Mask (LTE Band 53 – 5MHz QPSK – RB Size 1, RB Offset 24)




03:30:00 26.04.2025


Plot 7-34. Low Channel Conducted Emission Mask (LTE Band 53 – 10MHz QPSK – RB Size 50, RB Offset 0)

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 34 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.





Plot 7-35. Low Channel Conducted Emission Mask (LTE Band 53 – 10MHz QPSK – RB Size 50, RB Offset 0)



Plot 7-36. Low Channel Conducted Emission Mask (LTE Band 53 – 10MHz QPSK – RB Size 50, RB Offset 0)


FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT				Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch			Page 35 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 36 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-39. High Channel Conducted Emission Mask (LTE Band 53 – 10MHz QPSK – RB Size 1, RB Offset 49)




Plot 7-40. High Channel Conducted Emission Mask (LTE Band 53 – 10MHz QPSK – RB Size 1, RB Offset 49)

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 37 of 76

NR Band n53




Plot 7-41. Low Channel Conducted Emission Mask (NR Band n53 – 10MHz DFT-s-OFDM QPSK – 1 RB 0 Offset)




Plot 7-42. Low Channel Conducted Emission Mask (NR Band n53 – 10MHz DFT-s-OFDM QPSK – 1 RB 0 Offset)

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 38 of 76




Plot 7-43. Low Channel Conducted Emission Mask (NR Band n53 – 10MHz DFT-s-OFDM QPSK – 1 RB 0 Offset)




Plot 7-44. Low Channel Conducted Emission Mask (NR Band n53 – 10MHz DFT-s-OFDM QPSK – 1 RB 0 Offset)

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 39 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-45. High Channel Conducted Emission Mask (NR Band n53 – 10MHz DFT-s-OFDM QPSK – 1 RB 24 Offset)



Plot 7-46. High Channel Conducted Emission Mask (NR Band n53 – 10MHz DFT-s-OFDM QPSK – 1 RB 24 Offset)

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 40 of 76



Plot 7-47. High Channel Conducted Emission Mask (NR Band n53 – 10MHz DFT-s-OFDM QPSK – 1 RB 24 Offset)

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 41 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.4 Conducted Spurious Emission

§2.1051; §25.149(c)(4)(v), §25.149(c)(4)(vi)

Test Overview and Limit

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All modes of operation were investigated, and the worst-case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emissions is 55 + 10 log (P) dB where transmitting power (P) in Watts.

Test Procedure Used

ANSI C63.26-2015 – Section 5.7

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to at least 25GHz (separated into at least three plots per channel)
2. RBW = 100 kHz for below 1 GHz, and 1 MHz for above 1 GHz the measurement.
3. VBW \geq 3 x RBW
4. Detector = RMS
5. Trace mode = trace average for continuous emissions, max hold for pulse emissions
6. Sweep time = auto couple
7. The trace was allowed to stabilize

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 42 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-5. LTE Test Instrument & Measurement Setup





Figure 7-6. FR1 Test Instrument & Measurement Setup

Test Notes:


1. For NR operation, all subcarrier spacings (SCS) and transmission schemes (e.g. CP-OFDM and DFT-s-OFDM) were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 43 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-48. Conducted Spurious Plot (LTE Band 53 - 10MHz QPSK - RB Size 1, RB Offset 25 - Low Channel)




Plot 7-49. Conducted Spurious Plot (LTE Band 53 - 10MHz QPSK - RB Size 1, RB Offset 25 - Low Channel)

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 44 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-50. Conducted Spurious Plot (LTE Band 53 - 10MHz QPSK - RB Size 1, RB Offset 25 - Low Channel)




Plot 7-51. Conducted Spurious Plot (LTE Band 53 - 10MHz QPSK - RB Size 1, RB Offset 25 - Mid Channel)

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 45 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-52. Conducted Spurious Plot (LTE Band 53 - 10MHz QPSK - RB Size 1, RB Offset 25 - Mid Channel)




Plot 7-53. Conducted Spurious Plot (LTE Band 53 - 10MHz QPSK - RB Size 1, RB Offset 25 - Mid Channel)

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 46 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-54. Conducted Spurious Plot (LTE Band 53 - 10MHz QPSK - RB Size 1, RB Offset 25 - High Channel)



Plot 7-55. Conducted Spurious Plot (LTE Band 53 - 10MHz QPSK - RB Size 1, RB Offset 25 - High Channel)

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 47 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-56. Conducted Spurious Plot (LTE Band 53 - 10MHz QPSK - RB Size 1, RB Offset 25 - High Channel)


FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 48 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

NR Band n53




Plot 7-57. Conducted Spurious Plot (NR Band n53 - 10.0MHz DFT-s-OFDM QPSK - RB Size 1, RB Offset 12 - Low Channel)




Plot 7-58. Conducted Spurious Plot (NR Band n53 - 10.0MHz DFT-s-OFDM QPSK - RB Size 1, RB Offset 12 - Low Channel)

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 49 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Plot 7-59. Conducted Spurious Plot (NR Band n53 - 10.0MHz DFT-s-OFDM QPSK - RB Size 1, RB Offset 12 - Low Channel)




Plot 7-60. Conducted Spurious Plot (NR Band n53 - 10.0MHz DFT-s-OFDM QPSK - RB Size 1, RB Offset 12 - Mid Channel)

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 50 of 76




Plot 7-61. Conducted Spurious Plot (NR Band n53 - 10.0MHz DFT-s-OFDM QPSK - RB Size 1, RB Offset 12 - Mid Channel)




Plot 7-62. Conducted Spurious Plot (NR Band n53 - 10.0MHz DFT-s-OFDM QPSK - RB Size 1, RB Offset 12 - Mid Channel)

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 51 of 76




Plot 7-63. Conducted Spurious Plot (NR Band n53 - 10.0MHz DFT-s-OFDM QPSK - RB Size 1, RB Offset 12 - High Channel)



Plot 7-64. Conducted Spurious Plot (NR Band n53 - 10.0MHz DFT-s-OFDM QPSK - RB Size 1, RB Offset 12 - High Channel)

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 52 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-65. Conducted Spurious Plot (NR Band n53 - 10.0MHz DFT-s-OFDM QPSK - RB Size 1, RB Offset 12 - High Channel)

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 53 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.5 Maximum Power Spectral Density

§25.149(c)(4)(iv)

Test Overview and Limit

The maximum power density is measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

The maximum permissible power spectral density is 8 dBm in any 3 kHz band.

Test Procedure Used

ANSI C63.26-2015 – Section 5.2.4.5

Test Settings

1. Analyzer was set to the center frequency of the channel under investigation
2. Span = 2 x to 3 x the OBW
3. RBW = 3kHz
4. VBW \geq 3 x RBW
5. Detector = RMS
6. Sweep time = auto couple
7. Trace mode = trace average
8. Trace was allowed to stabilize

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 54 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-7. LTE Test Instrument & Measurement Setup




Figure 7-8. FR1 Test Instrument & Measurement Setup

Test Notes

1. Low, mid, high channels were tested and tabular data has been reported. Only Mid Channel plots have been reported.
2. For NR operation, all subcarrier spacings (SCS) and transmission schemes (e.g. CP-OFDM and DFT-s-OFDM) were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 55 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Power Spectral Density Measurements

Band	Mode	RB Allocation/ RB Offset	Frequency [MHz]	Measured Power Spectral Density [dBm / 3kHz]	Maximum Permissible Power Density [dBm / 3kHz]	Margin [dB]
LTE Band 53	1.4MHz, QPSK	1/0	2484.2	5.80	8.0	-2.20
			2489.5	5.97	8.0	-2.03
			2494.3	5.59	8.0	-2.41
	3MHz, QPSK	1/0	2485.0	6.18	8.0	-1.82
			2489.5	6.28	8.0	-1.72
			2493.5	6.27	8.0	-1.74
	5MHz, QPSK	1/0	2486.0	6.23	8.0	-1.77
			2489.5	6.56	8.0	-1.44
			2492.5	6.23	8.0	-1.77
	10MHz, QPSK	1/0	2488.5	6.18	8.0	-1.82
			2489.5	6.25	8.0	-1.75
			2490.0	6.06	8.0	-1.94
		50/0	2488.5	-9.46	8.0	-17.46
			2489.5	-9.49	8.0	-17.49
			2490.0	-9.83	8.0	-17.83

Table 7-4. LTE Band 53 Conducted Power Density Measurements


Band	Mode	RB Allocation/ RB Offset	Frequency [MHz]	Measured Power Spectral Density [dBm / 3kHz]	Maximum Permissible Power Density [dBm / 3kHz]	Margin [dB]
NR Band 53	10MHz, DFT-s- OFDM QPSK	1/0	2488.5	5.70	8.0	-2.30
			2489.3	5.85	8.0	-2.15
			2490.0	5.38	8.0	-2.62
		24/0	2488.5	-5.59	8.0	-13.59
			2489.3	-6.22	8.0	-14.22
			2490.0	-5.71	8.0	-13.71

Table 7-5. NR Band 53 Conducted Power Density Measurements


FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 56 of 76	

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

LTE Band 53




Plot 7-66. Power Spectral Density Plot (LTE Band 53 – 1.4MHz QPSK – Middle Channel RB Size 1, RB Offset 0)




Plot 7-67. Power Spectral Density Plot (LTE Band 53 – 3MHz QPSK – Middle Channel RB Size 1, RB Offset 0)

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 57 of 76




Plot 7-68. Power Spectral Density Plot (LTE Band 53 – 5MHz QPSK – Middle Channel RB Size 1, RB Offset 0)



Plot 7-69. Power Spectral Density Plot (LTE Band 53 – 10MHz QPSK – Middle Channel RB Size 1, RB Offset 0)


FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 58 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 59 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

FR1 Band n53


Plot 7-71. Power Spectral Density Plot (NR Band 53 – 10MHz DFT-s-OFDM QPSK – Middle Channel RB Size 1, RB Offset 0)



Plot 7-72. Power Spectral Density Plot (NR Band 53 – 10MHz DFT-s-OFDM QPSK – Middle Channel RB Size 24, RB Offset 0)

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 60 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.6 Conducted Output Power & EIRP

§25.149(c)(4)(iii)

Test Overview and Limit

Equivalent Isotropic Radiated Power (EIRP) measurements are calculated by adding the highest antenna gain to maximum measured conducted output power. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

The maximum transmit power is no more than 1 W (30dBm) with a peak EIRP of no more than 6 dBW.

Test Procedures Used

KDB 971168 D01 v03r01 – Section 5.2.1

ANSI C63.26-2015 – Section 5.2.5.5

Test Settings

The relevant equation for determining the EIRP from the conducted RF output power measured is:

$$\text{EIRP} = \text{PMes} - \text{LC} + \text{GT}$$

Where:

EIRP = Equivalent Isotropic Radiated Power (expressed in the same units as PMes, typically dBW or dBm)

PMes = measured transmitter output power or PSD, in dBW or dBm

LC = signal attenuation in the connecting cable between the transmitter and antenna in dB

GT = gain of the transmitting antenna, in dBi (EIRP)

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 61 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-9. LTE Test Instrument & Measurement Setup




Figure 7-10. FR1 Test Instrument & Measurement Setup

Test Notes:

1. The EUT was tested in all possible test configurations. The worst case emissions are reported with the EUT modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
2. This unit was tested with its standard battery.
3. The Level (dBm) readings in the table were taken with a correction table loaded into the base station simulator. The correction table was used to account for the signal attenuation in the connecting cable between the transmitter and antenna.
4. The Ant. Gains (GT) are listed in dBi.
5. For NR operation, all subcarrier spacings (SCS) and transmission schemes (e.g. CP-OFDM and DFT-s-OFDM) were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 62 of 76

LTE Band 53

Bandwidth	Modulation	Frequency [MHz]	Ant. Gain [dBi]	RB Size/Offset	Conducted Power [dBm]	Conducted Power Limit [dBm]	Margin [dB]	EIRP [dBm]	EIRP [mW]	EIRP Limit [dBm]	Margin [dB]
1.4 MHz	QPSK	2484.2	-8.20	1 / 0	20.73	30.00	-9.270	12.53	17.906	36.00	-23.47
		2489.5	-8.20	1 / 5	21.12	30.00	-8.880	12.92	19.588	36.00	-23.08
		2494.3	-8.20	1 / 0	21.15	30.00	-8.850	12.95	19.724	36.00	-23.05
	16-QAM	2489.5	-8.20	1 / 0	20.31	30.00	-9.690	12.11	16.255	36.00	-23.89
3 MHz	QPSK	2485.0	-8.20	1 / 14	20.98	30.00	-9.020	12.78	18.967	36.00	-23.22
		2489.5	-8.20	1 / 0	20.95	30.00	-9.050	12.75	18.836	36.00	-23.25
		2493.5	-8.20	1 / 0	20.96	30.00	-9.040	12.76	18.880	36.00	-23.24
	16-QAM	2489.5	-8.20	1 / 14	20.54	30.00	-9.460	12.34	17.140	36.00	-23.66
5 MHz	QPSK	2486.0	-8.20	1 / 0	20.97	30.00	-9.030	12.77	18.923	36.00	-23.23
		2489.5	-8.20	1 / 12	20.91	30.00	-9.090	12.71	18.664	36.00	-23.29
		2492.5	-8.20	1 / 0	20.91	30.00	-9.090	12.71	18.664	36.00	-23.29
	16-QAM	2486.0	-8.20	1 / 24	20.65	30.00	-9.350	12.45	17.579	36.00	-23.55
10 MHz	QPSK	2488.5	-8.20	1 / 0	20.94	30.00	-9.060	12.74	18.793	36.00	-23.26
		2489.5	-8.20	1 / 49	20.88	30.00	-9.120	12.68	18.535	36.00	-23.32
		2490.0	-8.20	1 / 49	21.05	30.00	-8.950	12.85	19.275	36.00	-23.15
	16-QAM	2489.5	-8.20	1 / 0	20.68	30.00	-9.320	12.48	17.701	36.00	-23.52

Table 7-6. Antenna BCM EIRP Data (LTE Band 53)

FCC ID: BCG-A3281		PART 25 MEASUREMENT REPORT				Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch				Page 63 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

NR Band n53

Bandwidth	Modulation	Frequency [MHz]	Ant. Gain [dBi]	RB Size/Offset	Conducted Power [dBm]	Conducted Power Limit [dBm]	Margin [dB]	EIRP [dBm]	EIRP [mW]	EIRP Limit [dBm]	Margin [dB]
10 MHz	π/2 BPSK	2488.5	-8.20	1 / 25	20.88	30.00	-9.120	12.68	18.537	36.00	-23.32
		2489.3	-8.20	1 / 25	21.09	30.00	-8.910	12.89	19.454	36.00	-23.11
		2490.0	-8.20	1 / 25	20.77	30.00	-9.225	12.57	18.092	36.00	-23.43
	QPSK	2488.5	-8.20	1 / 48	20.71	30.00	-9.290	12.51	17.824	36.00	-23.49
		2489.3	-8.20	1 / 1	20.98	30.00	-9.018	12.78	18.976	36.00	-23.22
		2490.0	-8.20	1 / 48	21.00	30.00	-9.003	12.80	19.043	36.00	-23.20
	16-QAM	2489.3	-8.20	1 / 1	20.48	30.00	-9.517	12.28	16.915	36.00	-23.72
	64-QAM	2488.5	-8.20	1 / 25	20.53	30.00	-9.474	12.33	17.085	36.00	-23.67

Table 7-7. Antenna BCM EIRP Data (NR Band n53)

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT				Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch			

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.7 Radiated Spurious Emissions Measurements

§2.1053; §25.149(c)(4)(v); §25.149(c)(4)(vi)

Test Overview

Radiated spurious emissions measurements are performed using the field strength conversion method described in KDB 971168 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using horizontally and vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

Test Procedures Used

ANSI C63.26-2015 – Section 5.5.4

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW \geq 3 x RBW
3. Span = 1.5 times the OBW
4. No. of sweep points \geq 2 x span / RBW
5. Detector = RMS
6. Trace mode = Average (Max Hold for pulsed emissions)
7. The trace was allowed to stabilize

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 65 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-11. Test Instrument & Measurement Setup < 1GHz




Figure 7-12. Test Instrument & Measurement Setup >1 GHz

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 66 of 76


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Test Notes


1. Field strengths are calculated using the Measurement quantity conversions in KDB 971168 D01 v03r01 Section 5.8.4.
 - a. $E(\text{dB}\mu\text{V}/\text{m}) = \text{Measured amplitude level (dBm)} + 107 + \text{Cable Loss (dB)} + \text{Antenna Factor (dB/m)}$
 - b. $\text{EIRP (dBm)} = E(\text{dB}\mu\text{V}/\text{m}) + 20\log D - 104.8$; where D is the measurement distance in meters.
2. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst-case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
3. This unit was tested with its standard battery.
4. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter. The worst-case emissions are reported.
5. D is the measurement test distance and emissions 1-18GHz were measured at a 3 meters test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
6. The "-" shown in the following RSE tables are used to denote a noise floor measurement.
7. For NR operation, all subcarrier spacings (SCS) and transmission schemes (e.g. CP-OFDM and DFT-s-OFDM) were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 67 of 76

LTE Band 53



Plot 7-73. Radiated Spurious Plot 1 - 18GHz (LTE Band 53 – Mid Channel)



Plot 7-74. Radiated Spurious Plot Above 18GHz (LTE Band 53 – Mid Channel)

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 68 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Bandwidth (MHz):	10
Frequency (MHz):	2488.5
RB / Offset:	1 / 25

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB μ V/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1584.5	V	-	-	-68.34	-2.75	35.91	-59.35	-50.00	-9.35
4977.0	V	368	370	-68.56	5.67	44.11	-51.15	-25.00	-26.15
7465.5	V	-	-	-71.51	8.58	44.07	-51.19	-25.00	-26.19
9954.0	V	-	-	-72.81	11.22	45.41	-49.85	-25.00	-24.85
12442.5	V	217	20	-73.44	15.74	49.30	-45.96	-25.00	-20.96
14931.0	V	-	-	-74.03	17.84	50.81	-44.44	-25.00	-19.44
17419.5	V	-	-	-74.67	22.61	54.94	-40.32	-25.00	-15.32

Table 7-8. Radiated Spurious Data (LTE Band 53 – Low Channel)

Bandwidth (MHz):	10
Frequency (MHz):	2489.5
RB / Offset:	1 / 25

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB μ V/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1584.5	V	-	-	-68.58	-2.75	35.67	-59.59	-50.00	-9.59
4979.0	V	282	314	-70.12	5.68	42.56	-52.70	-25.00	-27.70
7468.5	V	-	-	-71.05	8.58	44.53	-50.73	-25.00	-25.73
9958.0	V	-	-	-72.15	11.15	46.00	-49.26	-25.00	-24.26
12447.5	V	212	4	-71.87	15.66	50.79	-44.47	-25.00	-19.47
14937.0	V	-	-	-74.58	17.80	50.22	-45.04	-25.00	-20.04
17426.5	V	-	-	-75.27	22.68	54.41	-40.85	-25.00	-15.85

Table 7-9. Radiated Spurious Data (LTE Band 53 – Mid Channel)



Bandwidth (MHz):	10
Frequency (MHz):	2490.0
RB / Offset:	1 / 25

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB μ V/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1584.5	V	-	-	-67.54	-2.75	36.71	-58.55	-50.00	-8.55
4980.0	V	387	336	-67.87	5.68	44.81	-50.45	-25.00	-25.45
7470.0	V	-	-	-71.10	8.59	44.49	-50.77	-25.00	-25.77
9960.0	V	-	-	-72.74	11.17	45.43	-49.83	-25.00	-24.83
12450.0	V	207	17	-72.57	15.62	50.05	-45.21	-25.00	-20.21
14940.0	V	207	333	-74.03	17.78	50.75	-44.51	-25.00	-19.51
17430.0	V	-	-	-74.69	22.70	55.01	-40.25	-25.00	-15.25

Table 7-10. Radiated Spurious Data (LTE Band 53 – High Channel)

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT					Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch				Page 69 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

NR Band n53

Plot 7-75. Radiated Spurious Plot 1 - 18GHz (NR Band n53 – High Channel)

Plot 7-76. Radiated Spurious Plot Above 18GHz (NR Band n53 – High Channel)

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 70 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Bandwidth (MHz):	10
Frequency (MHz):	2488.5
RB / Offset:	1 / 12

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB μ V/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1584.5	V	-	-	-68.26	-2.75	35.99	-59.27	-50.00	-9.27
4977.0	V	293	327	-79.08	5.67	33.59	-61.67	-25.00	-36.67
7465.5	V	-	-	-81.17	8.58	34.41	-60.85	-25.00	-35.85
9954.0	V	-	-	-81.86	11.22	36.36	-58.90	-25.00	-33.90
12442.5	V	213	15	-79.64	15.74	43.10	-52.16	-25.00	-27.16
14931.0	V	218	331	-82.50	17.84	42.34	-52.91	-25.00	-27.91
17419.5	V	-	-	-84.88	22.61	44.73	-50.53	-25.00	-25.53

Table 7-11. Radiated Spurious Data (NR Band n53 – Low Channel)

Bandwidth (MHz):	10
Frequency (MHz):	2489.5
RB / Offset:	1 / 12

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB μ V/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1584.5	V	-	-	-68.41	-2.75	35.84	-59.42	-50.00	-9.42
4979.0	V	-	-	-79.73	5.68	32.95	-62.31	-25.00	-37.31
7468.5	V	-	-	-81.07	8.58	34.51	-60.75	-25.00	-35.75
9958.0	V	-	-	-81.90	11.16	36.26	-59.00	-25.00	-34.00
12447.5	V	215	22	-77.69	15.67	44.98	-50.28	-25.00	-25.28
14937.0	V	-	-	-84.12	17.81	40.69	-54.57	-25.00	-29.57
17426.5	V	-	-	-84.75	22.67	44.92	-50.33	-25.00	-25.33

Table 7-12. Radiated Spurious Data (NR Band n53 – Mid Channel)

Bandwidth (MHz):	10
Frequency (MHz):	2490.0
RB / Offset:	1 / 12

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB μ V/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1584.5	V	-	-	-68.37	-2.75	35.88	-59.38	-50.00	-9.38
4980.0	V	-	-	-79.99	5.68	32.69	-62.57	-25.00	-37.57
7470.0	V	-	-	-81.15	8.59	34.44	-60.82	-25.00	-35.82
9960.0	V	-	-	-81.72	11.17	36.45	-58.81	-25.00	-33.81
12450.0	V	214	359	-76.33	15.62	46.29	-48.97	-25.00	-23.97
14940.0	V	-	-	-84.09	17.78	40.69	-54.57	-25.00	-29.57
17430.0	V	-	-	-84.79	22.70	44.91	-50.35	-25.00	-25.35

Table 7-13. Radiated Spurious Data (NR Band n53 – High Channel)

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT					Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch				Page 71 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.8 Frequency Stability / Temperature Variation

§25.202(d)

Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

Per FCC Part 25.202(d) Frequency tolerance, Earth stations. The carrier frequency of each earth station transmitter authorized in these services shall be maintained within 0.001 percent of the reference frequency.

Test Procedure Used

ANSI C63.26-2015 – Section 5.6

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 72 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber. For LTE testing, in addition, the EUT was connected to a communication tester via an attenuated RF coupler.




Figure 7-13. LTE Test Instrument & Measurement Setup




Figure 7-14. FR1 Test Instrument & Measurement Setup

Test Notes

None

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 73 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Frequency Stability / Temperature Variation

LTE Band 53											
<table border="1"> <tr> <td>Operating Frequency (GHz):</td><td>2.4895</td></tr> <tr> <td>Ref. Voltage (VDC):</td><td>3.80</td></tr> <tr> <td>Deviation Limit:</td><td>± 0.001%</td></tr> </table>						Operating Frequency (GHz):	2.4895	Ref. Voltage (VDC):	3.80	Deviation Limit:	± 0.001%
Operating Frequency (GHz):	2.4895										
Ref. Voltage (VDC):	3.80										
Deviation Limit:	± 0.001%										
Voltage (%)	Power (VDC)	Temp (°C)	Frequency (GHz)	Freq. Dev. (GHz)	Deviation (%)						
100 %	3.80	- 30	2.489499809	-0.000000153	-0.000006146						
		- 20	2.489499883	-0.000000079	-0.000003173						
		- 10	2.489500077	0.000000115	0.000004619						
		0	2.489500051	0.000000089	0.000003575						
		+ 10	2.489500037	0.000000075	0.000003013						
		+ 20 (Ref)	2.489499962	0.000000000	0.000000000						
		+ 30	2.489499903	-0.000000059	-0.000002370						
		+ 40	2.489499817	-0.000000145	-0.000005824						
		+ 50	2.489500040	0.000000078	0.000003133						
Battery Endpoint	3.40	+ 20	2.489500033	0.000000071	0.000002852						

Table 7-14. LTE Band 53 Frequency Tolerance Data

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch		Page 74 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Frequency Stability / Temperature Variation

NR Band n53					
Voltage (%)	Power (VDC)	Operating Frequency (GHz): 2.4893			
		Ref. Voltage (VDC): 3.80			
		Deviation Limit: ± 0.001%			
100 %	3.80	- 30	2.489299933	-0.000000115	-0.000004620
		- 20	2.489300126	0.000000078	0.000003133
		- 10	2.489299922	-0.000000126	-0.000005062
		0	2.489299994	-0.000000054	-0.000002169
		+ 10	2.489300143	0.000000095	0.000003816
		+ 20 (Ref)	2.489300048	0.000000000	0.000000000
		+ 30	2.489299986	-0.000000062	-0.000002491
		+ 40	2.489299989	-0.000000059	-0.000002370
		+ 50	2.489300136	0.000000088	0.000003535
Battery Endpoint	3.40	+ 20	2.489300106	0.000000058	0.000002330

Table 7-15. NR Band n53 Frequency Tolerance Data

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch		Page 75 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Apple Watch FCC ID: BCG-A3281** complies with the requirements of Part 25 of the FCC rules.

FCC ID: BCG-A3281	PART 25 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2503270029-04.BCG	Test Dates: 01/17/2025 - 08/03/2025	EUT Type: Watch	Page 76 of 76

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.