

High Frequency Substitution Measurement
UL Fremont Radiated Chamber E

Project #: 14U17676
Date: 6/25/2014
Test Engineer: Ali Poushnejad
Configuration: EUT Only
Mode: CDMA Rev A 800MHz

Test Equipment:

Receiving: Sunol T408, and Chamber E Cable
 Substitution: Dipole S/N: 00022117, 8ft SMA Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	EIR{ (dBm)	ERP Limit (dBm)	EIRP Limit (dBm)	Margin (dB)	Notes
Low Ch										
817.90	11.61	V	0.6	0.0	10.99	13.14	38.45	40.60	-27.5	
817.90	17.15	H	0.6	0.0	16.53	18.68	38.45	40.60	-21.9	
Mid Ch										
819.15	12.10	V	0.6	0.0	11.48	13.63	38.45	40.60	-27.0	
819.15	18.12	H	0.6	0.0	17.50	19.65	38.45	40.60	-20.9	
High Ch										
824.10	11.80	V	0.6	0.0	11.18	13.33	38.45	40.60	-27.3	
824.10	18.23	H	0.6	0.0	17.61	19.76	38.45	40.60	-20.8	

Rev. 06.18.14

Two Carriers Min Separation

High Frequency Substitution Measurement UL Fremont Radiated Chamber D																		
Project #:	14U17676																	
Date:	06/26/14																	
Test Engineer:	R.Z																	
Configuration:	EUT only																	
Mode:	CDMA Rev B 2C Min Sep 850MHz																	
Test Equipment:																		
Receiving: Sunol T407, and Chamber D Cable																		
Substitution: Dipole S/N: 00022117, 8ft SMA Cable																		
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	EIRP (dBm)	Limit (dBm)	Margin EIRP (dB)	Notes									
Low Ch																		
825.3	8.80	V	0.6	0.0	8.18	10.33	38.5	-28.1										
825.3	13.97	H	0.6	0.0	13.35	15.50	38.5	-22.9										
Mid Ch																		
837.2	8.74	V	0.6	0.0	8.12	10.27	38.5	-28.2										
837.2	14.12	H	0.6	0.0	13.50	15.65	38.5	-22.8										
High Ch																		
847.6	8.31	V	0.6	0.0	7.69	9.84	38.5	-28.6										
847.6	14.50	H	0.6	0.0	13.88	16.03	38.5	-22.4										
Rev. 06.18.14																		

CDMA2000, REV B

Two Carriers Max Separation

High Frequency Substitution Measurement UL Fremont Radiated Chamber E																				
Company:																				
Project #:	14U17676																			
Date:	07/24/14																			
Test Engineer:	R.Z																			
Configuration:	EUT only																			
Mode:	CDMA Rev B 2C Min Sep 850MHz																			
Test Equipment:																				
Receiving: Sunol T408, and Chamber E Cable																				
Substitution: Dipole S/N: 00022117, 8ft SMA Cable																				
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	EIRP (dBm)	ERP Limit (dBm)	EIRP Limit (dBm)	Margin (dB)	Notes										
Low Ch																				
824.7 + 825.93MHz	8.47	V	0.6	0.0	7.85	10.00	38.45	40.60	-30.6											
824.7 + 825.93MHz	14.07	H	0.6	0.0	13.45	15.60	38.45	40.60	-25.0											
Mid Ch																				
836.52+837.75MHz	7.84	V	0.6	0.0	7.22	9.37	38.45	40.60	-31.2											
836.52+837.75MHz	14.09	H	0.6	0.0	13.47	15.62	38.45	40.60	-25.0											
High Ch																				
847.08+848.31MHz	8.75	V	0.6	0.0	8.13	10.28	38.45	40.60	-30.3											
847.08+848.31MHz	14.46	H	0.6	0.0	13.84	15.99	38.45	40.60	-24.6											
Rev. 06.18.14																				

Three Carriers Min Separation

High Frequency Substitution Measurement UL Fremont Radiated Chamber D																		
Project #:	14U17676																	
Date:	06/26/14																	
Test Engineer:	R.Z																	
Configuration:	EUT only																	
Mode:	CDMA Rev B 3C Min Sep 850MHz																	
Test Equipment:																		
Receiving: Sunol T407, and Chamber D Cable																		
Substitution: Dipole S/N: 00022117, 8ft SMA Cable																		
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	EIRP (dBm)	Limit (dBm)	Margin EIRP (dB)	Notes									
Low Ch																		
825.9	8.80	V	0.6	0.0	8.18	10.33	38.5	-28.1										
825.9	13.97	H	0.6	0.0	13.35	15.50	38.5	-22.9										
Mid Ch																		
837.7	8.74	V	0.6	0.0	8.12	10.27	38.5	-28.2										
837.7	14.12	H	0.6	0.0	13.50	15.65	38.5	-22.8										
High Ch																		
846.7	8.31	V	0.6	0.0	7.69	9.84	38.5	-28.6										
846.7	14.50	H	0.6	0.0	13.88	16.03	38.5	-22.4										
Rev. 06.18.14																		

10.2. PEAK-TO-AVERAGE RATIO

In addition, when the transmitter power is measured in terms of average value, the peak-to-average ratio of the power shall not exceed 13 dB.

Peak-To-Average Ratio:

Mode	Modulation	Couducted Power (dBm)		Peak-to-Average Ratio (PAR)
		*Peak	Average	
GSM850	GPRS	32.96	32.87	0.09
Mode	Ch. No.	Couducted Power (dBm)		Peak-to-Average Ratio (PAR)
		*Peak	Average	
GSM850	EGPRS	31.73	28.83	2.9

*Peak Reading = Average Reading + Peak-to-Average Ratio

Mode	Modulation	Couducted Power (dBm)		Peak-to-Average Ratio (PAR)
		*Peak	Average	
GSM1900	GPRS	29.64	29.55	0.09
Mode	Ch. No.	Couducted Power (dBm)		Peak-to-Average Ratio (PAR)
		*Peak	Average	
GSM1900	EGPRS	30.52	27.84	2.68

*Peak Reading = Average Reading + Peak-to-Average Ratio

Mode	Modulation	Couducted Power (dBm)		Peak-to-Average Ratio (PAR)
		*Peak	Average	
UMTS B2	REL99	28.1	25.06	3.04
Mode	Ch. No.	Couducted Power (dBm)		Peak-to-Average Ratio (PAR)
		*Peak	Average	
UMTS B2	HSDPA	27.95	24.2	3.75

*Peak Reading = Average Reading + Peak-to-Average Ratio

Mode	Modulation	Couducted Power (dBm)		Peak-to-Average Ratio (PAR)
		*Peak	Average	
UMTS B5	REL99	28.26	25.08	3.18
Mode	Ch. No.	Couducted Power (dBm)		Peak-to-Average Ratio (PAR)
		*Peak	Average	
UMTS B5	HSDPA	27.87	24.11	3.76

*Peak Reading = Average Reading + Peak-to-Average Ratio

Mode	Modulation	Couducted Power (dBm)		Peak-to-Average Ratio (PAR)
		*Peak	Average	
UMTS B4	REL99	28.23	25.04	3.19
Mode	Ch. No.	Couducted Power (dBm)		Peak-to-Average Ratio (PAR)
		*Peak	Average	
UMTS B4	HSDPA	27.96	24.16	3.8

*Peak Reading = Average Reading + Peak-to-Average Ratio

Mode	Modulation	Couducted Power (dBm)		Peak-to-Average Ratio (PAR)
		*Peak	Average	
BC0	1xRTT	28.24	24.16	4.08
Mode	Modulation	Couducted Power (dBm)		Peak-to-Average Ratio (PAR)
		*Peak	Average	
BC0	EVDO A	29.05	25.00	4.05

*Peak Reading = Average Reading + Peak-to-Average Ratio

Mode	Modulation	Couducted Power (dBm)		Peak-to-Average Ratio (PAR)
		*Peak	Average	
BC1	1xRTT	29.49	24.99	4.5
<hr/>				
Mode	Modulation	Couducted Power (dBm)		Peak-to-Average Ratio (PAR)
		*Peak	Average	
BC1	EVDO A	29.44	24.98	4.46

*Peak Reading = Average Reading + Peak-to-Average Ratio


Mode	Ch. No.	Couducted Power (dBm)		Peak-to-Average Ratio (PAR)
		*Peak	Average	
BC15	1xRTT	29.65	24.98	4.67
<hr/>				
Mode	Ch. No.	Couducted Power (dBm)		Peak-to-Average Ratio (PAR)
		*Peak	Average	
BC15	EVDO A	29.69	24.93	4.76

*Peak Reading = Average Reading + Peak-to-Average Ratio


Mode	Ch. No.	Couducted Power (dBm)		Peak-to-Average Ratio (PAR)
		*Peak	Average	
BC10	1xRTT	29.2	24.91	4.29
<hr/>				
Mode	Ch. No.	Couducted Power (dBm)		Peak-to-Average Ratio (PAR)
		*Peak	Average	
BC10	EVDO A	29.25	24.96	4.29



*Peak Reading = Average Reading + Peak-to-Average Ratio



GSM850, GPRS







GSM850, EGPRS




**GSM1900, EGPRS**

**UMTS850, HSDPA BAND 2**


**UMTS850, HSDPA BAND 5**

**UMTS850, HSDPA BAND 4**


BC 0, 1xRTT




BC 0, EVDO A




BC 1, 1xRTT




BC 1, EVDO A




BC 15, 1xRTT




BC 15, EVDO A



BC10, 1xRTT



BC10, EVDO A



10.3. FIELD STRENGTH OF SPURIOUS RADIATION

RULE PART(S)

FCC: §2.1053, §22.917, §24.238, §27.53 and § 90.691.

LIMIT

§22.917 (e) and §24.238 (a): Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

§27.53 (h) For operations in the 1710–1755 MHz and 2110–2155 MHz bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB

§ 90.691 Emission mask requirements for EA-based systems.

(a) Out-of-band emission requirement shall apply only to the “outer” channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:

(1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $116 \log_{10}(f/6.1)$ decibels or $50 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

(2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

(b) When an emission outside of the authorized bandwidth causes harmful interference, the Commission may, at its discretion, require greater attenuation than specified in this section.

TEST PROCEDURE

For Cellular equipment - Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 100 kHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

For PCS equipment - Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve

measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 1 MHz or 1 percent of emission bandwidth, as specified). The

emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

MODES TESTED

- GPRS/EGPRS.
- UMTS, REL 99 and HSDPA
- CDMA2000, BC0, BC1, BC10 and BC15

RESULTS

10.3.1.LAT

GPRS, 850MHz BAND 5

3m Radiated Emissions Chamber Above 1GHz Substitution Measurement									
Project #:		14U17676							
Date:		06/21/14							
Test Engineer:		T. Chu							
Configuration:		EUT only							
Mode:		GPRS 850MHz							
<u>Test Equipment:</u>									
Substitution: Horn T59 Substitution, and 8ft SMA Cable									
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber E		3m Chamber E				Part 22			
Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes
Low Channel (824.2MHz)									
1.648	2.7	H	3.0	37.6	1.0	-33.9	-13.0	-20.9	
2.472	-11.5	H	3.0	38.0	1.0	-48.4	-13.0	-35.4	
1.648	0.1	V	3.0	37.6	1.0	-36.4	-13.0	-23.4	
2.472	-11.1	V	3.0	38.0	1.0	-48.1	-13.0	-35.1	
Mid Channel (836.6MHz)									
1.673	-0.5	H	3.0	37.6	1.0	-37.1	-13.0	-24.1	
2.510	-10.1	H	3.0	37.9	1.0	-47.0	-13.0	-34.0	
1.673	0.3	V	3.0	37.6	1.0	-36.3	-13.0	-23.3	
2.510	9.4	V	3.0	37.9	1.0	-46.4	-13.0	-33.4	
High Channel (848.8MHz)									
1.698	-7.4	H	3.0	37.6	1.0	-44.0	-13.0	-31.0	
2.546	-6.9	H	3.0	38.0	1.0	-43.9	-13.0	-30.9	
1.698	-5.2	V	3.0	37.6	1.0	-41.8	-13.0	-28.8	
2.546	-8.3	V	3.0	38.0	1.0	-45.2	-13.0	-32.2	
Rev. 03.03.14									

3m Radiated Emissions Chamber Above 1GHz Substitution Measurement									
Project #:		14U17676							
Date:		06/21/14							
Test Engineer:		T. Chu							
Configuration:		EUT only							
Mode:		EGPRS 850MHz							
Test Equipment:									
Substitution: Horn T59 Substitution, and 8ft SMA Cable									
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber E		3m Chamber E				Part 22			
Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes
Low Channel (824.2MHz)									
1.648	-4.5	H	3.0	37.6	1.0	-41.1	-13.0	-28.1	
2.472	-15.9	H	3.0	38.0	1.0	-52.8	-13.0	-39.8	
1.648	-5.4	V	3.0	37.6	1.0	-42.0	-13.0	-29.0	
2.472	-13.2	V	3.0	38.0	1.0	-50.2	-13.0	-37.2	
Mid Channel (836.6MHz)									
1.673	-1.2	H	3.0	37.6	1.0	-37.7	-13.0	-24.7	
2.510	-14.7	H	3.0	37.9	1.0	-51.6	-13.0	-38.6	
1.673	-2.8	V	3.0	37.6	1.0	-39.4	-13.0	-26.4	
2.510	-12.7	V	3.0	37.9	1.0	-49.7	-13.0	-36.7	
High Channel (848.8MHz)									
1.698	-5.2	H	3.0	37.6	1.0	-41.8	-13.0	-28.8	
2.546	-11.4	H	3.0	38.0	1.0	-48.4	-13.0	-35.4	
1.698	-11.9	V	3.0	37.6	1.0	-48.5	-13.0	-35.5	
2.546	-9.6	V	3.0	38.0	1.0	-46.6	-13.0	-33.6	
Rev. 03.03.14									

3m Radiated Emissions Chamber Above 1GHz Substitution Measurement									
Project #: 14U17676 Date: 06/26/14 Test Engineer: E. Yu Configuration: EUT only Mode: GPRS 1900MHz									
Test Equipment: Substitution: Horn T59 Substitution, and 8ft SMA Cable									
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber F		3m Chamber F				Part 24			
Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes
Low Channel (1850.2MHz)									
3.700	-11.9	H	3.0	36.3	1.0	47.2	-13.0	-34.2	
5.551	-12.9	H	3.0	35.6	1.0	47.4	-13.0	-34.4	
3.700	-11.7	V	3.0	36.3	1.0	47.1	-13.0	-34.1	
5.551	-12.4	V	3.0	35.6	1.0	46.9	-13.0	-33.9	
Mid Channel (1880.0)									
3.760	-10.7	H	3.0	36.3	1.0	45.9	-13.0	-32.9	
5.640	-11.9	H	3.0	35.6	1.0	46.4	-13.0	-33.4	
3.760	-9.9	V	3.0	36.3	1.0	45.2	-13.0	-32.2	
5.640	-12.1	V	3.0	35.6	1.0	46.7	-13.0	-33.7	
High Channel (1909.8MHz)									
3.820	-10.0	H	3.0	36.3	1.0	45.2	-13.0	-32.2	
5.729	-8.7	H	3.0	35.6	1.0	43.3	-13.0	-30.3	
3.820	-8.9	V	3.0	36.3	1.0	44.2	-13.0	-31.2	
5.729	-9.0	V	3.0	35.6	1.0	43.6	-13.0	-30.6	
Rev. 03.03.14									

3m Radiated Emissions Chamber Above 1GHz Substitution Measurement									
Project #: 14U17676 Date: 06/26/14 Test Engineer: E. Yu Configuration: EUT only Mode: EGPRS 1900MHz									
Test Equipment: Substitution: Horn T59 Substitution, and 8ft SMA Cable									
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber F		3m Chamber F					Part 24		
Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes
Low Channel (1850.2MHz)									
3.700	-13.8	H	3.0	36.3	1.0	-49.1	-13.0	-36.1	
5.551	-12.8	H	3.0	35.6	1.0	-47.3	-13.0	-34.3	
3.700	-13.3	V	3.0	36.3	1.0	-48.6	-13.0	-35.6	
5.551	-11.9	V	3.0	35.6	1.0	-46.5	-13.0	-33.5	
Mid Channel (1880.0)									
3.760	-12.5	H	3.0	36.3	1.0	-47.8	-13.0	-34.8	
5.640	-12.2	H	3.0	35.6	1.0	-46.8	-13.0	-33.8	
3.760	-14.3	V	3.0	36.3	1.0	-49.6	-13.0	-36.6	
5.640	-11.2	V	3.0	35.6	1.0	-45.8	-13.0	-32.8	
High Channel (1909.8MHz)									
3.820	-10.7	H	3.0	36.3	1.0	-46.0	-13.0	-33.0	
5.729	-8.7	H	3.0	35.6	1.0	-43.3	-13.0	-30.3	
3.820	-10.0	V	3.0	36.3	1.0	-45.2	-13.0	-32.2	
5.729	-5.9	V	3.0	35.6	1.0	-40.5	-13.0	-27.5	

Rev. 03.03.14

3m Radiated Emissions Chamber Above 1GHz Substitution Measurement									
Project #:		14U17676							
Date:		6/23/2014							
Test Engineer:		Ali Poushnejad							
Configuration:		EUT only							
Mode:		Band 5 REL 99, 850MHz							
Test Equipment:									
Substitution: Horn T59 Substitution, and 8ft SMA Cable									
Chamber			Pre-amplifier			Filter		Limit	
3m Chamber F			3m Chamber F			Part 22		Part 22	
Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes
Low Channel (826.4MHz)									
1.653	-21.5	H	3.0	34.9	1.0	-55.4	-13.0	42.4	
2.479	-19.2	H	3.0	35.4	1.0	-53.5	-13.0	40.5	
3.306	-18.4	H	3.0	36.4	1.0	-53.8	-13.0	40.8	
1.653	-17.8	V	3.0	34.9	1.0	-51.7	-13.0	38.7	
2.479	-18.8	V	3.0	35.4	1.0	-53.1	-13.0	40.1	
3.306	-17.9	V	3.0	36.4	1.0	-53.3	-13.0	40.3	
Mid Channel (836MHz)									
1.672	-21.5	H	3.0	34.9	1.0	-55.3	-13.0	42.3	
2.508	-20.6	H	3.0	35.3	1.0	-54.9	-13.0	41.9	
3.344	-18.1	H	3.0	36.4	1.0	-53.5	-13.0	40.5	
1.672	-18.7	V	3.0	34.9	1.0	-52.6	-13.0	39.6	
2.508	-15.7	V	3.0	35.3	1.0	-49.9	-13.0	36.9	
3.344	-17.7	V	3.0	36.4	1.0	-53.1	-13.0	40.1	
High Channel (846.6MHz)									
1.693	-23.7	H	3.0	34.9	1.0	-57.6	-13.0	44.6	
2.540	-19.0	H	3.0	35.4	1.0	-53.3	-13.0	40.3	
3.386	-18.9	H	3.0	36.4	1.0	-54.3	-13.0	41.3	
1.693	-15.6	V	3.0	34.9	1.0	-49.4	-13.0	36.4	
2.540	-18.9	V	3.0	35.4	1.0	-53.3	-13.0	40.3	
3.386	-17.6	V	3.0	36.4	1.0	-53.0	-13.0	40.0	

Rev. 03.03.14

3m Radiated Emissions Chamber Above 1GHz Substitution Measurement									
Project #:		14U17676							
Date:		6/23/2014							
Test Engineer:		Ali Poushnejad							
Configuration:		EUT only							
Mode:		Band 5 HSDPA, 850MHz							
Test Equipment:									
Substitution: Horn T59 Substitution, and 8ft SMA Cable									
Chamber			Pre-amplifier			Filter		Limit	
3m Chamber F			3m Chamber F					Part 22	
Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes
Low Channel (826.4MHz)									
1.653	-22.0	H	3.0	34.9	1.0	-55.9	-13.0	.42.9	
2.479	-16.8	H	3.0	35.4	1.0	-51.1	-13.0	.38.1	
3.306	-19.2	H	3.0	36.4	1.0	-54.7	-13.0	.41.7	
1.653	-20.6	V	3.0	34.9	1.0	-54.5	-13.0	.41.5	
2.479	-18.6	V	3.0	35.4	1.0	-52.9	-13.0	.39.9	
3.306	-18.5	V	3.0	36.4	1.0	-53.9	-13.0	.40.9	
Mid Channel (836MHz)									
1.672	-23.3	H	3.0	34.9	1.0	-57.2	-13.0	.44.2	
2.508	-19.4	H	3.0	35.3	1.0	-53.6	-13.0	.40.6	
3.344	-19.1	H	3.0	36.4	1.0	-54.5	-13.0	.41.5	
1.672	-20.5	V	3.0	34.9	1.0	-54.4	-13.0	.41.4	
2.508	-18.4	V	3.0	35.3	1.0	-52.7	-13.0	.39.7	
3.344	-17.1	V	3.0	36.4	1.0	-52.5	-13.0	.39.5	
High Channel (846.6MHz)									
1.693	-22.9	H	3.0	34.9	1.0	-56.8	-13.0	.43.8	
2.540	-19.1	H	3.0	35.4	1.0	-53.5	-13.0	.40.5	
3.386	-17.6	H	3.0	36.4	1.0	-53.0	-13.0	.40.0	
1.693	-14.1	V	3.0	34.9	1.0	-48.0	-13.0	.35.0	
2.540	-15.4	V	3.0	35.4	1.0	-49.8	-13.0	.36.8	
3.386	-17.6	V	3.0	36.4	1.0	-52.9	-13.0	.39.9	

Rev. 03.03.14

**3m Radiated Emissions Chamber
Above 1GHz Substitution Measurement**

Project #: 14U17676
Date: 6/23/2014
Test Engineer: Ali Poushnejad
Configuration: EUT only
Mode: Band 2 REL 99, 1900MHz

Test Equipment:

Substitution: Horn T59 Substitution, and 8ft SMA Cable

Chamber	Pre-amplifier	Filter	Limit
3m Chamber F	3m Chamber F		Part 24

Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes
Low Channel (1852.4MHz)									
3.705	-16.0	H	3.0	36.3	1.0	-51.3	-13.0	-38.3	
5.557	-16.4	H	3.0	35.6	1.0	-50.9	-13.0	-37.9	
3.705	-14.6	V	3.0	36.3	1.0	-49.9	-13.0	-36.9	
5.557	-16.5	V	3.0	35.6	1.0	-51.0	-13.0	-38.0	
Mid Channel (1880MHz)									
3.760	-16.3	H	3.0	36.3	1.0	-51.6	-13.0	-38.6	
5.640	-16.5	H	3.0	35.6	1.0	-51.0	-13.0	-38.0	
3.760	-14.9	V	3.0	36.3	1.0	-50.2	-13.0	-37.2	
5.640	-15.7	V	3.0	35.6	1.0	-50.3	-13.0	-37.3	
High Channel (1907.6MHz)									
3.815	-16.1	H	3.0	36.3	1.0	-51.4	-13.0	-38.4	
5.723	-16.4	H	3.0	35.6	1.0	-51.0	-13.0	-38.0	
3.815	-16.0	V	3.0	36.3	1.0	-51.3	-13.0	-38.3	
5.723	-15.9	V	3.0	35.6	1.0	-50.5	-13.0	-37.5	

Rev. 03.03.14

**3m Radiated Emissions Chamber
Above 1GHz Substitution Measurement**

Project #: 14U17676
Date: 6/23/2014
Test Engineer: Ali Poushnejad
Configuration: EUT only
Mode: Band 2 HSDPA, 1900MHz

Test Equipment:

Substitution: Horn T59 Substitution, and 8ft SMA Cable

Chamber	Pre-amplifier	Filter	Limit
3m Chamber F	3m Chamber F		Part 24

Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes
Low Channel (1852.4MHz)									
3.705	-16.1	H	3.0	36.3	1.0	51.4	-13.0	-38.4	
5.557	-15.3	H	3.0	35.6	1.0	49.9	-13.0	-36.9	
3.705	-14.9	V	3.0	36.3	1.0	50.2	-13.0	-37.2	
5.557	-15.7	V	3.0	35.6	1.0	50.3	-13.0	-37.3	
Mid Channel (1880MHz)									
3.760	-15.0	H	3.0	36.3	1.0	50.3	-13.0	-37.3	
5.640	-17.7	H	3.0	35.6	1.0	52.3	-13.0	-39.3	
3.760	-15.6	V	3.0	36.3	1.0	50.9	-13.0	-37.9	
5.640	-15.8	V	3.0	35.6	1.0	50.3	-13.0	-37.3	
High Channel (1907.6MHz)									
3.815	-15.1	H	3.0	36.3	1.0	50.4	-13.0	-37.4	
5.723	-16.5	H	3.0	35.6	1.0	51.1	-13.0	-38.1	
3.815	-15.4	V	3.0	36.3	1.0	50.6	-13.0	-37.6	
5.723	-14.2	V	3.0	35.6	1.0	48.8	-13.0	-35.8	

Rev. 03.03.14

**3m Radiated Emissions Chamber
Above 1GHz Substitution Measurement**

Project #: 14U17676
Date: 6/23/2014
Test Engineer: Ali Poushnejad
Configuration: EUT only
Mode: Band 4 REL 99, 1700MHz

Test Equipment:

Substitution: Horn T59 Substitution, and 8ft SMA Cable

Chamber	Pre-amplifier	Filter	Limit
3m Chamber F	3m Chamber F		Part 27

Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes
Low Channel (1712.4MHz)									
3.425	-14.5	H	3.0	36.4	1.0	-49.9	-13.0	-36.9	
5.137	-17.4	H	3.0	35.5	1.0	-51.9	-13.0	-38.9	
3.425	-16.1	V	3.0	36.4	1.0	-51.4	-13.0	-38.4	
5.137	-16.1	V	3.0	35.5	1.0	-50.7	-13.0	-37.7	
Mid Channel (1732.6MHz)									
3.465	-17.6	H	3.0	36.4	1.0	-53.0	-13.0	-40.0	
5.198	-16.8	H	3.0	35.5	1.0	-51.3	-13.0	-38.3	
3.465	-17.5	V	3.0	36.4	1.0	-52.9	-13.0	-39.9	
5.198	-15.0	V	3.0	35.5	1.0	-49.5	-13.0	-36.5	
High Channel (1752.6MHz)									
3.505	-18.1	H	3.0	36.4	1.0	-53.5	-13.0	-40.5	
5.258	-17.7	H	3.0	35.5	1.0	-52.2	-13.0	-39.2	
3.505	-17.6	V	3.0	36.4	1.0	-53.0	-13.0	-40.0	
5.258	-17.2	V	3.0	35.5	1.0	-51.7	-13.0	-38.7	

Rev. 03.03.14

**3m Radiated Emissions Chamber
Above 1GHz Substitution Measurement**

Project #: 14U17676
Date: 6/23/2014
Test Engineer: Ali Poushnejad
Configuration: EUT only
Mode: Band 4 HSDPA, 1700MHz

Test Equipment:

Substitution: Horn T59 Substitution, and 8ft SMA Cable

Chamber	Pre-amplifier	Filter	Limit
3m Chamber F	3m Chamber F		Part 27

Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes
Low Channel (1712.4MHz)									
3.425	-17.1	H	3.0	36.4	1.0	-52.5	-13.0	-39.5	
5.137	-16.2	H	3.0	35.5	1.0	-50.7	-13.0	-37.7	
3.425	-14.7	V	3.0	36.4	1.0	-50.1	-13.0	-37.1	
5.137	-15.6	V	3.0	35.5	1.0	-50.1	-13.0	-37.1	
Mid Channel (1732.6MHz)									
3.465	-18.4	H	3.0	36.4	1.0	-53.8	-13.0	-40.8	
5.198	-18.2	H	3.0	35.5	1.0	-52.6	-13.0	-39.6	
3.465	-17.3	V	3.0	36.4	1.0	-52.7	-13.0	-39.7	
5.198	-16.9	V	3.0	35.5	1.0	-51.3	-13.0	-38.3	
High Channel (1752.6MHz)									
3.505	-17.8	H	3.0	36.4	1.0	-53.1	-13.0	-40.1	
5.258	-16.7	H	3.0	35.5	1.0	-51.2	-13.0	-38.2	
3.505	-17.3	V	3.0	36.4	1.0	-52.7	-13.0	-39.7	
5.258	-16.7	V	3.0	35.5	1.0	-51.2	-13.0	-38.2	

Rev. 03.03.14

**3m Radiated Emissions Chamber
Above 1GHz Substitution Measurement**

Project #: 14U17676
Date: 06/24/14
Test Engineer: E.Yu
Configuration: EUT Only
Mode: CDMA2000, 1xRTT BC0

Test Equipment:

Substitution: Horn T59 Substitution, and 8ft SMA Cable

Chamber	Pre-amplifier	Filter	Limit
3m Chamber F	3m Chamber F		Part 22

Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes
Low Channel (824.7MHz)									
1.649	-15.4	H	3.0	34.9	1.0	-49.3	-13.0	-36.3	
2.474	-14.9	H	3.0	35.4	1.0	-49.3	-13.0	-36.3	
1.649	-15.8	V	3.0	34.9	1.0	-49.7	-13.0	-36.7	
2.474	-14.0	V	3.0	35.4	1.0	-48.4	-13.0	-35.4	
Mid Channel (836.52MHz)									
1.673	-14.2	H	3.0	34.9	1.0	-48.1	-13.0	-35.1	
2.510	-14.4	H	3.0	35.3	1.0	-48.7	-13.0	-35.7	
1.673	-14.9	V	3.0	34.9	1.0	-48.8	-13.0	-35.8	
2.510	-13.9	V	3.0	35.3	1.0	-48.2	-13.0	-35.2	
High Channel (848.31MHz)									
1.687	-15.6	H	3.0	34.9	1.0	-49.5	-13.0	-36.5	
2.544	-15.8	H	3.0	35.4	1.0	-50.1	-13.0	-37.1	
1.687	-15.1	V	3.0	34.9	1.0	-48.9	-13.0	-35.9	
2.544	-14.1	V	3.0	35.4	1.0	-48.5	-13.0	-35.5	

Rev. 03.03.14

**3m Radiated Emissions Chamber
Above 1GHz Substitution Measurement**

Project #: 14U17676
Date: 06/24/14
Test Engineer: Ali Poushnejad
Configuration: EUT Only
Mode: CDMA2000, EVDO_A BC0

Test Equipment:

Substitution: Horn T59 Substitution, and 8ft SMA Cable

Chamber	Pre-amplifier	Filter	Limit
3m Chamber F	3m Chamber F	Filter 01	Part 22

Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes
Low Channel (824.7MHz)									
1.649	-13.2	H	3.0	34.9	1.0	47.1	-13.0	34.1	
2.474	-12.6	H	3.0	35.4	1.0	46.9	-13.0	33.9	
1.649	-14.5	V	3.0	34.9	1.0	48.4	-13.0	35.4	
2.474	-16.5	V	3.0	35.4	1.0	50.9	-13.0	37.9	
Mid Channel (836.52MHz)									
1.673	-12.2	H	3.0	34.9	1.0	46.1	-13.0	33.1	
2.510	-14.0	H	3.0	35.3	1.0	48.3	-13.0	35.3	
1.673	-14.2	V	3.0	34.9	1.0	48.1	-13.0	35.1	
2.510	-12.6	V	3.0	35.3	1.0	46.9	-13.0	33.9	
High Channel (848.31MHz)									
1.697	-13.4	H	3.0	34.9	1.0	47.2	-13.0	34.2	
2.545	-13.1	H	3.0	35.4	1.0	47.5	-13.0	34.5	
1.697	-15.8	V	3.0	34.9	1.0	49.7	-13.0	36.7	
2.545	-13.5	V	3.0	35.4	1.0	47.9	-13.0	34.9	

Rev. 03.03.14

3m Radiated Emissions Chamber
Above 1GHz Substitution Measurement

Project #: 14U17676
Date: 06/24/14
Test Engineer: E.Yu
Configuration: EUT Only
Mode: CDMA2000, 1xRTT BC1

Test Equipment:

Substitution: Horn T59 Substitution, and 8ft SMA Cable

Chamber	Pre-amplifier	Filter	Limit
3m Chamber D	3m Chamber D	Filter 01	Part 24

Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes
Low Channel (1851.25MHz)									
3.703	-12.7	H	3.0	38.0	1.0	-49.7	-13.0	-36.7	
5.554	-12.7	H	3.0	37.4	1.0	-49.1	-13.0	-36.1	
3.703	-14.4	V	3.0	38.0	1.0	-51.4	-13.0	-38.4	
5.554	-12.4	V	3.0	37.4	1.0	-48.8	-13.0	-35.8	
Mid Channel (1880MHz)									
3.760	-14.6	H	3.0	38.0	1.0	-51.6	-13.0	-38.6	
5.640	-13.5	H	3.0	37.3	1.0	-49.8	-13.0	-36.8	
3.760	-15.1	V	3.0	38.0	1.0	-52.1	-13.0	-39.1	
5.640	-13.2	V	3.0	37.3	1.0	-49.6	-13.0	-36.6	
High Channel (1908.75MHz)									
3.818	-12.9	H	3.0	37.9	1.0	-49.9	-13.0	-36.9	
5.726	-14.2	H	3.0	37.3	1.0	-50.5	-13.0	-37.5	
3.818	-10.2	V	3.0	37.9	1.0	-47.1	-13.0	-34.1	
5.726	-13.5	V	3.0	37.3	1.0	-49.8	-13.0	-36.8	

Rev. 03.03.14

3m Radiated Emissions Chamber
Above 1GHz Substitution Measurement

Project #: 14U17676
Date: 06/24/14
Test Engineer: Ali Poushnejad
Configuration: EUT only
Mode: CDMA EV DO_A BC 1

Test Equipment:

Substitution: Horn T59 Substitution, and 8ft SMA Cable

Chamber	Pre-amplifier	Filter	Limit
3m Chamber F	3m Chamber F		Part 24

Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes
Low Channel (1851.25MHz)									
3.703	-12.0	H	3.0	36.3	1.0	47.4	-13.0	-34.4	
5.554	-15.8	H	3.0	35.6	1.0	50.4	-13.0	-37.4	
3.703	-15.1	V	3.0	36.3	1.0	50.4	-13.0	-37.4	
5.554	-16.6	V	3.0	35.6	1.0	51.2	-13.0	-38.2	
Mid Channel (1880.0)									
3.760	-13.5	H	3.0	36.3	1.0	48.7	-13.0	-35.7	
5.640	-16.2	H	3.0	35.6	1.0	50.8	-13.0	-37.8	
3.760	-13.9	V	3.0	36.3	1.0	49.2	-13.0	-36.2	
5.640	-15.3	V	3.0	35.6	1.0	49.9	-13.0	-36.9	
High Channel (1908.75MHz)									
3.818	-15.5	H	3.0	36.3	1.0	50.8	-13.0	-37.8	
5.726	-17.3	H	3.0	35.6	1.0	51.9	-13.0	-38.9	
3.818	-13.5	V	3.0	36.3	1.0	48.7	-13.0	-35.7	
5.726	-16.3	V	3.0	35.6	1.0	50.9	-13.0	-37.9	

Rev. 03.03.14

3m Radiated Emissions Chamber Above 1GHz Substitution Measurement

Project #: 14U17676
Date: 6/24/2014
Test Engineer: T Wang
Configuration: EUT Only
Mode: CDMA 2000 1XRTT BC15

Test Equipment:

Substitution: Horn T59 Substitution, and 8ft SMA Cable

Chamber		Pre-amplifier		Filter		Limit			
3m Chamber F		3m Chamber F				Part 27			
Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes
Low Channel (1711.25MHz)									
3.423	-15.7	H	3.0	36.4	1.0	-51.1	-13.0	-38.1	
5.134	-11.0	H	3.0	35.5	1.0	-45.6	-13.0	-32.6	
3.423	-15.9	V	3.0	36.4	1.0	-51.3	-13.0	-38.3	
5.134	-9.4	V	3.0	35.5	1.0	-43.9	-13.0	-30.9	
Mid Channel (1732.5MHz)									
3.465	-11.5	H	3.0	36.4	1.0	-46.8	-13.0	-33.8	
5.198	-7.5	H	3.0	35.5	1.0	-42.0	-13.0	-29.0	
3.465	-15.4	V	3.0	36.4	1.0	-50.8	-13.0	-37.8	
5.198	-10.1	V	3.0	35.5	1.0	-44.6	-13.0	-31.6	
High Channel (1753.75MHz)									
3.508	-16.7	H	3.0	36.4	1.0	-52.1	-13.0	-39.1	
5.261	-13.8	H	3.0	35.5	1.0	-48.3	-13.0	-35.3	
3.508	-15.3	V	3.0	36.4	1.0	-50.7	-13.0	-37.7	
5.261	-13.4	V	3.0	35.5	1.0	-47.9	-13.0	-34.9	

3m Radiated Emissions Chamber
Above 1GHz Substitution Measurement

Project #: 14U17676
Date: 6/24/2014
Test Engineer: Ali Poushnejad
Configuration: EUT Only
Mode: CDMA EVDO_A BC15

Test Equipment:

Substitution: Horn T59 Substitution, and 8ft SMA Cable

Chamber		Pre-amplifier		Filter		Limit		
3m Chamber F		3m Chamber F				Part 27		
Frequency (GHz)								
SG reading (dBm)								
Ant. Pol. (H/V)								
Distance								
Preamp								
Attenuator								
EIRP								
Limit								
Delta								
Notes								
Low Channel (1711.25MHz)								
3.423	-4.8	H	3.0	36.4	1.0	-40.2	-13.0	-27.2
5.134	-9.8	H	3.0	35.5	1.0	-44.3	-13.0	-31.3
6.845	-2.5	H	3.0	35.9	1.0	-37.4	-13.0	-24.4
3.423	-5.0	V	3.0	36.4	1.0	-40.4	-13.0	-27.4
5.134	-8.9	V	3.0	35.5	1.0	-43.4	-13.0	-30.4
6.845	1.7	V	3.0	35.9	1.0	-33.1	-13.0	-20.1
Mid Channel (1732.5MHz)								
3.465	-2.3	H	3.0	36.4	1.0	-37.7	-13.0	-24.7
5.198	-7.1	H	3.0	35.5	1.0	-41.5	-13.0	-28.5
6.930	-3.9	H	3.0	35.9	1.0	-38.8	-13.0	-25.8
3.465	-4.4	V	3.0	36.4	1.0	-39.8	-13.0	-26.8
5.198	-5.8	V	3.0	35.5	1.0	-40.2	-13.0	-27.2
6.930	-0.9	V	3.0	35.9	1.0	-35.8	-13.0	-22.8
High Channel (1753.75MHz)								
3.508	-9.3	H	3.0	36.4	1.0	-44.7	-13.0	-31.7
5.261	-8.2	H	3.0	35.5	1.0	-42.7	-13.0	-29.7
7.015	-5.3	H	3.0	35.9	1.0	-40.1	-13.0	-27.1
3.508	-9.4	V	3.0	36.4	1.0	-44.7	-13.0	-31.7
5.261	-5.8	V	3.0	35.5	1.0	-40.3	-13.0	-27.3
7.015	-1.6	V	3.0	35.9	1.0	-36.5	-13.0	-23.5

Rev. 03.03.14

3m Radiated Emissions Chamber
Above 1GHz Substitution Measurement

Project #: 14U17676
 Date: 06/24/14
 Test Engineer: E.Yu
 Configuration: EUT Only
 Mode: CDMA2000, 1xRTT BC10

Test Equipment:

Substitution: Horn T59 Substitution, and 8ft SMA Cable

Chamber	Pre-amplifier	Filter	Limit
3m Chamber F	3m Chamber F		Part 90

Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes
Low Channel (817.25MHz)									
1.635	-14.7	H	3.0	34.9	1.0	-48.6	-13.0	-35.6	
2.452	-15.6	H	3.0	35.5	1.0	-50.1	-13.0	-37.1	
1.635	-14.6	V	3.0	34.9	1.0	-48.5	-13.0	-35.5	
2.452	-14.3	V	3.0	35.5	1.0	-48.8	-13.0	-35.8	
Mid Channel (820MHz)									
1.640	-13.6	H	3.0	34.9	1.0	-47.5	-13.0	-34.5	
2.460	-16.2	H	3.0	35.4	1.0	-50.7	-13.0	-37.7	
1.640	-15.9	V	3.0	34.9	1.0	-49.8	-13.0	-36.8	
2.460	-14.3	V	3.0	35.4	1.0	-48.8	-13.0	-35.8	
High Channel (822.75MHz)									
1.646	-13.8	H	3.0	34.9	1.0	-47.7	-13.0	-34.7	
2.468	-17.2	H	3.0	35.4	1.0	-51.6	-13.0	-38.6	
1.646	-13.3	V	3.0	34.9	1.0	-47.2	-13.0	-34.2	
2.468	-16.3	V	3.0	35.4	1.0	-50.7	-13.0	-37.7	

Rev. 03.03.14

3m Radiated Emissions Chamber
Above 1GHz Substitution Measurement

Project #: 14U17676
Date: 06/24/14
Test Engineer: Ali Poushnejad
Configuration: EUT Only
Mode: CDMA2000, EV DO_A BC10

Test Equipment:

Substitution: Horn T59 Substitution, and 8ft SMA Cable

Chamber	Pre-amplifier	Filter	Limit
3m Chamber F	3m Chamber F		Part 90

Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes
Low Channel (817.25MHz)									
1.635	-12.6	H	3.0	34.9	1.0	-46.5	-13.0	-33.5	
2.452	-14.1	H	3.0	35.5	1.0	-48.6	-13.0	-35.6	
1.635	-13.7	V	3.0	34.9	1.0	-47.6	-13.0	-34.6	
2.452	-11.6	V	3.0	35.5	1.0	-46.0	-13.0	-33.0	
Mid Channel (820.0MHz)									
1.640	-12.7	H	3.0	34.9	1.0	-46.6	-13.0	-33.6	
2.460	-11.5	H	3.0	35.4	1.0	-45.9	-13.0	-32.9	
1.640	-15.7	V	3.0	34.9	1.0	-49.7	-13.0	-36.7	
2.460	-11.5	V	3.0	35.4	1.0	-45.9	-13.0	-32.9	
High Channel (822.75MHz)									
1.646	-12.9	H	3.0	34.9	1.0	-46.8	-13.0	-33.8	
2.468	-13.1	H	3.0	35.4	1.0	-47.5	-13.0	-34.5	
1.646	-15.2	V	3.0	34.9	1.0	-49.1	-13.0	-36.1	
2.468	-11.4	V	3.0	35.4	1.0	-45.8	-13.0	-32.8	

Rev. 03.03.14

10.3.2.UAT

GPRS, 850MHz BAND 5

3m Radiated Emissions Chamber Above 1GHz Substitution Measurement									
Project #:		14U17676							
Date:		06/25/14							
Test Engineer:		E. Yu							
Configuration:		EUT only							
Mode:		GPRS 850MHz							
<u>Test Equipment:</u>									
Substitution: Horn T59 Substitution, and 8ft SMA Cable									
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber F		3m Chamber F				Part 22			
Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes
Low Channel (824.2MHz)									
1.648	-1.2	H	3.0	34.9	1.0	-35.1	-13.0	-22.1	
2.472	-11.6	H	3.0	35.4	1.0	-46.0	-13.0	-33.0	
1.648	-1.5	V	3.0	34.9	1.0	-35.4	-13.0	-22.4	
2.472	-13.5	V	3.0	35.4	1.0	-47.9	-13.0	-34.9	
Mid Channel (836.6MHz)									
1.673	2.6	H	3.0	34.9	1.0	-31.3	-13.0	-18.3	
2.510	-12.9	H	3.0	35.3	1.0	-47.2	-13.0	-34.2	
1.673	-3.0	V	3.0	34.9	1.0	-36.9	-13.0	-23.9	
2.510	-14.2	V	3.0	35.3	1.0	-48.5	-13.0	-35.5	
High Channel (848.8MHz)									
1.698	-0.9	H	3.0	34.9	1.0	-34.7	-13.0	-21.7	
2.546	-14.7	H	3.0	35.4	1.0	-49.1	-13.0	-36.1	
1.698	-0.9	V	3.0	34.9	1.0	-34.8	-13.0	-21.8	
2.546	-14.9	V	3.0	35.4	1.0	-49.3	-13.0	-36.3	

Rev. 03.03.14

3m Radiated Emissions Chamber Above 1GHz Substitution Measurement									
Company: Project #: 14U17676 Date: 06/21/14 Test Engineer: T. Chu Configuration: EUT only Mode: EGPRS 850MHz									
Test Equipment: Substitution: Horn T59 Substitution, and 8ft SMA Cable									
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber E	3m Chamber E	3m Chamber E	3m Chamber E	3m Chamber E	3m Chamber E	Part 22	Part 22	Part 22	Part 22
Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes
Low Channel (824.2MHz)									
1.648	-4.5	H	3.0	37.6	1.0	-41.1	-13.0	-28.1	
2.472	-15.9	H	3.0	38.0	1.0	-52.8	-13.0	-39.8	
1.648	-5.4	V	3.0	37.6	1.0	-42.0	-13.0	-29.0	
2.472	-13.2	V	3.0	38.0	1.0	-50.2	-13.0	-37.2	
Mid Channel (836.6MHz)									
1.673	-1.2	H	3.0	37.6	1.0	-37.7	-13.0	-24.7	
2.510	-14.7	H	3.0	37.9	1.0	-51.6	-13.0	-38.6	
1.673	-2.8	V	3.0	37.6	1.0	-39.4	-13.0	-26.4	
2.510	-12.7	V	3.0	37.9	1.0	-49.7	-13.0	-36.7	
High Channel (848.8MHz)									
1.698	-5.2	H	3.0	37.6	1.0	-41.8	-13.0	-28.8	
2.546	-11.4	H	3.0	38.0	1.0	-48.4	-13.0	-35.4	
1.698	-11.9	V	3.0	37.6	1.0	-48.5	-13.0	-35.5	
2.546	-9.6	V	3.0	38.0	1.0	-46.6	-13.0	-33.6	
Rev. 03.03.14									

3m Radiated Emissions Chamber Above 1GHz Substitution Measurement									
Project #:		14U17676							
Date:		06/12/14							
Test Engineer:		E. Yu							
Configuration:		EUT only							
Mode:		GPRS 1900MHz							
<u>Test Equipment:</u> Substitution: Horn T59 Substitution, and 8ft SMA Cable									
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber F		3m Chamber F				Part 24			
Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes
Low Channel (1850.2MHz)									
3.700	-11.6	H	3.0	36.3	1.0	-46.9	-13.0	-33.9	
5.551	-10.9	H	3.0	35.6	1.0	-45.5	-13.0	-32.5	
3.700	-12.4	V	3.0	36.3	1.0	-47.7	-13.0	-34.7	
5.551	-11.4	V	3.0	35.6	1.0	-46.0	-13.0	-33.0	
Mid Channel (1880.0)									
3.760	-10.2	H	3.0	36.3	1.0	-45.5	-13.0	-32.5	
5.640	-10.8	H	3.0	35.6	1.0	-45.4	-13.0	-32.4	
3.760	-11.9	V	3.0	36.3	1.0	-47.2	-13.0	-34.2	
5.640	-11.1	V	3.0	35.6	1.0	-45.6	-13.0	-32.6	
High Channel (1909.8MHz)									
3.820	-10.8	H	3.0	36.3	1.0	-46.1	-13.0	-33.1	
5.729	-10.8	H	3.0	35.6	1.0	-45.4	-13.0	-32.4	
3.820	-10.4	V	3.0	36.3	1.0	-45.7	-13.0	-32.7	
5.729	-11.3	V	3.0	35.6	1.0	-45.9	-13.0	-32.9	

Rev. 03.03.14

3m Radiated Emissions Chamber Above 1GHz Substitution Measurement									
Project #: 14U17676 Date: 06/25/14 Test Engineer: E. Yu Configuration: EUT only Mode: EGPRS 1900MHz									
Test Equipment: Substitution: Horn T59 Substitution, and 8ft SMA Cable									
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber F		3m Chamber F					Part 24		
Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes
Low Channel (1850.2MHz)									
3.700	-11.7	H	3.0	36.3	1.0	-47.0	-13.0	-34.0	
5.551	-10.5	H	3.0	35.6	1.0	-45.0	-13.0	-32.0	
3.700	-12.3	V	3.0	36.3	1.0	-47.6	-13.0	-34.6	
5.551	-11.4	V	3.0	35.6	1.0	-46.0	-13.0	-33.0	
Mid Channel (1880.0)									
3.760	-11.2	H	3.0	36.3	1.0	-46.5	-13.0	-33.5	
5.640	-10.1	H	3.0	35.6	1.0	-44.7	-13.0	-31.7	
3.760	-11.8	V	3.0	36.3	1.0	-47.1	-13.0	-34.1	
5.640	-11.4	V	3.0	35.6	1.0	-46.0	-13.0	-33.0	
High Channel (1909.8MHz)									
3.820	-11.4	H	3.0	36.3	1.0	-46.7	-13.0	-33.7	
5.729	-10.2	H	3.0	35.6	1.0	-44.7	-13.0	-31.7	
3.820	-12.0	V	3.0	36.3	1.0	-47.3	-13.0	-34.3	
5.729	-11.0	V	3.0	35.6	1.0	-45.6	-13.0	-32.6	

Rev. 03.03.14

3m Radiated Emissions Chamber Above 1GHz Substitution Measurement									
Project #: 14U17676 Date: 6/23/2014 Test Engineer: Ali Poushnejad Configuration: EUT only Mode: Band 5 REL 99, 850MHz									
Test Equipment: Substitution: Horn T59 Substitution, and 8ft SMA Cable									
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber F		3m Chamber F				Part 22			
Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes
Low Channel (826.4MHz)									
1.653	-24.0	H	3.0	34.9	1.0	-57.9	-13.0	44.9	
2.479	-19.2	H	3.0	35.4	1.0	-53.6	-13.0	40.6	
3.306	-19.1	H	3.0	36.4	1.0	-54.5	-13.0	41.5	
1.653	-21.8	V	3.0	34.9	1.0	-55.7	-13.0	42.7	
2.479	-18.3	V	3.0	35.4	1.0	-52.7	-13.0	39.7	
3.306	-17.4	V	3.0	36.4	1.0	-52.8	-13.0	39.8	
Mid Channel (836MHz)									
1.672	-22.4	H	3.0	34.9	1.0	-56.3	-13.0	43.3	
2.508	-19.9	H	3.0	35.3	1.0	-54.2	-13.0	41.2	
3.344	-18.7	H	3.0	36.4	1.0	-54.1	-13.0	41.1	
1.672	-20.3	V	3.0	34.9	1.0	-54.2	-13.0	41.2	
2.508	-18.7	V	3.0	35.3	1.0	-53.0	-13.0	40.0	
3.344	-17.7	V	3.0	36.4	1.0	-53.1	-13.0	40.1	
High Channel (846.6MHz)									
1.693	-23.5	H	3.0	34.9	1.0	-57.4	-13.0	44.4	
2.540	-20.1	H	3.0	35.4	1.0	-54.4	-13.0	41.4	
3.386	-17.3	H	3.0	36.4	1.0	-52.7	-13.0	39.7	
1.693	-21.2	V	3.0	34.9	1.0	-55.1	-13.0	42.1	
2.540	-17.9	V	3.0	35.4	1.0	-52.3	-13.0	39.3	
3.386	-16.5	V	3.0	36.4	1.0	-51.9	-13.0	38.9	

Rev. 03.03.14

3m Radiated Emissions Chamber Above 1GHz Substitution Measurement									
Project #: 14U17676 Date: 6/23/2014 Test Engineer: Ali Poushnejad Configuration: EUT only Mode: Band 5 HSDPA, 850MHz									
Test Equipment: Substitution: Horn T59 Substitution, and 8ft SMA Cable									
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber F		3m Chamber F				Part 22			
Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes
Low Channel (826.4MHz)									
1.653	-24.0	H	3.0	34.9	1.0	-57.9	-13.0	-44.9	
2.479	-19.0	H	3.0	35.4	1.0	-53.4	-13.0	-40.4	
3.306	-18.1	H	3.0	36.4	1.0	-53.5	-13.0	-40.5	
1.653	-21.0	V	3.0	34.9	1.0	-54.9	-13.0	-41.9	
2.479	-15.4	V	3.0	35.4	1.0	-49.7	-13.0	-36.7	
3.306	-18.3	V	3.0	36.4	1.0	-53.7	-13.0	-40.7	
Mid Channel (836MHz)									
1.672	-22.6	H	3.0	34.9	1.0	-56.5	-13.0	-43.5	
2.508	-19.4	H	3.0	35.3	1.0	-53.7	-13.0	-40.7	
3.344	-17.9	H	3.0	36.4	1.0	-53.3	-13.0	-40.3	
1.672	-20.9	V	3.0	34.9	1.0	-54.8	-13.0	-41.8	
2.508	-19.3	V	3.0	35.3	1.0	-53.8	-13.0	-40.8	
3.344	-17.2	V	3.0	36.4	1.0	-52.6	-13.0	-39.6	
High Channel (846.6MHz)									
1.693	-23.8	H	3.0	34.9	1.0	-57.7	-13.0	-44.7	
2.540	-20.1	H	3.0	35.4	1.0	-54.5	-13.0	-41.5	
3.386	-16.5	H	3.0	36.4	1.0	-51.9	-13.0	-38.9	
1.693	-21.5	V	3.0	34.9	1.0	-55.3	-13.0	-42.3	
2.540	-18.7	V	3.0	35.4	1.0	-53.1	-13.0	-40.1	
3.386	-17.2	V	3.0	36.4	1.0	-52.6	-13.0	-39.6	

Rev. 03.03.14

3m Radiated Emissions Chamber Above 1GHz Substitution Measurement									
Project #:		14U17676							
Date:		6/23/2014							
Test Engineer:		Ali Poushnejad							
Configuration:		EUT only							
Mode:		Band 2 REL 99, 1900MHz							
Test Equipment:									
Substitution: Horn T59 Substitution, and 8ft SMA Cable									
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber F		3m Chamber F				Part 24			
Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes
Low Channel (1852.4MHz)									
3.705	-16.5	H	3.0	36.3	1.0	-51.8	-13.0	-38.8	
5.557	-15.1	H	3.0	35.6	1.0	-49.6	-13.0	-36.6	
3.705	-15.5	V	3.0	36.3	1.0	-50.8	-13.0	-37.8	
5.557	-14.8	V	3.0	35.6	1.0	-49.4	-13.0	-36.4	
Mid Channel (1880MHz)									
3.760	-15.7	H	3.0	36.3	1.0	-51.0	-13.0	-38.0	
5.640	-16.5	H	3.0	35.6	1.0	-51.0	-13.0	-38.0	
3.760	-14.0	V	3.0	36.3	1.0	-49.3	-13.0	-36.3	
5.640	-16.4	V	3.0	35.6	1.0	-51.0	-13.0	-38.0	
High Channel (1907.6MHz)									
3.815	-15.3	H	3.0	36.3	1.0	-50.5	-13.0	-37.5	
5.723	-17.5	H	3.0	35.6	1.0	-52.1	-13.0	-39.1	
3.815	-15.1	V	3.0	36.3	1.0	-50.4	-13.0	-37.4	
5.723	-16.2	V	3.0	35.6	1.0	-50.8	-13.0	-37.8	
Rev. 03.03.14									

3m Radiated Emissions Chamber Above 1GHz Substitution Measurement									
Project #:		14U17676							
Date:		6/23/2014							
Test Engineer:		Ali Poushnejad							
Configuration:		EUT only							
Mode:		Band 2 HSDPA, 1900MHz							
Test Equipment:									
Substitution: Horn T59 Substitution, and 8ft SMA Cable									
Chamber			Pre-amplifier			Filter		Limit	
3m Chamber F			3m Chamber F					Part 24	
Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes
Low Channel (1852.4MHz)									
3.705	-16.7	H	3.0	36.3	1.0	-52.0	-13.0	-39.0	
5.557	-15.6	H	3.0	35.6	1.0	-50.1	-13.0	-37.1	
3.705	-15.8	V	3.0	36.3	1.0	-51.2	-13.0	-38.2	
5.557	-16.6	V	3.0	35.6	1.0	-51.1	-13.0	-38.1	
Mid Channel (1880MHz)									
3.760	-16.7	H	3.0	36.3	1.0	-52.0	-13.0	-39.0	
5.640	-16.3	H	3.0	35.6	1.0	-50.9	-13.0	-37.9	
3.760	-14.7	V	3.0	36.3	1.0	-50.0	-13.0	-37.0	
5.640	-17.1	V	3.0	35.6	1.0	-51.6	-13.0	-38.6	
High Channel (1907.6MHz)									
3.815	-16.0	H	3.0	36.3	1.0	-51.3	-13.0	-38.3	
5.723	-16.5	H	3.0	35.6	1.0	-51.1	-13.0	-38.1	
3.815	-16.4	V	3.0	36.3	1.0	-51.6	-13.0	-38.6	
5.723	-16.3	V	3.0	35.6	1.0	-50.9	-13.0	-37.9	
Rev. 03.03.14									

3m Radiated Emissions Chamber Above 1GHz Substitution Measurement																	
Project #:		14U17676															
Date:		6/23/2014															
Test Engineer:		Ali Poushnejad															
Configuration:		EUT only															
Mode:		Band 4 REL 99, 1700MHz															
<u>Test Equipment:</u>																	
Substitution: Horn T59 Substitution, and 8ft SMA Cable																	
Chamber		Pre-amplifier		Filter		Limit											
3m Chamber F		3m Chamber F				Part 27											
Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes								
Low Channel (1712.4MHz)																	
3.425	-18.0	H	3.0	36.4	1.0	-53.4	-13.0	-40.4									
5.137	-16.7	H	3.0	35.5	1.0	-51.2	-13.0	-38.2									
3.425	-16.9	V	3.0	36.4	1.0	-52.2	-13.0	-39.2									
5.137	-16.1	V	3.0	35.5	1.0	-50.6	-13.0	-37.6									
Mid Channel (1732.6MHz)																	
3.465	-18.7	H	3.0	36.4	1.0	-54.0	-13.0	-41.0									
5.198	-17.1	H	3.0	35.5	1.0	-51.6	-13.0	-38.6									
3.465	-17.2	V	3.0	36.4	1.0	-52.5	-13.0	-39.5									
5.198	-17.2	V	3.0	35.5	1.0	-51.7	-13.0	-38.7									
High Channel (1752.6MHz)																	
3.505	-17.8	H	3.0	36.4	1.0	-53.2	-13.0	-40.2									
5.258	-17.4	H	3.0	35.5	1.0	-51.9	-13.0	-38.9									
3.505	-18.7	V	3.0	36.4	1.0	-54.0	-13.0	-41.0									
5.258	-17.2	V	3.0	35.5	1.0	-51.7	-13.0	-38.7									

Rev. 03.03.14

3m Radiated Emissions Chamber Above 1GHz Substitution Measurement									
Project #:		14U17676							
Date:		6/23/2014							
Test Engineer:		Ali Poushnejad							
Configuration:		EUT only							
Mode:		Band 4 HSDPA, 1700MHz							
Test Equipment:									
Substitution: Horn T59 Substitution, and 8ft SMA Cable									
Chamber			Pre-amplifier			Filter		Limit	
3m Chamber F			3m Chamber F					Part 27	
Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes
Low Channel (1712.4MHz)									
3.425	-18.2	H	3.0	36.4	1.0	-53.6	-13.0	-40.6	
5.137	-17.3	H	3.0	35.5	1.0	-51.8	-13.0	-38.8	
3.425	-17.6	V	3.0	36.4	1.0	-52.9	-13.0	-39.9	
5.137	-16.5	V	3.0	35.5	1.0	-51.0	-13.0	-38.0	
Mid Channel (1732.6MHz)									
3.465	-18.9	H	3.0	36.4	1.0	-54.2	-13.0	-41.2	
5.198	-17.7	H	3.0	35.5	1.0	-52.1	-13.0	-39.1	
3.465	-18.3	V	3.0	36.4	1.0	-53.6	-13.0	-40.6	
5.198	-15.8	V	3.0	35.5	1.0	-50.3	-13.0	-37.3	
High Channel (1752.6MHz)									
3.505	-16.8	H	3.0	36.4	1.0	-52.2	-13.0	-39.2	
5.258	-17.2	H	3.0	35.5	1.0	-51.7	-13.0	-38.7	
3.505	-18.2	V	3.0	36.4	1.0	-53.5	-13.0	-40.5	
5.258	-17.4	V	3.0	35.5	1.0	-51.9	-13.0	-38.9	
Rev. 03.03.14									

3m Radiated Emissions Chamber Above 1GHz Substitution Measurement									
Project #: 14U17676 Date: 06/24/14 Test Engineer: T Wang Configuration: EUT Only Mode: CDMA2000, 1xRTT BC0									
Test Equipment: Substitution: Horn T59 Substitution, and 8ft SMA Cable									
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber F		3m Chamber F				Part 22			
Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes
Low Channel (824.7MHz)									
1.649	-20.0	H	3.0	34.9	1.0	-53.9	-13.0	-40.9	
2.474	-18.5	H	3.0	35.4	1.0	-52.8	-13.0	-39.8	
1.649	-23.1	V	3.0	34.9	1.0	-57.0	-13.0	-44.0	
2.474	-17.8	V	3.0	35.4	1.0	-52.2	-13.0	-39.2	
Mid Channel (836.52MHz)									
1.673	-7.9	H	3.0	34.9	1.0	-41.8	-13.0	-28.8	
2.510	-13.3	H	3.0	35.3	1.0	-47.6	-13.0	-34.6	
1.673	-10.0	V	3.0	34.9	1.0	-43.9	-13.0	-30.9	
2.510	-16.5	V	3.0	35.3	1.0	-50.8	-13.0	-37.8	
High Channel (848.31MHz)									
1.696	-12.6	H	3.0	34.9	1.0	-46.5	-13.0	-33.5	
2.544	-16.2	H	3.0	35.4	1.0	-50.6	-13.0	-37.6	
1.687	-10.8	V	3.0	34.9	1.0	-44.7	-13.0	-31.7	
2.544	-15.4	V	3.0	35.4	1.0	-49.8	-13.0	-36.8	
Rev. 03.03.14									

3m Radiated Emissions Chamber Above 1GHz Substitution Measurement									
Project #: 14U17676 Date: 06/24/14 Test Engineer: Ali Poushnejad Configuration: EUT Only Mode: CDMA2000, EVDO_A BC0									
Test Equipment: Substitution: Horn T59 Substitution, and 8ft SMA Cable									
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber F		3m Chamber F				Part 22			
Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes
Low Channel (824.7MHz)									
1.649	-24.6	H	3.0	34.9	1.0	-58.5	-13.0	-45.5	
2.474	-17.2	H	3.0	35.4	1.0	-51.6	-13.0	-38.6	
1.649	-22.9	V	3.0	34.9	1.0	-56.8	-13.0	-43.8	
2.474	-19.3	V	3.0	35.4	1.0	-53.7	-13.0	-40.7	
Mid Channel (836.52MHz)									
1.673	-23.9	H	3.0	34.9	1.0	-57.8	-13.0	-44.8	
2.510	-20.4	H	3.0	35.3	1.0	-54.7	-13.0	-41.7	
1.673	-22.4	V	3.0	34.9	1.0	-56.3	-13.0	-43.3	
2.510	-18.7	V	3.0	35.3	1.0	-53.0	-13.0	-40.0	
High Channel (848.31MHz)									
1.697	-23.1	H	3.0	34.9	1.0	-56.9	-13.0	-43.9	
2.545	-21.0	H	3.0	35.4	1.0	-55.4	-13.0	-42.4	
1.697	-22.3	V	3.0	34.9	1.0	-56.1	-13.0	-43.1	
2.545	-19.1	V	3.0	35.4	1.0	-53.4	-13.0	-40.4	
Rev. 03.03.14									

**3m Radiated Emissions Chamber
Above 1GHz Substitution Measurement**

Project #: 14U17676
Date: 06/24/14
Test Engineer: T Wang
Configuration: EUT Only
Mode: CDMA2000, 1xRTT BC1

Test Equipment:
 Substitution: Horn T59 Substitution, and 8ft SMA Cable

Chamber	Pre-amplifier	Filter	Limit						
3m Chamber F	3m Chamber F		Part 24						
Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes
Low Channel (1851.25MHz)									
3.703	-13.7	H	3.0	36.3	1.0	-49.0	-13.0	-36.0	
5.554	-12.8	H	3.0	35.6	1.0	-47.3	-13.0	-34.3	
3.703	-12.5	V	3.0	36.3	1.0	-47.8	-13.0	-34.8	
5.554	-12.2	V	3.0	35.6	1.0	-46.8	-13.0	-33.8	
Mid Channel (1880MHz)									
3.760	-13.6	H	3.0	36.3	1.0	-48.9	-13.0	-35.9	
5.640	-12.4	H	3.0	35.6	1.0	-47.0	-13.0	-34.0	
3.760	-11.9	V	3.0	36.3	1.0	-47.2	-13.0	-34.2	
5.640	-11.4	V	3.0	35.6	1.0	-46.0	-13.0	-33.0	
High Channel (1908.75MHz)									
3.818	-12.5	H	3.0	36.3	1.0	-47.8	-13.0	-34.8	
5.726	-13.5	H	3.0	35.6	1.0	-48.0	-13.0	-35.0	
3.818	-12.4	V	3.0	36.3	1.0	-47.7	-13.0	-34.7	
5.726	-13.2	V	3.0	35.6	1.0	-47.8	-13.0	-34.8	

Rev. 03.03.14

3m Radiated Emissions Chamber Above 1GHz Substitution Measurement									
Project #:		14U17676							
Date:		06/24/14							
Test Engineer:		Ali Poushnejad							
Configuration:		EUT only							
Mode:		CDMA EV DO_A BC 1							
Test Equipment:									
Substitution: Horn T59 Substitution, and 8ft SMA Cable									
Chamber			Pre-amplifier			Filter		Limit	
3m Chamber F			3m Chamber F					Part 24	
Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes
Low Channel (1851.25MHz)									
3.703	-13.3	H	3.0	36.3	1.0	-48.6	-13.0	-35.6	
5.554	-15.3	H	3.0	35.6	1.0	-49.8	-13.0	-36.8	
3.703	-14.1	V	3.0	36.3	1.0	-49.4	-13.0	-36.4	
5.554	-15.3	V	3.0	35.6	1.0	-49.9	-13.0	-36.9	
Mid Channel (1880.0)									
3.760	-15.1	H	3.0	36.3	1.0	-50.4	-13.0	-37.4	
5.640	-15.9	H	3.0	35.6	1.0	-50.4	-13.0	-37.4	
3.760	-13.9	V	3.0	36.3	1.0	-49.2	-13.0	-36.2	
5.640	-15.1	V	3.0	35.6	1.0	-49.7	-13.0	-36.7	
High Channel (1908.75MHz)									
3.818	-15.1	H	3.0	36.3	1.0	-50.4	-13.0	-37.4	
5.726	-15.3	H	3.0	35.6	1.0	-49.9	-13.0	-36.9	
3.818	-15.1	V	3.0	36.3	1.0	-50.4	-13.0	-37.4	
5.726	-15.1	V	3.0	35.6	1.0	-49.6	-13.0	-36.6	
Rev. 03.03.14									

3m Radiated Emissions Chamber Above 1GHz Substitution Measurement									
Project #:		14U17676							
Date:		6/24/2014							
Test Engineer:		T Wang							
Configuration:		EUT Only							
Mode:		CDMA 2000 1XRTT BC15							
Test Equipment:									
Substitution: Horn T59 Substitution, and 8ft SMA Cable									
Chamber			Pre-amplifier			Filter		Limit	
3m Chamber F			3m Chamber F					Part 27	
Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes
Low Channel (1711.25MHz)									
3.423	-14.7	H	3.0	36.4	1.0	-50.1	-13.0	-37.1	
5.134	-13.4	H	3.0	35.5	1.0	-48.0	-13.0	-35.0	
3.423	-14.4	V	3.0	36.4	1.0	-49.8	-13.0	-36.8	
5.134	-12.8	V	3.0	35.5	1.0	-47.3	-13.0	-34.3	
Mid Channel (1732.5MHz)									
3.465	-15.9	H	3.0	36.4	1.0	-51.2	-13.0	-38.2	
5.198	-14.1	H	3.0	35.5	1.0	-48.6	-13.0	-35.6	
3.465	-14.9	V	3.0	36.4	1.0	-50.3	-13.0	-37.3	
5.198	-13.9	V	3.0	35.5	1.0	-48.4	-13.0	-35.4	
High Channel (1753.75MHz)									
3.508	-15.8	H	3.0	36.4	1.0	-51.2	-13.0	-38.2	
5.261	-14.3	H	3.0	35.5	1.0	-48.8	-13.0	-35.8	
3.508	-16.0	V	3.0	36.4	1.0	-51.4	-13.0	-38.4	
5.261	-13.6	V	3.0	35.5	1.0	-48.1	-13.0	-35.1	
Rev. 03.03.14									

3m Radiated Emissions Chamber Above 1GHz Substitution Measurement									
Project #:		14U17676							
Date:		6/24/2014							
Test Engineer:		Ali Poushnejad							
Configuration:		EUT Only							
Mode:		CDMA EVDO_A BC15							
Test Equipment:									
Substitution: Horn T59 Substitution, and 8ft SMA Cable									
Chamber			Pre-amplifier			Filter		Limit	
3m Chamber F			3m Chamber F					Part 27	
Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes
Low Channel (1711.25MHz)									
3.423	-12.8	H	3.0	36.4	1.0	48.2	-13.0	-35.2	
5.134	-15.3	H	3.0	35.5	1.0	49.8	-13.0	-36.8	
6.845	-13.4	H	3.0	35.9	1.0	48.2	-13.0	-35.2	
3.423	-15.1	V	3.0	36.4	1.0	50.5	-13.0	-37.5	
5.134	-15.9	V	3.0	35.5	1.0	50.4	-13.0	-37.4	
6.845	-14.4	V	3.0	35.9	1.0	49.3	-13.0	-36.3	
Mid Channel (1732.5MHz)									
3.465	-16.9	H	3.0	36.4	1.0	52.3	-13.0	-39.3	
5.198	-16.3	H	3.0	35.5	1.0	50.8	-13.0	-37.8	
6.930	-13.9	H	3.0	35.9	1.0	48.8	-13.0	-35.8	
3.465	-16.7	V	3.0	36.4	1.0	52.1	-13.0	-39.1	
5.198	-15.6	V	3.0	35.5	1.0	50.0	-13.0	-37.0	
6.930	-14.4	V	3.0	35.9	1.0	49.3	-13.0	-36.3	
High Channel (1753.75MHz)									
3.508	-17.8	H	3.0	36.4	1.0	53.1	-13.0	-40.1	
5.261	-16.0	H	3.0	35.5	1.0	50.5	-13.0	-37.5	
7.015	-13.2	H	3.0	35.9	1.0	48.1	-13.0	-35.1	
3.508	-17.2	V	3.0	36.4	1.0	52.5	-13.0	-39.5	
5.261	-15.6	V	3.0	35.5	1.0	50.1	-13.0	-37.1	
7.015	-14.5	V	3.0	35.9	1.0	49.4	-13.0	-36.4	
Rev. 03.03.14									

3m Radiated Emissions Chamber Above 1GHz Substitution Measurement									
Project #: 14U17676 Date: 06/24/14 Test Engineer: T Wang Configuration: EUT Only Mode: CDMA2000, 1xRTT BC10									
Test Equipment: Substitution: Horn T59 Substitution, and 8ft SMA Cable									
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber F		3m Chamber F				Part 90			
Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes
Low Channel (817.25MHz)									
1.635	-18.9	H	3.0	34.9	1.0	-52.8	-13.0	-39.8	
2.452	-18.3	H	3.0	35.5	1.0	-52.8	-13.0	-39.8	
1.636	-15.8	V	3.0	34.9	1.0	-49.7	-13.0	-36.7	
2.452	-17.5	V	3.0	35.5	1.0	-51.9	-13.0	-38.9	
Mid Channel (820.0MHz)									
1.640	-15.2	H	3.0	34.9	1.0	-49.1	-13.0	-36.1	
2.460	-17.4	H	3.0	35.4	1.0	-51.8	-13.0	-38.8	
1.640	-16.6	V	3.0	34.9	1.0	-50.5	-13.0	-37.5	
2.460	-15.3	V	3.0	35.4	1.0	-49.8	-13.0	-36.8	
High Channel (822.75MHz)									
1.646	-16.3	H	3.0	34.9	1.0	-50.2	-13.0	-37.2	
2.468	-18.2	H	3.0	35.4	1.0	-52.6	-13.0	-39.6	
1.646	-13.7	V	3.0	34.9	1.0	-47.6	-13.0	-34.6	
2.468	-16.7	V	3.0	35.4	1.0	-51.1	-13.0	-38.1	
Rev. 03.03.14									

3m Radiated Emissions Chamber Above 1GHz Substitution Measurement									
Project #: 14U17676 Date: 06/24/14 Test Engineer: Ali Poushnejad Configuration: EUT Only Mode: CDMA2000, EV DO_A BC10									
Test Equipment: Substitution: Horn T59 Substitution, and 8ft SMA Cable									
Chamber		Pre-amplifier		Filter		Limit			
3m Chamber F		3m Chamber F				Part 90			
Frequency (GHz)	SG reading (dBm)	Ant. Pol. (H/V)	Distance	Preamp	Attenuator	EIRP	Limit	Delta	Notes
Low Channel (817.25MHz)									
1.635	-22.5	H	3.0	34.9	1.0	-56.4	-13.0	-43.4	
2.452	-16.4	H	3.0	35.5	1.0	-50.9	-13.0	-37.9	
1.635	-20.3	V	3.0	34.9	1.0	-54.3	-13.0	-41.3	
2.452	-15.8	V	3.0	35.5	1.0	-50.3	-13.0	-37.3	
Mid Channel (820.0MHz)									
1.640	-23.1	H	3.0	34.9	1.0	-57.1	-13.0	-44.1	
2.460	-19.5	H	3.0	35.4	1.0	-53.9	-13.0	-40.9	
1.640	-22.8	V	3.0	34.9	1.0	-56.7	-13.0	-43.7	
2.460	-17.7	V	3.0	35.4	1.0	-52.1	-13.0	-39.1	
High Channel (822.75MHz)									
1.646	-22.5	H	3.0	34.9	1.0	-56.4	-13.0	-43.4	
2.468	-18.3	H	3.0	35.4	1.0	-52.7	-13.0	-39.7	
1.646	-22.6	V	3.0	34.9	1.0	-56.5	-13.0	-43.5	
2.468	-14.1	V	3.0	35.4	1.0	-48.5	-13.0	-35.5	
Rev. 03.03.14									