



CERTIFICATION TEST REPORT

Report Number. : 12204512-E2V3

Applicant : APPLE INC.
1 APPLE PARK WAY
CUPERTINO, CA. 95014, U.S.A.

Model : A2101

FCC ID : BCG-E3234A

IC : 579C-E3234A

EUT Description : SMARTPHONE

Test Standard(s) : FCC 47 CFR PART 15 SUBPART C
ISED RSS-247 ISSUE 2
ISED RSS-GEN ISSUE 5

Date Of Issue:
August 10, 2018

Prepared by:
UL Verification Services Inc.
47173 Benicia Street
Fremont, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888

REPORT REVISION HISTORY

Rev.	Issue Date	Revisions	Revised By
V1	8/7/2018	Initial Issue	Francisco Guarnero
V2	8/9/2018	Address TCB's Questions	Chin Pang
V3	8/10/2018	Address TCB's Questions	Tri Pham

TABLE OF CONTENTS

REPORT REVISION HISTORY	2
TABLE OF CONTENTS	3
1. ATTESTATION OF TEST RESULTS	5
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION	6
4. CALIBRATION AND UNCERTAINTY	7
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	7
4.2. <i>SAMPLE CALCULATION</i>	7
4.3. <i>MEASUREMENT UNCERTAINTY</i>	7
5. EQUIPMENT UNDER TEST	8
5.1. <i>EUT DESCRIPTION</i>	8
5.2. <i>MAXIMUM OUTPUT POWER</i>	8
5.3. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	8
5.4. <i>SOFTWARE AND FIRMWARE</i>	8
5.5. <i>WORST-CASE CONFIGURATION AND MODE</i>	9
5.6. <i>DESCRIPTION OF TEST SETUP</i>	10
6. MEASUREMENT METHOD	15
7. TEST AND MEASUREMENT EQUIPMENT	16
8. ANTENNA PORT TEST RESULTS	17
8.1. <i>ON TIME AND DUTY CYCLE</i>	17
8.2. <i>99% BANDWIDTH</i>	19
8.2.1. <i>HIGH POWER BLE (1Mbps)</i>	20
8.2.2. <i>HIGH POWER BLE (2Mbps)</i>	22
8.2.3. <i>LOW POWER BLE (1Mbps)</i>	24
8.2.4. <i>LOW POWER BLE (2Mbps)</i>	26
8.3. <i>6 dB BANDWIDTH</i>	28
8.3.1. <i>HIGH POWER BLE (1Mbps)</i>	29
8.3.2. <i>HIGH POWER BLE (2Mbps)</i>	31
8.3.3. <i>LOW POWER BLE (1Mbps)</i>	33
8.3.4. <i>LOW POWER BLE (2Mbps)</i>	35
8.4. <i>OUTPUT POWER</i>	37
8.4.1. <i>HIGH POWER BLE (1Mbps)</i>	38
8.4.2. <i>HIGH POWER BLE (2Mbps)</i>	39
8.4.3. <i>LOW POWER BLE (1Mbps)</i>	40
8.4.4. <i>LOW POWER BLE (2Mbps)</i>	41

8.5. AVERAGE POWER.....	42
8.5.1. HIGH POWER BLE (1Mbps).....	43
8.5.2. HIGH POWER BLE (2Mbps).....	44
8.5.3. LOW POWER BLE (1Mbps)	45
8.5.4. LOW POWER BLE (2Mbps)	46
8.6. POWER SPECTRAL DENSITY.....	47
8.6.1. HIGH POWER BLE (1Mbps).....	48
8.6.2. HIGH POWER BLE (2Mbps).....	50
8.6.3. LOW POWER BLE (1Mbps)	52
8.6.4. LOW POWER BLE (2Mbps)	54
8.7. CONDUCTED SPURIOUS EMISSIONS.....	56
8.7.1. HIGH POWER BLE (1Mbps).....	57
8.7.2. HIGH POWER BLE (2Mbps).....	59
8.7.3. LOW POWER BLE (1Mbps)	61
8.7.4. LOW POWER BLE (2Mbps)	63
9. RADIATED TEST RESULTS.....	65
9.1. LIMITS AND PROCEDURE.....	65
9.2. TRANSMITTER ABOVE 1 GHz	66
9.2.1. HIGH POWER BLE (1Mbps).....	66
9.2.2. HIGH POWER BLE (2Mbps).....	86
9.2.3. LOW POWER BLE (1Mbps)	106
9.2.4. LOW POWER BLE (2Mbps)	126
9.3. Worst Case below 1 GHz.....	146
9.4. Worst Case 18-26 GHz.....	148
10. AC POWER LINE CONDUCTED EMISSIONS	149
10.1.1. AC Power Line Host.....	150
10.1.2. AC Power Line Norm.....	152
11. SETUP PHOTOS	154

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: APPLE, INC.
1 APPLE PARK WAY
CUPERTINO, CA 95014, U.S.A.

EUT DESCRIPTION: SMARTPHONE

MODEL: A2101

SERIAL NUMBER: C39WK00GK3VQ

DATE TESTED: MARCH 26, 2018 – AUGUST 09, 2018

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Complies
ISED RSS-247 Issue 2	Complies
ISED RSS-GEN Issue 5	Complies

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of the U.S. government.

Approved & Released For
UL Verification Services Inc. By:



Chin Pang
CONSUMER TECHNOLOGY DIVISION
Senior Engineer
UL Verification Services Inc.

Prepared By:



Jingang Li
CONSUMER TECHNOLOGY DIVISION
TEST ENGINEER
UL Verification Services Inc

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with FCC CFR 47 Part 2, FCC CFR 47 Part 15, KDB 558074 D01 v04, ANSI C63.10-2013, RSS-GEN Issue 5, and RSS-247 Issue 2.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 and 47266 Benicia Street, Fremont, California, USA. Line conducted emissions are measured only at the 47173 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

47173 Benicia Street	47266 Benicia Street
<input type="checkbox"/> Chamber A (ISED:2324B-1)	<input checked="" type="checkbox"/> Chamber D (ISED:22541-1)
<input type="checkbox"/> Chamber B (ISED:2324B-2)	<input checked="" type="checkbox"/> Chamber E (ISED:22541-2)
<input type="checkbox"/> Chamber C (ISED:2324B-3)	<input checked="" type="checkbox"/> Chamber F (ISED:22541-3)
	<input type="checkbox"/> Chamber G (ISED:22541-4)
	<input checked="" type="checkbox"/> Chamber H (ISED:22541-5)

The above test sites and facilities are covered under FCC Test Firm Registration # 208313. Chambers A through C are covered under ISED company address code 2324B with site numbers 2324B -1 through 2324B-3, respectively. Chambers D through H are covered under ISED company address code 22541 with site numbers 22541 -1 through 22541-5, respectively.

The above test sites and facilities are covered under FCC Test Firm Registration # 208313. UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at [NVLAP Lab Search](#).

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Worst Case Conducted Disturbance, 9KHz to 0.15 MHz	3.84 dB
Worst Case Conducted Disturbance, 0.15 to 30 MHz	3.65 dB
Worst Case Radiated Disturbance, 9KHz to 30 MHz	3.15 dB
Worst Case Radiated Disturbance, 30 to 1000 MHz	5.36 dB
Worst Case Radiated Disturbance, 1000 to 18000 MHz	4.32 dB
Worst Case Radiated Disturbance, 18000 to 26000 MHz	4.45 dB
Worst Case Radiated Disturbance, 26000 to 40000 MHz	5.24 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. EUT DESCRIPTION

The Apple iPhone, is a smartphone with multimedia functions (music, application support, and video), cellular GSM, GPRS, EGPRS, UMTS, LTE, TD-SCDMA, CDMA, IEEE 802.11a/b/g/n/ac, Bluetooth, GPS and NFC. All models support at least one UICC based SIM. The second SIM is either UICC based, electronic SIM (e-SIM), or second SIM is not present. The device has a built-in inductive charging receiver which is not user accessible. The rechargeable battery is not user accessible.

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak conducted output power as follows:

Antenna	Configuration	Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
Ant 4	Pstandalone	2402 - 2480	BLE 1M	18.35	68.39
	Plow			10.35	10.83
	Pstandalone		BLE 2M	18.30	67.62
	Plow			10.31	10.75
Ant 3	Pstandalone	2402 - 2480	BLE 1M	20.28	106.61
	Plow			10.32	10.76
	Pstandalone		BLE 2M	20.22	105.08
	Plow			10.31	10.74

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

Frequency Range (GHz)	Ant. 4 (dBi)	Ant. 3 (dBi)
2.4	-2.3	-4.8

5.4. SOFTWARE AND FIRMWARE

The EUT firmware installed during testing was BT FW: 16.1.98.

5.5.WORST-CASE CONFIGURATION AND MODE

The EUT was investigated in three orthogonal orientations X, Y and Z on Ant 4 (Antenna 4) and Ant 3 (Antenna 3). It was determined that Y (Landscape) orientation was the worst-case orientation for Ant 4 and X (Flatbed) for Ant 3.

Pstandalone is high power and Plow is low power.

Radiated band edge, harmonic, and spurious emissions from 1GHz to 18GHz were performed with the EUT was set to transmit at highest power on Low/Middle/High channels.

Radiated emissions below 30MHz, below 1GHz, 18-26GHz and power line conducted emissions were performed with the EUT transmits at the channel with the highest output power as worst-case scenario.

Below 1GHz tests were performed with EUT connected to AC power adapter as the worst case; and for above 1GHz, the worst-case configuration reported was tested with EUT only. For AC line conducted emission, test was investigated with AC power adapter and with laptop. There were no emissions found below 30MHz within 20dB of the limit.

For simultaneous transmission of multiple channels in the 2.4GHz BLE and 5GHz bands. No noticeable emission was found.

There are two vendors of the WiFi/Bluetooth radio modules: variant 1 and variant 2. The WiFi/Bluetooth radio modules have the same mechanical outline (e.g., the same package dimension and pin-out layout), use the same on-board antenna matching circuit, have an identical antenna structure, and are built and tested to conform to the same specifications and to operate within the same tolerances.

Baseline testing was performed on the two variants to determine the worst case on all conducted power and radiated emissions.

5.6.DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
laptop	Apple	Macbook Pro	C02P41RZG086	FCC DoC
Laptop AC/DC adapter	Liteon Technology	PA-1450-BA1	B123	NA
EUT AC Adapter	Apple	A1385	D292365CDYADHLHC3	NA

I/O CABLES (CONDUCTED TEST)

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	Antenna	1	SMA	Un-Shielded	0.2	To spectrum Analyzer
2	USB	1	USB	Shielded	1	N/A
3	AC	1	AC	Un-shielded	2	N/A

I/O CABLES (RADIATED ABOVE 1 GHZ)

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
None Used						


I/O CABLES (BELOW 1GHz AND AC POWER LINE TEST WITH ADAPTER AND LAPTOP)

I/O Cable List						
Cable No	Port	# of identical	Connector Type	Cable Type	Cable Length (m)	Remarks
1	AC	1	AC	Un-shielded	2	N/A
2	USB	1	USB	Un-shielded	1	N/A

TEST SETUP- CONDUCTED PORT

The EUT was tested connected to a host Laptop via USB cable adapter and spectrum analyzer to antenna port. Test software exercised the EUT.


SETUP DIAGRAM



TEST SETUP- RADIATED-ABOVE 1 GHZ

The EUT was powered by Battery. Test software exercised the EUT.


SETUP DIAGRAM




TEST SETUP- BELOW 1GHZ & AC LINE CONDUCTED TESTS

The EUT was powered by AC cord. Test software exercised the EUT.

SETUP DIAGRAM



TEST SETUP- AC LINE CONDUCTED: LAPTOP CONFIGURATION



6. MEASUREMENT METHOD

On Time and Duty Cycle: KDB 558074 D01 v04, Section 6.

6 dB BW: KDB 558074 D01 v04, Section 8.1.

Output Power: KDB 558074 D01 v04, Section 9.1.3.

Power Spectral Density: KDB 558074 D01 v04, Section 10.2.

Out-of-band emissions in non-restricted bands: KDB 558074 D01 v04, Section 11.0.

Out-of-band emissions in restricted bands: KDB 558074 D01 v04, Section 12.1.

Band-edge: KDB 558074 D01 v04, Section 12.1.

AC Power Line Conducted Emissions: ANSI C63.10-2013, Section 6.2.

7. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Description	Manufacturer	Model	ID Num	Cal Due
*Antenna, Horn 1-18GHz	ETS Lindgren	3117	T136	06/26/2018
*Antenna, Broadband Hybrid, 30MHz to 2000MHz	Sunol Sciences	JB3	T477	07/07/2018
*Amplifier, 10KHz to 1GHz, 32dB	Sonoma	310N	T286	06/02/2018
Spectrum Analyzer, PXA 3Hz to 44GHz	Keysight	N9030A	T340	12/15/2018
Amplifier, 1 to 18GHz	Miteq	AFS42-00101800-25-S-42	T740	12/30/2018
Antenna, Horn 1-18GHz	ETS Lindgren	3117	T346	02/08/2019
Amplifier, 1 to 18GHz	Miteq	AFS42-00101800-25-S-42	T741	12/30/2018
*Amplifier, 1 to 18GHz, 35dB	Amplical	AMP1G18-35	T1569	05/31/2018
*Amplifier, 10KHz to 1GHz, 32dB	Sonoma	310N	T835	06/24/2018
Antenna, Horn 1-18GHz	ETS Lindgren	3117	T344	02/08/2019
Spectrum Analyzer, PSA, 3Hz to 44GHz	Agilent (Keysight) Technologies	E4446A	T177	04/12/2019
*Antenna Horn 18 to 26.5GHz	ARA	MWH-1826/B	T449	06/12/2018
Pre-Amp 18-26GHz	Agilent Technology	8449B	T404	07/23/2018
Spectrum Analyzer, PXA, 3Hz to 44GHz	Agilent (Keysight) Technologies	N9030A	T1454	01/08/2019
*Spectrum Analyzer, PXA, 3Hz to 44GHz	Agilent (Keysight) Technologies	N9030A	T459	06/22/2018
Antenna, Active Loop 9KHz to 30MHz	EMCO	6502	T35	12/15/2018
Power Meter, P-series single channel	Keysight	N1912A	T1272	05/1/2019
Power Sensor	Keysight	N1921A	T1226	8/30/2018
AC Line Conducted				
EMI Test Receiver 9Khz-7GHz	Rohde & Schwarz	ESCI7	T1436	01/25/2019
Power Cable, Line Conducted Emissions	UL	PG1	T861	08/31/2018
*LISN for Conducted Emissions CISPR-16	Fischer	50/250-25-2-01	T1310	06/15/2018
UL AUTOMATION SOFTWARE				
Radiated Software	UL	UL EMC	Ver 9.5, April 26, 2016	
Conducted Software	UL	UL EMC	Ver 5.4, October 13, 2016	
AC Line Conducted Software	UL	UL EMC	Ver 9.5, May 26, 2015	

Note: *Testing is completed before equipment expiration date.

8. ANTENNA PORT TEST RESULTS

8.1.ON TIME AND DUTY CYCLE

LIMITS


None; for reporting purposes only.

PROCEDURE

ON TIME AND DUTY CYCLE RESULTS

Mode	ON Time B (msec)	Period (msec)	Duty Cycle x (linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/B Minimum VBW (kHz)
2.4GHz Band						
BLE	34.95	34.95	1.00	1.00	0.00	0.01

DUTY CYCLE PLOTS



8.2.99% BANDWIDTH

LIMITS

None; for reporting purposes only.

RESULTS

8.2.1. HIGH POWER BLE (1Mbps)


Antenna 4

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2402	1.0605
Middle	2440	1.0509
High	2480	1.0537



Antenna 3


Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2402	1.0613
Middle	2440	1.0583
High	2480	1.0548



8.2.2. HIGH POWER BLE (2Mbps)

Antenna 4

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2402	1.9908
Middle	2440	1.9967
High	2480	1.9741



Antenna 3


Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2402	1.9332
Middle	2440	1.9573
High	2480	1.9797



8.2.3. LOW POWER BLE (1Mbps)


Antenna 4

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2402	1.0484
Middle	2440	1.0554
High	2480	1.0502



Antenna 3


Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2402	1.0517
Middle	2440	1.0595
High	2480	1.0607



8.2.4. LOW POWER BLE (2Mbps)


Antenna 4

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2402	1.9436
Middle	2440	1.9736
High	2480	1.9463



Antenna 3

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2402	1.9466
Middle	2440	1.9589
High	2480	1.9654



8.3.6 dB BANDWIDTH

LIMITS

FCC §15.407 (e)

RSS-247 5.2 (a)


The minimum 6 dB bandwidth shall be at least 500 kHz.

RESULTS

8.3.1. HIGH POWER BLE (1Mbps)


Antenna 4

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2402	0.726	0.5
Middle	2440	0.681	0.5
High	2480	0.684	0.5



Antenna 3


Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2402	0.687	0.5
Middle	2440	0.702	0.5
High	2480	0.705	0.5



8.3.2. HIGH POWER BLE (2Mbps)


Antenna 4

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2402	1.125	0.5
Middle	2440	1.170	0.5
High	2480	1.185	0.5



Antenna 3


Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2402	1.176	0.5
Middle	2440	1.134	0.5
High	2480	1.158	0.5



8.3.3. LOW POWER BLE (1Mbps)


Antenna 4

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2402	0.717	0.5
Middle	2440	0.642	0.5
High	2480	0.702	0.5



Antenna 3


Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2402	0.663	0.5
Middle	2440	0.708	0.5
High	2480	0.681	0.5



8.3.4. LOW POWER BLE (2Mbps)


Antenna 4

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2402	1.155	0.5
Middle	2440	1.158	0.5
High	2480	1.248	0.5



Antenna 3

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2402	1.134	0.5
Middle	2440	1.137	0.5
High	2480	1.191	0.5



8.4.OUTPUT POWER

LIMITS

FCC §15.247 (b) (3)

RSS-247 5.4 (d)

The maximum antenna gain is less than or equal to 6 dBi, therefore the limit is 30 dBm.

TEST PROCEDURE

The transmitter output is connected to a power meter.

The cable assembly insertion loss of 10.5 dB (including 10 dB pad and 0.5 dB cable) was entered as an offset in the power meter to allow for a gated peak reading of power.

RESULTS

8.4.1. HIGH POWER BLE (1Mbps)

Antenna 4

Tested By:	30554
Date:	7/17/2018

Channel	Frequency (MHz)	Peak Power Reading (dBm)	Limit (dBm)	Margin (dB)
Low	2402	18.322	30	-11.678
Middle	2440	18.350	30	-11.650
High	2480	18.310	30	-11.690

Antenna 3

Tested By:	30554
Date:	7/17/2018

Channel	Frequency (MHz)	Peak Power Reading (dBm)	Limit (dBm)	Margin (dB)
Low	2402	20.239	30	-9.761
Middle	2440	20.278	30	-9.722
High	2480	20.186	30	-9.814

8.4.2. HIGH POWER BLE (2Mbps)

Antenna 4

Tested By:	30554
Date:	7/17/2018

Channel	Frequency (MHz)	Peak Power Reading (dBm)	Limit (dBm)	Margin (dB)
Low	2402	18.199	30	-11.801
Middle	2440	18.221	30	-11.779
High	2480	18.301	30	-11.699

Antenna 3

Tested By:	30554
Date:	7/17/2018

Channel	Frequency (MHz)	Peak Power Reading (dBm)	Limit (dBm)	Margin (dB)
Low	2402	20.197	30	-9.803
Middle	2440	20.215	30	-9.785
High	2480	20.198	30	-9.802

8.4.3. LOW POWER BLE (1Mbps)

Antenna 4

Tested By:	30554
Date:	7/17/2018

Channel	Frequency (MHz)	Peak Power Reading (dBm)	Limit (dBm)	Margin (dB)
Low	2402	10.213	30	-19.787
Middle	2440	10.345	30	-19.655
High	2480	10.235	30	-19.765

Antenna 3

Tested By:	30554
Date:	7/17/2018

Channel	Frequency (MHz)	Peak Power Reading (dBm)	Limit (dBm)	Margin (dB)
Low	2402	10.232	30	-19.768
Middle	2440	10.320	30	-19.680
High	2480	10.285	30	-19.715

8.4.4. LOW POWER BLE (2Mbps)

Antenna 4

Tested By:	30554
Date:	7/17/2018

Channel	Frequency (MHz)	Peak Power Reading (dBm)	Limit (dBm)	Margin (dB)
Low	2402	10.266	30	-19.734
Middle	2440	10.313	30	-19.687
High	2480	10.218	30	-19.782

Antenna 3

Tested By:	30554
Date:	7/17/2018

Channel	Frequency (MHz)	Peak Power Reading (dBm)	Limit (dBm)	Margin (dB)
Low	2402	10.229	30	-19.771
Middle	2440	10.312	30	-19.688
High	2480	10.267	30	-19.733

8.5.AVERAGE POWER

LIMITS

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to a power meter.

The cable assembly insertion loss of 10.5 dB (including 10 dB pad and 0.5 dB cable) was entered as an offset in the power meter to allow for a gated average reading of power.

RESULTS

8.5.1. HIGH POWER BLE (1Mbps)

Antenna 4

Tested By:	30554
Date:	7/17/2018

Channel	Frequency (MHz)	AV power (dBm)
Low	2402	17.9
Middle	2440	17.99
High	2480	17.86

Antenna 3

Tested By:	30554
Date:	7/17/2018

Channel	Frequency (MHz)	AV power (dBm)
Low	2402	19.89
Middle	2440	19.95
High	2480	19.88

8.5.2. HIGH POWER BLE (2Mbps)

Antenna 4

Tested By:	30554
Date:	7/17/2018

Channel	Frequency (MHz)	AV power (dBm)
Low	2402	17.86
Middle	2440	17.94
High	2480	17.75

Antenna 3

Tested By:	30554
Date:	7/17/2018

Channel	Frequency (MHz)	AV power (dBm)
Low	2402	19.8
Middle	2440	19.85
High	2480	19.77

8.5.3. LOW POWER BLE (1Mbps)

Antenna 4

Tested By:	30554
Date:	7/17/2018

Channel	Frequency (MHz)	AV power (dBm)
Low	2402	9.77
Middle	2440	9.9
High	2480	9.72

Antenna 3

Tested By:	30554
Date:	7/17/2018

Channel	Frequency (MHz)	AV power (dBm)
Low	2402	9.81
Middle	2440	9.88
High	2480	9.78

8.5.4. LOW POWER BLE (2Mbps)

Antenna 4

Tested By:	30554
Date:	7/17/2018

Channel	Frequency (MHz)	AV power (dBm)
Low	2402	9.69
Middle	2440	9.8
High	2480	9.66

Antenna 3

Tested By:	30554
Date:	7/17/2018

Channel	Frequency (MHz)	AV power (dBm)
Low	2402	9.74
Middle	2440	9.81
High	2480	9.71

8.6. POWER SPECTRAL DENSITY

LIMITS

FCC §15.247 (e)

RSS-247 (5.2) (b)


The power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

RESULTS

8.6.1. HIGH POWER BLE (1Mbps)


Antenna 4

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Margin (dB)
Low	2402	1.84	8	-6.16
Middle	2440	2.44	8	-5.56
High	2480	1.85	8	-6.15



Antenna 3


Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Margin (dB)
Low	2402	2.86	8	-5.14
Middle	2440	3.18	8	-4.82
High	2480	0.86	8	-7.14



8.6.2. HIGH POWER BLE (2Mbps)


Antenna 4

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Margin (dB)
Low	2402	1.33	8	-6.671
Middle	2440	2.77	8	-5.234
High	2480	1.68	8	-6.318



Antenna 3


Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Margin (dB)
Low	2402	3.00	8	-4.997
Middle	2440	3.52	8	-4.485
High	2480	1.11	8	-6.894



8.6.3. LOW POWER BLE (1Mbps)


Antenna 4

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Margin (dB)
Low	2402	-7.05	8	-15.050
Middle	2440	-5.63	8	-13.629
High	2480	-6.78	8	-14.783



Antenna 3


Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Margin (dB)
Low	2402	-6.00	8	-13.999
Middle	2440	-4.88	8	-12.883
High	2480	-8.87	8	-16.868



8.6.4. LOW POWER BLE (2Mbps)

Antenna 4

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Margin (dB)
Low	2402	-7.68	8	-15.675
Middle	2440	-6.19	8	-14.189
High	2480	-7.07	8	-15.072



Antenna 3

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Margin (dB)
Low	2402	-6.12	8	-14.115
Middle	2440	-6.34	8	-14.336
High	2480	-9.36	8	-17.356

