



CERTIFICATION TEST REPORT

Report Number. : 12258201-E4V2

Applicant : APPLE, INC.
1 APPLE PARK WAY
CUPERTINO, CA 95014, U.S.A.

Model : A2106

FCC ID : BCG-E3238A

EUT Description : SMARTPHONE

Test Standard(s) : FCC 47 CFR PART 15 SUBPART E

Date Of Issue:
August 27, 2018

Prepared by:
UL Verification Services Inc.
47173 Benicia Street
Fremont, CA 94538 U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888



NVLAP Lab code: 200065-0

REPORT REVISION HISTORY

Rev.	Issue Date	Revisions	Revised By
V1	8/17/2018	Initial Issue	Chin Pang
V2	8/27/2018	Addressed TCB Questions	Tony Li

TABLE OF CONTENTS

REPORT REVISION HISTORY	2
TABLE OF CONTENTS	3
1. ATTESTATION OF TEST RESULTS	6
2. TEST METHODOLOGY	7
3. FACILITIES AND ACCREDITATION	7
4. CALIBRATION AND UNCERTAINTY	8
4.1. MEASURING INSTRUMENT CALIBRATION	8
4.2. SAMPLE CALCULATION	8
4.3. MEASUREMENT UNCERTAINTY.....	8
5. EQUIPMENT UNDER TEST	9
5.1. EUT DESCRIPTION	9
5.2. MAXIMUM OUTPUT POWER.....	9
5.3. DESCRIPTION OF AVAILABLE ANTENNAS	12
5.4. SOFTWARE AND FIRMWARE.....	12
5.5. WORST-CASE CONFIGURATION AND MODE	13
5.6. DESCRIPTION OF TEST SETUP.....	14
6. MEASUREMENT METHOD.....	19
7. TEST AND MEASUREMENT EQUIPMENT	20
8. ANTENNA PORT TEST RESULTS	21
8.1. ON TIME AND DUTY CYCLE.....	21
8.2. 26 dB BANDWIDTH.....	23
8.2.1. 802.11n HT20 MODE IN THE 5.2 GHz BAND	24
8.2.2. 802.11n HT40 MODE IN THE 5.2 GHz BAND	28
8.2.3. 802.11ac VHT80 MODE IN THE 5.2 GHz BAND	31
8.2.4. 802.11n HT20 MODE IN THE 5.3 GHz BAND	34
8.2.5. 802.11n HT40 MODE IN THE 5.3 GHz BAND	38
8.2.6. 802.11ac VHT80 MODE IN THE 5.3 GHz BAND	41
8.2.7. 802.11n HT20 MODE IN THE 5.6 GHz BAND	44
8.2.8. 802.11n HT40 MODE IN THE 5.6 GHz BAND	48
8.2.9. 802.11ac VHT80 MODE IN THE 5.6 GHz BAND	52
8.2.10. 802.11n HT20 MODE IN THE 5.8 GHz BAND	56
8.2.11. 802.11n HT40 MODE IN THE 5.8 GHz BAND	60
8.2.12. 802.11ac VHT80 MODE IN THE 5.8 GHz BAND	63
8.3. 99% BANDWIDTH.....	66
8.3.1. 802.11n HT20 MODE IN THE 5.2 GHz BAND	67

8.3.2.	802.11n HT40 MODE IN THE 5.2 GHz BAND	71
8.3.3.	802.11ac VHT80 MODE IN THE 5.2 GHz BAND	74
8.3.4.	802.11n HT20 MODE IN THE 5.3 GHz BAND	77
8.3.5.	802.11n HT40 MODE IN THE 5.3 GHz BAND	81
8.3.6.	802.11ac VHT80 MODE IN THE 5.3 GHz BAND	84
8.3.7.	802.11n HT20 MODE IN THE 5.6 GHz BAND	87
8.3.8.	802.11n HT40 MODE IN THE 5.6 GHz BAND	91
8.3.9.	802.11ac VHT80 MODE IN THE 5.6 GHz BAND	95
8.3.10.	802.11n HT20 MODE IN THE 5.8 GHz BAND	99
8.3.11.	802.11n HT40 MODE IN THE 5.8 GHz BAND	103
8.3.12.	802.11ac VHT80 MODE IN THE 5.8 GHz BAND	106
8.4.	<i>6 dB BANDWIDTH.....</i>	<i>109</i>
8.4.1.	802.11n HT20 MODE IN THE 5.8 GHz BAND	110
8.4.2.	802.11n HT40 MODE IN THE 5.8 GHz BAND	114
8.4.3.	802.11ac VHT80 MODE IN THE 5.8 GHz BAND	118
8.5.	<i>OUTPUT POWER AND PSD.....</i>	<i>121</i>
8.5.1.	802.11n HT20 MODE IN THE 5.2 GHz BAND	123
8.5.2.	802.11n HT40 MODE IN THE 5.2 GHz BAND	129
8.5.3.	802.11ac VHT80 MODE IN THE 5.2 GHz BAND	133
8.5.4.	802.11n HT20 MODE IN THE 5.3 GHz BAND	136
8.5.5.	802.11n HT40 MODE IN THE 5.3 GHz BAND	142
8.5.6.	802.11ac VHT80 MODE IN THE 5.3 GHz BAND	146
8.5.7.	802.11n HT20 MODE IN THE 5.6 GHz BAND	149
8.5.8.	802.11n HT40 MODE IN THE 5.6 GHz BAND	156
8.5.9.	802.11ac VHT80 MODE IN THE 5.6 GHz BAND	163
8.5.10.	802.11n HT20 MODE IN THE 5.8 GHz BAND	169
8.5.11.	802.11n HT40 MODE IN THE 5.8 GHz BAND	176
8.5.12.	802.11ac VHT80 MODE IN THE 5.8 GHz BAND	183
9.	RADIATED TEST RESULTS.....	189
9.1.	<i>TRANSMITTER ABOVE 1 GHz.....</i>	<i>190</i>
9.1.1.	TX ABOVE 1 GHz 802.11n HT20 MODE IN THE 5.2 GHz BAND.....	190
9.1.2.	TX ABOVE 1 GHz 802.11n HT40 MODE IN THE 5.2 GHz BAND.....	202
9.1.3.	TX ABOVE 1 GHz 802.11ac VHT80 MODE IN THE 5.2 GHz BAND	212
9.1.4.	TX ABOVE 1 GHz 802.11n HT20 MODE IN THE 5.3 GHz BAND.....	220
9.1.5.	TX ABOVE 1 GHz 802.11n HT40 MODE IN THE 5.3 GHz BAND.....	232
9.1.6.	TX ABOVE 1 GHz 802.11ac VHT80 MODE IN THE 5.3 GHz BAND	242
9.1.7.	TX ABOVE 1 GHz 802.11n HT20 MODE IN THE 5.6 GHz BAND.....	250
9.1.8.	TX ABOVE 1 GHz 802.11n HT40 MODE IN THE 5.6 GHz BAND.....	270
9.1.9.	TX ABOVE 1 GHz 802.11ac VHT80 MODE IN THE 5.6 GHz BAND	290
9.1.10.	TX ABOVE 1 GHz 802.11n HT20 MODE IN THE 5.8 GHz BAND.....	302
9.1.11.	TX ABOVE 1 GHz 802.11n HT40 MODE IN THE 5.8 GHz BAND.....	320
9.1.12.	TX ABOVE 1 GHz 802.11ac VHT80 MODE IN THE 5.8 GHz BAND	336
9.2.	<i>Worst Case Below 1 GHz</i>	<i>350</i>
9.3.	<i>Worst Case 18-26 GHz.....</i>	<i>352</i>
9.4.	<i>Worst Case 26-40 GHz.....</i>	<i>354</i>
10.	AC POWER LINE CONDUCTED EMISSIONS.....	356
10.1.	<i>EUT POWERED BY AC/DC ADAPTER VIA USB CABLE.....</i>	<i>357</i>

10.2.	EUT POWERED BY HOST PC VIA USB CABLE.....	359
11.	SETUP PHOTOS.....	361

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: APPLE, INC.
1 APPLE PARK WAY
CUPERTINO, CA 95014, U.S.A

EUT DESCRIPTION: SMARTPHONE

MODEL: A2106

SERIAL NUMBER: C7CWW04EKJRC

DATE TESTED: May 26, 2018 to July 27, 2018

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart E	COMPLIES

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of the U.S. government.

Approved & Released For
UL Verification Services Inc. By:

Prepared By:



Chin Pang
CONSUMER TECHNOLOGY DIVISION
Senior Engineer
UL Verification Services Inc.

Tri Pham
CONSUMER TECHNOLOGY DIVISION
TEST ENGINEER
UL Verification Services Inc.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with FCC CFR 47 Part 2, FCC CFR 47 Part 15, FCC 14-30, FCC KDB 662911 D01 v02r01, FCC KDB 905462 D02 v02/D03 v01r02/D06 v02, FCC KDB 789033 D02 v02r01, FCC KDB 644545 D03 v01, ANSI C63.10-2013, FCC 06-96.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 and 47266 Benicia Street, and 47658 Kato Road, Fremont, California, USA. Line conducted emissions are measured only at the 47173 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

47173 Benicia Street	47266 Benicia Street	47658 Kato Rd
☐ Chamber A (ISED:2324B-1)	☒ Chamber D (ISED:22541-1)	☐ Chamber K (ISED:2324A-1)
☐ Chamber B (ISED:2324B-2)	☒ Chamber E (ISED:22541-2)	☐ Chamber L (ISED:2324A-3)
☐ Chamber C (ISED:2324B-3)	☐ Chamber F (ISED:22541-3)	
	☐ Chamber G (ISED:22541-4)	
	☐ Chamber H (ISED:22541-5)	

The above test sites and facilities are covered under FCC Test Firm Registration # 208313. Chambers A through C are covered under ISED company address code 2324B with site numbers 2324B -1 through 2324B-3, respectively. Chambers D through H are covered under ISED company address code 22541 with site numbers 22541 -1 through 22541-5, respectively. Chambers K and L are covered under ISED company address code 2324A with site numbers 2324A-1 and 2324A-3, respectively.

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at [NVLAP Lab Search](#).

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Worst Case Conducted Disturbance, 9KHz to 0.15 MHz	3.84 dB
Worst Case Conducted Disturbance, 0.15 to 30 MHz	3.65 dB
Worst Case Radiated Disturbance, 9KHz to 30 MHz	3.15 dB
Worst Case Radiated Disturbance, 30 to 1000 MHz	5.36 dB
Worst Case Radiated Disturbance, 1000 to 18000 MHz	4.32 dB
Worst Case Radiated Disturbance, 18000 to 26000 MHz	4.45 dB
Worst Case Radiated Disturbance, 26000 to 40000 MHz	5.24 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. EUT DESCRIPTION

The Apple iPhone, is a smartphone with multimedia functions (music, application support, and video), cellular GSM, GPRS, EGPRS, UMTS, LTE, TD-SCDMA, CDMA, IEEE 802.11a/b/g/n/ac, Bluetooth, GPS and NFC. All models support at least one UICC based SIM. The second SIM is either UICC based, electronic SIM (e-SIM), or second SIM is not present. The device has a built-in inductive charging receiver which is not user accessible. The rechargeable battery is not user accessible.

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum conducted output power as follows:

5.2 GHz BAND

Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
5.2 GHz band, 1TX			
5180-5240	802.11a	Covered by 802.11n HT20 1TX	
5180-5240	802.11n HT20	20.94	124.17
5190-5230	802.11n HT40	19.47	88.51
5180-5240	802.11ac VHT20	Covered by 802.11n HT20 1TX	
5190-5230	802.11ac VHT40	Covered by 802.11n HT40 1TX	
5210	802.11ac VHT80	17.47	55.85
5.2 GHz band, 2TX			
5180-5240	802.11n HT20 CDD	20.96	124.74
5180-5240	802.11n HT20 SDM	Covered by 802.11n HT20 2TX CDD	
5180-5240	802.11n HT20 STBC		
5190-5230	802.11n HT40 CDD	22.44	175.39
5190-5230	802.11n HT40 SDM	Covered by 802.11n HT40 2TX CDD	
5190-5230	802.11n HT40 STBC		
5180-5240	802.11ac VHT20 CDD	Covered by 802.11n HT20 2TX CDD	
5180-5240	802.11ac VHT20 SDM		
5180-5240	802.11ac VHT20 STBC		
5190-5230	802.11ac VHT40 CDD	Covered by 802.11n HT40 2TX CDD	
5190-5230	802.11ac VHT40 SDM		
5190-5230	802.11ac VHT40 STBC		
5210	802.11ac VHT80 CDD	19.45	88.10
5210	802.11ac VHT80 SDM	Covered by 802.11ac VHT80 2TX CDD	
5210	802.11ac VHT80 STBC		

5.3 GHz BAND

Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
5.3 GHz band, 1TX			
5260 - 5320	802.11a	Covered by 802.11n HT20 1TX	
5260 - 5320	802.11n HT20	20.92	123.59
5270 - 5310	802.11n HT40	19.38	86.70
5260 - 5320	802.11ac VHT20	Covered by 802.11n HT20 1TX	
5270 - 5310	802.11ac VHT40	Covered by 802.11n HT40 1TX	
5290	802.11ac VHT80	17.42	55.22
5.3 GHz band, 2TX			
5260 - 5320	802.11n HT20 CDD	20.94	124.17
5260 - 5320	802.11n HT20 SDM	Covered by 802.11n HT20 2TX CDD	
5260 - 5320	802.11n HT20 STBC		
5270 - 5310	802.11n HT40 CDD	22.42	174.58
5270 - 5310	802.11n HT40 SDM	Covered by 802.11n HT40 2TX CDD	
5270 - 5310	802.11n HT40 STBC		
5260 - 5320	802.11ac VHT20 CDD	Covered by 802.11n HT20 2TX CDD	
5260 - 5320	802.11ac VHT20 SDM		
5260 - 5320	802.11ac VHT20 STBC		
5270 - 5310	802.11ac VHT40 CDD	Covered by 802.11n HT40 2TX CDD	
5270 - 5310	802.11ac VHT40 SDM		
5270 - 5310	802.11ac VHT40 STBC		
5290	802.11ac VHT80 CDD	19.46	88.31
5290	802.11ac VHT80 SDM	Covered by 802.11n VHT80 2TX CDD	
5290	802.11ac VHT80 STBC		

5.6 GHz BAND

Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
5.6 GHz band, 1TX			
5500-5720	802.11a	Covered by 802.11n HT20 1TX	
5500-5720	802.11n HT20	20.89	122.74
5510-5710	802.11n HT40	19.45	88.10
5500-5720	802.11ac VHT20	Covered by 802.11n HT20 1TX	
5510-5710	802.11ac VHT40	Covered by 802.11n HT40 1TX	
5530-5690	802.11ac VHT80	19.42	87.50
5.6 GHz band, 2TX			
5500-5720	802.11n HT20 CDD	20.96	124.74
5500-5720	802.11n HT20 SDM	Covered by 802.11n HT20 2TX CDD	
5500-5720	802.11n HT20 STBC		
5510-5710	802.11n HT40 CDD	22.44	175.39
5510-5710	802.11n HT40 SDM	Covered by 802.11n HT40 2TX CDD	
5510-5710	802.11n HT40 STBC		
5500-5720	802.11ac VHT20 CDD	Covered by 802.11n HT20 2TX CDD	
5500-5720	802.11ac VHT20 SDM		
5500-5720	802.11ac VHT20 STBC		
5510-5710	802.11ac VHT40 CDD	Covered by 802.11n HT40 2TX CDD	
5510-5710	802.11ac VHT40 SDM		
5510-5710	802.11ac VHT40 STBC		
5530-5690	802.11ac VHT80 CDD	22.35	171.79
5530-5690	802.11ac VHT80 SDM	Covered by 802.11ac VHT80 2TX CDD	
5530-5690	802.11ac VHT80 STBC		

5.8 GHz BAND

Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
5.8 GHz band, 1Tx			
5745-5825	802.11a	Covered by 802.11n HT20 1Tx	
5745-5825	802.11n HT20	21.49	140.93
5755-5795	802.11n HT40	19.43	87.70
5745-5825	802.11ac VHT20	Covered by 802.11n HT20 1Tx	
5755-5795	802.11ac VHT40	Covered by 802.11n HT40 1Tx	
5775	802.11ac VHT80	19.48	88.72
5.8 GHz band, 2Tx			
5745-5825	802.11n HT20 CDD	24.45	278.61
5745-5825	802.11n HT20 SDM	Covered by 802.11n HT20 2Tx CDD	
5745-5825	802.11n HT20 STBC		
5755-5795	802.11n HT40 CDD	22.43	174.98
5755-5795	802.11n HT40 SDM	Covered by 802.11n HT40 2Tx CDD	
5755-5795	802.11n HT40 STBC		
5745-5825	802.11ac VHT20 CDD	Covered by 802.11n HT20 2Tx CDD	
5745-5825	802.11ac VHT20 SDM		
5745-5825	802.11ac VHT20 STBC		
5755-5795	802.11ac VHT40 CDD	Covered by 802.11n HT40 2Tx CDD	
5755-5795	802.11ac VHT40 SDM		
5755-5795	802.11ac VHT40 STBC		
5775	802.11ac VHT80 CDD	22.36	172.19
5775	802.11ac VHT80 SDM	Covered by 802.11ac VHT80 2Tx CDD	
5775	802.11ac VHT80 STBC		

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

Frequency Range (GHz)	Antenna 4 (dBi)	Antenna 5 (dBi)
5.2	-5.3	-5.0
5.3	-5.0	-5.2
5.6	-3.8	-3.9
5.8	-3.7	-4.9

5.4. SOFTWARE AND FIRMWARE

The EUT firmware installed during testing was v1.29.99992

The test utility software used during testing was QRCT v3.0.264.0.

5.5. WORST-CASE CONFIGURATION AND MODE

The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z on Ant 4 (Antenna 4) and Ant 5 (Antenna 5). It was determined that Z (Portrait) orientation was the worst-case orientation for Ant 4; and Y (Landscape) orientation was the worst case for Ant 5 and 2TX.

For radiated harmonics spurious below 1GHz, 1-18GHz L/M/H channels, 18-40GHz, and power line conducted emissions were performed with the EUT set at the 2TX CDD mode among the CDD/SDM modes with power setting equal or higher than SISO modes as worst-case scenario.

Radiated band edge, harmonic, and spurious emissions from 1GHz to 18GHz were performed with the EUT set to transmit at highest power on Low/Middle/High channels.

Below 1GHz tests were performed with EUT connected to AC power adapter as the worst case; and for above 1GHz, the worst-case configuration reported was tested with EUT only. For AC line conducted emission, test was investigated with AC power adapter and with laptop.

There were no emissions found below 30MHz within 20dB of the limit.

For simultaneous transmission with the Bluetooth was investigated, no noticeable emission was found.

Worst-case data rates as provided by the client were:

802.11n HT20mode: MCS0
802.11n HT40mode: MCS0
802.11ac VHT80 mode: MCS0

There are two vendors of the WiFi/Bluetooth radio modules: variant 1 and variant 2. The Wi-Fi/Bluetooth radio modules have the same mechanical outline (e.g., the same package dimension and pin-out layout), use the same on-board antenna matching circuit, have an identical antenna structure, and are built and tested to conform to the same specifications and to operate within the same tolerances.

Baseline testing was performed on the two variants to determine the worst case on all conducted power and radiated emissions.

5.6. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
laptop	Apple	Macbook Pro	C02P41RZG086	FCC DoC
Laptop AC/DC adapter	Liteon Technology	PA-1450-BA1	B123	NA
EUT AC Adapter	Apple	A1385	D292365CDYADHLHC3	NA

I/O CABLES (CONDUCTED TEST)

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	Antenna	1	SMA	Un-Shielded	0.2	To spectrum Analyzer
2	USB	1	USB	Shielded	1	N/A
3	AC	1	AC	Un-shielded	2	N/A

I/O CABLES (RADIATED ABOVE 1 GHZ)

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
NA						


I/O CABLES (BELOW 1GHz AND AC POWER LINE TEST WITH ADAPTER AND LAPTOP)

I/O Cable List						
Cable No	Port	# of identical	Connector Type	Cable Type	Cable Length (m)	Remarks
1	AC	1	AC	Un-shielded	2	N/A
2	USB	1	USB	Shielded	1	N/A


TEST SETUP - CONDUCTED TESTS

The EUT was tested connected to a host Laptop via USB cable adapter and spectrum analyzer to antenna port. Test software exercised the EUT.


SETUP DIAGRAM




SETUP DIAGRAM FOR RADIATED TESTS Above 1GHz



SETUP DIAGRAM FOR Below 1GHz and AC LINE CONDUCTED TEST



TEST SETUP- AC LINE CONDUCTED: LAPTOP CONFIGURATION



6. MEASUREMENT METHOD

On Time and Duty Cycle: KDB 789033 D02 v02r01, Section B.

6 dB Emission BW: KDB 789033 D02 v02r01, Section C.2

26 dB Emission BW: KDB 789033 D02 v02r01, Section C.1

99% Occupied BW: KDB 789033 D02 v02r01, Section D.

Conducted Output Power: KDB 789033 D02 v02r01, Section E.3.b (Method PM-G) and KDB 789033 D02 v02r01, Section E.2.b (Method SA-2)

Power Spectral Density: KDB 789033 D02 v02r01, Section F

Unwanted emissions in restricted bands: KDB 789033 D02 v02r01, Sections G.3, G.4, G.5, and G.6.

Unwanted emissions in non-restricted bands: KDB 789033 D02 v02r01, Sections G.3, G.4, and G.5.

AC Power Line Conducted Emissions: ANSI C63.10-2013, Section 6.2.

7. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Description	Manufacturer	Model	ID Num	Cal Due
Antenna, Horn 1-18GHz	ETS-Lindgren	3117	T862	05/24/2019
*Antenna, Horn 1-18GHz	ETS Lindgren	3117	T136	06/26/2018
Antenna, Horn 1-18GHz	ETS Lindgren	3117	T346	04/03/2019
Antenna, Horn 1-18GHz	ETS Lindgren	3117	T345	04/25/2019
Antenna, Broadband Hybrid, 30MHz to 2000MHz	Sunol Sciences	JB1	T185	04/19/2019
Amplifier, 10KHz to 1GHz, 32dB	Sonoma	310N	T835	12/15/2018
*Amplifier, 1 to 18GHz, 35dB	Amplical	AMP1G18-35	T1569	06/03/2018
**Amplifier, 1 to 18GHz	Miteq	AFS42-00101800-25-S-42	T1165	06/12/2018
Amplifier, 1 to 18GHz	Miteq	AFS42-00101800-25-S-42	T740	12/30/2018
Amplifier, 1 to 18GHz	Miteq	AFS42-00101800-25-S-42	T741	12/30/2018
Amplifier, 1 to 18GHz	Miteq	AFS42-00101800-25-S-42	T1131	12/30/2018
Spectrum Analyzer, PXA 3Hz to 44GHz	Keysight	N9030A	T340	12/15/2018
Spectrum Analyzer, PXA 3Hz to 44GHz	Keysight	N9030A	T906	02/16/2019
Spectrum Analyzer, PXA, 3Hz to 44GHz	Agilent (Keysight) Technologies	N9030A	T1454	01/08/2019
Spectrum Analyzer, PSA, 3Hz to 44GHz	Agilent (Keysight) Technologies	E4446A	T177	04/12/2019
Antenna, Active Loop 9KHz to 30MHz	ETS-Lindgren	6502	T757	09/14/2018
Power Meter, P-series single channel	Agilent (Keysight) Technologies	N1911A	T227	10/27/2018
Power Sensor	Keysight	N1921A	T1226	08/30/2018
Antenna Horn, 18 to 26GHz	ARA	MWH-1826	T89	01/18/2019
*Pre-Amp 18-26GHz	Agilent Technology	8449B	T404	07/23/2018
Antenna Horn 26-40GHz	ARA	MWH-2640	T90	08/25/2018
Amplifier, 26GHz to 40GHz	Miteq	TTA2640-35-HG	T1864	03/09/2019
AC Line Conducted				
EMI Test Receiver 9KHz-7GHz	Rohde & Schwarz	ESCI7	T1436	01/25/2019
Power Cable, Line Conducted Emissions	UL	PG1	T861	08/31/2018
**LISN for Conducted Emissions CISPR-16	Fischer	50/250-25-2-01	T1310	06/19/2019
UL AUTOMATION SOFTWARE				
Radiated Software	UL	UL EMC	Ver 9.5, April 26, 2016	
Conducted Software	UL	UL EMC	Ver 5.4, October 13, 2016	
AC Line Conducted Software	UL	UL EMC	Ver 9.5, May 26, 2015	

Note: *Testing is completed before equipment expiration date.

**Testing is completed after calibration was done

8. ANTENNA PORT TEST RESULTS

8.1. ON TIME AND DUTY CYCLE

LIMITS


None; for reporting purposes only.

PROCEDURE

KDB 789033 Zero-Span Spectrum Analyzer Method.

ON TIME AND DUTY CYCLE RESULTS

Mode	ON Time B (msec)	Period (msec)	Duty Cycle x (linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/B Minimum VBW (kHz)
802.11n HT20 1TX/2TX	1.921	1.944	0.988	98.82%	0.00	0.010
802.11n HT40 1TX/2TX	0.945	0.964	0.980	98.01%	0.00	0.010
802.11ac VHT80 1TX/2TX	0.460	0.482	0.954	95.44%	0.20	2.174



8.2. 26 dB BANDWIDTH

LIMITS


None; for reporting purposes only.

RESULTS

8.2.1. 802.11n HT20 MODE IN THE 5.2 GHz BAND


1TX Antenna 4 MODE

Channel	Frequency (MHz)	26 dB Bandwidth (MHz)
Low	5180	21.95
Mid	5200	21.90
High	5240	22.00



1TX Antenna 5 MODE



Channel	Frequency	26 dB Bandwidth
	(MHz)	(MHz)
Low	5180	21.85
Mid	5200	21.80
High	5240	21.85





2TX Antenna 4 + Antenna 5 CDD MODE

Channel	Frequency (MHz)	26 dB Bandwidth Antenna 4 (MHz)	26 dB Bandwidth Antenna 5 (MHz)
Low	5180	21.85	21.70
Mid	5200	21.65	21.45
High	5240	21.80	21.60


LOW CHANNEL



MID CHANNEL




HIGH CHANNEL



8.2.2. 802.11n HT40 MODE IN THE 5.2 GHz BAND


1TX Antenna 4 MODE

Channel	Frequency	26dB Bandwidth
	(MHz)	(MHz)
Low	5190	40.60
High	5230	40.50



1TX Antenna 5 MODE



Channel	Frequency (MHz)	26dB Bandwidth (MHz)
Low	5190	40.40
High	5230	40.40





2TX Antenna 4 + Antenna 5 CDD MODE

Channel	Frequency (MHz)	26 dB Bandwidth Antenna 4 (MHz)	26 dB Bandwidth Antenna 5 (MHz)
Low	5190	40.50	40.10
High	5230	40.60	40.00

LOW CHANNEL




HIGH CHANNEL



8.2.3. 802.11ac VHT80 MODE IN THE 5.2 GHz BAND

1TX Antenna 4 MODE


Channel	Frequency	26 dB Bandwidth
	(MHz)	(MHz)
Mid	5210	82.60



2TX Antenna 4 + Antenna 5 CDD MODE

Channel	Frequency (MHz)	26 dB Bandwidth Antenna 4 (MHz)	26 dB Bandwidth Antenna 5 (MHz)
Mid	5210	82.40	82.20


MID CHANNEL



8.2.4. 802.11n HT20 MODE IN THE 5.3 GHz BAND


1TX Antenna 4 MODE

Channel	Frequency	26 dB Bandwidth
	(MHz)	(MHz)
Low	5260	21.80
Mid	5300	21.95
High	5320	21.95



1TX Antenna 5 MODE


Channel	Frequency	26 dB Bandwidth
	(MHz)	(MHz)
Low	5260	21.95
Mid	5300	22.00
High	5320	21.90




2TX Antenna 4 + Antenna 5 CDD MODE

Channel	Frequency (MHz)	26 dB Bandwidth Antenna 4 (MHz)	26 dB Bandwidth Antenna 5 (MHz)
Low	5260	21.85	21.70
Mid	5300	21.80	21.50
High	5320	22.00	21.55


LOW CHANNEL



MID CHANNEL




HIGH CHANNEL



8.2.5. 802.11n HT40 MODE IN THE 5.3 GHz BAND


1TX Antenna 4 MODE

Channel	Frequency	26dB Bandwidth
	(MHz)	(MHz)
Low	5270	40.70
High	5310	40.50



1TX Antenna 5 MODE



Channel	Frequency	26dB Bandwidth
	(MHz)	(MHz)
Low	5270	40.60
High	5310	40.40





2TX Antenna 4 + Antenna 5 CDD MODE

Channel	Frequency (MHz)	26 dB Bandwidth Antenna 4 (MHz)	26 dB Bandwidth Antenna 5 (MHz)
Low	5270	40.60	40.10
High	5310	40.70	40.10

LOW CHANNEL




HIGH CHANNEL



8.2.6. 802.11ac VHT80 MODE IN THE 5.3 GHz BAND


1TX Antenna 4 MODE

Channel	Frequency	26 dB Bandwidth
	(MHz)	(MHz)
Mid	5290	82.40



1TX Antenna 5 MODE


Channel	Frequency	26 dB Bandwidth
	(MHz)	(MHz)
Mid	5290	82.40



2TX Antenna 4 + Antenna 5 CDD MODE

Channel	Frequency (MHz)	26 dB Bandwidth Antenna 4 (MHz)	26 dB Bandwidth Antenna 5 (MHz)
Mid	5290	82.20	81.80


MID CHANNEL



8.2.7. 802.11n HT20 MODE IN THE 5.6 GHz BAND





1TX Antenna 4 MODE

Channel	Frequency	26 dB Bandwidth
	(MHz)	(MHz)
Low	5500	21.70
Mid	5580	21.95
High	5700	21.90
144	5720	21.85



1TX Antenna 5 MODE


Channel	Frequency (MHz)	26 dB Bandwidth (MHz)
Low	5500	21.85
Mid	5580	22.05
High	5700	22.00
144	5720	21.95




2TX Antenna 4 + Antenna 5 CDD MODE

Channel	Frequency (MHz)	26 dB Bandwidth Antenna 4 (MHz)	26 dB Bandwidth Antenna 5 (MHz)
Low	5500	21.75	21.65
Mid	5580	21.80	21.55
High	5700	21.75	21.60
144	5720	22.05	21.65

LOW CHANNEL



MID CHANNEL



The figure displays two side-by-side screenshots of a Keysight Spectrum Analyzer, showing the frequency response of two antennas. Both plots are set to a Center Freq of 5.700000000 GHz, a Span of 50.000 MHz, and a Resolution Bandwidth (RBW) of 390 kHz. The left plot is for 'HIGH CHANNEL ANTENNA 4' and the right plot is for 'HIGH CHANNEL ANTENNA 5'. Both plots show a bandpass filter response with a peak around 5.7 GHz. The left plot has a peak level of -17.86 dBm, while the right plot has a peak level of -15.37 dBm. Both plots show a 3 dB bandwidth of approximately 10 MHz.

High Channel Antenna 4 Data:

- Center Freq: 5.700000000 GHz
- Start Freq: 5.675000000 GHz
- Stop Freq: 5.725000000 GHz
- CF Step: 5.000000 MHz
- Freq Offset: 0 Hz
- Scale Type: Auto
- Ref Offset: 16.65 dB
- Ref: 20.00 dBm
- ΔMkr1 : 21.75 MHz
- ΔMkr2 : -0.068 dB
- Peak Level: -17.86 dBm

High Channel Antenna 5 Data:

- Center Freq: 5.700000000 GHz
- Start Freq: 5.675000000 GHz
- Stop Freq: 5.725000000 GHz
- CF Step: 5.000000 MHz
- Freq Offset: 0 Hz
- Scale Type: Auto
- Ref Offset: 17.55 dB
- Ref: 20.00 dBm
- ΔMkr1 : 21.60 MHz
- ΔMkr2 : 0.766 dB
- Peak Level: -15.37 dBm

The image displays two side-by-side screenshots of the Keysight Spectrum Analyzer software interface, showing channel power measurements for two different antennas.

Left Screenshot (Antenna 4):

- Center Freq:** 5.720000000 GHz
- Ref Offset:** 16.57 dB
- Ref:** 20.00 dBm
- Auto Tune:** Center Freq 5.720000000 GHz, Start Freq 5.695000000 GHz, Stop Freq 5.745000000 GHz, CF Step 5.0000000 MHz, Freq Offset 0 Hz, Scale Type Log.
- Measurement:** ΔMkr1 22.05 MHz, 0.594 dB
- Power:** -18.64 dBm

Right Screenshot (Antenna 5):

- Center Freq:** 5.720000000 GHz
- Ref Offset:** 17.57 dB
- Ref:** 20.00 dBm
- Auto Tune:** Center Freq 5.720000000 GHz, Start Freq 5.695000000 GHz, Stop Freq 5.745000000 GHz, CF Step 5.0000000 MHz, Freq Offset 0 Hz, Scale Type Log.
- Measurement:** ΔMkr1 21.65 MHz, 0.524 dB
- Power:** -15.58 dBm

Both screenshots show a signal trace with a peak at 5.72 GHz. The power level for Antenna 4 is -18.64 dBm, and for Antenna 5, it is -15.58 dBm.