

FCC ID: BCG-E3500A
IC Certification ID: 579C-E3500A
Model Number: A2275, A2297, and A2298
Date: 2/5/2020

POWER REDUCTION VERIFICATION

This device supports manufacturer's proprietary power reduction mechanism called, 'Detect mode' for the Main Cellular Antenna. Details of this mechanism can be found in the Operational Description.

The verification plan consists of two parts.

- Verification of the detect mechanism
- Verification of the power reduction levels

The verification plan for the overall power setting is proposed to follow the Table 1 below.

A. Verification of the detect mechanism

Body detect verification will be done with following test cases.

- In-hand
- On-lap with little or no voluntary movement
- On a stationary object

B. Verification of power reduction levels

Table 1 lists the test plan. Since the reduction mechanism is antenna agnostic all tests will be conducted by locking transmission to one antenna and then verifying power.

Table 1

	Test Cases	Head Cell Table ¹	Body Cell Table ¹
Cellular ²	GSM 850 (2Slots)		
	GSM 1900 (2Slots)	29.1	25.4
	CDMA BC10		
	CDMA BC0		
	CDMA BC1	22.8	18.4
	WCDMA B5		
	WCDMA B4	24.4	19.5
	WCDMA B2	24.2	19.5
	LTE B12		
	LTE B13		

FCC ID: BCG-E3500A

IC Certification ID: 579C-E3500A

Model Number: A2275, A2297, and A2298

Date: 2/5/2020

	LTE B14				
	LTE B71				
	LTE B5				
	LTE B26				
	LTE B25	23.2		18.0	
	LTE B30	23.0		19.5	
	LTE B7	24.8		18.1	
	LTE B41	24.2		20.5	
	LTE B48	24.6		22.7	
Wi-Fi 1x mode, rate, channel	Test Cases	Cell On Head Wi-Fi Table	Cell Off Head Wi-Fi Table	Cell On Body Wi-Fi Table	Cell Off Body Wi-Fi Table
	2.4 GHz 11n HT20 Ch6 SISO	EP: 8.75 RP: 8.60	EP: 14.0 RP: 13.7	EP: 13.75 RP: 13.50	EP: 17.50 RP: 17.20
	5.0 GHz 802.11n HT20 Ch40 SISO Ant6	EP: 4.50 RP: 4.20	EP: 12.25 RP: 12.00	EP: 11.75 RP: 11.60	EP: 16.0 RP: 15.70

BT EDR, Hopping	Test Cases	Cell On 5GHz On Head Plow mode A BT Table P ₁	Cell On 5GHz Off Head PHigh mode A BT Table P ₃	Cell Off 5GHz On Head PHigh mode A BT Table P ₅	Cell Off 5GHz Off Head PStandalo ne BT Table P ₇	Cell On 5GHz On Body Plow mode B BT Table P ₂	Cell On 5GHz Off Body PHigh mode B BT Table P ₄	Cell Off 5GHz On Body PHigh mode B BT Table P ₆	Cell Off 5GHz Off Body PStandalon e BT Table P ₈
	Ch 39	EP: 6.5 RP: 6.4	EP: 8.5 RP: 8.3	EP: 8.5 RP: 8.2	EP: 13.5 RP: 13.4	EP: 7.0 RP: 6.9	EP: 11 RP: 10.8	EP: 10.5 RP: 10.3	EP: 13.5 RP: 13.1

Notes:

1. Head test cases will be done with the device resting on table and body test cases will be done with the device in hand.
2. When there is no delta between the head cell table and body cell table within a test case, we will exclude that test case

EP: expected power

RP: record power