



TEST REPORT

Report Number: 13336566-E2V1

Applicant : APPLE INC.
1 APPLE PARK WAY
CUPERTINO, CA 95014, U.S.A

Model : A2406

FCC ID : BCG-E3546A

IC : 579C-E3546A

EUT Description : SMARTPHONE

Test Standard(s) : FCC 47 CFR PART 15 SUBPART C
ISED RSS-247 ISSUE 2
ISED RSS-GEN ISSUE 5

Date of Issue:
September 21, 2020

Prepared by:
UL Verification Services Inc.
47173 Benicia Street
Fremont, CA 94538 U.S.A.
TEL: (510) 319-4000
FAX: (510) 661-0888

REPORT REVISION HISTORY

Rev.	Issue Date	Revisions	Revised By
V1	9/21/2020	Initial Issue	Chin Pang

TABLE OF CONTENTS

REPORT REVISION HISTORY	2
TABLE OF CONTENTS	3
1. ATTESTATION OF TEST RESULTS	4
2. TEST RESULTS SUMMARY	5
3. TEST METHODOLOGY	5
4. FACILITIES AND ACCREDITATION	5
5. DECISION RULES AND MEASUREMENT UNCERTAINTY	6
5.1. METROLOGICAL TRACEABILITY	6
5.2. DECISION RULES.....	6
5.3. MEASUREMENT UNCERTAINTY.....	6
6. INTRODUCTION OF TEST DATA REUSE.....	7
6.1. EUT DESCRIPTION	7
6.2. INTRODUCTION	7
6.3. SPOT CHECK VERIFICATION RESULTS SUMMARY	7
6.5. DESCRIPTION OF AVAILABLE ANTENNAS	14
6.6. SOFTWARE AND FIRMWARE.....	14
6.7. WORST-CASE CONFIGURATION AND MODE.....	14
6.8. DESCRIPTION OF TEST SETUP.....	15
7. MEASUREMENT METHOD.....	16
8. TEST AND MEASUREMENT EQUIPMENT	16
9. SETUP PHOTOS.....	16
Appendix A – Reference Test Report	17

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: APPLE INC.
1 APPLE PARK WAY
CUPERTINO, CA 95014, U.S.A

EUT DESCRIPTION: SMARTPHONE

MODEL: A2406

SERIAL NUMBER: (Original): G6TCP01UQ5R9, G6TCM020Q5T6
(Spot Check): G6TCN00GQ5W0, G6TCN00KQ5W0

DATE TESTED: JULY 24, 2020 – JULY 26, 2020

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Complies
ISED RSS-247 Issue 2	Complies
ISED RSS-GEN Issue 5	Complies

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. All samples tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise.


This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of the U.S. government.

Approved & Released For
UL Verification Services Inc. By:



Chin Pang
Senior Engineer
Consumer Technology Division
UL Verification Services Inc.

Prepared By:



Jingang Li
Test Engineer
Consumer Technology Division
UL Verification Services Inc.

2. TEST RESULTS SUMMARY

FCC Clause	ISED Clause	Requirement	Result	Comment
15.209, 15.205	RSS-GEN 8.9, 8.10	Radiated Emissions	complies	None.

3. TEST METHODOLOGY

The tests documented in this report were performed in accordance with FCC CFR 47 Part 2, FCC CFR 47 Part 15, ANSI C63.10-2013, KDB 558074 D01 15.247 Meas Guidance v05r02, KDB 662911, RSS-GEN Issue 5, and RSS-247 Issue 2.

4. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 and 47266 Benicia Street, and 47658 Kato Road, Fremont, California, USA. Line conducted emissions are measured only at the 47173 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

47173 Benicia Street	47266 Benicia Street	47658 Kato Rd.
☐ Chamber A (IC:2324B-1)	☐ Chamber D (IC:22541-1)	☐ Chamber I (IC: 2324A-5)
☐ Chamber B (IC:2324B-2)	☐ Chamber E (IC:22541-2)	☐ Chamber J (IC: 2324A-6)
☐ Chamber C (IC:2324B-3)	☐ Chamber F (IC:22541-3)	☐ Chamber K (IC: 2324A-1)
	☐ Chamber G (IC:22541-4)	☒ Chamber L (IC: 2324A-3)
	☐ Chamber H (IC:22541-5)	☐ Chamber M (IC: 2324A-2)

The above test sites and facilities are covered under FCC Test Firm Registration # 208313. Chambers above are covered under Industry Canada company address and respective code: 2324A.

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0

5. DECISION RULES AND MEASUREMENT UNCERTAINTY

5.1. METROLOGICAL TRACEABILITY

All test and measuring equipment utilized to perform the tests documented in this report are calibrated on a regular basis, with a maximum time between calibrations of one year or the manufacturers' recommendation, whichever is less, and where applicable is traceable to recognized national standards.

5.2. DECISION RULES

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4:2012 Clause 8.2. (Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

5.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	U _{Lab}
Worst Case Conducted Disturbance, 9KHz to 0.15 MHz	3.39 dB
Worst Case Conducted Disturbance, 0.15 to 30 MHz	3.07 dB
Worst Case Radiated Disturbance, 9KHz to 30 MHz	2.52 dB
Worst Case Radiated Disturbance, 30 to 1000 MHz	4.88 dB
Worst Case Radiated Disturbance, 1000 to 18000 MHz	4.24 dB
Worst Case Radiated Disturbance, 18000 to 26000 MHz	4.37 dB
Worst Case Radiated Disturbance, 26000 to 40000 MHz	5.17 dB

Uncertainty figures are valid to a confidence level of 95%.

6. INTRODUCTION OF TEST DATA REUSE

6.1. EUT DESCRIPTION

The Apple iPhone is a smartphone with multimedia functions (music, application support, and video), cellular GSM, GPRS, EGPRS, UMTS, LTE, 5G, CDMA, IEEE 802.11a/b/g/n/ac/ax, Bluetooth, Ultra-Wideband, GPS, NFC and WPT. All models support at least one UICC based SIM. The second SIM is either an UICC based p-SIM (physical SIM) or e-SIM (electronic SIM). The device supports a built-in inductive charging transmitter and receiver. The rechargeable battery is not user accessible.

6.2. INTRODUCTION

This application for certification is leveraging the data reuse procedures from KDB 484596 D01 based on reference FCC ID: BCG-E3545A, IC: 579C-E3545A to cover variant model BCG-E3546A, 579C-E3546A. The major difference between the parent/reference model and the variant model is the depopulation in the variant model of the mmWave transmitter. All other circuitry and features are identical. The data reuse test plan was approved via manufacturer KDB inquiry.

6.3. SPOT CHECK VERIFICATION RESULTS SUMMARY

Spot check verification has been done on device model A2406, FCC ID: BCG-E3546A, IC: 579C-E3546A for radiated spurious and radiated band-edge in accordance with the Test Plan that was approved via KDB inquiry.

BCG-E3546A, 579C-E3546A SPOT CHECK RESULTS										
Technology	Mode	Test Item	Channel	Measured	Original model		Spot check model		Delta (dB)	
					BCG-E3545A 579C-E3545A		BCG-E3546A 579C-E3546A			
					A2341		A2406			
				Frequency (MHz)	Peak (d	Ave	Peak	Ave	Peak	Ave
BLE	1Mbps	RBE	Low	2390.0	52.4	44.26	54.07	42.25	1.67	2.01
			High	2483.5	51.71	39.68	NF	NF	NA	NA
	1Mbps	RSE	Mid	12200.8	55.38	45.21	NF	NF	NA	-

Comparison of the models, upper deviation is within 3dB range and all tests are under FCC Technical Limits. The test report for FCC ID: BCG-E3545A, IC: 579C-E3545A is therefore being used to support the application for certification for FCC ID: BCG-E3546A & IC: 579C-E3546A.


Note: NF - noise floor.

Note: The output powers were verified on model A2406 to match with model A2341 before radiated emissions spot check was performed.

SPOT CHECK DATA

BANDEDGE (LOW CHANNEL)

HORIZONTAL RESULT




Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF 344 (dB/m)	Amp/Cbl/Filt/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	34.22	Pk	31.9	-13.1	53.02	-	-	74	-20.98	302	247	H
2	* 2.35395	35.57	Pk	31.6	-13.1	54.07	-	-	74	-19.93	302	247	H
3	* 2.39	22.34	RMS	31.9	-13.1	41.14	54	-12.86	-	-	302	247	H
4	* 2.37871	23.45	RMS	31.8	-13	42.25	54	-11.75	-	-	302	247	H

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

RMS - RMS detection

VERTICAL RESULT




Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF 344 (dB/m)	Amp/Cbl/Filtr/ Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	33	Pk	31.9	-13.1	51.8	-	-	74	-22.2	318	363	V
2	* 2.38465	35.56	Pk	31.8	-13	54.36	-	-	74	-19.64	318	363	V
3	* 2.39	22.2	RMS	31.9	-13.1	41	54	-13	-	-	318	363	V
4	* 2.37654	23.38	RMS	31.8	-13	42.18	54	-11.82	-	-	318	363	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
Pk - Peak detector
RMS - RMS detection

BANDEDGE (HIGH CHANNEL)


HORIZONTAL RESULT



Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF 344 (dB/m)	Amp/Cbl/Filtr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.4835	33.75	Pk	32.3	-12.9	53.15	-	-	74	-20.85	32	157	H
2	2.51689	35.74	Pk	32.4	-12.8	55.34	-	-	74	-18.66	32	157	H
3	* 2.4835	22.5	RMS	32.3	-12.9	41.9	54	-12.1	-	-	32	157	H
4	2.52688	23.55	RMS	32.4	-12.7	43.25	54	-10.75	-	-	32	157	H

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
Pk - Peak detector
RMS - RMS detection

VERTICAL RESULT





Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF 344 (dB/m)	Amp/Cbl/Filtr/ Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.4835	33.62	Pk	32.3	-12.9	53.02	-	-	74	-20.98	228	396	V
2	* 2.49124	35.68	Pk	32.3	-12.8	55.18	-	-	74	-18.82	228	396	V
3	* 2.4835	21.9	RMS	32.3	-12.9	41.3	54	-12.7	-	-	228	396	V
4	2.55574	23.47	RMS	32.3	-12.6	43.17	54	-10.83	-	-	228	396	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
Pk - Peak detector
RMS - RMS detection

HARMONICS AND SPURIOUS EMISSIONS

MID CHANNEL RESULTS



RADIATED EMISSIONS

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF 344 (dB/m)	Amp/Cbl/Filtr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 1.22937	30.55	PK2	28.5	-16.7	42.35	-	-	74	-31.65	0	200	H
	* 1.2293	19.63	MAv1	28.5	-16.7	31.43	54	-22.57	-	-	0	200	H
4	* 1.1689	35.64	PK2	27.6	-17.3	45.94	-	-	74	-28.06	351	106	V
	* 1.16968	24.84	MAv1	27.6	-17.2	35.24	54	-18.76	-	-	351	106	V
5	* 2.25789	35.34	PK2	31.7	-13.4	53.64	-	-	74	-20.36	221	147	V
	* 2.26038	25.91	MAv1	31.7	-13.4	44.21	54	-9.79	-	-	221	147	V
2	* 4.87943	36.38	PK2	34.1	-27.1	43.38	-	-	74	-30.62	151	253	H
	* 4.88031	26.75	MAv1	34.1	-27.1	33.75	54	-20.25	-	-	151	253	H
3	* 8.16992	31.39	PK2	35.7	-21.8	45.29	-	-	74	-28.71	228	261	H
	* 8.1679	21.47	MAv1	35.7	-21.8	35.37	54	-18.63	-	-	228	261	H
6	6.27218	34.9	PK2	35.6	-25.5	45	-	-	-	-	303	346	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

PK2 - KDB558074 Method: Maximum Peak

MAv1 - KDB558074 Option 1 Maximum RMS Average

6.4. REFERENCE DETAIL

Reference application that contains the reference data which is attached to this report in Appendix A.

Equipment Class	Reference FCC ID & IC	Reference Report	Report Title/Section
DTS	BCG-E3545A 579C-E3545A	13259315-E2V1	FCC IC_BLE Report / All sections

6.5. DESCRIPTION OF AVAILABLE ANTENNAS

Frequency Range (GHz)	ANT 4 (dBi)	ANT 3 (dBi)
2.4	-1.9	0.4

6.6. SOFTWARE AND FIRMWARE

The EUT firmware installed during testing was 18.1.148.558

6.7. WORST-CASE CONFIGURATION AND MODE

Radiated band edge and spurious emissions from 1GHz to 18GHz were performed based on the Model A2341 worst case with the EUT set at highest power at Low/Middle/High channels.

There are two vendors of the WiFi/Bluetooth radio modules: variant 1 and variant 2. The Wi-Fi/Bluetooth radio modules have the same mechanical outline (e.g., the same package dimension and pin-out layout), use the same on-board antenna matching circuit, have an identical antenna structure, and are built and tested to conform to the same specifications and to operate within the same tolerances.

Baseline testing was performed on the two variants to determine the worst case on all conducted power and radiated emissions.


6.8. DESCRIPTION OF TEST SETUP

SUPPORT TEST EQUIPMENT						
Description		Manufacturer	Model	Serial Number		FCC ID/ DoC
Laptop		Apple	A1502	HRP003436		QDS-BRCM1080
Laptop AC/DC adapter		Liteon Technology	PA-1450-BA1	B123		NA
EUT AC/DC adapter		Apple	A1385	D29325SM03XDHLHC9		NA
I/O CABLES (RF RADIATED TEST)						
Cable No.	Port	# of Identical Ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	AC	1	AC	Un-shielded	2	N/A
2	USB	1	USB	Un-shielded	1	N/A

TEST SETUP

The EUT is connected to a test laptop during the tests. Test software exercised the radio card.

SETUP DIAGRAM FOR RADIATED TESTS Above 1 GHz



7. MEASUREMENT METHOD

Output Power: ANSI C63.10 Subclause -11.9.1.3 Method PKPM1 Peak-reading power meter

Output Power: ANSI C63.10 Subclause -11.9.2.3.2 Measurement using gated average power meter.

Radiated emissions restricted frequency bands: ANSI C63.10 Subclause -11.12.1 & Clause 13

Band-edge: ANSI C63.10 Subclause -11.13.3.3 & Clause 13: Integration method -Trace averaging with continuous transmission at full power

Radiated emissions non-restricted frequency bands ANSI C63.10 Subclause -11.11 & Clause 13

NOTE: All conducted antenna port tests for Beamforming applied the same test procedures as BLE 1Mbps and BLE 2Mbps normal modes.

8. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment were utilized for the tests documented in this report:

TEST EQUIPMENT LIST					
Description	Manufacturer	Model	ID Num	Cal Due	Last Cal
Antenna, Horn 1-18GHz	ETS-Lindgren	3117	T344	05/26/2021	05/26/2020
Amplifier, 1 to 18GHz, 35dB	Amplicial	AFS42-00101800-25-S-42	T1568	04/14/2021	04/14/2020
EMI TEST RECEIVER	Rohde & Schwarz	ESW44	PRE0180917	02/26/2021	02/26/2020
Power Meter, P-series single channel	Keysight	N1911A	PRE0177682	01/21/2021	01/21/2020
Power Sensor	Keysight	N1921A	T1226	02/13/2021	02/13/2020

UL AUTOMATION SOFTWARE			
Radiated Software	UL	UL EMC	Ver 9.5, Mar 6, 2020

9. SETUP PHOTOS

Please refer to 13259315-EP1 for setup photos

END OF TEST REPORT

Appendix A – Reference Test Report

Attached is the test report (13259315-E2) containing the reference data from the parent model as detailed in section 6.4.



TEST REPORT

Report Number. : 13259315-E2V3

Applicant : APPLE INC.
1 APPLE PARK WAY
CUPERTINO, CA 95014, U.S.A

Model : A2341

FCC ID : BCG-E3545A

IC : 579C-E3545A

EUT Description : SMARTPHONE

Test Standard(s) : FCC 47 CFR PART 15 SUBPART C
ISED RSS-247 ISSUE 2
ISED RSS-GEN ISSUE 5

Date Of Issue:
September 21, 2020

Prepared by:
UL Verification Services Inc.
47173 Benicia Street
Fremont, CA 94538 U.S.A.
TEL: (510) 319-4000
FAX: (510) 661-0888



REPORT REVISION HISTORY

Rev.	Issue Date	Revisions	Revised By
V1	8/26/2020	Initial Issue	Chin Pang
V2	9/18/2020	Address TCB's Questions	Chin Pang
V3	9/21/2020	Address TCB's Questions	Chin Pang

TABLE OF CONTENTS

REPORT REVISION HISTORY	2
TABLE OF CONTENTS	3
1. ATTESTATION OF TEST RESULTS	6
2. TEST RESULTS SUMMARY	7
3. TEST METHODOLOGY	7
4. FACILITIES AND ACCREDITATION	7
5. DECISION RULES AND MEASUREMENT UNCERTAINTY	8
5.1. METROLOGICAL TRACEABILITY	8
5.2. DECISION RULES.....	8
5.3. MEASUREMENT UNCERTAINTY.....	8
6. EQUIPMENT UNDER TEST	9
6.1. EUT DESCRIPTION	9
6.2. MAXIMUM OUTPUT POWER.....	9
6.3. DESCRIPTION OF AVAILABLE ANTENNAS	9
6.4. SOFTWARE AND FIRMWARE.....	9
6.5. WORST-CASE CONFIGURATION AND MODE	10
6.6. DESCRIPTION OF TEST SETUP.....	11
7. MEASUREMENT METHOD.....	16
8. TEST AND MEASUREMENT EQUIPMENT	17
9. ANTENNA PORT TEST RESULTS	18
9.1. ON TIME AND DUTY CYCLE.....	18
9.2. 99% BANDWIDTH.....	20
9.2.1. HIGH POWER BLE (1Mbps).....	21
9.2.2. HIGH POWER BLE (2Mbps).....	22
9.2.3. HIGH POWER BLE TXBF (1Mbps).....	23
9.2.4. HIGH POWER BLE TXBF (2Mbps).....	24
9.3. 6 dB BANDWIDTH.....	25
9.3.1. HIGH POWER BLE (1Mbps).....	26
9.4. OUTPUT POWER.....	27
9.4.1. HIGH POWER BLE (1Mbps).....	28
9.4.2. HIGH POWER BLE (2Mbps).....	28
9.4.3. LOW POWER BLE (1Mbps)	29

9.4.4.	LOW POWER BLE (2Mbps)	29
9.4.5.	HIGH POWER BLE TXBF (1Mbps)	30
9.4.6.	HIGH POWER BLE TXBF (2Mbps)	30
9.4.7.	LOW POWER BLE TXBF (1Mbps)	30
9.4.8.	LOW POWER BLE TXBF (2Mbps)	30
9.5.	AVERAGE POWER	31
9.5.1.	HIGH POWER BLE (1Mbps)	32
9.5.2.	HIGH POWER BLE (2Mbps)	32
9.5.3.	LOW POWER BLE (1Mbps)	33
9.5.4.	LOW POWER BLE (2Mbps)	33
9.5.5.	HIGH POWER BLE TXBF (1Mbps)	34
9.5.6.	HIGH POWER BLE TXBF (2Mbps)	34
9.5.7.	LOW POWER BLE TXBF (1Mbps)	34
9.5.8.	LOW POWER BLE TXBF (2Mbps)	34
9.6.	POWER SPECTRAL DENSITY	35
9.6.1.	HIGH POWER BLE (1Mbps)	36
9.6.2.	HIGH POWER BLE (2Mbps)	37
9.6.3.	LOW POWER BLE (1Mbps)	38
9.6.4.	LOW POWER BLE (2Mbps)	39
9.6.5.	HIGH POWER BLE TXBF (1Mbps)	40
9.6.6.	HIGH POWER BLE TXBF (2Mbps)	41
9.6.7.	LOW POWER BLE TXBF (1Mbps)	42
9.6.8.	LOW POWER BLE TXBF (2Mbps)	43
9.7.	CONDUCTED SPURIOUS EMISSIONS	44
9.7.1.	HIGH POWER BLE (1Mbps)	45
9.7.2.	HIGH POWER BLE (2Mbps)	47
9.7.3.	LOW POWER BLE (1Mbps)	49
9.7.4.	LOW POWER BLE (2Mbps)	51
9.7.5.	HIGH POWER BLE TXBF (1Mbps)	53
9.7.6.	HIGH POWER BLE TXBF (2Mbps)	55
9.7.7.	LOW POWER BLE TXBF (1Mbps)	57
9.7.8.	LOW POWER BLE TXBF (2Mbps)	59
10.	RADIATED TEST RESULTS	61
10.1.	LIMITS AND PROCEDURE	61
10.2.	TRANSMITTER ABOVE 1 GHz	63
10.2.1.	HIGH POWER BLE (1Mbps)	63
10.2.2.	HIGH POWER BLE (2Mbps)	71
10.2.3.	LOW POWER BLE (1Mbps)	79
10.2.4.	LOW POWER BLE (2Mbps)	87
10.2.5.	HIGH POWER BLE TXBF (1Mbps)	95
10.2.6.	HIGH POWER BLE TXBF (2Mbps)	99
10.2.7.	LOW POWER BLE TXBF (1Mbps)	103
10.2.8.	LOW POWER BLE TXBF (2Mbps)	107
10.2.9.	HIGH POWER HARMONICS AND SPURIOUS EMISSIONS TXBF BLE (1Mbps)	111
10.3.	WORST CASE BELOW 1 GHz	117

10.4.	WORST CASE 18-26 GHz	119
11.	AC POWER LINE CONDUCTED EMISSIONS	121
11.1.	AC POWER LINE WITH AC/DC ADAPTER	122
11.2.	AC LINE WITH LAPTOP	124
12.	SETUP PHOTOS	126

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: APPLE INC.
1 APPLE PARK WAY
CUPERTINO, CA 95014, U.S.A

EUT DESCRIPTION: SMARTPHONE

MODEL: A2341

SERIAL NUMBER: G6TCP01UQ5R9, G6TCM020Q5T6

DATE TESTED: FEBRUARY 18, 2020 – AUGUST 14, 2020

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Complies
ISED RSS-247 Issue 2	Complies
ISED RSS-GEN Issue 5	Complies

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. All samples tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise.


This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of the U.S. government.

Approved & Released For
UL Verification Services Inc. By:



Chin Pang
Senior Engineer
Consumer Technology Division
UL Verification Services Inc.

Prepared By:



Jingang Li
Test Engineer
Consumer Technology Division
UL Verification Services Inc.

2. TEST RESULTS SUMMARY

FCC Clause	ISED Clause	Requirement	Result	Comment
See Comment		Duty Cycle	Reporting purposes only	ANSI C63.10 Section 11.6.
-	RSS-GEN 6.7	99% OBW	Reporting purposes only	ANSI C63.10 Section 6.9.3.
15.247 (a) (2)	RSS-247 5.2 (a)	6dB BW	complies	None.
15.247 (b) (3)	RSS-247 5.4 (d)	Output Power	complies	None.
See Comment		Average power	Reporting purposes only	Per ANSI C63.10, Section 11.9.2.3.2.
15.247 (e)	RSS-247 5.2 (b)	PSD	complies	None.
15.247 (d)	RSS-247 5.5	Conducted Spurious Emissions	complies	None.
15.209, 15.205	RSS-GEN 8.9, 8.10	Radiated Emissions	complies	None.
15.207	RSS-Gen 8.8	AC Mains Conducted Emissions	complies	None.

3. TEST METHODOLOGY

The tests documented in this report were performed in accordance with FCC CFR 47 Part 2, FCC CFR 47 Part 15, ANSI C63.10-2013, KDB 558074 D01 15.247 Meas Guidance v05r02, KDB 662911, RSS-GEN Issue 5, and RSS-247 Issue 2.

4. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 and 47266 Benicia Street, and 47658 Kato Road, Fremont, California, USA. Line conducted emissions are measured only at the 47173 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

47173 Benicia Street	47266 Benicia Street	47658 Kato Rd.
☐ Chamber A (IC:2324B-1)	☐ Chamber D (IC:22541-1)	☒ Chamber I (IC: 2324A-5)
☐ Chamber B (IC:2324B-2)	☒ Chamber E (IC:22541-2)	☒ Chamber J (IC: 2324A-6)
☐ Chamber C (IC:2324B-3)	☐ Chamber F (IC:22541-3)	☐ Chamber K (IC: 2324A-1)
	☐ Chamber G (IC:22541-4)	☐ Chamber L (IC: 2324A-3)
	☐ Chamber H (IC:22541-5)	☐ Chamber M (IC: 2324A-2)

The above test sites and facilities are covered under FCC Test Firm Registration # 208313. Chambers above are covered under Industry Canada company address and respective code.

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0

5. DECISION RULES AND MEASUREMENT UNCERTAINTY

5.1. METROLOGICAL TRACEABILITY

All test and measuring equipment utilized to perform the tests documented in this report are calibrated on a regular basis, with a maximum time between calibrations of one year or the manufacturers' recommendation, whichever is less, and where applicable is traceable to recognized national standards.

5.2. DECISION RULES

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4:2012 Clause 8.2. (Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

5.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	U _{Lab}
Worst Case Conducted Disturbance, 9KHz to 0.15 MHz	3.39 dB
Worst Case Conducted Disturbance, 0.15 to 30 MHz	3.07 dB
Worst Case Radiated Disturbance, 9KHz to 30 MHz	2.52 dB
Worst Case Radiated Disturbance, 30 to 1000 MHz	4.88 dB
Worst Case Radiated Disturbance, 1000 to 18000 MHz	4.24 dB
Worst Case Radiated Disturbance, 18000 to 26000 MHz	4.37 dB
Worst Case Radiated Disturbance, 26000 to 40000 MHz	5.17 dB

Uncertainty figures are valid to a confidence level of 95%.

6. EQUIPMENT UNDER TEST

6.1. EUT DESCRIPTION

The Apple iPhone is a smartphone with multimedia functions (music, application support, and video), cellular GSM, GPRS, EGPRS, UMTS, LTE, 5G, CDMA, IEEE 802.11a/b/g/n/ac/ax, Bluetooth, Ultra-Wideband, GPS, NFC and WPT. All models support at least one UICC based SIM. The second SIM is either an UICC based p-SIM (physical SIM) or e-SIM (electronic SIM). The device supports a built-in inductive charging transmitter and receiver. The rechargeable battery is not user accessible.

6.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak conducted output power as follows:

Antenna	Configuration	Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
ANT 4	High Power	2402 - 2480	BLE 1M	20.27	106.41
	Low Power			12.79	19.01
	High Power	2404 - 2478	BLE 2M	20.22	105.20
	Low Power			12.72	18.71
ANT 3	High Power	2402 - 2480	BLE 1M	20.25	105.93
	Low Power			12.79	19.01
	High Power	2404 - 2478	BLE 2M	20.19	104.47
	Low Power			12.85	19.28
BF, ANT 4 + ANT 3	High Power	2402 - 2480	BLE 1M	20.15	103.51
	Low Power			15.88	38.73
	High Power	2404 - 2478	BLE 2M	20.19	104.47
	Low Power			15.92	39.08

6.3. DESCRIPTION OF AVAILABLE ANTENNAS

Frequency Range (GHz)	ANT 4 (dBi)	ANT 3 (dBi)
2.4	-1.9	0.4

6.4. SOFTWARE AND FIRMWARE

The EUT firmware installed during testing was 18.1.148.558

6.5. WORST-CASE CONFIGURATION AND MODE

The EUT was investigated in three orthogonal orientations X (Flatbed), Y (Landscape) and Z (Portrait) on ANT 4 (Core 0), ANT 3 (Core 1) and 2TX beamforming (ANT4 + ANT 3). It was determined that X orientation was the worst-case for ANT 4 and MIMO and Z (Portrait) was the worst-case orientation for ANT 3.

Radiated band edge and harmonic and spurious emissions from 1GHz to 18GHz were performed with the EUT set to transmit at highest power on Low/Middle/High channels.

Radiated emissions below 1GHz, 18-26GHz and AC power line conducted emissions were performed with the EUT transmitting at the channel with the highest output power as worst-case scenario. There were no emissions found below 30MHz within 20dB of the limit

For below 1GHz, tests were performed with EUT connected to AC power adapter as the worst case and for above 1GHz, tests were performed with EUT only.. For AC power line conducted emission, tests were investigated with AC power adapter and with laptop.

For simultaneous transmission of multiple channels in the 2.4GHz BLE and 5GHz bands. No noticeable emission was found.

There are two vendors of the WiFi/Bluetooth radio modules: variant 1 and variant 2. The Wi-Fi/Bluetooth radio modules have the same mechanical outline (e.g., the same package dimension and pin-out layout), use the same on-board antenna matching circuit, have an identical antenna structure, and are built and tested to conform to the same specifications and to operate within the same tolerances.

Baseline testing was performed on the two variants to determine the worst case on all conducted power and radiated emissions.


6.6. DESCRIPTION OF TEST SETUP

SUPPORT TEST EQUIPMENT						
Description		Manufacturer	Model	Serial Number		FCC ID/ DoC
Laptop		Apple	Apple	A1989		C02YL3ZMJHC8
Laptop AC/DC adapter		Liteon Technology	Liteon Technology	A1718		C4N711404U3GN8RAW
EUT AC/DC adapter		Apple	Apple	A2305		C4H951700S7PF4F4F
I/O CABLES (RF CONDUCTED TEST)						
Cable No.	Port	# of Identical Ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	Antenna	1	SMA	Un-shielded	0.2	To spectrum Analyzer
2	USB	1	USB	Shielded	1.0	N/A
3	AC	1	AC	Un-shielded	2	N/A
I/O CABLES (RF RADIATED TEST)						
Cable No.	Port	# of Identical Ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	AC	1	AC	Un-shielded	2	N/A
2	USB	1	USB	Un-shielded	1	N/A


TEST SETUP

The EUT is connected to a test laptop during the tests. Test software exercised the radio card.


SETUP DIAGRAM FOR CONDUCTED TESTS




SETUP DIAGRAM FOR RADIATED TESTS Above 1GHz



SETUP DIAGRAM FOR Below 1GHz and AC LINE CONDUCTED TEST



TEST SETUP- AC LINE CONDUCTED: LAPTOP CONFIGURATION



7. MEASUREMENT METHOD

On Time and Duty Cycle: KDB 558074 D01 v05r02, Section 6.

6 dB BW: ANSI C63.10 Subclause -11.8.1 RBW $\geq$ DTS BW

Occupied BW (99%): ANSI C63.10-2013 Subclause 6.9.3

Output Power: ANSI C63.10 Subclause -11.9.1.3 Method PKPM1 Peak-reading power meter

Output Power: ANSI C63.10 Subclause -11.9.2.3.2 Measurement using gated average power meter.

PSD: ANSI C63.10 Subclause -11.10.2 Method PKPSD (peak PSD)

Radiated emissions non-restricted frequency bands: ANSI C63.10 Subclause -11.11 & Clause 13

Radiated emissions restricted frequency bands: ANSI C63.10 Subclause -11.12.1 & Clause 13

Conducted emissions in restricted frequency bands: ANSI C63.10 Subclause -11.12.2

Band-edge: ANSI C63.10 Subclause -11.13.3.2 & Clause 13 Integration method -Peak detection

Band-edge: ANSI C63.10 Subclause -11.13.3.3 & Clause 13 Integration method -Trace averaging with continuous transmission at full power

AC Power Line Conducted Emissions: ANSI C63.10-2013, Clause 6.2.

Radiated emissions non-restricted frequency bands ANSI C63.10 Subclause -11.11 & Clause 13

Radiated Spurious Emissions Below 30MHz: ANSI C63.10-2013 Clause 6.4 & Clause 13

NOTE: Test procedures and settings for BLE beamforming mode are the same as BLE normal mode.

8. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

TEST EQUIPMENT LIST					
Description	Manufacturer	Model	ID Num	Cal Due	Last Cal
*Antenna, Horn 1-18GHz	ETS Lindgren	3117	T862	08/20/2020	08/20/2019
RF Amplifier, 1-18GHz	MITEQ	AFS42-00101800-25-S-42	171460	08/24/2020	08/24/2019
EMI Test Receiver	Rohde & Schwarz	ESW44	Pre0179522	02/20/2021	02/20/2020
Antenna, Horn 1-18GHz	ETS-Lindgren	3117	T712	03/09/2021	03/09/2020
Amplifier, 1 to 18GHz	Ampical	AMP1G18-35	138301	01/14/2021	01/14/2020
Antenna, Double Ridge Guide Horn Antenna	A.H. Systems, Inc.	SAS-571	T963	01/25/2021	01/25/2020
Amplifier, 1 to 18GHz, 35dB	AMPLICAL	AMP1G18-35	T1569	01/30/2021	01/30/2020
Antenna, Horn 1-18GHz	ETS-Lindgren	3117	T712	03/09/2021	03/09/2020
Amplifier, 1 to 18GHz	Ampical	AMP1G18-35	138301	01/14/2021	01/14/2020
Spectrum Analyzer, PXA, 3Hz to 44GHz	Keysight Technologies Inc	N9030A-544	T1210	01/22/2021	01/22/2020
Spectrum Analyzer, PXA, 3Hz to 44GHz	Keysight Technologies Inc	N9030A	T1466	01/23/2021	01/23/2020
Spectrum Analyzer, PXA 3Hz to 44GHz	Keysight	N9030A	T917	01/21/2021	01/21/2020
Spectrum Analyzer, PXA 3Hz to 44GHz	Keysight	N9030A	T1466	01/23/2021	01/23/2020
*Antenna, Broadband Hybrid, 30-2000MHz	Sunol Sciences	JB1	T130	08/09/2020	08/09/2019
*Amplifier, 10KHz to 1GHz, 32dB	Sonoma	310N	T173	06/06/2020	06/06/2019
Antenna Horn, 18 to 26GHz	ARA	SWH-28	T125	04/17/2021	04/17/2020
Pre-Amp 18-26GHz	Agilent Technology	8449B	T404	04/08/2021	04/08/2020
Antenna Horn, 18 to 26GHz	ARA	SWH-28	T125	04/17/2021	04/17/2020
Pre-Amp 18-26GHz	Agilent Technology	8449B	T404	04/08/2021	04/08/2020
Spectrum Analyzer, PXA, 3Hz to 44GHz	Agilent (Keysight) Technologies	N9030A	T1454	01/23/2021	01/23/2020
Power Meter, P-series single channel	Keysight	N1911A	PRE0177682	01/21/2021	01/21/2020
Power Sensor	Keysight	N1921A	T1226	02/13/2021	02/13/2020
Antenna, Active Loop 9KHz to 30MHz	EMCO	6502	T1616	10/28/2020	10/28/2019
AC Line Conducted					
Description	Manufacturer	Model	ID Num	Cal Due	Last Cal
EMI Test Receiver 9kHz-7GHz	Rohde & Schwarz	ESR	T1436	02/20/2021	02/20/2020
Power Cable, Line Conducted Emissions	UL	PR1	T861	10/27/2020	10/27/2019
LISN for Conducted Emissions CISPR-16	FISCHER CUSTOM COMMUNICATIONS	FCC-LISN-50/250-25-2-01	PRE0186446	01/23/2021	01/23/2020
UL AUTOMATION SOFTWARE					
Radiated Software	UL	UL EMC	Ver 9.5, Mar 6, 2020		
Conducted Software	UL	UL EMC	2020.2.26		
AC Line Conducted Software	UL	UL EMC	Ver 9.5, February 21, 2020		

*Testing is completed before equipment expiration date.

9. ANTENNA PORT TEST RESULTS

9.1. ON TIME AND DUTY CYCLE

LIMITS

None; for reporting purposes only.

PROCEDURE


KDB 558074 Zero-Span Spectrum Analyzer Method.

ON TIME AND DUTY CYCLE RESULTS

Mode	ON Time B (msec)	Period (msec)	Duty Cycle x (linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/B Minimum VBW (kHz)
2.4GHz Band						
BLE, 1Mbps	1.000	1.000	1.000	100.00	0.00	0.010
BLE, 2Mbps	1.000	1.000	1.000	100.00	0.00	0.010
BLE TxBF, 1Mbps	1.000	1.000	1.000	100.00	0.00	0.010
BLE TxBF, 2Mbps	1.000	1.000	1.000	100.00	0.00	0.010

Note: Low power duty cycle is same as higher power

DUTY CYCLE PLOTS



9.2. 99% BANDWIDTH

LIMITS

None; for reporting purposes only.

RESULTS


Only High Power modes result is reported, it covers all Low Power modes. Only Mid channel plot is reported to show setting parameter complies with testing method/procedure.

ID:	44353	Date:	02/24/2020
------------	-------	--------------	------------

9.2.1. HIGH POWER BLE (1Mbps)


ANT 4

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2402	1.0413
Middle	2440	1.0516
High	2480	1.0498



ANT 3


Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2402	1.0496
Middle	2440	1.0514
High	2480	1.0510



9.2.2. HIGH POWER BLE (2Mbps)


ANT 4

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2404	1.9011
Middle	2440	1.9040
High	2478	1.9075



ANT 3



Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2404	1.9234
Middle	2440	1.9134
High	2478	1.9187



9.2.3. HIGH POWER BLE TXBF (1Mbps)


Channel	Frequency (MHz)	99% Bandwidth ANT 4 (MHz)	99% Bandwidth ANT 3 (MHz)
Low	2402	1.0496	1.0503
Mid	2440	1.0517	1.0501
High	2480	1.0502	1.0488

ID:	44353	Date:	02/24/2020
-----	-------	-------	------------



9.2.4. HIGH POWER BLE TXBF (2Mbps)

Channel	Frequency (MHz)	99% Bandwidth ANT 4 (MHz)	99% Bandwidth ANT 3 (MHz)
Low	2404	1.9341	1.9194
Mid	2440	1.9145	1.9195
High	2478	1.9237	1.9204



9.3. 6 dB BANDWIDTH

LIMITS

FCC §15.247 (a) (2)

RSS-247 5.2 (a)

The minimum 6 dB bandwidth shall be at least 500 kHz.

RESULTS


The 6dB bandwidth was measured for the narrowest bandwidth mode, High Power 1Mbps, to demonstrate compliance with the minimum required bandwidth of 500 kHz. Other modes were not tested as their bandwidth is greater than the High Power 1Mbps mode, as demonstrated by the 99% bandwidth measurements performed on all modes.

Only Mid channel plot is reported to show setting parameter complies with testing method/procedure.

9.3.1. HIGH POWER BLE (1Mbps)


ANT 4

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2402	0.6810	0.5
Middle	2440	0.6510	0.5
High	2480	0.6720	0.5



ANT 3

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2402	0.7020	0.5
Middle	2440	0.7050	0.5
High	2480	0.6820	0.5



9.4. OUTPUT POWER

LIMITS

FCC §15.247 (b) (3)

RSS-247 5.4 (d)

The maximum antenna gain is less than or equal to 6 dBi, therefore the limit is 30 dBm.

TEST PROCEDURE

The transmitter output is connected to a power meter with wideband power sensor..

The cable assembly insertion loss of 10.5 dB (including 10 dB pad and 0.5 dB cable) was entered as an offset in the power meter to allow for peak reading of power.

DIRECTIONAL ANTENNA GAIN

For 1 TX:

There is only one transmitter output therefore the directional gain is equal to the antenna gain.

For 2 TX:

Tx chains are correlated for power due to the device supporting Beamforming. The directional gains are as follows:

Band (GHz)	ANT 4 Antenna Gain (dBi)	ANT 3 Antenna Gain (dBi)	Uncorrelated Chains Directional Gain (dBi)	Correlated Chains Directional Gain (dBi)
2.4	-1.90	0.40	-0.60	2.34

RESULTS

9.4.1. HIGH POWER BLE (1Mbps)

ANT 4

Tested By:	20773
Date:	7/27/2020

Channel	Frequency (MHz)	Peak Power Reading (dBm)	Limit (dBm)	Margin (dB)
Low	2402	20.22	30	-9.78
Middle	2440	20.27	30	-9.73
High	2480	20.23	30	-9.77

ANT 3

Tested By:	20773
Date:	7/27/2020

Channel	Frequency (MHz)	Peak Power Reading (dBm)	Limit (dBm)	Margin (dB)
Low	2402	20.20	30	-9.80
Middle	2440	20.25	30	-9.75
High	2480	20.22	30	-9.78

9.4.2. HIGH POWER BLE (2Mbps)

ANT 4

Tested By:	20773
Date:	7/27/2020

Channel	Frequency (MHz)	Peak Power Reading (dBm)	Limit (dBm)	Margin (dB)
Low	2404	20.15	30	-9.85
Middle	2440	20.22	30	-9.78
High	2478	20.18	30	-9.82

ANT 3

Tested By:	20773
Date:	7/27/2020

Channel	Frequency (MHz)	Peak Power Reading (dBm)	Limit (dBm)	Margin (dB)
Low	2404	20.14	30	-9.86
Middle	2440	20.19	30	-9.81
High	2478	20.12	30	-9.88

9.4.3. LOW POWER BLE (1Mbps)

ANT 4

Tested By:	20773
Date:	7/27/2020

Channel	Frequency (MHz)	Peak Power Reading (dBm)	Limit (dBm)	Margin (dB)
Low	2402	12.75	30	-17.25
Middle	2440	12.77	30	-17.23
High	2480	12.79	30	-17.21

ANT 3

Tested By:	20773
Date:	7/27/2020

Channel	Frequency (MHz)	Peak Power Reading (dBm)	Limit (dBm)	Margin (dB)
Low	2402	12.62	30	-17.38
Middle	2440	12.79	30	-17.21
High	2480	12.69	30	-17.31

9.4.4. LOW POWER BLE (2Mbps)

ANT 4

Tested By:	20773
Date:	7/27/2020

Channel	Frequency (MHz)	Peak Power Reading (dBm)	Limit (dBm)	Margin (dB)
Low	2404	12.69	30	-17.31
Middle	2440	12.72	30	-17.28
High	2478	12.62	30	-17.38

ANT 3

Tested By:	20773
Date:	7/27/2020

Channel	Frequency (MHz)	Peak Power Reading (dBm)	Limit (dBm)	Margin (dB)
Low	2404	12.71	30	-17.29
Middle	2440	12.85	30	-17.15
High	2478	12.79	30	-17.21

9.4.5. HIGH POWER BLE TXBF (1Mbps)

ANT 4 + ANT 3

Tested By:	20773
Date:	7/27/2020

Channel	Frequency (MHz)	Output Power ANT 4 (dBm)	Output Power ANT 3 (dBm)	Total Power (dBm)	Limit (dBm)	Margin (dB)
Low	2402	17.10	17.14	20.13	30	-9.87
Middle	2440	17.08	17.20	20.15	30	-9.85
High	2480	17.10	17.12	20.12	30	-9.88

9.4.6. HIGH POWER BLE TXBF (2Mbps)

ANT 4 + ANT 3

Tested By:	20773
Date:	7/27/2020

Channel	Frequency (MHz)	Output Power ANT 4 (dBm)	Output Power ANT 3 (dBm)	Total Power (dBm)	Limit (dBm)	Margin (dB)
Low	2404	17.10	17.07	20.10	30	-9.90
Middle	2440	17.19	17.16	20.19	30	-9.81
High	2478	17.05	17.08	20.08	30	-9.92

9.4.7. LOW POWER BLE TXBF (1Mbps)

ANT 4 + ANT 3

Tested By:	20773
Date:	7/27/2020

Channel	Frequency (MHz)	Output Power ANT 4 (dBm)	Output Power ANT 3 (dBm)	Total Power (dBm)	Limit (dBm)	Margin (dB)
Low	2402	12.73	12.78	15.77	30	-14.23
Middle	2440	12.89	12.85	15.88	30	-14.12
High	2480	12.82	12.86	15.85	30	-14.15

9.4.8. LOW POWER BLE TXBF (2Mbps)

ANT 4 + ANT 3

Tested By:	20773
Date:	7/27/2020

Channel	Frequency (MHz)	Output Power ANT 4 (dBm)	Output Power ANT 3 (dBm)	Total Power (dBm)	Limit (dBm)	Margin (dB)
Low	2404	12.85	12.88	15.88	30	-14.12
Middle	2440	12.90	12.92	15.92	30	-14.08
High	2478	12.77	12.76	15.78	30	-14.22

9.5. AVERAGE POWER

LIMITS

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to a power meter with wideband power sensor.

The cable assembly insertion loss of 10.5 dB (including 10 dB pad and 0.5 dB cable) was entered as an offset in the power meter to allow for a gated average reading of power.

RESULTS

9.5.1. HIGH POWER BLE (1Mbps)

ANT 4

Tested By:	20773
Date:	7/25/2020

Channel	Frequency (MHz)	AV power (dBm)
Low	2402	19.76
Middle	2440	19.86
High	2480	19.83

ANT 3

Tested By:	20773
Date:	7/25/2020

Channel	Frequency (MHz)	AV power (dBm)
Low	2402	19.71
Middle	2440	19.91
High	2480	19.86

9.5.2. HIGH POWER BLE (2Mbps)

ANT 4

Tested By:	20773
Date:	7/25/2020

Channel	Frequency (MHz)	AV power (dBm)
Low	2404	19.68
Middle	2440	19.86
High	2478	19.80

ANT 3

Tested By:	20773
Date:	7/25/2020

Channel	Frequency (MHz)	AV power (dBm)
Low	2404	19.76
Middle	2440	19.89
High	2478	19.79

9.5.3. LOW POWER BLE (1Mbps)

ANT 4

Tested By:	20773
Date:	7/25/2020

Channel	Frequency (MHz)	AV power (dBm)
Low	2402	12.25
Middle	2440	12.33
High	2480	12.37

ANT 3

Tested By:	20773
Date:	7/25/2020

Channel	Frequency (MHz)	AV power (dBm)
Low	2402	12.20
Middle	2440	12.38
High	2480	12.29

9.5.4. LOW POWER BLE (2Mbps)

ANT 4

Tested By:	20773
Date:	7/25/2020

Channel	Frequency (MHz)	AV power (dBm)
Low	2404	12.19
Middle	2440	12.32
High	2478	12.26

ANT 3

Tested By:	20773
Date:	7/25/2020

Channel	Frequency (MHz)	AV power (dBm)
Low	2404	12.30
Middle	2440	12.41
High	2478	12.39

9.5.5. HIGH POWER BLE TXBF (1Mbps)

ANT 4 + ANT 3

Tested By:	20773
Date:	7/25/2020

Channel	Frequency (MHz)	Average Power ANT 4 (dBm)	Average Power ANT 3 (dBm)	Total Power (dBm)
Low	2402	17.21	17.23	20.23
Middle	2440	17.39	17.41	20.41
High	2480	17.19	17.32	20.27

9.5.6. HIGH POWER BLE TXBF (2Mbps)

ANT 4 + ANT 3

Tested By:	20773
Date:	7/25/2020

Channel	Frequency (MHz)	Average Power ANT 4 (dBm)	Average Power ANT 3 (dBm)	Total Power (dBm)
Low	2402	17.14	17.31	20.24
Middle	2440	17.23	17.29	20.27
High	2480	17.29	17.16	20.24

9.5.7. LOW POWER BLE TXBF (1Mbps)

ANT 4 + ANT 3

Tested By:	20773
Date:	7/25/2020

Channel	Frequency (MHz)	Average Power ANT 4 (dBm)	Average Power ANT 3 (dBm)	Total Power (dBm)
Low	2402	12.31	12.24	15.29
Middle	2440	12.40	12.39	15.41
High	2480	12.37	12.42	15.41

9.5.8. LOW POWER BLE TXBF (2Mbps)

ANT 4 + ANT 3

Tested By:	20773
Date:	7/25/2020

Channel	Frequency (MHz)	Average Power ANT 4 (dBm)	Average Power ANT 3 (dBm)	Total Power (dBm)
Low	2402	12.31	12.39	15.36
Middle	2440	12.39	12.42	15.42
High	2480	12.28	12.36	15.33

9.6. POWER SPECTRAL DENSITY

LIMITS

FCC §15.247 (e)

RSS-247 (5.2) (b)

The power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.


RESULTS

Only Mid channel plot is reported to show setting parameter complies with testing method/procedure.

9.6.1. HIGH POWER BLE (1Mbps)


ANT 4

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Margin (dB)
Low	2402	2.864	8	-5.14
Middle	2440	2.994	8	-5.01
High	2480	3.091	8	-4.91



ANT 3:


Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Margin (dB)
Low	2402	3.267	8	-4.73
Middle	2440	3.070	8	-4.93
High	2480	3.054	8	-4.95



9.6.2. HIGH POWER BLE (2Mbps)


ANT 4

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Margin (dB)
Low	2404	-2.117	8	-10.12
Middle	2440	-2.038	8	-10.04
High	2478	-2.153	8	-10.15



ANT 3


Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Margin (dB)
Low	2402	-1.942	8	-9.94
Middle	2440	-1.917	8	-9.92
High	2480	-2.120	8	-10.12



9.6.3. LOW POWER BLE (1Mbps)


ANT 4

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Margin (dB)
Low	2402	-4.668	8	-12.67
Middle	2440	-4.482	8	-12.48
High	2480	-1.850	8	-9.85



ANT 3


Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Margin (dB)
Low	2402	-4.691	8	-12.69
Middle	2440	-4.538	8	-12.54
High	2480	-4.304	8	-12.30



9.6.4. LOW POWER BLE (2Mbps)


ANT 4

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Margin (dB)
Low	2404	-9.850	8	-17.85
Middle	2440	-9.764	8	-17.76
High	2478	-10.891	8	-18.89



ANT 3

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Margin (dB)
Low	2404	-9.807	8	-17.81
Middle	2440	-9.712	8	-17.71
High	2478	-9.745	8	-17.75




9.6.5. HIGH POWER BLE TXBF (1Mbps)


Duty Cycle CF (dB)	0.00	Included in Calculations of Corr'd PSD
--------------------	------	--

PSD Results

Channel	Frequency (MHz)	ANT 4 Meas (dBm/ 3kHz)	ANT 3 Meas (dBm/ 3kHz)	Total Corr'd PSD (dBm/ 3kHz)	Limit (dBm/ 3kHz)	Margin (dB)
Low	2402	0.255	0.130	3.20	8.0	-4.80
Mid	2440	0.572	0.420	3.51	8.0	-4.49
Hjigh	2480	0.266	0.594	3.44	8.0	-4.56



MID CHANNEL ANT 4




MID CHANNEL ANT 3

9.6.6. HIGH POWER BLE TXBF (2Mbps)


Duty Cycle CF (dB)	0.00	Included in Calculations of Corr'd PSD
--------------------	------	--

PSD Results

Channel	Frequency (MHz)	ANT 4 Meas (dBm/ 3kHz)	ANT 3 Meas (dBm/ 3kHz)	Total Corr'd PSD (dBm/ 3kHz)	Limit (dBm/ 3kHz)	Margin (dB)
Low	2404	-5.030	-4.996	-2.00	8.0	-10.00
Mid	2440	-5.097	-5.177	-2.13	8.0	-10.13
Hjigh	2478	-4.950	-5.219	-2.07	8.0	-10.07



MID CHANNEL ANT 4




MID CHANNEL ANT 3

9.6.7. LOW POWER BLE TXBF (1Mbps)


Duty Cycle CF (dB)	0.00	Included in Calculations of Corr'd PSD
--------------------	------	--

PSD Results

Channel	Frequency (MHz)	ANT 4 Meas (dBm/ 3kHz)	ANT 3 Meas (dBm/ 3kHz)	Total Corr'd PSD (dBm/ 3kHz)	Limit (dBm/ 3kHz)	Margin (dB)
Low	2402	-4.406	-4.662	-1.52	8.0	-9.52
Mid	2440	-4.415	-4.576	-1.48	8.0	-9.48
Hjigh	2480	-2.156	-4.624	-0.21	8.0	-8.21



MID CHANNEL ANT 4




MID CHANNEL ANT 3

9.6.8. LOW POWER BLE TXBF (2Mbps)


Duty Cycle CF (dB)	0.00	Included in Calculations of Corr'd PSD
--------------------	------	--

PSD Results

Channel	Frequency (MHz)	ANT 4 Meas (dBm/ 3kHz)	ANT 3 Meas (dBm/ 3kHz)	Total Corr'd PSD (dBm/ 3kHz)	Limit (dBm/ 3kHz)	Margin (dB)
Low	2404	-9.851	-10.053	-6.94	8.0	-14.94
Mid	2440	-10.047	-9.863	-6.94	8.0	-14.94
Hjigh	2478	-10.988	-8.532	-6.58	8.0	-14.58



MID CHANNEL ANT 4



MID CHANNEL ANT 3

9.7. CONDUCTED SPURIOUS EMISSIONS

LIMITS

FCC §15.247 (d)


RSS-247 5.5

Output power was measured based on the use of a peak measurement, therefore the required attenuation is 20 dB.


RESULTS

9.7.1. HIGH POWER BLE (1Mbps)


ANT 4




ANT 3




LOW CHANNEL BANDEDGE




OUT-OF-BAND LOW CHANNEL




MID CHANNEL REFERENCE LEVEL



OUT-OF-BAND MID CHANNEL




HIGH CHANNEL BANDEDGE




OUT-OF-BAND HIGH CHANNEL

9.7.2. HIGH POWER BLE (2Mbps)

ANT 4




ANT 3




9.7.3. LOW POWER BLE (1Mbps)


ANT 4




LOW CHANNEL BANDEDGE




OUT-OF-BAND LOW CHANNEL




MID CHANNEL REFERENCE LEVEL



OUT-OF-BAND MID CHANNEL




HIGH CHANNEL BANDEDGE




OUT-OF-BAND HIGH CHANNEL


ANT 3




LOW CHANNEL BANDEDGE



OUT-OF-BAND LOW CHANNEL




MID CHANNEL REFERENCE LEVEL



OUT-OF-BAND MID CHANNEL




HIGH CHANNEL BANDEDGE




OUT-OF-BAND HIGH CHANNEL

9.7.4. LOW POWER BLE (2Mbps) ANT 4




LOW CHANNEL BANDEDGE




OUT-OF-BAND LOW CHANNEL




MID CHANNEL REFERENCE LEVEL



OUT-OF-BAND MID CHANNEL



HIGH CHANNEL BANDEDGE



OUT-OF-BAND HIGH CHANNEL

The figure displays four screenshots of a Keysight Spectrum Analyzer, each showing a different channel condition. The analyzer is set to a center frequency of 2.40000000 GHz, a resolution bandwidth (RBW) of 300 kHz, and a span of 10.00 MHz. The reference level is 10.4 dB, and the reference offset is 10.4 dB. The sweep rate is 5.000 ms (1001 pts).

LOW CHANNEL BANDEDGE: The spectrum shows a low-level signal at the lower edge of the channel. The peak is marked at 2.403 91 GHz with a power level of 10.380 dBm. The table below shows the measured data:

Row	Mode	Freq (GHz)	Power (dBm)
1	N	2.403 91	10.380
2	N	2.400 00	42.555
3	N	2.399 99	-39.620

OUT-OF-BAND LOW CHANNEL: The spectrum shows a low-level signal at the lower edge of the channel. The peak is marked at 2.403 99 GHz with a power level of 10.533 dBm. The table below shows the measured data:

Row	Mode	Freq (GHz)	Power (dBm)
1	N	2.403 99	10.533
2	N	2.400 00	42.555
3	N	2.399 99	-39.620

MID CHANNEL REFERENCE LEVEL: The spectrum shows a mid-channel signal at the reference level. The peak is marked at 2.439 89 GHz with a power level of 10.533 dBm. The table below shows the measured data:

Row	Mode	Freq (GHz)	Power (dBm)
1	N	2.439 89	10.533
2	N	2.400 00	42.555
3	N	2.399 99	-39.620

OUT-OF-BAND MID CHANNEL: The spectrum shows a mid-channel signal at the reference level. The peak is marked at 2.439 89 GHz with a power level of 10.533 dBm. The table below shows the measured data:

Row	Mode	Freq (GHz)	Power (dBm)
1	N	2.439 89	10.533
2	N	2.400 00	42.555
3	N	2.399 99	-39.620

HIGH CHANNEL BANDEDGE: The spectrum shows a high-level signal at the upper edge of the channel. The peak is marked at 2.478 15 GHz with a power level of 10.403 dBm. The table below shows the measured data:


Row	Mode	Freq (GHz)	Power (dBm)
1	N	2.478 15	10.403
2	N	2.487 53	-39.299
3	N	2.483 00	-43.277

OUT-OF-BAND HIGH CHANNEL: The spectrum shows a high-level signal at the upper edge of the channel. The peak is marked at 2.478 15 GHz with a power level of 10.403 dBm. The table below shows the measured data:


Row	Mode	Freq (GHz)	Power (dBm)
1	N	2.478 15	10.403
2	N	2.487 53	-39.299
3	N	2.483 00	-43.277

9.7.5. HIGH POWER BLE TXBF (1Mbps)

ANT 4




ANT 3




9.7.6. HIGH POWER BLE TXBF (2Mbps)

ANT 4




ANT 3




9.7.7. LOW POWER BLE TXBF (1Mbps)

ANT 4




ANT 3



9.7.8. LOW POWER BLE TXBF (2Mbps)

ANT 4



ANT 3

