



# **TEST REPORT**

**Report Number :** 15496282-E17V6

**Applicant :** APPLE INC.  
1 APPLE PARK WAY  
CUPERTINO, CA 95014, U.S.A

**Model :** A3260 (PARENT MODEL)  
A3516, A3517, A3518 (VARIANT MODEL)

**Brand :** APPLE

**FCC ID :** BCG-E8948A (PARENT MODEL)  
BCG-E8954A. BCG-E8955A.  
BCG-E8956A (VARIANT MODEL)

**IC :** 579C-E8948A (PARENT MODEL)  
579C-E8954A, 579C-E8955A,  
579C-E8956A (VARIANT MODEL)

**EUT Description :** SMARTPHONE

**Test Standard(s) :** CONTENTION BASED PROTOCOL PORTION of  
FCC 47 CFR PART 15 SUBPART E, KDB 987594  
CONTENTION BASED PROTOCOL PORTION of  
RSS-248, ISSUE 3

**Date Of Issue:**  
2025-08-13

**Prepared by:**  
UL VERIFICATION SERVICES INC.  
47173 Benicia Street  
Fremont, CA 94538, U.S.A.  
TEL: (510) 319-4000  
FAX: (510) 661-0888



Revision History

Rev.	Issue Date	Revisions	Revised By
V1	2025-06-19	Initial Issue	--
V2	2025-07-08	Section 7.2.5 Updated	Henry Lau
V3	2025-07-18	Section 7.2.5, 8.2.3 Updated	Henry Lau
V4	2025-07-22	Section 7.1.1 Updated	Henry Lau
V5	2025-07-28	Section 7.2.6 Updated	Thu Chan
V6	2025-08-13	Section 7.1.2, 7.2.5, 7.3 Updated	Henry Lau

## TABLE OF CONTENTS

<b>1. ATTESTATION OF TEST RESULTS.....</b>	<b>6</b>
<b>2. TEST METHODOLOGY .....</b>	<b>7</b>
<b>3. SUMMARY OF TEST RESULTS .....</b>	<b>7</b>
<b>4. REFERENCE DOCUMENTS .....</b>	<b>7</b>
<b>5. FACILITIES AND ACCREDITATION.....</b>	<b>7</b>
<b>6. DECISION RULES AND MEASUREMENT UNCERTAINTY.....</b>	<b>8</b>
6.1. <i>METROLOGICAL TRACEABILITY.....</i>	8
6.2. <i>DECISION RULES .....</i>	8
6.3. <i>MEASUREMENT UNCERTAINTY.....</i>	8
<b>7. CONTENTION BASED PROTOCOL.....</b>	<b>9</b>
7.1. <i>OVERVIEW.....</i>	9
7.1.1. <i>LIMITS .....</i>	9
7.1.2. <i>FREQUENCY BANDS AND GOVERNING RULES .....</i>	9
7.1.3. <i>EQUIPMENT CLASSIFICATIONS .....</i>	11
7.2. <i>DESCRIPTION OF TEST SETUP.....</i>	12
7.2.1. <i>TEST AND MEASUREMENT SYSTEM .....</i>	12
7.2.2. <i>TEST AND MEASUREMENT SOFTWARE .....</i>	14
7.2.3. <i>TEST ROOM ENVIRONMENT.....</i>	14
7.2.4. <i>SETUP OF EUT .....</i>	15
7.2.5. <i>DESCRIPTION OF EUT .....</i>	17
7.2.6. <i>MODEL DIFFERENCES .....</i>	19
7.3. <i>LIMITS AND PROCEDURES .....</i>	20
7.4. <i>U-NII 5 BAND TEST CONDITION 1 - 1 MHz BANDWIDTH RESULTS.....</i>	21
7.4.1. <i>TEST CHANNEL .....</i>	21
7.4.2. <i>INCUMBENT SIGNAL PLOTS .....</i>	22
7.4.3. <i>EUT TRANSMISSION PLOTS .....</i>	24
7.4.4. <i>TABULATED TEST RESULTS.....</i>	27
7.4.5. <i>Tx OPERATIONAL STATUS TEST RESULTS .....</i>	29
7.5. <i>U-NII 5 BAND TEST CONDITION 1 - 2 MHz BANDWIDTH RESULTS.....</i>	30
7.5.1. <i>TEST CHANNEL .....</i>	30
7.5.2. <i>INCUMBENT SIGNAL PLOTS .....</i>	31
7.5.3. <i>EUT TRANSMISSION PLOTS .....</i>	33
7.5.4. <i>TABULATED TEST RESULTS.....</i>	36
7.5.5. <i>Tx OPERATIONAL STATUS TEST RESULTS .....</i>	38
7.6. <i>U-NII 5 BAND TEST CONDITION 1 - 4 MHz BANDWIDTH RESULTS.....</i>	39
7.6.1. <i>TEST CHANNEL .....</i>	39
7.6.2. <i>INCUMBENT SIGNAL PLOTS .....</i>	40
7.6.3. <i>EUT TRANSMISSION PLOTS .....</i>	42
7.6.4. <i>TABULATED TEST RESULTS.....</i>	45
7.6.5. <i>Tx OPERATIONAL STATUS TEST RESULTS .....</i>	47

7.7. <i>U-NII 5 BAND TEST CONDITION 1 - 8 MHz BANDWIDTH RESULTS</i> .....	48
7.7.1. TEST CHANNEL .....	48
7.7.2. INCUMBENT SIGNAL PLOTS .....	49
7.7.3. EUT TRANSMISSION PLOTS .....	51
7.7.4. TABULATED TEST RESULTS.....	54
7.7.5. Tx OPERATIONAL STATUS TEST RESULTS.....	56
7.8. <i>U-NII 5 BAND TEST CONDITION 1 RESULTS</i> .....	57
7.9. <i>U-NII 5 BAND TEST CONDITION 2 RESULTS</i> .....	57
7.9.1. TEST CHANNEL .....	57
7.9.2. INCUMBENT SIGNAL PLOTS .....	57
7.9.3. EUT TRANSMISSION PLOTS .....	60
7.9.4. TABULATED TEST RESULTS.....	63
7.9.5. Tx OPERATIONAL STATUS TEST RESULTS.....	65
7.10. <i>U-NII 5 BAND TEST CONDITION 3 RESULTS</i> .....	66
7.11. <i>U-NII 5 BAND TEST CONDITION 4 RESULTS</i> .....	66
7.11.1. TEST CHANNEL .....	66
7.11.2. INCUMBENT SIGNAL PLOTS .....	66
7.11.3. EUT TRANSMISSION PLOTS .....	73
7.11.4. TABULATED TEST RESULTS.....	83
7.11.5. Tx OPERATIONAL STATUS TEST RESULTS.....	85
7.12. <i>U-NII 6 BAND TEST CONDITION 1 RESULTS</i> .....	86
7.13. <i>U-NII 6 BAND TEST CONDITION 2 RESULTS</i> .....	86
7.13.1. TEST CHANNEL .....	86
7.13.2. INCUMBENT SIGNAL PLOTS .....	86
7.13.3. EUT TRANSMISSION PLOTS .....	89
7.13.4. TABULATED TEST RESULTS.....	92
7.13.5. Tx OPERATIONAL STATUS TEST RESULTS.....	94
7.14. <i>U-NII 6 BAND TEST CONDITION 3 RESULTS</i> .....	95
7.15. <i>U-NII 6 BAND TEST CONDITION 4 RESULTS</i> .....	95
7.15.1. TEST CHANNEL .....	95
7.15.2. INCUMBENT SIGNAL PLOTS .....	95
7.15.3. EUT TRANSMISSION PLOTS .....	102
7.15.4. TABULATED TEST RESULTS.....	112
7.15.5. Tx OPERATIONAL STATUS TEST RESULTS.....	114
7.16. <i>U-NII 7 BAND TEST CONDITION 1 RESULTS</i> .....	115
7.17. <i>U-NII 7 BAND TEST CONDITION 2 RESULTS</i> .....	115
7.17.1. TEST CHANNEL .....	115
7.17.2. INCUMBENT SIGNAL PLOTS .....	115
7.17.3. EUT TRANSMISSION PLOTS .....	118
7.17.4. TABULATED TEST RESULTS.....	121
7.17.5. Tx OPERATIONAL STATUS TEST RESULTS.....	123
7.18. <i>U-NII 7 BAND TEST CONDITION 3 RESULTS</i> .....	124
7.19. <i>U-NII 7 BAND TEST CONDITION 4 RESULTS</i> .....	124
7.19.1. TEST CHANNEL .....	124
7.19.2. INCUMBENT SIGNAL PLOTS .....	124
7.19.3. EUT TRANSMISSION PLOTS .....	131
7.19.4. TABULATED TEST RESULTS.....	141

7.19.5. Tx OPERATIONAL STATUS TEST RESULTS .....	143
7.20. U-NII 8 BAND TEST CONDITION 1 RESULTS .....	144
7.21. U-NII 8 BAND TEST CONDITION 2 RESULTS .....	144
7.21.1. TEST CHANNEL .....	144
7.21.2. INCUMBENT SIGNAL PLOTS .....	144
7.21.3. EUT TRANSMISSION PLOTS .....	147
7.21.4. TABULATED TEST RESULTS .....	150
7.21.5. Tx OPERATIONAL STATUS TEST RESULTS .....	152
7.22. U-NII 8 BAND TEST CONDITION 3 RESULTS .....	153
7.23. U-NII 8 BAND TEST CONDITION 4 RESULTS .....	153
7.23.1. TEST CHANNEL .....	153
7.23.2. INCUMBENT SIGNAL PLOTS .....	153
7.23.3. EUT TRANSMISSION PLOTS .....	160
7.23.4. TABULATED TEST RESULTS .....	170
7.23.5. Tx OPERATIONAL STATUS TEST RESULTS .....	172
<b>8. SETUP PHOTOS.....</b>	<b>173</b>

## 1. ATTESTATION OF TEST RESULTS

**COMPANY NAME:** APPLE, INC.  
1 APPLE PARK WAY  
CUPERTINO, CA 95014, U.S.A.

**EUT DESCRIPTION:** SMARTPHONE

**MODEL:** A3260 (PARENT MODEL)  
A3516, A3517, A3518 (VARIANT MODEL)

**MODEL TESTED:** A3260

**SERIAL NUMBER:** DJ769QWPP7 (BT), G5Y9HXJQYQ (WLAN)

**DATE TESTED:** 2025-05-19 to 2025-05-27

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
Contention Based Protocol Portion of 47 CFR Part 15 Subpart E, KDB 987594	Complies
Contention Based Protocol Portion of RSS-248, Issue 3	Complies

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. All samples tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise.

This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document.

Approved & Released For  
UL Verification Services Inc. By:



---

Frank Ibrahim  
Project Engineer  
CONSUMER TECHNOLOGY DIVISION  
UL Verification Services Inc.

Prepared By:



---

Henry Lau  
Project Engineer  
CONSUMER TECHNOLOGY DIVISION  
UL Verification Services Inc.

## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with the following standards/rules/KDBs:

- FCC 47 CFR Part 15 Subpart E
- FCC KDB 987594 D01 U-NII 6GHz General Requirements
- FCC KDB 987594 D02 U-NII 6 GHz EMC Measurement
- FCC KDB 987594 D03 U-NII 6 GHz QA
- FCC KDB 987594 D04 UN6GHZ Pre-Approval Guidance Checklist
- RSS-248, ISSUE 3

## 3. SUMMARY OF TEST RESULTS

Requirement Description	Result	Remarks
Contention Based Protocol Portion of FCC 47 CFR PART 15 SUBPART E, KDB 987594	Complies	
Contention Based Protocol Portion of RSS-248	Complies	

## 4. REFERENCE DOCUMENTS

Measurements of transmitter parameters as referenced in this report and all other manufacturer's declarations relevant to the RF test requirements are documented in UL Verification Services report number 15496282-E12– E15.

This report contains data provided by the customer which can impact the validity of results. UL Verification Services Inc. is only responsible for correctly integrating customer-provided data with measurements performed by UL Verification Services Inc.

Below is a list of the data provided by the customer:

1. Antenna gain and type (see section 7.2.5)
2. Test Fixture Cable loss (2.8 dB)

## 5. FACILITIES AND ACCREDITATION

UL Verification Services Inc. is accredited by A2LA, certification #0751.05, for all testing performed within the scope of this report. Testing was performed at the locations noted below.

	Address	ISED CABID	ISED Company Number	FCC Registration
<input checked="" type="checkbox"/>	Building 1: 47173 Benicia Street, Fremont, California, USA	US0104	2324A	550739

## 6. DECISION RULES AND MEASUREMENT UNCERTAINTY

### 6.1. METROLOGICAL TRACEABILITY

All test and measuring equipment utilized to perform the tests documented in this report are calibrated on a regular basis, with a maximum time between calibrations of one year or the manufacturers' recommendation, whichever is less, and where applicable is traceable to recognized national standards.

### 6.2. DECISION RULES

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4:2012 Clause 8.2. (Measurement uncertainty is not taken into account when stating conformity with a specified requirement).

### 6.3. MEASUREMENT UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	U <sub>Lab</sub>
Radio Frequency (Spectrum Analyzer)	141.16 Hz
Occupied Bandwidth	1.22%
Power Spectral Density	2.47 dB
RF Power Measurement Direct Method Using Power Meter	1.3 dB (PK) / 0.45 dB (AV)
Unwanted Emissions, Conducted	1.94 dB
Worst Case Conducted Disturbance, 9kHz to 0.15 MHz	3.78 dB
Worst Case Conducted Disturbance, 0.15 to 30 MHz	3.40 dB
Worst Case Radiated Disturbance, 9kHz to 30 MHz	2.87 dB
Worst Case Radiated Disturbance, 30 to 1000 MHz	6.01 dB
Worst Case Radiated Disturbance, 1000 to 18000 MHz	4.73 dB
Worst Case Radiated Disturbance, 18000 to 26000 MHz	4.51 dB
Worst Case Radiated Disturbance, 26000 to 40000 MHz	5.29 dB
Time Domain Measurements	0.02 %
Temperature	0.57°C
Humidity	3.39%
DC Supply Voltages	0.57%

Uncertainty figures are valid to a confidence level of 95%.

## 7. CONTENTION BASED PROTOCOL

### 7.1. OVERVIEW

#### 7.1.1. LIMITS

##### FCC

FCC Part 15 Subpart E, FCC KDB 987594 D02 “U-NII 6 GHz devices operating in the 5.925-7.125 GHz band”; Section I.

##### INNOVATION, SCIENCE and ECONOMIC DEVELOPMENT CANADA (ISED)

**Per Section 4.7.2 of RSS-248:**

“The Federal Communications Commission’s accepted KDB procedure KDB 987594 D02 listed on ISED’s Certification and Engineering website (see the Normative Test Standards and Acceptable Alternate Procedures page) shall be used to demonstrate the compliance of a device with the contention based protocol requirements set out in this section:.

#### 7.1.2. FREQUENCY BANDS AND GOVERNING RULES

Band	Frequency (GHz)	Rules	Notes	KDB/Publication
U-NII 5	5.925-6.425	15.407(a)(4) – (8)	Low Power Indoor AP, Subordinates, Indoor Clients Standard Power AP, Fixed , Standard Clients, Dual Client & VLP	
U-NII 6	6.425-6.525	15.407(a)(5), (6), (8)	Low Power Indoor AP, Subordinates, Indoor Clients, Dual Client & VLP	789033 (U-NII) 987594 (6 GHz Band)
U-NII 7	6.525-6.875	15.407(a)(4) – (8)	Low Power Indoor AP, Subordinates, Indoor Clients Standard Power AP, Fixed Standard Clients, Dual Client & VLP	
U-NII 8	6.875 -7.125	15.407(a)(5), (6), (8)	Low Power Indoor AP, Subordinates, Indoor Clients, Dual Client & VLP	
<b>The transition period ended on June 2, 2015, for marketing DTS in the 5 GHz Band.</b>				


**Table 1: Overview of U-NII Rules**

**ISED**

Band	Frequency (GHz)	Rules	Notes	KDB/Publication
U-NII 5	5.925-6.425	RSS 248 - Section 4.2	Low-Power indoor AP, indoor subordinate devices, low-power client devices, Standard Power AP, Fixed client devices, standard client devices, dual client devices & VLP	
U-NII 6	6.425-6.525	RSS 248 - Section 4.2	Low-Power indoor AP, indoor subordinate devices, low-power client devices, Standard Power AP, Fixed client devices, standard client devices, dual client devices & VLP	RSS 248 987594 D02
U-NII 7	6.525-6.875	RSS 248 - Section 4.2	Low-Power indoor AP, indoor subordinate devices, low-power client devices, Standard Power AP, Fixed client devices, standard client devices, dual client devices & VLP	
U-NII 8	6.875 -7.125	RSS 248 - Section 4.2	Low-Power indoor AP, indoor subordinate devices, low-power client devices, dual client devices & VLP	

### 7.1.3. EQUIPMENT CLASSIFICATIONS

There are seven applicable equipment classes for U-NII 6 GHz device certifications, as illustrated in Figure 1. Multiple equipment classes can apply to one FCC ID. Equipment classes categorize the certification record by the different technical rules that apply.



#### DEFINITION OF EQUIPMENT CLASSES

1. 6ID: 15E 6 GHz Low power indoor access point.
2. 6PP: 15E 6 GHz Subordinate indoor device. These devices are under control of a Low power indoor access point (P1).
3. 6XD: 15E 6 GHz Low power Indoor client. These devices are under control of a low power indoor access point (P1).
4. 6SD: 15E 6 GHz Standard power access point. These devices are managed by the Automatic Frequency Coordination (AFC) system.
5. 6CD: 15E 6 GHz Dual client. These devices are under control of either a low power indoor access point (6ID) (P1) or Standard power access point (P2).
6. 6FX: 15E 6 GHz Standard client. These devices are under control of a Standard power access point (P2).
7. 6FC: 15E 6 GHz Fixed client. These devices are associated with a standard power access point (P3).
8. 6VL: 15E 6 GHz VLP device operating in U-NII bands 5-8.


## 7.2. DESCRIPTION OF TEST SETUP

### 7.2.1. TEST AND MEASUREMENT SYSTEM

These tests were performed using a Conducted instrument configuration.

#### CONDUCTED TEST CONFIGURATION

**NOTE:** This is a comprehensive setup diagram of the receiver performance test and measurement system. Not all of the devices shown below are used for every applicable receiver test. Also, coupler port designations "IN" and "OUT" refer to labeling on the coupler, not the RF signal flow.



## SYSTEM OVERVIEW

Should multiple RF ports be utilized for the EUT and/or Companion devices (for example, for diversity or MIMO implementations), combiner/dividers are inserted between the EUT MIMO Combiner/Divider and the attenuator connected to the EUT (and/or between the Companion MIMO Combiner/Divider and the attenuator connected to the Companion Device). Additional attenuators may be utilized such that there is one attenuator at each RF port on each device.

## SYSTEM CALIBRATION

The monitoring cable is disconnected from the spectrum analyzer and a 50-ohm load is connected to the end of the monitoring cable in place of the spectrum analyzer. The cable connected to the EUT is then attached to the spectrum analyzer in place of the monitoring cable. A signal generator is then set to produce a modulated AWGN Incumbent Signal that has a 99% occupied power bandwidth of 10 MHz. The output amplitude of the signal generator is adjusted to yield the allowable maximum AWGN Incumbent Signal level as measured on the spectrum analyzer. The EUT and monitoring cables are then returned to their original configurations to perform the test.

## TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

TEST EQUIPMENT LIST				
Description	Manufacturer	Model	ID No.	Cal Due
Spectrum Analyzer, PXA, 3Hz to 8.4GHz	Keysight	N9030A	150667	2026-01-31
Signal Generator, MXG X-Series RF Vector	Keysight	N5182B	215999	2026-01-31
Frequency Extender	Keysight	N5182BX	213906	2026-01-31

**Note:** An MXG series Signal Generator and separate external Frequency Extender module are shown in the preceding test system block diagram as a stand-alone Incumbent Signal Generator.

## 7.2.2. TEST AND MEASUREMENT SOFTWARE

The following test and measurement software was utilized for the tests documented in this report:

TEST SOFTWARE LIST		
Name	Version	Test / Function
PXA Read	3.1	Signal Generator Screen Capture

## 7.2.3. TEST ROOM ENVIRONMENT

The test room temperature and humidity shall be maintained within normal temperature of 15~35 °C and normal humidity 20~75% (relative humidity).


### ENVIRONMENT CONDITION

Parameter	Value
Temperature	23.6 °C
Humidity	46 %

## 7.2.4. SETUP OF EUT

### CONDUCTED METHOD EUT TEST SETUP

**NB UNII:**




### SUPPORT EQUIPMENT

The following support equipment was utilized for the tests documented in this report:

PERIPHERAL SUPPORT EQUIPMENT LIST				
Description	Manufacturer	Model	Serial Number	FCC ID
Notebook PC 1 (EUT Controller/Console)	Apple	A2779	DW4JXYW99G	DoC
Airpod Development System (Companion)	Apple	920-10664-04	GTS1403004G	None
Notebook PC 2 (Companion Host)	Apple	A2779	C962RJ4D3Y	DoC
Companion Device + Headset	Apple	MNHF2AM/A	250416CA05	DoC

**WLAN:**



**SUPPORT EQUIPMENT**

The following support equipment was utilized for the tests documented in this report:

PERIPHERAL SUPPORT EQUIPMENT LIST				
Description	Manufacturer	Model	Serial Number	FCC ID
Notebook PC 1 (EUT Controller/Console)	Apple	A2779	C962RJ4D3Y	DoC
WiFi 6e Gaming Router (Companion)	ASUS Computer International	GT-AXE11000	M6IAJF202341	MSQ-RTAXJF00
AC Adapter (Companion)	AC BEL	ADD011 LPS	ADD01117AG20450 4118A	DoC
Notebook PC (Companion Host)	Lenovo	Type 20B7-S0A200	PF-02JN9J 14/06	DoC
AC Adapter (Companion Host)	Lenovo	ADLX65NLC2A	11S45N0259Z1ZS97 4594A9	DoC

## 7.2.5. DESCRIPTION OF EUT

### NB UNII:

The EUT operates in the following band: U-NII 5 (5925 MHz-6425 MHz).

The EUT does not support the following bands: U-NII 6 (6425 MHz-6525 MHz), U-NII 7 (6525 MHz-6875 MHz) and U-NII 8 (6875 MHz-7125 MHz).

The EUT is classified as a 6 GHz VLP.

The manufacturer has declared that the lowest gain antenna assembly as follows

	A3260/A3516/A3517/A3518
UNII-5	-3

The manufacturer has declared that the lowest gain antenna assembly across all models has a gain of -3 dBi in the U-NII 5 band.

Two antennas are utilized to meet the diversity and MIMO operational requirements.

The maximum allowable conducted AWGN Incumbent Detection Threshold level is -62 dBm. After correction for antenna gain the conducted AWGN Incumbent Detection Threshold at the antenna port is -62 + antenna gain. This results in a maximum allowable AWGN Incumbent Detection Threshold of -65 dBm in the U-NII 5 band.

The EUT uses two transmitter/receiver chains, each connected to a 50-ohm coaxial antenna port. All antenna ports are connected to the test system via a power divider to perform conducted tests.

Traffic was generated by transferring a data stream from the EUT to the Companion Device using audio.

Four nominal channel bandwidths are implemented: 1 MHz, 2 MHz, 4 MHz & 8 MHz.

The software installed in the EUT is version 19.0.

**WLAN:**

The EUT operates in the following band / bands: U-NII 5 (5925 MHz-6425 MHz), U-NII 6 (6425 MHz-6525 MHz), U-NII 7 (6525 MHz-6875 MHz) and U-NII 8 (6875 MHz-7125 MHz).

The EUT is classified as a 6 GHz Dual Client & VLP.

The manufacturer has declared that the lowest gain antenna assembly as follows

	A3260/A3516/A3517/A3518
UNII-5	-3
UNII-6	-2.4
UNII-7	-2
UNII-8	-4.2

The lowest gain antenna assembly across the parent & variant models has a gain of -3 dBi in the U-NII 5 band, -2.4 dBi in the U-NII 6 band, -2 dBi in the U-NII 7 band and -4.2 dBi in the U-NII 8 band.

Two antennas are utilized to meet the diversity and MIMO operational requirements.

The maximum allowable conducted AWGN Incumbent Detection Threshold level is -62 dBm. After correction for antenna gain the conducted AWGN Incumbent Detection Threshold at the antenna port is -62 + antenna gain. This results in a maximum allowable AWGN Incumbent Detection Threshold of -65 dBm in the U-NII 5 band, -64.4 dBm in the U-NII 6 band, -64 dBm in the U-NII 7 band and -66.2 dBm in the U-NII 8 band.

The EUT uses two transmitter/receiver chains, each connected to a 50-ohm coaxial antenna port. All antenna ports are connected to the test system via a power divider to perform conducted tests.

WLAN traffic was generated by transferring a data stream from the EUT to the Companion Device using iPerf3 version 3.1.3 software package.

The EUT utilizes the 802.11ax and 802.11be architecture. Four nominal channel bandwidths are implemented: 20 MHz, 40 MHz, 80 MHz and 160 MHz.

The manufacturer declares that Channel Puncturing is supported but is used only for network optimization and is not used for the purposes of avoiding incumbents.

The manufacturer declares that Channel Bandwidth Reduction is supported.

The software installed in the EUT is version 19.0.

The firmware installed in the Companion Device is version V1.0.7.56\_2.0.65.

### **TEST SETUP**

#### **NB UNII:**

The EUT is attached to a USB port of a host notebook PC during testing. The EUT is linked to a companion 802.11 wireless radio device. An audio file was opened on the EUT and played by the companion radio device using a media player resident on the EUT.

#### **WLAN:**

The EUT is attached to a USB port of a host notebook PC during testing. The EUT is linked to a companion 802.11 wireless radio device. A commercial traffic generation program (iPERF) was utilized to generate traffic from the EUT to the companion radio device.

### **7.2.6. MODEL DIFFERENCES**

Models A3260, A3516, A3517, & A3518 are electrically identical. Only difference is the FR1 bands disabled or enabled by software as document in technical description. The difference does not affect CBP testing therefore the parent model is representative of the variant models.

## 8. CONTENTION BASED PROTOCOL

### 8.1. LIMITS AND PROCEDURES

#### LIMITS

FCC Part 15 Subpart E, FCC KDB 987594 D02 “U-NII 6 GHz devices operating in the 5.925-7.125 GHz band”; Section I.

#### AWGN INCUMBENT SIGNAL DETECTION THRESHOLD

FCC Part 15 Subpart E, FCC KDB 987594 D02 “U-NII 6 GHz devices operating in the 5.925-7.125 GHz band”; Section I, Clause (c), Step 6.

For an EUT with a non-zero dBi antenna gain the maximum detection threshold level,  $T_L$ , of the 10 MHz wide AWGN Incumbent Signal at the port of the radio module in a conducted test setup shall be no greater than -62 dBm. It shall be adjusted by the gain of the bypassed antenna as shown in the table below:

#### **NB UNII:**

Band	Frequency Range (MHz)	Antenna Gain (dBi)	$T_L$ at Radio Port (dBm)
U-NII 5	5925 to 6425	-3.00	-65

#### **WLAN:**

Band	Frequency Range (MHz)	Antenna Gain (dBi)	$T_L$ at Radio Port (dBm)
U-NII 5	5925 to 6425	-3.00	-65
U-NII 6	6425 to 6525	-2.40	-64.4
U-NII 7	6525 to 6875	-2.00	-64
U-NII 8	6875 to 7125	-4.20	-66.2

#### TEST PROCEDURE

FCC Part 15 Subpart E, FCC KDB 987594 D02 “U-NII 6 GHz devices operating in the 5.925-7.125 GHz band”; Section I, Clause (c).

## 8.2. U-NII 5 BAND TEST CONDITION 1 - 1 MHz BANDWIDTH RESULTS

### TEST CONDITION 1 CRITERIA

**99%  $BW_{EUT}$   $\leq$  99%  $BW_{INC}$**

#### 8.2.1. TEST CHANNEL

All tests were performed with the EUT set to a channel center frequency of 6350 MHz and a nominal channel bandwidth of 1 MHz.


Only the lowest and highest supported channel bandwidths are required to be tested.

**Note:** The RBW / VBW settings of the spectrum analyzer may be reduced to reject adjacent channel signals from being displayed in the test channel plots. The video trigger of the spectrum analyzer may also be enabled to facilitate the capture of time domain events. This in turn, depending on the model of the equipment used, may disable the RMS detector. These changes do not impact timing measurement data.


## 8.2.2. INCUMBENT SIGNAL PLOTS

All tests were performed with the Incumbent Signal frequency set to the test channel center frequency and a nominal 99% Occupied Power Bandwidth of 10 MHz.

### INCUMBENT SIGNAL 99% OCCUPIED POWER BANDWIDTH




**MINIMUM PASSING INCUMBENT SIGNAL POWER AT TEXT FIXTURE**




### 8.2.3. EUT TRANSMISSION PLOTS

#### EUT 99% OCCUPIED POWER BANDWIDTH




**TRAFFIC WITHOUT THE INCUMBENT SIGNAL PRESENT**



### EUT RESPONSE TO THE APPLIED INCUMBENT SIGNAL

A link between the EUT and the Companion Device was established on the test channel. Traffic flowing from the EUT to the Companion Device was then initiated. A sweep was started and the incumbent signal was continuously applied at approximately 3 seconds after the start of the sweep for a minimum duration of 10 seconds and removed after the end of the observation period. Markers are placed at the beginning and end of the observation period.



Normal Traffic

Application of Incumbent  
Transmissions Ceased

Incumbent Removed  
Transmissions Resume

Transmissions cease within 513ms while the Incumbent AWGN Signal is present and resume after it is removed.

## 8.2.4. TABULATED TEST RESULTS

### INCUMBENT SIGNAL DETECTION RESULTS

<b>EUT Channel Center Frequency, <math>f_{c1}</math> (MHz)</b>	6350
<b>EUT Nominal Channel Bandwidth (MHz)</b>	1
<b>99% Occupied Bandwidth of the EUT (MHz)</b>	0.85293
<b>EUT 99% OBW Lower Edge, <math>F_L</math> (MHz)</b>	6349.57
<b>EUT 99% OBW Upper Edge, <math>F_H</math> (MHz)</b>	6350.43
<b>Test Frequency of Incumbent Signal (MHz)</b>	<b>6350</b>
<b>Maximum Allowed Incumbent Amplitude at Antenna (dBm)</b>	-62
<b>Minimum Antenna Gain (dBi)</b>	-3.00
<b>Maximum Allowed Incumbent Amplitude at Radio Port (dBm)</b>	-65.00
<hr/>	
<b>Lowest Passing Measured Incumbent Signal Amplitude (Test Fixture)(dBm)</b>	-63.95
<b>Test Fixture Cable Loss (dB)</b>	2.80
<b>Lowest Passing Measured Incumbent Signal Amplitude (dBm)</b>	-66.75
<b>Margin (dBm)</b>	-1.75
<b>Result (PASS / FAIL)</b>	<b>PASS</b>

**Test Date: 2025-05-27**

**Tested by: 44352**

**Test location: 1-DFS-A**

**INCUMBENT SIGNAL DETECTION CERTAINTY RATE**

AWGN Detected (Yes / No)	
Trial	Incumbent AWGN at $f_{c1}$
1	Yes
2	Yes
3	Yes
4	Yes
5	Yes
6	Yes
7	Yes
8	Yes
9	Yes
10	Yes
<b>Test Result</b>	<b>PASS</b>

**Test Date: 2025-05-27**

**Tested by: 44352**

**Test location: 1-DFS-A**

A minimum detection rate of 90% is required for the EUT to be compliant.

### 8.2.5. Tx OPERATIONAL STATUS TEST RESULTS

**Test Condition 1: 99% BW<sub>EUT</sub> ≤ 99% BW<sub>INC</sub>**

**Incumbent AWGN at f<sub>c1</sub>:**

Measured Incumbent Power at the EUT Test Fixture Connector (dBm)	Test Fixture Cable Path Loss (dB)	Adjusted Incumbent Power at the Radio Port (dBm)	Antenna Gain (dBi)	Adjusted Incumbent Power at the Antenna (dBm)	Detection Limit (dBm)	EUT Tx Status
-63.95	2.8	-66.8	-3.00	-63.75	-62	Ceased
<b>-64.56</b>	2.8	-67.4	-3.00	-64.36	-62	Minimal
<b>-64.98</b>	2.8	-67.8	-3.00	-64.78	-62	Normal

**Test Date: 2025-05-27**

**Tested by: 44352**

**Test location: 1-DFS-A**

### 8.3. U-NII 5 BAND TEST CONDITION 1 - 2 MHz BANDWIDTH RESULTS

#### TEST CONDITION 1 CRITERIA

$$99\% \text{ BW}_{\text{EUT}} \leq 99\% \text{ BW}_{\text{INC}}$$

#### 8.3.1. TEST CHANNEL

All tests were performed with the EUT set to a channel center frequency of 6350 MHz and a nominal channel bandwidth of 2 MHz.


Only the lowest and highest supported channel bandwidths are required to be tested.

**Note:** The RBW / VBW settings of the spectrum analyzer may be reduced to reject adjacent channel signals from being displayed in the test channel plots. The video trigger of the spectrum analyzer may also be enabled to facilitate the capture of time domain events. This in turn, depending on the model of the equipment used, may disable the RMS detector. These changes do not impact timing measurement data.


### 8.3.2. INCUMBENT SIGNAL PLOTS

All tests were performed with the Incumbent Signal frequency set to the test channel center frequency and a nominal 99% Occupied Power Bandwidth of 10 MHz.

#### INCUMBENT SIGNAL 99% OCCUPIED POWER BANDWIDTH




**MINIMUM PASSING INCUMBENT SIGNAL POWER AT TEXT FIXTURE**




### 8.3.3. EUT TRANSMISSION PLOTS

#### EUT 99% OCCUPIED POWER BANDWIDTH




**TRAFFIC WITHOUT THE INCUMBENT SIGNAL PRESENT**



### EUT RESPONSE TO THE APPLIED INCUMBENT SIGNAL

A link between the EUT and the Companion Device was established on the test channel. Traffic flowing from the EUT to the Companion Device was then initiated. A sweep was started and the incumbent signal was continuously applied at approximately 3 seconds after the start of the sweep for a minimum duration of 10 seconds and removed after the end of the observation period. Markers are placed at the beginning and end of the observation period.



Normal Traffic

Application of Incumbent  
Transmissions Ceased

Incumbent Removed  
Transmissions Resume

Transmissions cease within 707.3ms while the Incumbent AWGN Signal is present and resume after it is removed.

### 8.3.4. TABULATED TEST RESULTS

#### INCUMBENT SIGNAL DETECTION RESULTS

<b>EUT Channel Center Frequency, <math>f_{c1}</math> (MHz)</b>	6350
<b>EUT Nominal Channel Bandwidth (MHz)</b>	2
<b>99% Occupied Bandwidth of the EUT (MHz)</b>	2.3672
<b>EUT 99% OBW Lower Edge, <math>F_L</math> (MHz)</b>	6348.82
<b>EUT 99% OBW Upper Edge, <math>F_H</math> (MHz)</b>	6351.18
<b>Test Frequency of Incumbent Signal (MHz)</b>	<b>6350</b>
<b>Maximum Allowed Incumbent Amplitude at Antenna (dBm)</b>	-62
<b>Minimum Antenna Gain (dBi)</b>	-3.00
<b>Maximum Allowed Incumbent Amplitude at Radio Port (dBm)</b>	-65.00
<hr/>	
<b>Lowest Passing Measured Incumbent Signal Amplitude (Test Fixture)(dBm)</b>	-65.09
<b>Test Fixture Cable Loss (dB)</b>	2.80
<b>Lowest Passing Measured Incumbent Signal Amplitude (dBm)</b>	-67.89
<b>Margin (dBm)</b>	-2.89
<b>Result (PASS / FAIL)</b>	<b>PASS</b>

**Test Date: 2025-05-20**

**Tested by: 44352**

**Test location: 1-DFS-A**

**INCUMBENT SIGNAL DETECTION CERTAINTY RATE**

Trial	AWGN Detected (Yes / No)
	Incumbent AWGN at $f_{c1}$
1	Yes
2	Yes
3	Yes
4	Yes
5	Yes
6	Yes
7	Yes
8	Yes
9	Yes
10	Yes
<b>Test Result</b>	<b>PASS</b>

**Test Date: 2025-05-20**

**Tested by: 44352**

**Test location: 1-DFS-A**

A minimum detection rate of 90% is required for the EUT to be compliant.

### 8.3.5. Tx OPERATIONAL STATUS TEST RESULTS

**Test Condition 1: 99% BW<sub>EUT</sub> ≤ 99% BW<sub>INC</sub>**

**Incumbent AWGN at f<sub>c1</sub>:**

Measured Incumbent Power at the EUT Test Fixture Connector (dBm)	Test Fixture Cable Path Loss (dB)	Adjusted Incumbent Power at the Radio Port (dBm)	Antenna Gain (dBi)	Adjusted Incumbent Power at the Antenna (dBm)	Detection Limit (dBm)	EUT Tx Status
-65.09	2.8	-67.9	-3.00	-64.89	-62	Ceased
-65.19	2.8	-68.0	-3.00	-64.99	-62	Minimal
-66.3	2.8	-69.1	-3.00	-66.1	-62	Normal

**Test Date: 2025-05-20**

**Tested by: 44352**

**Test location: 1-DFS-A**

## 8.4. U-NII 5 BAND TEST CONDITION 1 - 4 MHz BANDWIDTH RESULTS

### TEST CONDITION 1 CRITERIA

$$99\% \text{ BW}_{\text{EUT}} \leq 99\% \text{ BW}_{\text{INC}}$$

#### 8.4.1. TEST CHANNEL

All tests were performed with the EUT set to a channel center frequency of 6350 MHz and a nominal channel bandwidth of 4 MHz.


Only the lowest and highest supported channel bandwidths are required to be tested.

**Note:** The RBW / VBW settings of the spectrum analyzer may be reduced to reject adjacent channel signals from being displayed in the test channel plots. The video trigger of the spectrum analyzer may also be enabled to facilitate the capture of time domain events. This in turn, depending on the model of the equipment used, may disable the RMS detector. These changes do not impact timing measurement data.


#### 8.4.2. INCUMBENT SIGNAL PLOTS

All tests were performed with the Incumbent Signal frequency set to the test channel center frequency and a nominal 99% Occupied Power Bandwidth of 10 MHz.

##### INCUMBENT SIGNAL 99% OCCUPIED POWER BANDWIDTH




**MINIMUM PASSING INCUMBENT SIGNAL POWER**




### 8.4.3. EUT TRANSMISSION PLOTS

#### EUT 99% OCCUPIED POWER BANDWIDTH




**TRAFFIC WITHOUT THE INCUMBENT SIGNAL PRESENT**



### EUT RESPONSE TO THE APPLIED INCUMBENT SIGNAL

A link between the EUT and the Companion Device was established on the test channel. Traffic flowing from the EUT to the Companion Device was then initiated. A sweep was started and the incumbent signal was continuously applied at approximately 3 seconds after the start of the sweep for a minimum duration of 10 seconds and removed after the end of the observation period. Markers are placed at the beginning and end of the observation period.



Normal Traffic

Application of Incumbent  
Transmissions Ceased

Incumbent Removed  
Transmissions Resume

Transmissions cease within 663 ms while the Incumbent AWGN Signal is present and resume after it is removed.

#### 8.4.4. TABULATED TEST RESULTS

##### INCUMBENT SIGNAL DETECTION RESULTS

EUT Channel Center Frequency, $f_{c1}$ (MHz)	6350
EUT Nominal Channel Bandwidth (MHz)	4
99% Occupied Bandwidth of the EUT (MHz)	4.7265
EUT 99% OBW Lower Edge, $F_L$ (MHz)	6347.64
EUT 99% OBW Upper Edge, $F_H$ (MHz)	6352.36
Test Frequency of Incumbent Signal (MHz)	<b>6350</b>
Maximum Allowed Incumbent Amplitude at Antenna (dBm)	-62
Minimum Antenna Gain (dBi)	-3.00
Maximum Allowed Incumbent Amplitude at Radio Port (dBm)	-65.00
<hr/>	
Lowest Passing Measured Incumbent Signal Amplitude (Test Fixture)(dBm)	-65.30
Text Fixture Cable Loss (dB)	2.80
Lowest Passing Measured Incumbent Signal Amplitude (dBm)	-68.10
Margin (dBm)	-3.10
<b>Result (PASS / FAIL)</b>	<b>PASS</b>

**Test Date: 2025-05-20**

**Tested by: 44352**

**Test location: 1-DFS-A**

**INCUMBENT SIGNAL DETECTION CERTAINTY RATE**

Trial	AWGN Detected (Yes / No)
	Incumbent AWGN at $f_{c1}$
1	Yes
2	Yes
3	Yes
4	Yes
5	Yes
6	Yes
7	Yes
8	Yes
9	Yes
10	Yes
<b>Test Result</b>	<b>PASS</b>

**Test Date: 2025-05-20**

**Tested by: 44352**

**Test location: 1-DFS-A**

A minimum detection rate of 90% is required for the EUT to be compliant.

#### 8.4.5. Tx OPERATIONAL STATUS TEST RESULTS

**Test Condition 1: 99% BW<sub>EUT</sub> ≤ 99% BW<sub>INC</sub>**

**Incumbent AWGN at f<sub>c1</sub>:**

Measured Incumbent Power at the EUT Test Fixture Connector (dBm)	Test Fixture Cable Path Loss (dB)	Adjusted Incumbent Power at the Radio Port (dBm)	Antenna Gain (dBi)	Adjusted Incumbent Power at the Antenna (dBm)	Detection Limit (dBm)	EUT Tx Status
-65.3	2.8	-68.1	-3.00	-65.1	-62	Ceased
-65.65	2.8	-68.5	-3.00	-65.45	-62	Minimal
-66.55	2.8	-69.4	-3.00	-66.35	-62	Normal

**Test Date: 2025-05-20**

**Tested by: 44352**

**Test location: 1-DFS-A**

## 8.5. U-NII 5 BAND TEST CONDITION 1 - 8 MHz BANDWIDTH RESULTS

### TEST CONDITION 1 CRITERIA

$$99\% \text{ BW}_{\text{EUT}} \leq 99\% \text{ BW}_{\text{INC}}$$

#### 8.5.1. TEST CHANNEL

All tests were performed with the EUT set to a channel center frequency of 6350 MHz and a nominal channel bandwidth of 8 MHz.


Only the lowest and highest supported channel bandwidths are required to be tested.

**Note:** The RBW / VBW settings of the spectrum analyzer may be reduced to reject adjacent channel signals from being displayed in the test channel plots. The video trigger of the spectrum analyzer may also be enabled to facilitate the capture of time domain events. This in turn, depending on the model of the equipment used, may disable the RMS detector. These changes do not impact timing measurement data.


### 8.5.2. INCUMBENT SIGNAL PLOTS

All tests were performed with the Incumbent Signal frequency set to the test channel center frequency and a nominal 99% Occupied Power Bandwidth of 10 MHz.

#### INCUMBENT SIGNAL 99% OCCUPIED POWER BANDWIDTH




**MINIMUM PASSING INCUMBENT SIGNAL POWER**




### 8.5.3. EUT TRANSMISSION PLOTS

#### EUT 99% OCCUPIED POWER BANDWIDTH




**TRAFFIC WITHOUT THE INCUMBENT SIGNAL PRESENT**



### EUT RESPONSE TO THE APPLIED INCUMBENT SIGNAL

A link between the EUT and the Companion Device was established on the test channel. Traffic flowing from the EUT to the Companion Device was then initiated. A sweep was started and the incumbent signal was continuously applied at approximately 3 seconds after the start of the sweep for a minimum duration of 10 seconds and removed after the end of the observation period. Markers are placed at the beginning and end of the observation period.



Normal Traffic

Application of Incumbent  
Transmissions Ceased

Incumbent Removed  
Transmissions Resume

Transmissions cease within 465.8 ms while the Incumbent AWGN Signal is present and resume after it is removed.

#### 8.5.4. TABULATED TEST RESULTS

##### INCUMBENT SIGNAL DETECTION RESULTS

EUT Channel Center Frequency, $f_{c1}$ (MHz)	6350
EUT Nominal Channel Bandwidth (MHz)	8
99% Occupied Bandwidth of the EUT (MHz)	9.451
EUT 99% OBW Lower Edge, $F_L$ (MHz)	6345.27
EUT 99% OBW Upper Edge, $F_H$ (MHz)	6354.73
Test Frequency of Incumbent Signal (MHz)	<b>6350</b>
Maximum Allowed Incumbent Amplitude at Antenna (dBm)	-62
Minimum Antenna Gain (dBi)	-3.00
Maximum Allowed Incumbent Amplitude at Radio Port (dBm)	-65.00
<hr/>	
Lowest Passing Measured Incumbent Signal Amplitude (Test Fixture)(dBm)	-63.84
Text Fixture Cable Loss (dB)	2.80
Lowest Passing Measured Incumbent Signal Amplitude (dBm)	-66.64
Margin (dBm)	-1.64
<b>Result (PASS / FAIL)</b>	<b>PASS</b>

**Test Date: 2025-05-27**

**Tested by: 44352**

**Test location: 1-DFS-A**

**INCUMBENT SIGNAL DETECTION CERTAINTY RATE**

Trial	AWGN Detected (Yes / No)
	Incumbent AWGN at $f_{c1}$
1	Yes
2	Yes
3	Yes
4	Yes
5	Yes
6	Yes
7	Yes
8	Yes
9	Yes
10	Yes
<b>Test Result</b>	<b>PASS</b>

**Test Date: 2025-05-27**

**Tested by: 44352**

**Test location: 1-DFS-A**

A minimum detection rate of 90% is required for the EUT to be compliant.

### 8.5.5. Tx OPERATIONAL STATUS TEST RESULTS

**Test Condition 1: 99% BW<sub>EUT</sub> ≤ 99% BW<sub>INC</sub>**

**Incumbent AWGN at f<sub>c1</sub>:**

Measured Incumbent Power at the EUT Test Fixture Connector (dBm)	Test Fixture Cable Path Loss (dB)	Adjusted Incumbent Power at the Radio Port (dBm)	Antenna Gain (dBi)	Adjusted Incumbent Power at the Antenna (dBm)	Detection Limit (dBm)	EUT Tx Status
-63.84	2.8	-66.6	-3.00	-63.64	-62	Ceased
-64.83	2.8	-67.6	-3.00	-64.63	-62	Minimal
-65.76	2.8	-68.6	-3.00	-65.56	-62	Normal

**Test Date: 2025-05-27**

**Tested by: 44352**

**Test location: 1-DFS-A**

## 8.6. U-NII 5 BAND TEST CONDITION 1 RESULTS

### TEST CONDITION 1 CRITERIA

$$99\% \text{ BW}_{\text{EUT}} \leq 99\% \text{ BW}_{\text{INC}}$$

The lowest and highest supported channel bandwidths do not meet the criteria for this test condition therefore this test was not performed.

## 8.7. U-NII 5 BAND TEST CONDITION 2 RESULTS

### TEST CONDITION 2 CRITERIA

$$99\% \text{ BW}_{\text{INC}} < 99\% \text{ BW}_{\text{EUT}} \leq 2 \times 99\% \text{ BW}_{\text{INC}}$$

### 8.7.1. TEST CHANNEL


All tests were performed with the EUT set to a channel center frequency of 6 MHz and a nominal channel bandwidth of 20 MHz.

Only the lowest and highest supported channel bandwidths are required to be tested.


### 8.7.2. INCUMBENT SIGNAL PLOTS

All tests were performed with the Incumbent Signal frequency set to the test channel center frequency and a nominal 99% Occupied Power Bandwidth of 10 MHz.

**INCUMBENT SIGNAL 99% OCCUPIED POWER BANDWIDTH**




**MINIMUM PASSING INCUMBENT SIGNAL POWER AT TEST FIXTURE**




### 8.7.3. EUT TRANSMISSION PLOTS

#### EUT 99% OCCUPIED POWER BANDWIDTH




**TRAFFIC WITHOUT THE INCUMBENT SIGNAL PRESENT**



### EUT RESPONSE TO THE APPLIED INCUMBENT SIGNAL

A link between the EUT and the Companion Device was established on the test channel. Traffic flowing from the EUT to the Companion Device was then initiated. A sweep was started and the incumbent signal was continuously applied at approximately 3 seconds after the start of the sweep for a minimum duration of 10 seconds and removed after the end of the observation period. Markers are placed at the beginning and end of the observation period.



Normal Traffic

Application of Incumbent  
Transmissions Ceased

Incumbent Removed  
Transmissions Resume

Transmissions cease while the Incumbent AWGN Signal is present and resume after it is removed.

#### 8.7.4. TABULATED TEST RESULTS

##### INCUMBENT SIGNAL DETECTION RESULTS

<b>EUT Channel Center Frequency, <math>f_{c1}</math> (MHz)</b>	6135
<b>EUT Nominal Channel Bandwidth (MHz)</b>	20
<b>99% Occupied Bandwidth of the EUT (MHz)</b>	18.955
<b>EUT 99% OBW Lower Edge, <math>F_L</math> (MHz)</b>	6125.52
<b>EUT 99% OBW Upper Edge, <math>F_H</math> (MHz)</b>	6144.48
<b>Test Frequency of Incumbent Signal (MHz)</b>	<b>6135</b>
<b>Maximum Allowed Incumbent Amplitude at Antenna (dBm)</b>	-62
<b>Minimum Antenna Gain (dBi)</b>	-3.00
<b>Maximum Allowed Incumbent Amplitude at Radio Port (dBm)</b>	-65.00
<hr/>	
<b>Lowest Passing Measured Incumbent Signal Amplitude at Text Fixture(dBm)</b>	-65.20
<b>Text Fixture Cable Loss</b>	2.80
<b>Lowest Passing Measured Incumbent Signal Amplitude (dBm)</b>	-68.00
<b>Margin (dBm)</b>	-3.00
<b>Result (PASS / FAIL)</b>	<b>PASS</b>

**Test Date: 2025-05-19**

**Tested by: 44352**

**Test location: 1-DFS-A**

**INCUMBENT SIGNAL DETECTION CERTAINTY RATE**

Trial	AWGN Detected (Yes / No)
	Incumbent AWGN at $f_{c1}$
1	Yes
2	Yes
3	Yes
4	Yes
5	Yes
6	Yes
7	Yes
8	Yes
9	Yes
10	Yes
<b>Test Result</b>	<b>PASS</b>

**Test Date: 2025-05-19**

**Tested by: 44352**

**Test location: 1-DFS-A**

A minimum detection rate of 90% is required for the EUT to be compliant.

### 8.7.5. Tx OPERATIONAL STATUS TEST RESULTS

**Test Condition 2: 99% BW<sub>INC</sub> < 99% BW<sub>EUT</sub> ≤ 2 x 99% BW<sub>INC</sub>**

**Incumbent AWGN at f<sub>c1</sub>:**

Measured Incumbent Power at the EUT Test Fixture Connector (dBm)	Test Fixture Cable Path Loss (dB)	Adjusted Incumbent Power at the Radio Port (dBm)	Antenna Gain (dBi)	Adjusted Incumbent Power at the Antenna (dBm)	Detection Limit (dBm)	EUT Tx Status
-65.2	2.8	-68.0	-3.00	-65	-62	Ceased
-66.23	2.8	-69.0	-3.00	-66.03	-62	Minimal
-73.42	2.8	-76.2	-3.00	-73.22	-62	Normal

**Test Date: 2025-05-19**

**Tested by: 44352**

**Test location: 1-DFS-A**

## 8.8. U-NII 5 BAND TEST CONDITION 3 RESULTS

### TEST CONDITION 3 CRITERIA

$$2 \times 99\% \text{ BW}_{\text{INC}} < 99\% \text{ BW}_{\text{EUT}} \leq 4 \times 99\% \text{ BW}_{\text{INC}}$$

The lowest and highest supported channel bandwidths do not meet the criteria for this test condition therefore this test was not performed.

## 8.9. U-NII 5 BAND TEST CONDITION 4 RESULTS

### TEST CONDITION 4 CRITERIA

$$99\% \text{ BW}_{\text{EUT}} > 4 \times 99\% \text{ BW}_{\text{INC}}$$

#### 8.9.1. TEST CHANNEL

All tests were performed with the EUT set to a channel center frequency of 6185 MHz and a nominal channel bandwidth of 160 MHz.


Only the lowest and highest supported channel bandwidths are required to be tested.

#### 8.9.2. INCUMBENT SIGNAL PLOTS


All tests were performed with the Incumbent Signal frequency set to the test channel center frequency and a nominal 99% Occupied Power Bandwidth of 10 MHz.

**INCUMBENT SIGNAL 99% OCCUPIED POWER BANDWIDTH**


**Lower Edge Incumbent Signal  $f_{c2}$ :**



**Center Frequency Incumbent Signal  $f_{c1}$ :**




### Upper Edge Incumbent Signal $f_{c3}$ :




**MINIMUM PASSING INCUMBENT SIGNAL POWER AT TEST FIXTURE**


**Lower Edge Incumbent Signal  $f_{c2}$ :**



**Center Frequency Incumbent Signal  $f_{c1}$ :**




**Upper Edge Incumbent Signal  $f_{c3}$ :**




### 8.9.3. EUT TRANSMISSION PLOTS

#### EUT 99% OCCUPIED POWER BANDWIDTH




**TRAFFIC WITHOUT THE INCUMBENT SIGNAL PRESENT**


**Lower Edge  $f_{c2}$ :**



**Center Frequency fc1:**




Upper Edge fc3:



## EUT RESPONSE TO THE APPLIED INCUMBENT SIGNAL

A link between the EUT and the Companion Device was established on the test channel. Traffic flowing from the EUT to the Companion Device was then initiated. A sweep was started and the incumbent signal was continuously applied at approximately 3 seconds after the start of the sweep for a minimum duration of 10 seconds and removed after the end of the observation period. Markers are placed at the beginning and end of the observation period.

### Lower Edge Incumbent Signal $f_{c2}$ :




## Normal Traffic

## Application of Incumbent Transmissions Ceased

## Incumbent Removed Transmissions Resume

Transmissions cease on the incumbered channel while the Incumbent AWGN Signal is present with the bandwidth reducing from 160 MHz to 20 MHz and resume after it is removed.

**Center Frequency Incumbent Signal fc1:**




Normal Traffic

Application of Incumbent  
Transmissions Ceased

Incumbent Removed  
Transmissions Resume

Transmissions cease on the incumbered channel while the Incumbent AWGN Signal is present with the bandwidth reducing from 160 MHz to 40 MHz and resume after it is removed.

### Upper Edge Incumbent Signal fc3:



Normal Traffic


Application of Incumbent  
Transmissions Ceased

Incumbent Removed  
Transmissions Resume


Transmissions cease on the incumbered channel while the Incumbent AWGN Signal is present with the bandwidth reducing from 160 MHz to 80 MHz and resume after it is removed.

### EUT BANDWIDTH REDUCTION


The EUT is allowed to continue operating at a reduced bandwidth in the presence of the Incumbent Signal, so long as the EUT transmissions do not overlap with the channel used by the Incumbent Signal.



With the Incumbent Signal set to the Lower Edge  $f_{c2}$  the EUT continues to operate at a reduced 20MHz nominal bandwidth.



With the Incumbent Signal set to the Center  $f_{c1}$  the EUT continues to operate at a reduced 40MHz nominal bandwidth.



With the Incumbent Signal set to the upper edge  $f_{c3}$  the EUT continues to operate at a reduced 80MHz nominal bandwidth.

#### 8.9.4. TABULATED TEST RESULTS

##### INCUMBENT SIGNAL DETECTION RESULTS

EUT Channel Center Frequency, $f_{c1}$ (MHz)	6185
EUT Nominal Channel Bandwidth (MHz)	160
99% Occupied Bandwidth of the EUT (MHz)	155.19
EUT 99% OBW Lower Edge, $F_L$ (MHz)	6107.41
EUT 99% OBW Upper Edge, $F_H$ (MHz)	6262.60
99% Occupied Bandwidth of the Incumbent Signal (MHz)	10.007
Test Frequency of Incumbent Signal ( $f_{c2}$ ) Near EUT $F_L$ (MHz)	6113
Test Frequency of Incumbent Signal at $f_{c1}$ (MHz)	6185
Test Frequency of Incumbent Signal ( $f_{c3}$ ) Near EUT $F_H$ (MHz)	6257
Maximum Allowed Incumbent Amplitude at Antenna (dBm)	-62
Minimum Antenna Gain (dBi)	-3.00
Maximum Allowed Incumbent Amplitude at Radio Port (dBm)	-65.00
Lowest Passing Measured Incumbent Signal Amplitude at $f_{c2}$ at test fixture(dBm)	-71.86
Text Fixture Cable Loss	2.80
Lowest Passing Measured Incumbent Signal Amplitude at $f_{c2}$ (dBm)	-74.66
Margin (dBm)	-9.66
Result (PASS / FAIL)	PASS
Lowest Passing Measured Incumbent Signal Amplitude at $f_{c1}$ at test fixture(dBm)	-67.22
Text Fixture Cable Loss	2.80
Lowest Passing Measured Incumbent Signal Amplitude at $f_{c1}$ (dBm)	-70.02
Margin (dBm)	-5.02
Result (PASS / FAIL)	PASS
Lowest Passing Measured Incumbent Signal Amplitude at $f_{c3}$ at test fixture(dBm)	-71.98
Text Fixture Cable Loss	2.80
Lowest Passing Measured Incumbent Signal Amplitude at $f_{c3}$ (dBm)	-74.78
Margin (dBm)	-9.78
Result (PASS / FAIL)	PASS

**INCUMBENT SIGNAL DETECTION CERTAINTY RATE**

Trial	AWGN Detected (Yes / No)		
	Incumbent AWGN at $f_{c2}$	Incumbent AWGN at $f_{c1}$	Incumbent AWGN at $f_{c3}$
1	Yes	Yes	Yes
2	Yes	Yes	Yes
3	Yes	Yes	Yes
4	Yes	Yes	Yes
5	Yes	Yes	Yes
6	Yes	Yes	Yes
7	Yes	Yes	Yes
8	Yes	Yes	Yes
9	Yes	Yes	Yes
10	Yes	Yes	Yes
<b>Test Result</b>	<b>PASS</b>	<b>PASS</b>	<b>PASS</b>

**Test Date: 2025-05-19**

**Tested by: 44352**

**Test location: 1-DFS-A**

A minimum detection rate of 90% is required for the EUT to be compliant.

### 8.9.5. Tx OPERATIONAL STATUS TEST RESULTS

#### Test Condition 4: 99% BW<sub>EUT</sub> > 4 x 99% BW<sub>INC</sub>

##### Incumbent AWGN at f<sub>c2</sub>:

Measured Incumbent Power at the EUT Test Fixture Connector (dBm)	Test Fixture Cable Path Loss (dB)	Adjusted Incumbent Power at the Radio Port (dBm)	Antenna Gain (dBi)	Adjusted Incumbent Power at the Antenna (dBm)	Detection Limit (dBm)	EUT Tx Status
-71.86	2.8	-74.66	-3.00	-71.66	-62	Ceased
-72.71	2.8	-75.51	-3.00	-72.51	-62	Minimal
-74.88	2.8	-77.68	-3.00	-74.68	-62	Normal

##### Incumbent AWGN at f<sub>c1</sub>:

Measured Incumbent Power at the EUT Test Fixture Connector (dBm)	Test Fixture Cable Path Loss (dB)	Adjusted Incumbent Power at the Radio Port (dBm)	Antenna Gain (dBi)	Adjusted Incumbent Power at the Antenna (dBm)	Detection Limit (dBm)	EUT Tx Status
-67.22	2.8	-70.02	-3.00	-67.02	-62	Ceased
-67.94	2.8	-70.74	-3.00	-67.74	-62	Minimal
-70.89	2.8	-73.69	-3.00	-70.69	-62	Normal

##### Incumbent AWGN at f<sub>c3</sub>:

Measured Incumbent Power at the EUT Test Fixture Connector (dBm)	Test Fixture Cable Path Loss (dB)	Adjusted Incumbent Power at the Radio Port (dBm)	Antenna Gain (dBi)	Adjusted Incumbent Power at the Antenna (dBm)	Detection Limit (dBm)	EUT Tx Status
-71.98	2.8	-74.78	-3.00	-71.78	-62	Ceased
-72.74	2.8	-75.54	-3.00	-72.54	-62	Minimal
-73.9	2.8	-76.7	-3.00	-73.7	-62	Normal

**Test Date: 2025-05-19**

**Tested by: 44352**

**Test location: 1-DFS-A**

## 8.10. U-NII 6 BAND TEST CONDITION 1 RESULTS

### TEST CONDITION 1 CRITERIA

$$99\% \text{ BW}_{\text{EUT}} \leq 99\% \text{ BW}_{\text{INC}}$$

The lowest and highest supported channel bandwidths do not meet the criteria for this test condition therefore this test was not performed.

## 8.11. U-NII 6 BAND TEST CONDITION 2 RESULTS

### TEST CONDITION 2 CRITERIA

$$99\% \text{ BW}_{\text{INC}} < 99\% \text{ BW}_{\text{EUT}} \leq 2 \times 99\% \text{ BW}_{\text{INC}}$$

### 8.11.1. TEST CHANNEL


All tests were performed with the EUT set to a channel center frequency of 6455 MHz and a nominal channel bandwidth of 20 MHz.

Only the lowest and highest supported channel bandwidths are required to be tested.


### 8.11.2. INCUMBENT SIGNAL PLOTS

All tests were performed with the Incumbent Signal frequency set to the test channel center frequency and a nominal 99% Occupied Power Bandwidth of 10 MHz.

**INCUMBENT SIGNAL 99% OCCUPIED POWER BANDWIDTH**




**MINIMUM PASSING INCUMBENT SIGNAL POWER**




### 8.11.3. EUT TRANSMISSION PLOTS

#### EUT 99% OCCUPIED POWER BANDWIDTH




**TRAFFIC WITHOUT THE INCUMBENT SIGNAL PRESENT**



### EUT RESPONSE TO THE APPLIED INCUMBENT SIGNAL

A link between the EUT and the Companion Device was established on the test channel. Traffic flowing from the EUT to the Companion Device was then initiated. A sweep was started and the incumbent signal was continuously applied at approximately 3 seconds after the start of the sweep for a minimum duration of 10 seconds and removed after the end of the observation period. Markers are placed at the beginning and end of the observation period.



Normal Traffic

Application of Incumbent  
Transmissions Ceased

Incumbent Removed  
Transmissions Resume

Transmissions cease while the Incumbent AWGN Signal is present and resume after it is removed

#### 8.11.4. TABULATED TEST RESULTS

##### INCUMBENT SIGNAL DETECTION RESULTS

EUT Channel Center Frequency, $f_{c1}$ (MHz)	6455
EUT Nominal Channel Bandwidth (MHz)	20
99% Occupied Bandwidth of the EUT (MHz)	18.942
EUT 99% OBW Lower Edge, $F_L$ (MHz)	6445.53
EUT 99% OBW Upper Edge, $F_H$ (MHz)	6464.47
<b>Test Frequency of Incumbent Signal (MHz)</b>	<b>6455</b>
<b>Maximum Allowed Incumbent Amplitude at Antenna (dBm)</b>	<b>-62</b>
<b>Minimum Antenna Gain (dBi)</b>	<b>-2.40</b>
<b>Maximum Allowed Incumbent Amplitude at Radio Port (dBm)</b>	<b>-64.40</b>
<hr/>	
<b>Lowest Passing Measured Incumbent Signal Amplitude at Text Fixture(dBm)</b>	<b>-65.59</b>
<b>Text Fixture Cable Loss</b>	<b>2.80</b>
<b>Lowest Passing Measured Incumbent Signal Amplitude (dBm)</b>	<b>-68.39</b>
<b>Margin (dBm)</b>	<b>-3.99</b>
<b>Result (PASS / FAIL)</b>	<b>PASS</b>

**Test Date: 2025-05-19**

**Tested by: 44352**

**Test location: 1-DFS-A**

**INCUMBENT SIGNAL DETECTION CERTAINTY RATE**

Trial	AWGN Detected (Yes / No)
	Incumbent AWGN at $f_{c1}$
1	Yes
2	Yes
3	Yes
4	Yes
5	Yes
6	Yes
7	Yes
8	Yes
9	Yes
10	Yes
<b>Test Result</b>	<b>PASS</b>

**Test Date: 2025-05-19**

**Tested by: 44352**

**Test location: 1-DFS-A**

A minimum detection rate of 90% is required for the EUT to be compliant.

### 8.11.5. Tx OPERATIONAL STATUS TEST RESULTS

**Test Condition 2: 99% BW<sub>INC</sub> < 99% BW<sub>EUT</sub> ≤ 2 x 99% BW<sub>INC</sub>**

**Incumbent AWGN at f<sub>c1</sub>:**

Measured Incumbent Power at the EUT Test Fixture Connector (dBm)	Test Fixture Cable Path Loss (dB)	Adjusted Incumbent Power at the Radio Port (dBm)	Antenna Gain (dBi)	Adjusted Incumbent Power at the Antenna (dBm)	Detection Limit (dBm)	EUT Tx Status
-65.59	2.8	-68.4	-2.40	-65.99	-62	Ceased
-66.68	2.8	-69.5	-2.40	-67.08	-62	Minimal
-73.89	2.8	-76.7	-2.40	-74.29	-62	Normal

**Test Date: 2025-05-19**

**Tested by: 44352**

**Test location: 1-DFS-A**

## 8.12. U-NII 6 BAND TEST CONDITION 3 RESULTS

### TEST CONDITION 3 CRITERIA

$$2 \times 99\% \text{ BW}_{\text{INC}} < 99\% \text{ BW}_{\text{EUT}} \leq 4 \times 99\% \text{ BW}_{\text{INC}}$$

The lowest and highest supported channel bandwidths do not meet the criteria for this test condition therefore this test was not performed.

## 8.13. U-NII 6 BAND TEST CONDITION 4 RESULTS

### TEST CONDITION 4 CRITERIA

$$99\% \text{ BW}_{\text{EUT}} > 4 \times 99\% \text{ BW}_{\text{INC}}$$

#### 8.13.1. TEST CHANNEL

All tests were performed with the EUT set to a channel center frequency of 6505 MHz and a nominal channel bandwidth of 160 MHz.


Only the lowest and highest supported channel bandwidths are required to be tested.

#### 8.13.2. INCUMBENT SIGNAL PLOTS


All tests were performed with the Incumbent Signal frequency set to the test channel center frequency and a nominal 99% Occupied Power Bandwidth of 10 MHz.

**INCUMBENT SIGNAL 99% OCCUPIED POWER BANDWIDTH**


**Lower Edge Incumbent Signal  $f_{c2}$ :**



**Center Frequency Incumbent Signal  $f_{c1}$ :**




**Upper Edge Incumbent Signal  $f_{c3}$ :**




**MINIMUM PASSING INCUMBENT SIGNAL POWER**


**Lower Edge Incumbent Signal  $f_{c2}$ :**



**Center Frequency Incumbent Signal  $f_{c1}$ :**




**Upper Edge Incumbent Signal  $f_{c3}$ :**




### 8.13.3. EUT TRANSMISSION PLOTS

#### EUT 99% OCCUPIED POWER BANDWIDTH




**TRAFFIC WITHOUT THE INCUMBENT SIGNAL PRESENT**


**Lower Edge  $f_{c2}$ :**



**Center Frequency fc1:**




Upper Edge fc3:



### EUT RESPONSE TO THE APPLIED INCUMBENT SIGNAL

A link between the EUT and the Companion Device was established on the test channel. Traffic flowing from the EUT to the Companion Device was then initiated. A sweep was started and the incumbent signal was continuously applied at approximately 3 seconds after the start of the sweep for a minimum duration of 10 seconds and removed after the end of the observation period. Markers are placed at the beginning and end of the observation period.

#### Lower Edge Incumbent Signal $f_{c2}$ :




Normal Traffic

Application of Incumbent  
Transmissions Ceased

Incumbent Removed  
Transmissions Resume

Transmissions cease on the incumbered channel while the Incumbent AWGN Signal is present with the bandwidth reducing from 160 MHz to 20 MHz on an adjacent channel and resume after it is removed.

**Center Frequency Incumbent Signal  $f_{c1}$ :**




Normal Traffic

Application of Incumbent Transmissions Ceased

Incumbent Removed Transmissions Resume

Transmissions cease on the incumbered channel while the Incumbent AWGN Signal is present with the bandwidth reducing from 160 MHz to 40 MHz on an adjacent channel and resume after it is removed.

**Upper Edge Incumbent Signal fc3:**



Normal Traffic


Application of Incumbent Transmissions Ceased

Incumbent Removed Transmissions Resume


Transmissions cease on the incumbered channel while the Incumbent AWGN Signal is present with the bandwidth reducing from 160 MHz to 80 MHz on an adjacent and resume after it is removed.

### EUT BANDWIDTH REDUCTION


The EUT is allowed to continue operating at a reduced bandwidth in the presence of the Incumbent Signal, so long as the EUT transmissions do not overlap with the channel used by the Incumbent Signal.



With the Incumbent Signal set to the Lower Edge  $f_{c2}$  the EUT continues to operate at a reduced 20MHz nominal bandwidth.



With the Incumbent Signal set to the Center  $f_{c1}$  the EUT continues to operate at a reduced 40MHz nominal bandwidth.



With the Incumbent Signal set to the upper edge  $f_{c3}$  the EUT continues to operate at a reduced 80MHz nominal bandwidth.

### 8.13.4. TABULATED TEST RESULTS

#### INCUMBENT SIGNAL DETECTION RESULTS

EUT Channel Center Frequency, $f_{c1}$ (MHz)	6505
EUT Nominal Channel Bandwidth (MHz)	160
99% Occupied Bandwidth of the EUT (MHz)	155.02
EUT 99% OBW Lower Edge, $F_L$ (MHz)	6427.49
EUT 99% OBW Upper Edge, $F_H$ (MHz)	6582.51
99% Occupied Bandwidth of the Incumbent Signal (MHz)	10.011
Test Frequency of Incumbent Signal ( $f_{c2}$ ) Near EUT $F_L$ (MHz)	6433
Test Frequency of Incumbent Signal at $f_{c1}$ (MHz)	6505
Test Frequency of Incumbent Signal ( $f_{c3}$ ) Near EUT $F_H$ (MHz)	6577
Maximum Allowed Incumbent Amplitude at Antenna (dBm)	-62
Minimum Antenna Gain (dBi)	-2.40
Maximum Allowed Incumbent Amplitude at Radio Port (dBm)	-64.40
Lowest Passing Measured Incumbent Signal Amplitude at $f_{c2}$ at test fixture(dBm)	-69.64
Text Fixture Cable Loss	2.80
Lowest Passing Measured Incumbent Signal Amplitude at $f_{c2}$ (dBm)	-72.44
Margin (dBm)	-8.04
Result (PASS / FAIL)	PASS
Lowest Passing Measured Incumbent Signal Amplitude at $f_{c1}$ at test fixture(dBm)	-68.30
Text Fixture Cable Loss	2.80
Lowest Passing Measured Incumbent Signal Amplitude at $f_{c1}$ (dBm)	-71.10
Margin (dBm)	-6.70
Result (PASS / FAIL)	PASS
Lowest Passing Measured Incumbent Signal Amplitude at $f_{c3}$ at test fixture(dBm)	-70.83
Text Fixture Cable Loss	2.80
Lowest Passing Measured Incumbent Signal Amplitude at $f_{c3}$ (dBm)	-73.63
Margin (dBm)	-9.23
Result (PASS / FAIL)	PASS

**INCUMBENT SIGNAL DETECTION CERTAINTY RATE**

Trial	AWGN Detected (Yes / No)		
	Incumbent AWGN at $f_{c2}$	Incumbent AWGN at $f_{c1}$	Incumbent AWGN at $f_{c3}$
1	Yes	Yes	Yes
2	Yes	Yes	Yes
3	Yes	Yes	Yes
4	Yes	Yes	Yes
5	Yes	Yes	Yes
6	Yes	Yes	Yes
7	Yes	Yes	Yes
8	Yes	Yes	Yes
9	Yes	Yes	Yes
10	Yes	Yes	Yes
<b>Test Result</b>	<b>PASS</b>	<b>PASS</b>	<b>PASS</b>

**Test Date: 2025-05-19**

**Tested by: 44352**

**Test location: 1-DFS-A**

A minimum detection rate of 90% is required for the EUT to be compliant.

### 8.13.5. Tx OPERATIONAL STATUS TEST RESULTS

#### Test Condition 4: 99% BW<sub>EUT</sub> > 4 x 99% BW<sub>INC</sub>

##### Incumbent AWGN at f<sub>c2</sub>:

Measured Incumbent Power at the EUT Test Fixture Connector (dBm)	Test Fixture Cable Path Loss (dB)	Adjusted Incumbent Power at the Radio Port (dBm)	Antenna Gain (dBi)	Adjusted Incumbent Power at the Antenna (dBm)	Detection Limit (dBm)	EUT Tx Status
-69.64	2.8	-72.44	-2.40	-70.04	-62	Ceased
-71.67	2.8	-74.47	-2.40	-72.07	-62	Minimal
-74.93	2.8	-77.73	-2.40	-75.33	-62	Normal

##### Incumbent AWGN at f<sub>c1</sub>:

Measured Incumbent Power at the EUT Test Fixture Connector (dBm)	Test Fixture Cable Path Loss (dB)	Adjusted Incumbent Power at the Radio Port (dBm)	Antenna Gain (dBi)	Adjusted Incumbent Power at the Antenna (dBm)	Detection Limit (dBm)	EUT Tx Status
-68.3	2.8	-71.1	-2.40	-68.7	-62	Ceased
-69.26	2.8	-72.06	-2.40	-69.66	-62	Minimal
-72.28	2.8	-75.08	-2.40	-72.68	-62	Normal

##### Incumbent AWGN at f<sub>c3</sub>:

Measured Incumbent Power at the EUT Test Fixture Connector (dBm)	Test Fixture Cable Path Loss (dB)	Adjusted Incumbent Power at the Radio Port (dBm)	Antenna Gain (dBi)	Adjusted Incumbent Power at the Antenna (dBm)	Detection Limit (dBm)	EUT Tx Status
-70.83	2.8	-73.63	-2.40	-71.23	-62	Ceased
-71.88	2.8	-74.68	-2.40	-72.28	-62	Minimal
-73.87	2.8	-76.67	-2.40	-74.27	-62	Normal

**Test Date: 2025-05-19**

**Tested by: 44352**

**Test location: 1-DFS-A**

## 8.14. U-NII 7 BAND TEST CONDITION 1 RESULTS

### TEST CONDITION 1 CRITERIA

$$99\% \text{ BW}_{\text{EUT}} \leq 99\% \text{ BW}_{\text{INC}}$$

The lowest and highest supported channel bandwidths do not meet the criteria for this test condition therefore this test was not performed.

## 8.15. U-NII 7 BAND TEST CONDITION 2 RESULTS

### TEST CONDITION 2 CRITERIA

$$99\% \text{ BW}_{\text{INC}} < 99\% \text{ BW}_{\text{EUT}} \leq 2 \times 99\% \text{ BW}_{\text{INC}}$$

### 8.15.1. TEST CHANNEL


All tests were performed with the EUT set to a channel center frequency of 6695 MHz and a nominal channel bandwidth of 20 MHz.

Only the lowest and highest supported channel bandwidths are required to be tested.


### 8.15.2. INCUMBENT SIGNAL PLOTS

All tests were performed with the Incumbent Signal frequency set to the test channel center frequency and a nominal 99% Occupied Power Bandwidth of 10 MHz.

**INCUMBENT SIGNAL 99% OCCUPIED POWER BANDWIDTH**




**MINIMUM PASSING INCUMBENT SIGNAL POWER**




### 8.15.3. EUT TRANSMISSION PLOTS

#### EUT 99% OCCUPIED POWER BANDWIDTH




**TRAFFIC WITHOUT THE INCUMBENT SIGNAL PRESENT**



### EUT RESPONSE TO THE APPLIED INCUMBENT SIGNAL

A link between the EUT and the Companion Device was established on the test channel. Traffic flowing from the EUT to the Companion Device was then initiated. A sweep was started and the incumbent signal was continuously applied at approximately 3 seconds after the start of the sweep for a minimum duration of 10 seconds and removed after the end of the observation period. Markers are placed at the beginning and end of the observation period.



Normal Traffic

Application of Incumbent  
Transmissions Ceased

Incumbent Removed  
Transmissions Resume

Transmissions cease while the Incumbent AWGN Signal is present and resume after it is removed

#### 8.15.4. TABULATED TEST RESULTS

##### INCUMBENT SIGNAL DETECTION RESULTS

<b>EUT Channel Center Frequency, <math>f_{c1}</math> (MHz)</b>	6695
<b>EUT Nominal Channel Bandwidth (MHz)</b>	20
<b>99% Occupied Bandwidth of the EUT (MHz)</b>	18.974
<b>EUT 99% OBW Lower Edge, <math>F_L</math> (MHz)</b>	6685.51
<b>EUT 99% OBW Upper Edge, <math>F_H</math> (MHz)</b>	6704.49
<b>Test Frequency of Incumbent Signal (MHz)</b>	<b>6695</b>
<b>Maximum Allowed Incumbent Amplitude at Antenna (dBm)</b>	-62
<b>Minimum Antenna Gain (dBi)</b>	-2.00
<b>Maximum Allowed Incumbent Amplitude at Radio Port (dBm)</b>	-64.00
<hr/>	
<b>Lowest Passing Measured Incumbent Signal Amplitude at Text Fixture(dBm)</b>	-64.87
<b>Text Fixture Cable Loss</b>	2.80
<b>Lowest Passing Measured Incumbent Signal Amplitude (dBm)</b>	-67.67
<b>Margin (dBm)</b>	-3.67
<b>Result (PASS / FAIL)</b>	<b>PASS</b>

**Test Date: 2025-05-19**

**Tested by: 44352**

**Test location: 1-DFS-A**

**INCUMBENT SIGNAL DETECTION CERTAINTY RATE**

Trial	AWGN Detected (Yes / No)
	Incumbent AWGN at $f_{c1}$
1	Yes
2	Yes
3	Yes
4	Yes
5	Yes
6	Yes
7	Yes
8	Yes
9	Yes
10	Yes
<b>Test Result</b>	<b>PASS</b>

**Test Date: 2025-05-19**

**Tested by: 44352**

**Test location: 1-DFS-A**

A minimum detection rate of 90% is required for the EUT to be compliant.

### 8.15.5. Tx OPERATIONAL STATUS TEST RESULTS

**Test Condition 2: 99% BW<sub>INC</sub> < 99% BW<sub>EUT</sub> ≤ 2 x 99% BW<sub>INC</sub>**

**Incumbent AWGN at f<sub>c1</sub>:**

Measured Incumbent Power at the EUT Test Fixture Connector (dBm)	Test Fixture Cable Path Loss (dB)	Adjusted Incumbent Power at the Radio Port (dBm)	Antenna Gain (dBi)	Adjusted Incumbent Power at the Antenna (dBm)	Detection Limit (dBm)	EUT Tx Status
-64.87	2.8	-67.7	-2.00	-65.67	-62	Ceased
-66.13	2.8	-68.9	-2.00	-66.93	-62	Minimal
-74.6	2.8	-77.4	-2.00	-75.4	-62	Normal

**Test Date: 2025-05-19**

**Tested by: 44352**

**Test location: 1-DFS-A**

## 8.16. U-NII 7 BAND TEST CONDITION 3 RESULTS

### TEST CONDITION 3 CRITERIA

$$2 \times 99\% \text{ BW}_{\text{INC}} < 99\% \text{ BW}_{\text{EUT}} \leq 4 \times 99\% \text{ BW}_{\text{INC}}$$

The lowest and highest supported channel bandwidths do not meet the criteria for this test condition therefore this test was not performed.

## 8.17. U-NII 7 BAND TEST CONDITION 4 RESULTS

### TEST CONDITION 4 CRITERIA

$$99\% \text{ BW}_{\text{EUT}} > 4 \times 99\% \text{ BW}_{\text{INC}}$$

#### 8.17.1. TEST CHANNEL

All tests were performed with the EUT set to a channel center frequency of 6665 MHz and a nominal channel bandwidth of 160 MHz.


Only the lowest and highest supported channel bandwidths are required to be tested.

#### 8.17.2. INCUMBENT SIGNAL PLOTS


All tests were performed with the Incumbent Signal frequency set to the test channel center frequency and a nominal 99% Occupied Power Bandwidth of 10 MHz.

**INCUMBENT SIGNAL 99% OCCUPIED POWER BANDWIDTH**


**Lower Edge Incumbent Signal  $f_{c2}$ :**



**Center Frequency Incumbent Signal  $f_{c1}$ :**




**Upper Edge Incumbent Signal  $f_{c3}$ :**




**MINIMUM PASSING INCUMBENT SIGNAL POWER**


**Lower Edge Incumbent Signal  $f_{c2}$ :**



**Center Frequency Incumbent Signal  $f_{c1}$ :**




**Upper Edge Incumbent Signal  $f_{c3}$ :**




### 8.17.3. EUT TRANSMISSION PLOTS

#### EUT 99% OCCUPIED POWER BANDWIDTH




**TRAFFIC WITHOUT THE INCUMBENT SIGNAL PRESENT**


**Lower Edge  $f_{c2}$ :**



**Center Frequency fc1:**




Upper Edge fc3:



### EUT RESPONSE TO THE APPLIED INCUMBENT SIGNAL

A link between the EUT and the Companion Device was established on the test channel. Traffic flowing from the EUT to the Companion Device was then initiated. A sweep was started and the incumbent signal was continuously applied at approximately 3 seconds after the start of the sweep for a minimum duration of 10 seconds and removed after the end of the observation period. Markers are placed at the beginning and end of the observation period.

#### Lower Edge Incumbent Signal $f_{c2}$ :




Normal Traffic

Application of Incumbent  
Transmissions Ceased

Incumbent Removed  
Transmissions Resume

Transmissions cease on the incumbered channel while the Incumbent AWGN Signal is present with the bandwidth reducing from 160 MHz to 80 MHz on an adjacent channel and resume after it is removed.

**Center Frequency Incumbent Signal  $f_{c1}$ :**




Normal Traffic

Application of Incumbent Transmissions Ceased

Incumbent Removed Transmissions Resume

Transmissions cease on the incumbered channel while the Incumbent AWGN Signal is present with the bandwidth reducing from 160 MHz to 20 MHz on an adjacent channel and resume after it is removed.

## Upper Edge Incumbent Signal $f_{C3}$ :



### Normal Traffic


## Application of Incumbent Transmissions Ceased

## Incumbent Removed Transmissions Resume


Transmissions cease on the incumbent channel while the Incumbent AWGN Signal is present with the bandwidth reducing from 160 MHz to 40 MHz on an adjacent and resume after it is removed.

### EUT BANDWIDTH REDUCTION


The EUT is allowed to continue operating at a reduced bandwidth in the presence of the Incumbent Signal, so long as the EUT transmissions do not overlap with the channel used by the Incumbent Signal.



With the Incumbent Signal set to the Lower Edge  $f_{c2}$  the EUT continues to operate at a reduced 80MHz nominal bandwidth.



With the Incumbent Signal set to the Center  $f_{c1}$  the EUT continues to operate at a reduced 20MHz nominal bandwidth.



With the Incumbent Signal set to the upper edge  $f_{c3}$  the EUT continues to operate at a reduced 40MHz nominal bandwidth.

#### 8.17.4. TABULATED TEST RESULTS

##### INCUMBENT SIGNAL DETECTION RESULTS

EUT Channel Center Frequency, $f_{c1}$ (MHz)	6665
EUT Nominal Channel Bandwidth (MHz)	160
99% Occupied Bandwidth of the EUT (MHz)	156
EUT 99% OBW Lower Edge, $F_L$ (MHz)	6587.00
EUT 99% OBW Upper Edge, $F_H$ (MHz)	6743.00
99% Occupied Bandwidth of the Incumbent Signal (MHz)	9.9772
Test Frequency of Incumbent Signal ( $f_{c2}$ ) Near EUT $F_L$ (MHz)	6592
Test Frequency of Incumbent Signal at $f_{c1}$ (MHz)	6665
Test Frequency of Incumbent Signal ( $f_{c3}$ ) Near EUT $F_H$ (MHz)	6738
Maximum Allowed Incumbent Amplitude at Antenna (dBm)	-62
Minimum Antenna Gain (dBi)	-2.00
Maximum Allowed Incumbent Amplitude at Radio Port (dBm)	-64.00
Lowest Passing Measured Incumbent Signal Amplitude at $f_{c2}$ at test fixture(dBm)	-69.53
Text Fixture Cable Loss	2.80
Lowest Passing Measured Incumbent Signal Amplitude at $f_{c2}$ (dBm)	-72.33
Margin (dBm)	-8.33
Result (PASS / FAIL)	PASS
Lowest Passing Measured Incumbent Signal Amplitude at $f_{c1}$ at test fixture(dBm)	-66.80
Text Fixture Cable Loss	2.80
Lowest Passing Measured Incumbent Signal Amplitude at $f_{c1}$ (dBm)	-69.60
Margin (dBm)	-5.60
Result (PASS / FAIL)	PASS
Lowest Passing Measured Incumbent Signal Amplitude at $f_{c3}$ at test fixture(dBm)	-69.44
Text Fixture Cable Loss	2.80
Lowest Passing Measured Incumbent Signal Amplitude at $f_{c3}$ (dBm)	-72.24
Margin (dBm)	-8.24
Result (PASS / FAIL)	PASS

**INCUMBENT SIGNAL DETECTION CERTAINTY RATE**

Trial	AWGN Detected (Yes / No)		
	Incumbent AWGN at $f_{c2}$	Incumbent AWGN at $f_{c1}$	Incumbent AWGN at $f_{c3}$
1	Yes	Yes	Yes
2	Yes	Yes	Yes
3	Yes	Yes	Yes
4	Yes	Yes	Yes
5	Yes	Yes	Yes
6	Yes	Yes	Yes
7	Yes	Yes	Yes
8	Yes	Yes	Yes
9	Yes	Yes	Yes
10	Yes	Yes	Yes
<b>Test Result</b>	<b>PASS</b>	<b>PASS</b>	<b>PASS</b>

**Test Date: 2025-05-19**

**Tested by: 44352**

**Test location: 1-DFS-A**

A minimum detection rate of 90% is required for the EUT to be compliant.

### 8.17.5. Tx OPERATIONAL STATUS TEST RESULTS

#### Test Condition 4: 99% BW<sub>EUT</sub> > 4 x 99% BW<sub>INC</sub>

##### Incumbent AWGN at f<sub>c2</sub>:

Measured Incumbent Power at the EUT Test Fixture Connector (dBm)	Test Fixture Cable Path Loss (dB)	Adjusted Incumbent Power at the Radio Port (dBm)	Antenna Gain (dBi)	Adjusted Incumbent Power at the Antenna (dBm)	Detection Limit (dBm)	EUT Tx Status
-69.53	2.8	-72.33	-2.00	-70.33	-62	Ceased
-70.85	2.8	-73.65	-2.00	-71.65	-62	Minimal
-74.83	2.8	-77.63	-2.00	-75.63	-62	Normal

##### Incumbent AWGN at f<sub>c1</sub>:

Measured Incumbent Power at the EUT Test Fixture Connector (dBm)	Test Fixture Cable Path Loss (dB)	Adjusted Incumbent Power at the Radio Port (dBm)	Antenna Gain (dBi)	Adjusted Incumbent Power at the Antenna (dBm)	Detection Limit (dBm)	EUT Tx Status
-66.8	2.8	-69.6	-2.00	-67.6	-62	Ceased
-69.23	2.8	-72.03	-2.00	-70.03	-62	Minimal
-73.4	2.8	-76.2	-2.00	-74.2	-62	Normal

##### Incumbent AWGN at f<sub>c3</sub>:

Measured Incumbent Power at the EUT Test Fixture Connector (dBm)	Test Fixture Cable Path Loss (dB)	Adjusted Incumbent Power at the Radio Port (dBm)	Antenna Gain (dBi)	Adjusted Incumbent Power at the Antenna (dBm)	Detection Limit (dBm)	EUT Tx Status
-69.44	2.8	-72.24	-2.00	-70.24	-62	Ceased
-70.82	2.8	-73.62	-2.00	-71.62	-62	Minimal
-72.96	2.8	-75.76	-2.00	-73.76	-62	Normal

**Test Date: 2025-05-19**

**Tested by: 44352**

**Test location: 1-DFS-A**

## 8.18. U-NII 8 BAND TEST CONDITION 1 RESULTS

### TEST CONDITION 1 CRITERIA

$$99\% \text{ BW}_{\text{EUT}} \leq 99\% \text{ BW}_{\text{INC}}$$

The lowest and highest supported channel bandwidths do not meet the criteria for this test condition therefore this test was not performed.

## 8.19. U-NII 8 BAND TEST CONDITION 2 RESULTS

### TEST CONDITION 2 CRITERIA

$$99\% \text{ BW}_{\text{INC}} < 99\% \text{ BW}_{\text{EUT}} \leq 2 \times 99\% \text{ BW}_{\text{INC}}$$

### 8.19.1. TEST CHANNEL


All tests were performed with the EUT set to a channel center frequency of 6935 MHz and a nominal channel bandwidth of 20 MHz.

Only the lowest and highest supported channel bandwidths are required to be tested.


### 8.19.2. INCUMBENT SIGNAL PLOTS

All tests were performed with the Incumbent Signal frequency set to the test channel center frequency and a nominal 99% Occupied Power Bandwidth of 10 MHz.

**INCUMBENT SIGNAL 99% OCCUPIED POWER BANDWIDTH**




**MINIMUM PASSING INCUMBENT SIGNAL POWER**




### 8.19.3. EUT TRANSMISSION PLOTS

#### EUT 99% OCCUPIED POWER BANDWIDTH




**TRAFFIC WITHOUT THE INCUMBENT SIGNAL PRESENT**



### EUT RESPONSE TO THE APPLIED INCUMBENT SIGNAL

A link between the EUT and the Companion Device was established on the test channel. Traffic flowing from the EUT to the Companion Device was then initiated. A sweep was started and the incumbent signal was continuously applied at approximately 3 seconds after the start of the sweep for a minimum duration of 10 seconds and removed after the end of the observation period. Markers are placed at the beginning and end of the observation period.



Normal Traffic

Application of Incumbent  
Transmissions Ceased

Incumbent Removed  
Transmissions Resume

Transmissions cease while the Incumbent AWGN Signal is present and resume after it is removed

#### 8.19.4. TABULATED TEST RESULTS

##### INCUMBENT SIGNAL DETECTION RESULTS

<b>EUT Channel Center Frequency, <math>f_{c1}</math> (MHz)</b>	6935
<b>EUT Nominal Channel Bandwidth (MHz)</b>	20
<b>99% Occupied Bandwidth of the EUT (MHz)</b>	18.943
<b>EUT 99% OBW Lower Edge, <math>F_L</math> (MHz)</b>	6925.53
<b>EUT 99% OBW Upper Edge, <math>F_H</math> (MHz)</b>	6944.47
<b>Test Frequency of Incumbent Signal (MHz)</b>	<b>6935</b>
<b>Maximum Allowed Incumbent Amplitude at Antenna (dBm)</b>	-62
<b>Minimum Antenna Gain (dBi)</b>	-4.20
<b>Maximum Allowed Incumbent Amplitude at Radio Port (dBm)</b>	-66.20
<hr/>	
<b>Lowest Passing Measured Incumbent Signal Amplitude at Text Fixture(dBm)</b>	-65.26
<b>Text Fixture Cable Loss</b>	2.80
<b>Lowest Passing Measured Incumbent Signal Amplitude (dBm)</b>	-68.06
<b>Margin (dBm)</b>	-1.86
<b>Result (PASS / FAIL)</b>	<b>PASS</b>

**Test Date: 2025-05-19**

**Tested by: 44352**

**Test location: 1-DFS-A**

**INCUMBENT SIGNAL DETECTION CERTAINTY RATE**

Trial	AWGN Detected (Yes / No)
	Incumbent AWGN at $f_{c1}$
1	Yes
2	Yes
3	Yes
4	Yes
5	Yes
6	Yes
7	Yes
8	Yes
9	Yes
10	Yes
<b>Test Result</b>	<b>PASS</b>

**Test Date: 2025-05-19**

**Tested by: 44352**

**Test location: 1-DFS-A**

A minimum detection rate of 90% is required for the EUT to be compliant.

### 8.19.5. Tx OPERATIONAL STATUS TEST RESULTS

Test Condition 2:  $99\% \text{ BW}_{\text{INC}} < 99\% \text{ BW}_{\text{EUT}} \leq 2 \times 99\% \text{ BW}_{\text{INC}}$

Incumbent AWGN at  $f_{c1}$ :

Measured Incumbent Power at the EUT Test Fixture Connector (dBm)	Test Fixture Cable Path Loss (dB)	Adjusted Incumbent Power at the Radio Port (dBm)	Antenna Gain (dBi)	Adjusted Incumbent Power at the Antenna (dBm)	Detection Limit (dBm)	EUT Tx Status
-65.26	2.8	-68.1	-4.20	-63.86	-62	Ceased
-67.62	2.8	-70.4	-4.20	-66.22	-62	Minimal
-75.55	2.8	-78.4	-4.20	-74.15	-62	Normal

**Test Date: 2025-05-19**

**Tested by: 44352**

**Test location: 1-DFS-A**

## 8.20. U-NII 8 BAND TEST CONDITION 3 RESULTS

### TEST CONDITION 3 CRITERIA

$$2 \times 99\% \text{ BW}_{\text{INC}} < 99\% \text{ BW}_{\text{EUT}} \leq 4 \times 99\% \text{ BW}_{\text{INC}}$$

The lowest and highest supported channel bandwidths do not meet the criteria for this test condition therefore this test was not performed.

## 8.21. U-NII 8 BAND TEST CONDITION 4 RESULTS

### TEST CONDITION 4 CRITERIA

$$99\% \text{ BW}_{\text{EUT}} > 4 \times 99\% \text{ BW}_{\text{INC}}$$

#### 8.21.1. TEST CHANNEL

All tests were performed with the EUT set to a channel center frequency of 6985 MHz and a nominal channel bandwidth of 160 MHz.


Only the lowest and highest supported channel bandwidths are required to be tested.

#### 8.21.2. INCUMBENT SIGNAL PLOTS


All tests were performed with the Incumbent Signal frequency set to the test channel center frequency and a nominal 99% Occupied Power Bandwidth of 10 MHz.

**INCUMBENT SIGNAL 99% OCCUPIED POWER BANDWIDTH**


**Lower Edge Incumbent Signal  $f_{c2}$ :**



**Center Frequency Incumbent Signal  $f_{c1}$ :**




**Upper Edge Incumbent Signal  $f_{c3}$ :**




**MINIMUM PASSING INCUMBENT SIGNAL POWER**


**Lower Edge Incumbent Signal  $f_{c2}$ :**



**Center Frequency Incumbent Signal  $f_{c1}$ :**




**Upper Edge Incumbent Signal  $f_{c3}$ :**




### 8.21.3. EUT TRANSMISSION PLOTS

#### EUT 99% OCCUPIED POWER BANDWIDTH




**TRAFFIC WITHOUT THE INCUMBENT SIGNAL PRESENT**


**Lower Edge  $f_{c2}$ :**



**Center Frequency fc1:**




Upper Edge fc3:



### EUT RESPONSE TO THE APPLIED INCUMBENT SIGNAL

A link between the EUT and the Companion Device was established on the test channel. Traffic flowing from the EUT to the Companion Device was then initiated. A sweep was started and the incumbent signal was continuously applied at approximately 3 seconds after the start of the sweep for a minimum duration of 10 seconds and removed after the end of the observation period. Markers are placed at the beginning and end of the observation period.

#### Lower Edge Incumbent Signal $f_{c2}$ :




Normal Traffic

Application of Incumbent  
Transmissions Ceased

Incumbent Removed  
Transmissions Resume

Transmissions cease on the incumbered channel while the Incumbent AWGN Signal is present with the bandwidth reducing from 160 MHz to 20 MHz on an adjacent channel and resume after it is removed.

**Center Frequency Incumbent Signal fc1:**




Normal Traffic

Application of Incumbent  
Transmissions Ceased

Incumbent Removed  
Transmissions Resume

Transmissions cease on the incumbered channel while the Incumbent AWGN Signal is present with the bandwidth reducing from 160 MHz to 40 MHz on an adjacent channel and resume after it is removed.


**Upper Edge Incumbent Signal fc3:**




Transmissions cease on the incumbered channel while the Incumbent AWGN Signal is present with the bandwidth reducing from 160 MHz to 80 MHz on an adjacent and resume after it is removed.

### EUT BANDWIDTH REDUCTION


The EUT is allowed to continue operating at a reduced bandwidth in the presence of the Incumbent Signal, so long as the EUT transmissions do not overlap with the channel used by the Incumbent Signal.



With the Incumbent Signal set to the Lower Edge  $f_{c2}$  the EUT continues to operate at a reduced 20MHz nominal bandwidth.



With the Incumbent Signal set to the Center  $f_{c1}$  the EUT continues to operate at a reduced 40MHz nominal bandwidth.



With the Incumbent Signal set to the upper edge  $f_{c3}$  the EUT continues to operate at a reduced 80MHz nominal bandwidth.

#### 8.21.4. TABULATED TEST RESULTS

##### INCUMBENT SIGNAL DETECTION RESULTS

EUT Channel Center Frequency, $f_{c1}$ (MHz)	6985
EUT Nominal Channel Bandwidth (MHz)	160
99% Occupied Bandwidth of the EUT (MHz)	155.95
EUT 99% OBW Lower Edge, $F_L$ (MHz)	6907.03
EUT 99% OBW Upper Edge, $F_H$ (MHz)	7062.98
99% Occupied Bandwidth of the Incumbent Signal (MHz)	10.043
Test Frequency of Incumbent Signal ( $f_{c2}$ ) Near EUT $F_L$ (MHz)	6913
Test Frequency of Incumbent Signal at $f_{c1}$ (MHz)	6985
Test Frequency of Incumbent Signal ( $f_{c3}$ ) Near EUT $F_H$ (MHz)	7057
Maximum Allowed Incumbent Amplitude at Antenna (dBm)	-62
Minimum Antenna Gain (dBi)	-4.20
Maximum Allowed Incumbent Amplitude at Radio Port (dBm)	-66.20
Lowest Passing Measured Incumbent Signal Amplitude at $f_{c2}$ at test fixture(dBm)	-72.41
Text Fixture Cable Loss	2.80
Lowest Passing Measured Incumbent Signal Amplitude at $f_{c2}$ (dBm)	-75.21
Margin (dBm)	-9.01
Result (PASS / FAIL)	PASS
Lowest Passing Measured Incumbent Signal Amplitude at $f_{c1}$ at test fixture(dBm)	-67.45
Text Fixture Cable Loss	2.80
Lowest Passing Measured Incumbent Signal Amplitude at $f_{c1}$ (dBm)	-70.25
Margin (dBm)	-4.05
Result (PASS / FAIL)	PASS
Lowest Passing Measured Incumbent Signal Amplitude at $f_{c3}$ at test fixture(dBm)	-72.26
Text Fixture Cable Loss	2.80
Lowest Passing Measured Incumbent Signal Amplitude at $f_{c3}$ (dBm)	-75.06
Margin (dBm)	-8.86
Result (PASS / FAIL)	PASS

**INCUMBENT SIGNAL DETECTION CERTAINTY RATE**

Trial	AWGN Detected (Yes / No)		
	Incumbent AWGN at $f_{c2}$	Incumbent AWGN at $f_{c1}$	Incumbent AWGN at $f_{c3}$
1	Yes	Yes	Yes
2	Yes	Yes	Yes
3	Yes	Yes	Yes
4	Yes	Yes	Yes
5	Yes	Yes	Yes
6	Yes	Yes	Yes
7	Yes	Yes	Yes
8	Yes	Yes	Yes
9	Yes	Yes	Yes
10	Yes	Yes	Yes
<b>Test Result</b>	<b>PASS</b>	<b>PASS</b>	<b>PASS</b>

**Test Date: 2025-05-19**

**Tested by: 44352**

**Test location: 1-DFS-A**

A minimum detection rate of 90% is required for the EUT to be compliant.

### 8.21.5. Tx OPERATIONAL STATUS TEST RESULTS

#### Test Condition 4: 99% BW<sub>EUT</sub> > 4 x 99% BW<sub>INC</sub>

Incumbent AWGN at f<sub>c2</sub>:

Measured Incumbent Power at the EUT Test Fixture Connector (dBm)	Test Fixture Cable Path Loss (dB)	Adjusted Incumbent Power at the Radio Port (dBm)	Antenna Gain (dBi)	Adjusted Incumbent Power at the Antenna (dBm)	Detection Limit (dBm)	EUT Tx Status
-72.41	2.8	-75.21	-4.20	-71.01	-62	Ceased
-73.69	2.8	-76.49	-4.20	-72.29	-62	Minimal
-75.65	2.8	-78.45	-4.20	-74.25	-62	Normal

Incumbent AWGN at f<sub>c1</sub>:

Measured Incumbent Power at the EUT Test Fixture Connector (dBm)	Test Fixture Cable Path Loss (dB)	Adjusted Incumbent Power at the Radio Port (dBm)	Antenna Gain (dBi)	Adjusted Incumbent Power at the Antenna (dBm)	Detection Limit (dBm)	EUT Tx Status
-67.45	2.8	-70.25	-4.20	-66.05	-62	Ceased
-68.69	2.8	-71.49	-4.20	-67.29	-62	Minimal
-72.86	2.8	-75.66	-4.20	-71.46	-62	Normal

Incumbent AWGN at f<sub>c3</sub>:

Measured Incumbent Power at the EUT Test Fixture Connector (dBm)	Test Fixture Cable Path Loss (dB)	Adjusted Incumbent Power at the Radio Port (dBm)	Antenna Gain (dBi)	Adjusted Incumbent Power at the Antenna (dBm)	Detection Limit (dBm)	EUT Tx Status
-72.26	2.8	-75.06	-4.20	-70.86	-62	Ceased
-73.58	2.8	-76.38	-4.20	-72.18	-62	Minimal
-74.66	2.8	-77.46	-4.20	-73.26	-62	Normal

**Test Date: 2025-05-19**

**Tested by: 44352**

**Test location: 1-DFS-A**

## 9. SETUP PHOTOS

Please refer to 15496282-EP1V1 for setup photos

**END OF TEST REPORT**