



August 29, 2007

Apple Inc.
FCC ID: BCGA1213
Request for transmitter modular approval

Transmitter Module Characteristics

Item	Requirements	EUT
1	Have its own RF shielding	Device is equipped with Metal shielding to cover RF section. Refer to external photos
2	Have buffered modulation/data inputs (if such inputs are provided)	Device was tested inside the final end product for limited modular approval.
3	Have its own power supply regulation	The power supply voltages are all regulated. Refer to Block diagram & Schematic
4	Meet the antenna requirements of Section 15.203	The connector is for Mfg. test purposes only and is not accessible to the user. Refer to external photos
5	Be tested in a stand-alone configuration, i.e., the antenna, AC or DC power and data input/output lines must be connected to the module but, the module must not be inside another case during testing	Device was tested inside the final end product for limited modular approval.
6	Be labeled with its own FCC ID number, and if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module.	The outside of the product containing the radio module is labeled with "Contains FCC ID: BCGA1213
7	The modular transmitter is manufactured so that the user cannot influence the operation of the transmitter that will operate outside of the scope of the regulations.	The modular transmitter is inside a product that has no user access areas.
8	Address compliance with the Commission's RF exposure limits in Sections 1.1310 and 2.1093. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF exposure compliance in accordance with Section 15.247(b)(4).	SAR testing was performed on the module in the only system it will be used in and it passed for body contact device.