



Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 2462MHz
 Channel: 11



Plot 7-169. Radiated Restricted Upper Band Edge Measurement SISO Core 1 Primary (Average & Peak)


Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 2467MHz
 Channel: 12



Plot 7-170. Radiated Restricted Upper Band Edge Measurement SISO Core 1 Primary (Average & Peak)

FCC ID: BCGA1876	 MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1C1806050010-02.BCG	Test Dates: 07/27/2018-09/21/2018	EUT Type: Tablet Device	Page 126 of 149	

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 2472MHz
 Channel: 13



Plot 7-171. Radiated Restricted Upper Band Edge Measurement SISO Core 1 Primary (Average & Peak)


FCC ID: BCGA1876	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050010-02.BCG	Test Dates: 07/27/2018-09/21/2018	EUT Type: Tablet Device	Page 127 of 149

7.7.8 SISO Core 1 Diversity Radiated Restricted Band Edge Measurements

§15.205 §15.209; RSS-Gen [8.9]


The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting.

Worst Case Mode: 802.11b
Worst Case Transfer Rate: 1 Mbps
Distance of Measurements: 3 Meters
Operating Frequency: 2412MHz
Channel: 1



Plot 7-172. Radiated Restricted Lower Band Edge Measurement SISO Core 1 Diversity (Average & Peak)


Worst Case Mode: 802.11b
Worst Case Transfer Rate: 1 Mbps
Distance of Measurements: 3 Meters
Operating Frequency: 2472MHz
Channel: 13



Plot 7-173. Radiated Restricted Upper Band Edge Measurement SISO Core 1 Diversity (Average & Peak)


FCC ID: BCGA1876	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050010-02.BCG	Test Dates: 07/27/2018-09/21/2018	EUT Type: Tablet Device	Page 128 of 149

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 2412MHz
 Channel: 1



Plot 7-174. Radiated Restricted Lower Band Edge Measurement SISO Core 1 Diversity (Average & Peak)


Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 2417MHz
 Channel: 2



Plot 7-175. Radiated Restricted Lower Band Edge Measurement SISO Core 1 Diversity (Average & Peak)


FCC ID: BCGA1876	 MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1C1806050010-02.BCG	Test Dates: 07/27/2018-09/21/2018	EUT Type: Tablet Device		Page 129 of 149

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 2452MHz
 Channel: 9



Plot 7-176. Radiated Restricted Upper Band Edge Measurement SISO Core 1 Diversity (Average & Peak)


Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 2457MHz
 Channel: 10



Plot 7-177. Radiated Restricted Upper Band Edge Measurement SISO Core 1 Diversity (Average & Peak)


FCC ID: BCGA1876	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050010-02.BCG	Test Dates: 07/27/2018-09/21/2018	EUT Type: Tablet Device	Page 130 of 149

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 2462MHz
 Channel: 11



Plot 7-178. Radiated Restricted Upper Band Edge Measurement SISO Core 1 Diversity (Average & Peak)


Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 2467MHz
 Channel: 12



Plot 7-179. Radiated Restricted Upper Band Edge Measurement SISO Core 1 Diversity (Average & Peak)

FCC ID: BCGA1876	 MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1C1806050010-02.BCG	Test Dates: 07/27/2018-09/21/2018	EUT Type: Tablet Device	Page 131 of 149	

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 2472MHz
 Channel: 13



Plot 7-180. Radiated Restricted Upper Band Edge Measurement SISO Core 1 Diversity (Average & Peak)


FCC ID: BCGA1876	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1C1806050010-02.BCG	Test Dates: 07/27/2018-09/21/2018	EUT Type: Tablet Device	Page 132 of 149	

7.7.9 CDD Primary Radiated Restricted Band Edge Measurements

§15.205 §15.209; RSS-Gen [8.9]


The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting.

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 2412MHz
 Channel: 1



Plot 7-181. Radiated Restricted Lower Band Edge Measurement CDD Primary (Average & Peak)


Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 2417MHz
 Channel: 2



Plot 7-182. Radiated Restricted Lower Band Edge Measurement CDD Primary (Average & Peak)


FCC ID: BCGA1876	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050010-02.BCG	Test Dates: 07/27/2018-09/21/2018	EUT Type: Tablet Device	Page 133 of 149

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 2452MHz
 Channel: 9



Plot 7-183. Radiated Restricted Upper Band Edge Measurement CDD Primary (Average & Peak)


Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 2457MHz
 Channel: 10



Plot 7-184. Radiated Restricted Upper Band Edge Measurement CDD Primary (Average & Peak)


FCC ID: BCGA1876	 MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1C1806050010-02.BCG	Test Dates: 07/27/2018-09/21/2018	EUT Type: Tablet Device		Page 134 of 149

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 2462MHz
 Channel: 11



Plot 7-185. Radiated Restricted Upper Band Edge Measurement CDD Primary (Average & Peak)


Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 2467MHz
 Channel: 12



Plot 7-186. Radiated Restricted Upper Band Edge Measurement CDD Primary (Average & Peak)

FCC ID: BCGA1876	 MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1C1806050010-02.BCG	Test Dates: 07/27/2018-09/21/2018	EUT Type: Tablet Device		Page 135 of 149

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 2472MHz
 Channel: 13



Plot 7-187. Radiated Restricted Upper Band Edge Measurement CDD Primary (Average & Peak)


FCC ID: BCGA1876	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050010-02.BCG	Test Dates: 07/27/2018-09/21/2018	EUT Type: Tablet Device	Page 136 of 149

7.7.10 CDD Diversity Radiated Restricted Band Edge Measurements

§15.205 §15.209; RSS-Gen [8.9]


The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting.

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 2412MHz
 Channel: 1



Plot 7-188. Radiated Restricted Lower Band Edge Measurement CDD Diversity (Average & Peak)


Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 2417MHz
 Channel: 2



Plot 7-189. Radiated Restricted Lower Band Edge Measurement CDD Diversity (Average & Peak)


FCC ID: BCGA1876	 MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1C1806050010-02.BCG	Test Dates: 07/27/2018-09/21/2018	EUT Type: Tablet Device		Page 137 of 149

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 2452MHz
 Channel: 9



Plot 7-190. Radiated Restricted Upper Band Edge Measurement CDD Diversity (Average & Peak)


Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 2457MHz
 Channel: 10



Plot 7-191. Radiated Restricted Upper Band Edge Measurement CDD Diversity (Average & Peak)


FCC ID: BCGA1876	 MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1C1806050010-02.BCG	Test Dates: 07/27/2018-09/21/2018	EUT Type: Tablet Device		Page 138 of 149

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 2462MHz
 Channel: 11



Plot 7-192. Radiated Restricted Upper Band Edge Measurement CDD Diversity (Average & Peak)


Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 2467MHz
 Channel: 12



Plot 7-193. Radiated Restricted Upper Band Edge Measurement CDD Diversity (Average & Peak)

FCC ID: BCGA1876	 MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1C1806050010-02.BCG	Test Dates: 07/27/2018-09/21/2018	EUT Type: Tablet Device	Page 139 of 149	

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 2472MHz
 Channel: 13



Plot 7-194. Radiated Restricted Upper Band Edge Measurement CDD Diversity (Average & Peak)

FCC ID: BCGA1876	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050010-02.BCG	Test Dates: 07/27/2018-09/21/2018	EUT Type: Tablet Device	Page 140 of 149

7.8 Radiated Spurious Emissions Measurements – Below 1GHz

§15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-40 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [μ V/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-40. Radiated Limits

Test Procedures Used

ANSI C63.10-2013

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: BCGA1876	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050010-02.BCG	Test Dates: 07/27/2018-09/21/2018	EUT Type: Tablet Device	Page 141 of 149

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.




Figure 7-7. Radiated Test Setup < 30Mhz




Figure 7-8. Radiated Test Setup < 1GHz

FCC ID: BCGA1876	 PCTEST® <small>ENGINEERING LABORATORY, INC.</small>		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1806050010-02.BCG	Test Dates: 07/27/2018-09/21/2018	EUT Type: Tablet Device		Page 142 of 149


Test Notes

1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen(8.10) are below the limit shown in Table 7-40.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. There were no emissions detected in the 30MHz – 1GHz frequency range, as shown in the subsequent plots.

FCC ID: BCGA1876	PCTEST [®] ENGINEERING LABORATORY, INC.		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1806050010-02.BCG	Test Dates: 07/27/2018-09/21/2018	EUT Type: Tablet Device	Page 143 of 149	

CDD Primary Radiated Spurious Emissions Measurements (Below 1GHz)

§15.209; RSS-Gen [8.9]



Plot 7-195. Radiated Spurious Plot below 1GHz CDD Primary 11n Ch.6 with AC/DC Adapter

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
40.09	Max Peak	V	100	144	-71.06	-14.36	21.58	40.00	-18.42
48.87	Max Peak	V	100	156	-60.09	-20.66	26.25	40.00	-13.75
84.81	Max Peak	V	100	3	-75.42	-18.40	13.18	40.00	-26.82
145.87	Max Peak	H	250	258	-73.20	-19.06	14.74	43.52	-28.78
167.26	Max Peak	H	100	252	-68.89	-17.84	20.27	43.52	-23.26
220.99	Max Peak	H	100	310	-74.21	-18.16	14.63	46.02	-31.39

Table 7-41. Radiated Spurious Emissions below 1GHz CDD Primary 11n Ch.6 with AC/DC Adapter

FCC ID: BCGA1876		MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1C1806050010-02.BCG	Test Dates: 07/27/2018-09/21/2018	EUT Type: Tablet Device			

7.9 Line-Conducted Test Data

§15.207; RSS-Gen [8.8]

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.207 and RSS-Gen (8.8).

Frequency of emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-42. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10-2013, Section 6.2

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: BCGA1876	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050010-02.BCG	Test Dates: 07/27/2018-09/21/2018	EUT Type: Tablet Device	Page 145 of 149

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-9. Test Instrument & Measurement Setup

Test Notes

1. All modes of operation were investigated and the worst-case emissions are reported using mid channel. The emissions found were not affected by the choice of channel used during testing.
2. The limit for an intentional radiator from 150kHz to 30MHz are specified in Part 15.207 and RSS-Gen(8.8).
3. Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
4. QP/AV Level (dB μ V) = QP/AV Analyzer/Receiver Level (dB μ V) + Corr. (dB)
5. Margin (dB) = QP/AV Limit (dB μ V) - QP/AV Level (dB μ V)
6. Traces shown in plot are made using a peak detector.
7. Deviations to the Specifications: None.

FCC ID: BCGA1876	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050010-02.BCG	Test Dates: 07/27/2018-09/21/2018	EUT Type: Tablet Device	Page 146 of 149




Plot 7-196. Line Conducted Plot with CDD Primary 802.11n Ch.6 (L1) with AC/DC charger

Frequency MHz	Process State	QuasiPeak dB μ V	Average dB μ V	Limit dB μ V	Margin dB	Bandwidth kHz	Line	PE
0.163000	FINAL	—	28.08	55.31	-27.23	9.000	L1	GND
0.168000	FINAL	41.02	—	65.06	-24.04	9.000	L1	GND
0.195000	FINAL	45.52	—	63.82	-18.30	9.000	L1	GND
0.200000	FINAL	—	32.82	53.61	-20.79	9.000	L1	GND
0.232000	FINAL	—	23.59	52.38	-28.79	9.000	L1	GND
0.294000	FINAL	36.99	—	60.41	-23.42	9.000	L1	GND
0.296000	FINAL	—	23.23	50.35	-27.12	9.000	L1	GND
0.395000	FINAL	—	19.81	47.96	-28.15	9.000	L1	GND
0.402000	FINAL	35.25	—	57.81	-22.56	9.000	L1	GND
0.484000	FINAL	37.02	—	56.27	-19.25	9.000	L1	GND
0.504000	FINAL	—	21.67	46.00	-24.33	9.000	L1	GND
0.596000	FINAL	38.23	—	56.00	-17.77	9.000	L1	GND

Table 7-43. Line Conducted Data with CDD Primary 802.11n Ch.6 (L1) with AC/DC charger

FCC ID: BCGA1876	 MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1C1806050010-02.BCG	Test Dates: 07/27/2018-09/21/2018	EUT Type: Tablet Device	Page 147 of 149	



Plot 7-197. Line Conducted Plot with CDD Primary 802.11n Ch.6 (N) with AC/DC charger

Frequency MHz	Process State	QuasiPeak dB μ V	Average dB μ V	Limit dB μ V	Margin dB	Bandwidth kHz	Line	PE
0.164000	FINAL	—	27.42	55.26	-27.84	9.000	N	GND
0.166000	FINAL	39.92	—	65.16	-25.24	9.000	N	GND
0.195000	FINAL	43.32	—	63.82	-20.50	9.000	N	GND
0.199000	FINAL	—	31.45	53.65	-22.20	9.000	N	GND
0.233000	FINAL	—	22.08	52.34	-30.26	9.000	N	GND
0.292000	FINAL	36.61	—	60.47	-23.86	9.000	N	GND
0.297000	FINAL	—	21.97	50.33	-28.36	9.000	N	GND
0.397000	FINAL	34.39	—	57.92	-23.53	9.000	N	GND
0.398000	FINAL	—	20.35	47.90	-27.55	9.000	N	GND
0.495000	FINAL	35.82	—	56.08	-20.26	9.000	N	GND
0.606000	FINAL	—	21.00	46.00	-25.00	9.000	N	GND
0.608000	FINAL	37.80	—	56.00	-18.20	9.000	N	GND

Table 7-44. Line Conducted Data with CDD Primary 802.11n Ch.6 (N) with AC/DC charger

FCC ID: BCGA1876	 MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1C1806050010-02.BCG	Test Dates: 07/27/2018-09/21/2018	EUT Type: Tablet Device	Page 148 of 149	

8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Apple Tablet Device** **FCC ID: BCGA1876** is in compliance with Part 15 Subpart C (15.247) of the FCC Rules and RSS-247 of the Innovation, Science and Economic Development Canada Rules.

FCC ID: BCGA1876	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050010-02.BCG	Test Dates: 07/27/2018-09/21/2018	EUT Type: Tablet Device	Page 149 of 149