



PCTEST ENGINEERING LABORATORY, INC.

382 Piercy Rd, San Jose, CA 95138 USA
Tel. +1.410.290.6652 / Fax +1.410.290.6654
<http://www.pctest.com>



SAR EVALUATION REPORT

Applicant Name:

Apple, Inc.
1 Infinite Loop
Cupertino, CA 95014

Date of Testing:

01/10/18 - 01/18/18

Test Site/Location:

PCTEST Lab, San Jose, CA, USA

Document Serial No.:

1C1710060005-01-R4.BCG

FCC ID:

BCGA1893

APPLICANT:

APPLE, INC.

DUT Type: Tablet Device

Application Type: Certification

FCC Rule Part(s): CFR §2.1093

Model: A1893

Equipment Class	Band & Mode	Tx Frequency	SAR
			1g Body (W/kg)
DTS	2.4 GHz WLAN	2412 - 2472 MHz	1.18
NII	U-NII-1	5180 - 5240 MHz	N/A
NII	U-NII-2A	5260 - 5320 MHz	1.14
NII	U-NII-2C	5500 - 5720 MHz	1.10
NII	U-NII-3	5745 - 5825 MHz	0.93
DSS/DTS	Bluetooth	2402 - 2480 MHz	1.01
Simultaneous SAR per KDB 690783 D01v01r03:			1.30

This revised Test Report (S/N: 1C1710060005-01-R4.BCG) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.7 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.

Randy Ortanez
President



The SAR Tick is an initiative of the Mobile & Wireless Forum (MWF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MWF. Further details can be obtained by emailing: sartick@mwfai.info.

FCC ID: BCGA1893	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device	Page 1 of 43

T A B L E O F C O N T E N T S

1	DEVICE UNDER TEST	3
2	INTRODUCTION	8
3	DOSIMETRIC ASSESSMENT	9
4	TEST CONFIGURATION POSITIONS	10
5	RF EXPOSURE LIMITS	11
6	FCC MEASUREMENT PROCEDURES.....	12
7	RF CONDUCTED POWERS.....	15
8	SYSTEM VERIFICATION.....	28
9	SAR DATA SUMMARY	30
10	FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS.....	35
11	SAR MEASUREMENT VARIABILITY	38
12	EQUIPMENT LIST.....	39
13	MEASUREMENT UNCERTAINTIES.....	40
14	CONCLUSION.....	41
15	REFERENCES	42
APPENDIX A: SAR TEST PLOTS		
APPENDIX B: SAR DIPOLE VERIFICATION PLOTS		
APPENDIX C: PROBE AND DIPOLE CALIBRATION CERTIFICATES		
APPENDIX D: SAR TISSUE SPECIFICATIONS		
APPENDIX E: SAR SYSTEM VALIDATION		
APPENDIX F: DUT ANTENNA DIAGRAM & SAR TEST SETUP PHOTOGRAPHS		

FCC ID: BCGA1893	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device	Page 2 of 43

1 DEVICE UNDER TEST

1.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
2.4 GHz WLAN	Data	2412 - 2472 MHz
U-NII-1	Data	5180 - 5240 MHz
U-NII-2A	Data	5260 - 5320 MHz
U-NII-2C	Data	5500 - 5720 MHz
U-NII-3	Data	5745 - 5825 MHz
Bluetooth	Data	2402 - 2480 MHz

1.2 Power Reduction for SAR

This device utilizes an independent single step power reduction mechanism for Bluetooth operations. When Bluetooth is operating simultaneously with 5 GHz WLAN, the output power of Bluetooth is reduced for the duration of simultaneous operation. SAR evaluation was additionally performed at the maximum allowed output power for Bluetooth which is applicable for all other use cases.

Detailed description of the mechanism and the verification procedures are included in the operational description document. Section 7.2.1 contain a summary of the verification results.

1.3 Nominal and Maximum Output Power Specifications

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v06.

1.3.1 Maximum Output Power

Mode / Band		Modulated Average - Single Tx Chain (dBm)				
		Ch. 1	Ch. 2-10	Ch. 11	Ch. 12	Ch. 13
IEEE 802.11b (2.4 GHz)	Maximum		15.5			14.0
IEEE 802.11g (2.4 GHz)	Maximum	15.0	15.5	13.5	12.0	1.5
IEEE 802.11n (2.4 GHz)	Maximum	15.0	15.5	13.5	12.0	1.5

FCC ID: BCGA1893	 PCTEST Engineering Laboratory, Inc.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device		Page 3 of 43

Mode / Band		Modulated Average - MIMO (dBm)				
		Ch. 1	Ch. 2-10	Ch. 11	Ch. 12	Ch. 13
IEEE 802.11g (2.4 GHz)	Maximum	13.0	15.5	12.5	10.0	0.0
IEEE 802.11n (2.4 GHz)	Maximum	13.0	15.5	12.5	10.0	0.0

Note: In MIMO operations, each Antenna A and Antenna B transmits at maximum allowed powers as indicated above.

Mode / Band		Modulated Average - Single Tx Chain (dBm)				
Bluetooth BDR (P_{High})	Maximum	17.0				
Bluetooth LE (P_{High})	Maximum	17.0				
Bluetooth EDR (P_{High})	Maximum	14.5				

Mode / Band		Modulated Average - Single Tx Chain (dBm)															
		20 MHz Bandwidth							40 MHz Bandwidth							80 MHz Bandwidth	
		Ch. 36, 64	Ch. 40-48, 149-165	Ch. 52-60, 104-136	Ch. 64	Ch. 100	Ch. 140	Ch. 38	Ch. 46, 151, 159	Ch. 54, 110-126, 142	Ch. 62	Ch. 102	Ch. 134	Ch. 42, 58	Ch. 106		
IEEE 802.11a (5 GHz)	Maximum	16.0	16.5	17.0	15.5	15.0	15.0	13.5	16.5	17.0	15.0	14.5	16.0	13.0	14.0	17.0	16.5
IEEE 802.11n (5 GHz)	Maximum	16.0	16.5	17.0	15.5	15.0	15.0	13.5	16.5	17.0	15.0	14.5	16.0	13.0	14.0	17.0	16.5
IEEE 802.11ac (5 GHz)	Maximum	16.0	16.5	17.0	15.5	15.0	15.0	13.5	16.5	17.0	15.0	14.5	16.0	13.0	14.0	17.0	16.5

Mode / Band		Modulated Average - MIMO (dBm) 2Tx CDD																
		20 MHz Bandwidth							40 MHz Bandwidth							80 MHz Bandwidth		
		Ch. 36	Ch. 40-60, 149-165	Ch. 64	Ch. 100	Ch. 104-136	Ch. 140	Ch. 144	Ch. 38	Ch. 46, 151, 159	Ch. 54, 110-126, 142	Ch. 62	Ch. 102	Ch. 134	Ch. 42, 58	Ch. 106	Ch. 122-138	Ch. 155
IEEE 802.11a (5 GHz)	Maximum	15.0	16.5	14.5	15.0	15.5	14.0	17.0	12.5	16.5	17.0	13.5	13.0	15.0	12.0	13.0	17.0	16.0
IEEE 802.11n (5 GHz)	Maximum	15.0	16.5	14.5	15.0	15.5	14.0	17.0	12.5	16.5	17.0	13.5	13.0	15.0	12.0	13.0	17.0	16.0
IEEE 802.11ac (5 GHz)	Maximum	15.0	16.5	14.5	15.0	15.5	14.0	17.0	12.5	16.5	17.0	13.5	13.0	15.0	12.0	13.0	17.0	16.0

Note: In MIMO operations, each Antenna A and Antenna B transmits at maximum allowed powers as indicated above.

Mode / Band		Modulated Average - MIMO (dBm) 2Tx SDM														
		20 MHz Bandwidth							40 MHz Bandwidth							80 MHz Bandwidth
		Ch. 36, 100	Ch. 40-48, 149-165	Ch. 52-60, 104-136, 144	Ch. 64	Ch. 140	Ch. 38	Ch. 46, 151, 159	Ch. 54, 110-126, 142	Ch. 62	Ch. 102	Ch. 134	Ch. 42, 58	Ch. 106	Ch. 122-138	
IEEE 802.11n (5 GHz)	Maximum	15.0	16.5	17.0	14.5	14.0	12.5	16.5	17.0	13.5	13.0	15.0	12.0	13.0	17.0	16.0
IEEE 802.11ac (5 GHz)	Maximum	15.0	16.5	17.0	14.5	14.0	12.5	16.5	17.0	13.5	13.0	15.0	12.0	13.0	17.0	16.0

Note: In MIMO operations, each Antenna A and Antenna B transmits at maximum allowed powers as indicated above.

FCC ID: BCGA1893	 PCTEST	SAR EVALUATION REPORT					Approved by:
Document S/N:	Test Dates:	DUT Type:					
1C1710060005-01-R4.BCG	01/10/18 - 01/18/18	Tablet Device					

1.3.2

Reduced Output Power

Mode / Band		Modulated Average - Single Tx Chain (dBm)
Bluetooth BDR (P_{Low})	Maximum	9.5
Bluetooth LE (P_{Low})	Maximum	7.0
Bluetooth EDR (P_{Low})	Maximum	9.0

Note: Bluetooth P_{Low} is the reduced output power of Bluetooth when it is operating simultaneously with 5 GHz WLAN. Detailed description of the power reduction mechanism is included in the operational description.

1.4 DUT Antenna Locations

The overall diagonal dimension of the device is > 200 mm. A diagram showing the location of the device antennas can be found in Appendix F. Exact antenna dimensions and separation distances are shown in the Technical Descriptions in the FCC filings.

Table 1-1
Device Edges/Sides for SAR Testing

Mode	Back	Top	Bottom	Right	Left
2.4 GHz WLAN Ant A	Yes	No	Yes	No	Yes
2.4 GHz WLAN Ant B	Yes	No	Yes	Yes	No
5 GHz WLAN Ant A	Yes	No	Yes	No	Yes
5 GHz WLAN Ant B	Yes	No	Yes	Yes	No
Bluetooth	Yes	No	Yes	No	Yes

Note:

- 1) Per FCC KDB Publication 616217 D04v01r01, particular edges were not required to be evaluated for SAR based on the SAR exclusion threshold in KDB 447498 D01V06

FCC ID: BCGA1893		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device	Page 5 of 43

1.5 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D01v06, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds.

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v06 4.3.2 procedures.

Table 1-2
Simultaneous Transmission Scenarios

No.	Capable Transmit Configuration	Body
1	2.4 GHz Wi-Fi MIMO	Yes
2	5 GHz Wi-Fi MIMO	Yes
3	2.4 GHz Bluetooth + 5 GHz Wi-Fi	Yes
4	2.4 GHz Bluetooth + 5 GHz Wi-Fi MIMO	Yes

1. 2.4 GHz WLAN and 2.4 GHz Bluetooth share the same antenna path and cannot transmit simultaneously.
2. This device supports 2x2 MIMO Tx for WLAN. 802.11a/g/n/ac supports CDD and 802.11 n/ac additionally supports SDM. Each WLAN antenna can transmit independently or together when operating with MIMO.

FCC ID: BCGA1893	 SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device

1.6 Miscellaneous SAR Test Considerations

(A) WIFI/BT

Since U-NII-1 and U-NII-2A bands have the same maximum output power and the highest reported SAR for U-NII-2A is less than 1.2 W/kg, SAR is not required for U-NII-1 band according to FCC KDB Publication 248227 D01v02r02.

The WLAN/Bluetooth chipset in this device is produced by two different suppliers. The electrically identical modules are manufactured with the identical mechanical structure to meet the same specifications and functions. Two device variants are referenced as Variant 1 and Variant 2 in this report.

WLAN/Bluetooth SAR testing was completely performed on Variant 1, and Variant 2 is additionally evaluated for WLAN/Bluetooth SAR with the same configuration of the highest reported SAR of Variant 1.

This device supports IEEE 802.11ac with the following features:

- a) Up to 80 MHz Bandwidth only
- b) No aggregate channel configurations
- c) 2 Tx antenna output
- d) TDWR and Band gap channels are supported

This device supports channel 1-13 for 2.4 GHz WLAN. However, since channels 12 and 13 have equal or less maximum output power, channels 1, 6, and 11 were considered for SAR testing per KDB 248227 D01v02r02.

1.7 Guidance Applied

- FCC KDB Publication 248227 D01v02r02 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D01v06 (General SAR Guidance)
- FCC KDB Publication 865664 D01v01r04, D02v01r02 (SAR Measurements up to 6 GHz)
- FCC KDB Publication 616217 D04v01r02 (Tablet)

1.8 Device Serial Numbers

Several samples with identical hardware were used to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units. The serial numbers used for each test are indicated alongside the results in Section 9.

FCC ID: BCGA1893	 PCTEST Engineering Laboratory, Inc.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device		Page 7 of 43

2 INTRODUCTION

The FCC and Innovation, Science, and Economic Development Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields," Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

2.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 2-1).

**Equation 2-1
SAR Mathematical Equation**

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dV} \right)$$

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

σ = conductivity of the tissue-simulating material (S/m)

ρ = mass density of the tissue-simulating material (kg/m³)

E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

FCC ID: BCGA1893	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device	Page 8 of 43

3 DOSIMETRIC ASSESSMENT

3.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01r04 (See Table 3-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01r04 (See Table 3-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
 - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 3-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
 - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the “Not a knot” condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.




Figure 3-1
Sample SAR Area
Scan

point

Frequency	Maximum Area Scan Resolution (mm) ($\Delta x_{area}, \Delta y_{area}$)	Maximum Zoom Scan Resolution (mm) ($\Delta x_{zoom}, \Delta y_{zoom}$)	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid		Graded Grid	
			$\Delta z_{zoom}(n)$	$\Delta z_{zoom}(1)^*$	$\Delta z_{zoom}(n>1)^*$	
≤ 2 GHz	≤ 15	≤ 8	≤ 5	≤ 4	$\le 1.5^* \Delta z_{zoom}(n-1)$	≥ 30
2-3 GHz	≤ 12	≤ 5	≤ 5	≤ 4	$\le 1.5^* \Delta z_{zoom}(n-1)$	≥ 30
3-4 GHz	≤ 12	≤ 5	≤ 4	≤ 3	$\le 1.5^* \Delta z_{zoom}(n-1)$	≥ 28
4-5 GHz	≤ 10	≤ 4	≤ 3	≤ 2.5	$\le 1.5^* \Delta z_{zoom}(n-1)$	≥ 25
5-6 GHz	≤ 10	≤ 4	≤ 2	≤ 2	$\le 1.5^* \Delta z_{zoom}(n-1)$	≥ 22

*Also compliant to IEEE 1528-2013 Table 6

FCC ID: BCGA1893	 SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device

4 TEST CONFIGURATION POSITIONS

4.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$.

4.2 SAR Testing for Tablet per KDB Publication 616217 D04v01r02

Per FCC KDB Publication 616217 D04v01r02, the back surface and edges of the tablet should be tested for SAR compliance with the tablet touching the phantom. The SAR Exclusion Threshold in KDB 447498 D01v06 can be applied to determine SAR test exclusion for adjacent edge configurations. The closest distance from the antenna to an adjacent tablet edge is used to determine if SAR testing is required for the adjacent edges, with the adjacent edge positioned against the phantom and the edge containing the antenna positioned perpendicular to the phantom.

FCC ID: BCGA1893	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device	Page 10 of 43

5 RF EXPOSURE LIMITS

5.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

5.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 5-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
Peak Spatial Average SAR Head	1.6	8.0
Whole Body SAR	0.08	0.4
Peak Spatial Average SAR Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: BCGA1893	 PCTEST Engineering Laboratory, Inc.	SAR EVALUATION REPORT	
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device	Approved by: Quality Manager Page 11 of 43

6 FCC MEASUREMENT PROCEDURES

6.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v06, when SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as **reported** SAR. The highest **reported** SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r03.

6.2 SAR Testing with 802.11 Transmitters

The normal network operating configurations of 802.11 transmitters are not suitable for SAR measurements. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v02r02 for more details.

6.2.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters.

A periodic duty factor is required for current generation SAR systems to measure SAR. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR is scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

6.2.2 U-NII-1 and U-NII-2A

For devices that operate in both U-NII-1 and U-NII-2A bands, when the same maximum output power is specified for both bands, SAR measurement using OFDM SAR test procedures is not required for U-NII-1 unless the highest reported SAR for U-NII-2A is $> 1.2 \text{ W/kg}$. When different maximum output powers are specified for the bands, SAR measurement for the U-NII band with the lower maximum output power is not required unless the highest reported SAR for the U-NII band with the higher maximum output power, adjusted by the ratio of lower to higher specified maximum output power for the two bands, is $> 1.2 \text{ W/kg}$.

6.2.3 U-NII-2C and U-NII-3

The frequency range covered by U-NII-2C and U-NII-3 is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. When Terminal Doppler Weather Radar (TDWR) restriction applies, the channels at 5.60 – 5.65 GHz in U-NII-2C band must be disabled with acceptable mechanisms and documented in the equipment certification. Unless band gap channels are permanently disabled, SAR must be considered for these channels. Each band is tested independently according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.

FCC ID: BCGA1893	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device	Page 12 of 43

6.2.4 2.4 GHz SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either the fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) When the reported SAR of the highest measured maximum output power channel for the exposure configuration is $\leq 0.8 \text{ W/kg}$, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) When the reported SAR is $> 0.8 \text{ W/kg}$, SAR is required for that position using the next highest measured output power channel. When any reported SAR is $> 1.2 \text{ W/kg}$, SAR is required for the third channel; i.e., all channels require testing.

2.4 GHz 802.11 g/n OFDM are additionally evaluated for SAR if the highest reported SAR for 802.11b, adjusted by the ratio of the OFDM to DSSS specified maximum output power, is $> 1.2 \text{ W/kg}$. When SAR is required for OFDM modes in 2.4 GHz band, the Initial Test Configuration Procedures should be followed.

6.2.5 OFDM Transmission Mode and SAR Test Channel Selection

When the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate. When the maximum output power of a channel is the same for equivalent OFDM configurations; for example, 802.11a, 802.11n and 802.11ac or 802.11g and 802.11n with the same channel bandwidth, modulation and data rate etc., the lower order 802.11 mode i.e., 802.11a, then 802.11n and 802.11ac or 802.11g then 802.11n, is used for SAR measurement. When the maximum output power are the same for multiple test channels, either according to the default or additional power measurement requirements, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.

6.2.6 Initial Test Configuration Procedure

For OFDM, an initial test configuration is determined for each frequency band and aggregated band, according to the transmission mode with the highest maximum output power specified for SAR measurements. When the same maximum output power is specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration(s) with the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order IEEE 802.11 mode. The channel of the transmission mode with the highest average RF output conducted power will be the initial test configuration.

When the reported SAR is $\leq 0.8 \text{ W/kg}$, no additional measurements on other test channels are required. Otherwise, SAR is evaluated using the subsequent highest average RF output channel until the reported SAR result is $\leq 1.2 \text{ W/kg}$ or all channels are measured. When there are multiple untested channels having the same subsequent highest average RF output power, the channel with higher frequency from the lowest 802.11 mode is considered for SAR measurements (See Section 6.2.5).

6.2.7 Subsequent Test Configuration Procedures

For OFDM configurations in each frequency band and aggregated band, SAR is evaluated for initial test configuration using the fixed test position or the initial test position procedure. When the highest reported SAR (for the initial test configuration), adjusted by the ratio of the specified maximum output power of the subsequent test configuration to initial test configuration, is $\leq 1.2 \text{ W/kg}$, no additional SAR tests for the subsequent test configurations are required.

FCC ID: BCGA1893	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device	Page 13 of 43

6.2.8 MIMO SAR considerations

Per KDB Publication 248227 D01v02r02, the simultaneous SAR provisions in KDB Publication 447498 D01v06 should be applied to determine simultaneous transmission SAR test exclusion for WIFI MIMO. If the sum of 1g single transmission chain SAR measurements is <1.6 W/kg, no additional SAR measurements for MIMO are required. Alternatively, SAR for MIMO can be measured with all antennas transmitting simultaneously at the specified maximum output power of MIMO operation.

FCC ID: BCGA1893	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device	Page 14 of 43

7 RF CONDUCTED POWERS

7.1 WLAN Conducted Powers

7.1.1 Variant 1

Table 7-1
2.4 GHz WLAN Average RF Power – Ant A

2.4GHz Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11b	802.11g	802.11n
2412	1	15.50	14.79	14.70
2437	6	15.41	15.38	15.50
2462	11	15.50	13.46	13.47

Table 7-2
2.4 GHz WLAN Average RF Power – Ant B

2.4GHz Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11b	802.11g	802.11n
2412	1	15.50	14.92	14.94
2437	6	15.35	15.50	15.31
2462	11	15.50	13.46	13.42

FCC ID: BCGA1893	 PCTEST Engineering Laboratory, Inc.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device		Page 15 of 43

Table 7-3
5 GHz WLAN Average RF Power – Ant A

5GHz (40MHz) Conducted Power [dBm]		
Freq [MHz]	Channel	IEEE Transmission Mode
		802.11n
5190	38	13.35
5230	46	16.48
5270	54	16.00
5310	62	14.48
5510	102	14.37
5550	110	17.00
5590	118	16.95
5630	126	16.99
5670	134	16.00
5710	142	16.99
5755	151	16.35
5795	159	16.50

5GHz (80MHz) Conducted Power [dBm]		
Freq [MHz]	Channel	IEEE Transmission Mode
		802.11ac
5210	42	12.87
5290	58	12.84
5530	106	14.00
5610	122	16.98
5690	138	16.99
5775	155	16.50

FCC ID: BCGA1893	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device	Page 16 of 43

Table 7-4
5 GHz WLAN Antenna B Average RF Power – Ant B

5GHz (40MHz) Conducted Power [dBm]		
Freq [MHz]	Channel	IEEE Transmission Mode
		802.11n
5190	38	13.33
5230	46	16.36
5270	54	16.93
5310	62	14.50
5510	102	14.50
5550	110	16.99
5590	118	17.00
5630	126	17.00
5670	134	15.90
5710	142	16.97
5755	151	16.50
5795	159	16.50

5GHz (80MHz) Conducted Power [dBm]		
Freq [MHz]	Channel	IEEE Transmission Mode
		802.11ac
5210	42	12.93
5290	58	12.88
5530	106	14.00
5610	122	15.97
5690	138	16.00
5775	155	15.94

FCC ID: BCGA1893	 PCTEST Engineering Laboratory, Inc.	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device	Page 17 of 43

Table 7-5
5 GHz WLAN Average RF Power – MIMO

5GHz (40MHz) Conducted Power [dBm]			
Freq [MHz]	Channel	ANT A	ANT B
802.11n			
5190	38	12.50	12.50
5230	46	16.50	16.35
5270	54	15.94	16.98
5310	62	13.36	13.32
5755	151	16.26	16.45
5795	159	16.31	16.39

5GHz (80MHz) Conducted Power [dBm]			
Freq [MHz]	Channel	ANT A	ANT B
802.11ac			
5530	106	13.00	12.92
5610	122	16.91	15.98
5690	138	17.00	15.98

FCC ID: BCGA1893	 PCTEST Engineering Laboratory, Inc.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device		Page 18 of 43

7.1.2 Variant 2

Table 7-6
2.4 GHz WLAN Average RF Power – Ant A

2.4GHz Conducted Power [dBm]		
Freq [MHz]	Channel	IEEE Transmission Mode
		802.11b
2412	1	15.44
2437	6	15.50
2462	11	15.49

Table 7-7
2.4 GHz WLAN Average RF Power – Ant B

2.4GHz Conducted Power [dBm]		
Freq [MHz]	Channel	IEEE Transmission Mode
		802.11b
2412	1	15.40
2437	6	15.44
2462	11	15.33

Table 7-8
5 GHz WLAN Average RF Power – Ant A

5GHz (40MHz) Conducted Power [dBm]		
Freq [MHz]	Channel	IEEE Transmission Mode
		802.11n
5270	54	16.00
5310	62	14.48

5GHz (80MHz) Conducted Power [dBm]		
Freq [MHz]	Channel	IEEE Transmission Mode
		802.11ac
5530	106	14.00
5610	122	16.91
5690	138	17.00
5775	155	16.50

FCC ID: BCGA1893	 PCTEST Engineering Laboratory, Inc.	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device	Page 19 of 43

Table 7-9
5 GHz WLAN Average RF Power – Ant B

5GHz (40MHz) Conducted Power [dBm]		
Freq [MHz]	Channel	IEEE Transmission Mode
		802.11n
5270	54	17.00
5310	62	14.50

5GHz (80MHz) Conducted Power [dBm]		
Freq [MHz]	Channel	IEEE Transmission Mode
		802.11ac
5530	106	13.91
5610	122	15.99
5690	138	16.00
5775	155	16.00

Table 7-10
5 GHz WLAN Average RF Power – MIMO

5GHz (40MHz) Conducted Power [dBm]			
Freq [MHz]	Channel	ANT A	ANT B
802.11n			
5270	54	15.92	17.00
5310	62	13.50	13.46
5755	151	16.48	16.48
5795	159	16.48	16.47

5GHz (80MHz) Conducted Power [dBm]			
Freq [MHz]	Channel	ANT A	ANT B
802.11ac			
5530	106	13.00	12.98
5610	122	16.92	16.00
5690	138	17.00	16.00

FCC ID: BCGA1893	 PCTEST Engineering Laboratory, Inc.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device		Page 20 of 43

7.1.3 Notes for WLAN

Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02:

- Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
- For transmission modes with the same maximum output power specification, powers were measured for the largest channel bandwidth, lowest order modulation and lowest data rate.
- For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.
- For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, due to an even number of channels, both channels were measured.
- The WLAN chipset in this device is produced by two different suppliers. The electrically identical modules are manufactured with the identical mechanical structure to meet the same specifications and functions. Two device variants are referenced as Variant 1 and Variant 2 in this report.
- WLAN SAR testing is completely performed on Variant 1, and Variant 2 is additionally evaluated for WLAN SAR with the same configuration of the highest reported SAR of Variant 1.
- Full power measurements were performed for variant 1 per FCC KDB Procedures 248227. Additional power measurements for variant 2 were additionally performed to support the SAR test configurations.
- The bolded data rate and channel above were tested for SAR.




Figure 7-1
WLAN Power Measurement Setup

FCC ID: BCGA1893	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device	Page 21 of 43

7.2 Bluetooth Conducted Powers

Table 7-11
Bluetooth P_{High} Maximum Average RF Power – Variant 1

Frequency [MHz]	Modulation	Channel No.	Avg Conducted Power	
			[dBm]	[mW]
2402	GFSK	0	15.94	39.283
2441	GFSK	39	16.98	49.831
2480	GFSK	78	16.06	40.402
2402	8PSK	0	13.70	23.421
2441	8PSK	39	13.74	23.643
2480	8PSK	78	14.38	27.441

Note: The bolded data rate and channel above were tested for SAR.

Table 7-12
Bluetooth P_{Low} Reduced Average RF Power – Variant 1

Frequency [MHz]	Modulation	Channel No.	Avg Conducted Power	
			[dBm]	[mW]
2402	GFSK	0	9.50	8.913
2441	GFSK	39	9.18	8.277
2480	GFSK	78	8.91	7.784
2402	8PSK	0	8.75	7.495
2441	8PSK	39	9.00	7.943
2480	8PSK	78	8.88	7.732

Notes:

1. The bolded data rate and channel above were tested for SAR.
2. Bluetooth P_{Low} is the reduced output power of Bluetooth when it is operating simultaneously with 5 GHz WLAN. Detailed description of the power reduction mechanism is included in the operational description.

FCC ID: BCGA1893	 PCTEST Engineering Laboratory, Inc.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device		

Table 7-13
Bluetooth P_{High} Maximum Average RF Power – Variant 2

Frequency [MHz]	Modulation	Channel No.	Avg Conducted Power	
			[dBm]	[mW]
2402	GFSK	0	16.76	47.424
2441	GFSK	39	16.49	44.586
2480	GFSK	78	16.04	40.216

FCC ID: BCGA1893	 SAR EVALUATION REPORT			Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device		




Figure 7-2
Bluetooth P_{High} Transmission Plot & Duty Cycle Calculation – Variant 1

$$\text{Duty Cycle} = \frac{\text{Pulse Width}}{\text{Period}} * 100\% = \frac{2.900\text{ms}}{3.750\text{ms}} * 100\% = 77.3\%$$

FCC ID: BCGA1893	SAR EVALUATION REPORT			Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device	Page 24 of 43	




Figure 7-3
Bluetooth P_{Low} Transmission Plot & Duty Cycle Calculation – Variant 1

$$\text{Duty Cycle} = \frac{\text{Pulse Width}}{\text{Period}} * 100\% = \frac{2.900\text{ms}}{3.750\text{ms}} * 100\% = 77.3\%$$

FCC ID: BCGA1893	PCTEST® SAR EVALUATION REPORT			Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device	Page 25 of 43	




Figure 7-4
Bluetooth P_{High} Transmission Plot & Duty Cycle Calculation – Variant 2

$$\text{Duty Cycle} = \frac{\text{Pulse Width}}{\text{Period}} * 100\% = \frac{2.905\text{ms}}{3.750\text{ms}} * 100\% = 77.5\%$$

FCC ID: BCGA1893	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device		Page 26 of 43

7.2.1 Bluetooth Power Reduction Verification Summary

Bluetooth Mode	Data Rate [Mbps]	Maximum	Test Case 1	Maximum		Test Case 1	
		Average Target Power [dBm] (Tolerance [dB])	Average Target Power [dBm] (Tolerance [dB])	Peak Conducted Power		Peak Conducted Power	
				[dBm]	[mW]	[dBm]	[mW]
BT BDR	1.0	15.5 (± 1.5)	8.0 (± 1.5)	15.51	35.580	7.83	6.069
BT EDR	2.0	13.0 (± 1.5)	7.5 (± 1.5)	15.07	32.151	9.93	9.838
BT LE	1.0	15.5 (± 1.5)	5.5 (± 1.5)	16.13	41.020	5.58	3.614

Test Case 1 represents a scenario in which Bluetooth powers would be reduced. Due to test setup conditions, peak powers were used to confirm the power reduction mechanism. According to the expected Peak-to-Average-Ratio of Bluetooth modes, the above measured peak powers confirm that the average powers for both maximum and reduced output power conditions are within allowed tolerance ranges.

7.2.2 Notes for Bluetooth

- The Bluetooth chipset in this device is produced by two different suppliers. The electrically identical modules are manufactured with the identical mechanical structure to meet the same specifications and functions. Two device variants are referenced as Variant 1 and Variant 2 in this report.
- Bluetooth SAR testing is completely performed on Variant 1, and Variant 2 is additionally evaluated for Bluetooth SAR with the same configuration of the highest reported SAR of Variant 1.
- Full power measurements were performed for variant 1 per FCC KDB Procedures 248227. Additional power measurements for variant 2 were additionally performed to support the SAR test configurations.




Figure 7-5
Bluetooth Power Measurement Setup

FCC ID: BCGA1893	 PCTEST	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device		Page 27 of 43

8 SYSTEM VERIFICATION

8.1 Tissue Verification

Table 8-1
Measured Tissue Properties

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
1/15/2018	2400B	21.7	2400	1.945	51.131	1.902	52.767	2.26%	-3.10%
			2450	2.015	50.952	1.950	52.700	3.33%	-3.32%
			2500	2.080	50.722	2.021	52.636	2.92%	-3.64%
1/18/2018	2400B	22.4	2400	1.955	51.747	1.902	52.767	2.79%	-1.93%
			2450	2.024	51.555	1.950	52.700	3.79%	-2.17%
			2500	2.094	51.348	2.021	52.636	3.61%	-2.45%
01/10/2018	5200B-5800B	22.8	5240	5.510	48.575	5.346	48.960	3.07%	-0.79%
			5260	5.536	48.513	5.369	48.933	3.11%	-0.86%
			5280	5.553	48.523	5.393	48.906	2.97%	-0.78%
			5300	5.570	48.476	5.416	48.879	2.84%	-0.82%
			5320	5.607	48.449	5.439	48.851	3.09%	-0.82%
			5520	5.891	48.124	5.673	48.580	3.84%	-0.94%
			5540	5.916	48.089	5.696	48.553	3.86%	-0.96%
			5600	5.988	47.954	5.766	48.471	3.85%	-1.07%
			5620	6.020	47.941	5.790	48.444	3.97%	-1.04%
			5680	6.118	47.829	5.860	48.363	4.40%	-1.10%
			5700	6.128	47.822	5.883	48.336	4.16%	-1.06%
			5745	6.196	47.783	5.936	48.275	4.38%	-1.02%
			5765	6.218	47.688	5.959	48.248	4.35%	-1.16%
			5785	6.257	47.625	5.982	48.220	4.60%	-1.23%

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 D01v01r04 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

FCC ID: BCGA1893	 SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device

8.2 Test System Verification

Prior to SAR assessment, the system is verified to $\pm 10\%$ of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix E.

Table 8-2
System Verification Results – 1g

System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Source SN	Probe SN	Measured SAR _{1g} (W/kg)	1 W Target SAR _{1g} (W/kg)	1 W Normalized SAR _{1g} (W/kg)	Deviation _{1g} (%)
CAL3	2450	BODY	01/15/2018	22.8	21.0	0.100	945	3333	5.420	50.200	54.200	7.97%
CAL3	2450	BODY	01/18/2018	23.9	21.2	0.100	921	3333	5.200	50.700	52.000	2.56%
CAL4	5250	BODY	01/10/2018	21.1	22.8	0.050	1123	7416	3.520	75.900	70.400	-7.25%
CAL4	5600	BODY	01/10/2018	21.1	22.8	0.050	1123	7416	3.920	78.900	78.400	-0.63%
CAL4	5750	BODY	01/10/2018	21.1	22.8	0.050	1123	7416	3.530	76.300	70.600	-7.47%




Figure 8-1
System Verification Setup Diagram



Figure 8-2
System Verification Setup Photo

FCC ID: BCGA1893	 SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device

9 SAR DATA SUMMARY

9.1 Standalone Body SAR Data

**Table 9-1
2.4 GHz WLAN Body SAR Data**

MEASUREMENT RESULTS																					
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Variant	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (1g) (W/kg)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g) (W/kg)	SAR (10g) (W/kg)	Reported SAR (10g) (W/kg)	Plot #
MHz	Ch.																				
2462	11	802.11b	DSSS	22	15.5	15.50	0.05	0 mm	A	1	F9FVT003JMN9	1	back	100.0	0.086	1.000	1.000	0.086	0.042	0.042	
2412	1	802.11b	DSSS	22	15.5	15.50	0.05	0 mm	A	1	F9FVT019JMN4G	1	bottom	100.0	0.984	1.000	1.000	0.984	0.314	0.314	
2437	6	802.11b	DSSS	22	15.5	15.41	-0.05	0 mm	A	1	F9FVT019JMN4G	1	bottom	100.0	0.847	1.021	1.000	0.865	0.273	0.279	
2462	11	802.11b	DSSS	22	15.5	15.50	-0.04	0 mm	A	1	F9FVT019JMN4G	1	bottom	100.0	0.760	1.000	1.000	0.760	0.246	0.246	
2412	1	802.11b	DSSS	22	15.5	15.44	0.03	0 mm	A	2	F9FVT019JMN48	1	bottom	99.9	0.846	1.014	1.001	0.859	0.269	0.273	
2462	11	802.11b	DSSS	22	15.5	15.50	0.01	0 mm	A	1	F9FVT003JMN9	1	left	100.0	0.227	1.000	1.000	0.227	0.103	0.103	
2462	11	802.11b	DSSS	22	15.5	15.50	-0.02	0 mm	B	1	F9FVT003JMN9	1	back	100.0	0.073	1.000	1.000	0.073	0.034	0.034	
2412	1	802.11b	DSSS	22	15.5	15.50	0.00	0 mm	B	1	F9FVT019JMN4G	1	bottom	100.0	0.780	1.000	1.000	0.780	0.253	0.253	
2437	6	802.11b	DSSS	22	15.5	15.35	-0.01	0 mm	B	1	F9FVT019JMN4G	1	bottom	100.0	0.891	1.035	1.000	0.922	0.290	0.300	
2462	11	802.11b	DSSS	22	15.5	15.50	-0.01	0 mm	B	1	F9FVT019JMN4G	1	bottom	100.0	1.180	1.000	1.000	1.180	0.384	0.384	
2462	11	802.11b	DSSS	22	15.5	15.33	0.01	0 mm	B	2	F9FVT01CJM48	1	bottom	99.9	1.060	1.040	1.001	1.104	0.340	0.354	
2462	11	802.11b	DSSS	22	15.5	15.50	0.01	0 mm	B	1	F9FVT003JMN9	1	right	100.0	0.149	1.000	1.000	0.149	0.066	0.066	
2462	11	802.11b	DSSS	22	15.5	15.50	0.00	0 mm	B	1	F9FVT019JMN4G	1	bottom	100.0	1.160	1.000	1.000	1.160	0.378	0.378	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT										Body											
Spatial Peak										1.6 W/kg (mW/g)											
Uncontrolled Exposure/General Population										averaged over 1 gram											

Note: Blue entry indicates variability measurement.

**Table 9-2
U-NII-2A WLAN Body SAR Data**

MEASUREMENT RESULTS																					
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Variant	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (1g) (W/kg)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g) (W/kg)	SAR (10g) (W/kg)	Reported SAR (10g) (W/kg)	Plot #
MHz	Ch.																				
5270	54	802.11n	OFDM	40	17.0	16.00	0.01	0 mm	A	1	F9FVT01DJM4G	13.5	back	98.2	0.032	1.259	1.018	0.041	0.011	0.014	
5270	54	802.11n	OFDM	40	17.0	16.00	0.02	0 mm	A	1	F9FVT01DJM4G	13.5	bottom	98.2	0.712	1.259	1.018	0.913	0.236	0.302	
5310	62	802.11n	OFDM	40	15.0	14.48	-0.07	0 mm	A	1	F9FVT01DJM4G	13.5	bottom	98.2	0.455	1.127	1.018	0.522	0.147	0.169	
5270	54	802.11n	OFDM	40	17.0	16.00	0.01	0 mm	A	2	F9FVT01NJM48	13.5	bottom	98.3	0.704	1.259	1.017	0.901	0.236	0.302	
5270	54	802.11n	OFDM	40	17.0	16.00	0.17	0 mm	A	1	F9FVT01DJM4G	13.5	left	98.2	0.055	1.259	1.018	0.070	0.022	0.028	
5270	54	802.11n	OFDM	40	17.0	16.93	0.13	0 mm	B	1	F9FVT01DJM4G	13.5	back	98.1	0.055	1.016	1.019	0.057	0.021	0.022	
5270	54	802.11n	OFDM	40	17.0	16.93	0.02	0 mm	B	1	F9FVT01DJM4G	13.5	bottom	98.1	1.100	1.016	1.019	1.139	0.377	0.390	
5310	62	802.11n	OFDM	40	15.0	14.50	0.03	0 mm	B	1	F9FVT01DJM4G	13.5	bottom	98.1	0.545	1.122	1.019	0.623	0.190	0.217	
5270	54	802.11n	OFDM	40	17.0	17.00	0.06	0 mm	B	2	F9FVT01NJM48	13.5	bottom	98.3	1.080	1.000	1.017	1.098	0.359	0.365	
5270	54	802.11n	OFDM	40	17.0	16.93	0.11	0 mm	B	1	F9FVT01DJM4G	13.5	right	98.1	0.084	1.016	1.019	0.087	0.030	0.031	
5270	54	802.11n	OFDM	40	17.0	16.93	-0.10	0 mm	B	1	F9FVT01DJM4G	13.5	bottom	98.1	1.070	1.016	1.019	1.108	0.365	0.378	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT										Body											
Spatial Peak										1.6 W/kg (mW/g)											
Uncontrolled Exposure/General Population										averaged over 1 gram											

Note: Blue entry indicates variability measurement.

FCC ID: BCGA1893	 PCTEST Engineering Laboratory, Inc.	SAR EVALUATION REPORT										Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device										Page 30 of 43

Table 9-3
U-NII-2C WLAN Body SAR Data

MEASUREMENT RESULTS																					
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Variant	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (1g) (W/kg)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g) (W/kg)	SAR (10g) (W/kg)	Reported SAR (10g) (W/kg)	Plot #
MHz	Ch.																				
5690	138	802.11ac	OFDM	80	17.0	16.99	0.11	0 mm	A	1	F9FVT01JJM4G	29.3	back	96.6	0.063	1.002	1.035	0.065	0.020	0.021	
5690	122	802.11ac	OFDM	80	17.0	16.98	0.01	0 mm	A	1	F9FVT01JJM4G	29.3	bottom	96.6	1.020	1.005	1.035	1.061	0.354	0.368	
5690	138	802.11ac	OFDM	80	17.0	16.99	0.14	0 mm	A	1	F9FVT01JJM4G	29.3	bottom	96.6	0.732	1.002	1.035	0.759	0.254	0.263	
5690	122	802.11ac	OFDM	80	17.0	16.91	-0.03	0 mm	A	2	F9FVT01FJM48	29.3	bottom	96.6	1.040	1.021	1.035	1.099	0.366	0.387	
5690	138	802.11ac	OFDM	80	17.0	16.99	-0.09	0 mm	A	1	F9FVT01JJM4G	29.3	left	96.6	0.121	1.002	1.035	0.125	0.047	0.049	
5690	138	802.11ac	OFDM	80	17.0	16.00	0.09	0 mm	B	1	F9FVT01JJM4G	29.3	back	96.6	0.068	1.259	1.035	0.089	0.027	0.035	
5530	106	802.11ac	OFDM	80	14.0	14.00	0.03	0 mm	B	1	F9FVT01JJM4G	29.3	bottom	96.6	0.380	1.000	1.035	0.393	0.134	0.139	
5610	122	802.11ac	OFDM	80	17.0	15.97	0.12	0 mm	B	1	F9FVT01JJM4G	29.3	bottom	96.6	0.625	1.268	1.035	0.820	0.229	0.301	
5690	138	802.11ac	OFDM	80	17.0	16.00	0.01	0 mm	B	1	F9FVT01JJM4G	29.3	bottom	96.6	0.698	1.259	1.035	0.910	0.260	0.339	
5690	138	802.11ac	OFDM	80	17.0	16.00	0.07	0 mm	B	2	F9FVT01FJM48	29.3	bottom	96.6	0.658	1.259	1.035	0.857	0.238	0.310	
5690	138	802.11ac	OFDM	80	17.0	16.00	0.08	0 mm	B	1	F9FVT01JJM4G	29.3	right	96.6	0.121	1.259	1.035	0.158	0.048	0.063	
5610	122	802.11ac	OFDM	80	17.0	16.91	-0.15	0 mm	A	2	F9FVT01FJM48	29.3	bottom	96.6	1.030	1.021	1.035	1.088	0.358	0.378	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT										Body											
Spatial Peak										1.6 W/kg (mW/g)											
Uncontrolled Exposure/General Population										averaged over 1 gram											

Note: Blue entry indicates variability measurement.

Table 9-4
U-NII-3 WLAN Body SAR Data

MEASUREMENT RESULTS																					
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Variant	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (1g) (W/kg)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g) (W/kg)	SAR (10g) (W/kg)	Reported SAR (10g) (W/kg)	Plot #
MHz	Ch.																				
5775	155	802.11ac	OFDM	80	16.5	16.50	0.07	0 mm	A	1	F9FVT01JJM4G	29.3	back	96.6	0.052	1.000	1.035	0.054	0.016	0.017	
5775	155	802.11ac	OFDM	80	16.5	16.50	-0.12	0 mm	A	1	F9FVT01JJM4G	29.3	bottom	96.6	0.802	1.000	1.035	0.830	0.277	0.287	
5775	155	802.11ac	OFDM	80	16.5	16.50	-0.01	0 mm	A	2	F9FVT01JJM48	29.3	bottom	96.6	0.720	1.000	1.035	0.745	0.249	0.258	
5775	155	802.11ac	OFDM	80	16.5	16.50	0.21	0 mm	A	1	F9FVT01JJM4G	29.3	left	96.6	0.105	1.000	1.035	0.109	0.035	0.036	
5775	155	802.11ac	OFDM	80	16.5	15.94	0.03	0 mm	B	1	F9FVT01JJM4G	29.3	back	96.6	0.068	1.138	1.035	0.080	0.023	0.027	
5775	155	802.11ac	OFDM	80	16.5	15.94	0.00	0 mm	B	1	F9FVT01JJM4G	29.3	bottom	96.6	0.787	1.138	1.035	0.927	0.291	0.343	
5775	155	802.11ac	OFDM	80	16.5	16.00	0.01	0 mm	B	2	F9FVT01FJM48	29.3	bottom	96.6	0.723	1.122	1.035	0.840	0.264	0.307	
5775	155	802.11ac	OFDM	80	16.5	15.94	0.03	0 mm	B	1	F9FVT01JJM4G	29.3	right	96.6	0.132	1.138	1.035	0.155	0.047	0.055	
5775	155	802.11ac	OFDM	80	16.5	16.50	-0.14	0 mm	A	1	F9FVT01JJM4G	29.3	bottom	96.6	0.817	1.000	1.035	0.846	0.279	0.289	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT										Body											
Spatial Peak										1.6 W/kg (mW/g)											
Uncontrolled Exposure/General Population										averaged over 1 gram											

Note: Blue entry indicates variability measurement.

FCC ID: BCGA1893		SAR EVALUATION REPORT									Approved by: Quality Manager						
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device								Page 31 of 43							

© 2018 PCTEST Engineering Laboratory, Inc. REV 20.06 M
2018 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Table 9-5
WLAN MIMO Body SAR Data

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Variant	Cube	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (1g) (W/kg)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g) (W/kg)	SAR (10g) (W/kg)	Reported SAR (10g) (W/kg)	Plot #
MHz	Ch.																					
5270	54	802.11n	OFDM	40	17.0	15.94	-0.03	0 mm	MIMO	1	1	F9FVT01DJM4G	13.5	bottom	98.3	0.690	1.276	1.017	0.895	0.229	0.297	
					17.0	16.98					2					1.030	1.005	1.017	1.053	0.350	0.358	
5310	62	802.11n	OFDM	40	13.5	13.36	0.04	0 mm	MIMO	1	1	F9FVT01DJM4G	13.5	bottom	98.3	0.336	1.033	1.017	0.353	0.115	0.121	
					13.5	13.32					2					0.401	1.042	1.017	0.425	0.138	0.146	
5270	54	802.11n	OFDM	40	17.0	15.92	-0.07	0 mm	MIMO	2	1	F9FVT01FJM48	13.5	bottom	98.3	0.627	1.282	1.017	0.817	0.201	0.262	
					17.0	17.00					2					0.996	1.000	1.017	1.013	0.342	0.348	
5530	106	802.11ac	OFDM	80	13.0	13.00	-0.12	0 mm	MIMO	1	1	F9FVT01JJM4G	29.3	bottom	95.6	0.416	1.000	1.046	0.435	0.145	0.152	
					13.0	12.92					2					0.316	1.019	1.046	0.337	0.113	0.120	
5610	122	802.11ac	OFDM	80	17.0	16.91	-0.17	0 mm	MIMO	1	1	F9FVT01JJM4G	29.3	bottom	95.6	0.958	1.021	1.046	1.023	0.336	0.359	
					17.0	15.98					2					0.673	1.265	1.046	0.891	0.247	0.327	
5690	138	802.11ac	OFDM	80	17.0	17.00	-0.14	0 mm	MIMO	1	1	F9FVT01JJM4G	29.3	bottom	95.6	0.855	1.000	1.046	0.894	0.296	0.310	
					17.0	15.98					2					0.650	1.265	1.046	0.860	0.234	0.310	
5610	122	802.11ac	OFDM	80	17.0	16.92	-0.09	0 mm	MIMO	2	1	F9FVT01FJM48	29.3	bottom	95.6	0.916	1.019	1.046	0.976	0.315	0.336	
					17.0	16.00					2					0.634	1.259	1.046	0.835	0.228	0.300	
5755	151	802.11n	OFDM	40	16.5	16.26	-0.11	0 mm	MIMO	1	1	F9FVT01JJM4G	13.5	bottom	98.3	0.705	1.057	1.017	0.758	0.228	0.245	
					16.5	16.45					2					0.719	1.012	1.017	0.740	0.270	0.278	
5755	151	802.11n	OFDM	40	16.5	16.48	0.06	0 mm	MIMO	2	1	F9FVT01FJM48	13.5	bottom	98.3	0.755	1.005	1.017	0.772	0.257	0.263	
					16.5	16.48					2					0.716	1.005	1.017	0.732	0.258	0.264	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					Body 1.6 W/kg (mW/g) averaged over 1 gram																	

Note: Due to the spatial separation of Antenna A and Antenna B, two measurement cubes were evaluated during MIMO SAR testing. Cube 1 and 2 are located over the SAR distributions produced by Antenna A and B, respectively. Due to the spatial separation of the distributions, the conducted power of each antenna was individually considered for each measurement cube to determine the reported SAR, per manufacturer's request.

Table 9-6
Bluetooth P_{High} Body SAR Data

MEASUREMENT RESULTS																				
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Variant	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (1g) (W/kg)	Scaling Factor (Cond Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g) (W/kg)	SAR (10g) (W/kg)	Reported SAR (10g) (W/kg)	Plot #	
MHz	Ch.																			
2441	39	Bluetooth	FHSS	17.0	16.98	0.07	0 mm	1	F9FVT019JM4G	1	back	77.3	0.068	1.005	1.003	0.069	0.032	0.032		
2402	0	Bluetooth	FHSS	17.0	15.94	0.07	0 mm	1	F9FVT019JM4G	1	bottom	77.3	0.504	1.276	1.003	0.645	0.164	0.210		
2441	39	Bluetooth	FHSS	17.0	16.98	-0.09	0 mm	1	F9FVT019JM4G	1	bottom	77.3	1.000	1.005	1.003	1.008	0.327	0.330	A3	
2441	39	Bluetooth	FHSS	17.0	16.49	0.04	0 mm	2	F9FVT01FJM48	1	bottom	77.5	0.825	1.125	1.000	0.928	0.268	0.302		
2480	78	Bluetooth	FHSS	17.0	16.06	0.07	0 mm	1	F9FVT019JM4G	1	bottom	77.3	0.552	1.242	1.003	0.688	0.181	0.225		
2441	39	Bluetooth	FHSS	17.0	16.98	0.05	0 mm	1	F9FVT019JM4G	1	left	77.3	0.156	1.005	1.003	0.157	0.070	0.071		
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					Body 1.6 W/kg (mW/g) averaged over 1 gram															

Note: The reported SAR was scaled to the 77.5% transmission duty factor to determine compliance since the duty factor of the device is permanently limited to 77.5% per the manufacturer.

FCC ID: BCGA1893	 PCTEST [®] Engineering Laboratory, Inc.	SAR EVALUATION REPORT								Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device								Page 32 of 43

© 2018 PCTEST Engineering Laboratory, Inc. REV 20.06 M
12/06/2017

© 2018 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

Table 9-7
Bluetooth P_{Low} Body SAR Data

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Variant	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle	SAR (1g)	Scaling Factor (Cond Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.												(W/kg)	(W/kg)	(W/kg)	(W/kg)	(W/kg)		
2402	0	Bluetooth	FHSS	9.5	9.50	0.03	0 mm	1	F9FVT019JM4G	1	back	77.3	0.014	1.000	1.003	0.014	0.005	0.005	
2402	0	Bluetooth	FHSS	9.5	9.50	-0.08	0 mm	1	F9FVT019JM4G	1	bottom	77.3	0.147	1.000	1.003	0.147	0.047	0.047	
2441	39	Bluetooth	FHSS	9.5	9.18	0.14	0 mm	1	F9FVT019JM4G	1	bottom	77.3	0.149	1.076	1.003	0.161	0.048	0.052	
2480	78	Bluetooth	FHSS	9.5	8.91	0.14	0 mm	1	F9FVT019JM4G	1	bottom	77.3	0.122	1.146	1.003	0.140	0.039	0.045	
2402	0	Bluetooth	FHSS	9.5	9.50	0.10	0 mm	1	F9FVT019JM4G	1	left	77.3	0.030	1.000	1.003	0.030	0.013	0.013	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT				Body 1.6 W/kg (mW/g) averaged over 1 gram															
Spatial Peak				Uncontrolled Exposure/General Population															

Note: The reported SAR was scaled to the 77.5% transmission duty factor to determine compliance since the duty factor of the device is permanently limited to 77.5% per the manufacturer.

FCC ID: BCGA1893	 SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device

9.2 SAR Test Notes

General Notes:

1. The test data reported are the worst-case SAR values according to test procedures specified in FCC KDB Publication 616217 D04v01r02 and FCC KDB Publication 447498 D01v06.
2. Batteries are fully charged at the beginning of the SAR measurements.
3. Liquid tissue depth was at least 15.0 cm for all frequencies.
4. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
5. SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v06.
6. Per FCC KDB 865664 D01v01r04, variability SAR tests were performed when the measured SAR results for a frequency band were greater than or equal to 0.8 W/kg. Repeated SAR measurements are highlighted in the tables above for clarity. Please see Section 11 for variability analysis.
7. FCC KDB Publication 616217 D04v01r02 Section 4.3, SAR tests are required for the back surface and edges of the tablet with the tablet touching the phantom. The SAR Exclusion Threshold in FCC KDB 447498 D01v06 was applied to determine SAR test exclusion for adjacent edge configurations.

WLAN/Bluetooth Notes:

1. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 2.4 GHz WIFI single transmission chain operations, the highest measured maximum output power channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4 GHz 802.11g/n) was not required due to the maximum allowed powers and the highest reported DSSS SAR. See Section 6.2.4 for more information.
2. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 5 GHz WIFI single transmission chain operations, the initial test configuration was selected according to the transmission mode with the highest maximum allowed powers. Other transmission modes were not investigated since the highest reported SAR for initial test configuration adjusted by the ratio of maximum output powers is less than 1.2 W/kg for 1g evaluations. See Section 6.2.5 for more information.
3. Per KDB Publication 248227 D01v02r02, SAR for MIMO was evaluated by following the simultaneous SAR provisions from KDB Publication 447498 D01v06 by either evaluating the sum of the 1g SAR values of each antenna transmitting independently or making a SAR measurement with both antennas transmitting simultaneously. Please see Section 10 for complete analysis.
4. When the maximum reported 1g averaged SAR is ≤ 0.8 W/kg, SAR testing on additional channels was not required. Otherwise, SAR for the next highest output power channel was required until the reported SAR result was ≤ 1.20 W/kg for 1g evaluations or all test channels were measured.
5. The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools. The reported SAR was scaled to the 100% transmission duty factor to determine compliance. Procedures used to measure the duty factor are identical to that in the associated EMC test reports.
6. Bluetooth SAR was measured with a test mode with hopping disabled with DH5 operation. The reported SAR was scaled to the 77.5% transmission duty factor to determine compliance since the duty factor of the device is limited to 77.5% per the manufacturer. See Section 7.2 for the time domain plot and calculation for the duty factor of the device.

FCC ID: BCGA1893	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device	Page 34 of 43

10 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

10.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v06 are applicable to devices with built-in unlicensed transmitters such as 802.11 and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

10.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore, simultaneous transmission analysis is required. Per FCC KDB Publication 447498 D01v06 4.3.2 and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1g SAR for all the simultaneous transmitting antennas in a specific physical test configuration is ≤ 1.6 W/kg. The different test positions in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1g or 10g SAR.

10.3 Body SAR Simultaneous Transmission Analysis

Table 10-1
Simultaneous Transmission Scenario with 2.4 GHz WLAN

Simult Tx	Configuration	2.4 GHz WLAN Ant A SAR (W/kg)	2.4 GHz WLAN Ant B SAR (W/kg)	Σ SAR (W/kg)	SPLSR
		1	2	1+2	1+2
Body SAR	Back	0.086	0.073	0.159	N/A
	Bottom	0.984	1.180	See Note 1	0.03
	Right	0.400*	0.149	0.549	N/A
	Left	0.227	0.400*	0.627	N/A

Table 10-2
Simultaneous Transmission Scenario with 5 GHz WLAN

Simult Tx	Configuration	5 GHz WLAN Ant A SAR (W/kg)	5 GHz WLAN Ant B SAR (W/kg)	Σ SAR (W/kg)	SPLSR
		1	2	1+2	1+2
Body SAR	Back	0.065	0.089	0.154	N/A
	Bottom	1.099	1.139	See Note 3	N/A
	Right	0.400*	0.158	0.558	N/A
	Left	0.125	0.400*	0.525	N/A

FCC ID: BCGA1893	 PCTEST Engineering Laboratory, Inc.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device		Page 35 of 43

Table 10-3
Simultaneous Transmission Scenario with 2.4 GHz Bluetooth and 5 GHz WLAN MIMO

Simult Tx	Configuration	Bluetooth P_{low} SAR (W/kg)	5 GHz WLAN Ant A SAR (W/kg)	5 GHz WLAN Ant B SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Body SAR	Back	0.014	0.065	0.089	0.079	0.103	0.168
	Bottom	0.161	1.099	1.139	1.260	1.300	See Table 10-4
	Right	0.400*	0.400*	0.158	0.800	0.558	0.958
	Left	0.030	0.125	0.400*	0.155	0.430	0.555

Table 10-4
Bottom Edge Simultaneous Transmission Scenario with Bluetooth and 5 GHz WLAN

Simult Tx	Configuration	Bluetooth P_{Low} SAR (W/kg)	5 GHz WLAN MIMO SAR (W/kg)	Σ SAR (W/kg)
		1	2	
Body SAR	Bottom	0.161	1.053	1.214

Notes:

1. No evaluation was performed to determine the aggregate 1g SAR for this configuration as the SPLS ratio between the antenna pairs was not greater than 0.04 per FCC KDB 447498 D01v06. See Section 10.4 for detailed SPLS ratio analysis.
2. (*) When the antenna separation distance was > 50 mm, an estimated SAR of 0.4 W/kg was used to determine the simultaneous transmission SAR exclusion for test positions excluded per FCC KDB Publication 447498D01v06. The simultaneous SAR sum using this estimation are highlighted in gray.
3. Simultaneous transmission of 5 GHz WLAN Ant A and 5 GHz WLAN Ant B for the bottom edge was evaluated with both antennas transmitting per KDB Publication 248227 D01v02r02. Please see Table 9-5 for data for this configuration.

10.4 SPLSR Evaluation and Analysis

Per FCC KDB Publication 447498 D01v06, when the sum of the standalone transmitters is more than 1.6 W/kg for 1g, the SAR sum to peak locations can be analyzed to determine SAR distribution overlaps. When the SAR peak to location ratio (shown below) for each pair of antennas is ≤ 0.04 for 1g, simultaneous SAR evaluation is not required. The distance between the transmitters was calculated using the following formula.

$$\text{Distance}_{\text{Tx1} - \text{Tx2}} = R_i = \sqrt{(x_1 - x_2)^2 + (y_1 - y_2)^2}$$

$$\text{SPLS Ratio} = \frac{(SAR_1 + SAR_2)^{1.5}}{R_i}$$

FCC ID: BCGA1893	PCTEST® Engineering Laboratory, Inc.			SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device			

10.4.1 Bottom Side SPLSR Evaluation and Analysis


Table 10-5
Peak SAR Locations for Body Bottom Side

Mode/Band	x (mm)	y (mm)	Reported SAR (W/kg)
2.4 GHz WLAN Antenna A	-12.50	61.20	0.984
2.4 GHz WLAN Antenna B	-8.50	-61.20	1.18

Table 10-6
Bottom Edge SAR to Peak Location Separation Ratio Calculations

Antenna Pair		Standalone SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio	Plot Number
Ant "a"	Ant "b"	a	b	a+b	D_{a-b}	$(a+b)^{1.5}/D_{a-b}$	
2.4 GHz WLAN Antenna A	2.4 GHz WLAN Antenna B	0.984	1.18	2.164	122.47	0.03	Figure 10-1

Figure 10-1
Bottom Side SAR to Peak Location Separation Ratio Plot



10.5 Simultaneous Transmission Conclusion

The above numerical summed SAR results and SPLSR analysis are sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v06 and IEEE 1528- 2013 Section 6.3.4.1.

FCC ID: BCGA1893		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device		Page 37 of 43

11 SAR MEASUREMENT VARIABILITY

11.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01r04, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

- 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg ($\sim 10\%$ from the 1g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
- 4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

Table 11-1
Body SAR Measurement Variability Results

BODY VARIABILITY RESULTS																
Band	FREQUENCY		Mode	Service	Variant	Data Rate (Mbps)	Side	Spacing	Measured SAR (1g) (W/kg)	1st Repeated SAR (1g) (W/kg)	Ratio	2nd Repeated SAR (1g) (W/kg)	Ratio	3rd Repeated SAR (1g) (W/kg)	Ratio	
	MHz	Ch.														
2450	2462.00	11	802.11b, 22 MHz Bandwidth	DSSS, Antenna B	1	1	bottom	0 mm	1.180	1.160	1.02	N/A	N/A	N/A	N/A	
5250	5270.00	54	802.11n, 40 MHz Bandwidth	OFDM, Antenna B	1	13.5	bottom	0 mm	1.100	1.070	1.03	N/A	N/A	N/A	N/A	
5600	5610.00	122	802.11ac, 80 MHz Bandwidth	OFDM, Antenna A	2	29.3	bottom	0 mm	1.040	1.030	1.01	N/A	N/A	N/A	N/A	
5750	5775.00	155	802.11ac, 80 MHz Bandwidth	OFDM, Antenna A	1	29.3	bottom	0 mm	0.802	0.817	1.02	N/A	N/A	N/A	N/A	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Body 1.6 W/kg (mW/g) averaged over 1 gram							

11.2 Measurement Uncertainty

The measured SAR was < 1.5 W/kg for all frequency bands. Therefore, per KDB Publication 865664 D01v01r04, the extended measurement uncertainty analysis per IEEE 1528-2013 was not required.

FCC ID: BCGA1893	 PCTEST Engineering Laboratory, Inc.	SAR EVALUATION REPORT				Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device				

12 EQUIPMENT LIST

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	E8257D	(250kHz-20GHz) Signal Generator	3/22/2017	Annual	3/22/2018	MY45470194
Agilent	8594A	(9kHz-2.9GHz) Spectrum Analyzer	N/A	N/A	N/A	3051A00187
SPEAG	D2450V2	2450 MHz SAR Dipole	5/9/2017	Annual	5/9/2018	945
SPEAG	D2450V2	2450 MHz SAR Dipole	9/11/2017	Annual	9/11/2018	921
Keysight Technologies	N9030A	3Hz-44GHz PXA Signal Analyzer	3/13/2017	Annual	3/13/2018	MY49430244
Narda	4014C-6	4 - 8 GHz SMA 6 dB Directional Coupler	CBT	N/A	CBT	N/A
SPEAG	D5GHzV2	5 GHz SAR Dipole	3/9/2017	Annual	3/9/2018	1123
MCL	BW-N6W5+	6dB Attenuator	CBT	N/A	CBT	1139
Amplifier Research	150A100C	Amplifier	CBT	N/A	CBT	350132
Amplifier Research	1551G6	Amplifier	CBT	N/A	CBT	343972
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Narda	BW-S3W2	Attenuator (3dB)	CBT	N/A	CBT	120
Pasternack	PE2208-6	Bidirectional Coupler	CBT	N/A	CBT	N/A
Pasternack	PE2209-10	Bidirectional Coupler	CBT	N/A	CBT	N/A
SPEAG	DAE4	Dasy Data Acquisition Electronics	9/15/2017	Annual	9/15/2018	1408
SPEAG	DAE4	Dasy Data Acquisition Electronics	6/21/2017	Annual	6/21/2018	701
SPEAG	DAK-3.5	Dielectric Assessment Kit	5/10/2017	Annual	5/10/2018	1070
Mitutoyo	CD-6"CSX	Digital Caliper	3/2/2016	Biennial	3/2/2018	13264162
Keysight	772D	Dual Directional Coupler	CBT	N/A	CBT	MY52180215
Agilent	E4438C	ESG Vector Signal Generator	3/24/2017	Annual	3/24/2018	MY45091346
MiniCircuits	SLP-2400+	Low Pass Filter	CBT	N/A	CBT	R8979500903
MiniCircuits	VLF-6000+	Low Pass Filter	N/A	N/A	N/A	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Agilent	N5182A	MXG Vector Signal Generator	2/28/2017	Annual	2/28/2018	MY47420800
Anritsu	ML2496A	Power Meter	10/9/2017	Annual	10/9/2018	1138001
Anritsu	MA2411B	Pulse Power Sensor	11/15/2017	Annual	11/15/2018	1339007
Anritsu	MA2411B	Pulse Power Sensor	11/22/2017	Annual	11/22/2018	1339008
Rohde & Schwarz	CMW500	Radio Communication Tester	4/12/2017	Annual	4/12/2018	128635
SPEAG	ES3DV3	SAR Probe	9/18/2017	Annual	9/18/2018	3333
SPEAG	EX3DV4	SAR Probe	7/18/2017	Annual	7/18/2018	7416
COMTECH	AR85729-5/5759B	Solid State Amplifier	CBT	N/A	CBT	M3W1A00-1002
COMTech	AR85729-5	Solid State Amplifier	CBT	N/A	CBT	M155A00-009
Agilent	8753ES	S-Parameter Network Analyzer	9/14/2017	Annual	9/14/2018	US39170118
Agilent	8753ES	S-Parameter Vector Network Analyzer	8/17/2017	Annual	8/17/2018	MY40003841
Control Company	4040	Therm./ Clock/ Humidity Monitor	3/1/2017	Biennial	3/1/2019	170152009
Control Company	4040	Therm./Clock/Humidity Monitor	3/31/2017	Biennial	3/31/2019	170232394
Pasternack	PE5011-1	Torque Wrench	7/19/2017	Biennial	7/19/2019	N/A
Pasternack	PE5011-1	Torque Wrench	7/19/2017	Biennial	7/19/2019	N/A
Control Company	4352	Ultra Long Stem Thermometer	2/14/2017	Biennial	2/14/2019	170112507
Control Company	4352	Ultra Long Stem Thermometer	5/2/2017	Biennial	5/2/2019	170330160
Control Company	4352	Ultra Long Stem Thermometer	3/8/2016	Biennial	3/8/2018	160261729
Control Company	4352	Ultra Long Stem Thermometer	3/8/2016	Biennial	3/8/2018	160261694
Anritsu	MA24106A	USB Power Sensor	7/5/2017	Annual	7/5/2018	1349511
Anritsu	MA24106A	USB Power Sensor	7/5/2017	Annual	7/5/2018	1349513
Agilent	E5515C	Wireless Communications Test Set	6/18/2015	Triennial	6/18/2018	GB41450275
Agilent	N4010A	Wireless Connectivity Test Set	N/A	N/A	N/A	GB46170464

Note: CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.

FCC ID: BCGA1893	 SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device

13 MEASUREMENT UNCERTAINTIES

a	c	d	e = f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System								
Probe Calibration	6.55	N	1	1.0	1.0	6.6	6.6	∞
Axial Isotropy	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemispherical Isotropy	1.3	N	1	0.7	0.7	0.9	0.9	∞
Boundary Effect	2.0	R	1.73	1.0	1.0	1.2	1.2	∞
Linearity	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	0.25	R	1.73	1.0	1.0	0.1	0.1	∞
Readout Electronics	0.3	N	1	1.0	1.0	0.3	0.3	∞
Response Time	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions - Noise	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
RF Ambient Conditions - Reflections	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	6.7	R	1.73	1.0	1.0	3.9	3.9	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Test Sample Related								
Test Sample Positioning	2.7	N	1	1.0	1.0	2.7	2.7	35
Device Holder Uncertainty	1.67	N	1	1.0	1.0	1.7	1.7	5
Output Power Variation - SAR drift measurement	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
SAR Scaling	0.0	R	1.73	1.0	1.0	0.0	0.0	∞
Phantom & Tissue Parameters								
Phantom Uncertainty (Shape & Thickness tolerances)	7.6	R	1.73	1.0	1.0	4.4	4.4	∞
Liquid Conductivity - measurement uncertainty	4.2	N	1	0.78	0.71	3.3	3.0	10
Liquid Permittivity - measurement uncertainty	4.1	N	1	0.23	0.26	1.0	1.1	10
Liquid Conductivity - Temperature Uncertainty	3.4	R	1.73	0.78	0.71	1.5	1.4	∞
Liquid Permittivity - Temperature Uncertainty	0.6	R	1.73	0.23	0.26	0.1	0.1	∞
Liquid Conductivity - deviation from target values	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Permittivity - deviation from target values	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Combined Standard Uncertainty (k=1)	RSS					11.5	11.3	60
Expanded Uncertainty (95% CONFIDENCE LEVEL)	k=2					23.0	22.6	

FCC ID: BCGA1893	 SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device

14 CONCLUSION

14.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Innovation, Science, and Economic Development Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

FCC ID: BCGA1893	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device	Page 41 of 43

15 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2013, IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 1 -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

FCC ID: BCGA1893	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device	Page 42 of 43

- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz), July 2016.
- [21] Innovation, Science, Economic Development Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 5, March 2015.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2015
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement Guidance for IEEE 802.11 Transmitters, KDB Publication 248227 D01
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D03-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

FCC ID: BCGA1893	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C1710060005-01-R4.BCG	Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device	Page 43 of 43

APPENDIX A: SAR TEST DATA

PCTEST ENGINEERING LABORATORY, INC.

DUT: BCGA1893; Type: Tablet Device; Serial: F9FVT019JM4G

Communication System: UID 0, IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2462$ MHz; $\sigma = 2.031$ S/m; $\epsilon_r = 50.897$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 0 cm

Test Date: 01-15-2018; Ambient Temp: 22.8°C; Tissue Temp: 21.0°C

Probe: ES3DV3 - SN3333; ConvF(4.35, 4.35, 4.35); Calibrated: 9/18/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 9/15/2017

Phantom: SAM with CRP v5.0; Type: QD000P40CD; Serial: TP:1868

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

**Mode: IEEE 802.11b, 22 MHz Bandwidth,
Body SAR, Ch 11, 1 Mbps, Bottom Edge, Antenna B, Variant 1**


Area Scan (11x16x1): Measurement grid: dx=5mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 28.43 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 3.66 W/kg

SAR(1 g) = 1.18 W/kg; SAR(10 g) = 0.384 W/kg



0 dB = 1.86 W/kg = 2.70 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: BCGA1893; Type: Tablet Device; Serial: F9FVT01DJM4G

Communication System: UID 0, IEEE 802.11n; Frequency: 5270 MHz; Duty Cycle: 1:1

Medium: 5 GHz Medium parameters used (interpolated):

$f = 5270$ MHz; $\sigma = 5.544$ S/m; $\epsilon_r = 48.518$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 0 cm

Test Date: 01-10-2018; Ambient Temp: 21.1°C; Tissue Temp: 22.8°C

Probe: EX3DV4 - SN7416; ConvF(4.88, 4.88, 4.88); Calibrated: 7/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn701; Calibrated: 6/21/2017

Phantom: SAM with CRP v5.0; Type: QD000P40CD; Serial: TP:1873

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

**Mode: IEEE 802.11n, U-NII-2A, 40 MHz Bandwidth,
Body SAR, Ch 54, 13.5 Mbps, Bottom Edge, Antenna B, Variant 1**


Area Scan (10x19x1): Measurement grid: dx=5mm, dy=10mm

Zoom Scan (9x9x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 14.99 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 4.66 W/kg

SAR(1 g) = 1.1 W/kg; SAR(10 g) = 0.377 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: BCGA1893; Type: Tablet Device; Serial: F9FVT019JM4G

Communication System: UID 0, Bluetooth; Frequency: 2441 MHz; Duty Cycle: 1:1.2936

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2441$ MHz; $\sigma = 2.012$ S/m; $\epsilon_r = 51.59$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 0 cm

Test Date: 01-18-2018; Ambient Temp: 23.9°C; Tissue Temp: 21.2°C

Probe: ES3DV3 - SN3333; ConvF(4.35, 4.35, 4.35); Calibrated: 9/18/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 9/15/2017

Phantom: SAM with CRP v5.0; Type: QD000P40CD; Serial: TP:1868

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

Mode: Bluetooth, Body SAR, Ch 39, 1 Mbps, Bottom Edge, Variant 1


Area Scan (11x16x1): Measurement grid: dx=5mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 22.30 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 3.05 W/kg

SAR(1 g) = 1 W/kg; SAR(10g) = 0.327 W/kg



APPENDIX B: SYSTEM VERIFICATION

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 945

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2450$ MHz; $\sigma = 2.015$ S/m; $\epsilon_r = 50.952$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-15-2018; Ambient Temp: 22.8°C; Tissue Temp: 21.0°C

Probe: ES3DV3 - SN3333; ConvF(4.35, 4.35, 4.35); Calibrated: 9/18/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 9/15/2017

Phantom: SAM with CRP v5.0; Type: QD000P40CD; Serial: TP:1868

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 11.3 W/kg

SAR(1 g) = 5.42 W/kg; SAR(10 g) = 2.49 W/kg

Deviation(1 g) = 7.97%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 921

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2450$ MHz; $\sigma = 2.024$ S/m; $\epsilon_r = 51.555$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-18-2018; Ambient Temp: 23.9°C; Tissue Temp: 21.2°C

Probe: ES3DV3 - SN3333; ConvF(4.35, 4.35, 4.35); Calibrated: 9/18/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 9/15/2017

Phantom: SAM with CRP v5.0; Type: QD000P40CD; Serial: TP:1868

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 10.9 W/kg

SAR(1 g) = 5.2 W/kg; SAR(10 g) = 2.4 W/kg

Deviation(1 g) = 2.56%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1123

Communication System: UID 0, CW; Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: 5 GHz Medium parameters used (interpolated):

$f = 5250$ MHz; $\sigma = 5.523$ S/m; $\epsilon_r = 48.544$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-10-2018; Ambient Temp: 21.1°C; Tissue Temp: 22.8°C

Probe: EX3DV4 - SN7416; ConvF(4.88, 4.88, 4.88); Calibrated: 7/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn701; Calibrated: 6/21/2017

Phantom: SAM with CRP v5.0; Type: QD000P40CD; Serial: TP:1873

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

5250 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 15.8 W/kg

SAR(1 g) = 3.52 W/kg; SAR(10 g) = 0.980 W/kg

Deviation(1 g) = -7.25%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1123

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5 GHz Medium parameters used:

$f = 5600$ MHz; $\sigma = 5.988$ S/m; $\epsilon_r = 47.954$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-10-2018; Ambient Temp: 21.1°C; Tissue Temp: 22.8°C

Probe: EX3DV4 - SN7416; ConvF(4.15, 4.15, 4.15); Calibrated: 7/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn701; Calibrated: 6/21/2017

Phantom: SAM with CRP v5.0; Type: QD000P40CD; Serial: TP:1873

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

5600 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 18.6 W/kg

SAR(1 g) = 3.92 W/kg; SAR(10 g) = 1.08 W/kg

Deviation(1 g) = -0.63%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1123

Communication System: UID 0, CW; Frequency: 5750 MHz; Duty Cycle: 1:1

Medium: 5 GHz Medium parameters used (interpolated):

$f = 5750$ MHz; $\sigma = 6.201$ S/m; $\epsilon_r = 47.759$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 01-10-2018; Ambient Temp: 21.1°C; Tissue Temp: 22.8°C

Probe: EX3DV4 - SN7416; ConvF(4.35, 4.35, 4.35); Calibrated: 7/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn701; Calibrated: 6/21/2017

Phantom: SAM with CRP v5.0; Type: QD000P40CD; Serial: TP:1873

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

5750 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 16.7 W/kg

SAR(1 g) = 3.53 W/kg; SAR(10 g) = 0.983 W/kg

Deviation(1 g) = -7.47%



APPENDIX C: PROBE CALIBRATION



Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **PC Test**

Certificate No: **D2450V2-945_May17**

CALIBRATION CERTIFICATE

Object **D2450V2 - SN:945**

Calibration procedure(s) **QA CAL-05.v9**
Calibration procedure for dipole validation kits above 700 MHz

Calibration date: **May 09, 2017**

BNV

05-23-2017

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-17 (No. 217-02521/02522)	Apr-18
Power sensor NRP-Z91	SN: 103244	04-Apr-17 (No. 217-02521)	Apr-18
Power sensor NRP-Z91	SN: 103245	04-Apr-17 (No. 217-02522)	Apr-18
Reference 20 dB Attenuator	SN: 5058 (20k)	07-Apr-17 (No. 217-02528)	Apr-18
Type-N mismatch combination	SN: 5047.2 / 06327	07-Apr-17 (No. 217-02529)	Apr-18
Reference Probe EX3DV4	SN: 7349	31-Dec-16 (No. EX3-7349_Dec16)	Dec-17
DAE4	SN: 601	28-Mar-17 (No. DAE4-601_Mar17)	Mar-18
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power meter EPM-442A	SN: GB37480704	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: US37292783	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: MY41092317	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
RF generator R&S SMT-06	SN: 100972	15-Jun-15 (in house check Oct-16)	In house check: Oct-18
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-16)	In house check: Oct-17

Calibrated by: **Claudio Leubler** **Name** **Function** **Laboratory Technician**

[Signature]

Approved by: **Katja Pokovic** **Name** **Function** **Technical Manager**

[Signature]

Issued: May 11, 2017

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- c) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- d) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- e) DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.10.0
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	2450 MHz ± 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	39.2	1.80 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	37.9 ± 6 %	1.88 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	13.2 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	51.3 W/kg ± 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	Condition	
SAR measured	250 mW input power	6.08 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	23.9 W/kg ± 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	52.7	1.95 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	52.4 ± 6 %	2.03 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	12.8 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	50.2 W/kg ± 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	Condition	
SAR measured	250 mW input power	5.98 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	23.7 W/kg ± 16.5 % (k=2)

Appendix (Additional assessments outside the scope of SCS 0108)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	$55.3 \Omega + 1.8 j\Omega$
Return Loss	- 25.4 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	$50.6 \Omega + 3.6 j\Omega$
Return Loss	- 28.8 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.157 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	March 15, 2014

DASY5 Validation Report for Head TSL

Date: 09.05.2017

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:945

Communication System: UID 0 - CW; Frequency: 2450 MHz

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.88$ S/m; $\epsilon_r = 37.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(7.72, 7.72, 7.72); Calibrated: 31.12.2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 28.03.2017
- Phantom: Flat Phantom 5.0 (front); Type: QD 000 P50 AA; Serial: 1001
- DASY52 52.10.0(1442); SEMCAD X 14.6.10(7413)

Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 114.4 V/m; Power Drift = -0.03 dB


Peak SAR (extrapolated) = 27.3 W/kg

SAR(1 g) = 13.2 W/kg; SAR(10 g) = 6.08 W/kg

Maximum value of SAR (measured) = 22.0 W/kg



Impedance Measurement Plot for Head TSL



DASY5 Validation Report for Body TSL

Date: 09.05.2017

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:945

Communication System: UID 0 - CW; Frequency: 2450 MHz

Medium parameters used: $f = 2450$ MHz; $\sigma = 2.03$ S/m; $\epsilon_r = 52.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(7.79, 7.79, 7.79); Calibrated: 31.12.2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 28.03.2017
- Phantom: Flat Phantom 5.0 (back); Type: QD 000 P50 AA; Serial: 1002
- DASY52 52.10.0(1442); SEMCAD X 14.6.10(7413)

Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 104.8 V/m; Power Drift = -0.08 dB


Peak SAR (extrapolated) = 25.3 W/kg

SAR(1 g) = 12.8 W/kg; SAR(10 g) = 5.98 W/kg

Maximum value of SAR (measured) = 19.9 W/kg



Impedance Measurement Plot for Body TSL





Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **PC Test**

Certificate No: **D2450V2-921_Sep17**

CALIBRATION CERTIFICATE

Object **D2450V2 - SN:921**

Calibration procedure(s) **QA CAL-05.v9**
 Calibration procedure for dipole validation kits above 700 MHz

*SC ✓
 10/03/2017*

Calibration date: **September 11, 2017**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-17 (No. 217-02521/02522)	Apr-18
Power sensor NRP-Z91	SN: 103244	04-Apr-17 (No. 217-02521)	Apr-18
Power sensor NRP-Z91	SN: 103245	04-Apr-17 (No. 217-02522)	Apr-18
Reference 20 dB Attenuator	SN: 5058 (20k)	07-Apr-17 (No. 217-02528)	Apr-18
Type-N mismatch combination	SN: 5047.2 / 06327	07-Apr-17 (No. 217-02529)	Apr-18
Reference Probe EX3DV4	SN: 7349	31-May-17 (No. EX3-7349_May17)	May-18
DAE4	SN: 601	28-Mar-17 (No. DAE4-601_Mar17)	Mar-18

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power meter EPM-442A	SN: GB37480704	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: US37292783	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: MY41092317	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
RF generator R&S SMT-06	SN: 100972	15-Jun-15 (in house check Oct-16)	In house check: Oct-18
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-16)	In house check: Oct-17

Calibrated by: Name **Michael Weber** Function **Laboratory Technician**

Signature

M. Weber

Approved by: Name **Katja Pokovic** Function **Technical Manager**

K. Pokovic

Issued: September 11, 2017

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Glossary:

TS	tissue simulating liquid
ConvF	sensitivity in TS / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- b) IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- c) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- d) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- e) DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TS:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TS parameters:* The measured TS parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.10.0
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	2450 MHz \pm 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	39.2	1.80 mho/m
Measured Head TSL parameters	(22.0 \pm 0.2) °C	37.8 \pm 6 %	1.86 mho/m \pm 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	13.4 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	52.3 W/kg \pm 17.0 % (k=2)

SAR averaged over 10 cm³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	6.22 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	24.5 W/kg \pm 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	52.7	1.95 mho/m
Measured Body TSL parameters	(22.0 \pm 0.2) °C	51.9 \pm 6 %	2.04 mho/m \pm 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	13.0 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	50.7 W/kg \pm 17.0 % (k=2)

SAR averaged over 10 cm³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	6.07 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	23.9 W/kg \pm 16.5 % (k=2)

Appendix (Additional assessments outside the scope of SCS 0108)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	$53.3 \Omega + 3.6 j\Omega$
Return Loss	- 26.6 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	$49.7 \Omega + 5.9 j\Omega$
Return Loss	- 24.6 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.157 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	September 26, 2013

DASY5 Validation Report for Head TSL

Date: 11.09.2017

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 921

Communication System: UID 0 - CW; Frequency: 2450 MHz

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.86$ S/m; $\epsilon_r = 37.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(8.12, 8.12, 8.12); Calibrated: 31.05.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 28.03.2017
- Phantom: Flat Phantom 5.0 (front); Type: QD 000 P50 AA; Serial: 1001
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 112.8 V/m; Power Drift = -0.08 dB


Peak SAR (extrapolated) = 26.8 W/kg

SAR(1 g) = 13.4 W/kg; SAR(10 g) = 6.22 W/kg

Maximum value of SAR (measured) = 21.4 W/kg



Impedance Measurement Plot for Head TSL



DASY5 Validation Report for Body TSL

Date: 11.09.2017

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 921

Communication System: UID 0 - CW; Frequency: 2450 MHz

Medium parameters used: $f = 2450$ MHz; $\sigma = 2.04$ S/m; $\epsilon_r = 51.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(8.1, 8.1, 8.1); Calibrated: 31.05.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 28.03.2017
- Phantom: Flat Phantom 5.0 (back); Type: QD 000 P50 AA; Serial: 1002
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 103.9 V/m; Power Drift = -0.08 dB


Peak SAR (extrapolated) = 25.4 W/kg

SAR(1 g) = 13 W/kg; SAR(10 g) = 6.07 W/kg

Maximum value of SAR (measured) = 19.8 W/kg



Impedance Measurement Plot for Body TSL





Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **PC Test**

Certificate No: **D5GHzV2-1123_Mar17**

CALIBRATION CERTIFICATE

Object **D5GHzV2 - SN:1123**

Calibration procedure(s) **QA CAL-22.v2**
 Calibration procedure for dipole validation kits between 3-6 GHz

BNV
03-27-2017

Calibration date: **March 09, 2017**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^\circ\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	06-Apr-16 (No. 217-02288/02289)	Apr-17
Power sensor NRP-Z91	SN: 103244	06-Apr-16 (No. 217-02288)	Apr-17
Power sensor NRP-Z91	SN: 103245	06-Apr-16 (No. 217-02289)	Apr-17
Reference 20 dB Attenuator	SN: 5058 (20k)	05-Apr-16 (No. 217-02292)	Apr-17
Type-N mismatch combination	SN: 5047.2 / 06327	05-Apr-16 (No. 217-02295)	Apr-17
Reference Probe EX3DV4	SN: 3503	31-Dec-16 (No. EX3-3503_Dec16)	Dec-17
DAE4	SN: 601	04-Jan-17 (No. DAE4-601_Jan17)	Jan-18
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power meter EPM-442A	SN: GB37480704	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: US37292783	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: MY41092317	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
RF generator R&S SMT-06	SN: 100972	15-Jun-15 (in house check Oct-16)	In house check: Oct-18
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-16)	In house check: Oct-17

Calibrated by: **Johannes Kurikka** Function: **Laboratory Technician**

Signature

Approved by: **Katja Pokovic** Technical Manager

Issued: March 10, 2017

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- b) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- c) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- d) DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.8
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom V5.0	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	$dx, dy = 4.0 \text{ mm}, dz = 1.4 \text{ mm}$	Graded Ratio = 1.4 (Z direction)
Frequency	5250 MHz $\pm 1 \text{ MHz}$ 5600 MHz $\pm 1 \text{ MHz}$ 5750 MHz $\pm 1 \text{ MHz}$	

Head TSL parameters at 5250 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.9	4.71 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	34.9 $\pm 6 \text{ \%}$	4.57 mho/m $\pm 6 \text{ \%}$
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL at 5250 MHz

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	7.98 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	79.3 W/kg $\pm 19.9 \text{ \% (k=2)}$

SAR averaged over 10 cm ³ (10 g) of Head TSL	Condition	
SAR measured	100 mW input power	2.29 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	22.7 W/kg $\pm 19.5 \text{ \% (k=2)}$

Head TSL parameters at 5600 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.5	5.07 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	34.4 $\pm 6 \text{ \%}$	4.92 mho/m $\pm 6 \text{ \%}$
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL at 5600 MHz

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	8.49 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	84.2 W / kg $\pm 19.9 \text{ \% (k=2)}$

SAR averaged over 10 cm ³ (10 g) of Head TSL	Condition	
SAR measured	100 mW input power	2.42 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	24.0 W/kg $\pm 19.5 \text{ \% (k=2)}$

Head TSL parameters at 5750 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.4	5.22 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	34.2 ± 6 %	5.07 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL at 5750 MHz

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	8.30 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	82.3 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	Condition	
SAR measured	100 mW input power	2.35 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	23.3 W/kg ± 19.5 % (k=2)

Body TSL parameters at 5250 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	48.9	5.36 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	48.1 ± 6 %	5.52 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL at 5250 MHz

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	100 mW input power	7.61 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	75.9 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	100 mW input power	2.14 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	21.3 W/kg ± 19.5 % (k=2)

Body TSL parameters at 5600 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	48.5	5.77 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	47.5 ± 6 %	5.99 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL at 5600 MHz

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	100 mW input power	7.91 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	78.9 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	100 mW input power	2.22 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	22.1 W/kg ± 19.5 % (k=2)

Body TSL parameters at 5750 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	48.3	5.94 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	47.2 ± 6 %	6.21 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL at 5750 MHz

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	100 mW input power	7.65 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	76.3 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	Condition	
SAR measured	100 mW input power	2.14 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	21.3 W/kg ± 19.5 % (k=2)

Appendix (Additional assessments outside the scope of SCS 0108)

Antenna Parameters with Head TSL at 5250 MHz

Impedance, transformed to feed point	$51.6 \Omega - 5.7 j\Omega$
Return Loss	- 24.7 dB

Antenna Parameters with Head TSL at 5600 MHz

Impedance, transformed to feed point	$55.9 \Omega - 0.7 j\Omega$
Return Loss	- 25.1 dB

Antenna Parameters with Head TSL at 5750 MHz

Impedance, transformed to feed point	$56.7 \Omega + 1.2 j\Omega$
Return Loss	- 23.9 dB

Antenna Parameters with Body TSL at 5250 MHz

Impedance, transformed to feed point	$51.8 \Omega - 3.8 j\Omega$
Return Loss	- 27.7 dB

Antenna Parameters with Body TSL at 5600 MHz

Impedance, transformed to feed point	$58.2 \Omega + 1.4 j\Omega$
Return Loss	- 22.3 dB

Antenna Parameters with Body TSL at 5750 MHz

Impedance, transformed to feed point	$57.3 \Omega + 3.7 j\Omega$
Return Loss	- 22.4 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.205 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	September 08, 2011

DASY5 Validation Report for Head TSL

Date: 08.03.2017

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1123

Communication System: UID 0 - CW; Frequency: 5250 MHz, Frequency: 5600 MHz, Frequency: 5750 MHz
Medium parameters used: $f = 5250$ MHz; $\sigma = 4.57$ S/m; $\epsilon_r = 34.9$; $\rho = 1000$ kg/m³, Medium parameters used: $f = 5600$ MHz; $\sigma = 4.92$ S/m; $\epsilon_r = 34.4$; $\rho = 1000$ kg/m³, Medium parameters used: $f = 5750$ MHz; $\sigma = 5.07$ S/m; $\epsilon_r = 34.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN3503; ConvF(5.58, 5.58, 5.58); Calibrated: 31.12.2016, ConvF(5.09, 5.09, 5.09); Calibrated: 31.12.2016, ConvF(5.02, 5.02, 5.02); Calibrated: 31.12.2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 04.01.2017
- Phantom: Flat Phantom 5.0 (front); Type: QD 000 P50 AA; Serial: 1001
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5250 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 71.62 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 29.9 W/kg

SAR(1 g) = 7.98 W/kg; SAR(10 g) = 2.29 W/kg

Maximum value of SAR (measured) = 18.3 W/kg

Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5600 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 71.47 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 34.1 W/kg

SAR(1 g) = 8.49 W/kg; SAR(10 g) = 2.42 W/kg

Maximum value of SAR (measured) = 19.8 W/kg


Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5750 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 70.34 V/m; Power Drift = -0.05 dB


Peak SAR (extrapolated) = 34.6 W/kg

SAR(1 g) = 8.3 W/kg; SAR(10 g) = 2.35 W/kg

Maximum value of SAR (measured) = 19.6 W/kg



Impedance Measurement Plot for Head TSL



DASY5 Validation Report for Body TSL

Date: 09.03.2017

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1123

Communication System: UID 0 - CW; Frequency: 5250 MHz, Frequency: 5600 MHz, Frequency: 5750 MHz
Medium parameters used: $f = 5250 \text{ MHz}$; $\sigma = 5.52 \text{ S/m}$; $\epsilon_r = 48.1$; $\rho = 1000 \text{ kg/m}^3$, Medium parameters used: $f = 5600 \text{ MHz}$; $\sigma = 5.99 \text{ S/m}$; $\epsilon_r = 47.5$; $\rho = 1000 \text{ kg/m}^3$, Medium parameters used: $f = 5750 \text{ MHz}$; $\sigma = 6.21 \text{ S/m}$; $\epsilon_r = 47.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN3503; ConvF(5.14, 5.14, 5.14); Calibrated: 31.12.2016, ConvF(4.57, 4.57, 4.57); Calibrated: 31.12.2016, ConvF(4.52, 4.52, 4.52); Calibrated: 31.12.2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 04.01.2017
- Phantom: Flat Phantom 5.0 (back); Type: QD 000 P50 AA; Serial: 1002
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5250MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:

Measurement grid: $dx=4 \text{ mm}$, $dy=4 \text{ mm}$, $dz=1.4 \text{ mm}$

Reference Value = 64.40 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 29.1 W/kg

SAR(1 g) = 7.61 W/kg; SAR(10 g) = 2.14 W/kg

Maximum value of SAR (measured) = 17.5 W/kg

Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5600 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:

Measurement grid: $dx=4 \text{ mm}$, $dy=4 \text{ mm}$, $dz=1.4 \text{ mm}$

Reference Value = 63.91 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 33.2 W/kg

SAR(1 g) = 7.91 W/kg; SAR(10 g) = 2.22 W/kg

Maximum value of SAR (measured) = 18.7 W/kg

Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5750 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:


Measurement grid: $dx=4 \text{ mm}$, $dy=4 \text{ mm}$, $dz=1.4 \text{ mm}$

Reference Value = 63.25 V/m; Power Drift = -0.07 dB


Peak SAR (extrapolated) = 33.4 W/kg

SAR(1 g) = 7.65 W/kg; SAR(10 g) = 2.14 W/kg

Maximum value of SAR (measured) = 18.3 W/kg



Impedance Measurement Plot for Body TSL





Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **PC Test**

Certificate No: **ES3-3333_Sep17**

CALIBRATION CERTIFICATE

Object **ES3DV3 - SN:3333**

Calibration procedure(s) **QA CAL-01.v9, QA CAL-23.v5, QA CAL-25.v6**
 Calibration procedure for dosimetric E-field probes

SLV
 10/03/2017

Calibration date: **September 18, 2017**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-17 (No. 217-02521/02522)	Apr-18
Power sensor NRP-Z91	SN: 103244	04-Apr-17 (No. 217-02521)	Apr-18
Power sensor NRP-Z91	SN: 103245	04-Apr-17 (No. 217-02525)	Apr-18
Reference 20 dB Attenuator	SN: S5277 (20x)	07-Apr-17 (No. 217-02528)	Apr-18
Reference Probe ES3DV2	SN: 3013	31-Dec-16 (No. ES3-3013_Dec16)	Dec-17
DAE4	SN: 660	7-Dec-16 (No. DAE4-660_Dec16)	Dec-17
Secondary Standards	ID	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB41293874	06-Apr-16 (in house check Jun-16)	In house check: Jun-18
Power sensor E4412A	SN: MY41498087	06-Apr-16 (in house check Jun-16)	In house check: Jun-18
Power sensor E4412A	SN: 000110210	06-Apr-16 (in house check Jun-16)	In house check: Jun-18
RF generator HP 8648C	SN: US3642U01700	04-Aug-99 (in house check Jun-16)	In house check: Jun-18
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-16)	In house check: Oct-17

Calibrated by:	Name Leif Klysner	Function Laboratory Technician	Signature
Approved by:	Name Katja Pokovic	Function Technical Manager	Signature

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Issued: September 19, 2017



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary:

TSL	tissue simulating liquid
NORM x,y,z	sensitivity in free space
ConvF	sensitivity in TSL / NORM x,y,z
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization φ	φ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, ", "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Methods Applied and Interpretation of Parameters:

- NORM x,y,z** : Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM x,y,z are only intermediate values, i.e., the uncertainties of NORM x,y,z does not affect the E²-field uncertainty inside TSL (see below **ConvF**).
- NORM(f) x,y,z = NORM x,y,z * frequency_response** (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of **ConvF**.
- DCP x,y,z** : DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A x,y,z ; B x,y,z ; C x,y,z ; D x,y,z ; VR x,y,z** : A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to $NORMx,y,z * ConvF$ whereby the uncertainty corresponds to that given for **ConvF**. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the **NORMx** (no uncertainty required).

Probe ES3DV3

SN:3333

Manufactured: January 24, 2012
Calibrated: September 18, 2017

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3333

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	1.04	0.87	0.85	$\pm 10.1 \%$
DCP (mV) ^B	106.0	106.0	106.2	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB $\sqrt{\mu\text{V}}$	C	D dB	VR mV	Unc ^E (k=2)
0	CW	X	0.0	0.0	1.0	0.00	190.2	$\pm 3.3 \%$
		Y	0.0	0.0	1.0		193.0	
		Z	0.0	0.0	1.0		202.1	

Note: For details on UID parameters see Appendix.

Sensor Model Parameters

	C1 fF	C2 fF	α V^{-1}	T1 $\text{ms} \cdot \text{V}^{-2}$	T2 $\text{ms} \cdot \text{V}^{-1}$	T3 ms	T4 V^{-2}	T5 V^{-1}	T6
X	60.55	430.6	34.96	48.60	4.480	5.100	0.000	0.804	1.011
Y	49.16	346.3	34.36	29.47	3.353	5.072	0.531	0.555	1.007
Z	42.72	307.2	35.63	7.541	1.029	4.942	0.552	0.284	1.005

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of Norm X,Y,Z do not affect the E^2 -field uncertainty inside TSL (see Pages 5 and 6).

^B Numerical linearization parameter: uncertainty not required.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3333

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unc (k=2)
750	41.9	0.89	6.54	6.54	6.54	0.76	1.20	± 12.0 %
835	41.5	0.90	6.28	6.28	6.28	0.80	1.17	± 12.0 %
1750	40.1	1.37	5.26	5.26	5.26	0.51	1.45	± 12.0 %
1900	40.0	1.40	5.06	5.06	5.06	0.53	1.48	± 12.0 %
2300	39.5	1.67	4.74	4.74	4.74	0.63	1.41	± 12.0 %
2450	39.2	1.80	4.49	4.49	4.49	0.71	1.33	± 12.0 %
2600	39.0	1.96	4.40	4.40	4.40	0.80	1.28	± 12.0 %

^C Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3333

Calibration Parameter Determined in Body Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unc (k=2)
750	55.5	0.96	6.19	6.19	6.19	0.80	1.19	± 12.0 %
835	55.2	0.97	6.14	6.14	6.14	0.80	1.16	± 12.0 %
1750	53.4	1.49	4.99	4.99	4.99	0.80	1.24	± 12.0 %
1900	53.3	1.52	4.77	4.77	4.77	0.69	1.39	± 12.0 %
2300	52.9	1.81	4.56	4.56	4.56	0.80	1.28	± 12.0 %
2450	52.7	1.95	4.35	4.35	4.35	0.80	1.25	± 12.0 %
2600	52.5	2.16	4.19	4.19	4.19	0.80	1.28	± 12.0 %


^C Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

Frequency Response of E-Field

(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ (k=2)

Receiving Pattern (ϕ), $\theta = 0^\circ$



$f=600$ MHz, TEM

$f=1800$ MHz, R22




Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ ($k=2$)

Dynamic Range f(SAR_{head}) (TEM cell, f_{eval}= 1900 MHz)




Uncertainty of Linearity Assessment: $\pm 0.6\%$ ($k=2$)

Conversion Factor Assessment



Deviation from Isotropy in Liquid Error (ϕ, θ), $f = 900 \text{ MHz}$



DASY/EASY - Parameters of Probe: ES3DV3 - SN:3333

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	-33.5
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	10 mm
Tip Diameter	4 mm
Probe Tip to Sensor X Calibration Point	2 mm
Probe Tip to Sensor Y Calibration Point	2 mm
Probe Tip to Sensor Z Calibration Point	2 mm
Recommended Measurement Distance from Surface	3 mm

Appendix: Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB/ μ V	C	D dB	VR mV	Max Unc ^E (k=2)
0	CW	X	0.00	0.00	1.00	0.00	190.2	$\pm 3.3\%$
		Y	0.00	0.00	1.00		193.0	
		Z	0.00	0.00	1.00		202.1	
10010-CAA	SAR Validation (Square, 100ms, 10ms)	X	9.66	79.30	20.13	10.00	25.0	$\pm 9.6\%$
		Y	9.16	80.51	19.97		25.0	
		Z	2.66	65.90	10.52		25.0	
10011-CAB	UMTS-FDD (WCDMA)	X	1.23	70.21	16.98	0.00	150.0	$\pm 9.6\%$
		Y	1.10	68.64	16.03		150.0	
		Z	1.15	69.47	16.54		150.0	
10012-CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps)	X	1.47	66.75	16.81	0.41	150.0	$\pm 9.6\%$
		Y	1.35	65.64	16.13		150.0	
		Z	1.19	64.13	15.44		150.0	
10013-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps)	X	5.32	67.73	17.72	1.46	150.0	$\pm 9.6\%$
		Y	5.12	67.50	17.46		150.0	
		Z	4.80	66.75	16.98		150.0	
10021-DAC	GSM-FDD (TDMA, GMSK)	X	11.96	83.86	23.32	9.39	50.0	$\pm 9.6\%$
		Y	16.36	91.67	25.56		50.0	
		Z	6.08	75.97	15.89		50.0	
10023-DAC	GPRS-FDD (TDMA, GMSK, TN 0)	X	11.74	83.38	23.19	9.57	50.0	$\pm 9.6\%$
		Y	14.91	89.88	25.00		50.0	
		Z	5.64	74.80	15.47		50.0	
10024-DAC	GPRS-FDD (TDMA, GMSK, TN 0-1)	X	15.75	89.81	23.89	6.56	60.0	$\pm 9.6\%$
		Y	63.92	113.05	29.92		60.0	
		Z	5.35	76.96	15.09		60.0	
10025-DAC	EDGE-FDD (TDMA, 8PSK, TN 0)	X	18.55	99.19	36.88	12.57	50.0	$\pm 9.6\%$
		Y	12.89	91.72	34.00		50.0	
		Z	15.31	107.42	41.47		50.0	
10026-DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1)	X	18.34	96.96	32.83	9.56	60.0	$\pm 9.6\%$
		Y	14.71	94.53	32.13		60.0	
		Z	9.08	90.99	31.70		60.0	
10027-DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2)	X	40.02	104.62	27.19	4.80	80.0	$\pm 9.6\%$
		Y	100.00	118.54	29.99		80.0	
		Z	11.10	85.74	17.06		80.0	
10028-DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2-3)	X	100.00	117.64	29.50	3.55	100.0	$\pm 9.6\%$
		Y	100.00	118.63	29.17		100.0	
		Z	100.00	107.03	21.61		100.0	
10029-DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2)	X	14.97	93.17	30.46	7.80	80.0	$\pm 9.6\%$
		Y	11.03	88.98	29.12		80.0	
		Z	5.33	79.39	26.09		80.0	
10030-CAA	IEEE 802.15.1 Bluetooth (GFSK, DH1)	X	20.88	94.46	24.59	5.30	70.0	$\pm 9.6\%$
		Y	100.00	118.13	30.14		70.0	
		Z	3.73	74.04	13.46		70.0	
10031-CAA	IEEE 802.15.1 Bluetooth (GFSK, DH3)	X	100.00	118.93	28.43	1.88	100.0	$\pm 9.6\%$
		Y	100.00	119.90	28.11		100.0	
		Z	100.00	105.96	19.97		100.0	

10032-CAA	IEEE 802.15.1 Bluetooth (GFSK, DH5)	X	100.00	123.36	29.18	1.17	100.0	± 9.6 %
		Y	100.00	125.05	29.17		100.0	
		Z	100.00	114.70	22.69		100.0	
10033-CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH1)	X	11.98	87.05	23.74	5.30	70.0	± 9.6 %
		Y	11.99	88.88	23.96		70.0	
		Z	3.77	75.14	17.41		70.0	
10034-CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH3)	X	9.37	88.28	22.64	1.88	100.0	± 9.6 %
		Y	7.64	86.38	21.51		100.0	
		Z	1.85	70.21	14.53		100.0	
10035-CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH5)	X	6.57	85.17	21.38	1.17	100.0	± 9.6 %
		Y	4.80	81.69	19.66		100.0	
		Z	1.56	69.46	14.16		100.0	
10036-CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH1)	X	12.91	88.44	24.26	5.30	70.0	± 9.6 %
		Y	13.68	91.19	24.78		70.0	
		Z	4.16	76.68	18.07		70.0	
10037-CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH3)	X	9.09	87.87	22.48	1.88	100.0	± 9.6 %
		Y	7.09	85.36	21.15		100.0	
		Z	1.76	69.67	14.28		100.0	
10038-CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH5)	X	6.88	86.06	21.75	1.17	100.0	± 9.6 %
		Y	4.96	82.42	20.01		100.0	
		Z	1.57	69.72	14.39		100.0	
10039-CAB	CDMA2000 (1xRTT, RC1)	X	2.41	75.57	18.06	0.00	150.0	± 9.6 %
		Y	2.23	75.10	17.16		150.0	
		Z	2.25	75.51	16.82		150.0	
10042-CAB	IS-54 / IS-136 FDD (TDMA/FDM, PI/4-DQPSK, Halfrate)	X	13.73	86.44	22.81	7.78	50.0	± 9.6 %
		Y	30.19	100.48	26.61		50.0	
		Z	4.14	72.78	13.66		50.0	
10044-CAA	IS-91/EIA/TIA-553 FDD (FDMA, FM)	X	0.01	123.77	11.69	0.00	150.0	± 9.6 %
		Y	0.00	96.62	0.14		150.0	
		Z	0.01	112.45	3.33		150.0	
10048-CAA	DECT (TDD, TDMA/FDM, GFSK, Full Slot, 24)	X	10.89	79.50	23.62	13.80	25.0	± 9.6 %
		Y	10.70	81.48	23.80		25.0	
		Z	5.66	70.49	15.21		25.0	
10049-CAA	DECT (TDD, TDMA/FDM, GFSK, Double Slot, 12)	X	11.27	81.87	23.07	10.79	40.0	± 9.6 %
		Y	12.12	85.48	23.87		40.0	
		Z	5.45	72.94	14.99		40.0	
10056-CAA	UMTS-TDD (TD-SCDMA, 1.28 Mcps)	X	11.54	82.58	23.29	9.03	50.0	± 9.6 %
		Y	11.21	84.01	23.38		50.0	
		Z	7.30	79.08	19.14		50.0	
10058-DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2-3)	X	12.39	90.09	28.69	6.55	100.0	± 9.6 %
		Y	8.67	84.91	26.96		100.0	
		Z	4.07	74.34	23.23		100.0	
10059-CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps)	X	1.80	69.75	18.12	0.61	110.0	± 9.6 %
		Y	1.55	67.87	17.16		110.0	
		Z	1.20	64.88	15.76		110.0	
10060-CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps)	X	100.00	128.04	32.92	1.30	110.0	± 9.6 %
		Y	100.00	130.72	33.62		110.0	
		Z	3.50	87.69	22.59		110.0	

10061-CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps)	X	14.19	97.99	27.17	2.04	110.0	± 9.6 %
		Y	8.73	92.62	25.68		110.0	
		Z	2.00	73.84	19.02		110.0	
10062-CAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps)	X	4.97	67.31	16.93	0.49	100.0	± 9.6 %
		Y	4.81	67.22	16.76		100.0	
		Z	4.63	66.87	16.56		100.0	
10063-CAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps)	X	5.03	67.52	17.09	0.72	100.0	± 9.6 %
		Y	4.86	67.39	16.89		100.0	
		Z	4.64	66.91	16.61		100.0	
10064-CAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps)	X	5.37	67.86	17.36	0.86	100.0	± 9.6 %
		Y	5.16	67.67	17.13		100.0	
		Z	4.90	67.14	16.81		100.0	
10065-CAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps)	X	5.31	68.00	17.57	1.21	100.0	± 9.6 %
		Y	5.08	67.72	17.30		100.0	
		Z	4.76	66.96	16.84		100.0	
10066-CAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps)	X	5.40	68.22	17.84	1.46	100.0	± 9.6 %
		Y	5.14	67.86	17.52		100.0	
		Z	4.76	66.93	16.95		100.0	
10067-CAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps)	X	5.75	68.44	18.33	2.04	100.0	± 9.6 %
		Y	5.48	68.11	18.00		100.0	
		Z	5.05	67.14	17.38		100.0	
10068-CAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps)	X	5.96	68.98	18.78	2.55	100.0	± 9.6 %
		Y	5.61	68.39	18.33		100.0	
		Z	5.08	67.09	17.52		100.0	
10069-CAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps)	X	6.04	68.93	18.98	2.67	100.0	± 9.6 %
		Y	5.70	68.39	18.52		100.0	
		Z	5.16	67.12	17.72		100.0	
10071-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 9 Mbps)	X	5.51	68.09	18.16	1.99	100.0	± 9.6 %
		Y	5.28	67.76	17.84		100.0	
		Z	4.89	66.79	17.22		100.0	
10072-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 12 Mbps)	X	5.65	68.82	18.56	2.30	100.0	± 9.6 %
		Y	5.35	68.32	18.16		100.0	
		Z	4.85	67.03	17.37		100.0	
10073-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 18 Mbps)	X	5.86	69.37	19.07	2.83	100.0	± 9.6 %
		Y	5.51	68.73	18.59		100.0	
		Z	4.90	67.15	17.64		100.0	
10074-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 24 Mbps)	X	5.97	69.62	19.41	3.30	100.0	± 9.6 %
		Y	5.58	68.85	18.84		100.0	
		Z	4.89	67.05	17.75		100.0	
10075-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 36 Mbps)	X	6.23	70.37	20.02	3.82	90.0	± 9.6 %
		Y	5.74	69.30	19.31		90.0	
		Z	4.92	67.13	18.01		90.0	
10076-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 48 Mbps)	X	6.28	70.27	20.19	4.15	90.0	± 9.6 %
		Y	5.80	69.19	19.47		90.0	
		Z	4.95	66.99	18.16		90.0	
10077-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 54 Mbps)	X	6.34	70.42	20.32	4.30	90.0	± 9.6 %
		Y	5.85	69.32	19.59		90.0	
		Z	4.98	67.06	18.25		90.0	

10081-CAB	CDMA2000 (1xRTT, RC3)	X	1.13	69.62	15.25	0.00	150.0	± 9.6 %
		Y	0.96	67.89	13.71		150.0	
		Z	0.95	68.21	13.42		150.0	
10082-CAB	IS-54 / IS-136 FDD (TDMA/FDM, PI/4-DQPSK, Fullrate)	X	3.50	66.82	11.38	4.77	80.0	± 9.6 %
		Y	2.44	64.79	9.69		80.0	
		Z	0.56	58.11	3.15		80.0	
10090-DAC	GPRS-FDD (TDMA, GMSK, TN 0-4)	X	15.56	89.64	23.86	6.56	60.0	± 9.6 %
		Y	60.72	112.32	29.77		60.0	
		Z	5.26	76.74	15.03		60.0	
10097-CAB	UMTS-FDD (HSDPA)	X	1.96	68.60	16.46	0.00	150.0	± 9.6 %
		Y	1.90	68.52	16.16		150.0	
		Z	1.94	69.07	16.39		150.0	
10098-CAB	UMTS-FDD (HSUPA, Subtest 2)	X	1.92	68.60	16.45	0.00	150.0	± 9.6 %
		Y	1.87	68.48	16.13		150.0	
		Z	1.91	69.05	16.38		150.0	
10099-DAC	EDGE-FDD (TDMA, 8PSK, TN 0-4)	X	18.22	96.78	32.76	9.56	60.0	± 9.6 %
		Y	14.66	94.42	32.09		60.0	
		Z	9.12	91.05	31.71		60.0	
10100-CAD	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	X	3.45	71.72	17.36	0.00	150.0	± 9.6 %
		Y	3.24	71.09	17.07		150.0	
		Z	3.21	71.07	17.23		150.0	
10101-CAD	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)	X	3.44	68.33	16.38	0.00	150.0	± 9.6 %
		Y	3.31	68.00	16.16		150.0	
		Z	3.27	67.98	16.28		150.0	
10102-CAD	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)	X	3.53	68.19	16.43	0.00	150.0	± 9.6 %
		Y	3.41	67.96	16.25		150.0	
		Z	3.37	67.93	16.35		150.0	
10103-CAD	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	X	9.29	77.51	20.85	3.98	65.0	± 9.6 %
		Y	8.45	77.58	20.94		65.0	
		Z	5.52	73.37	19.14		65.0	
10104-CAD	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)	X	9.54	77.06	21.50	3.98	65.0	± 9.6 %
		Y	8.45	76.32	21.20		65.0	
		Z	5.75	72.23	19.47		65.0	
10105-CAD	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)	X	8.74	75.31	21.00	3.98	65.0	± 9.6 %
		Y	7.42	73.76	20.35		65.0	
		Z	5.61	71.59	19.50		65.0	
10108-CAE	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	X	3.03	70.89	17.20	0.00	150.0	± 9.6 %
		Y	2.84	70.33	16.91		150.0	
		Z	2.80	70.41	17.11		150.0	
10109-CAE	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)	X	3.10	68.16	16.33	0.00	150.0	± 9.6 %
		Y	2.97	67.90	16.10		150.0	
		Z	2.92	67.94	16.21		150.0	
10110-CAE	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	X	2.50	70.03	16.94	0.00	150.0	± 9.6 %
		Y	2.31	69.47	16.56		150.0	
		Z	2.28	69.75	16.77		150.0	
10111-CAE	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)	X	2.80	68.77	16.64	0.00	150.0	± 9.6 %
		Y	2.70	68.89	16.50		150.0	
		Z	2.66	69.07	16.55		150.0	

10112-CAE	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)	X	3.22	68.04	16.34	0.00	150.0	± 9.6 %
		Y	3.09	67.88	16.15		150.0	
		Z	3.05	67.93	16.25		150.0	
10113-CAE	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)	X	2.95	68.79	16.72	0.00	150.0	± 9.6 %
		Y	2.85	69.01	16.62		150.0	
		Z	2.81	69.19	16.66		150.0	
10114-CAB	IEEE 802.11n (HT Greenfield, 13.5 Mbps, BPSK)	X	5.26	67.49	16.61	0.00	150.0	± 9.6 %
		Y	5.18	67.55	16.58		150.0	
		Z	5.15	67.58	16.71		150.0	
10115-CAB	IEEE 802.11n (HT Greenfield, 81 Mbps, 16-QAM)	X	5.64	67.81	16.77	0.00	150.0	± 9.6 %
		Y	5.48	67.70	16.66		150.0	
		Z	5.42	67.65	16.75		150.0	
10116-CAB	IEEE 802.11n (HT Greenfield, 135 Mbps, 64-QAM)	X	5.40	67.77	16.67	0.00	150.0	± 9.6 %
		Y	5.29	67.76	16.61		150.0	
		Z	5.24	67.76	16.73		150.0	
10117-CAB	IEEE 802.11n (HT Mixed, 13.5 Mbps, BPSK)	X	5.27	67.51	16.63	0.00	150.0	± 9.6 %
		Y	5.15	67.40	16.52		150.0	
		Z	5.12	67.43	16.65		150.0	
10118-CAB	IEEE 802.11n (HT Mixed, 81 Mbps, 16-QAM)	X	5.71	67.99	16.87	0.00	150.0	± 9.6 %
		Y	5.57	67.92	16.78		150.0	
		Z	5.50	67.88	16.88		150.0	
10119-CAB	IEEE 802.11n (HT Mixed, 135 Mbps, 64-QAM)	X	5.37	67.72	16.66	0.00	150.0	± 9.6 %
		Y	5.26	67.70	16.59		150.0	
		Z	5.23	67.74	16.73		150.0	
10140-CAD	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)	X	3.58	68.20	16.35	0.00	150.0	± 9.6 %
		Y	3.45	67.96	16.17		150.0	
		Z	3.40	67.94	16.27		150.0	
10141-CAD	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)	X	3.69	68.21	16.48	0.00	150.0	± 9.6 %
		Y	3.57	68.05	16.33		150.0	
		Z	3.53	68.04	16.43		150.0	
10142-CAD	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, QPSK)	X	2.28	70.10	16.80	0.00	150.0	± 9.6 %
		Y	2.10	69.63	16.33		150.0	
		Z	2.07	70.00	16.44		150.0	
10143-CAD	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)	X	2.70	69.61	16.60	0.00	150.0	± 9.6 %
		Y	2.60	69.89	16.35		150.0	
		Z	2.55	70.05	16.21		150.0	
10144-CAD	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)	X	2.51	67.70	15.24	0.00	150.0	± 9.6 %
		Y	2.33	67.34	14.62		150.0	
		Z	2.25	67.33	14.37		150.0	
10145-CAE	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)	X	1.65	68.62	14.61	0.00	150.0	± 9.6 %
		Y	1.36	66.65	12.74		150.0	
		Z	1.17	65.15	11.33		150.0	
10146-CAE	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)	X	3.63	74.04	16.68	0.00	150.0	± 9.6 %
		Y	2.36	68.47	12.91		150.0	
		Z	1.49	63.95	9.76		150.0	
10147-CAE	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)	X	4.60	77.51	18.23	0.00	150.0	± 9.6 %
		Y	2.97	71.42	14.36		150.0	
		Z	1.65	65.07	10.45		150.0	

10149-CAD	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)	X	3.11	68.21	16.38	0.00	150.0	± 9.6 %
		Y	2.97	67.97	16.15		150.0	
		Z	2.93	68.01	16.25		150.0	
10150-CAD	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM)	X	3.23	68.09	16.38	0.00	150.0	± 9.6 %
		Y	3.10	67.93	16.19		150.0	
		Z	3.05	67.99	16.29		150.0	
10151-CAD	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	X	9.70	79.29	21.64	3.98	65.0	± 9.6 %
		Y	9.00	79.89	21.91		65.0	
		Z	5.61	75.19	19.91		65.0	
10152-CAD	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)	X	9.20	77.25	21.37	3.98	65.0	± 9.6 %
		Y	8.03	76.39	20.94		65.0	
		Z	5.25	71.98	18.98		65.0	
10153-CAD	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM)	X	9.53	77.84	21.91	3.98	65.0	± 9.6 %
		Y	8.46	77.29	21.65		65.0	
		Z	5.59	72.89	19.74		65.0	
10154-CAE	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	X	2.55	70.46	17.20	0.00	150.0	± 9.6 %
		Y	2.37	69.95	16.85		150.0	
		Z	2.33	70.14	17.02		150.0	
10155-CAE	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)	X	2.80	68.78	16.65	0.00	150.0	± 9.6 %
		Y	2.70	68.90	16.51		150.0	
		Z	2.66	69.10	16.57		150.0	
10156-CAE	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, QPSK)	X	2.16	70.48	16.84	0.00	150.0	± 9.6 %
		Y	1.96	69.91	16.23		150.0	
		Z	1.92	70.20	16.21		150.0	
10157-CAE	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)	X	2.37	68.50	15.48	0.00	150.0	± 9.6 %
		Y	2.19	68.12	14.77		150.0	
		Z	2.11	68.03	14.41		150.0	
10158-CAE	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)	X	2.95	68.84	16.75	0.00	150.0	± 9.6 %
		Y	2.86	69.08	16.67		150.0	
		Z	2.82	69.26	16.71		150.0	
10159-CAE	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)	X	2.49	68.90	15.74	0.00	150.0	± 9.6 %
		Y	2.31	68.65	15.09		150.0	
		Z	2.21	68.43	14.66		150.0	
10160-CAD	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	X	2.98	69.60	16.87	0.00	150.0	± 9.6 %
		Y	2.83	69.33	16.65		150.0	
		Z	2.84	69.68	16.92		150.0	
10161-CAD	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM)	X	3.12	67.99	16.33	0.00	150.0	± 9.6 %
		Y	2.99	67.89	16.14		150.0	
		Z	2.95	67.97	16.21		150.0	
10162-CAD	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)	X	3.22	68.04	16.39	0.00	150.0	± 9.6 %
		Y	3.10	68.03	16.24		150.0	
		Z	3.06	68.14	16.33		150.0	
10166-CAE	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)	X	4.09	70.78	19.86	3.01	150.0	± 9.6 %
		Y	3.78	70.38	19.46		150.0	
		Z	3.40	69.51	19.22		150.0	
10167-CAE	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM)	X	5.25	73.87	20.38	3.01	150.0	± 9.6 %
		Y	4.80	73.59	20.01		150.0	
		Z	4.07	72.45	19.71		150.0	

10168-CAE	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM)	X	5.68	75.58	21.40	3.01	150.0	± 9.6 %
		Y	5.38	76.11	21.44		150.0	
		Z	4.53	74.81	21.10		150.0	
10169-CAD	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	X	3.79	72.05	20.39	3.01	150.0	± 9.6 %
		Y	3.30	70.41	19.46		150.0	
		Z	2.71	68.18	18.69		150.0	
10170-CAD	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	X	5.42	77.77	22.38	3.01	150.0	± 9.6 %
		Y	4.81	77.07	21.99		150.0	
		Z	3.51	73.74	21.00		150.0	
10171-AAD	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)	X	4.58	74.12	20.05	3.01	150.0	± 9.6 %
		Y	3.86	72.40	19.06		150.0	
		Z	2.94	70.04	18.35		150.0	
10172-CAD	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	X	24.36	101.92	30.98	6.02	65.0	± 9.6 %
		Y	15.93	96.81	29.42		65.0	
		Z	5.16	82.08	24.55		65.0	
10173-CAD	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	X	20.36	94.96	27.50	6.02	65.0	± 9.6 %
		Y	21.23	98.21	28.32		65.0	
		Z	6.80	84.14	23.28		65.0	
10174-CAD	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)	X	18.26	92.11	26.20	6.02	65.0	± 9.6 %
		Y	16.88	93.24	26.33		65.0	
		Z	5.80	80.75	21.54		65.0	
10175-CAE	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	X	3.75	71.74	20.16	3.01	150.0	± 9.6 %
		Y	3.25	70.06	19.20		150.0	
		Z	2.68	67.93	18.47		150.0	
10176-CAE	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)	X	5.43	77.79	22.39	3.01	150.0	± 9.6 %
		Y	4.81	77.10	22.01		150.0	
		Z	3.51	73.77	21.01		150.0	
10177-CAG	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, QPSK)	X	3.78	71.89	20.25	3.01	150.0	± 9.6 %
		Y	3.28	70.23	19.30		150.0	
		Z	2.70	68.05	18.54		150.0	
10178-CAE	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)	X	5.37	77.55	22.27	3.01	150.0	± 9.6 %
		Y	4.76	76.84	21.87		150.0	
		Z	3.49	73.60	20.92		150.0	
10179-CAE	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)	X	4.97	75.84	21.09	3.01	150.0	± 9.6 %
		Y	4.28	74.56	20.38		150.0	
		Z	3.20	71.84	19.57		150.0	
10180-CAE	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)	X	4.57	74.04	20.00	3.01	150.0	± 9.6 %
		Y	3.85	72.32	19.01		150.0	
		Z	2.94	70.00	18.31		150.0	
10181-CAD	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	X	3.77	71.88	20.24	3.01	150.0	± 9.6 %
		Y	3.27	70.21	19.29		150.0	
		Z	2.70	68.04	18.54		150.0	
10182-CAD	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)	X	5.36	77.53	22.26	3.01	150.0	± 9.6 %
		Y	4.75	76.81	21.86		150.0	
		Z	3.48	73.58	20.91		150.0	
10183-AAC	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)	X	4.56	74.02	19.99	3.01	150.0	± 9.6 %
		Y	3.84	72.29	19.00		150.0	
		Z	2.93	69.98	18.30		150.0	

10184-CAD	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, QPSK)	X	3.79	71.91	20.26	3.01	150.0	± 9.6 %
		Y	3.29	70.25	19.31		150.0	
		Z	2.71	68.07	18.56		150.0	
10185-CAD	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM)	X	5.38	77.59	22.29	3.01	150.0	± 9.6 %
		Y	4.77	76.89	21.90		150.0	
		Z	3.50	73.65	20.94		150.0	
10186-AAD	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM)	X	4.58	74.08	20.02	3.01	150.0	± 9.6 %
		Y	3.86	72.36	19.03		150.0	
		Z	2.95	70.04	18.34		150.0	
10187-CAE	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)	X	3.79	71.96	20.31	3.01	150.0	± 9.6 %
		Y	3.30	70.31	19.38		150.0	
		Z	2.72	68.13	18.63		150.0	
10188-CAE	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	X	5.54	78.19	22.62	3.01	150.0	± 9.6 %
		Y	4.95	77.65	22.31		150.0	
		Z	3.59	74.21	21.28		150.0	
10189-AAE	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)	X	4.67	74.48	20.26	3.01	150.0	± 9.6 %
		Y	3.95	72.83	19.32		150.0	
		Z	3.00	70.42	18.60		150.0	
10193-CAB	IEEE 802.11n (HT Greenfield, 6.5 Mbps, BPSK)	X	4.69	66.92	16.39	0.00	150.0	± 9.6 %
		Y	4.57	66.95	16.29		150.0	
		Z	4.53	67.02	16.38		150.0	
10194-CAB	IEEE 802.11n (HT Greenfield, 39 Mbps, 16-QAM)	X	4.89	67.29	16.51	0.00	150.0	± 9.6 %
		Y	4.75	67.27	16.41		150.0	
		Z	4.69	67.31	16.51		150.0	
10195-CAB	IEEE 802.11n (HT Greenfield, 65 Mbps, 64-QAM)	X	4.93	67.30	16.51	0.00	150.0	± 9.6 %
		Y	4.79	67.30	16.42		150.0	
		Z	4.73	67.34	16.53		150.0	
10196-CAB	IEEE 802.11n (HT Mixed, 6.5 Mbps, BPSK)	X	4.71	67.02	16.43	0.00	150.0	± 9.6 %
		Y	4.58	67.02	16.31		150.0	
		Z	4.52	67.06	16.39		150.0	
10197-CAB	IEEE 802.11n (HT Mixed, 39 Mbps, 16-QAM)	X	4.90	67.31	16.52	0.00	150.0	± 9.6 %
		Y	4.76	67.29	16.42		150.0	
		Z	4.70	67.33	16.52		150.0	
10198-CAB	IEEE 802.11n (HT Mixed, 65 Mbps, 64-QAM)	X	4.93	67.32	16.52	0.00	150.0	± 9.6 %
		Y	4.79	67.32	16.44		150.0	
		Z	4.73	67.35	16.54		150.0	
10219-CAB	IEEE 802.11n (HT Mixed, 7.2 Mbps, BPSK)	X	4.66	67.03	16.39	0.00	150.0	± 9.6 %
		Y	4.53	67.04	16.27		150.0	
		Z	4.47	67.09	16.35		150.0	
10220-CAB	IEEE 802.11n (HT Mixed, 43.3 Mbps, 16-QAM)	X	4.90	67.30	16.51	0.00	150.0	± 9.6 %
		Y	4.76	67.26	16.41		150.0	
		Z	4.69	67.29	16.51		150.0	
10221-CAB	IEEE 802.11n (HT Mixed, 72.2 Mbps, 64-QAM)	X	4.94	67.25	16.51	0.00	150.0	± 9.6 %
		Y	4.80	67.24	16.42		150.0	
		Z	4.74	67.28	16.52		150.0	
10222-CAB	IEEE 802.11n (HT Mixed, 15 Mbps, BPSK)	X	5.25	67.52	16.63	0.00	150.0	± 9.6 %
		Y	5.12	67.42	16.52		150.0	
		Z	5.09	67.42	16.64		150.0	

10223-CAB	IEEE 802.11n (HT Mixed, 90 Mbps, 16-QAM)	X	5.62	67.86	16.83	0.00	150.0	± 9.6 %
		Y	5.43	67.62	16.64		150.0	
		Z	5.39	67.68	16.79		150.0	
10224-CAB	IEEE 802.11n (HT Mixed, 150 Mbps, 64-QAM)	X	5.30	67.62	16.60	0.00	150.0	± 9.6 %
		Y	5.17	67.53	16.51		150.0	
		Z	5.13	67.53	16.62		150.0	
10225-CAB	UMTS-FDD (HSPA+)	X	2.96	66.59	15.83	0.00	150.0	± 9.6 %
		Y	2.86	66.60	15.57		150.0	
		Z	2.81	66.71	15.53		150.0	
10226-CAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	X	20.89	95.49	27.73	6.02	65.0	± 9.6 %
		Y	22.40	99.28	28.72		65.0	
		Z	7.12	85.00	23.67		65.0	
10227-CAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)	X	18.52	92.45	26.38	6.02	65.0	± 9.6 %
		Y	19.90	96.10	27.28		65.0	
		Z	6.76	83.01	22.34		65.0	
10228-CAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)	X	25.24	103.08	31.43	6.02	65.0	± 9.6 %
		Y	20.21	101.73	31.03		65.0	
		Z	5.65	83.87	25.22		65.0	
10229-CAB	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM)	X	20.37	94.95	27.51	6.02	65.0	± 9.6 %
		Y	21.30	98.26	28.34		65.0	
		Z	6.84	84.21	23.32		65.0	
10230-CAB	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM)	X	18.13	92.02	26.19	6.02	65.0	± 9.6 %
		Y	19.01	95.23	26.95		65.0	
		Z	6.46	82.25	22.00		65.0	
10231-CAB	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK)	X	24.50	102.42	31.18	6.02	65.0	± 9.6 %
		Y	19.24	100.68	30.64		65.0	
		Z	5.47	83.20	24.90		65.0	
10232-CAD	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)	X	20.36	94.95	27.50	6.02	65.0	± 9.6 %
		Y	21.28	98.25	28.34		65.0	
		Z	6.83	84.20	23.31		65.0	
10233-CAD	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)	X	18.14	92.04	26.19	6.02	65.0	± 9.6 %
		Y	18.99	95.23	26.95		65.0	
		Z	6.45	82.23	22.00		65.0	
10234-CAD	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK)	X	23.73	101.67	30.87	6.02	65.0	± 9.6 %
		Y	18.36	99.63	30.22		65.0	
		Z	5.31	82.57	24.55		65.0	
10235-CAD	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)	X	20.39	94.99	27.52	6.02	65.0	± 9.6 %
		Y	21.32	98.29	28.35		65.0	
		Z	6.83	84.23	23.32		65.0	
10236-CAD	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)	X	18.21	92.10	26.21	6.02	65.0	± 9.6 %
		Y	19.11	95.31	26.98		65.0	
		Z	6.51	82.35	22.03		65.0	
10237-CAD	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	X	24.68	102.58	31.22	6.02	65.0	± 9.6 %
		Y	19.32	100.79	30.68		65.0	
		Z	5.47	83.25	24.92		65.0	
10238-CAD	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)	X	20.36	94.96	27.51	6.02	65.0	± 9.6 %
		Y	21.27	98.25	28.34		65.0	
		Z	6.81	84.18	23.30		65.0	

10239-CAD	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)	X	18.14	92.06	26.20	6.02	65.0	± 9.6 %
		Y	18.98	95.22	26.95		65.0	
		Z	6.43	82.20	21.99		65.0	
10240-CAD	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	X	24.63	102.55	31.21	6.02	65.0	± 9.6 %
		Y	19.28	100.75	30.67		65.0	
		Z	5.46	83.21	24.90		65.0	
10241-CAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM)	X	14.28	87.35	27.51	6.98	65.0	± 9.6 %
		Y	12.14	85.97	26.76		65.0	
		Z	7.04	79.06	24.07		65.0	
10242-CAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM)	X	13.42	85.94	26.88	6.98	65.0	± 9.6 %
		Y	10.82	83.53	25.73		65.0	
		Z	6.67	78.01	23.57		65.0	
10243-CAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)	X	11.69	85.00	27.38	6.98	65.0	± 9.6 %
		Y	8.81	80.72	25.46		65.0	
		Z	5.63	75.35	23.38		65.0	
10244-CAB	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	X	10.02	79.30	20.73	3.98	65.0	± 9.6 %
		Y	8.46	77.87	19.42		65.0	
		Z	3.91	69.29	14.56		65.0	
10245-CAB	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	X	9.96	78.99	20.57	3.98	65.0	± 9.6 %
		Y	8.30	77.36	19.17		65.0	
		Z	3.87	68.92	14.34		65.0	
10246-CAB	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	X	9.41	80.77	21.17	3.98	65.0	± 9.6 %
		Y	8.30	80.48	20.60		65.0	
		Z	3.58	71.24	15.84		65.0	
10247-CAD	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)	X	8.60	77.45	20.38	3.98	65.0	± 9.6 %
		Y	7.36	76.46	19.56		65.0	
		Z	4.03	70.11	16.08		65.0	
10248-CAD	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)	X	8.64	77.16	20.27	3.98	65.0	± 9.6 %
		Y	7.30	75.94	19.34		65.0	
		Z	4.07	69.84	15.95		65.0	
10249-CAD	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK)	X	10.04	81.96	22.13	3.98	65.0	± 9.6 %
		Y	9.43	82.85	22.21		65.0	
		Z	4.61	75.07	18.53		65.0	
10250-CAD	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)	X	9.40	79.04	22.08	3.98	65.0	± 9.6 %
		Y	8.37	78.79	21.88		65.0	
		Z	5.06	73.38	19.41		65.0	
10251-CAD	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)	X	9.09	77.53	21.26	3.98	65.0	± 9.6 %
		Y	7.91	76.72	20.74		65.0	
		Z	4.94	71.87	18.41		65.0	
10252-CAD	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	X	10.11	81.50	22.50	3.98	65.0	± 9.6 %
		Y	9.55	82.58	22.88		65.0	
		Z	5.37	76.64	20.34		65.0	
10253-CAD	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM)	X	9.04	76.83	21.24	3.98	65.0	± 9.6 %
		Y	7.89	75.94	20.75		65.0	
		Z	5.17	71.58	18.75		65.0	
10254-CAD	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)	X	9.38	77.43	21.75	3.98	65.0	± 9.6 %
		Y	8.29	76.78	21.39		65.0	
		Z	5.48	72.40	19.43		65.0	

10255-CAD	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	X	9.53	79.18	21.80	3.98	65.0	± 9.6 %
		Y	8.74	79.56	21.97		65.0	
		Z	5.42	74.77	19.92		65.0	
10256-CAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)	X	9.23	77.69	19.45	3.98	65.0	± 9.6 %
		Y	7.14	74.85	17.37		65.0	
		Z	3.00	65.84	11.77		65.0	
10257-CAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)	X	9.15	77.24	19.21	3.98	65.0	± 9.6 %
		Y	6.97	74.18	17.00		65.0	
		Z	2.98	65.48	11.50		65.0	
10258-CAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)	X	8.58	78.92	19.98	3.98	65.0	± 9.6 %
		Y	6.86	76.97	18.57		65.0	
		Z	2.71	67.19	13.01		65.0	
10259-CAB	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)	X	8.93	78.02	20.98	3.98	65.0	± 9.6 %
		Y	7.75	77.30	20.38		65.0	
		Z	4.44	71.40	17.32		65.0	
10260-CAB	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)	X	8.96	77.84	20.93	3.98	65.0	± 9.6 %
		Y	7.75	77.03	20.28		65.0	
		Z	4.48	71.23	17.25		65.0	
10261-CAB	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK)	X	9.85	81.43	22.19	3.98	65.0	± 9.6 %
		Y	9.12	82.10	22.26		65.0	
		Z	4.77	75.20	19.07		65.0	
10262-CAD	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)	X	9.39	79.01	22.05	3.98	65.0	± 9.6 %
		Y	8.36	78.73	21.84		65.0	
		Z	5.05	73.33	19.36		65.0	
10263-CAD	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)	X	9.08	77.52	21.27	3.98	65.0	± 9.6 %
		Y	7.90	76.71	20.74		65.0	
		Z	4.93	71.85	18.40		65.0	
10264-CAD	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	X	10.07	81.41	22.45	3.98	65.0	± 9.6 %
		Y	9.47	82.42	22.80		65.0	
		Z	5.33	76.49	20.26		65.0	
10265-CAD	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)	X	9.20	77.26	21.38	3.98	65.0	± 9.6 %
		Y	8.03	76.40	20.95		65.0	
		Z	5.25	71.99	18.99		65.0	
10266-CAD	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)	X	9.53	77.84	21.91	3.98	65.0	± 9.6 %
		Y	8.46	77.29	21.65		65.0	
		Z	5.58	72.88	19.74		65.0	
10267-CAD	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	X	9.69	79.27	21.63	3.98	65.0	± 9.6 %
		Y	8.99	79.86	21.90		65.0	
		Z	5.60	75.16	19.90		65.0	
10268-CAD	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)	X	9.63	76.84	21.55	3.98	65.0	± 9.6 %
		Y	8.57	76.15	21.24		65.0	
		Z	5.92	72.21	19.57		65.0	
10269-CAD	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)	X	9.59	76.55	21.51	3.98	65.0	± 9.6 %
		Y	8.52	75.79	21.16		65.0	
		Z	5.93	71.91	19.49		65.0	
10270-CAD	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	X	9.45	77.41	21.05	3.98	65.0	± 9.6 %
		Y	8.64	77.50	21.13		65.0	
		Z	5.77	73.46	19.39		65.0	

10274-CAB	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.10)	X	2.71	66.93	15.74	0.00	150.0	± 9.6 %
		Y	2.64	67.00	15.51		150.0	
		Z	2.64	67.30	15.59		150.0	
10275-CAB	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.4)	X	1.82	69.60	16.64	0.00	150.0	± 9.6 %
		Y	1.69	68.87	16.10		150.0	
		Z	1.72	69.40	16.40		150.0	
10277-CAA	PHS (QPSK)	X	7.72	72.48	16.59	9.03	50.0	± 9.6 %
		Y	5.94	69.93	14.43		50.0	
		Z	2.42	61.89	7.23		50.0	
10278-CAA	PHS (QPSK, BW 884MHz, Rolloff 0.5)	X	9.86	78.48	20.87	9.03	50.0	± 9.6 %
		Y	8.14	76.65	19.32		50.0	
		Z	3.62	67.11	12.28		50.0	
10279-CAA	PHS (QPSK, BW 884MHz, Rolloff 0.38)	X	9.99	78.65	20.95	9.03	50.0	± 9.6 %
		Y	8.24	76.76	19.38		50.0	
		Z	3.70	67.32	12.43		50.0	
10290-AAB	CDMA2000, RC1, SO55, Full Rate	X	1.92	72.11	16.36	0.00	150.0	± 9.6 %
		Y	1.65	70.76	15.04		150.0	
		Z	1.57	70.54	14.47		150.0	
10291-AAB	CDMA2000, RC3, SO55, Full Rate	X	1.10	69.28	15.07	0.00	150.0	± 9.6 %
		Y	0.93	67.60	13.55		150.0	
		Z	0.93	67.89	13.25		150.0	
10292-AAB	CDMA2000, RC3, SO32, Full Rate	X	1.51	74.94	18.00	0.00	150.0	± 9.6 %
		Y	1.36	73.85	16.79		150.0	
		Z	1.57	75.91	17.13		150.0	
10293-AAB	CDMA2000, RC3, SO3, Full Rate	X	2.29	81.62	21.09	0.00	150.0	± 9.6 %
		Y	2.74	84.37	21.27		150.0	
		Z	4.49	91.07	22.86		150.0	
10295-AAB	CDMA2000, RC1, SO3, 1/8th Rate 25 fr.	X	11.44	82.37	23.79	9.03	50.0	± 9.6 %
		Y	10.54	82.29	23.20		50.0	
		Z	8.18	80.06	20.52		50.0	
10297-AAC	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	X	3.05	70.99	17.26	0.00	150.0	± 9.6 %
		Y	2.85	70.44	16.98		150.0	
		Z	2.81	70.51	17.17		150.0	
10298-AAC	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	X	1.95	70.17	16.02	0.00	150.0	± 9.6 %
		Y	1.71	69.10	14.90		150.0	
		Z	1.59	68.65	14.28		150.0	
10299-AAC	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	X	3.97	74.87	17.74	0.00	150.0	± 9.6 %
		Y	3.15	71.93	15.42		150.0	
		Z	2.19	68.02	12.96		150.0	
10300-AAC	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	X	2.94	69.51	14.70	0.00	150.0	± 9.6 %
		Y	2.21	66.40	12.15		150.0	
		Z	1.65	63.93	10.18		150.0	
10301-AAA	IEEE 802.16e WiMAX (29:18, 5ms, 10MHz, QPSK, PUSC)	X	6.58	70.59	19.94	4.17	80.0	± 9.6 %
		Y	5.77	68.64	18.75		80.0	
		Z	4.49	65.14	17.31		80.0	
10302-AAA	IEEE 802.16e WiMAX (29:18, 5ms, 10MHz, QPSK, PUSC, 3 CTRL symbols)	X	7.27	71.98	21.13	4.96	80.0	± 9.6 %
		Y	6.27	69.27	19.50		80.0	
		Z	5.07	66.21	18.27		80.0	

10303- AAA	IEEE 802.16e WiMAX (31:15, 5ms, 10MHz, 64QAM, PUSC)	X	7.31	72.63	21.44	4.96	80.0	± 9.6 %
		Y	6.13	69.36	19.53		80.0	
		Z	4.82	65.82	18.08		80.0	
10304- AAA	IEEE 802.16e WiMAX (29:18, 5ms, 10MHz, 64QAM, PUSC)	X	6.65	71.10	20.22	4.17	80.0	± 9.6 %
		Y	5.74	68.63	18.74		80.0	
		Z	4.62	65.68	17.56		80.0	
10305- AAA	IEEE 802.16e WiMAX (31:15, 10ms, 10MHz, 64QAM, PUSC, 15 symbols)	X	14.90	90.20	28.80	6.02	50.0	± 9.6 %
		Y	12.34	87.95	27.80		50.0	
		Z	4.37	68.09	19.74		50.0	
10306- AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, 64QAM, PUSC, 18 symbols)	X	9.57	79.82	25.23	6.02	50.0	± 9.6 %
		Y	8.03	77.50	24.09		50.0	
		Z	4.63	66.82	19.24		50.0	
10307- AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, QPSK, PUSC, 18 symbols)	X	10.33	81.61	25.71	6.02	50.0	± 9.6 %
		Y	8.60	79.30	24.64		50.0	
		Z	4.53	66.99	19.21		50.0	
10308- AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, 16QAM, PUSC)	X	10.79	82.74	26.15	6.02	50.0	± 9.6 %
		Y	8.96	80.42	25.12		50.0	
		Z	4.52	67.24	19.38		50.0	
10309- AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, 16QAM, AMC 2x3, 18 symbols)	X	9.79	80.28	25.45	6.02	50.0	± 9.6 %
		Y	8.15	77.83	24.26		50.0	
		Z	4.68	67.00	19.38		50.0	
10310- AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, QPSK, AMC 2x3, 18 symbols)	X	9.84	80.49	25.38	6.02	50.0	± 9.6 %
		Y	8.26	78.27	24.32		50.0	
		Z	4.59	66.91	19.24		50.0	
10311- AAC	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	X	3.41	70.19	16.84	0.00	150.0	± 9.6 %
		Y	3.22	69.69	16.60		150.0	
		Z	3.17	69.67	16.75		150.0	
10313- AAA	iDEN 1:3	X	8.33	77.15	18.64	6.99	70.0	± 9.6 %
		Y	7.40	77.84	18.73		70.0	
		Z	2.54	68.72	14.02		70.0	
10314- AAA	iDEN 1:6	X	10.17	81.42	22.36	10.00	30.0	± 9.6 %
		Y	9.33	82.96	22.94		30.0	
		Z	3.39	72.69	18.27		30.0	
10315- AAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 96pc duty cycle)	X	1.28	66.00	16.48	0.17	150.0	± 9.6 %
		Y	1.20	65.17	15.91		150.0	
		Z	1.11	64.23	15.53		150.0	
10316- AAB	IEEE 802.11g WiFi 2.4 GHz (ERP- OFDM, 6 Mbps, 96pc duty cycle)	X	4.83	67.22	16.65	0.17	150.0	± 9.6 %
		Y	4.68	67.15	16.49		150.0	
		Z	4.54	66.91	16.38		150.0	
10317- AAB	IEEE 802.11a WiFi 5 GHz (OFDM, 6 Mbps, 96pc duty cycle)	X	4.83	67.22	16.65	0.17	150.0	± 9.6 %
		Y	4.68	67.15	16.49		150.0	
		Z	4.54	66.91	16.38		150.0	
10400- AAC	IEEE 802.11ac WiFi (20MHz, 64-QAM, 99pc duty cycle)	X	4.90	67.37	16.52	0.00	150.0	± 9.6 %
		Y	4.74	67.32	16.40		150.0	
		Z	4.67	67.37	16.52		150.0	
10401- AAC	IEEE 802.11ac WiFi (40MHz, 64-QAM, 99pc duty cycle)	X	5.54	67.46	16.61	0.00	150.0	± 9.6 %
		Y	5.45	67.53	16.57		150.0	
		Z	5.45	67.70	16.77		150.0	

10402-AAC	IEEE 802.11ac WiFi (80MHz, 64-QAM, 99pc duty cycle)	X	5.83	67.94	16.68	0.00	150.0	± 9.6 %
		Y	5.69	67.80	16.56		150.0	
		Z	5.65	67.75	16.66		150.0	
10403-AAB	CDMA2000 (1xEV-DO, Rev. 0)	X	1.92	72.11	16.36	0.00	115.0	± 9.6 %
		Y	1.65	70.76	15.04		115.0	
		Z	1.57	70.54	14.47		115.0	
10404-AAB	CDMA2000 (1xEV-DO, Rev. A)	X	1.92	72.11	16.36	0.00	115.0	± 9.6 %
		Y	1.65	70.76	15.04		115.0	
		Z	1.57	70.54	14.47		115.0	
10406-AAB	CDMA2000, RC3, SO32, SCH0, Full Rate	X	21.76	102.46	27.35	0.00	100.0	± 9.6 %
		Y	100.00	122.22	30.92		100.0	
		Z	100.00	122.86	30.31		100.0	
10410-AAC	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	119.28	30.94	3.23	80.0	± 9.6 %
		Y	100.00	119.72	30.33		80.0	
		Z	4.17	79.89	18.05		80.0	
10415-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 99pc duty cycle)	X	1.05	63.76	15.33	0.00	150.0	± 9.6 %
		Y	1.04	63.55	15.02		150.0	
		Z	1.06	63.77	15.26		150.0	
10416-AAA	IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 99pc duty cycle)	X	4.69	66.96	16.44	0.00	150.0	± 9.6 %
		Y	4.58	66.99	16.35		150.0	
		Z	4.53	67.05	16.45		150.0	
10417-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 99pc duty cycle)	X	4.69	66.96	16.44	0.00	150.0	± 9.6 %
		Y	4.58	66.99	16.35		150.0	
		Z	4.53	67.05	16.45		150.0	
10418-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Long preamble)	X	4.68	67.10	16.44	0.00	150.0	± 9.6 %
		Y	4.57	67.16	16.37		150.0	
		Z	4.52	67.24	16.50		150.0	
10419-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Short preamble)	X	4.70	67.06	16.45	0.00	150.0	± 9.6 %
		Y	4.59	67.10	16.37		150.0	
		Z	4.54	67.18	16.49		150.0	
10422-AAA	IEEE 802.11n (HT Greenfield, 7.2 Mbps, BPSK)	X	4.83	67.06	16.47	0.00	150.0	± 9.6 %
		Y	4.70	67.10	16.38		150.0	
		Z	4.65	67.16	16.49		150.0	
10423-AAA	IEEE 802.11n (HT Greenfield, 43.3 Mbps, 16-QAM)	X	5.03	67.44	16.60	0.00	150.0	± 9.6 %
		Y	4.87	67.42	16.50		150.0	
		Z	4.80	67.45	16.60		150.0	
10424-AAA	IEEE 802.11n (HT Greenfield, 72.2 Mbps, 64-QAM)	X	4.94	67.38	16.57	0.00	150.0	± 9.6 %
		Y	4.79	67.37	16.47		150.0	
		Z	4.72	67.41	16.58		150.0	
10425-AAA	IEEE 802.11n (HT Greenfield, 15 Mbps, BPSK)	X	5.52	67.70	16.72	0.00	150.0	± 9.6 %
		Y	5.40	67.69	16.65		150.0	
		Z	5.35	67.68	16.77		150.0	
10426-AAA	IEEE 802.11n (HT Greenfield, 90 Mbps, 16-QAM)	X	5.53	67.74	16.73	0.00	150.0	± 9.6 %
		Y	5.41	67.72	16.66		150.0	
		Z	5.39	67.82	16.83		150.0	

10427-AAA	IEEE 802.11n (HT Greenfield, 150 Mbps, 64-QAM)	X	5.54	67.73	16.73	0.00	150.0	± 9.6 %
		Y	5.42	67.69	16.64		150.0	
		Z	5.37	67.69	16.76		150.0	
10430-AAB	LTE-FDD (OFDMA, 5 MHz, E-TM 3.1)	X	4.34	70.31	18.15	0.00	150.0	± 9.6 %
		Y	4.38	71.59	18.56		150.0	
		Z	4.27	71.64	18.42		150.0	
10431-AAB	LTE-FDD (OFDMA, 10 MHz, E-TM 3.1)	X	4.43	67.55	16.52	0.00	150.0	± 9.6 %
		Y	4.26	67.58	16.37		150.0	
		Z	4.18	67.68	16.43		150.0	
10432-AAB	LTE-FDD (OFDMA, 15 MHz, E-TM 3.1)	X	4.71	67.43	16.54	0.00	150.0	± 9.6 %
		Y	4.56	67.43	16.43		150.0	
		Z	4.49	67.49	16.52		150.0	
10433-AAB	LTE-FDD (OFDMA, 20 MHz, E-TM 3.1)	X	4.95	67.42	16.59	0.00	150.0	± 9.6 %
		Y	4.81	67.40	16.49		150.0	
		Z	4.74	67.44	16.59		150.0	
10434-AAA	W-CDMA (BS Test Model 1, 64 DPCH)	X	4.43	71.04	18.15	0.00	150.0	± 9.6 %
		Y	4.52	72.60	18.60		150.0	
		Z	4.39	72.59	18.35		150.0	
10435-AAC	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	97.54	118.79	30.79	3.23	80.0	± 9.6 %
		Y	100.00	119.55	30.25		80.0	
		Z	4.00	79.29	17.79		80.0	
10447-AAB	LTE-FDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)	X	3.75	67.66	16.06	0.00	150.0	± 9.6 %
		Y	3.56	67.67	15.74		150.0	
		Z	3.46	67.73	15.62		150.0	
10448-AAB	LTE-FDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)	X	4.25	67.32	16.38	0.00	150.0	± 9.6 %
		Y	4.10	67.36	16.24		150.0	
		Z	4.03	67.47	16.30		150.0	
10449-AAB	LTE-FDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)	X	4.50	67.25	16.44	0.00	150.0	± 9.6 %
		Y	4.37	67.26	16.33		150.0	
		Z	4.31	67.32	16.42		150.0	
10450-AAB	LTE-FDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)	X	4.68	67.18	16.45	0.00	150.0	± 9.6 %
		Y	4.57	67.17	16.35		150.0	
		Z	4.52	67.21	16.45		150.0	
10451-AAA	W-CDMA (BS Test Model 1, 64 DPCH, Clipping 44%)	X	3.68	67.97	15.83	0.00	150.0	± 9.6 %
		Y	3.46	67.88	15.38		150.0	
		Z	3.33	67.81	15.12		150.0	
10456-AAA	IEEE 802.11ac WiFi (160MHz, 64-QAM, 99pc duty cycle)	X	6.38	68.31	16.88	0.00	150.0	± 9.6 %
		Y	6.27	68.21	16.78		150.0	
		Z	6.29	68.32	16.97		150.0	
10457-AAA	UMTS-FDD (DC-HSDPA)	X	3.88	65.59	16.17	0.00	150.0	± 9.6 %
		Y	3.82	65.62	16.06		150.0	
		Z	3.82	65.71	16.16		150.0	
10458-AAA	CDMA2000 (1xEV-DO, Rev. B, 2 carriers)	X	4.05	70.23	17.64	0.00	150.0	± 9.6 %
		Y	4.14	71.77	17.94		150.0	
		Z	4.00	71.72	17.57		150.0	
10459-AAA	CDMA2000 (1xEV-DO, Rev. B, 3 carriers)	X	5.16	67.69	18.00	0.00	150.0	± 9.6 %
		Y	5.18	68.95	18.39		150.0	
		Z	5.00	68.86	18.13		150.0	

10460- AAA	UMTS-FDD (WCDMA, AMR)	X	1.07	71.26	18.01	0.00	150.0	± 9.6 %
		Y	0.97	69.65	17.02		150.0	
		Z	1.03	70.73	17.64		150.0	
10461- AAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	120.51	31.57	3.29	80.0	± 9.6 %
		Y	100.00	121.90	31.42		80.0	
		Z	2.04	72.45	16.29		80.0	
10462- AAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	100.00	110.28	26.66	3.23	80.0	± 9.6 %
		Y	35.06	96.58	22.15		80.0	
		Z	0.82	60.00	7.48		80.0	
10463- AAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	47.18	99.47	23.58	3.23	80.0	± 9.6 %
		Y	9.70	81.05	17.35		80.0	
		Z	0.84	60.00	6.95		80.0	
10464- AAA	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	119.12	30.79	3.23	80.0	± 9.6 %
		Y	100.00	120.04	30.41		80.0	
		Z	1.63	69.53	14.55		80.0	
10465- AAA	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16- QAM, UL Subframe=2,3,4,7,8,9)	X	76.64	106.75	25.76	3.23	80.0	± 9.6 %
		Y	19.06	89.58	20.25		80.0	
		Z	0.82	60.00	7.42		80.0	
10466- AAA	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64- QAM, UL Subframe=2,3,4,7,8,9)	X	32.86	94.98	22.37	3.23	80.0	± 9.6 %
		Y	7.02	77.47	16.16		80.0	
		Z	0.84	60.00	6.91		80.0	
10467- AAC	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	119.27	30.86	3.23	80.0	± 9.6 %
		Y	100.00	120.25	30.50		80.0	
		Z	1.69	70.01	14.78		80.0	
10468- AAC	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16- QAM, UL Subframe=2,3,4,7,8,9)	X	86.27	108.29	26.14	3.23	80.0	± 9.6 %
		Y	22.00	91.25	20.72		80.0	
		Z	0.82	60.00	7.44		80.0	
10469- AAC	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64- QAM, UL Subframe=2,3,4,7,8,9)	X	33.81	95.32	22.45	3.23	80.0	± 9.6 %
		Y	7.12	77.64	16.22		80.0	
		Z	0.84	60.00	6.91		80.0	
10470- AAC	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	119.29	30.86	3.23	80.0	± 9.6 %
		Y	100.00	120.26	30.50		80.0	
		Z	1.68	69.99	14.76		80.0	
10471- AAC	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16- QAM, UL Subframe=2,3,4,7,8,9)	X	87.04	108.37	26.15	3.23	80.0	± 9.6 %
		Y	21.89	91.17	20.69		80.0	
		Z	0.82	60.00	7.42		80.0	
10472- AAC	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64- QAM, UL Subframe=2,3,4,7,8,9)	X	34.06	95.39	22.46	3.23	80.0	± 9.6 %
		Y	7.10	77.59	16.19		80.0	
		Z	0.84	60.00	6.89		80.0	
10473- AAC	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	119.27	30.85	3.23	80.0	± 9.6 %
		Y	100.00	120.24	30.49		80.0	
		Z	1.68	69.97	14.75		80.0	
10474- AAC	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16- QAM, UL Subframe=2,3,4,7,8,9)	X	86.03	108.23	26.12	3.23	80.0	± 9.6 %
		Y	21.60	91.03	20.65		80.0	
		Z	0.82	60.00	7.42		80.0	
10475- AAC	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64- QAM, UL Subframe=2,3,4,7,8,9)	X	33.67	95.27	22.43	3.23	80.0	± 9.6 %
		Y	7.03	77.51	16.16		80.0	
		Z	0.83	60.00	6.90		80.0	

10477-AAC	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	79.85	107.22	25.85	3.23	80.0	± 9.6 %
		Y	19.52	89.83	20.30		80.0	
		Z	0.82	60.00	7.40		80.0	
10478-AAC	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	33.24	95.09	22.38	3.23	80.0	± 9.6 %
		Y	6.95	77.36	16.11		80.0	
		Z	0.84	60.00	6.88		80.0	
10479-AAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	16.65	93.99	25.98	3.23	80.0	± 9.6 %
		Y	17.37	95.70	25.85		80.0	
		Z	3.34	74.18	17.89		80.0	
10480-AAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	14.77	87.65	22.72	3.23	80.0	± 9.6 %
		Y	14.77	88.14	21.96		80.0	
		Z	2.56	67.69	13.42		80.0	
10481-AAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	13.23	85.45	21.74	3.23	80.0	± 9.6 %
		Y	11.67	84.24	20.41		80.0	
		Z	2.19	65.52	12.09		80.0	
10482-AAA	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	7.97	81.53	20.73	2.23	80.0	± 9.6 %
		Y	5.90	78.61	19.23		80.0	
		Z	1.80	65.32	12.97		80.0	
10483-AAA	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	10.18	82.34	21.04	2.23	80.0	± 9.6 %
		Y	7.73	79.02	18.98		80.0	
		Z	2.12	64.26	11.79		80.0	
10484-AAA	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	9.50	81.15	20.64	2.23	80.0	± 9.6 %
		Y	7.03	77.54	18.46		80.0	
		Z	2.10	63.89	11.62		80.0	
10485-AAC	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	8.15	82.17	21.58	2.23	80.0	± 9.6 %
		Y	6.22	79.78	20.52		80.0	
		Z	2.30	68.12	15.38		80.0	
10486-AAC	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	6.04	75.14	18.80	2.23	80.0	± 9.6 %
		Y	4.94	73.53	17.76		80.0	
		Z	2.39	65.54	13.62		80.0	
10487-AAC	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	5.95	74.60	18.60	2.23	80.0	± 9.6 %
		Y	4.85	72.96	17.52		80.0	
		Z	2.41	65.32	13.49		80.0	
10488-AAC	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	7.54	79.89	21.24	2.23	80.0	± 9.6 %
		Y	5.85	77.65	20.42		80.0	
		Z	2.83	69.05	16.75		80.0	
10489-AAC	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	5.93	74.06	19.26	2.23	80.0	± 9.6 %
		Y	4.95	72.63	18.56		80.0	
		Z	2.98	66.92	15.80		80.0	
10490-AAC	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	5.94	73.64	19.13	2.23	80.0	± 9.6 %
		Y	4.99	72.30	18.45		80.0	
		Z	3.08	66.89	15.80		80.0	
10491-AAC	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	6.87	76.77	20.23	2.23	80.0	± 9.6 %
		Y	5.58	75.00	19.58		80.0	
		Z	3.20	68.52	16.76		80.0	
10492-AAC	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	6.00	72.68	18.97	2.23	80.0	± 9.6 %
		Y	5.11	71.35	18.35		80.0	
		Z	3.42	66.80	16.18		80.0	

10493-AAC	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	6.03	72.42	18.89	2.23	80.0	± 9.6 %
		Y	5.15	71.14	18.28		80.0	
		Z	3.49	66.74	16.16		80.0	
10494-AAC	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	7.68	78.60	20.73	2.23	80.0	± 9.6 %
		Y	6.17	76.71	20.08		80.0	
		Z	3.36	69.48	17.04		80.0	
10495-AAC	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	6.14	73.26	19.19	2.23	80.0	± 9.6 %
		Y	5.19	71.82	18.57		80.0	
		Z	3.43	67.05	16.35		80.0	
10496-AAC	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	6.12	72.76	19.04	2.23	80.0	± 9.6 %
		Y	5.22	71.42	18.44		80.0	
		Z	3.53	66.93	16.33		80.0	
10497-AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	6.47	78.29	18.97	2.23	80.0	± 9.6 %
		Y	4.32	73.89	16.61		80.0	
		Z	1.27	61.50	9.92		80.0	
10498-AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	4.57	71.09	15.46	2.23	80.0	± 9.6 %
		Y	2.79	66.02	12.38		80.0	
		Z	1.29	60.00	8.06		80.0	
10499-AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	4.45	70.43	15.08	2.23	80.0	± 9.6 %
		Y	2.66	65.24	11.89		80.0	
		Z	1.31	60.00	7.92		80.0	
10500-AAA	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	7.59	80.61	21.25	2.23	80.0	± 9.6 %
		Y	5.88	78.41	20.32		80.0	
		Z	2.51	68.47	15.94		80.0	
10501-AAA	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	5.96	74.55	18.92	2.23	80.0	± 9.6 %
		Y	4.94	73.15	18.05		80.0	
		Z	2.66	66.29	14.55		80.0	
10502-AAA	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	5.96	74.22	18.76	2.23	80.0	± 9.6 %
		Y	4.96	72.86	17.89		80.0	
		Z	2.71	66.20	14.45		80.0	
10503-AAC	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	7.45	79.69	21.16	2.23	80.0	± 9.6 %
		Y	5.77	77.41	20.32		80.0	
		Z	2.80	68.91	16.68		80.0	
10504-AAC	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	5.90	73.98	19.22	2.23	80.0	± 9.6 %
		Y	4.92	72.53	18.50		80.0	
		Z	2.97	66.85	15.75		80.0	
10505-AAC	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	5.91	73.56	19.09	2.23	80.0	± 9.6 %
		Y	4.96	72.20	18.39		80.0	
		Z	3.07	66.82	15.75		80.0	
10506-AAC	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	7.62	78.46	20.67	2.23	80.0	± 9.6 %
		Y	6.12	76.54	20.01		80.0	
		Z	3.34	69.37	16.98		80.0	
10507-AAC	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	6.11	73.21	19.16	2.23	80.0	± 9.6 %
		Y	5.17	71.75	18.53		80.0	
		Z	3.42	67.00	16.31		80.0	

10508-AAC	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	6.10	72.70	19.00	2.23	80.0	± 9.6 %
		Y	5.20	71.34	18.40		80.0	
		Z	3.52	66.87	16.30		80.0	
10509-AAC	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	7.19	75.78	19.71	2.23	80.0	± 9.6 %
		Y	6.06	74.37	19.21		80.0	
		Z	3.79	68.85	16.82		80.0	
10510-AAC	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	6.43	72.35	18.90	2.23	80.0	± 9.6 %
		Y	5.55	71.05	18.36		80.0	
		Z	3.94	67.04	16.51		80.0	
10511-AAC	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	6.41	71.97	18.80	2.23	80.0	± 9.6 %
		Y	5.57	70.72	18.27		80.0	
		Z	4.01	66.90	16.49		80.0	
10512-AAC	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	7.93	77.92	20.34	2.23	80.0	± 9.6 %
		Y	6.55	76.25	19.78		80.0	
		Z	3.82	69.75	17.05		80.0	
10513-AAC	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	6.42	72.93	19.10	2.23	80.0	± 9.6 %
		Y	5.48	71.46	18.51		80.0	
		Z	3.81	67.15	16.55		80.0	
10514-AAC	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	6.33	72.33	18.94	2.23	80.0	± 9.6 %
		Y	5.45	70.95	18.36		80.0	
		Z	3.86	66.89	16.49		80.0	
10515-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 99pc duty cycle)	X	1.01	64.02	15.44	0.00	150.0	± 9.6 %
		Y	1.00	63.77	15.10		150.0	
		Z	1.02	64.01	15.36		150.0	
10516-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 99pc duty cycle)	X	0.91	78.00	21.21	0.00	150.0	± 9.6 %
		Y	0.69	72.78	18.73		150.0	
		Z	0.80	75.40	20.13		150.0	
10517-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 99pc duty cycle)	X	0.90	66.79	16.56	0.00	150.0	± 9.6 %
		Y	0.86	65.97	15.93		150.0	
		Z	0.89	66.45	16.34		150.0	
10518-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 99pc duty cycle)	X	4.69	67.04	16.42	0.00	150.0	± 9.6 %
		Y	4.57	67.07	16.33		150.0	
		Z	4.52	67.14	16.44		150.0	
10519-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 99pc duty cycle)	X	4.91	67.33	16.56	0.00	150.0	± 9.6 %
		Y	4.75	67.30	16.45		150.0	
		Z	4.68	67.34	16.54		150.0	
10520-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 99pc duty cycle)	X	4.75	67.31	16.49	0.00	150.0	± 9.6 %
		Y	4.61	67.27	16.37		150.0	
		Z	4.54	67.29	16.47		150.0	
10521-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 99pc duty cycle)	X	4.69	67.32	16.48	0.00	150.0	± 9.6 %
		Y	4.54	67.27	16.36		150.0	
		Z	4.47	67.28	16.45		150.0	
10522-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 99pc duty cycle)	X	4.73	67.31	16.52	0.00	150.0	± 9.6 %
		Y	4.60	67.36	16.45		150.0	
		Z	4.54	67.42	16.56		150.0	

10523-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 99pc duty cycle)	X	4.61	67.20	16.37	0.00	150.0	± 9.6 %
		Y	4.48	67.23	16.30		150.0	
		Z	4.43	67.32	16.43		150.0	
10524-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 99pc duty cycle)	X	4.69	67.26	16.50	0.00	150.0	± 9.6 %
		Y	4.54	67.27	16.41		150.0	
		Z	4.48	67.34	16.53		150.0	
10525-AAA	IEEE 802.11ac WiFi (20MHz, MCS0, 99pc duty cycle)	X	4.64	66.28	16.08	0.00	150.0	± 9.6 %
		Y	4.53	66.33	16.01		150.0	
		Z	4.49	66.40	16.12		150.0	
10526-AAA	IEEE 802.11ac WiFi (20MHz, MCS1, 99pc duty cycle)	X	4.84	66.69	16.23	0.00	150.0	± 9.6 %
		Y	4.70	66.69	16.15		150.0	
		Z	4.64	66.73	16.25		150.0	
10527-AAA	IEEE 802.11ac WiFi (20MHz, MCS2, 99pc duty cycle)	X	4.76	66.66	16.18	0.00	150.0	± 9.6 %
		Y	4.62	66.66	16.10		150.0	
		Z	4.56	66.70	16.20		150.0	
10528-AAA	IEEE 802.11ac WiFi (20MHz, MCS3, 99pc duty cycle)	X	4.78	66.68	16.22	0.00	150.0	± 9.6 %
		Y	4.64	66.67	16.13		150.0	
		Z	4.58	66.71	16.23		150.0	
10529-AAA	IEEE 802.11ac WiFi (20MHz, MCS4, 99pc duty cycle)	X	4.78	66.68	16.22	0.00	150.0	± 9.6 %
		Y	4.64	66.67	16.13		150.0	
		Z	4.58	66.71	16.23		150.0	
10531-AAA	IEEE 802.11ac WiFi (20MHz, MCS6, 99pc duty cycle)	X	4.79	66.83	16.25	0.00	150.0	± 9.6 %
		Y	4.63	66.78	16.14		150.0	
		Z	4.58	66.71	16.23		150.0	
10532-AAA	IEEE 802.11ac WiFi (20MHz, MCS7, 99pc duty cycle)	X	4.64	66.70	16.19	0.00	150.0	± 9.6 %
		Y	4.49	66.64	16.08		150.0	
		Z	4.43	66.64	16.16		150.0	
10533-AAA	IEEE 802.11ac WiFi (20MHz, MCS8, 99pc duty cycle)	X	4.79	66.71	16.20	0.00	150.0	± 9.6 %
		Y	4.65	66.72	16.12		150.0	
		Z	4.59	66.78	16.23		150.0	
10534-AAA	IEEE 802.11ac WiFi (40MHz, MCS0, 99pc duty cycle)	X	5.29	66.81	16.26	0.00	150.0	± 9.6 %
		Y	5.17	66.76	16.17		150.0	
		Z	5.13	66.75	16.28		150.0	
10535-AAA	IEEE 802.11ac WiFi (40MHz, MCS1, 99pc duty cycle)	X	5.36	66.96	16.31	0.00	150.0	± 9.6 %
		Y	5.24	66.94	16.26		150.0	
		Z	5.20	66.95	16.38		150.0	
10536-AAA	IEEE 802.11ac WiFi (40MHz, MCS2, 99pc duty cycle)	X	5.23	66.95	16.29	0.00	150.0	± 9.6 %
		Y	5.11	66.89	16.21		150.0	
		Z	5.07	66.91	16.33		150.0	
10537-AAA	IEEE 802.11ac WiFi (40MHz, MCS3, 99pc duty cycle)	X	5.30	66.92	16.28	0.00	150.0	± 9.6 %
		Y	5.17	66.86	16.20		150.0	
		Z	5.13	66.86	16.31		150.0	
10538-AAA	IEEE 802.11ac WiFi (40MHz, MCS4, 99pc duty cycle)	X	5.41	66.99	16.36	0.00	150.0	± 9.6 %
		Y	5.26	66.87	16.24		150.0	
		Z	5.20	66.86	16.35		150.0	
10540-AAA	IEEE 802.11ac WiFi (40MHz, MCS6, 99pc duty cycle)	X	5.31	66.94	16.35	0.00	150.0	± 9.6 %
		Y	5.19	66.90	16.27		150.0	
		Z	5.14	66.85	16.36		150.0	

10541-AAA	IEEE 802.11ac WiFi (40MHz, MCS7, 99pc duty cycle)	X	5.29	66.84	16.29	0.00	150.0	± 9.6 %
		Y	5.16	66.76	16.19		150.0	
		Z	5.11	66.72	16.29		150.0	
10542-AAA	IEEE 802.11ac WiFi (40MHz, MCS8, 99pc duty cycle)	X	5.44	66.88	16.33	0.00	150.0	± 9.6 %
		Y	5.32	66.83	16.24		150.0	
		Z	5.27	66.82	16.35		150.0	
10543-AAA	IEEE 802.11ac WiFi (40MHz, MCS9, 99pc duty cycle)	X	5.53	66.89	16.35	0.00	150.0	± 9.6 %
		Y	5.39	66.86	16.28		150.0	
		Z	5.33	66.84	16.38		150.0	
10544-AAA	IEEE 802.11ac WiFi (80MHz, MCS0, 99pc duty cycle)	X	5.58	66.91	16.23	0.00	150.0	± 9.6 %
		Y	5.48	66.86	16.16		150.0	
		Z	5.46	66.83	16.26		150.0	
10545-AAA	IEEE 802.11ac WiFi (80MHz, MCS1, 99pc duty cycle)	X	5.79	67.34	16.39	0.00	150.0	± 9.6 %
		Y	5.68	67.29	16.32		150.0	
		Z	5.67	67.33	16.47		150.0	
10546-AAA	IEEE 802.11ac WiFi (80MHz, MCS2, 99pc duty cycle)	X	5.67	67.20	16.34	0.00	150.0	± 9.6 %
		Y	5.55	67.07	16.23		150.0	
		Z	5.51	67.00	16.31		150.0	
10547-AAA	IEEE 802.11ac WiFi (80MHz, MCS3, 99pc duty cycle)	X	5.76	67.27	16.36	0.00	150.0	± 9.6 %
		Y	5.62	67.11	16.24		150.0	
		Z	5.59	67.08	16.35		150.0	
10548-AAA	IEEE 802.11ac WiFi (80MHz, MCS4, 99pc duty cycle)	X	6.10	68.45	16.93	0.00	150.0	± 9.6 %
		Y	5.88	68.08	16.70		150.0	
		Z	5.84	68.04	16.80		150.0	
10550-AAA	IEEE 802.11ac WiFi (80MHz, MCS6, 99pc duty cycle)	X	5.69	67.15	16.32	0.00	150.0	± 9.6 %
		Y	5.58	67.10	16.25		150.0	
		Z	5.57	67.15	16.40		150.0	
10551-AAA	IEEE 802.11ac WiFi (80MHz, MCS7, 99pc duty cycle)	X	5.71	67.24	16.32	0.00	150.0	± 9.6 %
		Y	5.58	67.14	16.23		150.0	
		Z	5.54	67.06	16.32		150.0	
10552-AAA	IEEE 802.11ac WiFi (80MHz, MCS8, 99pc duty cycle)	X	5.61	66.99	16.22	0.00	150.0	± 9.6 %
		Y	5.50	66.93	16.14		150.0	
		Z	5.47	66.90	16.24		150.0	
10553-AAA	IEEE 802.11ac WiFi (80MHz, MCS9, 99pc duty cycle)	X	5.70	67.05	16.27	0.00	150.0	± 9.6 %
		Y	5.58	66.96	16.18		150.0	
		Z	5.53	66.90	16.27		150.0	
10554-AAB	IEEE 802.11ac WiFi (160MHz, MCS0, 99pc duty cycle)	X	5.98	67.29	16.33	0.00	150.0	± 9.6 %
		Y	5.89	67.22	16.24		150.0	
		Z	5.88	67.19	16.35		150.0	
10555-AAB	IEEE 802.11ac WiFi (160MHz, MCS1, 99pc duty cycle)	X	6.13	67.63	16.47	0.00	150.0	± 9.6 %
		Y	6.02	67.53	16.37		150.0	
		Z	6.01	67.50	16.49		150.0	
10556-AAB	IEEE 802.11ac WiFi (160MHz, MCS2, 99pc duty cycle)	X	6.14	67.65	16.47	0.00	150.0	± 9.6 %
		Y	6.05	67.58	16.39		150.0	
		Z	6.03	67.56	16.51		150.0	
10557-AAB	IEEE 802.11ac WiFi (160MHz, MCS3, 99pc duty cycle)	X	6.13	67.60	16.47	0.00	150.0	± 9.6 %
		Y	6.01	67.47	16.36		150.0	
		Z	5.98	67.42	16.45		150.0	

10558-AAB	IEEE 802.11ac WiFi (160MHz, MCS4, 99pc duty cycle)	X	6.19	67.80	16.59	0.00	150.0	± 9.6 %
		Y	6.06	67.64	16.46		150.0	
		Z	6.03	67.57	16.55		150.0	
10560-AAB	IEEE 802.11ac WiFi (160MHz, MCS6, 99pc duty cycle)	X	6.18	67.62	16.53	0.00	150.0	± 9.6 %
		Y	6.05	67.48	16.42		150.0	
		Z	6.02	67.42	16.51		150.0	
10561-AAB	IEEE 802.11ac WiFi (160MHz, MCS7, 99pc duty cycle)	X	6.09	67.58	16.55	0.00	150.0	± 9.6 %
		Y	5.97	67.46	16.44		150.0	
		Z	5.96	67.43	16.55		150.0	
10562-AAB	IEEE 802.11ac WiFi (160MHz, MCS8, 99pc duty cycle)	X	6.26	68.09	16.81	0.00	150.0	± 9.6 %
		Y	6.10	67.83	16.63		150.0	
		Z	6.04	67.69	16.68		150.0	
10563-AAB	IEEE 802.11ac WiFi (160MHz, MCS9, 99pc duty cycle)	X	6.60	68.64	17.03	0.00	150.0	± 9.6 %
		Y	6.31	68.08	16.71		150.0	
		Z	6.14	67.64	16.62		150.0	
10564-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 99pc duty cycle)	X	5.04	67.20	16.62	0.46	150.0	± 9.6 %
		Y	4.90	67.16	16.49		150.0	
		Z	4.84	67.16	16.56		150.0	
10565-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 99pc duty cycle)	X	5.29	67.66	16.93	0.46	150.0	± 9.6 %
		Y	5.13	67.61	16.81		150.0	
		Z	5.05	67.57	16.86		150.0	
10566-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 99pc duty cycle)	X	5.13	67.55	16.78	0.46	150.0	± 9.6 %
		Y	4.97	67.46	16.64		150.0	
		Z	4.88	67.42	16.68		150.0	
10567-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 99pc duty cycle)	X	5.15	67.90	17.09	0.46	150.0	± 9.6 %
		Y	5.01	67.87	17.00		150.0	
		Z	4.91	67.78	17.02		150.0	
10568-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 99pc duty cycle)	X	5.05	67.34	16.57	0.46	150.0	± 9.6 %
		Y	4.89	67.24	16.40		150.0	
		Z	4.79	67.20	16.45		150.0	
10569-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 99pc duty cycle)	X	5.10	67.93	17.11	0.46	150.0	± 9.6 %
		Y	4.97	68.00	17.08		150.0	
		Z	4.87	67.91	17.10		150.0	
10570-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 99pc duty cycle)	X	5.14	67.77	17.05	0.46	150.0	± 9.6 %
		Y	4.99	67.81	16.99		150.0	
		Z	4.90	67.77	17.05		150.0	
10571-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 90pc duty cycle)	X	1.57	68.03	17.35	0.46	130.0	± 9.6 %
		Y	1.40	66.58	16.54		130.0	
		Z	1.16	64.38	15.51		130.0	
10572-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 90pc duty cycle)	X	1.61	68.80	17.76	0.46	130.0	± 9.6 %
		Y	1.43	67.29	16.94		130.0	
		Z	1.17	64.90	15.83		130.0	
10573-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 90pc duty cycle)	X	31.38	123.52	33.35	0.46	130.0	± 9.6 %
		Y	5.86	99.02	27.14		130.0	
		Z	1.62	82.45	22.34		130.0	
10574-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 90pc duty cycle)	X	2.19	77.51	21.53	0.46	130.0	± 9.6 %
		Y	1.78	74.82	20.45		130.0	
		Z	1.24	70.10	18.57		130.0	

10575-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 90pc duty cycle)	X	4.89	67.15	16.76	0.46	130.0	± 9.6 %
		Y	4.73	67.07	16.59		130.0	
		Z	4.59	66.83	16.48		130.0	
10576-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 90pc duty cycle)	X	4.91	67.30	16.82	0.46	130.0	± 9.6 %
		Y	4.76	67.24	16.66		130.0	
		Z	4.62	67.00	16.55		130.0	
10577-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 90pc duty cycle)	X	5.14	67.61	16.99	0.46	130.0	± 9.6 %
		Y	4.96	67.51	16.82		130.0	
		Z	4.80	67.26	16.71		130.0	
10578-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 90pc duty cycle)	X	5.04	67.77	17.07	0.46	130.0	± 9.6 %
		Y	4.87	67.70	16.94		130.0	
		Z	4.70	67.40	16.80		130.0	
10579-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 90pc duty cycle)	X	4.83	67.23	16.50	0.46	130.0	± 9.6 %
		Y	4.63	66.98	16.24		130.0	
		Z	4.46	66.67	16.10		130.0	
10580-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 90pc duty cycle)	X	4.87	67.21	16.51	0.46	130.0	± 9.6 %
		Y	4.68	67.00	16.26		130.0	
		Z	4.51	66.75	16.14		130.0	
10581-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 90pc duty cycle)	X	4.95	67.88	17.05	0.46	130.0	± 9.6 %
		Y	4.77	67.77	16.90		130.0	
		Z	4.60	67.44	16.75		130.0	
10582-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 90pc duty cycle)	X	4.78	67.01	16.32	0.46	130.0	± 9.6 %
		Y	4.57	66.72	16.02		130.0	
		Z	4.40	66.47	15.91		130.0	
10583-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 90pc duty cycle)	X	4.89	67.15	16.76	0.46	130.0	± 9.6 %
		Y	4.73	67.07	16.59		130.0	
		Z	4.59	66.83	16.48		130.0	
10584-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 90pc duty cycle)	X	4.91	67.30	16.82	0.46	130.0	± 9.6 %
		Y	4.76	67.24	16.66		130.0	
		Z	4.62	67.00	16.55		130.0	
10585-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 90pc duty cycle)	X	5.14	67.61	16.99	0.46	130.0	± 9.6 %
		Y	4.96	67.51	16.82		130.0	
		Z	4.80	67.26	16.71		130.0	
10586-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 90pc duty cycle)	X	5.04	67.77	17.07	0.46	130.0	± 9.6 %
		Y	4.87	67.70	16.94		130.0	
		Z	4.70	67.40	16.80		130.0	
10587-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 90pc duty cycle)	X	4.83	67.23	16.50	0.46	130.0	± 9.6 %
		Y	4.63	66.98	16.24		130.0	
		Z	4.46	66.67	16.10		130.0	
10588-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 90pc duty cycle)	X	4.87	67.21	16.51	0.46	130.0	± 9.6 %
		Y	4.68	67.00	16.26		130.0	
		Z	4.51	66.75	16.14		130.0	
10589-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 90pc duty cycle)	X	4.95	67.88	17.05	0.46	130.0	± 9.6 %
		Y	4.77	67.77	16.90		130.0	
		Z	4.60	67.44	16.75		130.0	
10590-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 90pc duty cycle)	X	4.78	67.01	16.32	0.46	130.0	± 9.6 %
		Y	4.57	66.72	16.02		130.0	
		Z	4.40	66.47	15.91		130.0	

10591- AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS0, 90pc duty cycle)	X	5.03	67.17	16.84	0.46	130.0	± 9.6 %
		Y	4.88	67.11	16.69		130.0	
		Z	4.74	66.89	16.59		130.0	
10592- AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS1, 90pc duty cycle)	X	5.20	67.51	16.96	0.46	130.0	± 9.6 %
		Y	5.03	67.45	16.82		130.0	
		Z	4.88	67.21	16.72		130.0	
10593- AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS2, 90pc duty cycle)	X	5.13	67.48	16.87	0.46	130.0	± 9.6 %
		Y	4.96	67.36	16.70		130.0	
		Z	4.80	67.10	16.59		130.0	
10594- AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS3, 90pc duty cycle)	X	5.18	67.61	17.00	0.46	130.0	± 9.6 %
		Y	5.01	67.53	16.86		130.0	
		Z	4.85	67.26	16.74		130.0	
10595- AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS4, 90pc duty cycle)	X	5.16	67.59	16.91	0.46	130.0	± 9.6 %
		Y	4.98	67.49	16.76		130.0	
		Z	4.82	67.23	16.64		130.0	
10596- AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS5, 90pc duty cycle)	X	5.10	67.62	16.93	0.46	130.0	± 9.6 %
		Y	4.92	67.49	16.76		130.0	
		Z	4.75	67.22	16.64		130.0	
10597- AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS6, 90pc duty cycle)	X	5.06	67.56	16.84	0.46	130.0	± 9.6 %
		Y	4.87	67.39	16.64		130.0	
		Z	4.70	67.09	16.50		130.0	
10598- AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS7, 90pc duty cycle)	X	5.03	67.78	17.08	0.46	130.0	± 9.6 %
		Y	4.86	67.65	16.92		130.0	
		Z	4.68	67.30	16.75		130.0	
10599- AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS0, 90pc duty cycle)	X	5.69	67.74	17.02	0.46	130.0	± 9.6 %
		Y	5.55	67.63	16.88		130.0	
		Z	5.44	67.46	16.85		130.0	
10600- AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS1, 90pc duty cycle)	X	5.89	68.35	17.30	0.46	130.0	± 9.6 %
		Y	5.68	68.04	17.06		130.0	
		Z	5.59	67.97	17.09		130.0	
10601- AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS2, 90pc duty cycle)	X	5.74	67.98	17.13	0.46	130.0	± 9.6 %
		Y	5.57	67.79	16.95		130.0	
		Z	5.46	67.64	16.94		130.0	
10602- AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS3, 90pc duty cycle)	X	5.83	67.99	17.05	0.46	130.0	± 9.6 %
		Y	5.66	67.82	16.88		130.0	
		Z	5.59	67.81	16.94		130.0	
10603- AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS4, 90pc duty cycle)	X	5.91	68.27	17.31	0.46	130.0	± 9.6 %
		Y	5.74	68.12	17.16		130.0	
		Z	5.65	68.06	17.20		130.0	
10604- AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS5, 90pc duty cycle)	X	5.69	67.70	17.02	0.46	130.0	± 9.6 %
		Y	5.55	67.60	16.89		130.0	
		Z	5.53	67.72	17.02		130.0	
10605- AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS6, 90pc duty cycle)	X	5.81	68.02	17.19	0.46	130.0	± 9.6 %
		Y	5.66	67.93	17.05		130.0	
		Z	5.58	67.86	17.08		130.0	
10606- AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS7, 90pc duty cycle)	X	5.58	67.50	16.80	0.46	130.0	± 9.6 %
		Y	5.40	67.24	16.57		130.0	
		Z	5.30	67.09	16.55		130.0	

10607- AAA	IEEE 802.11ac WiFi (20MHz, MCS0, 90pc duty cycle)	X	4.85	66.45	16.43	0.46	130.0	± 9.6 %
		Y	4.72	66.43	16.31		130.0	
		Z	4.59	66.22	16.21		130.0	
10608- AAA	IEEE 802.11ac WiFi (20MHz, MCS1, 90pc duty cycle)	X	5.07	66.88	16.60	0.46	130.0	± 9.6 %
		Y	4.90	66.83	16.48		130.0	
		Z	4.75	66.59	16.37		130.0	
10609- AAA	IEEE 802.11ac WiFi (20MHz, MCS2, 90pc duty cycle)	X	4.96	66.77	16.47	0.46	130.0	± 9.6 %
		Y	4.79	66.68	16.32		130.0	
		Z	4.64	66.43	16.20		130.0	
10610- AAA	IEEE 802.11ac WiFi (20MHz, MCS3, 90pc duty cycle)	X	5.01	66.92	16.62	0.46	130.0	± 9.6 %
		Y	4.84	66.85	16.48		130.0	
		Z	4.69	66.58	16.36		130.0	
10611- AAA	IEEE 802.11ac WiFi (20MHz, MCS4, 90pc duty cycle)	X	4.94	66.77	16.49	0.46	130.0	± 9.6 %
		Y	4.76	66.65	16.33		130.0	
		Z	4.61	66.39	16.21		130.0	
10612- AAA	IEEE 802.11ac WiFi (20MHz, MCS5, 90pc duty cycle)	X	4.96	66.93	16.54	0.46	130.0	± 9.6 %
		Y	4.77	66.81	16.37		130.0	
		Z	4.61	66.54	16.26		130.0	
10613- AAA	IEEE 802.11ac WiFi (20MHz, MCS6, 90pc duty cycle)	X	4.97	66.85	16.44	0.46	130.0	± 9.6 %
		Y	4.77	66.68	16.25		130.0	
		Z	4.61	66.39	16.12		130.0	
10614- AAA	IEEE 802.11ac WiFi (20MHz, MCS7, 90pc duty cycle)	X	4.89	67.01	16.65	0.46	130.0	± 9.6 %
		Y	4.72	66.90	16.50		130.0	
		Z	4.56	66.57	16.35		130.0	
10615- AAA	IEEE 802.11ac WiFi (20MHz, MCS8, 90pc duty cycle)	X	4.94	66.61	16.29	0.46	130.0	± 9.6 %
		Y	4.76	66.47	16.10		130.0	
		Z	4.60	66.24	15.99		130.0	
10616- AAA	IEEE 802.11ac WiFi (40MHz, MCS0, 90pc duty cycle)	X	5.50	66.96	16.61	0.46	130.0	± 9.6 %
		Y	5.36	66.86	16.48		130.0	
		Z	5.24	66.64	16.42		130.0	
10617- AAA	IEEE 802.11ac WiFi (40MHz, MCS1, 90pc duty cycle)	X	5.55	67.07	16.63	0.46	130.0	± 9.6 %
		Y	5.43	67.04	16.55		130.0	
		Z	5.32	66.88	16.52		130.0	
10618- AAA	IEEE 802.11ac WiFi (40MHz, MCS2, 90pc duty cycle)	X	5.45	67.15	16.68	0.46	130.0	± 9.6 %
		Y	5.31	67.06	16.57		130.0	
		Z	5.21	66.87	16.53		130.0	
10619- AAA	IEEE 802.11ac WiFi (40MHz, MCS3, 90pc duty cycle)	X	5.48	66.98	16.54	0.46	130.0	± 9.6 %
		Y	5.33	66.86	16.41		130.0	
		Z	5.22	66.66	16.36		130.0	
10620- AAA	IEEE 802.11ac WiFi (40MHz, MCS4, 90pc duty cycle)	X	5.59	67.08	16.64	0.46	130.0	± 9.6 %
		Y	5.42	66.89	16.47		130.0	
		Z	5.30	66.69	16.42		130.0	
10621- AAA	IEEE 802.11ac WiFi (40MHz, MCS5, 90pc duty cycle)	X	5.56	67.10	16.76	0.46	130.0	± 9.6 %
		Y	5.42	67.03	16.66		130.0	
		Z	5.31	66.81	16.60		130.0	
10622- AAA	IEEE 802.11ac WiFi (40MHz, MCS6, 90pc duty cycle)	X	5.56	67.23	16.82	0.46	130.0	± 9.6 %
		Y	5.43	67.20	16.74		130.0	
		Z	5.33	67.02	16.70		130.0	

10623- AAA	IEEE 802.11ac WiFi (40MHz, MCS7, 90pc duty cycle)	X	5.45	66.84	16.51	0.46	130.0	± 9.6 %
		Y	5.31	66.71	16.36		130.0	
		Z	5.19	66.48	16.30		130.0	
10624- AAA	IEEE 802.11ac WiFi (40MHz, MCS8, 90pc duty cycle)	X	5.64	67.01	16.65	0.46	130.0	± 9.6 %
		Y	5.49	66.90	16.52		130.0	
		Z	5.39	66.71	16.48		130.0	
10625- AAA	IEEE 802.11ac WiFi (40MHz, MCS9, 90pc duty cycle)	X	6.07	68.13	17.26	0.46	130.0	± 9.6 %
		Y	5.86	67.88	17.06		130.0	
		Z	5.63	67.34	16.85		130.0	
10626- AAA	IEEE 802.11ac WiFi (80MHz, MCS0, 90pc duty cycle)	X	5.75	66.97	16.53	0.46	130.0	± 9.6 %
		Y	5.65	66.90	16.43		130.0	
		Z	5.56	66.69	16.38		130.0	
10627- AAA	IEEE 802.11ac WiFi (80MHz, MCS1, 90pc duty cycle)	X	6.01	67.55	16.77	0.46	130.0	± 9.6 %
		Y	5.89	67.48	16.68		130.0	
		Z	5.83	67.38	16.70		130.0	
10628- AAA	IEEE 802.11ac WiFi (80MHz, MCS2, 90pc duty cycle)	X	5.82	67.17	16.53	0.46	130.0	± 9.6 %
		Y	5.68	66.99	16.37		130.0	
		Z	5.58	66.74	16.31		130.0	
10629- AAA	IEEE 802.11ac WiFi (80MHz, MCS3, 90pc duty cycle)	X	5.91	67.23	16.55	0.46	130.0	± 9.6 %
		Y	5.76	67.04	16.39		130.0	
		Z	5.67	66.86	16.37		130.0	
10630- AAA	IEEE 802.11ac WiFi (80MHz, MCS4, 90pc duty cycle)	X	6.51	69.21	17.54	0.46	130.0	± 9.6 %
		Y	6.22	68.61	17.17		130.0	
		Z	6.10	68.35	17.11		130.0	
10631- AAA	IEEE 802.11ac WiFi (80MHz, MCS5, 90pc duty cycle)	X	6.33	68.73	17.47	0.46	130.0	± 9.6 %
		Y	6.10	68.36	17.24		130.0	
		Z	5.95	67.99	17.12		130.0	
10632- AAA	IEEE 802.11ac WiFi (80MHz, MCS6, 90pc duty cycle)	X	5.98	67.57	16.90	0.46	130.0	± 9.6 %
		Y	5.86	67.54	16.85		130.0	
		Z	5.80	67.45	16.87		130.0	
10633- AAA	IEEE 802.11ac WiFi (80MHz, MCS7, 90pc duty cycle)	X	5.91	67.39	16.66	0.46	130.0	± 9.6 %
		Y	5.74	67.14	16.48		130.0	
		Z	5.64	66.92	16.43		130.0	
10634- AAA	IEEE 802.11ac WiFi (80MHz, MCS8, 90pc duty cycle)	X	5.88	67.35	16.69	0.46	130.0	± 9.6 %
		Y	5.73	67.18	16.55		130.0	
		Z	5.62	66.92	16.49		130.0	
10635- AAA	IEEE 802.11ac WiFi (80MHz, MCS9, 90pc duty cycle)	X	5.78	66.78	16.17	0.46	130.0	± 9.6 %
		Y	5.60	66.49	15.94		130.0	
		Z	5.49	66.26	15.89		130.0	
10636- AAB	IEEE 802.11ac WiFi (160MHz, MCS0, 90pc duty cycle)	X	6.16	67.35	16.62	0.46	130.0	± 9.6 %
		Y	6.06	67.25	16.51		130.0	
		Z	6.00	67.08	16.49		130.0	
10637- AAB	IEEE 802.11ac WiFi (160MHz, MCS1, 90pc duty cycle)	X	6.33	67.76	16.80	0.46	130.0	± 9.6 %
		Y	6.22	67.64	16.68		130.0	
		Z	6.16	67.49	16.68		130.0	
10638- AAB	IEEE 802.11ac WiFi (160MHz, MCS2, 90pc duty cycle)	X	6.33	67.73	16.76	0.46	130.0	± 9.6 %
		Y	6.21	67.60	16.64		130.0	
		Z	6.16	67.47	16.64		130.0	

10639-AAB	IEEE 802.11ac WiFi (160MHz, MCS3, 90pc duty cycle)	X	6.33	67.73	16.81	0.46	130.0	± 9.6 %
		Y	6.19	67.55	16.66		130.0	
		Z	6.11	67.34	16.62		130.0	
10640-AAB	IEEE 802.11ac WiFi (160MHz, MCS4, 90pc duty cycle)	X	6.36	67.84	16.82	0.46	130.0	± 9.6 %
		Y	6.19	67.56	16.61		130.0	
		Z	6.11	67.36	16.58		130.0	
10641-AAB	IEEE 802.11ac WiFi (160MHz, MCS5, 90pc duty cycle)	X	6.35	67.56	16.69	0.46	130.0	± 9.6 %
		Y	6.24	67.46	16.58		130.0	
		Z	6.19	67.38	16.61		130.0	
10642-AAB	IEEE 802.11ac WiFi (160MHz, MCS6, 90pc duty cycle)	X	6.41	67.85	16.99	0.46	130.0	± 9.6 %
		Y	6.28	67.72	16.87		130.0	
		Z	6.20	67.52	16.84		130.0	
10643-AAB	IEEE 802.11ac WiFi (160MHz, MCS7, 90pc duty cycle)	X	6.25	67.58	16.77	0.46	130.0	± 9.6 %
		Y	6.12	67.40	16.61		130.0	
		Z	6.06	67.28	16.62		130.0	
10644-AAB	IEEE 802.11ac WiFi (160MHz, MCS8, 90pc duty cycle)	X	6.49	68.30	17.16	0.46	130.0	± 9.6 %
		Y	6.28	67.90	16.88		130.0	
		Z	6.15	67.57	16.78		130.0	
10645-AAB	IEEE 802.11ac WiFi (160MHz, MCS9, 90pc duty cycle)	X	6.86	68.94	17.42	0.46	130.0	± 9.6 %
		Y	6.60	68.46	17.12		130.0	
		Z	6.33	67.74	16.84		130.0	
10646-AAD	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,7)	X	26.02	104.79	34.37	9.30	60.0	± 9.6 %
		Y	23.52	105.75	34.71		60.0	
		Z	12.48	99.37	32.99		60.0	
10647-AAC	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,7)	X	28.31	107.43	35.30	9.30	60.0	± 9.6 %
		Y	24.05	107.03	35.23		60.0	
		Z	11.06	97.45	32.51		60.0	
10648-AAA	CDMA2000 (1x Advanced)	X	0.88	66.20	13.03	0.00	150.0	± 9.6 %
		Y	0.74	64.70	11.52		150.0	
		Z	0.71	64.50	10.98		150.0	
10652-AAB	LTE-TDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)	X	5.14	70.23	18.05	2.23	80.0	± 9.6 %
		Y	4.53	69.27	17.47		80.0	
		Z	3.37	66.06	15.81		80.0	
10653-AAB	LTE-TDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)	X	5.53	69.25	18.02	2.23	80.0	± 9.6 %
		Y	4.96	68.29	17.48		80.0	
		Z	3.95	65.73	16.22		80.0	
10654-AAB	LTE-TDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)	X	5.44	68.93	18.01	2.23	80.0	± 9.6 %
		Y	4.91	67.93	17.49		80.0	
		Z	3.96	65.42	16.27		80.0	
10655-AAB	LTE-TDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)	X	5.50	68.95	18.05	2.23	80.0	± 9.6 %
		Y	4.96	67.90	17.51		80.0	
		Z	4.03	65.40	16.33		80.0	

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client PC Test

Certificate No: EX3-7416_Jul17

CALIBRATION CERTIFICATE

Object	EX3DV4 - SN:7416
Calibration procedure(s)	QA CAL-01.v9, QA CAL-14.v4, QA CAL-23.v5, QA CAL-25.v6 Calibration procedure for dosimetric E-field probes
Calibration date:	July 18, 2017
This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.	
All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^\circ\text{C}$ and humidity < 70%.	
Calibration Equipment used (M&TE critical for calibration)	

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-17 (No. 217-02521/02522)	Apr-18
Power sensor NRP-Z91	SN: 103244	04-Apr-17 (No. 217-02521)	Apr-18
Power sensor NRP-Z91	SN: 103245	04-Apr-17 (No. 217-02525)	Apr-18
Reference 20 dB Attenuator	SN: S5277 (20x)	07-Apr-17 (No. 217-02528)	Apr-18
Reference Probe ES3DV2	SN: 3013	31-Dec-16 (No. ES3-3013_Dec16)	Dec-17
DAE4	SN: 660	7-Dec-16 (No. DAE4-660_Dec16)	Dec-17
Secondary Standards	ID	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB41293874	06-Apr-16 (in house check Jun-16)	In house check: Jun-18
Power sensor E4412A	SN: MY41498087	06-Apr-16 (in house check Jun-16)	In house check: Jun-18
Power sensor E4412A	SN: 000110210	06-Apr-16 (in house check Jun-16)	In house check: Jun-18
RF generator HP 8648C	SN: US3642U01700	04-Aug-99 (in house check Jun-16)	In house check: Jun-18
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-16)	In house check: Oct-17

Calibrated by:	Name: Michael Weber	Function: Laboratory Technician	Signature:
Approved by:	Name: Katja Pokovic	Function: Technical Manager	Signature:
Issued: July 18, 2017			
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.			



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 0108**

The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
NORM x,y,z	sensitivity in free space
ConvF	sensitivity in TSL / NORM x,y,z
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization φ	φ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, ", "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Methods Applied and Interpretation of Parameters:

- $NORMx,y,z$: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). $NORMx,y,z$ are only intermediate values, i.e., the uncertainties of $NORMx,y,z$ does not affect the E^2 -field uncertainty inside TSL (see below ConvF).
- $NORM(f)x,y,z = NORMx,y,z * frequency_response$ (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- $DCPx,y,z$: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR : PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- $Ax,y,z; Bx,y,z; Cx,y,z; Dx,y,z; VRx,y,z; A, B, C, D$ are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters*: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to $NORMx,y,z * ConvF$ whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)*: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset*: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle*: The angle is assessed using the information gained by determining the $NORMx$ (no uncertainty required).

Probe EX3DV4

SN:7416

Manufactured: March 10, 2016
Calibrated: July 18, 2017

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

DASY/EASY - Parameters of Probe: EX3DV4 - SN:7416

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	0.59	0.51	0.53	$\pm 10.1\%$
DCP (mV) ^B	93.7	95.9	97.0	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB $\sqrt{\mu\text{V}}$	C	D dB	VR mV	Unc ^E (k=2)
0	CW	X	0.0	0.0	1.0	0.00	161.7	$\pm 2.7\%$
		Y	0.0	0.0	1.0		173.6	
		Z	0.0	0.0	1.0		160.8	

Note: For details on UID parameters see Appendix.

Sensor Model Parameters

	C1 fF	C2 fF	α V^{-1}	T1 ms.V^{-2}	T2 ms.V^{-1}	T3 ms	T4 V^{-2}	T5 V^{-1}	T6
X	27.45	212.0	37.95	9.816	0.000	5.070	0	0.131	1.013
Y	39.23	298.8	36.81	10.36	0.064	5.082	0	0.481	1.004
Z	40.32	304.8	36.41	12.81	0.000	5.060	0	0.454	1.005

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of Norm X,Y,Z do not affect the E^2 -field uncertainty inside TSL (see Pages 5 and 6).

^B Numerical linearization parameter: uncertainty not required.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: EX3DV4 - SN:7416

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unc (k=2)
750	41.9	0.89	9.97	9.97	9.97	0.56	0.80	± 12.0 %
835	41.5	0.90	9.54	9.54	9.54	0.52	0.80	± 12.0 %
1750	40.1	1.37	8.39	8.39	8.39	0.33	0.80	± 12.0 %
1900	40.0	1.40	8.02	8.02	8.02	0.38	0.80	± 12.0 %
2300	39.5	1.67	7.65	7.65	7.65	0.34	0.81	± 12.0 %
2450	39.2	1.80	7.24	7.24	7.24	0.29	0.80	± 12.0 %
2600	39.0	1.96	7.15	7.15	7.15	0.35	0.87	± 12.0 %
5250	35.9	4.71	5.53	5.53	5.53	0.30	1.80	± 13.1 %
5600	35.5	5.07	4.87	4.87	4.87	0.35	1.80	± 13.1 %
5750	35.4	5.22	5.09	5.09	5.09	0.40	1.80	± 13.1 %

^C Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

DASY/EASY - Parameters of Probe: EX3DV4 - SN:7416

Calibration Parameter Determined in Body Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unc (k=2)
750	55.5	0.96	9.71	9.71	9.71	0.53	0.80	± 12.0 %
835	55.2	0.97	9.52	9.52	9.52	0.55	0.80	± 12.0 %
1750	53.4	1.49	7.98	7.98	7.98	0.42	0.80	± 12.0 %
1900	53.3	1.52	7.73	7.73	7.73	0.39	0.80	± 12.0 %
2300	52.9	1.81	7.57	7.57	7.57	0.37	0.88	± 12.0 %
2450	52.7	1.95	7.45	7.45	7.45	0.33	0.86	± 12.0 %
2600	52.5	2.16	7.18	7.18	7.18	0.28	0.99	± 12.0 %
5250	48.9	5.36	4.88	4.88	4.88	0.40	1.90	± 13.1 %
5600	48.5	5.77	4.15	4.15	4.15	0.45	1.90	± 13.1 %
5750	48.3	5.94	4.35	4.35	4.35	0.50	1.90	± 13.1 %


^C Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

Frequency Response of E-Field


(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\% (k=2)$

Receiving Pattern (ϕ), $\theta = 0^\circ$



f=600 MHz, TEM



f=1800 MHz, R22


Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ (k=2)

Dynamic Range $f(\text{SAR}_{\text{head}})$ (TEM cell , $f_{\text{eval}} = 1900 \text{ MHz}$)




Uncertainty of Linearity Assessment: $\pm 0.6\%$ ($k=2$)

Conversion Factor Assessment



Deviation from Isotropy in Liquid

Error (ϕ, θ), $f = 900$ MHz



DASY/EASY - Parameters of Probe: EX3DV4 - SN:7416

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	-23.3
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	9 mm
Tip Diameter	2.5 mm
Probe Tip to Sensor X Calibration Point	1 mm
Probe Tip to Sensor Y Calibration Point	1 mm
Probe Tip to Sensor Z Calibration Point	1 mm
Recommended Measurement Distance from Surface	1.4 mm

Appendix: Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB/ μ V	C	D dB	VR mV	Max Unc ^E (k=2)
0	CW	X	0.00	0.00	1.00	0.00	161.7	$\pm 2.7\%$
		Y	0.00	0.00	1.00		173.6	
		Z	0.00	0.00	1.00		160.8	
10010-CAA	SAR Validation (Square, 100ms, 10ms)	X	23.89	91.63	18.92	10.00	20.0	$\pm 9.6\%$
		Y	3.21	70.92	12.33		20.0	
		Z	1.97	66.02	9.84		20.0	
10011-CAB	UMTS-FDD (WCDMA)	X	1.29	72.25	17.98	0.00	150.0	$\pm 9.6\%$
		Y	0.94	65.61	14.15		150.0	
		Z	1.04	67.46	15.36		150.0	
10012-CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps)	X	1.24	65.05	16.38	0.41	150.0	$\pm 9.6\%$
		Y	1.15	63.13	14.74		150.0	
		Z	1.18	63.82	15.30		150.0	
10013-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps)	X	4.67	67.32	17.55	1.46	150.0	$\pm 9.6\%$
		Y	4.78	66.64	17.08		150.0	
		Z	4.80	66.73	17.15		150.0	
10021-DAC	GSM-FDD (TDMA, GMSK)	X	100.00	121.08	29.80	9.39	50.0	$\pm 9.6\%$
		Y	100.00	117.45	28.32		50.0	
		Z	100.00	112.60	25.91		50.0	
10023-DAC	GPRS-FDD (TDMA, GMSK, TN 0)	X	100.00	119.16	28.98	9.57	50.0	$\pm 9.6\%$
		Y	100.00	116.36	27.87		50.0	
		Z	100.00	111.82	25.60		50.0	
10024-DAC	GPRS-FDD (TDMA, GMSK, TN 0-1)	X	100.00	129.15	32.27	6.56	60.0	$\pm 9.6\%$
		Y	100.00	121.34	28.99		60.0	
		Z	100.00	114.29	25.81		60.0	
10025-DAC	EDGE-FDD (TDMA, 8PSK, TN 0)	X	7.14	94.38	40.96	12.57	50.0	$\pm 9.6\%$
		Y	3.65	67.84	25.70		50.0	
		Z	7.30	93.60	39.53		50.0	
10026-DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1)	X	5.96	86.71	33.00	9.56	60.0	$\pm 9.6\%$
		Y	6.15	84.89	31.00		60.0	
		Z	8.69	94.93	35.17		60.0	
10027-DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2)	X	100.00	141.25	36.61	4.80	80.0	$\pm 9.6\%$
		Y	100.00	126.64	30.48		80.0	
		Z	100.00	117.76	26.67		80.0	
10028-DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2-3)	X	100.00	157.13	42.40	3.55	100.0	$\pm 9.6\%$
		Y	100.00	132.97	32.40		100.0	
		Z	100.00	122.84	28.19		100.0	
10029-DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2)	X	4.16	76.98	27.21	7.80	80.0	$\pm 9.6\%$
		Y	4.32	76.34	25.99		80.0	
		Z	5.18	81.20	28.20		80.0	
10030-CAA	IEEE 802.15.1 Bluetooth (GFSK, DH1)	X	100.00	128.75	31.54	5.30	70.0	$\pm 9.6\%$
		Y	100.00	120.24	28.03		70.0	
		Z	100.00	113.11	24.91		70.0	
10031-CAA	IEEE 802.15.1 Bluetooth (GFSK, DH3)	X	100.00	172.41	46.56	1.88	100.0	$\pm 9.6\%$
		Y	100.00	131.84	30.37		100.0	
		Z	100.00	124.48	27.51		100.0	

10032-CAA	IEEE 802.15.1 Bluetooth (GFSK, DH5)	X	100.00	207.39	58.89	1.17	100.0	± 9.6 %
		Y	100.00	140.75	32.87		100.0	
		Z	100.00	138.59	32.13		100.0	
10033-CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH1)	X	100.00	128.20	33.38	5.30	70.0	± 9.6 %
		Y	38.88	117.25	32.17		70.0	
		Z	63.07	123.01	33.06		70.0	
10034-CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH3)	X	100.00	118.95	27.68	1.88	100.0	± 9.6 %
		Y	3.21	79.06	18.68		100.0	
		Z	4.26	82.58	19.85		100.0	
10035-CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH5)	X	16.97	97.60	22.11	1.17	100.0	± 9.6 %
		Y	1.86	72.46	15.74		100.0	
		Z	2.39	75.63	17.06		100.0	
10036-CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH1)	X	100.00	128.99	33.72	5.30	70.0	± 9.6 %
		Y	100.00	132.98	36.00		70.0	
		Z	100.00	130.72	34.94		70.0	
10037-CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH3)	X	55.26	112.08	26.19	1.88	100.0	± 9.6 %
		Y	2.82	77.46	18.09		100.0	
		Z	3.71	80.85	19.25		100.0	
10038-CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH5)	X	18.15	99.12	22.73	1.17	100.0	± 9.6 %
		Y	1.86	72.71	15.97		100.0	
		Z	2.40	75.99	17.33		100.0	
10039-CAB	CDMA2000 (1xRTT, RC1)	X	1.45	70.75	12.91	0.00	150.0	± 9.6 %
		Y	1.31	67.99	13.09		150.0	
		Z	1.65	71.12	14.76		150.0	
10042-CAB	IS-54 / IS-136 FDD (TDMA/FDM, PI/4-DQPSK, Halfrate)	X	100.00	119.04	28.16	7.78	50.0	± 9.6 %
		Y	100.00	114.37	26.20		50.0	
		Z	100.00	109.42	23.89		50.0	
10044-CAA	IS-91/EIA/TIA-553 FDD (FDMA, FM)	X	0.03	119.57	11.19	0.00	150.0	± 9.6 %
		Y	0.00	91.40	2.55		150.0	
		Z	0.01	93.63	0.92		150.0	
10048-CAA	DECT (TDD, TDMA/FDM, GFSK, Full Slot, 24)	X	100.00	112.01	27.13	13.80	25.0	± 9.6 %
		Y	100.00	111.42	27.08		25.0	
		Z	100.00	108.24	25.19		25.0	
10049-CAA	DECT (TDD, TDMA/FDM, GFSK, Double Slot, 12)	X	100.00	114.24	27.07	10.79	40.0	± 9.6 %
		Y	100.00	112.97	26.66		40.0	
		Z	100.00	109.35	24.74		40.0	
10056-CAA	UMTS-TDD (TD-SCDMA, 1.28 Mcps)	X	100.00	125.71	33.42	9.03	50.0	± 9.6 %
		Y	100.00	127.14	34.51		50.0	
		Z	100.00	125.52	33.62		50.0	
10058-DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2-3)	X	3.49	73.09	24.43	6.55	100.0	± 9.6 %
		Y	3.59	72.62	23.41		100.0	
		Z	4.06	75.73	24.87		100.0	
10059-CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps)	X	1.26	66.19	17.08	0.61	110.0	± 9.6 %
		Y	1.16	63.99	15.30		110.0	
		Z	1.20	64.85	15.92		110.0	
10060-CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps)	X	100.00	153.74	42.52	1.30	110.0	± 9.6 %
		Y	4.11	92.97	25.47		110.0	
		Z	30.77	124.38	33.70		110.0	

10061-CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps)	X	2.96	84.69	25.39	2.04	110.0	± 9.6 %
		Y	2.11	76.57	21.38		110.0	
		Z	2.73	81.09	23.06		110.0	
10062-CAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps)	X	4.45	67.22	16.90	0.49	100.0	± 9.6 %
		Y	4.58	66.57	16.45		100.0	
		Z	4.60	66.71	16.56		100.0	
10063-CAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps)	X	4.47	67.35	17.03	0.72	100.0	± 9.6 %
		Y	4.59	66.67	16.55		100.0	
		Z	4.61	66.80	16.66		100.0	
10064-CAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps)	X	4.68	67.51	17.20	0.86	100.0	± 9.6 %
		Y	4.85	66.91	16.78		100.0	
		Z	4.87	67.03	16.88		100.0	
10065-CAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps)	X	4.56	67.33	17.30	1.21	100.0	± 9.6 %
		Y	4.72	66.78	16.88		100.0	
		Z	4.74	66.90	16.97		100.0	
10066-CAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps)	X	4.56	67.30	17.44	1.46	100.0	± 9.6 %
		Y	4.74	66.80	17.06		100.0	
		Z	4.75	66.91	17.14		100.0	
10067-CAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps)	X	4.83	67.56	17.92	2.04	100.0	± 9.6 %
		Y	5.03	67.06	17.56		100.0	
		Z	5.04	67.15	17.62		100.0	
10068-CAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps)	X	4.88	67.58	18.17	2.55	100.0	± 9.6 %
		Y	5.05	67.00	17.75		100.0	
		Z	5.07	67.09	17.80		100.0	
10069-CAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps)	X	4.92	67.54	18.32	2.67	100.0	± 9.6 %
		Y	5.13	67.03	17.94		100.0	
		Z	5.15	67.13	18.01		100.0	
10071-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 9 Mbps)	X	4.76	67.40	17.88	1.99	100.0	± 9.6 %
		Y	4.87	66.71	17.40		100.0	
		Z	4.88	66.80	17.46		100.0	
10072-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 12 Mbps)	X	4.70	67.59	18.08	2.30	100.0	± 9.6 %
		Y	4.83	66.97	17.61		100.0	
		Z	4.84	67.07	17.67		100.0	
10073-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 18 Mbps)	X	4.77	67.85	18.48	2.83	100.0	± 9.6 %
		Y	4.88	67.13	17.95		100.0	
		Z	4.89	67.22	18.00		100.0	
10074-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 24 Mbps)	X	4.80	67.88	18.70	3.30	100.0	± 9.6 %
		Y	4.87	67.03	18.11		100.0	
		Z	4.88	67.12	18.15		100.0	
10075-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 36 Mbps)	X	4.82	67.88	18.96	3.82	90.0	± 9.6 %
		Y	4.89	67.05	18.39		90.0	
		Z	4.89	67.15	18.43		90.0	
10076-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 48 Mbps)	X	4.86	67.72	19.13	4.15	90.0	± 9.6 %
		Y	4.91	66.87	18.53		90.0	
		Z	4.91	66.97	18.58		90.0	
10077-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 54 Mbps)	X	4.89	67.84	19.27	4.30	90.0	± 9.6 %
		Y	4.94	66.95	18.64		90.0	
		Z	4.94	67.04	18.68		90.0	

10081-CAB	CDMA2000 (1xRTT, RC3)	X	0.74	66.37	10.74	0.00	150.0	± 9.6 %
		Y	0.69	63.78	10.63		150.0	
		Z	0.78	65.50	11.82		150.0	
10082-CAB	IS-54 / IS-136 FDD (TDMA/FDM, PI/4-DQPSK, Fullrate)	X	0.37	57.25	2.41	4.77	80.0	± 9.6 %
		Y	0.43	58.49	3.51		80.0	
		Z	0.42	57.19	2.26		80.0	
10090-DAC	GPRS-FDD (TDMA, GMSK, TN 0-4)	X	100.00	129.04	32.24	6.56	60.0	± 9.6 %
		Y	100.00	121.34	29.01		60.0	
		Z	100.00	114.27	25.82		60.0	
10097-CAB	UMTS-FDD (HSDPA)	X	2.15	71.92	17.30	0.00	150.0	± 9.6 %
		Y	1.74	66.92	14.99		150.0	
		Z	1.84	67.99	15.71		150.0	
10098-CAB	UMTS-FDD (HSUPA, Subtest 2)	X	2.11	71.90	17.32	0.00	150.0	± 9.6 %
		Y	1.71	66.85	14.96		150.0	
		Z	1.80	67.95	15.69		150.0	
10099-DAC	EDGE-FDD (TDMA, 8PSK, TN 0-4)	X	6.01	86.92	33.09	9.56	60.0	± 9.6 %
		Y	6.19	85.06	31.07		60.0	
		Z	8.79	95.20	35.27		60.0	
10100-CAC	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	X	3.07	71.18	17.72	0.00	150.0	± 9.6 %
		Y	2.91	69.14	16.19		150.0	
		Z	3.06	70.10	16.74		150.0	
10101-CAC	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)	X	3.13	67.94	16.52	0.00	150.0	± 9.6 %
		Y	3.12	66.91	15.62		150.0	
		Z	3.19	67.40	15.95		150.0	
10102-CAC	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)	X	3.23	67.93	16.58	0.00	150.0	± 9.6 %
		Y	3.23	66.94	15.74		150.0	
		Z	3.29	67.37	16.03		150.0	
10103-CAC	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	X	5.69	76.86	21.92	3.98	65.0	± 9.6 %
		Y	5.85	75.85	21.01		65.0	
		Z	5.93	75.91	20.91		65.0	
10104-CAC	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)	X	5.41	73.30	20.93	3.98	65.0	± 9.6 %
		Y	5.57	72.62	20.29		65.0	
		Z	5.90	73.68	20.70		65.0	
10105-CAC	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)	X	5.13	71.94	20.57	3.98	65.0	± 9.6 %
		Y	5.51	72.19	20.39		65.0	
		Z	5.44	71.88	20.19		65.0	
10108-CAD	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	X	2.66	70.91	17.69	0.00	150.0	± 9.6 %
		Y	2.53	68.44	15.99		150.0	
		Z	2.65	69.40	16.57		150.0	
10109-CAD	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)	X	2.79	68.29	16.45	0.00	150.0	± 9.6 %
		Y	2.76	66.76	15.45		150.0	
		Z	2.83	67.30	15.82		150.0	
10110-CAD	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	X	2.19	70.82	17.31	0.00	150.0	± 9.6 %
		Y	2.03	67.54	15.46		150.0	
		Z	2.15	68.62	16.14		150.0	
10111-CAD	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)	X	2.62	70.41	16.82	0.00	150.0	± 9.6 %
		Y	2.46	67.59	15.58		150.0	
		Z	2.55	68.26	16.05		150.0	

10112-CAD	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)	X	2.91	68.36	16.50	0.00	150.0	± 9.6 %
		Y	2.89	66.84	15.54		150.0	
		Z	2.96	67.33	15.89		150.0	
10113-CAD	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)	X	2.74	70.44	16.85	0.00	150.0	± 9.6 %
		Y	2.61	67.81	15.74		150.0	
		Z	2.70	68.42	16.18		150.0	
10114-CAB	IEEE 802.11n (HT Greenfield, 13.5 Mbps, BPSK)	X	4.94	67.42	16.86	0.00	150.0	± 9.6 %
		Y	5.03	66.98	16.35		150.0	
		Z	5.06	67.16	16.49		150.0	
10115-CAB	IEEE 802.11n (HT Greenfield, 81 Mbps, 16-QAM)	X	5.18	67.56	16.91	0.00	150.0	± 9.6 %
		Y	5.29	67.07	16.40		150.0	
		Z	5.32	67.22	16.53		150.0	
10116-CAB	IEEE 802.11n (HT Greenfield, 135 Mbps, 64-QAM)	X	5.01	67.63	16.89	0.00	150.0	± 9.6 %
		Y	5.12	67.18	16.38		150.0	
		Z	5.15	67.35	16.51		150.0	
10117-CAB	IEEE 802.11n (HT Mixed, 13.5 Mbps, BPSK)	X	4.91	67.29	16.82	0.00	150.0	± 9.6 %
		Y	5.02	66.91	16.34		150.0	
		Z	5.04	67.07	16.46		150.0	
10118-CAB	IEEE 802.11n (HT Mixed, 81 Mbps, 16-QAM)	X	5.23	67.65	16.96	0.00	150.0	± 9.6 %
		Y	5.36	67.27	16.51		150.0	
		Z	5.40	67.43	16.64		150.0	
10119-CAB	IEEE 802.11n (HT Mixed, 135 Mbps, 64-QAM)	X	5.02	67.64	16.90	0.00	150.0	± 9.6 %
		Y	5.11	67.16	16.38		150.0	
		Z	5.14	67.32	16.51		150.0	
10140-CAC	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)	X	3.24	68.01	16.51	0.00	150.0	± 9.6 %
		Y	3.25	66.95	15.65		150.0	
		Z	3.32	67.39	15.96		150.0	
10141-CAC	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)	X	3.37	68.18	16.69	0.00	150.0	± 9.6 %
		Y	3.38	67.11	15.85		150.0	
		Z	3.44	67.51	16.13		150.0	
10142-CAD	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, QPSK)	X	2.00	71.32	16.52	0.00	150.0	± 9.6 %
		Y	1.78	67.35	14.83		150.0	
		Z	1.92	68.63	15.65		150.0	
10143-CAD	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)	X	2.39	70.56	15.39	0.00	150.0	± 9.6 %
		Y	2.25	67.93	14.86		150.0	
		Z	2.39	68.92	15.52		150.0	
10144-CAD	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)	X	1.83	66.06	12.62	0.00	150.0	± 9.6 %
		Y	2.02	65.59	13.17		150.0	
		Z	2.12	66.38	13.76		150.0	
10145-CAD	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)	X	0.59	60.00	6.22	0.00	150.0	± 9.6 %
		Y	0.93	62.44	9.37		150.0	
		Z	1.02	63.47	10.20		150.0	
10146-CAD	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)	X	0.74	60.00	5.85	0.00	150.0	± 9.6 %
		Y	1.23	61.78	8.25		150.0	
		Z	1.33	62.62	8.97		150.0	
10147-CAD	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)	X	0.74	60.00	5.91	0.00	150.0	± 9.6 %
		Y	1.31	62.33	8.65		150.0	
		Z	1.43	63.42	9.51		150.0	

10149-CAC	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)	X	2.80	68.36	16.50	0.00	150.0	± 9.6 %
		Y	2.77	66.82	15.50		150.0	
		Z	2.84	67.36	15.87		150.0	
10150-CAC	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM)	X	2.92	68.43	16.55	0.00	150.0	± 9.6 %
		Y	2.90	66.90	15.58		150.0	
		Z	2.97	67.38	15.93		150.0	
10151-CAC	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	X	6.41	81.38	23.73	3.98	65.0	± 9.6 %
		Y	6.00	78.20	22.06		65.0	
		Z	6.58	79.61	22.48		65.0	
10152-CAC	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)	X	5.00	73.67	20.52	3.98	65.0	± 9.6 %
		Y	5.10	72.64	19.95		65.0	
		Z	5.45	73.77	20.40		65.0	
10153-CAC	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM)	X	5.39	74.88	21.42	3.98	65.0	± 9.6 %
		Y	5.47	73.72	20.80		65.0	
		Z	5.82	74.77	21.19		65.0	
10154-CAD	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	X	2.23	71.21	17.54	0.00	150.0	± 9.6 %
		Y	2.06	67.88	15.68		150.0	
		Z	2.19	68.97	16.36		150.0	
10155-CAD	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)	X	2.63	70.48	16.87	0.00	150.0	± 9.6 %
		Y	2.47	67.62	15.60		150.0	
		Z	2.56	68.29	16.07		150.0	
10156-CAD	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, QPSK)	X	1.80	70.93	15.66	0.00	150.0	± 9.6 %
		Y	1.60	67.10	14.34		150.0	
		Z	1.75	68.56	15.27		150.0	
10157-CAD	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)	X	1.59	65.75	11.89	0.00	150.0	± 9.6 %
		Y	1.82	65.79	12.92		150.0	
		Z	1.95	66.80	13.63		150.0	
10158-CAD	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)	X	2.76	70.56	16.92	0.00	150.0	± 9.6 %
		Y	2.62	67.88	15.79		150.0	
		Z	2.71	68.49	16.23		150.0	
10159-CAD	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)	X	1.63	65.84	11.94	0.00	150.0	± 9.6 %
		Y	1.90	66.13	13.14		150.0	
		Z	2.04	67.17	13.86		150.0	
10160-CAC	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	X	2.69	70.24	17.33	0.00	150.0	± 9.6 %
		Y	2.60	67.96	15.90		150.0	
		Z	2.70	68.71	16.39		150.0	
10161-CAC	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM)	X	2.80	68.49	16.38	0.00	150.0	± 9.6 %
		Y	2.79	66.84	15.47		150.0	
		Z	2.86	67.35	15.83		150.0	
10162-CAC	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)	X	2.91	68.75	16.53	0.00	150.0	± 9.6 %
		Y	2.90	67.05	15.61		150.0	
		Z	2.97	67.54	15.96		150.0	
10166-CAD	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)	X	2.90	68.50	19.82	3.01	150.0	± 9.6 %
		Y	3.23	68.12	18.35		150.0	
		Z	3.30	68.67	18.76		150.0	
10167-CAD	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM)	X	3.11	70.88	20.29	3.01	150.0	± 9.6 %
		Y	3.74	70.30	18.53		150.0	
		Z	3.85	71.04	19.02		150.0	

10168-CAD	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM)	X	3.42	73.26	21.82	3.01	150.0	± 9.6 %
		Y	4.14	72.52	19.91		150.0	
		Z	4.23	73.11	20.29		150.0	
10169-CAC	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	X	2.29	65.92	18.67	3.01	150.0	± 9.6 %
		Y	2.63	66.60	17.62		150.0	
		Z	2.66	67.13	18.06		150.0	
10170-CAC	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	X	2.45	69.32	20.47	3.01	150.0	± 9.6 %
		Y	3.23	70.79	19.38		150.0	
		Z	3.27	71.40	19.82		150.0	
10171-AAC	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)	X	2.17	66.90	18.27	3.01	150.0	± 9.6 %
		Y	2.76	67.60	16.92		150.0	
		Z	2.82	68.39	17.50		150.0	
10172-CAC	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	X	3.09	78.10	26.58	6.02	65.0	± 9.6 %
		Y	4.72	82.18	25.96		65.0	
		Z	4.91	83.30	26.42		65.0	
10173-CAC	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	X	5.51	91.51	30.30	6.02	65.0	± 9.6 %
		Y	7.59	88.82	26.56		65.0	
		Z	9.70	93.28	27.91		65.0	
10174-CAC	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)	X	4.71	87.54	28.24	6.02	65.0	± 9.6 %
		Y	5.48	82.26	23.72		65.0	
		Z	7.22	87.02	25.25		65.0	
10175-CAD	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	X	2.28	65.75	18.48	3.01	150.0	± 9.6 %
		Y	2.60	66.36	17.40		150.0	
		Z	2.64	66.91	17.86		150.0	
10176-CAD	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)	X	2.45	69.34	20.48	3.01	150.0	± 9.6 %
		Y	3.24	70.81	19.39		150.0	
		Z	3.28	71.41	19.83		150.0	
10177-CAF	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, QPSK)	X	2.29	65.83	18.53	3.01	150.0	± 9.6 %
		Y	2.62	66.47	17.47		150.0	
		Z	2.65	67.01	17.93		150.0	
10178-CAD	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)	X	2.45	69.27	20.43	3.01	150.0	± 9.6 %
		Y	3.22	70.68	19.31		150.0	
		Z	3.26	71.30	19.76		150.0	
10179-CAD	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)	X	2.30	68.18	19.34	3.01	150.0	± 9.6 %
		Y	2.97	69.09	18.02		150.0	
		Z	3.03	69.85	18.56		150.0	
10180-CAD	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)	X	2.17	66.89	18.25	3.01	150.0	± 9.6 %
		Y	2.76	67.56	16.89		150.0	
		Z	2.82	68.36	17.47		150.0	
10181-CAC	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	X	2.28	65.81	18.53	3.01	150.0	± 9.6 %
		Y	2.61	66.45	17.47		150.0	
		Z	2.65	67.00	17.92		150.0	
10182-CAC	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)	X	2.44	69.25	20.42	3.01	150.0	± 9.6 %
		Y	3.21	70.66	19.30		150.0	
		Z	3.26	71.28	19.75		150.0	
10183-AAB	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)	X	2.17	66.87	18.24	3.01	150.0	± 9.6 %
		Y	2.76	67.54	16.88		150.0	
		Z	2.82	68.34	17.46		150.0	

10184-CAD	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, QPSK)	X	2.29	65.84	18.55	3.01	150.0	± 9.6 %
		Y	2.62	66.49	17.48		150.0	
		Z	2.66	67.03	17.94		150.0	
10185-CAD	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM)	X	2.45	69.30	20.46	3.01	150.0	± 9.6 %
		Y	3.23	70.72	19.33		150.0	
		Z	3.27	71.33	19.78		150.0	
10186-AAD	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM)	X	2.18	66.92	18.27	3.01	150.0	± 9.6 %
		Y	2.77	67.59	16.91		150.0	
		Z	2.83	68.39	17.49		150.0	
10187-CAD	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)	X	2.30	65.91	18.62	3.01	150.0	± 9.6 %
		Y	2.63	66.55	17.55		150.0	
		Z	2.66	67.09	18.00		150.0	
10188-CAD	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	X	2.49	69.63	20.71	3.01	150.0	± 9.6 %
		Y	3.30	71.20	19.65		150.0	
		Z	3.34	71.77	20.07		150.0	
10189-AAD	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)	X	2.20	67.17	18.48	3.01	150.0	± 9.6 %
		Y	2.81	67.90	17.14		150.0	
		Z	2.87	68.70	17.72		150.0	
10193-CAB	IEEE 802.11n (HT Greenfield, 6.5 Mbps, BPSK)	X	4.33	67.32	16.55	0.00	150.0	± 9.6 %
		Y	4.42	66.51	16.02		150.0	
		Z	4.46	66.69	16.17		150.0	
10194-CAB	IEEE 802.11n (HT Greenfield, 39 Mbps, 16-QAM)	X	4.45	67.46	16.67	0.00	150.0	± 9.6 %
		Y	4.57	66.77	16.15		150.0	
		Z	4.61	66.96	16.31		150.0	
10195-CAB	IEEE 802.11n (HT Greenfield, 65 Mbps, 64-QAM)	X	4.47	67.43	16.67	0.00	150.0	± 9.6 %
		Y	4.61	66.80	16.17		150.0	
		Z	4.65	66.98	16.33		150.0	
10196-CAB	IEEE 802.11n (HT Mixed, 6.5 Mbps, BPSK)	X	4.31	67.26	16.51	0.00	150.0	± 9.6 %
		Y	4.41	66.52	16.02		150.0	
		Z	4.45	66.71	16.18		150.0	
10197-CAB	IEEE 802.11n (HT Mixed, 39 Mbps, 16-QAM)	X	4.45	67.45	16.68	0.00	150.0	± 9.6 %
		Y	4.58	66.78	16.16		150.0	
		Z	4.62	66.97	16.32		150.0	
10198-CAB	IEEE 802.11n (HT Mixed, 65 Mbps, 64-QAM)	X	4.46	67.42	16.66	0.00	150.0	± 9.6 %
		Y	4.61	66.80	16.18		150.0	
		Z	4.65	66.99	16.33		150.0	
10219-CAB	IEEE 802.11n (HT Mixed, 7.2 Mbps, BPSK)	X	4.27	67.35	16.51	0.00	150.0	± 9.6 %
		Y	4.36	66.54	15.98		150.0	
		Z	4.40	66.73	16.14		150.0	
10220-CAB	IEEE 802.11n (HT Mixed, 43.3 Mbps, 16-QAM)	X	4.44	67.41	16.66	0.00	150.0	± 9.6 %
		Y	4.58	66.74	16.15		150.0	
		Z	4.62	66.93	16.30		150.0	
10221-CAB	IEEE 802.11n (HT Mixed, 72.2 Mbps, 64-QAM)	X	4.48	67.38	16.66	0.00	150.0	± 9.6 %
		Y	4.62	66.75	16.17		150.0	
		Z	4.66	66.93	16.32		150.0	
10222-CAB	IEEE 802.11n (HT Mixed, 15 Mbps, BPSK)	X	4.89	67.31	16.81	0.00	150.0	± 9.6 %
		Y	4.99	66.89	16.31		150.0	
		Z	5.02	67.06	16.44		150.0	

10223-CAB	IEEE 802.11n (HT Mixed, 90 Mbps, 16-QAM)	X	5.09	67.34	16.82	0.00	150.0	± 9.6 %
		Y	5.27	67.13	16.45		150.0	
		Z	5.30	67.28	16.57		150.0	
10224-CAB	IEEE 802.11n (HT Mixed, 150 Mbps, 64-QAM)	X	4.94	67.46	16.81	0.00	150.0	± 9.6 %
		Y	5.02	67.00	16.30		150.0	
		Z	5.05	67.16	16.43		150.0	
10225-CAB	UMTS-FDD (HSPA+)	X	2.63	67.02	15.06	0.00	150.0	± 9.6 %
		Y	2.68	65.76	14.81		150.0	
		Z	2.74	66.17	15.16		150.0	
10226-CAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	X	5.86	92.93	30.90	6.02	65.0	± 9.6 %
		Y	8.05	90.01	27.06		65.0	
		Z	10.31	94.50	28.40		65.0	
10227-CAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)	X	6.52	94.38	30.69	6.02	65.0	± 9.6 %
		Y	8.36	89.57	26.27		65.0	
		Z	10.42	93.29	27.32		65.0	
10228-CAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)	X	3.61	81.81	28.20	6.02	65.0	± 9.6 %
		Y	4.97	83.57	26.58		65.0	
		Z	6.35	88.86	28.52		65.0	
10229-CAB	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM)	X	5.55	91.61	30.34	6.02	65.0	± 9.6 %
		Y	7.65	88.93	26.60		65.0	
		Z	9.77	93.37	27.95		65.0	
10230-CAB	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM)	X	6.01	92.63	30.03	6.02	65.0	± 9.6 %
		Y	7.86	88.40	25.80		65.0	
		Z	9.78	92.10	26.87		65.0	
10231-CAB	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK)	X	3.50	81.08	27.82	6.02	65.0	± 9.6 %
		Y	4.80	82.82	26.22		65.0	
		Z	6.12	88.04	28.15		65.0	
10232-CAC	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)	X	5.54	91.57	30.33	6.02	65.0	± 9.6 %
		Y	7.63	88.91	26.59		65.0	
		Z	9.75	93.36	27.95		65.0	
10233-CAC	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)	X	5.98	92.53	30.00	6.02	65.0	± 9.6 %
		Y	7.83	88.35	25.79		65.0	
		Z	9.75	92.07	26.86		65.0	
10234-CAC	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK)	X	3.45	80.68	27.55	6.02	65.0	± 9.6 %
		Y	4.68	82.21	25.87		65.0	
		Z	5.94	87.34	27.79		65.0	
10235-CAC	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)	X	5.54	91.61	30.35	6.02	65.0	± 9.6 %
		Y	7.64	88.93	26.60		65.0	
		Z	9.77	93.40	27.96		65.0	
10236-CAC	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)	X	6.10	92.88	30.10	6.02	65.0	± 9.6 %
		Y	7.92	88.52	25.84		65.0	
		Z	9.89	92.27	26.92		65.0	
10237-CAC	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	X	3.50	81.08	27.83	6.02	65.0	± 9.6 %
		Y	4.80	82.84	26.23		65.0	
		Z	6.12	88.09	28.18		65.0	
10238-CAC	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)	X	5.52	91.54	30.32	6.02	65.0	± 9.6 %
		Y	7.61	88.88	26.58		65.0	
		Z	9.73	93.33	27.94		65.0	

10239-CAC	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)	X	5.95	92.45	29.98	6.02	65.0	± 9.6 %
		Y	7.80	88.31	25.77		65.0	
		Z	9.71	92.02	26.85		65.0	
10240-CAC	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	X	3.49	81.08	27.83	6.02	65.0	± 9.6 %
		Y	4.79	82.81	26.22		65.0	
		Z	6.10	88.05	28.16		65.0	
10241-CAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM)	X	6.18	82.34	27.74	6.98	65.0	± 9.6 %
		Y	6.74	79.09	24.85		65.0	
		Z	7.26	80.80	25.58		65.0	
10242-CAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM)	X	5.72	80.71	27.01	6.98	65.0	± 9.6 %
		Y	5.88	76.22	23.56		65.0	
		Z	6.56	78.67	24.62		65.0	
10243-CAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)	X	4.79	76.15	25.80	6.98	65.0	± 9.6 %
		Y	5.34	74.93	23.87		65.0	
		Z	5.31	74.92	23.91		65.0	
10244-CAB	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	X	3.96	72.35	15.57	3.98	65.0	± 9.6 %
		Y	4.42	72.46	16.54		65.0	
		Z	4.70	73.13	16.80		65.0	
10245-CAB	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	X	3.63	70.86	14.82	3.98	65.0	± 9.6 %
		Y	4.27	71.69	16.14		65.0	
		Z	4.54	72.35	16.40		65.0	
10246-CAB	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	X	3.93	75.25	17.14	3.98	65.0	± 9.6 %
		Y	4.93	78.34	19.63		65.0	
		Z	5.44	79.35	19.87		65.0	
10247-CAC	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)	X	3.77	71.44	16.20	3.98	65.0	± 9.6 %
		Y	4.35	72.96	18.04		65.0	
		Z	4.62	73.67	18.26		65.0	
10248-CAC	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)	X	3.56	70.15	15.58	3.98	65.0	± 9.6 %
		Y	4.27	72.12	17.63		65.0	
		Z	4.55	72.89	17.89		65.0	
10249-CAC	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK)	X	7.20	85.80	22.91	3.98	65.0	± 9.6 %
		Y	6.26	82.63	22.49		65.0	
		Z	7.15	84.34	22.93		65.0	
10250-CAC	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)	X	5.23	76.98	21.45	3.98	65.0	± 9.6 %
		Y	5.19	75.46	21.10		65.0	
		Z	5.55	76.46	21.42		65.0	
10251-CAC	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)	X	4.71	73.79	19.58	3.98	65.0	± 9.6 %
		Y	4.90	73.09	19.63		65.0	
		Z	5.25	74.18	20.04		65.0	
10252-CAC	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	X	7.25	86.32	25.18	3.98	65.0	± 9.6 %
		Y	6.16	81.37	23.24		65.0	
		Z	7.01	83.33	23.82		65.0	
10253-CAC	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM)	X	4.94	73.36	20.16	3.98	65.0	± 9.6 %
		Y	5.03	72.23	19.69		65.0	
		Z	5.35	73.29	20.12		65.0	
10254-CAC	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)	X	5.26	74.32	20.87	3.98	65.0	± 9.6 %
		Y	5.36	73.19	20.44		65.0	
		Z	5.68	74.19	20.82		65.0	

10255-CAC	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	X	6.05	80.45	23.41	3.98	65.0	± 9.6 %
		Y	5.67	77.32	21.87		65.0	
		Z	6.21	78.75	22.32		65.0	
10256-CAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)	X	2.17	64.51	10.31	3.98	65.0	± 9.6 %
		Y	3.11	67.47	13.02		65.0	
		Z	3.30	68.03	13.28		65.0	
10257-CAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)	X	2.08	63.71	9.72	3.98	65.0	± 9.6 %
		Y	3.02	66.72	12.53		65.0	
		Z	3.19	67.26	12.79		65.0	
10258-CAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)	X	2.03	65.71	11.35	3.98	65.0	± 9.6 %
		Y	3.25	71.53	15.68		65.0	
		Z	3.48	72.10	15.82		65.0	
10259-CAB	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)	X	4.43	74.02	18.32	3.98	65.0	± 9.6 %
		Y	4.71	74.05	19.21		65.0	
		Z	5.02	74.87	19.47		65.0	
10260-CAB	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)	X	4.38	73.44	18.03	3.98	65.0	± 9.6 %
		Y	4.72	73.68	19.04		65.0	
		Z	5.02	74.47	19.29		65.0	
10261-CAB	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK)	X	6.83	85.03	23.41	3.98	65.0	± 9.6 %
		Y	5.83	80.99	22.37		65.0	
		Z	6.62	82.75	22.88		65.0	
10262-CAC	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)	X	5.21	76.87	21.38	3.98	65.0	± 9.6 %
		Y	5.17	75.38	21.05		65.0	
		Z	5.54	76.39	21.37		65.0	
10263-CAC	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)	X	4.70	73.77	19.57	3.98	65.0	± 9.6 %
		Y	4.89	73.06	19.62		65.0	
		Z	5.24	74.14	20.03		65.0	
10264-CAC	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	X	7.14	86.00	25.04	3.98	65.0	± 9.6 %
		Y	6.09	81.13	23.12		65.0	
		Z	6.93	83.09	23.70		65.0	
10265-CAC	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)	X	5.00	73.68	20.53	3.98	65.0	± 9.6 %
		Y	5.10	72.64	19.95		65.0	
		Z	5.45	73.78	20.40		65.0	
10266-CAC	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)	X	5.38	74.87	21.41	3.98	65.0	± 9.6 %
		Y	5.47	73.71	20.79		65.0	
		Z	5.82	74.76	21.18		65.0	
10267-CAC	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	X	6.39	81.30	23.69	3.98	65.0	± 9.6 %
		Y	5.99	78.15	22.04		65.0	
		Z	6.57	79.56	22.45		65.0	
10268-CAC	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)	X	5.59	73.41	20.99	3.98	65.0	± 9.6 %
		Y	5.73	72.57	20.35		65.0	
		Z	6.05	73.54	20.73		65.0	
10269-CAC	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)	X	5.61	73.05	20.84	3.98	65.0	± 9.6 %
		Y	5.73	72.17	20.20		65.0	
		Z	6.03	73.11	20.57		65.0	
10270-CAC	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	X	5.98	77.12	22.16	3.98	65.0	± 9.6 %
		Y	5.87	75.17	20.91		65.0	
		Z	6.26	76.14	21.20		65.0	

10274-CAB	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.10)	X	2.55	68.17	15.46	0.00	150.0	± 9.6 %
		Y	2.49	66.17	14.76		150.0	
		Z	2.56	66.71	15.18		150.0	
10275-CAB	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.4)	X	1.81	71.52	17.29	0.00	150.0	± 9.6 %
		Y	1.49	66.64	14.71		150.0	
		Z	1.60	68.01	15.58		150.0	
10277-CAA	PHS (QPSK)	X	1.20	59.10	4.33	9.03	50.0	± 9.6 %
		Y	1.54	60.11	5.61		50.0	
		Z	1.50	60.00	5.38		50.0	
10278-CAA	PHS (QPSK, BW 884MHz, Rolloff 0.5)	X	2.43	65.13	10.33	9.03	50.0	± 9.6 %
		Y	4.35	72.80	15.16		50.0	
		Z	3.88	71.21	14.25		50.0	
10279-CAA	PHS (QPSK, BW 884MHz, Rolloff 0.38)	X	2.48	65.27	10.47	9.03	50.0	± 9.6 %
		Y	4.49	73.17	15.39		50.0	
		Z	4.04	71.64	14.51		50.0	
10290-AAB	CDMA2000, RC1, SO55, Full Rate	X	0.85	65.05	10.07	0.00	150.0	± 9.6 %
		Y	1.08	65.56	11.63		150.0	
		Z	1.26	67.59	12.88		150.0	
10291-AAB	CDMA2000, RC3, SO55, Full Rate	X	0.71	65.97	10.53	0.00	150.0	± 9.6 %
		Y	0.68	63.64	10.53		150.0	
		Z	0.77	65.28	11.69		150.0	
10292-AAB	CDMA2000, RC3, SO32, Full Rate	X	8.82	93.45	20.21	0.00	150.0	± 9.6 %
		Y	0.82	66.63	12.45		150.0	
		Z	1.06	70.24	14.45		150.0	
10293-AAB	CDMA2000, RC3, SO3, Full Rate	X	100.00	124.12	28.30	0.00	150.0	± 9.6 %
		Y	1.21	71.68	15.19		150.0	
		Z	2.01	78.98	18.41		150.0	
10295-AAB	CDMA2000, RC1, SO3, 1/8th Rate 25 fr.	X	100.00	119.05	31.20	9.03	50.0	± 9.6 %
		Y	24.63	103.59	29.58		50.0	
		Z	19.78	99.71	28.31		50.0	
10297-AAB	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	X	2.68	71.03	17.77	0.00	150.0	± 9.6 %
		Y	2.54	68.53	16.06		150.0	
		Z	2.67	69.50	16.63		150.0	
10298-AAC	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	X	1.01	64.51	10.53	0.00	150.0	± 9.6 %
		Y	1.25	65.17	12.09		150.0	
		Z	1.39	66.65	13.09		150.0	
10299-AAC	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	X	1.37	64.96	10.25	0.00	150.0	± 9.6 %
		Y	1.71	64.67	10.97		150.0	
		Z	1.89	66.01	11.90		150.0	
10300-AAC	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	X	0.94	60.70	7.08	0.00	150.0	± 9.6 %
		Y	1.43	62.18	8.95		150.0	
		Z	1.50	62.80	9.52		150.0	
10301-AAA	IEEE 802.16e WiMAX (29:18, 5ms, 10MHz, QPSK, PUSC)	X	4.48	66.56	17.74	4.17	50.0	± 9.6 %
		Y	4.54	65.14	17.13		50.0	
		Z	4.63	65.66	17.54		50.0	
10302-AAA	IEEE 802.16e WiMAX (29:18, 5ms, 10MHz, QPSK, PUSC, 3 CTRL symbols)	X	4.83	66.58	18.17	4.96	50.0	± 9.6 %
		Y	5.00	65.66	17.79		50.0	
		Z	5.03	65.96	18.09		50.0	

10303-AAA	IEEE 802.16e WiMAX (31:15, 5ms, 10MHz, 64QAM, PUSC)	X	4.61	66.31	17.96	4.96	50.0	± 9.6 %
		Y	4.75	65.26	17.58		50.0	
		Z	4.77	65.54	17.87		50.0	
10304-AAA	IEEE 802.16e WiMAX (29:18, 5ms, 10MHz, 64QAM, PUSC)	X	4.46	66.32	17.54	4.17	50.0	± 9.6 %
		Y	4.58	65.22	17.12		50.0	
		Z	4.61	65.50	17.40		50.0	
10305-AAA	IEEE 802.16e WiMAX (31:15, 10ms, 10MHz, 64QAM, PUSC, 15 symbols)	X	3.93	67.44	18.36	6.02	35.0	± 9.6 %
		Y	4.05	66.33	18.54		35.0	
		Z	4.03	66.39	18.80		35.0	
10306-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, 64QAM, PUSC, 18 symbols)	X	4.30	66.92	18.60	6.02	35.0	± 9.6 %
		Y	4.44	65.81	18.47		35.0	
		Z	4.43	65.88	18.69		35.0	
10307-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, QPSK, PUSC, 18 symbols)	X	4.17	66.85	18.45	6.02	35.0	± 9.6 %
		Y	4.32	65.81	18.36		35.0	
		Z	4.30	65.87	18.58		35.0	
10308-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, 16QAM, PUSC)	X	4.16	67.08	18.62	6.02	35.0	± 9.6 %
		Y	4.29	65.97	18.48		35.0	
		Z	4.27	66.05	18.72		35.0	
10309-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, 16QAM, AMC 2x3, 18 symbols)	X	4.31	66.96	18.69	6.02	35.0	± 9.6 %
		Y	4.47	65.93	18.58		35.0	
		Z	4.47	66.03	18.82		35.0	
10310-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, QPSK, AMC 2x3, 18 symbols)	X	4.26	67.01	18.62	6.02	35.0	± 9.6 %
		Y	4.39	65.84	18.44		35.0	
		Z	4.37	65.90	18.66		35.0	
10311-AAB	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	X	3.03	69.88	17.26	0.00	150.0	± 9.6 %
		Y	2.89	67.87	15.77		150.0	
		Z	3.03	68.75	16.28		150.0	
10313-AAA	iDEN 1:3	X	9.23	93.10	24.89	6.99	70.0	± 9.6 %
		Y	4.30	79.25	19.39		70.0	
		Z	4.82	79.70	19.10		70.0	
10314-AAA	iDEN 1:6	X	10.97	102.43	31.47	10.00	30.0	± 9.6 %
		Y	7.12	91.40	26.96		30.0	
		Z	6.61	89.38	25.89		30.0	
10315-AAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 96pc duty cycle)	X	1.16	65.17	16.40	0.17	150.0	± 9.6 %
		Y	1.06	63.03	14.60		150.0	
		Z	1.09	63.74	15.20		150.0	
10316-AAB	IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 96pc duty cycle)	X	4.35	67.20	16.66	0.17	150.0	± 9.6 %
		Y	4.47	66.54	16.18		150.0	
		Z	4.50	66.70	16.32		150.0	
10317-AAB	IEEE 802.11a WiFi 5 GHz (OFDM, 6 Mbps, 96pc duty cycle)	X	4.35	67.20	16.66	0.17	150.0	± 9.6 %
		Y	4.47	66.54	16.18		150.0	
		Z	4.50	66.70	16.32		150.0	
10400-AAC	IEEE 802.11ac WiFi (20MHz, 64-QAM, 99pc duty cycle)	X	4.37	67.37	16.61	0.00	150.0	± 9.6 %
		Y	4.54	66.79	16.14		150.0	
		Z	4.59	67.00	16.31		150.0	
10401-AAC	IEEE 802.11ac WiFi (40MHz, 64-QAM, 99pc duty cycle)	X	5.16	67.37	16.79	0.00	150.0	± 9.6 %
		Y	5.26	66.90	16.30		150.0	
		Z	5.31	67.11	16.46		150.0	

10402-AAC	IEEE 802.11ac WiFi (80MHz, 64-QAM, 99pc duty cycle)	X	5.46	67.61	16.83	0.00	150.0	± 9.6 %
		Y	5.54	67.25	16.36		150.0	
		Z	5.57	67.40	16.47		150.0	
10403-AAB	CDMA2000 (1xEV-DO, Rev. 0)	X	0.85	65.05	10.07	0.00	115.0	± 9.6 %
		Y	1.08	65.56	11.63		115.0	
		Z	1.26	67.59	12.88		115.0	
10404-AAB	CDMA2000 (1xEV-DO, Rev. A)	X	0.85	65.05	10.07	0.00	115.0	± 9.6 %
		Y	1.08	65.56	11.63		115.0	
		Z	1.26	67.59	12.88		115.0	
10406-AAB	CDMA2000, RC3, SO32, SCH0, Full Rate	X	100.00	144.32	38.42	0.00	100.0	± 9.6 %
		Y	6.28	84.84	20.31		100.0	
		Z	12.70	95.38	23.84		100.0	
10410-AAB	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	155.75	44.41	3.23	80.0	± 9.6 %
		Y	19.16	104.95	27.25		80.0	
		Z	66.43	121.59	31.01		80.0	
10415-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 99pc duty cycle)	X	1.10	64.49	15.88	0.00	150.0	± 9.6 %
		Y	1.01	62.42	14.08		150.0	
		Z	1.03	63.06	14.69		150.0	
10416-AAA	IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 99pc duty cycle)	X	4.31	67.21	16.59	0.00	150.0	± 9.6 %
		Y	4.42	66.52	16.09		150.0	
		Z	4.46	66.70	16.25		150.0	
10417-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 99pc duty cycle)	X	4.31	67.21	16.59	0.00	150.0	± 9.6 %
		Y	4.42	66.52	16.09		150.0	
		Z	4.46	66.70	16.25		150.0	
10418-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Long preamble)	X	4.31	67.47	16.69	0.00	150.0	± 9.6 %
		Y	4.41	66.70	16.13		150.0	
		Z	4.45	66.89	16.29		150.0	
10419-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Short preamble)	X	4.32	67.38	16.66	0.00	150.0	± 9.6 %
		Y	4.43	66.64	16.12		150.0	
		Z	4.47	66.83	16.28		150.0	
10422-AAA	IEEE 802.11n (HT Greenfield, 7.2 Mbps, BPSK)	X	4.42	67.32	16.66	0.00	150.0	± 9.6 %
		Y	4.54	66.63	16.14		150.0	
		Z	4.58	66.81	16.29		150.0	
10423-AAA	IEEE 802.11n (HT Greenfield, 43.3 Mbps, 16-QAM)	X	4.52	67.55	16.73	0.00	150.0	± 9.6 %
		Y	4.68	66.90	16.24		150.0	
		Z	4.72	67.09	16.39		150.0	
10424-AAA	IEEE 802.11n (HT Greenfield, 72.2 Mbps, 64-QAM)	X	4.46	67.48	16.70	0.00	150.0	± 9.6 %
		Y	4.61	66.85	16.21		150.0	
		Z	4.65	67.05	16.37		150.0	
10425-AAA	IEEE 802.11n (HT Greenfield, 15 Mbps, BPSK)	X	5.11	67.53	16.90	0.00	150.0	± 9.6 %
		Y	5.24	67.14	16.44		150.0	
		Z	5.27	67.29	16.56		150.0	
10426-AAA	IEEE 802.11n (HT Greenfield, 90 Mbps, 16-QAM)	X	5.17	67.76	17.01	0.00	150.0	± 9.6 %
		Y	5.26	67.23	16.48		150.0	
		Z	5.28	67.37	16.60		150.0	

10427-AAA	IEEE 802.11n (HT Greenfield, 150 Mbps, 64-QAM)	X	5.11	67.45	16.85	0.00	150.0	± 9.6 %
		Y	5.23	67.07	16.39		150.0	
		Z	5.27	67.24	16.53		150.0	
10430-AAA	LTE-FDD (OFDMA, 5 MHz, E-TM 3.1)	X	4.32	73.64	18.59	0.00	150.0	± 9.6 %
		Y	4.15	71.13	17.99		150.0	
		Z	4.15	71.07	18.04		150.0	
10431-AAA	LTE-FDD (OFDMA, 10 MHz, E-TM 3.1)	X	3.89	67.96	16.38	0.00	150.0	± 9.6 %
		Y	4.04	67.01	15.96		150.0	
		Z	4.10	67.27	16.17		150.0	
10432-AAA	LTE-FDD (OFDMA, 15 MHz, E-TM 3.1)	X	4.22	67.69	16.63	0.00	150.0	± 9.6 %
		Y	4.36	66.90	16.12		150.0	
		Z	4.41	67.12	16.30		150.0	
10433-AAA	LTE-FDD (OFDMA, 20 MHz, E-TM 3.1)	X	4.48	67.52	16.73	0.00	150.0	± 9.6 %
		Y	4.62	66.88	16.23		150.0	
		Z	4.66	67.08	16.39		150.0	
10434-AAA	W-CDMA (BS Test Model 1, 64 DPCH)	X	4.32	74.00	17.97	0.00	150.0	± 9.6 %
		Y	4.21	71.88	17.80		150.0	
		Z	4.24	71.90	17.91		150.0	
10435-AAB	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	155.40	44.24	3.23	80.0	± 9.6 %
		Y	17.90	103.83	26.90		80.0	
		Z	59.43	119.80	30.54		80.0	
10447-AAA	LTE-FDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)	X	3.06	67.49	14.71	0.00	150.0	± 9.6 %
		Y	3.28	66.77	14.91		150.0	
		Z	3.36	67.18	15.25		150.0	
10448-AAA	LTE-FDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)	X	3.78	67.79	16.29	0.00	150.0	± 9.6 %
		Y	3.90	66.80	15.83		150.0	
		Z	3.95	67.06	16.04		150.0	
10449-AAA	LTE-FDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)	X	4.08	67.53	16.54	0.00	150.0	± 9.6 %
		Y	4.20	66.73	16.02		150.0	
		Z	4.24	66.95	16.20		150.0	
10450-AAA	LTE-FDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)	X	4.30	67.31	16.60	0.00	150.0	± 9.6 %
		Y	4.41	66.65	16.08		150.0	
		Z	4.45	66.85	16.24		150.0	
10451-AAA	W-CDMA (BS Test Model 1, 64 DPCH, Clipping 44%)	X	2.74	66.60	13.48	0.00	150.0	± 9.6 %
		Y	3.10	66.65	14.28		150.0	
		Z	3.20	67.15	14.68		150.0	
10456-AAA	IEEE 802.11ac WiFi (160MHz, 64-QAM, 99pc duty cycle)	X	6.67	69.79	17.97	0.00	150.0	± 9.6 %
		Y	6.19	67.86	16.70		150.0	
		Z	6.21	67.97	16.79		150.0	
10457-AAA	UMTS-FDD (DC-HSDPA)	X	3.74	66.12	16.37	0.00	150.0	± 9.6 %
		Y	3.75	65.23	15.80		150.0	
		Z	3.77	65.40	15.96		150.0	
10458-AAA	CDMA2000 (1xEV-DO, Rev. B, 2 carriers)	X	2.21	63.78	11.12	0.00	150.0	± 9.6 %
		Y	2.86	65.69	13.35		150.0	
		Z	2.97	66.25	13.82		150.0	
10459-AAA	CDMA2000 (1xEV-DO, Rev. B, 3 carriers)	X	3.54	64.20	13.62	0.00	150.0	± 9.6 %
		Y	4.05	64.79	14.93		150.0	
		Z	4.22	65.48	15.42		150.0	

10460-AAA	UMTS-FDD (WCDMA, AMR)	X	1.27	75.08	19.80	0.00	150.0	± 9.6 %
		Y	0.82	65.98	14.72		150.0	
		Z	0.91	68.24	16.19		150.0	
10461-AAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	161.77	47.27	3.29	80.0	± 9.6 %
		Y	7.31	93.33	24.99		80.0	
		Z	15.34	103.86	27.76		80.0	
10462-AAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	100.00	132.71	33.20	3.23	80.0	± 9.6 %
		Y	1.46	66.08	11.77		80.0	
		Z	1.53	66.43	11.75		80.0	
10463-AAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	100.00	121.70	28.30	3.23	80.0	± 9.6 %
		Y	0.95	61.39	9.01		80.0	
		Z	0.95	61.37	8.84		80.0	
10464-AAA	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	160.44	46.32	3.23	80.0	± 9.6 %
		Y	6.23	90.14	23.37		80.0	
		Z	14.07	101.09	26.27		80.0	
10465-AAA	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	100.00	131.00	32.46	3.23	80.0	± 9.6 %
		Y	1.28	64.64	11.07		80.0	
		Z	1.32	64.93	11.04		80.0	
10466-AAA	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	100.00	119.91	27.55	3.23	80.0	± 9.6 %
		Y	0.90	60.85	8.68		80.0	
		Z	0.90	60.82	8.52		80.0	
10467-AAB	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	161.06	46.59	3.23	80.0	± 9.6 %
		Y	6.93	91.78	23.91		80.0	
		Z	16.54	103.53	26.96		80.0	
10468-AAB	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	100.00	131.80	32.80	3.23	80.0	± 9.6 %
		Y	1.32	65.04	11.27		80.0	
		Z	1.37	65.34	11.24		80.0	
10469-AAB	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	100.00	120.20	27.66	3.23	80.0	± 9.6 %
		Y	0.90	60.87	8.69		80.0	
		Z	0.90	60.84	8.53		80.0	
10470-AAB	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	161.24	46.66	3.23	80.0	± 9.6 %
		Y	6.96	91.88	23.93		80.0	
		Z	16.80	103.78	27.02		80.0	
10471-AAB	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	100.00	131.74	32.77	3.23	80.0	± 9.6 %
		Y	1.31	64.98	11.23		80.0	
		Z	1.36	65.28	11.20		80.0	
10472-AAB	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	100.00	120.06	27.60	3.23	80.0	± 9.6 %
		Y	0.89	60.84	8.66		80.0	
		Z	0.89	60.81	8.50		80.0	
10473-AAB	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	161.22	46.64	3.23	80.0	± 9.6 %
		Y	6.93	91.81	23.91		80.0	
		Z	16.75	103.72	26.99		80.0	
10474-AAB	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	100.00	131.79	32.78	3.23	80.0	± 9.6 %
		Y	1.31	64.94	11.22		80.0	
		Z	1.36	65.23	11.18		80.0	
10475-AAB	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	100.00	120.12	27.62	3.23	80.0	± 9.6 %
		Y	0.89	60.82	8.65		80.0	
		Z	0.89	60.79	8.49		80.0	

10477-AAB	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	100.00	131.25	32.54	3.23	80.0	± 9.6 %
		Y	1.27	64.63	11.05		80.0	
		Z	1.31	64.90	11.01		80.0	
10478-AAB	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	100.00	119.89	27.52	3.23	80.0	± 9.6 %
		Y	0.89	60.79	8.62		80.0	
		Z	0.89	60.75	8.46		80.0	
10479-AAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	143.20	40.52	3.23	80.0	± 9.6 %
		Y	5.80	83.90	22.21		80.0	
		Z	7.03	86.65	23.11		80.0	
10480-AAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	100.00	126.24	32.30	3.23	80.0	± 9.6 %
		Y	4.92	76.76	17.64		80.0	
		Z	5.56	78.22	18.15		80.0	
10481-AAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	100.00	121.94	30.24	3.23	80.0	± 9.6 %
		Y	3.69	72.56	15.67		80.0	
		Z	4.12	73.80	16.15		80.0	
10482-AAA	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	2.63	71.91	15.00	2.23	80.0	± 9.6 %
		Y	2.37	70.07	15.65		80.0	
		Z	2.66	71.49	16.23		80.0	
10483-AAA	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	6.33	78.41	16.56	2.23	80.0	± 9.6 %
		Y	2.52	67.01	13.39		80.0	
		Z	2.84	68.40	14.08		80.0	
10484-AAA	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.52	71.86	14.27	2.23	80.0	± 9.6 %
		Y	2.41	66.16	12.99		80.0	
		Z	2.68	67.44	13.66		80.0	
10485-AAB	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	4.95	81.91	20.82	2.23	80.0	± 9.6 %
		Y	2.83	72.43	17.91		80.0	
		Z	3.15	73.85	18.45		80.0	
10486-AAB	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	2.56	68.51	14.29	2.23	80.0	± 9.6 %
		Y	2.73	68.25	15.30		80.0	
		Z	2.90	68.98	15.64		80.0	
10487-AAB	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	2.43	67.46	13.77	2.23	80.0	± 9.6 %
		Y	2.71	67.79	15.06		80.0	
		Z	2.88	68.48	15.39		80.0	
10488-AAB	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	3.68	76.35	20.71	2.23	80.0	± 9.6 %
		Y	3.07	71.33	18.42		80.0	
		Z	3.32	72.54	18.88		80.0	
10489-AAB	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.41	71.34	18.09	2.23	80.0	± 9.6 %
		Y	3.13	68.37	16.96		80.0	
		Z	3.26	68.96	17.21		80.0	
10490-AAB	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.42	70.89	17.85	2.23	80.0	± 9.6 %
		Y	3.21	68.23	16.89		80.0	
		Z	3.34	68.78	17.13		80.0	
10491-AAB	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	3.56	72.82	19.59	2.23	80.0	± 9.6 %
		Y	3.34	69.96	17.99		80.0	
		Z	3.54	70.86	18.34		80.0	
10492-AAB	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.54	69.44	17.91	2.23	80.0	± 9.6 %
		Y	3.47	67.60	17.00		80.0	
		Z	3.59	68.11	17.22		80.0	

10493-AAB	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.57	69.22	17.77	2.23	80.0	± 9.6 %
		Y	3.53	67.49	16.95		80.0	
		Z	3.65	67.98	17.16		80.0	
10494-AAB	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	3.86	74.32	20.21	2.23	80.0	± 9.6 %
		Y	3.57	71.29	18.45		80.0	
		Z	3.83	72.33	18.84		80.0	
10495-AAB	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.55	69.56	18.16	2.23	80.0	± 9.6 %
		Y	3.49	67.86	17.20		80.0	
		Z	3.61	68.40	17.42		80.0	
10496-AAB	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.62	69.26	18.03	2.23	80.0	± 9.6 %
		Y	3.57	67.65	17.13		80.0	
		Z	3.69	68.15	17.33		80.0	
10497-AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	0.88	60.00	7.81	2.23	80.0	± 9.6 %
		Y	1.49	64.24	11.70		80.0	
		Z	1.64	65.22	12.20		80.0	
10498-AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	1.07	60.00	6.21	2.23	80.0	± 9.6 %
		Y	1.22	60.00	8.25		80.0	
		Z	1.24	60.00	8.32		80.0	
10499-AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	1.10	60.00	6.01	2.23	80.0	± 9.6 %
		Y	1.23	60.00	8.08		80.0	
		Z	1.26	60.00	8.16		80.0	
10500-AAA	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	4.22	79.34	20.69	2.23	80.0	± 9.6 %
		Y	2.89	71.78	18.04		80.0	
		Z	3.18	73.09	18.55		80.0	
10501-AAA	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.15	70.87	16.24	2.23	80.0	± 9.6 %
		Y	2.94	68.56	16.05		80.0	
		Z	3.09	69.21	16.34		80.0	
10502-AAA	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.11	70.28	15.87	2.23	80.0	± 9.6 %
		Y	2.98	68.40	15.89		80.0	
		Z	3.14	69.02	16.18		80.0	
10503-AAB	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	3.62	76.09	20.58	2.23	80.0	± 9.6 %
		Y	3.03	71.14	18.32		80.0	
		Z	3.28	72.34	18.79		80.0	
10504-AAB	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.38	71.20	18.00	2.23	80.0	± 9.6 %
		Y	3.11	68.27	16.90		80.0	
		Z	3.24	68.86	17.15		80.0	
10505-AAB	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.40	70.78	17.78	2.23	80.0	± 9.6 %
		Y	3.19	68.14	16.83		80.0	
		Z	3.32	68.70	17.08		80.0	
10506-AAB	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	3.83	74.17	20.13	2.23	80.0	± 9.6 %
		Y	3.55	71.16	18.38		80.0	
		Z	3.80	72.20	18.77		80.0	
10507-AAB	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.54	69.50	18.12	2.23	80.0	± 9.6 %
		Y	3.47	67.80	17.16		80.0	
		Z	3.60	68.34	17.38		80.0	

10508-AAB	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.60	69.19	17.98	2.23	80.0	± 9.6 %
		Y	3.56	67.58	17.08		80.0	
		Z	3.68	68.09	17.29		80.0	
10509-AAB	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	4.07	72.04	19.25	2.23	80.0	± 9.6 %
		Y	3.95	70.15	17.94		80.0	
		Z	4.15	70.90	18.22		80.0	
10510-AAB	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.92	68.55	17.94	2.23	80.0	± 9.6 %
		Y	3.95	67.54	17.17		80.0	
		Z	4.07	68.02	17.36		80.0	
10511-AAB	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.99	68.36	17.86	2.23	80.0	± 9.6 %
		Y	4.02	67.35	17.11		80.0	
		Z	4.13	67.80	17.30		80.0	
10512-AAB	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	4.24	73.51	19.76	2.23	80.0	± 9.6 %
		Y	4.06	71.47	18.37		80.0	
		Z	4.32	72.41	18.70		80.0	
10513-AAB	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.82	68.65	18.03	2.23	80.0	± 9.6 %
		Y	3.83	67.69	17.25		80.0	
		Z	3.96	68.21	17.46		80.0	
10514-AAB	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.86	68.26	17.88	2.23	80.0	± 9.6 %
		Y	3.88	67.34	17.14		80.0	
		Z	3.99	67.83	17.33		80.0	
10515-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 99pc duty cycle)	X	1.06	64.80	16.03	0.00	150.0	± 9.6 %
		Y	0.97	62.54	14.10		150.0	
		Z	0.99	63.24	14.75		150.0	
10516-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 99pc duty cycle)	X	1.17	82.52	23.85	0.00	150.0	± 9.6 %
		Y	0.52	66.30	14.94		150.0	
		Z	0.63	70.27	17.40		150.0	
10517-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 99pc duty cycle)	X	0.95	67.83	17.43	0.00	150.0	± 9.6 %
		Y	0.80	63.79	14.36		150.0	
		Z	0.84	65.07	15.37		150.0	
10518-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 99pc duty cycle)	X	4.31	67.36	16.61	0.00	150.0	± 9.6 %
		Y	4.41	66.60	16.08		150.0	
		Z	4.45	66.79	16.23		150.0	
10519-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 99pc duty cycle)	X	4.42	67.49	16.68	0.00	150.0	± 9.6 %
		Y	4.57	66.79	16.18		150.0	
		Z	4.61	66.98	16.33		150.0	
10520-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 99pc duty cycle)	X	4.29	67.42	16.60	0.00	150.0	± 9.6 %
		Y	4.42	66.72	16.09		150.0	
		Z	4.46	66.92	16.25		150.0	
10521-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 99pc duty cycle)	X	4.22	67.34	16.56	0.00	150.0	± 9.6 %
		Y	4.35	66.69	16.06		150.0	
		Z	4.40	66.90	16.23		150.0	
10522-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 99pc duty cycle)	X	4.24	67.37	16.60	0.00	150.0	± 9.6 %
		Y	4.41	66.82	16.17		150.0	
		Z	4.45	67.03	16.34		150.0	

10523- AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 99pc duty cycle)	X	4.23	67.62	16.67	0.00	150.0	± 9.6 %
		Y	4.32	66.76	16.05		150.0	
		Z	4.36	66.96	16.22		150.0	
10524- AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 99pc duty cycle)	X	4.22	67.47	16.68	0.00	150.0	± 9.6 %
		Y	4.36	66.76	16.14		150.0	
		Z	4.40	66.96	16.31		150.0	
10525- AAA	IEEE 802.11ac WiFi (20MHz, MCS0, 99pc duty cycle)	X	4.29	66.64	16.33	0.00	150.0	± 9.6 %
		Y	4.38	65.85	15.76		150.0	
		Z	4.42	66.05	15.92		150.0	
10526- AAA	IEEE 802.11ac WiFi (20MHz, MCS1, 99pc duty cycle)	X	4.38	66.84	16.42	0.00	150.0	± 9.6 %
		Y	4.51	66.14	15.88		150.0	
		Z	4.55	66.36	16.04		150.0	
10527- AAA	IEEE 802.11ac WiFi (20MHz, MCS2, 99pc duty cycle)	X	4.32	66.85	16.37	0.00	150.0	± 9.6 %
		Y	4.44	66.10	15.81		150.0	
		Z	4.48	66.32	15.98		150.0	
10528- AAA	IEEE 802.11ac WiFi (20MHz, MCS3, 99pc duty cycle)	X	4.33	66.85	16.39	0.00	150.0	± 9.6 %
		Y	4.45	66.12	15.84		150.0	
		Z	4.50	66.34	16.02		150.0	
10529- AAA	IEEE 802.11ac WiFi (20MHz, MCS4, 99pc duty cycle)	X	4.33	66.85	16.39	0.00	150.0	± 9.6 %
		Y	4.45	66.12	15.84		150.0	
		Z	4.50	66.34	16.02		150.0	
10531- AAA	IEEE 802.11ac WiFi (20MHz, MCS6, 99pc duty cycle)	X	4.28	66.82	16.35	0.00	150.0	± 9.6 %
		Y	4.42	66.15	15.83		150.0	
		Z	4.47	66.39	16.01		150.0	
10532- AAA	IEEE 802.11ac WiFi (20MHz, MCS7, 99pc duty cycle)	X	4.18	66.70	16.29	0.00	150.0	± 9.6 %
		Y	4.30	66.01	15.76		150.0	
		Z	4.34	66.25	15.94		150.0	
10533- AAA	IEEE 802.11ac WiFi (20MHz, MCS8, 99pc duty cycle)	X	4.33	66.96	16.41	0.00	150.0	± 9.6 %
		Y	4.46	66.19	15.85		150.0	
		Z	4.50	66.41	16.02		150.0	
10534- AAA	IEEE 802.11ac WiFi (40MHz, MCS0, 99pc duty cycle)	X	4.91	66.64	16.43	0.00	150.0	± 9.6 %
		Y	5.02	66.21	15.95		150.0	
		Z	5.05	66.39	16.08		150.0	
10535- AAA	IEEE 802.11ac WiFi (40MHz, MCS1, 99pc duty cycle)	X	4.94	66.76	16.49	0.00	150.0	± 9.6 %
		Y	5.07	66.36	16.02		150.0	
		Z	5.11	66.55	16.16		150.0	
10536- AAA	IEEE 802.11ac WiFi (40MHz, MCS2, 99pc duty cycle)	X	4.84	66.75	16.46	0.00	150.0	± 9.6 %
		Y	4.95	66.33	15.99		150.0	
		Z	4.99	66.53	16.13		150.0	
10537- AAA	IEEE 802.11ac WiFi (40MHz, MCS3, 99pc duty cycle)	X	4.93	66.86	16.53	0.00	150.0	± 9.6 %
		Y	5.01	66.31	15.98		150.0	
		Z	5.04	66.49	16.11		150.0	
10538- AAA	IEEE 802.11ac WiFi (40MHz, MCS4, 99pc duty cycle)	X	4.95	66.67	16.46	0.00	150.0	± 9.6 %
		Y	5.08	66.30	16.01		150.0	
		Z	5.12	66.48	16.15		150.0	
10540- AAA	IEEE 802.11ac WiFi (40MHz, MCS6, 99pc duty cycle)	X	4.89	66.64	16.47	0.00	150.0	± 9.6 %
		Y	5.01	66.27	16.01		150.0	
		Z	5.05	66.45	16.15		150.0	

10541- AAA	IEEE 802.11ac WiFi (40MHz, MCS7, 99pc duty cycle)	X	4.89	66.61	16.43	0.00	150.0	± 9.6 %
		Y	4.99	66.16	15.94		150.0	
		Z	5.03	66.35	16.08		150.0	
10542- AAA	IEEE 802.11ac WiFi (40MHz, MCS8, 99pc duty cycle)	X	5.03	66.67	16.48	0.00	150.0	± 9.6 %
		Y	5.15	66.28	16.02		150.0	
		Z	5.19	66.45	16.15		150.0	
10543- AAA	IEEE 802.11ac WiFi (40MHz, MCS9, 99pc duty cycle)	X	5.10	66.78	16.56	0.00	150.0	± 9.6 %
		Y	5.22	66.32	16.07		150.0	
		Z	5.25	66.47	16.19		150.0	
10544- AAA	IEEE 802.11ac WiFi (80MHz, MCS0, 99pc duty cycle)	X	5.29	66.62	16.39	0.00	150.0	± 9.6 %
		Y	5.36	66.31	15.95		150.0	
		Z	5.39	66.48	16.08		150.0	
10545- AAA	IEEE 802.11ac WiFi (80MHz, MCS1, 99pc duty cycle)	X	5.47	67.16	16.63	0.00	150.0	± 9.6 %
		Y	5.54	66.76	16.14		150.0	
		Z	5.57	66.92	16.26		150.0	
10546- AAA	IEEE 802.11ac WiFi (80MHz, MCS2, 99pc duty cycle)	X	5.31	66.72	16.42	0.00	150.0	± 9.6 %
		Y	5.39	66.44	15.99		150.0	
		Z	5.42	66.62	16.12		150.0	
10547- AAA	IEEE 802.11ac WiFi (80MHz, MCS3, 99pc duty cycle)	X	5.48	67.16	16.64	0.00	150.0	± 9.6 %
		Y	5.47	66.54	16.03		150.0	
		Z	5.50	66.70	16.15		150.0	
10548- AAA	IEEE 802.11ac WiFi (80MHz, MCS4, 99pc duty cycle)	X	5.49	67.36	16.72	0.00	150.0	± 9.6 %
		Y	5.65	67.27	16.37		150.0	
		Z	5.69	67.45	16.51		150.0	
10550- AAA	IEEE 802.11ac WiFi (80MHz, MCS6, 99pc duty cycle)	X	5.47	67.30	16.73	0.00	150.0	± 9.6 %
		Y	5.45	66.61	16.09		150.0	
		Z	5.48	66.76	16.20		150.0	
10551- AAA	IEEE 802.11ac WiFi (80MHz, MCS7, 99pc duty cycle)	X	5.28	66.65	16.36	0.00	150.0	± 9.6 %
		Y	5.40	66.45	15.97		150.0	
		Z	5.44	66.64	16.10		150.0	
10552- AAA	IEEE 802.11ac WiFi (80MHz, MCS8, 99pc duty cycle)	X	5.29	66.77	16.42	0.00	150.0	± 9.6 %
		Y	5.36	66.40	15.95		150.0	
		Z	5.39	66.57	16.07		150.0	
10553- AAA	IEEE 802.11ac WiFi (80MHz, MCS9, 99pc duty cycle)	X	5.33	66.67	16.39	0.00	150.0	± 9.6 %
		Y	5.42	66.38	15.97		150.0	
		Z	5.46	66.55	16.09		150.0	
10554- AAA	IEEE 1602.11ac WiFi (160MHz, MCS0, 99pc duty cycle)	X	5.74	66.93	16.46	0.00	150.0	± 9.6 %
		Y	5.78	66.67	16.05		150.0	
		Z	5.80	66.82	16.16		150.0	
10555- AAA	IEEE 1602.11ac WiFi (160MHz, MCS1, 99pc duty cycle)	X	5.82	67.13	16.55	0.00	150.0	± 9.6 %
		Y	5.88	66.93	16.16		150.0	
		Z	5.91	67.09	16.28		150.0	
10556- AAA	IEEE 1602.11ac WiFi (160MHz, MCS2, 99pc duty cycle)	X	5.89	67.36	16.66	0.00	150.0	± 9.6 %
		Y	5.92	67.02	16.20		150.0	
		Z	5.94	67.17	16.31		150.0	
10557- AAA	IEEE 1602.11ac WiFi (160MHz, MCS3, 99pc duty cycle)	X	5.80	67.09	16.54	0.00	150.0	± 9.6 %
		Y	5.87	66.88	16.15		150.0	
		Z	5.90	67.04	16.26		150.0	

10558-AAA	IEEE 1602.11ac WiFi (160MHz, MCS4, 99pc duty cycle)	X	5.77	67.03	16.53	0.00	150.0	± 9.6 %
		Y	5.90	66.99	16.22		150.0	
		Z	5.93	67.17	16.34		150.0	
10560-AAA	IEEE 1602.11ac WiFi (160MHz, MCS6, 99pc duty cycle)	X	5.81	67.01	16.55	0.00	150.0	± 9.6 %
		Y	5.90	66.88	16.20		150.0	
		Z	5.93	67.04	16.32		150.0	
10561-AAA	IEEE 1602.11ac WiFi (160MHz, MCS7, 99pc duty cycle)	X	5.75	67.01	16.58	0.00	150.0	± 9.6 %
		Y	5.84	66.87	16.23		150.0	
		Z	5.87	67.03	16.35		150.0	
10562-AAA	IEEE 1602.11ac WiFi (160MHz, MCS8, 99pc duty cycle)	X	5.79	67.14	16.64	0.00	150.0	± 9.6 %
		Y	5.90	67.07	16.33		150.0	
		Z	5.94	67.26	16.46		150.0	
10563-AAA	IEEE 1602.11ac WiFi (160MHz, MCS9, 99pc duty cycle)	X	5.94	67.31	16.70	0.00	150.0	± 9.6 %
		Y	5.99	67.01	16.27		150.0	
		Z	6.02	67.17	16.38		150.0	
10564-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 99pc duty cycle)	X	4.61	67.32	16.73	0.46	150.0	± 9.6 %
		Y	4.74	66.67	16.25		150.0	
		Z	4.77	66.85	16.39		150.0	
10565-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 99pc duty cycle)	X	4.78	67.70	17.03	0.46	150.0	± 9.6 %
		Y	4.94	67.09	16.56		150.0	
		Z	4.97	67.25	16.70		150.0	
10566-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 99pc duty cycle)	X	4.63	67.51	16.84	0.46	150.0	± 9.6 %
		Y	4.77	66.90	16.36		150.0	
		Z	4.81	67.09	16.51		150.0	
10567-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 99pc duty cycle)	X	4.67	67.89	17.21	0.46	150.0	± 9.6 %
		Y	4.81	67.30	16.74		150.0	
		Z	4.84	67.45	16.86		150.0	
10568-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 99pc duty cycle)	X	4.49	67.11	16.50	0.46	150.0	± 9.6 %
		Y	4.67	66.65	16.11		150.0	
		Z	4.72	66.88	16.29		150.0	
10569-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 99pc duty cycle)	X	4.67	68.23	17.42	0.46	150.0	± 9.6 %
		Y	4.78	67.49	16.85		150.0	
		Z	4.81	67.62	16.96		150.0	
10570-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 99pc duty cycle)	X	4.64	67.91	17.25	0.46	150.0	± 9.6 %
		Y	4.80	67.29	16.75		150.0	
		Z	4.83	67.45	16.88		150.0	
10571-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 90pc duty cycle)	X	1.22	65.52	16.64	0.46	130.0	± 9.6 %
		Y	1.12	63.42	14.91		130.0	
		Z	1.16	64.20	15.50		130.0	
10572-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 90pc duty cycle)	X	1.23	66.17	17.06	0.46	130.0	± 9.6 %
		Y	1.13	63.89	15.22		130.0	
		Z	1.17	64.72	15.84		130.0	
10573-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 90pc duty cycle)	X	4.75	105.03	31.49	0.46	130.0	± 9.6 %
		Y	1.00	73.95	18.94		130.0	
		Z	1.62	82.63	22.62		130.0	
10574-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 90pc duty cycle)	X	1.39	73.10	20.78	0.46	130.0	± 9.6 %
		Y	1.13	68.05	17.48		130.0	
		Z	1.23	69.81	18.53		130.0	

10575-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 90pc duty cycle)	X	4.39	67.09	16.74	0.46	130.0	± 9.6 %
		Y	4.52	66.46	16.29		130.0	
		Z	4.55	66.62	16.42		130.0	
10576-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 90pc duty cycle)	X	4.43	67.35	16.87	0.46	130.0	± 9.6 %
		Y	4.55	66.65	16.37		130.0	
		Z	4.58	66.80	16.49		130.0	
10577-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 90pc duty cycle)	X	4.57	67.55	16.99	0.46	130.0	± 9.6 %
		Y	4.72	66.90	16.53		130.0	
		Z	4.75	67.05	16.65		130.0	
10578-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 90pc duty cycle)	X	4.48	67.69	17.11	0.46	130.0	± 9.6 %
		Y	4.62	67.04	16.63		130.0	
		Z	4.65	67.17	16.74		130.0	
10579-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 90pc duty cycle)	X	4.22	66.80	16.32	0.46	130.0	± 9.6 %
		Y	4.38	66.24	15.88		130.0	
		Z	4.41	66.45	16.05		130.0	
10580-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 90pc duty cycle)	X	4.23	66.76	16.28	0.46	130.0	± 9.6 %
		Y	4.42	66.30	15.91		130.0	
		Z	4.46	66.52	16.09		130.0	
10581-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 90pc duty cycle)	X	4.41	67.88	17.16	0.46	130.0	± 9.6 %
		Y	4.52	67.09	16.59		130.0	
		Z	4.55	67.24	16.70		130.0	
10582-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 90pc duty cycle)	X	4.14	66.58	16.11	0.46	130.0	± 9.6 %
		Y	4.31	66.00	15.66		130.0	
		Z	4.35	66.24	15.85		130.0	
10583-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 90pc duty cycle)	X	4.39	67.09	16.74	0.46	130.0	± 9.6 %
		Y	4.52	66.46	16.29		130.0	
		Z	4.55	66.62	16.42		130.0	
10584-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 90pc duty cycle)	X	4.43	67.35	16.87	0.46	130.0	± 9.6 %
		Y	4.55	66.65	16.37		130.0	
		Z	4.58	66.80	16.49		130.0	
10585-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 90pc duty cycle)	X	4.57	67.55	16.99	0.46	130.0	± 9.6 %
		Y	4.72	66.90	16.53		130.0	
		Z	4.75	67.05	16.65		130.0	
10586-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 90pc duty cycle)	X	4.48	67.69	17.11	0.46	130.0	± 9.6 %
		Y	4.62	67.04	16.63		130.0	
		Z	4.65	67.17	16.74		130.0	
10587-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 90pc duty cycle)	X	4.22	66.80	16.32	0.46	130.0	± 9.6 %
		Y	4.38	66.24	15.88		130.0	
		Z	4.41	66.45	16.05		130.0	
10588-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 90pc duty cycle)	X	4.23	66.76	16.28	0.46	130.0	± 9.6 %
		Y	4.42	66.30	15.91		130.0	
		Z	4.46	66.52	16.09		130.0	
10589-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 90pc duty cycle)	X	4.41	67.88	17.16	0.46	130.0	± 9.6 %
		Y	4.52	67.09	16.59		130.0	
		Z	4.55	67.24	16.70		130.0	
10590-AAA	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 90pc duty cycle)	X	4.14	66.58	16.11	0.46	130.0	± 9.6 %
		Y	4.31	66.00	15.66		130.0	
		Z	4.35	66.24	15.85		130.0	

10591- AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS0, 90pc duty cycle)	X	4.55	67.20	16.89	0.46	130.0	± 9.6 %
		Y	4.68	66.55	16.41		130.0	
		Z	4.70	66.69	16.53		130.0	
10592- AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS1, 90pc duty cycle)	X	4.64	67.43	16.99	0.46	130.0	± 9.6 %
		Y	4.80	66.85	16.54		130.0	
		Z	4.83	66.99	16.66		130.0	
10593- AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS2, 90pc duty cycle)	X	4.57	67.33	16.86	0.46	130.0	± 9.6 %
		Y	4.72	66.73	16.40		130.0	
		Z	4.75	66.88	16.53		130.0	
10594- AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS3, 90pc duty cycle)	X	4.62	67.49	17.02	0.46	130.0	± 9.6 %
		Y	4.78	66.90	16.57		130.0	
		Z	4.81	67.05	16.68		130.0	
10595- AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS4, 90pc duty cycle)	X	4.58	67.50	16.95	0.46	130.0	± 9.6 %
		Y	4.74	66.87	16.47		130.0	
		Z	4.77	67.02	16.59		130.0	
10596- AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS5, 90pc duty cycle)	X	4.51	67.41	16.92	0.46	130.0	± 9.6 %
		Y	4.67	66.84	16.46		130.0	
		Z	4.71	67.00	16.59		130.0	
10597- AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS6, 90pc duty cycle)	X	4.47	67.28	16.76	0.46	130.0	± 9.6 %
		Y	4.62	66.71	16.32		130.0	
		Z	4.66	66.88	16.45		130.0	
10598- AAA	IEEE 802.11n (HT Mixed, 20MHz, MCS7, 90pc duty cycle)	X	4.48	67.55	17.05	0.46	130.0	± 9.6 %
		Y	4.61	66.94	16.58		130.0	
		Z	4.64	67.09	16.70		130.0	
10599- AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS0, 90pc duty cycle)	X	5.42	68.12	17.46	0.46	130.0	± 9.6 %
		Y	5.36	67.07	16.68		130.0	
		Z	5.38	67.17	16.76		130.0	
10600- AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS1, 90pc duty cycle)	X	5.38	68.02	17.38	0.46	130.0	± 9.6 %
		Y	5.48	67.47	16.85		130.0	
		Z	5.50	67.58	16.94		130.0	
10601- AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS2, 90pc duty cycle)	X	5.31	67.88	17.33	0.46	130.0	± 9.6 %
		Y	5.37	67.22	16.74		130.0	
		Z	5.39	67.34	16.84		130.0	
10602- AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS3, 90pc duty cycle)	X	5.35	67.75	17.19	0.46	130.0	± 9.6 %
		Y	5.51	67.40	16.75		130.0	
		Z	5.53	67.53	16.86		130.0	
10603- AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS4, 90pc duty cycle)	X	5.34	67.77	17.33	0.46	130.0	± 9.6 %
		Y	5.59	67.72	17.05		130.0	
		Z	5.60	67.82	17.13		130.0	
10604- AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS5, 90pc duty cycle)	X	5.26	67.45	17.14	0.46	130.0	± 9.6 %
		Y	5.46	67.35	16.84		130.0	
		Z	5.48	67.46	16.93		130.0	
10605- AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS6, 90pc duty cycle)	X	5.31	67.63	17.24	0.46	130.0	± 9.6 %
		Y	5.47	67.37	16.85		130.0	
		Z	5.50	67.50	16.96		130.0	
10606- AAA	IEEE 802.11n (HT Mixed, 40MHz, MCS7, 90pc duty cycle)	X	5.23	67.57	17.07	0.46	130.0	± 9.6 %
		Y	5.23	66.72	16.38		130.0	
		Z	5.25	66.84	16.48		130.0	

10607- AAA	IEEE 802.11ac WiFi (20MHz, MCS0, 90pc duty cycle)	X	4.42	66.61	16.57	0.46	130.0	± 9.6 %
		Y	4.52	65.87	16.04		130.0	
		Z	4.55	66.03	16.17		130.0	
10608- AAA	IEEE 802.11ac WiFi (20MHz, MCS1, 90pc duty cycle)	X	4.52	66.86	16.69	0.46	130.0	± 9.6 %
		Y	4.67	66.22	16.20		130.0	
		Z	4.70	66.38	16.32		130.0	
10609- AAA	IEEE 802.11ac WiFi (20MHz, MCS2, 90pc duty cycle)	X	4.43	66.72	16.52	0.46	130.0	± 9.6 %
		Y	4.56	66.05	16.02		130.0	
		Z	4.60	66.23	16.15		130.0	
10610- AAA	IEEE 802.11ac WiFi (20MHz, MCS3, 90pc duty cycle)	X	4.48	66.89	16.69	0.46	130.0	± 9.6 %
		Y	4.61	66.21	16.19		130.0	
		Z	4.65	66.38	16.31		130.0	
10611- AAA	IEEE 802.11ac WiFi (20MHz, MCS4, 90pc duty cycle)	X	4.39	66.66	16.53	0.46	130.0	± 9.6 %
		Y	4.53	66.01	16.03		130.0	
		Z	4.56	66.19	16.16		130.0	
10612- AAA	IEEE 802.11ac WiFi (20MHz, MCS5, 90pc duty cycle)	X	4.36	66.74	16.55	0.46	130.0	± 9.6 %
		Y	4.52	66.14	16.06		130.0	
		Z	4.56	66.34	16.21		130.0	
10613- AAA	IEEE 802.11ac WiFi (20MHz, MCS6, 90pc duty cycle)	X	4.36	66.55	16.38	0.46	130.0	± 9.6 %
		Y	4.51	65.97	15.92		130.0	
		Z	4.56	66.17	16.07		130.0	
10614- AAA	IEEE 802.11ac WiFi (20MHz, MCS7, 90pc duty cycle)	X	4.35	66.81	16.65	0.46	130.0	± 9.6 %
		Y	4.48	66.19	16.17		130.0	
		Z	4.51	66.36	16.30		130.0	
10615- AAA	IEEE 802.11ac WiFi (20MHz, MCS8, 90pc duty cycle)	X	4.38	66.53	16.30	0.46	130.0	± 9.6 %
		Y	4.52	65.85	15.80		130.0	
		Z	4.56	66.05	15.95		130.0	
10616- AAA	IEEE 802.11ac WiFi (40MHz, MCS0, 90pc duty cycle)	X	5.06	66.67	16.71	0.46	130.0	± 9.6 %
		Y	5.17	66.26	16.25		130.0	
		Z	5.19	66.40	16.35		130.0	
10617- AAA	IEEE 802.11ac WiFi (40MHz, MCS1, 90pc duty cycle)	X	5.09	66.78	16.75	0.46	130.0	± 9.6 %
		Y	5.23	66.44	16.32		130.0	
		Z	5.26	66.59	16.43		130.0	
10618- AAA	IEEE 802.11ac WiFi (40MHz, MCS2, 90pc duty cycle)	X	5.00	66.82	16.79	0.46	130.0	± 9.6 %
		Y	5.13	66.48	16.35		130.0	
		Z	5.16	66.62	16.46		130.0	
10619- AAA	IEEE 802.11ac WiFi (40MHz, MCS3, 90pc duty cycle)	X	5.07	66.85	16.74	0.46	130.0	± 9.6 %
		Y	5.14	66.27	16.18		130.0	
		Z	5.17	66.41	16.29		130.0	
10620- AAA	IEEE 802.11ac WiFi (40MHz, MCS4, 90pc duty cycle)	X	5.07	66.60	16.65	0.46	130.0	± 9.6 %
		Y	5.22	66.29	16.24		130.0	
		Z	5.24	66.43	16.35		130.0	
10621- AAA	IEEE 802.11ac WiFi (40MHz, MCS5, 90pc duty cycle)	X	5.09	66.73	16.83	0.46	130.0	± 9.6 %
		Y	5.23	66.42	16.43		130.0	
		Z	5.25	66.54	16.52		130.0	
10622- AAA	IEEE 802.11ac WiFi (40MHz, MCS6, 90pc duty cycle)	X	5.08	66.82	16.88	0.46	130.0	± 9.6 %
		Y	5.22	66.53	16.48		130.0	
		Z	5.25	66.66	16.57		130.0	

10623- AAA	IEEE 802.11ac WiFi (40MHz, MCS7, 90pc duty cycle)	X	5.00	66.49	16.57	0.46	130.0	± 9.6 %
		Y	5.10	66.05	16.10		130.0	
		Z	5.13	66.21	16.22		130.0	
10624- AAA	IEEE 802.11ac WiFi (40MHz, MCS8, 90pc duty cycle)	X	5.17	66.67	16.72	0.46	130.0	± 9.6 %
		Y	5.30	66.31	16.30		130.0	
		Z	5.33	66.45	16.40		130.0	
10625- AAA	IEEE 802.11ac WiFi (40MHz, MCS9, 90pc duty cycle)	X	5.28	66.93	16.92	0.46	130.0	± 9.6 %
		Y	5.45	66.64	16.52		130.0	
		Z	5.51	66.86	16.67		130.0	
10626- AAA	IEEE 802.11ac WiFi (80MHz, MCS0, 90pc duty cycle)	X	5.42	66.61	16.64	0.46	130.0	± 9.6 %
		Y	5.50	66.32	16.23		130.0	
		Z	5.52	66.45	16.32		130.0	
10627- AAA	IEEE 802.11ac WiFi (80MHz, MCS1, 90pc duty cycle)	X	5.65	67.30	16.97	0.46	130.0	± 9.6 %
		Y	5.74	66.96	16.51		130.0	
		Z	5.75	67.06	16.59		130.0	
10628- AAA	IEEE 802.11ac WiFi (80MHz, MCS2, 90pc duty cycle)	X	5.41	66.58	16.53	0.46	130.0	± 9.6 %
		Y	5.50	66.32	16.12		130.0	
		Z	5.52	66.47	16.23		130.0	
10629- AAA	IEEE 802.11ac WiFi (80MHz, MCS3, 90pc duty cycle)	X	5.65	67.25	16.88	0.46	130.0	± 9.6 %
		Y	5.59	66.47	16.20		130.0	
		Z	5.61	66.60	16.29		130.0	
10630- AAA	IEEE 802.11ac WiFi (80MHz, MCS4, 90pc duty cycle)	X	5.66	67.48	17.00	0.46	130.0	± 9.6 %
		Y	5.90	67.58	16.75		130.0	
		Z	5.92	67.75	16.87		130.0	
10631- AAA	IEEE 802.11ac WiFi (80MHz, MCS5, 90pc duty cycle)	X	5.66	67.57	17.22	0.46	130.0	± 9.6 %
		Y	5.84	67.51	16.91		130.0	
		Z	5.86	67.63	16.99		130.0	
10632- AAA	IEEE 802.11ac WiFi (80MHz, MCS6, 90pc duty cycle)	X	5.78	67.90	17.40	0.46	130.0	± 9.6 %
		Y	5.73	67.08	16.72		130.0	
		Z	5.73	67.16	16.77		130.0	
10633- AAA	IEEE 802.11ac WiFi (80MHz, MCS7, 90pc duty cycle)	X	5.42	66.64	16.60	0.46	130.0	± 9.6 %
		Y	5.56	66.51	16.25		130.0	
		Z	5.59	66.67	16.36		130.0	
10634- AAA	IEEE 802.11ac WiFi (80MHz, MCS8, 90pc duty cycle)	X	5.46	66.87	16.76	0.46	130.0	± 9.6 %
		Y	5.55	66.56	16.34		130.0	
		Z	5.57	66.69	16.42		130.0	
10635- AAA	IEEE 802.11ac WiFi (80MHz, MCS9, 90pc duty cycle)	X	5.30	66.09	16.10	0.46	130.0	± 9.6 %
		Y	5.42	65.84	15.70		130.0	
		Z	5.45	66.02	15.83		130.0	
10636- AAA	IEEE 1602.11ac WiFi (160MHz, MCS0, 90pc duty cycle)	X	5.89	66.94	16.72	0.46	130.0	± 9.6 %
		Y	5.93	66.70	16.32		130.0	
		Z	5.95	66.82	16.41		130.0	
10637- AAA	IEEE 1602.11ac WiFi (160MHz, MCS1, 90pc duty cycle)	X	6.00	67.26	16.88	0.46	130.0	± 9.6 %
		Y	6.07	67.05	16.49		130.0	
		Z	6.09	67.17	16.57		130.0	
10638- AAA	IEEE 1602.11ac WiFi (160MHz, MCS2, 90pc duty cycle)	X	6.08	67.49	16.97	0.46	130.0	± 9.6 %
		Y	6.08	67.05	16.46		130.0	
		Z	6.09	67.17	16.55		130.0	

10639- AAA	IEEE 1602.11ac WiFi (160MHz, MCS3, 90pc duty cycle)	X	5.96	67.14	16.83	0.46	130.0	± 9.6 %
		Y	6.04	66.95	16.46		130.0	
		Z	6.06	67.08	16.54		130.0	
10640- AAA	IEEE 1602.11ac WiFi (160MHz, MCS4, 90pc duty cycle)	X	5.88	66.91	16.66	0.46	130.0	± 9.6 %
		Y	6.02	66.91	16.38		130.0	
		Z	6.05	67.07	16.49		130.0	
10641- AAA	IEEE 1602.11ac WiFi (160MHz, MCS5, 90pc duty cycle)	X	6.03	67.18	16.82	0.46	130.0	± 9.6 %
		Y	6.11	66.94	16.42		130.0	
		Z	6.12	67.07	16.51		130.0	
10642- AAA	IEEE 1602.11ac WiFi (160MHz, MCS6, 90pc duty cycle)	X	6.01	67.21	16.99	0.46	130.0	± 9.6 %
		Y	6.13	67.13	16.68		130.0	
		Z	6.14	67.25	16.76		130.0	
10643- AAA	IEEE 1602.11ac WiFi (160MHz, MCS7, 90pc duty cycle)	X	5.86	66.92	16.74	0.46	130.0	± 9.6 %
		Y	5.97	66.84	16.42		130.0	
		Z	6.00	66.98	16.52		130.0	
10644- AAA	IEEE 1602.11ac WiFi (160MHz, MCS8, 90pc duty cycle)	X	5.92	67.09	16.84	0.46	130.0	± 9.6 %
		Y	6.05	67.07	16.56		130.0	
		Z	6.08	67.24	16.67		130.0	
10645- AAA	IEEE 1602.11ac WiFi (160MHz, MCS9, 90pc duty cycle)	X	6.05	67.20	16.87	0.46	130.0	± 9.6 %
		Y	6.21	67.21	16.60		130.0	
		Z	6.22	67.32	16.68		130.0	
10646- AAC	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,7)	X	5.41	90.03	34.30	9.30	60.0	± 9.6 %
		Y	7.98	94.06	33.27		60.0	
		Z	13.74	108.15	38.22		60.0	
10647- AAB	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,7)	X	4.80	87.06	33.21	9.30	60.0	± 9.6 %
		Y	7.05	91.55	32.48		60.0	
		Z	11.43	104.24	37.10		60.0	
10648- AAA	CDMA2000 (1x Advanced)	X	0.46	61.72	7.76	0.00	150.0	± 9.6 %
		Y	0.57	61.92	9.05		150.0	
		Z	0.62	62.86	9.86		150.0	

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

APPENDIX D: SAR TISSUE SPECIFICATIONS

Measurement Procedure for Tissue verification:

- 1) The network analyzer and probe system were configured and calibrated.
- 2) The probe was immersed in the tissue. The tissue was placed in a nonmetallic container. Trapped air bubbles beneath the flange were minimized by placing the probe at a slight angle.
- 3) The complex admittance with respect to the probe aperture was measured
- 4) The complex relative permittivity ϵ' can be calculated from the below equation (Pournaropoulos and Misra):

$$Y = \frac{j2\omega\epsilon_r\epsilon_0}{[\ln(b/a)]^2} \int_a^b \int_a^b \int_0^\pi \cos\phi' \frac{\exp[-j\omega r(\mu_0\epsilon_r\epsilon_0)^{1/2}]}{r} d\phi' d\rho' d\rho$$

where Y is the admittance of the probe in contact with the sample, the primed and unprimed coordinates refer to source and observation points, respectively, $r^2 = \rho^2 + \rho'^2 - 2\rho\rho' \cos\phi'$, ω is the angular frequency, and $j = \sqrt{-1}$.

Table D-I
Composition of the Tissue Equivalent Matter

Frequency (MHz)	2450	5200-5800
Tissue	Body	Body
DGBE	26.7	
NaCl	0.1	
Polysorbate (Tween) 80		20
Water	73.2	80

FCC ID: BCGA1893



SAR EVALUATION REPORT

Approved by:
Quality Manager

Test Dates:

01/10/18 - 01/18/18

DUT Type:

Tablet Device

APPENDIX D:
Page 1 of 1

APPENDIX E: SAR SYSTEM VALIDATION

Per FCC KDB Publication 865664 D02v01r02, SAR system validation status should be documented to confirm measurement accuracy. The SAR systems (including SAR probes, system components and software versions) used for this device were validated against its performance specifications prior to the SAR measurements. Reference dipoles were used with the required tissue- equivalent media for system validation, according to the procedures outlined in FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013. Since SAR probe calibrations are frequency dependent, each probe calibration point was validated at a frequency within the valid frequency range of the probe calibration point, using the system that normally operates with the probe for routine SAR measurements and according to the required tissue-equivalent media.

A tabulated summary of the system validation status including the validation date(s), measurement frequencies, SAR probes and tissue dielectric parameters has been included.

Table E-1
SAR System Validation Summary – 1g

SAR SYSTEM #	FREQ. [MHz]	DATE	PROBE SN	PROBE TYPE	PROBE CAL. POINT		COND. (σ)	PERM. (ϵ_r)	CW VALIDATION			MOD. VALIDATION		
									SENSITIVITY	PROBE LINEARITY	PROBE ISOTROPY	MOD. TYPE	DUTY FACTOR	PAR
CAL3	2450	12/22/2017	3333	ES3DV3	2450	Body	2.027	50.985	PASS	PASS	PASS	OFDM/TDD	PASS	PASS
CAL4	5250	12/29/2017	7416	EX3DV4	5250	Body	5.459	49.040	PASS	PASS	PASS	OFDM	N/A	PASS
CAL4	5600	12/27/2017	7416	EX3DV4	5600	Body	5.942	48.440	PASS	PASS	PASS	OFDM	N/A	PASS
CAL4	5750	12/30/2017	7416	EX3DV4	5750	Body	6.153	48.178	PASS	PASS	PASS	OFDM	N/A	PASS

NOTE: While the probes have been calibrated for both CW and modulated signals, all measurements were performed using communication systems calibrated for CW signals only. Modulations in the table above represent test configurations for which the measurement system has been validated per FCC KDB Publication 865664 D01v01r04 for scenarios when CW probe calibrations are used with other signal types. SAR systems were validated for modulated signals with a periodic duty cycle, such as GMSK, or with a high peak to average ratio (>5 dB), such as OFDM according to FCC KDB Publication 865664 D01v01r04.

FCC ID: BCGA1893	 PCTEST Engineering Laboratory, Inc.	SAR EVALUATION REPORT	Approved by: Quality Manager
Test Dates: 01/10/18 - 01/18/18	DUT Type: Tablet Device		APPENDIX E: Page 1 of 1