



Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5320MHz
 Channel: 64



Plot 7-239. Radiated Upper Band Edge Plot SISO CORE 1 (UNII Band 2A)


Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5500MHz
 Channel: 100



Plot 7-240. Radiated Lower Band Edge Plot SISO CORE 1 (UNII Band 2C)


FCC ID: BCGA2270	PCTEST® Proud to be part of 			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device	Page 176 of 211		

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5520MHz
 Channel: 104



Plot 7-241. Radiated Lower Band Edge Plot SISO CORE 1 (UNII Band 2C)


Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5680MHz
 Channel: 136



Plot 7-242. Radiated Upper Band Edge Plot SISO CORE 1 (Peak – UNII Band 2C)


FCC ID: BCGA2270	PCTEST Proud to be part of 			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device			

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5700MHz
 Channel: 140



Plot 7-243. Radiated Upper Band Edge Plot SISO CORE 1 (Peak – UNII Band 2C)


Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5745MHz
 Channel: 149



Plot 7-244. Radiated Lower Band Edge Plot SISO CORE 1 (Peak – UNII Band 3)

FCC ID: BCGA2270	PCTEST® Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device	Page 178 of 211	

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5825MHz
 Channel: 165




Plot 7-245. Radiated Upper Band Edge Plot SISO CORE 1 (Peak – UNII Band 3)

FCC ID: BCGA2270	PCTEST® Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device	Page 179 of 211	

7.6.9 SISO Core-1 Radiated Band Edge Measurements (40MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]


Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5190MHz
 Channel: 38



Plot 7-246. Radiated Lower Band Edge Plot SISO CORE 1 (UNII Band 1)


FCC ID: BCGA2270	PCTEST Proud to be part of  element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device	Page 180 of 211	

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5230MHz
 Channel: 46



Plot 7-247. Radiated Lower Band Edge Plot SISO CORE 1 (UNII Band 1)


Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5270MHz
 Channel: 54



Plot 7-248. Radiated Upper Band Edge Plot SISO CORE 1 (UNII Band 2A)


FCC ID: BCGA2270	PCTEST Proud to be part of 			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device			

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5310MHz
 Channel: 62



Plot 7-249. Radiated Upper Band Edge Plot SISO CORE 1 (UNII Band 2A)


Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5510MHz
 Channel: 102



Plot 7-250. Radiated Lower Band Edge Plot SISO CORE 1 (UNII Band 2C)


FCC ID: BCGA2270	PCTEST Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device	Page 182 of 211	

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5550MHz
 Channel: 110



Plot 7-251. Radiated Lower Band Edge Plot SISO CORE 1 (UNII Band 2C)


Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5670MHz
 Channel: 134



Plot 7-252. Radiated Upper Band Edge Plot SISO CORE 1 (Peak - UNII Band 2C)


FCC ID: BCGA2270	PCTEST Proud to be part of 			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device			

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5755MHz
 Channel: 151



Plot 7-253. Radiated Lower Band Edge Plot SISO CORE 1 (Peak – UNII Band 3)

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5795MHz
 Channel: 159




Plot 7-254. Radiated Upper Band Edge Plot SISO CORE 1 (Peak – UNII Band 3)

FCC ID: BCGA2270	PCTEST Proud to be part of 			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device			

7.6.10 SISO Core-1 Radiated Band Edge Measurements (80MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]


Worst Case Mode: 802.11ac
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5210MHz
 Channel: 42



Plot 7-255. Radiated Lower Band Edge Plot SISO CORE 1 (UNII Band 1)


FCC ID: BCGA2270	PCTEST Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device	Page 185 of 211	

Worst Case Mode: 802.11ac
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5290MHz
 Channel: 58



Plot 7-256. Radiated Upper Band Edge Plot SISO CORE 1 (UNII Band 2A)


Worst Case Mode: 802.11ac
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5530MHz
 Channel: 106



Plot 7-257. Radiated Lower Band Edge Plot SISO CORE 1 (UNII Band 2C)


FCC ID: BCGA2270	PCTEST Proud to be part of 			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device			

Worst Case Mode: 802.11ac
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5775MHz
 Channel: 155



Plot 7-258. Radiated Lower Band Edge Plot SISO CORE 1 (Peak – UNII Band 3)

Worst Case Mode: 802.11ac
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5775MHz
 Channel: 155




Plot 7-259. Radiated Upper Band Edge Plot SISO CORE 1 (Peak – UNII Band 3)

FCC ID: BCGA2270	PCTEST Proud to be part of 			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device			

7.6.11 CDD/SDM Radiated Band Edge Measurements (20MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]


Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5180MHz
 Channel: 36



Plot 7-260. Radiated Lower Band Edge Plot CDD (UNII Band 1)


FCC ID: BCGA2270	PCTEST Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device	Page 188 of 211	

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5200MHz
 Channel: 40



Plot 7-261. Radiated Lower Band Edge Plot CDD (UNII Band 1)


Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC8
 Distance of Measurements: 3 Meters
 Operating Frequency: 5300MHz
 Channel: 60



Plot 7-262. Radiated Upper Band Edge Plot SDM (UNII Band 2A)


FCC ID: BCGA2270	PCTEST Proud to be part of 			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device			

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5320MHz
 Channel: 64



Plot 7-263. Radiated Upper Band Edge Plot CDD (UNII Band 2A)


Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5500MHz
 Channel: 100



Plot 7-264. Radiated Lower Band Edge Plot CDD (UNII Band 2C)


FCC ID: BCGA2270	PCTEST Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device	Page 190 of 211	

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC8
 Distance of Measurements: 3 Meters
 Operating Frequency: 5520MHz
 Channel: 104



Plot 7-265. Radiated Lower Band Edge Plot SDM (UNII Band 2C)


Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC8
 Distance of Measurements: 3 Meters
 Operating Frequency: 5580MHz
 Channel: 136



Plot 7-266. Radiated Upper Band Edge Plot SDM (Peak – UNII Band 2C)


FCC ID: BCGA2270	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device	Page 191 of 211	

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5700MHz
 Channel: 140



Plot 7-267. Radiated Upper Band Edge Plot CDD (Peak – UNII Band 2C)


Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5745MHz
 Channel: 149



Plot 7-268. Radiated Lower Band Edge Plot CDD (Peak – UNII Band 3)

FCC ID: BCGA2270	PCTEST® Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device	Page 192 of 211	

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5825MHz
 Channel: 165




Plot 7-269. Radiated Upper Band Edge Plot CDD (Peak – UNII Band 3)

FCC ID: BCGA2270	PCTEST® Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device	Page 193 of 211	

7.6.12 CDD/SDM Radiated Band Edge Measurements (40MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]


Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5190MHz
 Channel: 38



Plot 7-270. Radiated Lower Band Edge Plot CDD (UNII Band 1)


FCC ID: BCGA2270	PCTEST Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device	Page 194 of 211	

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5230MHz
 Channel: 46



Plot 7-271. Radiated Lower Band Edge Plot CDD (UNII Band 1)


Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5270MHz
 Channel: 54



Plot 7-272. Radiated Upper Band Edge Plot CDD (UNII Band 2A)


FCC ID: BCGA2270	PCTEST Proud to be part of 			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device			

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5310MHz
 Channel: 62




Plot 7-273. Radiated Upper Band Edge Plot CDD (UNII Band 2A)


Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5510MHz
 Channel: 102



Plot 7-274. Radiated Lower Band Edge Plot CDD (UNII Band 2C)


FCC ID: BCGA2270	PCTEST Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device	Page 196 of 211	

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5550MHz
 Channel: 110



Plot 7-275. Radiated Lower Band Edge Plot CDD (UNII Band 2C)


Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5670MHz
 Channel: 134



Plot 7-276. Radiated Upper Band Edge Plot CDD (Peak - UNII Band 2C)


FCC ID: BCGA2270	PCTEST Proud to be part of 			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device			

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5755MHz
 Channel: 151



Plot 7-277. Radiated Lower Band Edge Plot CDD (Peak – UNII Band 3)

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5795MHz
 Channel: 159




Plot 7-278. Radiated Upper Band Edge Plot CDD (Peak – UNII Band 3)

FCC ID: BCGA2270	PCTEST Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device	Page 198 of 211	

7.6.13 CDD/SDM Radiated Band Edge Measurements (80MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]


Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5210MHz
 Channel: 42



Plot 7-279. Radiated Lower Band Edge Plot CDD (UNII Band 1)


FCC ID: BCGA2270	PCTEST Proud to be part of 			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device	Page 199 of 211		

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5290MHz
 Channel: 58



Plot 7-280. Radiated Upper Band Edge Plot CDD (UNII Band 2A)


Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5530MHz
 Channel: 106



Plot 7-281. Radiated Lower Band Edge Plot CDD (UNII Band 2C)


FCC ID: BCGA2270	PCTEST Proud to be part of 			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device			

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5775MHz
 Channel: 155



Plot 7-282. Radiated Lower Band Edge Plot CDD (Peak – UNII Band 3)

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MSC0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5775MHz
 Channel: 155



Plot 7-283. Radiated Upper Band Edge Plot CDD (Peak – UNII Band 3)

FCC ID: BCGA2270	PCTEST Proud to be part of 			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device			

7.7 Radiated Spurious Emissions – Below 1GHz

§15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 7 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-74 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [μ V/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-74. Radiated Limits

Test Procedures Used

ANSI C63.10-2013

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. VBW = 30kHz
4. Detector = quasi-peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: BCGA2270	 PCTEST® Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device	Page 202 of 211	

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.




Figure 7-6. Radiated Test Setup < 30MHz




Figure 7-7. Radiated Test Setup < 1GHz

FCC ID: BCGA2270	PCTEST® Proud to be part of  element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device	Page 203 of 211	

Test Notes

1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen (8.10) are below the limit shown in Table 7-74.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes. For below 30MHz the loop antenna was positioned in 3 orthogonal planes (X front, Y side, Z top) to determine the orientation resulting in the worst case emissions.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector on emissions that were within 6dB of the limit. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. There were no emissions detected in the 30MHz – 1GHz frequency range, as shown in the subsequent plots.
10. Both configurations below were investigated, and the worst case has been reported.
 - a. EUT powered by AC/DC adaptor via USB-C cable with wire charger
 - b. EUT powered by host PC via USB-C cable with wire charger
11. All antenna configurations were investigated and only the worst case is reported.

Sample Calculations


Determining Spurious Emissions Levels

- Field Strength Level $[\text{dB}_{\mu\text{V/m}}]$ = Analyzer Level $[\text{dBm}]$ + 107 + AFCL $[\text{dB/m}]$
- AFCL $[\text{dB/m}]$ = Antenna Factor $[\text{dB/m}]$ + Cable Loss $[\text{dB}]$ – Preamplifier Gain $[\text{dB}]$
- Margin $[\text{dB}]$ = Field Strength Level $[\text{dB}_{\mu\text{V/m}}]$ – Limit $[\text{dB}_{\mu\text{V/m}}]$

FCC ID: BCGA2270	 PCTEST[®] Proud to be part of element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device	Page 204 of 211	

7.7.1 CDD/SDM Radiated Spurious Emissions Measurements (Below 1GHz)

§15.209; RSS-Gen [8.9]



Plot 7-284. Radiated Spurious Emissions below 1GHz CDD – Ch.36 with AC/DC Adapter

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turtable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
36.50	Max-Peak	V	100	17	-60.84	-21.16	25.00	40.00	-15.00
69.67	Max-Peak	V	250	215	-62.76	-26.49	17.75	40.00	-22.25
150.91	Max-Peak	V	100	8	-67.83	-22.38	16.79	43.52	-26.73
191.55	Max-Peak	V	100	12	-60.99	-22.91	23.10	43.52	-20.42
299.47	Max-Peak	H	100	128	-68.37	-19.01	19.62	46.02	-26.40
941.90	Max-Peak	V	100	30	-79.59	-5.17	22.24	46.02	-23.78


Table 7-75. Radiated Spurious Emissions below 1GHz CDD – Ch.36 with AC/DC Adapter

FCC ID: BCGA2270	PCTEST® Proud to be part of 			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device			

7.7.2 Simultaneous Tx Radiated Spurious Emissions Measurements (Below 1GHz) §15.209; RSS-Gen [8.9]

Description	Bluetooth	802.11a/n/ac 5GHz
Antenna	A	A
Channel	78	36
Operating Frequency (MHz)	2480	5180
Data Rate (Mbps)	1.0	MSC0
Mode	GFSK/ePA	802.11n

Table 7-76. Worst Case Simultaneous Transmission Configuration



Plot 7-285. Radiated Spurious Emissions below 1GHz (2.4GHz Ch.78 – 5GHz Ch.36), with AC/DC adapter

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
36.06	Max-Peak	V	100	352	-60.70	-20.93	25.37	40.00	-14.63
69.48	Max-Peak	H	250	22	-62.59	-26.50	17.91	40.00	-22.09
146.11	Max-Peak	V	100	256	-68.91	-23.96	14.13	43.52	-29.40
194.90	Max-Peak	H	100	236	-63.75	-22.89	20.36	43.52	-23.16
316.64	Max-Peak	H	100	273	-65.90	-18.65	22.45	46.02	-23.57
341.03	Max-Peak	H	100	277	-67.06	-17.38	22.56	46.02	-23.46
523.58	Max-Peak	V	250	17	-78.92	-11.40	16.68	46.02	-29.34

Table 7-77. Radiated Spurious Emissions below 1GHz (2.4GHz Ch.78 – 5GHz Ch.36), with AC/DC adapter

FCC ID: BCGA2270	PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)				Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device				

7.8 AC Line-Conducted Emissions Measurement

§15.407; RSS-Gen [8.8]

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for AC Line conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.207 and RSS-Gen (8.8).

Frequency of emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-78. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10-2013, Section 6.2

Test Settings

Quasi-Peak Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Average Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: BCGA2270	 PCTEST® Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device	Page 207 of 211	

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-8. Test Instrument & Measurement Setup

Test Notes

1. All modes of operation were investigated and the worst-case emissions are reported. The emissions found were not affected by the choice of channel used during testing.
2. For AC line conducted and radiated test below 1GHz, following configuration were investigated and EUT powered by AC/DC was the worst case.
 - a. EUT powered by AC/DC adaptor via USB-C cable with wire charger
 - b. EUT powered by host PC via USB-C cable with wire charger
3. The limit for an intentional radiator from 150kHz to 30MHz are specified in 15.207 and RSS-Gen (8.8).
4. Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
5. QP/AV Level (dB μ V) = QP/AV Analyzer/Receiver Level (dB μ V) + Corr. (dB)
6. Margin (dB) = QP/AV Level (dB μ V) – QP/AV Limit (dB μ V)
7. Traces shown in plot are made using quasi-peak and average detectors.
8. Deviations to the Specifications: None.

FCC ID: BCGA2270	PCTEST® Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device	Page 208 of 211	




Plot 7-286. AC Line Conducted Plot with 802.11n UNII Band 1 – Ch.36 (L1), with AC/DC adapter

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.152	FINAL	—	37.75	55.88	-18.13	L1	GND
0.159	FINAL	50.9	—	65.52	-14.59	L1	GND
0.200	FINAL	50.4	—	63.63	-13.23	L1	GND
0.200	FINAL	—	35.19	53.63	-18.44	L1	GND
0.544	FINAL	—	23.16	46.00	-22.84	L1	GND
0.546	FINAL	35.8	—	56.00	-20.24	L1	GND
0.593	FINAL	35.1	—	56.00	-20.87	L1	GND
0.596	FINAL	—	22.54	46.00	-23.46	L1	GND
0.645	FINAL	—	21.04	46.00	-24.96	L1	GND
0.645	FINAL	34.0	—	56.00	-22.04	L1	GND
0.697	FINAL	33.2	—	56.00	-22.78	L1	GND
0.697	FINAL	—	22.01	46.00	-23.99	L1	GND

Table 7-79. AC Line Conducted Data with 802.1n UNII Band 1 – Ch.36 (L1) with AC/DC adapter

FCC ID: BCGA2270	PCTEST® Proud to be part of 			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device			



Plot 7-287. AC Line Conducted Plot with 802.11n UNII Band 1 – Ch.36 (N), with AC/DC adapter

Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.150	FINAL	49.1	—	66.00	-16.89	N	GND
0.152	FINAL	—	34.26	55.88	-21.62	N	GND
0.200	FINAL	47.4	—	63.63	-16.23	N	GND
0.200	FINAL	—	32.11	53.63	-21.52	N	GND
0.544	FINAL	—	22.05	46.00	-23.95	N	GND
0.546	FINAL	34.4	—	56.00	-21.60	N	GND
0.596	FINAL	—	21.63	46.00	-24.37	N	GND
0.596	FINAL	34.1	—	56.00	-21.89	N	GND
0.645	FINAL	—	19.77	46.00	-26.23	N	GND
0.647	FINAL	33.0	—	56.00	-22.96	N	GND
0.697	FINAL	—	21.59	46.00	-24.41	N	GND
0.699	FINAL	33.0	—	56.00	-22.99	N	GND

Table 7-80. AC Line Conducted Data with 802.11n UNII Band 1 – Ch.36 (N), with AC/DC adapter

FCC ID: BCGA2270	PCTEST® Proud to be part of 			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device			

8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Apple Tablet Device** **FCC ID: BCGA2270** is in compliance with Part 15 Subpart E (15.407) of the FCC Rules and RSS-247 of the Innovation, Science and Economic Development Canada Rules.

FCC ID: BCGA2270	 PCTEST [®] Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2004270032-06.BCG	Test Dates: 05/01/2020 - 07/01/2020	EUT Type: Tablet Device	Page 211 of 211	