

## MEASUREMENT REPORT

### FCC PART 15.247 / ISED RSS-247 Bluetooth (HDR)

**Applicant Name:**

Apple Inc.  
One Apple Park Way  
Cupertino, CA 95014  
United States

**Date of Testing:**

12/15/2020-2/25/2021

**Test Site/Location:**

PCTEST Lab. Morgan Hill, CA, USA

**Test Report Serial No.:**

1C2101020002-11.BCG

<b>FCC ID:</b>	<b>BCGA2301</b>
<b>IC:</b>	<b>579C-A2301</b>
<b>APPLICANT:</b>	<b>Apple Inc.</b>

<b>Application Type:</b>	Certification
<b>Model/HVIN:</b>	A2301
<b>EUT Type:</b>	Tablet Device
<b>Max. RF Output Power:</b>	46.345 mW (16.66 dBm) Peak Conducted
<b>Frequency Range:</b>	2404 – 2476MHz
<b>FCC Classification:</b>	Digital Transmission System (DTS)
<b>FCC Rule Part(s):</b>	Part 15 Subpart C (15.247)
<b>ISED Specification:</b>	RSS-247 Issue 2
<b>Test Procedure(s):</b>	ANSI C63.10-2013, KDB 558074 D01 v05r02

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013 and KDB 558074 D01 v05r02. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Randy Ortanez  
President



FCC ID: BCGA2301 IC: 579C-A2301	<b>PCTEST<sup>®</sup></b> Proud to be part of element		<b>MEASUREMENT REPORT (CERTIFICATION)</b>	<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1C2101020002-11.BCG	<b>Test Dates:</b> 12/15/2020-2/25/2021		<b>EUT Type:</b> Tablet Device	<b>Page 1 of 101</b>

## T A B L E   O F   C O N T E N T S

---

1.0	INTRODUCTION .....	3
1.1	Scope .....	3
1.2	PCTEST Test Location.....	3
1.3	Test Facility / Accreditations.....	3
2.0	PRODUCT INFORMATION.....	4
2.1	Equipment Description .....	4
2.2	Device Capabilities .....	4
2.3	Antenna Description .....	5
2.4	Test Support Equipment.....	5
2.5	Test Configuration .....	6
2.6	Software and Firmware .....	6
2.7	EMI Suppression Device(s)/Modifications .....	6
3.0	DESCRIPTION OF TESTS .....	7
3.1	Evaluation Procedure .....	7
3.2	AC Line Conducted Emissions.....	7
3.3	Radiated Emissions.....	8
3.4	Environmental Conditions.....	8
4.0	ANTENNA REQUIREMENTS .....	9
5.0	MEASUREMENT UNCERTAINTY .....	10
6.0	TEST EQUIPMENT CALIBRATION DATA .....	11
7.0	TEST RESULTS.....	12
7.1	Summary .....	12
7.2	Bandwidth Measurement – Bluetooth (HDR).....	13
7.3	Output Power Measurement – Bluetooth (HDR) .....	23
7.3.1	Peak Output Power Measurement – Bluetooth (HDR) .....	24
7.3.2	Average Output Power Measurement – Bluetooth (HDR) .....	25
7.4	Power Spectral Density – Bluetooth (HDR) .....	27
7.5	Conducted Authorized Band Edge .....	55
7.6	Conducted Spurious Emissions.....	60
7.7	Radiated Spurious Emissions – Above 1GHz .....	68
7.7.1	Radiated Restricted Band Edge Measurements.....	81
7.8	Radiated Spurious Emissions – Below 1GHz.....	93
7.9	AC Line-Conducted Emissions Measurement .....	97
8.0	CONCLUSION.....	101

FCC ID: BCGA2301 IC: 579C-A2301	 <b>PCTEST®</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 2 of 101

## 1.0 INTRODUCTION

### 1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

### 1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST facility located at 18855 Adams Court, Morgan Hill, CA 95037. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014 and KDB 414788 D01 v01r01.

### 1.3 Test Facility / Accreditations

Measurements were performed at PCTEST located in Morgan Hill, CA 95037, U.S.A.

- PCTEST is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.02 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- PCTEST facility is a registered (22831) test laboratory with the site description on file with ISED.

FCC ID: BCGA2301 IC: 579C-A2301	 <b>PCTEST</b> <sup>®</sup> Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 3 of 101	

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **Apple Tablet Device FCC ID: BCGA2301, IC: 579C-A2301**. The data found in this test report was taken with the EUT operating in Bluetooth HDR mode. While in HDR mode, the Bluetooth transmitter hops pseudo-randomly between 73 channels.

**Test Device Serial No.:** LGXMHP6X6Y, JDP7MWF160, NQ73CFK6VJ, N9TXL9P7K6

### 2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, 5G NR (FR1/FR2), 802.11b/g/n/ax WLAN, 802.11a/n/ac/ax UNII, Bluetooth (1x, EDR, LE1M, LE2M, HDR4, HDR8), WPT

This device supports BT Beamforming

Ch.	Frequency (MHz)
1	2404
:	:
38	2441
:	:
73	2476

**Table 2-1. Bluetooth HDR Frequency / Channel Operations**

Measured Duty Cycles				
HDR Mode		Duty Cycle [%]		
		Antenna 4a	Antenna 2a	TxBF
HDR4	ePA	100.0	100.0	100.0
	iPA	100.0	100.0	100.0
HDR8	ePA	100.0	100.0	100.0
	iPA	100.0	100.0	100.0

**Table 2-2. Measured Duty Cycles**

This device is capable of operating in hopping and non-hopping mode. The EUT can hop between 73 different channels in the 2400 – 2483.5MHz band.

FCC ID: BCGA2301 IC: 579C-A2301	 <b>PCTEST®</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 4 of 101

This device supports simultaneous transmission operations, which allows for multiple transmitters to transmit simultaneously on the same antenna. The table below shows all configurations possible.

Antenna	Simultaneous Tx Config	WLAN	Bluetooth	GSM / WCDMA	LTE / FR1 NR			UNII
		802.11 b/g/n/ax	BDR, EDR, HDR4/8, LE 1M/2M	Mid Band	Mid Band	High Band	Ultra High Band	802.11 a/n/ac/ax
2a	Config 1	✓	✗	✗	✗	✗	✓	✗
2a	Config 2	✗	✓	✗	✗	✗	✓	✗
4a	Config 3	✓	✗	✗	✗	✗	✓	✗
4a	Config 4	✗	✓	✗	✗	✗	✓	✗
4b	Config 5	✗	✗	✓	✗	✗	✗	✓
4b	Config 6	✗	✗	✗	✓	✗	✗	✓
4b	Config 7	✗	✗	✗	✗	✓	✗	✓

**Table 2-3. Simultaneous Transmission Configurations**

✓ = Support; ✗ = Not Support

**Note:**

All the above simultaneous transmission configurations have been tested and the worst case configuration was found to be Config 6 and reported in UNII OFDMA and FCC part 27b test reports.

## 2.3 Antenna Description

Following antenna gains provided by manufacturer were used for testing.

Frequency [GHz]	Antenna Gain (dBi)	
	Antenna 4a	Antenna 2a
2.4	1.5	2.5

**Table 2-4. Highest Antenna Gain**

## 2.4 Test Support Equipment

Test Support Equipment List				
1	Apple MacBook Pro w/AC/DC Adapter	Model: A2141 Model: A2166	S/N: N/A	C02DV7VKMD6T
2	Apple USB-C Cable	Model: Chimp	S/N: 420A57	
3	USB-C Cable w/ AC Adapter	Model: A146 Model: A2305	S/N: N/A	
4	Apple Pencil	Model: N/A	S/N: GQXYGSXBJKM9	
5	DC Power Supply	Model: KPS3010D	S/N: N/A	

**Table 2-5. Test Support Equipment List**

FCC ID: BCGA2301 IC: 579C-A2301	 <b>PCTEST®</b> Proud to be part of 			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device			

## 2.5 Test Configuration

The EUT was tested per the guidance of ANSI C63.10-2013 and KDB 558074 D01 v05r02. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See Sections 3.2 for AC line conducted emissions test setups, 3.3 for radiated emissions test setups, and 7.2, 7.3, 7.4, 7.5, and 7.6 for antenna port conducted emissions test setups.

There are two vendors of the WiFi/Bluetooth radio modules, variant 1 and variant 2. Both radio modules have the same mechanical outline, same on-board antenna matching circuit, identical antenna structure, and are built and tested to conform to the same specifications and to operate within the same tolerances. The worst case configuration was found between the two variants. The EUT was also investigated with and without charger.

For emissions from 1GHz – 18GHz, low, mid, and high channels were tested with highest power and worst case configuration. The emissions below 1GHz and above 18GHz were tested with the highest transmitting power and the worst case channel.

The EUT was manipulated through three orthogonal planes of X-orientation (flatbed), Y-orientation (landscape), and Z-orientation (portrait) during the testing. Only the worst case emissions were reported in this test report.

For AC line conducted and radiated test below 1GHz, following configuration were investigated and the worst case was reported.

- EUT powered by AC/DC adaptor via USB-C cable with wire charger
- EUT powered by host PC via USB-C cable with wire charger

## 2.6 Software and Firmware

The test was conducted with firmware version 18E20700y installed on the EUT.

## 2.7 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

FCC ID: BCGA2301 IC: 579C-A2301	 <b>PCTEST<sup>®</sup></b> Proud to be part of element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 6 of 101	

## 3.0 DESCRIPTION OF TESTS

### 3.1 Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013) and the guidance provided in KDB 558074 D01 v05r02 were used in the measurement of the EUT.

**Deviation from measurement procedure.....**None

### 3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 7m x 3.66m x 2.7m shielded enclosure. The shielded enclosure is manufactured by AP Americas. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50µH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is an EPCOS 2X60A Power Line Filter (100dB Attenuation, 14kHz-18GHz) and the two EPCOs 2X48A filters (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that the cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 7.10. Automated test software was used to perform the AC line conducted emissions testing. Automated measurement software utilized is Rohde & Schwarz EMC32, Version 10.50.40.

FCC ID: BCGA2301 IC: 579C-A2301	 <b>PCTEST<sup>®</sup></b> Proud to be part of element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device		Page 7 of 101

### 3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

Per KDB 414788, radiated emission test sites other than open-field test sites (e.g., shielded anechoic chambers), may be employed for emission measurements below 30MHz if characterized so that the measurements correspond to those obtained at an open-field test site. To determine test site equivalency, a reference sample transmitting at 149kHz was measured on an open field test site (asphalt with no ground plane) and then measured in the 3m semi-anechoic chamber. A calibrated 60cm loop antenna was rotated about its vertical axis while the reference device was rotated through the X, Y and Z axis in order to capture the worst case level. A maximum deviation of 2.77dB at 149kHz was measured when comparing the 3 meter semi-anechoic chamber to the open field site.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33 depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

### 3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: BCGA2301 IC: 579C-A2301	 <b>PCTEST<sup>®</sup></b> Proud to be part of element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device		Page 8 of 101

## 4.0 ANTENNA REQUIREMENTS

### Excerpt from §15.203 of the FCC Rules/Regulations:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

- The antenna(s) of the EUT are **permanently attached**.
- There are no provisions for connection to an external antenna.

### Conclusion:

The EUT complies with the requirement of §15.203.

FCC ID: BCGA2301 IC: 579C-A2301	 <b>PCTEST</b> <sup>®</sup> Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 9 of 101	

## 5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.23-2012. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the  $U_{CISPR}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ( $\pm$ dB)
Conducted Bench Top Measurements	1.65
Line Conducted Disturbance	2.75
Radiated Disturbance (<30MHz)	4.06
Radiated Disturbance (30MHz - 1GHz)	4.30
Radiated Disturbance (1 -18GHz)	4.78
Radiated Disturbance (>18GHz)	4.79

FCC ID: BCGA2301 IC: 579C-A2301	 PCTEST <sup>®</sup> Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 10 of 101

## 6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent Technologies	N9030A	3Hz-44GHz PXA Signal Analyzer	3/4/2020	Annual	3/4/2021	MY49430244
Anritsu	ML2496A	Power Meter	4/9/2020	Annual	4/9/2021	2002005
Anritsu	MA2411B	Pulse Power Sensor	3/10/2020	Annual	3/10/2021	1911105
Anritsu	MA2411B	Pulse Power Sensor	3/10/2020	Annual	3/10/2021	1911106
ATM	180-442A-KF	20dB Nominal Gain Horn Antenna	8/11/2020	Annual	8/11/2021	T058701-01
COM-POWER	LIN-120A	LISN	3/4/2020	Annual	3/4/2021	241297
ETS-Lindgren	3142E	BiConiLog Antenna (30MHz - 6GHz)	9/15/2020	Annual	9/15/2021	208204
ETS-Lindgren	3117	Double Ridged Guide Antenna (1-18 GHz)	4/21/2020	Annual	4/21/2021	205956
Rohde & Schwarz	ESW26	EMI Test Receiver	6/1/2020	Annual	6/1/2021	101299
Rohde & Schwarz	ESW44	EMI Test Receiver	8/7/2020	Annual	8/7/2021	101668
Rohde & Schwarz	TS-PR1840	Pre-Amplifier (18GHz - 40GHz)	4/3/2020	Annual	4/3/2021	100052
Rohde & Schwarz	TC-TA18	Cross Polarized Vivaldi Antenna (400MHz-18GHz)	10/2/2020	Annual	10/2/2021	101063
Rohde & Schwarz	HFH2-Z2	Loop Antenna	3/12/2020	Annual	3/12/2021	100546
Rohde & Schwarz	TS-PR18	Pre-Amplifier (1GHz - 18GHz)	12/3/2020	Annual	12/3/2021	101648
Rohde & Schwarz	TS-PR8	Pre-Amplifier (30MHz - 8GHz)	3/4/2020	Annual	3/4/2021	102325
Rohde & Schwarz	ENV216	Two-Line V-Network (LISN)	12/7/2020	Annual	12/7/2021	101364

**Table 6-1. Test Equipment List**

**Note:**

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

FCC ID: BCGA2301 IC: 579C-A2301	 <b>PCTEST<sup>®</sup></b> Proud to be part of element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device		

## 7.0 TEST RESULTS

### 7.1 Summary

Company Name: Apple Inc.  
 FCC ID: BCGA2301  
 IC: 579C-A2301  
 FCC Classification: Digital Transmission System (DTS)  
 Number of Channels: 73

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.247(a)(2)	RSS-247 [5.2]	6dB Bandwidth	> 500kHz	CONDUCTED	PASS	Section 7.2
2.1049	RSS-Gen [6.7]	Occupied Bandwidth	N/A		N/A	Section 7.2
15.247(b)(3)	RSS-247 [5.4(d)]	Transmitter Output Power	< 1 Watt		PASS	Sections 7.3
15.247(e)	RSS-247 [5.2]	Transmitter Power Spectral Density	< 8dBm / 3kHz Band		PASS	Section 7.4
15.247(d)	RSS-247 [5.5]	Band Edge / Out-of-Band Emissions	≥ 20dBc		PASS	Sections 7.5, 7.6
15.205 15.209	RSS-Gen [8.9]	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-Gen [8.9])	RADIATED	PASS	Sections 7.7, 7.7.1, 7.8
15.207	RSS-Gen [8.8]	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 limits (RSS-Gen[8.8])	AC LINE CONDUCTED	PASS	Section 7.10

**Table 7-1. Summary of Test Results**

#### Notes:

1. All modes of operation were investigated. The test results shown in the following sections represent the worst case emissions.
2. The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
3. All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
4. For radiated band edge, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "Chamber Automation," Version 1.3.1.

FCC ID: BCGA2301 IC: 579C-A2301	 PCTEST <sup>®</sup> Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 12 of 101

## 7.2 Bandwidth Measurement – Bluetooth (HDR)

§2.1049; §15.247(a.2); RSS-247 [5.2]; RSS-Gen [6.7]

### Test Overview and Limit

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the transmitter antenna terminal of the EUT while the EUT is operating at maximum power and at the appropriate frequencies. All modes of operation were investigated and the worst case configuration results are reported in this section.

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

***The minimum permissible 6dB bandwidth is 500 kHz.***

### Test Procedure Used

ANSI C63.10-2013 – Section 11.8.2 Option 2

KDB 558074 D01 v05r02 – Section 8.2

RSS-Gen [6.7]

### Test Settings

1. The signal analyzers' automatic bandwidth measurement capability of the spectrum analyzer was used to perform the 99% occupied bandwidth and the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to X = 6. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 100kHz
3. VBW  $\geq 3 \times$  RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

FCC ID: BCGA2301 IC: 579C-A2301	 <b>PCTEST®</b> <small>Proud to be part of element</small>		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device		Page 13 of 101

## Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-1. Test Instrument & Measurement Setup**

## Test Notes

All supported modulation, antennas (including TxBF mode) and power schemes have been tested on the unit and only the worst case configuration is reported.


FCC ID: BCGA2301 IC: 579C-A2301	 <b>PCTEST</b> Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device		Page 14 of 101

**Antenna 4a**


Frequency [MHz]	Data Rate [Mbps]	Power Scheme	Channel No.	99% Occupied Bandwidth [kHz]	6dB Bandwidth [kHz]	Minimum 6dB Bandwidth [kHz]	Pass / Fail
2404	4.0	ePA	1	2342.2	2111.0	500	Pass
2441	4.0	ePA	38	2342.0	2110.0	500	Pass
2476	4.0	ePA	73	2343.0	2114.0	500	Pass
2404	8.0	ePA	1	4704.7	4113.0	500	Pass
2441	8.0	ePA	38	4700.8	4117.0	500	Pass
2476	8.0	ePA	73	4693.8	4129.0	500	Pass

**Table 7-2. 6dB BW & 99% OBW Measurements Antenna 4a**

FCC ID: BCGA2301 IC: 579C-A2301	 <b>PCTEST®</b> Proud to be part of  <b>MEASUREMENT REPORT (CERTIFICATION)</b>			Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 15 of 101	




Plot 7-1. 6dB BW & 99% OBW Plot Antenna 4a (Bluetooth (HDR4), 4Mbps, ePA – Ch. 1)




Plot 7-2. 6dB BW & 99% OBW Plot Antenna 4a (Bluetooth (HDR4), 4Mbps, ePA – Ch. 38)

FCC ID: BCGA2301 IC: 579C-A2301	<b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 16 of 101




Plot 7-3. 6dB BW & 99% OBW Plot Antenna 4a (Bluetooth (HDR4), 4Mbps, ePA – Ch. 73)




Plot 7-4. 6dB BW & 99% OBW Plot Antenna 4a (Bluetooth (HDR8), 8Mbps, ePA – Ch. 1)

FCC ID: BCGA2301 IC: 579C-A2301	<b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 17 of 101



Plot 7-5. 6dB BW & 99% OBW Plot Antenna 4a (Bluetooth (HDR8), 8Mbps, ePA – Ch. 38)



Plot 7-6. 6dB BW & 99% OBW Plot Antenna 4a (Bluetooth (HDR8), 8Mbps, ePA – Ch. 73)


FCC ID: BCGA2301 IC: 579C-A2301	<b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 18 of 101

**Antenna 2a**


Frequency [MHz]	Data Rate [Mbps]	Power Scheme	Channel No.	99% Occupied Bandwidth [kHz]	6dB Bandwidth [kHz]	Minimum 6dB Bandwidth [kHz]	Pass / Fail
2404	4.0	ePA	1	2342.0	2111.0	500	Pass
2441	4.0	ePA	38	2342.4	2111.0	500	Pass
2476	4.0	ePA	73	2342.4	2114.0	500	Pass
2404	8.0	ePA	1	4701.9	4114.0	500	Pass
2441	8.0	ePA	38	4697.8	4121.0	500	Pass
2476	8.0	ePA	73	4691.1	4141.0	500	Pass

**Table 7-3. 6dB BW & 99% OBW Measurements Antenna 2a**

FCC ID: BCGA2301 IC: 579C-A2301	 <b>PCTEST®</b> Proud to be part of  <b>MEASUREMENT REPORT (CERTIFICATION)</b>			Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 19 of 101	




Plot 7-7. 6dB BW & 99% OBW Plot Antenna 2a (Bluetooth (HDR4), 4Mbps, ePA – Ch. 1)




Plot 7-8. 6dB BW & 99% OBW Plot Antenna 2a (Bluetooth (HDR4), 4Mbps, ePA – Ch. 38)

FCC ID: BCGA2301 IC: 579C-A2301	 Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 20 of 101




Plot 7-9. 6dB BW & 99% OBW Plot Antenna 2a (Bluetooth (HDR4), 4Mbps, ePA – Ch. 73)




Plot 7-10. 6dB BW & 99% OBW Plot Antenna 2a (Bluetooth (HDR8), 8Mbps, ePA – Ch. 1)

FCC ID: BCGA2301 IC: 579C-A2301	<b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 21 of 101



Plot 7-11. 6dB BW & 99% OBW Plot Antenna 2a (Bluetooth (HDR8), 8Mbps, ePA – Ch. 38)



Plot 7-12. 6dB BW & 99% OBW Plot Antenna 2a (Bluetooth (HDR8), 8Mbps, ePA – Ch. 73)

FCC ID: BCGA2301 IC: 579C-A2301	 PCTEST® Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 22 of 101

## 7.3 Output Power Measurement – Bluetooth (HDR)

§15.247(b.3); RSS-247 [5.4(d)]

### Test Overview and Limits

The transmitter antenna terminal of the EUT is connected to the input of a spectrum analyzer. Measurements are made while the EUT is operating at maximum power and at the appropriate frequencies.

***The maximum peak conducted output power of digital modulation systems operating in the 2400-2483.5 MHz band is 1 Watt.***

***The conducted output power limit on paragraph above is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.***

***For DTSs employing digital modulation techniques operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1 W. The e.i.r.p. shall not exceed 4 W.***

### Test Procedure Used

ANSI C63.10-2013 – Section 11.9.1.3

ANSI C63.10-2013 – Section 11.9.2.3.2

KDB 558074 D01 v05r02 – Section 8.3.1.3, 8.3.2.3

ANSI C63.10-2013 – Section 14.2 Measure-and-Sum Technique

KDB 662911 D01 v02r01 – Section E(1) Measure-and-Sum Technique

### Test Settings

#### Method PKPM1 (Peak Power Measurement)

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

#### Method AVGPM-G (Average Power Measurement)

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-2. Test Instrument & Measurement Setup for Peak and Average Power Measurement**

### Test Notes

None

FCC ID: BCGA2301 IC: 579C-A2301	 <b>PCTEST</b> <sup>®</sup> Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device		Page 23 of 101

### 7.3.1 Peak Output Power Measurement – Bluetooth (HDR)

Frequency [MHz]	Data Rate [Mbps]	Power Scheme	Channel No.	Peak Conducted Power		Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]
				[dBm]	[mW]						
2404	4.0	ePA	1	12.87	19.364	30.00	-17.13	1.50	14.37	36.02	-21.65
2441	4.0	ePA	38	12.89	19.454	30.00	-17.11	1.50	14.39	36.02	-21.63
2476	4.0	ePA	73	12.81	19.099	30.00	-17.19	1.50	14.31	36.02	-21.71
2404	4.0	iPA	1	6.87	4.864	30.00	-23.13	1.50	8.37	36.02	-27.65
2441	4.0	iPA	38	6.49	4.457	30.00	-23.51	1.50	7.99	36.02	-28.03
2476	4.0	iPA	73	6.88	4.875	30.00	-23.12	1.50	8.38	36.02	-27.64
2404	8.0	ePA	1	13.98	25.003	30.00	-16.02	1.50	15.48	36.02	-20.54
2441	8.0	ePA	38	13.61	22.961	30.00	-16.39	1.50	15.11	36.02	-20.91
2476	8.0	ePA	73	13.68	23.335	30.00	-16.32	1.50	15.18	36.02	-20.84
2404	8.0	iPA	1	7.95	6.237	30.00	-22.05	1.50	9.45	36.02	-26.57
2441	8.0	iPA	38	7.60	5.754	30.00	-22.40	1.50	9.10	36.02	-26.92
2476	8.0	iPA	73	7.86	6.109	30.00	-22.14	1.50	9.36	36.02	-26.66

Table 7-4. Peak Conducted Output Power Measurements Antenna 4a (Bluetooth HDR)

Frequency [MHz]	Data Rate [Mbps]	Power Scheme	Channel No.	Peak Conducted Power		Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]
				[dBm]	[mW]						
2404	4.0	ePA	1	12.32	17.061	30.00	-17.68	2.50	14.82	36.02	-21.20
2441	4.0	ePA	38	12.55	17.989	30.00	-17.45	2.50	15.05	36.02	-20.97
2476	4.0	ePA	73	12.29	16.943	30.00	-17.71	2.50	14.79	36.02	-21.23
2404	4.0	iPA	1	5.44	3.499	30.00	-24.56	2.50	7.94	36.02	-28.08
2441	4.0	iPA	38	5.20	3.311	30.00	-24.80	2.50	7.70	36.02	-28.32
2476	4.0	iPA	73	5.46	3.516	30.00	-24.54	2.50	7.96	36.02	-28.06
2404	8.0	ePA	1	13.51	22.439	30.00	-16.49	2.50	16.01	36.02	-20.01
2441	8.0	ePA	38	13.18	20.797	30.00	-16.82	2.50	15.68	36.02	-20.34
2476	8.0	ePA	73	13.20	20.893	30.00	-16.80	2.50	15.70	36.02	-20.32
2404	8.0	iPA	1	6.25	4.217	30.00	-23.75	2.50	8.75	36.02	-27.27
2441	8.0	iPA	38	6.00	3.981	30.00	-24.00	2.50	8.50	36.02	-27.52
2476	8.0	iPA	73	6.28	4.246	30.00	-23.72	2.50	8.78	36.02	-27.24

Table 7-5. Peak Conducted Output Power Measurements Antenna 2a (Bluetooth HDR)

Frequency [MHz]	Data Rate [Mbps]	Power Scheme	Channel No.	Peak Conducted Power					Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Directional Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]		
				Antenna 4a		Antenna 2a		Summed								
[dBm]	[mW]	[dBm]	[mW]	[dBm]	[mW]	[dBm]	[mW]	[dBm]								
2404	4.0	ePA	1	13.10	20.417	12.36	17.219	15.76	37.670	30.00	-14.24	5.02	20.78	36.02	-15.24	
2441	4.0	ePA	38	13.37	21.727	12.26	16.827	15.86	38.548	30.00	-14.14	5.02	20.88	36.02	-15.14	
2476	4.0	ePA	73	13.19	20.845	12.38	17.298	15.81	38.107	30.00	-14.19	5.02	20.83	36.02	-15.19	
2404	4.0	iPA	1	6.47	4.436	5.20	3.311	8.89	7.745	30.00	-21.11	5.02	13.91	36.02	-22.11	
2441	4.0	iPA	38	6.22	4.188	5.19	3.304	8.75	7.499	30.00	-21.25	5.02	13.77	36.02	-22.25	
2476	4.0	iPA	73	6.23	4.198	5.28	3.373	8.79	7.568	30.00	-21.21	5.02	13.81	36.02	-22.21	
2404	8.0	ePA	1	13.75	23.714	13.54	22.594	16.66	46.345	30.00	-13.34	5.02	21.68	36.02	-14.34	
2441	8.0	ePA	38	13.69	23.388	12.93	19.634	16.34	43.053	30.00	-13.66	5.02	21.36	36.02	-14.66	
2476	8.0	ePA	73	13.73	23.605	12.95	19.724	16.37	43.351	30.00	-13.63	5.02	21.39	36.02	-14.63	
2404	8.0	iPA	1	7.16	5.200	6.07	4.046	9.66	9.247	30.00	-20.34	5.02	14.68	36.02	-21.34	
2441	8.0	iPA	38	7.04	5.058	5.97	3.954	9.55	9.016	30.00	-20.45	5.02	14.57	36.02	-21.45	
2476	8.0	iPA	73	7.06	5.082	6.09	4.064	9.61	9.141	30.00	-20.39	5.02	14.63	36.02	-21.39	

Table 7-6. Peak Conducted Output Power Measurements TxBF (Bluetooth HDR)

FCC ID: BCGA2301 IC: 579C-A2301	 PCTEST <sup>®</sup> Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 24 of 101

### 7.3.2 Average Output Power Measurement – Bluetooth (HDR)

Frequency [MHz]	Data Rate [Mbps]	Power Scheme	Channel No.	Average Conducted Power		Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]
				[dBm]	[mW]						
2404	4.0	ePA	1	9.93	9.840	30.00	-20.07	1.50	11.43	36.02	-24.59
2441	4.0	ePA	38	9.92	9.817	30.00	-20.08	1.50	11.42	36.02	-24.60
2476	4.0	ePA	73	9.79	9.528	30.00	-20.21	1.50	11.29	36.02	-24.73
2404	4.0	iPA	1	3.96	2.489	30.00	-26.04	1.50	5.46	36.02	-30.56
2441	4.0	iPA	38	3.58	2.280	30.00	-26.42	1.50	5.08	36.02	-30.94
2476	4.0	iPA	73	3.90	2.455	30.00	-26.10	1.50	5.40	36.02	-30.62
2404	8.0	ePA	1	9.72	9.376	30.00	-20.28	1.50	11.22	36.02	-24.80
2441	8.0	ePA	38	9.53	8.974	30.00	-20.47	1.50	11.03	36.02	-24.99
2476	8.0	ePA	73	9.56	9.036	30.00	-20.44	1.50	11.06	36.02	-24.96
2404	8.0	iPA	1	3.98	2.500	30.00	-26.02	1.50	5.48	36.02	-30.54
2441	8.0	iPA	38	3.61	2.296	30.00	-26.39	1.50	5.11	36.02	-30.91
2476	8.0	iPA	73	3.92	2.466	30.00	-26.08	1.50	5.42	36.02	-30.60

Table 7-7. Average Conducted Output Power Measurements Antenna 4a (Bluetooth HDR)

Frequency [MHz]	Data Rate [Mbps]	Power Scheme	Channel No.	Average Conducted Power		Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]
				[dBm]	[mW]						
2404	4.0	ePA	1	9.62	9.162	30.00	-20.38	2.50	12.12	36.02	-23.90
2441	4.0	ePA	38	9.87	9.705	30.00	-20.13	2.50	12.37	36.02	-23.65
2476	4.0	ePA	73	9.63	9.183	30.00	-20.37	2.50	12.13	36.02	-23.89
2404	4.0	iPA	1	2.83	1.919	30.00	-27.17	2.50	5.33	36.02	-30.69
2441	4.0	iPA	38	2.58	1.811	30.00	-27.42	2.50	5.08	36.02	-30.94
2476	4.0	iPA	73	2.87	1.936	30.00	-27.13	2.50	5.37	36.02	-30.65
2404	8.0	ePA	1	10.00	10.000	30.00	-20.00	2.50	12.50	36.02	-23.52
2441	8.0	ePA	38	9.71	9.354	30.00	-20.29	2.50	12.21	36.02	-23.81
2476	8.0	ePA	73	9.68	9.290	30.00	-20.32	2.50	12.18	36.02	-23.84
2404	8.0	iPA	1	2.87	1.936	30.00	-27.13	2.50	5.37	36.02	-30.65
2441	8.0	iPA	38	2.62	1.828	30.00	-27.38	2.50	5.12	36.02	-30.90
2476	8.0	iPA	73	2.92	1.959	30.00	-27.08	2.50	5.42	36.02	-30.60

Table 7-8. Average Conducted Output Power Measurements Antenna 2a (Bluetooth HDR)

Frequency [MHz]	Data Rate [Mbps]	Power Scheme	Channel No.	Average Conducted Power						Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Directional Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]						
				Antenna 4a		Antenna 2a		Summed													
				[dBm]	[mW]	[dBm]	[mW]	[dBm]	[mW]												
2404	4.0	ePA	1	10.00	10.000	9.69	9.311	12.86	19.320	30.00	-17.14	5.02	17.88	36.02	-18.14						
2441	4.0	ePA	38	10.00	10.000	9.50	8.913	12.77	18.923	30.00	-17.23	5.02	17.79	36.02	-18.23						
2476	4.0	ePA	73	10.00	10.000	9.68	9.290	12.85	19.275	30.00	-17.15	5.02	17.87	36.02	-18.15						
2404	4.0	iPA	1	3.86	2.432	2.58	1.811	6.28	4.246	30.00	-23.72	5.02	11.30	36.02	-24.72						
2441	4.0	iPA	38	3.62	2.301	2.52	1.786	6.12	4.093	30.00	-23.88	5.02	11.14	36.02	-24.88						
2476	4.0	iPA	73	3.64	2.312	2.67	1.849	6.19	4.159	30.00	-23.81	5.02	11.21	36.02	-24.81						
2404	8.0	ePA	1	10.00	10.000	10.00	10.000	13.01	19.999	30.00	-16.99	5.02	18.03	36.02	-17.99						
2441	8.0	ePA	38	10.00	10.000	9.52	8.954	12.78	18.967	30.00	-17.22	5.02	17.80	36.02	-18.22						
2476	8.0	ePA	73	10.00	10.000	9.51	8.933	12.77	18.923	30.00	-17.23	5.02	17.79	36.02	-18.23						
2404	8.0	iPA	1	3.79	2.393	2.70	1.862	6.29	4.256	30.00	-23.71	5.02	11.31	36.02	-24.71						
2441	8.0	iPA	38	3.72	2.355	2.63	1.832	6.22	4.188	30.00	-23.78	5.02	11.24	36.02	-24.78						
2476	8.0	iPA	73	3.68	2.333	2.74	1.879	6.25	4.217	30.00	-23.75	5.02	11.27	36.02	-24.75						

Table 7-9. Average Conducted Output Power Measurements TxBF (Bluetooth HDR)

FCC ID: BCGA2301 IC: 579C-A2301	 PCTEST <sup>®</sup> Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 25 of 101

**Note:**

Per ANSI C63.10-2013 and KDB 662911 D01 v02r01 Section E)1), the conducted powers at Antenna 4a and Antenna 2a were first measured separately during TxBF transmission as shown in the section above. The measured values were then summed in linear power units then converted back to dBm.

Per ANSI C63.10-2013 Section 14.4.3, the directional gain is calculated using the following formula, where  $G_N$  is the gain of the nth antenna and  $N_{ANT}$ , the total number of antennas used.

$$\text{Directional gain} = 10 \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_{N/20}})^2 / N_{ANT}] \text{ dBi}$$

**Sample TxBF Calculation:**

At 2404MHz the average conducted output power was measured to be 10.00 dBm for Antenna 4a and 9.69 dBm for Antenna 2a.

$$\text{Antenna 4a} + \text{Antenna 2a} = \text{TxBF}$$

$$(10.00 \text{ dBm} + 9.69 \text{ dBm}) = (10.00 \text{ mW} + 9.31 \text{ mW}) = 19.32 \text{ mW} = 12.86 \text{ dBm}$$

**Sample e.i.r.p. Calculation:**

At 2404MHz, the average conducted output power was calculated to be 12.86 dBm with directional gain of 5.02 dBi.

$$\text{e.i.r.p. (dBm)} = \text{Conducted Power (dBm)} + \text{Ant gain (dBi)}$$

$$12.86 \text{ dBm} + 5.02 \text{ dBi} = 17.88 \text{ dBm}$$

FCC ID: BCGA2301 IC: 579C-A2301	 <b>PCTEST<sup>®</sup></b> Proud to be part of element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device		Page 26 of 101

## 7.4 Power Spectral Density – Bluetooth (HDR)

§15.247(e); RSS-247 [5.2]

### Test Overview and Limit

The peak power density is measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power and at the appropriate frequencies.

***The maximum permissible power spectral density is 8 dBm in any 3 kHz band.***

### Test Procedure Used

ANSI C63.10-2013 – Section 11.10.2 Method PKPSD

KDB 558074 D01 v05r02 – Section 8.4 DTS Maximum Power Spectral Density level in the fundamental emission

ANSI C63.10-2013 – Section 14.3.2.2 Measure-and-Sum Technique

KDB 662911 D01 v02r01 – Section E2) Measure-and-Sum Technique

### Test Settings

1. Analyzer was set to the center frequency of the DTS channel under investigation
2. Span = 1.5 times the DTS channel bandwidth
3. RBW = 3kHz
4. VBW = 1MHz
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Trace was allowed to stabilize

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-3. Test Instrument & Measurement Setup**

### Test Notes

None


FCC ID: BCGA2301 IC: 579C-A2301	 <b>PCTEST®</b> <small>Proud to be part of element</small>		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device		Page 27 of 101

**Antenna 4a**


Frequency [MHz]	Data Rate [Mbps]	Power Scheme	Channel No.	Measured Power Spectral Density [dBm / 3kHz]	Maximum Permissible Power Density [dBm / 3kHz]	Margin [dB]
2404	4.0	ePA	1	-5.69	8.0	-13.69
2441	4.0	ePA	38	-5.44	8.0	-13.44
2476	4.0	ePA	73	-5.99	8.0	-13.99
2404	4.0	iPA	1	-12.33	8.0	-20.33
2441	4.0	iPA	38	-12.13	8.0	-20.13
2476	4.0	iPA	73	-12.84	8.0	-20.84
2404	8.0	ePA	1	-8.56	8.0	-16.56
2441	8.0	ePA	38	-8.40	8.0	-16.40
2476	8.0	ePA	73	-8.45	8.0	-16.45
2404	8.0	iPA	1	-14.92	8.0	-22.92
2441	8.0	iPA	38	-14.51	8.0	-22.51
2476	8.0	iPA	73	-14.63	8.0	-22.63

**Table 7-10. Conducted Power Density Measurements Antenna 4a**

FCC ID: BCGA2301 IC: 579C-A2301	 <b>PCTEST®</b> Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device		




Plot 7-13. Power Spectral Density Plot Antenna 4a (Bluetooth (HDR4), 4Mbps, ePA – Ch. 1)




Plot 7-14. Power Spectral Density Plot Antenna 4a (Bluetooth (HDR4), 4Mbps, ePA – Ch. 38)

FCC ID: BCGA2301 IC: 579C-A2301	<b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 29 of 101




Plot 7-15. Power Spectral Density Plot Antenna 4a (Bluetooth (HDR4), 4Mbps, ePA – Ch. 73)




Plot 7-16. Power Spectral Density Plot Antenna 4a (Bluetooth (HDR4), 4Mbps, iPA – Ch. 1)

FCC ID: BCGA2301 IC: 579C-A2301	<b>PCTEST</b> Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 30 of 101	




Plot 7-17. Power Spectral Density Plot Antenna 4a (Bluetooth (HDR4), 4Mbps, iPA – Ch. 38)




Plot 7-18. Power Spectral Density Plot Antenna 4a (Bluetooth (HDR4), 4Mbps, iPA – Ch. 73)

FCC ID: BCGA2301 IC: 579C-A2301	<b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 31 of 101




Plot 7-19. Power Spectral Density Plot Antenna 4a (Bluetooth (HDR8), 8Mbps, ePA – Ch. 1)




Plot 7-20. Power Spectral Density Plot Antenna 4a (Bluetooth (HDR8), 8Mbps, ePA – Ch. 38)

FCC ID: BCGA2301 IC: 579C-A2301	<b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 32 of 101




Plot 7-21. Power Spectral Density Plot Antenna 4a (Bluetooth (HDR8), 8Mbps, ePA – Ch. 73)




Plot 7-22. Power Spectral Density Plot Antenna 4a (Bluetooth (HDR8), 8Mbps, iPA – Ch. 1)

FCC ID: BCGA2301 IC: 579C-A2301	<b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 33 of 101



Plot 7-23. Power Spectral Density Plot Antenna 4a (Bluetooth (HDR8), 8Mbps, iPA – Ch. 38)



Plot 7-24. Power Spectral Density Plot Antenna 4a (Bluetooth (HDR8), 8Mbps, iPA – Ch. 73)


FCC ID: BCGA2301 IC: 579C-A2301	<b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 34 of 101

**Antenna 2a**


Frequency [MHz]	Data Rate [Mbps]	Power Scheme	Channel No.	Measured Power Spectral Density [dBm / 3kHz]	Maximum Permissible Power Density [dBm / 3kHz]	Margin [dB]
2404	4.0	ePA	1	-5.95	8.0	-13.95
2441	4.0	ePA	38	-5.75	8.0	-13.75
2476	4.0	ePA	73	-6.47	8.0	-14.47
2404	4.0	iPA	1	-13.34	8.0	-21.34
2441	4.0	iPA	38	-13.57	8.0	-21.57
2476	4.0	iPA	73	-13.24	8.0	-21.24
2404	8.0	ePA	1	-8.80	8.0	-16.80
2441	8.0	ePA	38	-8.29	8.0	-16.29
2476	8.0	ePA	73	-8.53	8.0	-16.53
2404	8.0	iPA	1	-15.32	8.0	-23.32
2441	8.0	iPA	38	-15.56	8.0	-23.56
2476	8.0	iPA	73	-15.77	8.0	-23.77

**Table 7-11. Conducted Power Density Measurements Antenna 2a**

FCC ID: BCGA2301 IC: 579C-A2301	 <b>PCTEST®</b> Proud to be part of  <b>MEASUREMENT REPORT (CERTIFICATION)</b>			Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 35 of 101	




Plot 7-25. Power Spectral Density Plot Antenna 2a (Bluetooth (HDR4), 4Mbps, ePA – Ch. 1)




Plot 7-26. Power Spectral Density Plot Antenna 2a (Bluetooth (HDR4), 4Mbps, ePA – Ch. 38)

FCC ID: BCGA2301 IC: 579C-A2301	<b>PCTEST</b> Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 36 of 101	




Plot 7-27. Power Spectral Density Plot Antenna 2a (Bluetooth (HDR4), 4Mbps, ePA – Ch. 73)




Plot 7-28. Power Spectral Density Plot Antenna 2a (Bluetooth (HDR4), 4Mbps, iPA – Ch. 1)

FCC ID: BCGA2301 IC: 579C-A2301	<b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 37 of 101




Plot 7-29. Power Spectral Density Plot Antenna 2a (Bluetooth (HDR4), 4Mbps, iPA – Ch. 38)




Plot 7-30. Power Spectral Density Plot Antenna 2a (Bluetooth (HDR4), 4Mbps, iPA – Ch. 73)

FCC ID: BCGA2301 IC: 579C-A2301	<b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 38 of 101




Plot 7-31. Power Spectral Density Plot Antenna 2a (Bluetooth (HDR8), 8Mbps, ePA – Ch. 1)




Plot 7-32. Power Spectral Density Plot Antenna 2a (Bluetooth (HDR8), 8Mbps, ePA – Ch. 38)

FCC ID: BCGA2301 IC: 579C-A2301	<b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 39 of 101




Plot 7-33. Power Spectral Density Plot Antenna 2a (Bluetooth (HDR8), 8Mbps, ePA – Ch. 73)




Plot 7-34. Power Spectral Density Plot Antenna 2a (Bluetooth (HDR8), 8Mbps, iPA – Ch. 1)

FCC ID: BCGA2301 IC: 579C-A2301	<b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 40 of 101



Plot 7-35. Power Spectral Density Plot Antenna 2a (Bluetooth (HDR8), 8Mbps, iPA – Ch. 38)



Plot 7-36. Power Spectral Density Plot Antenna 2a (Bluetooth (HDR8), 8Mbps, iPA – Ch. 73)


FCC ID: BCGA2301 IC: 579C-A2301	<b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 41 of 101

## Tx-BF (Beamforming Mode)


Frequency [MHz]	Data Rate [Mbps]	Power Scheme	Channel No.	Measured Power Spectral Density [dBm / 3kHz]			Maximum Permissible Power Density [dBm / 3kHz]	Margin [dB]
				Antenna 4a	Antenna 2a	Summed		
2404	4.0	ePA	1	-5.79	-6.41	-3.08	8.0	-11.08
2441	4.0	ePA	38	-6.12	-6.37	-3.23	8.0	-11.23
2476	4.0	ePA	73	-6.04	-6.22	-3.12	8.0	-11.12
2404	4.0	iPA	1	-12.28	-11.76	-9.00	8.0	-17.00
2441	4.0	iPA	38	-11.58	-13.06	-9.25	8.0	-17.25
2476	4.0	iPA	73	-12.28	-13.34	-9.77	8.0	-17.77
2404	8.0	ePA	1	-5.21	-6.65	-2.86	8.0	-10.86
2441	8.0	ePA	38	-4.96	-7.01	-2.85	8.0	-10.85
2476	8.0	ePA	73	-4.94	-6.91	-2.80	8.0	-10.80
2404	8.0	iPA	1	-13.60	-13.94	-10.76	8.0	-18.76
2441	8.0	iPA	38	-13.35	-14.18	-10.73	8.0	-18.73
2476	8.0	iPA	73	-13.53	-15.86	-11.53	8.0	-19.53

Table 7-12. Conducted Power Density Measurements TxBF

FCC ID: BCGA2301 IC: 579C-A2301	 <b>PCTEST</b> Proud to be part of element			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device			




Plot 7-37. Power Spectral Density Plot TxBF Antenna 4a (Bluetooth (HDR4), 4Mbps, ePA – Ch. 1)




Plot 7-38. Power Spectral Density Plot TxBF Antenna 2a (Bluetooth (HDR4), 4Mbps, ePA – Ch. 1)

FCC ID: BCGA2301 IC: 579C-A2301	<b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 43 of 101




Plot 7-39. Power Spectral Density Plot TxBF Antenna 4a (Bluetooth (HDR4), 4Mbps, ePA – Ch. 38)




Plot 7-40. Power Spectral Density Plot TxBF Antenna 2a (Bluetooth (HDR4), 4Mbps, ePA – Ch. 38)

FCC ID: BCGA2301 IC: 579C-A2301	<b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 44 of 101




Plot 7-41. Power Spectral Density Plot TxBF Antenna 4a (Bluetooth (HDR4), 4Mbps, ePA – Ch. 73)




Plot 7-42. Power Spectral Density Plot TxBF Antenna 2a (Bluetooth (HDR4), 4Mbps, ePA – Ch. 73)

FCC ID: BCGA2301 IC: 579C-A2301	<b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 45 of 101




Plot 7-43. Power Spectral Density Plot TxBF Antenna 4a (Bluetooth (HDR4), 4Mbps, iPA – Ch. 1)




Plot 7-44. Power Spectral Density Plot TxBF Antenna 2a (Bluetooth (HDR4), 4Mbps, iPA – Ch. 1)

FCC ID: BCGA2301 IC: 579C-A2301	<b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 46 of 101




Plot 7-45. Power Spectral Density Plot TxBF Antenna 4a (Bluetooth (HDR4), 4Mbps, iPA – Ch. 38)




Plot 7-46. Power Spectral Density Plot TxBF Antenna 2a (Bluetooth (HDR4), 4Mbps, iPA – Ch. 38)

FCC ID: BCGA2301 IC: 579C-A2301	<b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 47 of 101




Plot 7-47. Power Spectral Density Plot TxBF Antenna 4a (Bluetooth (HDR4), 4Mbps, iPA – Ch. 73)




Plot 7-48. Power Spectral Density Plot TxBF Antenna 2a (Bluetooth (HDR4), 4Mbps, iPA – Ch. 73)

FCC ID: BCGA2301 IC: 579C-A2301	<b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 48 of 101




Plot 7-49. Power Spectral Density Plot TxBF Antenna 4a (Bluetooth (HDR8), 8Mbps, ePA – Ch. 1)




Plot 7-50. Power Spectral Density Plot TxBF Antenna 2a (Bluetooth (HDR8), 8Mbps, ePA – Ch. 1)

FCC ID: BCGA2301 IC: 579C-A2301	<b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 49 of 101




Plot 7-51. Power Spectral Density Plot TxBF Antenna 4a (Bluetooth (HDR8), 8Mbps, ePA – Ch. 38)




Plot 7-52. Power Spectral Density Plot TxBF Antenna 2a (Bluetooth (HDR8), 8Mbps, ePA – Ch. 38)

FCC ID: BCGA2301 IC: 579C-A2301	<b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 50 of 101




Plot 7-53. Power Spectral Density Plot TxBF Antenna 4a (Bluetooth (HDR8), 8Mbps, ePA – Ch. 73)




Plot 7-54. Power Spectral Density Plot TxBF Antenna 2a (Bluetooth (HDR8), 8Mbps, ePA – Ch. 73)

FCC ID: BCGA2301 IC: 579C-A2301	<b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 51 of 101




Plot 7-55. Power Spectral Density Plot TxBF Antenna 4a (Bluetooth (HDR8), 8Mbps, iPA – Ch. 1)




Plot 7-56. Power Spectral Density Plot TxBF Antenna 2a (Bluetooth (HDR8), 8Mbps, iPA – Ch. 1)

FCC ID: BCGA2301 IC: 579C-A2301	<b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 52 of 101




Plot 7-57. Power Spectral Density Plot TxBF Antenna 4a (Bluetooth (HDR8), 8Mbps, iPA – Ch. 38)




Plot 7-58. Power Spectral Density Plot TxBF Antenna 2a (Bluetooth (HDR8), 8Mbps, iPA – Ch. 38)

FCC ID: BCGA2301 IC: 579C-A2301	<b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 53 of 101



Plot 7-59. Power Spectral Density Plot TxBF Antenna 4a (Bluetooth (HDR8), 8Mbps, iPA – Ch. 73)



Plot 7-60. Power Spectral Density Plot TxBF Antenna 2a (Bluetooth (HDR8), 8Mbps, iPA – Ch. 73)

FCC ID: BCGA2301 IC: 579C-A2301	<b>PCTEST</b> Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 54 of 101

## 7.5 Conducted Authorized Band Edge

§15.247(d); RSS-247 [5.5]

### Test Overview and Limit

For the following out of band conducted spurious emissions plots at the band edge, the EUT was set to transmit at maximum power with the largest packet size available. These settings produced the worst-case emissions.

***The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth.***

### Test Procedure Used

ANSI C63.10-2013 – Section 11.11.3  
 KDB 558074 D01 v05r02 – Section 8.7.2

### Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW = 100kHz
4. VBW = 300kHz
5. Detector = Peak
6. Number of sweep points  $\geq 2 \times \text{Span/RBW}$
7. Trace mode = max hold
8. Sweep time = auto couple
9. The trace was allowed to stabilize

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-4. Test Instrument & Measurement Setup**

### Test Notes

All supported modulation, antennas (including TxBF mode) and power schemes have been tested on the unit and only the worst case configuration is reported.

FCC ID: BCGA2301 IC: 579C-A2301	 <b>PCTEST®</b> Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-11.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 55 of 101	
© 2021 PCTEST				V 9.0 11/16/2020