



DATA REFERENCE REPORT FCC PART 15.247 / ISED RSS-247 Bluetooth

Applicant Name:

Apple Inc.
One Apple Park Way
Cupertino, CA 95014
United States

Date of Testing:

12/15/2020 - 03/03/2021

Test Site/Location:

PCTEST Lab. Morgan Hill, CA, USA

Test Report Serial No.:

1C2101020003-14.BCG

FCC ID:	BCGA2459
IC:	579C-A2459
APPLICANT:	Apple Inc.

Reference Model/HVIN:

A2301

Variant Model/HVIN:

A2459, A2460

EUT Type:

Tablet Device

Frequency Range:

2402 – 2480MHz

Type of Modulation:

GFSK, $\pi/4$ -DQPSK, 8DPSK

FCC Classification:

FCC Part 15 Spread Spectrum Transmitter (DSS)

FCC Rule Part(s):

Part 15 Subpart C (15.247)

ISED Specification:

RSS-247 Issue 2

Test Procedure(s):

ANSI C63.10-2013

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Randy Ortanez
President



FCC ID: BCGA2459 IC: 579C-A2459	PCTEST Proud to be part of element		DATA REFERENCE REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020003-14.BCG	Test Dates: 12/15/2020 - 03/03/2021	EUT Type: Tablet Device	Page 1 of 34	

T A B L E O F C O N T E N T S

1.0	INTRODUCTION	3
1.1	Scope	3
1.2	PCTEST Test Location.....	3
1.3	Test Facility / Accreditations	3
2.0	PRODUCT INFORMATION.....	4
2.1	Equipment Description	4
2.2	Device Capabilities	4
2.3	Antenna Description	6
2.4	Test Support Equipment.....	6
2.5	Test Configuration	7
2.6	Software and Firmware	7
2.7	EMI Suppression Device(s)/Modifications	7
3.0	DESCRIPTION OF TESTS	8
3.1	Evaluation Procedure	8
3.2	Radiated Emissions.....	8
3.3	Environmental Conditions.....	9
4.0	ANTENNA REQUIREMENTS	10
5.0	MEASUREMENT UNCERTAINTY	11
6.0	TEST EQUIPMENT CALIBRATION DATA	12
7.0	TEST RESULTS (SPOT-CHECK DATA)	13
7.1	Summary	13
7.2	Radiated Spurious Emissions.....	14
8.0	TEST RESULTS (ANTENNA 4a)	15
8.1	Summary	15
8.2	Radiated Spurious Emissions – Above 1GHz	16
8.2.1	Radiated Restricted Band Edge Measurements.....	25
9.0	CONCLUSION.....	33
10.0	APPENDIX A: REFERENCE MODEL TEST REPORT.....	34

FCC ID: BCGA2459 IC: 579C-A2459	 PCTEST [®] Proud to be part of 		DATA REFERENCE REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020003-14.BCG	Test Dates: 12/15/2020 - 03/03/2021	EUT Type: Tablet Device	Page 2 of 34	

1.0 INTRODUCTION

1.1 Scope

Per manufacturer declaration, there are two tablet device models, A2301 and A2459(A2460), with high degree of similarity, reference model FCC ID: BCGA2301 / IC: 579C-A2301 and variant model **FCC ID: BCGA2459 / IC: 579C-A2459**. The reference model supports mmWave operations, while the variant model has the mmWave components/antennas removed. Both models share the same material, form factor, circuit design, and components, including antennas and their locations. The reference and variant models use the same power tables and have same tune-up tolerances.

Per FCC/ISED approved Data Referencing Test Plan, testing was done fully on the reference model FCC ID: BCGA2301 / IC: 579C-A2301, while radiated spot-check verification has been performed on variant model **FCC ID: BCGA2459 / IC: 579C-A2459**. Additionally, due to Antenna 4a location being close to the depopulated mmWave components, full radiated testing has been done for all supported technologies on Antenna 4a. Spot-check measurements were conducted, all measurements were investigated and found to be within acceptable tolerance.

Equipment Class	Reference Model FCC ID & IC	Reference Report	Report Title
DTS	BCGA2301 579C-A2301	1C2101020002-13.BCG	RF Bluetooth Test Report

Table 1-1. Reference Model Details

Reference model FCC ID: BCGA2301 / IC: 579C-A2301 test report has been included in Appendix A.

1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST facility located at 18855 Adams Court, Morgan Hill, CA 95037. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014 and KDB 414788 D01 v01r01.

1.3 Test Facility / Accreditations

Measurements were performed at PCTEST located in Morgan Hill, CA 95037, U.S.A.

- PCTEST is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.02 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- PCTEST facility is a registered (22831) test laboratory with the site description on file with ISED.

FCC ID: BCGA2459 IC: 579C-A2459	PCTEST [®] Proud to be part of element		DATA REFERENCE REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020003-14.BCG	Test Dates: 12/15/2020 - 03/03/2021	EUT Type: Tablet Device	Page 3 of 34	

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Apple Tablet Device FCC ID: BCGA2459 / IC: 579C-A2459**. The test data contained in this report pertains only to the emissions due to the EUT's Bluetooth transmitter.

- This Bluetooth module has been tested by manufacturer, and confirmed the following:
 - A) The hopping sequence is pseudorandom
 - B) All channels are used equally on average
 - C) The receiver input bandwidth equals the transmit bandwidth
 - D) The receiver hops in sequence with the transmit signal
- 15.247(g): In accordance with the Bluetooth Industry Standard, the system is designed to comply with all of the regulations in Section 15.247 when the transmitter is presented with a continuous data (or information) system.
- 15.247(h): In accordance with the Bluetooth Industry Standard, the system does not coordinate its channels selection/ hopping sequence with other frequency hopping systems for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters.
- 15.247(h): The EUT employs Adaptive Frequency Hopping (AFH) which identifies sources of interference namely devices operating in 802.11 WLAN and excludes them from the list of available channels. The process of re-mapping reduces the number of test channels from 79 channels to a minimum number of 20 channels.

Test Device Serial No.: DLX0497003G0J801S, DLX0496001Z0J7X1N, QJ59J42G1X, Q5H7X9XL5W

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-Band LTE, 5G NR (FR1), 802.11b/g/n/ax WLAN, 802.11a/n/ac/ax UNII, Bluetooth (1x, EDR, LE1M, LE2M, HDR4, HDR8), WPT

This device supports BT Beamforming

Ch.	Frequency (MHz)
00	2402
:	:
39	2441
:	:
78	2480

Table 2-1. Bluetooth Frequency / Channel Operations

FCC ID: BCGA2459 IC: 579C-A2459	PCTEST [®] Proud to be part of element		DATA REFERENCE REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020003-14.BCG	Test Dates: 12/15/2020 - 03/03/2021	EUT Type: Tablet Device	Page 4 of 34	

Measured Duty Cycles					
Bluetooth Mode		Duty Cycle [%]			
		Antenna 4a	Antenna 2a	TxBF	
GFSK	ePA	100	100	100	
	iPA	100	100	100	
8PSK	ePA	100	100	100	
	iPA	100	100	100	
$\pi/4$ -DQPSK	ePA	100	100	100	
	iPA	100	100	100	

Table 2-2. Measured Duty Cycles

This device supports simultaneous transmission operations, which allows for multiple transmitters to transmit simultaneously on the same antenna. The table below shows all configurations possible.


Antenna	Simultaneous Tx Config	WLAN	Bluetooth	GSM / WCDMA	LTE / FR1 NR			UNII
		802.11 b/g/n/ax	BDR, EDR, HDR4/8, LE1/2M	Mid Band	Mid Band	High Band	Ultra High Band	802.11 a/n/ac/ax
2a	Config 1	✓	✗	✗	✗	✗	✓	✗
2a	Config 2	✗	✓	✗	✗	✗	✓	✗
4a	Config 3	✓	✗	✗	✗	✗	✓	✗
4a	Config 4	✗	✓	✗	✗	✗	✓	✗
4b	Config 5	✗	✗	✓	✗	✗	✗	✓
4b	Config 6	✗	✗	✗	✓	✗	✗	✓
4b	Config 7	✗	✗	✗	✗	✓	✗	✓

Table 2-3. Simultaneous Transmission Configurations

✓ = Support; ✗ = Not Support

Notes:

1. This device is capable of operating in hopping and non-hopping mode. The EUT can hop between 79 different channels in the 2400 – 2483.5MHz band. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = peak per the guidance of Section 6.0 b) of KDB 558074 D01 v05r02 and ANSI C63.10-2013. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

FCC ID: BCGA2459 IC: 579C-A2459	 PCTEST® Proud to be part of 	DATA REFERENCE REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020003-14.BCG	Test Dates: 12/15/2020 - 03/03/2021	EUT Type: Tablet Device	Page 5 of 34

2.3 Antenna Description

Following antenna gains provided by manufacturer were used for testing.

Frequency [GHz]	Antenna Gain (dBi)	
	Antenna 4a	Antenna 2a
2.4	1.5	2.5

Table 2-4. Highest Antenna Gain

2.4 Test Support Equipment

Test Support Equipment List				
1	Apple MacBook Pro w/AC/DC Adapter	Model: A2141 Model: A2166	S/N: C02DV7VKMD6T S/N: N/A	
2	Apple USB-C Cable	Model: Chimp	S/N: 420A57	
3	USB-C Cable w/ AC Adapter	Model: A146 Model: A2305	S/N: N/A S/N: N/A	
4	Apple Pencil	Model: N/A	S/N: GQXYGSXBJKM9	
5	DC Power Supply	Model: KPS3010D	S/N: N/A	

Table 2-5. Test Support Equipment List

FCC ID: BCGA2459 IC: 579C-A2459	PCTEST [®] Proud to be part of element		DATA REFERENCE REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020003-14.BCG	Test Dates: 12/15/2020 - 03/03/2021	EUT Type: Tablet Device		

2.5 Test Configuration

The EUT was tested per the guidance of ANSI C63.10-2013. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions. See Sections 3.2 for radiated emissions test setups.

There are two vendors of the WiFi/Bluetooth radio modules, variant 1 and variant 2. Both radio modules have the same mechanical outline, same on-board antenna matching circuit, identical antenna structure, and are built and tested to conform to the same specifications and to operate within the same tolerances. The worst case configuration was found between the two variants. The EUT was also investigated with and without charger.

For emissions from 1GHz – 18GHz, low, mid, and high channels were tested with highest power and worst case configuration. The emissions below 1GHz and above 18GHz were tested with the highest transmitting power and the worst case channel.

The EUT was manipulated through three orthogonal planes of X-orientation (flatbed), Y-orientation (landscape), and Z-orientation (portrait) during the testing. Only the worst case emissions were reported in this test report.

Per FCC/ISED Approved Data Referencing Test Plan, Antenna 4a radiated testing and spot-check measurements have been conducted and reported. Bluetooth (BDR, EDR, LE, HDR) Spot-check Test Plan can be referred to below Table 2-6.

Technology	Test Case	FCC ID: BCGA2459 IC: 579C-A2459	
		Mode	Channel
BT (BDR, EDR, LE, HDR)	Radiated Spurious Emissions	Max Power Only ePA: GFSK	M

Table 2-6. FCC/ISED Approved Data Referencing Test Plan

Output powers were measured and confirmed to be consistent between Reference and Variant models prior to testing.

2.6 Software and Firmware

The test was conducted with firmware version 18E20700y installed on the EUT.

2.7 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

FCC ID: BCGA2459 IC: 579C-A2459	PCTEST [®] Proud to be part of element		DATA REFERENCE REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020003-14.BCG	Test Dates: 12/15/2020 - 03/03/2021	EUT Type: Tablet Device		Page 7 of 34

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedure described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013) was used in the measurement of the EUT.

Deviation from measurement procedure.....None

3.2 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

Per KDB 414788, radiated emission test sites other than open-field test sites (e.g., shielded anechoic chambers), may be employed for emission measurements below 30MHz if characterized so that the measurements correspond to those obtained at an open-field test site. To determine test site equivalency, a reference sample transmitting at 149kHz was measured on an open field test site (asphalt with no ground plane) and then measured in the 3m semi-anechoic chamber. A calibrated 60cm loop antenna was rotated about its vertical axis while the reference device was rotated through the X, Y and Z axis in order to capture the worst case level. A maximum deviation of 2.77dB at 149kHz was measured when comparing the 3 meter semi-anechoic chamber to the open field site.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33 depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

FCC ID: BCGA2459 IC: 579C-A2459	 PCTEST[®] Proud to be part of element		DATA REFERENCE REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020003-14.BCG	Test Dates: 12/15/2020 - 03/03/2021	EUT Type: Tablet Device		Page 8 of 34

3.3 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: BCGA2459 IC: 579C-A2459	 PCTEST [®] Proud to be part of  element		DATA REFERENCE REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020003-14.BCG	Test Dates: 12/15/2020 - 03/03/2021	EUT Type: Tablet Device	Page 9 of 34	

4.0 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna(s) of the EUT are **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The EUT complies with the requirement of §15.203.

FCC ID: BCGA2459 IC: 579C-A2459	 PCTEST Proud to be part of  element		DATA REFERENCE REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020003-14.BCG	Test Dates: 12/15/2020 - 03/03/2021	EUT Type: Tablet Device	Page 10 of 34	

5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.23-2012. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (\pm dB)
Radiated Disturbance (<30MHz)	4.06
Radiated Disturbance (30MHz - 1GHz)	4.30
Radiated Disturbance (1 - 18GHz)	4.78
Radiated Disturbance (>18GHz)	4.79

FCC ID: BCGA2459 IC: 579C-A2459	 PCTEST [®] Proud to be part of element	DATA REFERENCE REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020003-14.BCG	Test Dates: 12/15/2020 - 03/03/2021	EUT Type: Tablet Device	Page 11 of 34

6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent Technologies	N9030A	PXA Signal Analyzer (3Hz - 26.5 GHz)	7/24/2020	Annual	7/24/2021	MY49430244
Anritsu	ML2496A	Power Meter	4/9/2020	Annual	4/9/2021	2002005
Anritsu	MA2411B	Pulse Power Sensor	11/10/2020	Annual	11/10/2021	1726261
Anritsu	MA2411B	Pulse Power Sensor	12/9/2020	Annual	12/9/2021	1726262
ATM	180-442A-KF	20dB Nominal Gain Horn Antenna	8/11/2020	Annual	8/11/2021	T058701-01
Rohde & Schwarz	TS-PR8	Pre-Amplifier (30MHz - 8GHz)	12/3/2020	Annual	12/3/2021	102328
ETS-Lindgren	3142E	BiConiLog Antenna (30MHz - 6GHz)	9/15/2020	Annual	9/15/2021	208204
ETS-Lindgren	3117	Double Ridged Guide Antenna (1-18 GHz)	4/21/2020	Annual	4/21/2021	205956
Rohde & Schwarz	ESW26	EMI Test Receiver	6/1/2020	Annual	6/1/2021	101299
Rohde & Schwarz	ESW44	EMI Test Receiver	8/7/2020	Annual	8/7/2021	101668
Rohde & Schwarz	TS-PR1840	Pre-Amplifier (18GHz - 40GHz)	4/3/2020	Annual	4/3/2021	100052
Rohde & Schwarz	TC-TA18	Cross Polarized Vivaldi Antenna (400MHz-18GHz)	10/2/2020	Annual	10/2/2021	101063
Rohde & Schwarz	HFH2-Z2	Loop Antenna	3/12/2020	Annual	3/12/2021	100546
Rohde & Schwarz	TS-PR18	Pre-Amplifier (1GHz - 18GHz)	12/3/2020	Annual	12/3/2021	101648
Rohde & Schwarz	ENV216	Two-Line V-Network (LISN)	12/7/2020	Annual	12/7/2021	101364

Table 6-1. Test Equipment List

Note:

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

FCC ID: BCGA2459 IC: 579C-A2459	 PCTEST[®] Proud to be part of element			DATA REFERENCE REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020003-14.BCG	Test Dates: 12/15/2020 - 03/03/2021	EUT Type: Tablet Device			

7.0 TEST RESULTS (SPOT-CHECK DATA)

7.1 Summary

Company Name: Apple Inc.
 FCC ID: BCGA2459
 IC: 579C-A2459
 FCC Classification: Frequency Hopping Spread Spectrum (FHSS)
 Number of Channels: 79

Technology	Test Configurations					Reference Model	Variant Model	Delta
	Test Description	Data Rate [Mbps]	Power Scheme	Channel	Measurement Frequency [MHz]	FCC ID: BCGA2301 IC: 579C-A2301	FCC ID: BCGA2459 IC: 579C-A245959	
						Peak [dB μ V/m]	Peak [dB μ V/m]	
Bluetooth	Radiated Spurious Emissions	1.0	ePA	39	4882	45.39	45.71	0.32


Table 7-1. Worst Case Spot-check Results

Spot-checks were conducted, all measurements were investigated and found to be within acceptable tolerance in accordance with FCC/ISED Approved Data Referencing Test Plan.

FCC ID: BCGA2459 IC: 579C-A2459	 DATA REFERENCE REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1C2101020003-14.BCG	Test Dates: 12/15/2020 - 03/03/2021	EUT Type: Tablet Device	Page 13 of 34	

7.2 Radiated Spurious Emissions

§15.205 §15.209 §15.247(d); RSS-Gen [8.9]




Plot 7-1: Radiated Spurious Emissions above 1GHz TxBF (BT GFSK ePA – Ch. 39)

Bluetooth Mode:	<u>Bluetooth</u>
Worst Case Data Rate	<u>1 Mbps</u>
Distance of Measurements:	<u>3 Meters</u>
Operating Frequency:	<u>2441MHz</u>
Channel:	<u>39</u>

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4882.00	Peak	H	-	-	-67.36	6.07	45.71	73.98	-28.27
7323.00	Peak	H	-	-	-67.54	8.60	48.06	73.98	-25.92
12205.00	Peak	H	-	-	-70.51	15.25	51.74	73.98	-22.24

Table 7-2: Radiated Measurements TxBF

FCC ID: BCGA2459 IC: 579C-A2459	 PCTEST® Proud to be part of 	DATA REFERENCE REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1C2101020003-14.BCG	Test Dates: 12/15/2020 - 03/03/2021	EUT Type: Tablet Device			

8.0 TEST RESULTS (ANTENNA 4a)

8.1 Summary

Company Name: Apple Inc.
 FCC ID: BCGA2459
 IC: 579C-A2459
 FCC Classification: Frequency Hopping Spread Spectrum (FHSS)
 Number of Channels: 79

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.205 15.209	RSS-Gen [8.9]	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-Gen [8.9])	RADIATED	PASS	Sections 8.2

Table 8-1. Summary of Test Results

Notes:

1. All modes of operation were investigated. The test results shown in the following sections represent the worst case emissions.
2. For radiated band edge, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "Chamber Automation," Version 1.3.1.
3. Radiated test results in following sections has been conducted on Antenna 4a, per FCC/ISED Approved Data Referencing Test Plan.
4. Below 1GHz and Above 18GHz Radiated Spurious Emissions have been investigated and no significant emissions were found.

FCC ID: BCGA2459 IC: 579C-A2459	PCTEST [®] Proud to be part of element			DATA REFERENCE REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020003-14.BCG	Test Dates: 12/15/2020 - 03/03/2021	EUT Type: Tablet Device			

8.2 Radiated Spurious Emissions – Above 1GHz

§15.205 §15.209 §15.247(d); RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at maximum power and at the appropriate frequencies. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 7 of RSS-Gen (8.10) must not exceed the limits shown in Table 8-2 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [μ V/m]	Measured Distance [Meters]
Above 960.0 MHz	500	3

Table 8-2. Radiated Limits

Test Procedures Used

ANSI C63.10-2013 – Section 6.6.4.3

Test Settings

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: BCGA2459 IC: 579C-A2459	 PCTEST [®] Proud to be part of element	DATA REFERENCE REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020003-14.BCG	Test Dates: 12/15/2020 - 03/03/2021	EUT Type: Tablet Device	Page 16 of 34

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 8-1. Radiated Test Setup >1GHz

Test Notes

1. All emissions lying in restricted bands specified in §15.205 and Section 8.10 of RSS-Gen are below the limit shown in Table 8-2.
2. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
3. This unit was tested with its standard battery.
4. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas.
5. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section.
6. D is the measurement test distance and emissions 1-18GHz were measured at a 3 meters test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
7. The "-" shown in the following RSE tables are used to denote a noise floor measurement.
8. All supported modulation, antenna (including TxBF mode) and power schemes have been tested on the unit and only worst case configuration is reported.
9. Average emissions were not reported since the duty cycle correction factor was greater than 20dB.

FCC ID: BCGA2459 IC: 579C-A2459	 PCTEST® Proud to be part of 	DATA REFERENCE REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020003-14.BCG	Test Dates: 12/15/2020 - 03/03/2021	EUT Type: Tablet Device	Page 17 of 34

Sample Calculation

- Field Strength Level [$\text{dB}_{\mu\text{V/m}}$] = Analyzer Level [dBm] + 107 + AFCL [dB/m]
- AFCL [dB/m] = Antenna Factor [dB/m] + Cable Loss [dB] – Preamplifier Gain [dB]
- Margin [dB] = Field Strength Level [$\text{dB}_{\mu\text{V/m}}$] – Limit [$\text{dB}_{\mu\text{V/m}}$]

Duty Cycle Correction Factor Calculation

- Channel hop rate = 800 hops/second (AFH Mode)
- Adjusted channel hop rate for DH5 mode = 133.33 hops/second
- Time per channel hop = 1 / 133.33 hops/second = 7.50 ms
- Time to cycle through all channels = 7.50 x 20 channels = 150 ms
- Number of times transmitter hits on one channel = 100 ms / 150 ms = 1 time(s)
- Worst case dwell time = 7.5 ms

Duty cycle correction factor = $20\log_{10}(7.5\text{ms}/100\text{ms}) = -22.5 \text{ dB}$

Average Emission Calculation


- Average Emission = Measured Peak Emissions [$\text{dB}_{\mu\text{V/m}}$] – Duty Cycle Correction Factor [dB]

FCC ID: BCGA2459 IC: 579C-A2459	 PCTEST[®] Proud to be part of element	DATA REFERENCE REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020003-14.BCG	Test Dates: 12/15/2020 - 03/03/2021	EUT Type: Tablet Device	Page 18 of 34

Radiated Spurious Emission Measurements (1 – 18GHz)

§15.205 §15.209 §15.247(d); RSS-Gen [8.9]

Antenna 4a





Plot 8-1. Radiated Spurious Emissions Above 1GHz Antenna 4a (BT GFSK ePA – Ch. 0)

Bluetooth Mode:	Bluetooth
Worst Case Data Rate	1 Mbps
Distance of Measurements:	3 Meters
Operating Frequency:	2402MHz
Channel:	0

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4804.00	Peak	H	109	159	-65.93	9.09	50.16	73.98	-23.82
12010.00	Peak	H	-	-	-73.03	21.24	55.21	73.98	-18.76

Table 8-3. Radiated Measurements Antenna 4a

FCC ID: BCGA2459 IC: 579C-A2459	 PCTEST® Proud to be part of 				DATA REFERENCE REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1C2101020003-14.BCG	Test Dates: 12/15/2020 - 03/03/2021	EUT Type: Tablet Device					Page 19 of 34	





Plot 8-2. Radiated Spurious Emissions Above 1GHz Antenna 4a (BT GFSK ePA – Ch. 39)

Bluetooth Mode:	Bluetooth
Worst Case Data Rate	1 Mbps
Distance of Measurements:	3 Meters
Operating Frequency:	2441MHz
Channel:	39

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
4882.00	Peak	H	-	-	-70.74	9.49	45.75	73.98	-28.23
7323.00	Peak	H	-	-	-72.65	13.93	48.28	73.98	-25.70
12205.00	Peak	H	-	-	-73.43	21.40	54.97	73.98	-19.00

Table 8-4. Radiated Measurements Antenna 4a

FCC ID: BCGA2459 IC: 579C-A2459	 PCTEST® Proud to be part of 			DATA REFERENCE REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020003-14.BCG	Test Dates: 12/15/2020 - 03/03/2021	EUT Type: Tablet Device			




Plot 8-3. Radiated Spurious Emissions Above 1GHz Antenna 4a (BT GFSK ePA – Ch. 78)

Bluetooth Mode:	Bluetooth
Worst Case Data Rate	1 Mbps
Distance of Measurements:	3 Meters
Operating Frequency:	2480MHz
Channel:	78

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
4960.00	Peak	V	257	190	-69.79	9.41	46.62	73.98	-27.36
7440.00	Peak	V	-	-	-72.55	14.77	49.22	73.98	-24.76
12400.00	Peak	V	-	-	-74.41	21.89	54.48	73.98	-19.50


Table 8-5. Radiated Measurements Antenna 4a

FCC ID: BCGA2459 IC: 579C-A2459	 PCTEST® Proud to be part of 			DATA REFERENCE REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020003-14.BCG	Test Dates: 12/15/2020 - 03/03/2021	EUT Type: Tablet Device			

Radiated Spurious Emission Measurements (Above 1GHz)

§15.205 §15.209 §15.247(d); RSS-Gen [8.9]

TxBF




Plot 8-4. Radiated Spurious Emissions Above 1GHz TxBF (BT GFSK ePA – Ch. 0)

Bluetooth Mode:	Bluetooth
Worst Case Data Rate	1 Mbps
Distance of Measurements:	3 Meters
Operating Frequency:	2402MHz
Channel:	0

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4804.00	Peak	H	-	-	-67.28	5.80	45.52	73.98	-28.46
12010.00	Peak	H	-	-	-71.20	15.47	51.27	73.98	-22.71

Table 8-6. Radiated Measurements TxBF

FCC ID: BCGA2459 IC: 579C-A2459	PCTEST® Proud to be part of 				DATA REFERENCE REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020003-14.BCG	Test Dates: 12/15/2020 - 03/03/2021	EUT Type: Tablet Device				




Plot 8-5. Radiated Spurious Emissions Above 1GHz TxBF (BT GFSK ePA – Ch. 39)

Bluetooth Mode: Bluetooth
 Worst Case Data Rate 1 Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 2441MHz
 Channel: 39

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
4882.00	Peak	H	-	-	-67.36	6.07	45.71	73.98	-28.27
7323.00	Peak	H	-	-	-67.54	8.60	48.06	73.98	-25.92
12205.00	Peak	H	-	-	-70.51	15.25	51.74	73.98	-22.24

Table 8-7. Radiated Measurements TxBF

FCC ID: BCGA2459 IC: 579C-A2459	 DATA REFERENCE REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1C2101020003-14.BCG	Test Dates: 12/15/2020 - 03/03/2021	EUT Type: Tablet Device	Page 23 of 34	



Plot 8-6. Radiated Spurious Emissions Above 1GHz TxBF (BT GFSK ePA – Ch. 78)

Bluetooth Mode: Bluetooth
 Worst Case Data Rate 1 Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 2480MHz
 Channel: 78

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
4960.00	Peak	H	-	-	-67.34	5.97	45.63	73.98	-28.35
7440.00	Peak	H	-	-	-68.29	8.97	47.68	73.98	-26.30
12400.00	Peak	H	-	-	-71.35	16.12	51.77	73.98	-22.21

Table 8-8. Radiated Measurements TxBF

FCC ID: BCGA2459 IC: 579C-A2459	 DATA REFERENCE REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1C2101020003-14.BCG	Test Dates: 12/15/2020 - 03/03/2021	EUT Type: Tablet Device	Page 24 of 34	

8.2.1 Radiated Restricted Band Edge Measurements


§15.205 §15.209; RSS-Gen [8.9]

Antenna 4a

The amplitude offset shown in the following plots for average measurements was calculated using the formula:

$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + \text{Attenuator}) - \text{Preamplifier Gain}$$

Mode:	Bluetooth-Antenna 4a
Modulation:	GFSK
Worst Case Power Scheme:	ePA
Measurement Distance:	3 Meters
Operating Frequency:	2402MHz
Channel:	0



Plot 8-7. Radiated Restricted Lower Band Edge Measurement Antenna 4a (Average & Peak)

FCC ID: BCGA2459 IC: 579C-A2459	 PCTEST® Proud to be part of 	DATA REFERENCE REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020003-14.BCG	Test Dates: 12/15/2020 - 03/03/2021	EUT Type: Tablet Device	Page 25 of 34


Radiated Restricted Band Edge Measurements

§15.205 §15.209; RSS-Gen [8.9]

The amplitude offset shown in the following plots for average measurements was calculated using the formula:

Offset (dB) = (Antenna Factor + Cable Loss + Attenuator) – Preamplifier Gain

Mode:	Bluetooth-Antenna 4a
Modulation:	8DPSK
Worst Case Power Scheme:	ePA
Measurement Distance:	3 Meters
Operating Frequency:	2402MHz
Channel:	0



Plot 8-8. Radiated Restricted Lower Band Edge Measurement Antenna 4a (Average & Peak)

FCC ID: BCGA2459 IC: 579C-A2459	 PCTEST® Proud to be part of  element		DATA REFERENCE REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020003-14.BCG	Test Dates: 12/15/2020 - 03/03/2021	EUT Type: Tablet Device	Page 26 of 34	


Radiated Restricted Band Edge Measurements

§15.205 §15.209; RSS-Gen [8.9]

The amplitude offset shown in the following plots for average measurements was calculated using the formula:

Offset (dB) = (Antenna Factor + Cable Loss + Attenuator) – Preamplifier Gain

Mode:	Bluetooth-Antenna 4a
Modulation:	GFSK
Worst Case Power Scheme:	ePA
Measurement Distance:	3 Meters
Operating Frequency:	2480MHz
Channel:	78



Plot 8-9. Radiated Restricted Upper Band Edge Measurement Antenna 4a (Average & Peak)

FCC ID: BCGA2459 IC: 579C-A2459	 PCTEST® Proud to be part of 	DATA REFERENCE REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020003-14.BCG	Test Dates: 12/15/2020 - 03/03/2021	EUT Type: Tablet Device	Page 27 of 34


Radiated Restricted Band Edge Measurements

§15.205 §15.209; RSS-Gen [8.9]

The amplitude offset shown in the following plots for average measurements was calculated using the formula:

Offset (dB) = (Antenna Factor + Cable Loss + Attenuator) – Preamplifier Gain

Mode:	Bluetooth-Antenna 4a
Modulation:	8DPSK
Worst Case Power Scheme:	ePA
Measurement Distance:	3 Meters
Operating Frequency:	2480MHz
Channel:	78



Plot 8-10. Radiated Restricted Upper Band Edge Measurement Antenna 4a (Average & Peak)

FCC ID: BCGA2459 IC: 579C-A2459	 PCTEST® Proud to be part of 	DATA REFERENCE REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020003-14.BCG	Test Dates: 12/15/2020 - 03/03/2021	EUT Type: Tablet Device	Page 28 of 34

Radiated Restricted Band Edge Measurements


§15.205 §15.209; RSS-Gen [8.9]

TxBF

The amplitude offset shown in the following plots for average measurements was calculated using the formula:

$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + \text{Attenuator}) - \text{Preamplifier Gain}$$

Mode:	Bluetooth-TxBF
Modulation:	GFSK
Worst Case Power Scheme:	ePA
Measurement Distance:	3 Meters
Operating Frequency:	2402MHz
Channel:	0



Plot 8-11. Radiated Restricted Lower Band Edge Measurement TxBF (Average & Peak)

FCC ID: BCGA2459 IC: 579C-A2459	 PCTEST® Proud to be part of 	DATA REFERENCE REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020003-14.BCG	Test Dates: 12/15/2020 - 03/03/2021	EUT Type: Tablet Device	Page 29 of 34


Radiated Restricted Band Edge Measurements

§15.205 §15.209; RSS-Gen [8.9]

The amplitude offset shown in the following plots for average measurements was calculated using the formula:

Offset (dB) = (Antenna Factor + Cable Loss + Attenuator) – Preamplifier Gain

Mode:	Bluetooth-TxBF
Modulation:	8DPSK
Worst Case Power Scheme:	ePA
Measurement Distance:	3 Meters
Operating Frequency:	2402MHz
Channel:	0



Plot 8-12. Radiated Restricted Lower Band Edge Measurement TxBF (Average & Peak)

FCC ID: BCGA2459 IC: 579C-A2459	 PCTEST® Proud to be part of  element	DATA REFERENCE REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020003-14.BCG	Test Dates: 12/15/2020 - 03/03/2021	EUT Type: Tablet Device	Page 30 of 34


Radiated Restricted Band Edge Measurements

§15.205 §15.209; RSS-Gen [8.9]

The amplitude offset shown in the following plots for average measurements was calculated using the formula:

Offset (dB) = (Antenna Factor + Cable Loss + Attenuator) – Preamplifier Gain

Mode:	Bluetooth-TxBF
Modulation:	GFSK
Worst Case Power Scheme:	ePA
Measurement Distance:	3 Meters
Operating Frequency:	2480MHz
Channel:	78



Plot 8-13. Radiated Restricted Upper Band Edge Measurement TxBF (Average & Peak)

FCC ID: BCGA2459 IC: 579C-A2459	 PCTEST® Proud to be part of 		DATA REFERENCE REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020003-14.BCG	Test Dates: 12/15/2020 - 03/03/2021	EUT Type: Tablet Device	Page 31 of 34	


Radiated Restricted Band Edge Measurements

§15.205 §15.209; RSS-Gen [8.9]

The amplitude offset shown in the following plots for average measurements was calculated using the formula:

Offset (dB) = (Antenna Factor + Cable Loss + Attenuator) – Preamplifier Gain

Mode:	Bluetooth-TxBF
Modulation:	8DPSK
Worst Case Power Scheme:	ePA
Measurement Distance:	3 Meters
Operating Frequency:	2480MHz
Channel:	78



Plot 8-14. Radiated Restricted Upper Band Edge Measurement TxBF (Average & Peak)

FCC ID: BCGA2459 IC: 579C-A2459	 PCTEST® Proud to be part of 		DATA REFERENCE REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020003-14.BCG	Test Dates: 12/15/2020 - 03/03/2021	EUT Type: Tablet Device	Page 32 of 34	

9.0 CONCLUSION

The spot-check data measured for variant model **FCC ID: BCGA2459 / IC: 579C-A2459** is in tolerance with reference model FCC ID: BCGA2301 / IC: 579C-A2301 per FCC/ISED Approved Data Referencing Test Plan. Additionally, Antenna 4a radiated testing has been fully conducted and results were found in compliance with Part 15 Subpart C (15.247) of the FCC Rules and RSS-247 of the Innovation, Science and Economic Development Canada Rules.

FCC ID: BCGA2459 IC: 579C-A2459	PCTEST [®] Proud to be part of element		DATA REFERENCE REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020003-14.BCG	Test Dates: 12/15/2020 - 03/03/2021	EUT Type: Tablet Device	Page 33 of 34	

10.0 APPENDIX A: REFERENCE MODEL TEST REPORT

Attached is the test report (1C2101020002-13.BCG) from reference model FCC ID: BCGA2301 / IC: 579C-A2301, which includes referenced data results.

FCC ID: BCGA2459 IC: 579C-A2459	 PCTEST [®] Proud to be part of 		DATA REFERENCE REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020003-14.BCG	Test Dates: 12/15/2020 - 03/03/2021	EUT Type: Tablet Device		Page 34 of 34



MEASUREMENT REPORT FCC PART 15.247 / ISED RSS-247 Bluetooth

Applicant Name:

Apple Inc.
One Apple Park Way
Cupertino, CA 95014
United States

Date of Testing:

12/15/2020-2/25/2021

Test Site/Location:

PCTEST Lab. Morgan Hill, CA, USA

Test Report Serial No.:

1C2101020002-13.BCG

FCC ID:	BCGA2301
IC:	579C-A2301
APPLICANT:	Apple Inc.

Application Type:	Certification
Mode/HVIN:	A2301
EUT Type:	Tablet Device
Max. RF Output Power:	73.961 mW (18.69dBm) Peak Conducted
Frequency Range:	2402 – 2480MHz
Type of Modulation:	GFSK, $\pi/4$ -DQPSK, 8DPSK
FCC Classification:	FCC Part 15 Spread Spectrum Transmitter (DSS)
FCC Rule Part(s):	Part 15 Subpart C (15.247)
ISED Specification:	RSS-247 Issue 2
Test Procedure(s):	ANSI C63.10-2013

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Randy Ortanez
President



FCC ID: BCGA2301 IC: 579C-A2301	PCTEST Proud to be part of element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021		EUT Type: Tablet Device	Page 1 of 91

T A B L E O F C O N T E N T S

1.0	INTRODUCTION	3
1.1	Scope	3
1.2	PCTEST Test Location.....	3
1.3	Test Facility / Accreditations	3
2.0	PRODUCT INFORMATION.....	4
2.1	Equipment Description	4
2.2	Device Capabilities	4
2.3	Antenna Description	6
2.4	Test Support Equipment.....	6
2.5	Test Configuration	6
2.6	Software and Firmware	7
2.7	EMI Suppression Device(s)/Modifications	7
3.0	DESCRIPTION OF TESTS	8
3.1	Evaluation Procedure	8
3.2	AC Line Conducted Emissions	8
3.3	Radiated Emissions.....	9
3.4	Environmental Conditions.....	9
4.0	ANTENNA REQUIREMENTS	10
5.0	MEASUREMENT UNCERTAINTY	11
6.0	TEST EQUIPMENT CALIBRATION DATA	12
7.0	TEST RESULTS.....	13
7.1	Summary	13
7.2	Bandwidth Measurement.....	14
7.3	Output Power Measurement.....	24
7.3.1	Peak Output Power Measurement.....	25
7.3.2	Average Output Power Measurement	26
7.4	Conducted Authorized Band Edge	28
7.5	Carrier Frequency Separation	37
7.6	Time of Occupancy.....	42
7.7	Number of Hopping Channels	46
7.8	Conducted Spurious Emissions.....	51
7.9	Radiated Spurious Emissions – Above 1GHz	58
7.10	Radiated Restricted Band Edge Measurements.....	71
7.11	Radiated Spurious Emissions – Below 1GHz.....	83
7.12	AC Line-Conducted Emissions Measurement	87
8.0	CONCLUSION.....	91

FCC ID: BCGA2301 IC: 579C-A2301	 PCTEST [®] Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 2 of 91

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST facility located at 18855 Adams Court, Morgan Hill, CA 95037. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014 and KDB 414788 D01 v01r01.

1.3 Test Facility / Accreditations

Measurements were performed at PCTEST located in Morgan Hill, CA 95037, U.S.A.

- PCTEST is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.02 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- PCTEST facility is a registered (22831) test laboratory with the site description on file with ISED.

FCC ID: BCGA2301 IC: 579C-A2301	 PCTEST Proud to be part of  element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 3 of 91	

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Apple Tablet Device FCC ID: BCGA2301, IC: 579C-A2301**. The test data contained in this report pertains only to the emissions due to the EUT's Bluetooth transmitter.

- This Bluetooth module has been tested by manufacturer, and confirmed the following:
 - A) The hopping sequence is pseudorandom
 - B) All channels are used equally on average
 - C) The receiver input bandwidth equals the transmit bandwidth
 - D) The receiver hops in sequence with the transmit signal
- 15.247(g): In accordance with the Bluetooth Industry Standard, the system is designed to comply with all of the regulations in Section 15.247 when the transmitter is presented with a continuous data (or information) system.
- 15.247(h): In accordance with the Bluetooth Industry Standard, the system does not coordinate its channels selection/ hopping sequence with other frequency hopping systems for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters.
- 15.247(h): The EUT employs Adaptive Frequency Hopping (AFH) which identifies sources of interference namely devices operating in 802.11 WLAN and excludes them from the list of available channels. The process of re-mapping reduces the number of test channels from 79 channels to a minimum number of 20 channels.

Test Device Serial No.: LGXMHP6X6Y, JDP7MWF160, NQ73CFK6VJ, VTXRQ6J9MW

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, 5G NR (FR1/FR2), 802.11b/g/n/ax WLAN, 802.11a/n/ac/ax UNII, Bluetooth (1x, EDR, LE1M, LE2M, HDR4, HDR8), WPT

This device supports BT Beamforming.

Ch.	Frequency (MHz)
00	2402
:	:
39	2441
:	:
78	2480

Table 2-1. Bluetooth Frequency/ Channel Operations

FCC ID: BCGA2301 IC: 579C-A2301	 PCTEST [®] Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 4 of 91

Notes:

1. This device is capable of operating in hopping and non-hopping mode. The EUT can hop between 79 different channels in the 2400 – 2483.5MHz band. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = peak per the guidance of Section 6.0 b) of KDB 558074 D01 v05r02 and ANSI C63.10-2013. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Measured Duty Cycles					
Bluetooth Mode		Duty Cycle [%]			
		Antenna 4a	Antenna 2a	TxBF	
GFSK	ePA	100	100	100	100
	iPA	100	100	100	100
8PSK	ePA	100	100	100	100
	iPA	100	100	100	100
$\pi/4$ -DQPSK	ePA	100	100	100	100
	iPA	100	100	100	100

Table 2-2. Measured Duty Cycles

This device supports simultaneous transmission operations, which allows for multiple transmitters to transmit simultaneously on the same antenna. The table below shows all configurations possible.

Antenna	Simultaneous Tx Config	WLAN	Bluetooth	GSM / WCDMA	LTE / FR1 NR			UNII
		802.11 b/g/n/ax	BDR, EDR, HDR4/8, LE1M/2M	Mid Band	Mid Band	High Band	Ultra High Band	802.11 a/n/ac/ax
2a	Config 1	✓	✗	✗	✗	✗	✓	✗
2a	Config 2	✗	✓	✗	✗	✗	✓	✗
4a	Config 3	✓	✗	✗	✗	✗	✓	✗
4a	Config 4	✗	✓	✗	✗	✗	✓	✗
4b	Config 5	✗	✗	✓	✗	✗	✗	✓
4b	Config 6	✗	✗	✗	✓	✗	✗	✓
4b	Config 7	✗	✗	✗	✗	✓	✗	✓

Table 2-3. Simultaneous Transmission Configurations

✓ = Support; ✗ = Not Support

Note:

All the above simultaneous transmission configurations have been tested and the worst case configuration was found to be Config 6 and reported in UNII OFDMA and FCC part 27b test reports.

FCC ID: BCGA2301 IC: 579C-A2301	 PCTEST® Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 5 of 91

2.3 Antenna Description

Following antenna gains provided by manufacturer were used for the testing.

Frequency [GHz]	Antenna Gain (dBi)	
	Antenna 4a	Antenna 2a
2.4	1.5	2.5

Table 2-4. Highest Antenna Gain

2.4 Test Support Equipment

1	Apple MacBook Pro w/AC/DC Adapter	Model: A2141 Model: A2166	S/N: C02DV7VKMD6T S/N: N/A
2	Apple USB-C Cable	Model: Chimp	S/N: 420A57
3	USB-C Cable w/ AC Adapter	Model: A146 Model: A2305	S/N: N/A S/N: N/A
4	Apple Pencil	Model: N/A	S/N: GQXYGSXBJKM9
5	DC Power Supply	Model: KPS3010D	S/N: N/A

Table 2-5. Test Support Equipment List

2.5 Test Configuration

The EUT was tested per the guidance of ANSI C63.10-2013. ANSI C63.10-2013 was also used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See Sections 3.2 for AC line conducted emissions test setups, 3.3 for radiated emissions test setups, and 7.2, 7.3, 7.4, 7.5, 7.6, 7.7, and 7.8 for antenna port conducted emissions test setups.

There are two vendors of the WiFi/Bluetooth radio modules, variant 1 and variant 2. Both radio modules have the same mechanical outline, same on-board antenna matching circuit, identical antenna structure, and are built and tested to conform to the same specifications and to operate within the same tolerances. The worst case configuration was found between the two variants. The EUT was also investigated with and without charger.

For emissions from 1GHz – 18GHz, low, mid, and high channels were tested with highest power and worst case configuration. The emissions below 1GHz and above 18GHz were tested with the highest transmitting power and the worst case channel.

The EUT was manipulated through three orthogonal planes of X-orientation (flatbed), Y-orientation (landscape), and Z-orientation (portrait) during the testing. Only the worst case emissions were reported in this test report.

For AC line conducted and radiated test below 1GHz, following configuration were investigated and EUT powered by AC/DC was the worst case.

- EUT powered by AC/DC adaptor via USB-C cable with wire charger
- EUT powered by host PC via USB-C cable with wire charger

π/4-DQPSK has been investigated and confirmed as not the worst case.

FCC ID: BCGA2301 IC: 579C-A2301	 PCTEST Proud to be part of element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 6 of 91	

2.6 Software and Firmware

The test was conducted with firmware version 18E20700y installed on the EUT.

2.7 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: BCGA2301 IC: 579C-A2301	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 7 of 91

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedure described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013) was used in the measurement of the EUT.

Deviation from measurement procedure.....None

3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 7m x 3.66m x 2.7m shielded enclosure. The shielded enclosure is manufactured by AP Americas. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50µH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is an EPCOS 2X60A Power Line Filter (100dB Attenuation, 14kHz-18GHz) and the two EPCOs 2X48A filters (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that the cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 7.12. Automated test software was used to perform the AC line conducted emissions testing. Automated measurement software utilized is Rohde & Schwarz EMC32, Version 10.50.40.

FCC ID: BCGA2301 IC: 579C-A2301	 PCTEST[®] Proud to be part of element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device		Page 8 of 91

3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

Per KDB 414788, radiated emission test sites other than open-field test sites (e.g., shielded anechoic chambers), may be employed for emission measurements below 30MHz if characterized so that the measurements correspond to those obtained at an open-field test site. To determine test site equivalency, a reference sample transmitting at 149kHz was measured on an open field test site (asphalt with no ground plane) and then measured in the 3m semi-anechoic chamber. A calibrated 60cm loop antenna was rotated about its vertical axis while the reference device was rotated through the X, Y and Z axis in order to capture the worst case level. A maximum deviation of 2.77dB at 149kHz was measured when comparing the 3 meter semi-anechoic chamber to the open field site.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33 depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: BCGA2301 IC: 579C-A2301	 PCTEST [®] Proud to be part of element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 9 of 91	

4.0 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

- The antennas of the EUT are **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The EUT complies with the requirement of §15.203.

FCC ID: BCGA2301 IC: 579C-A2301	 PCTEST [®] Proud to be part of element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 10 of 91	

5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.23-2012. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (\pm dB)
Conducted Bench Top Measurements	1.65
Conducted Disturbance	2.75
Radiated Disturbance (<30MHz)	4.06
Radiated Disturbance (30MHz - 1GHz)	4.30
Radiated Disturbance (1 - 18GHz)	4.78
Radiated Disturbance (>18GHz)	4.79

FCC ID: BCGA2301 IC: 579C-A2301	 PCTEST [®] Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 11 of 91

6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent Technologies	N9030A	3Hz-44GHz PXA Signal Analyzer	3/4/2020	Annual	3/4/2021	MY49430244
Anritsu	ML2496A	Power Meter	4/9/2020	Annual	4/9/2021	2002005
Anritsu	MA2411B	Pulse Power Sensor	3/10/2020	Annual	3/10/2021	1911105
Anritsu	MA2411B	Pulse Power Sensor	3/10/2020	Annual	3/10/2021	1911106
ATM	180-442A-KF	20dB Nominal Gain Horn Antenna	8/11/2020	Annual	8/11/2021	T058701-01
COM-POWER	LIN-120A	LISN	3/4/2020	Annual	3/4/2021	241297
ETS-Lindgren	3142E	BiConiLog Antenna (30MHz - 6GHz)	9/15/2020	Annual	9/15/2021	208204
ETS-Lindgren	3117	Double Ridged Guide Antenna (1-18 GHz)	4/21/2020	Annual	4/21/2021	205956
Rohde & Schwarz	ESW26	EMI Test Receiver	6/1/2020	Annual	6/1/2021	101299
Rohde & Schwarz	ESW44	EMI Test Receiver	8/7/2020	Annual	8/7/2021	101668
Rohde & Schwarz	TS-PR1840	Pre-Amplifier (18GHz - 40GHz)	4/3/2020	Annual	4/3/2021	100052
Rohde & Schwarz	TC-TA18	Cross Polarized Vivaldi Antenna (400MHz-18GHz)	10/2/2020	Annual	10/2/2021	101063
Rohde & Schwarz	HFH2-Z2	Loop Antenna	3/12/2020	Annual	3/12/2021	100546
Rohde & Schwarz	TS-PR18	Pre-Amplifier (1GHz - 18GHz)	12/3/2020	Annual	12/3/2021	101648
Rohde & Schwarz	TS-PR8	Pre-Amplifier (30MHz - 8GHz)	3/4/2020	Annual	3/4/2021	102325
Rohde & Schwarz	ENV216	Two-Line V-Network (LISN)	12/7/2020	Annual	12/7/2021	101364

Table 6-1. Test Equipment List

Notes:

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

FCC ID: BCGA2301 IC: 579C-A2301	 PCTEST [®] Proud to be part of element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 12 of 91	

7.0 TEST RESULTS

7.1 Summary

Company Name: Apple Inc.
 FCC ID: BCGA2301
 IC: 579C-A2301
 Method/System: Frequency Hopping Spread Spectrum (FHSS)
 Number of Channels: 79

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.247(a)(1)	RSS-247 [5.1(a)]	20dB Bandwidth	N/A	CONDUCTED	N/A	Section 7.2
2.1049	RSS-Gen [6.7]	Occupied Bandwidth	N/A		N/A	Section 7.2
15.247(b)(1)	RSS-247 [5.4(b)]	Peak Transmitter Output Power	< 1 Watt if \geq 75 non-overlapping channels used		PASS	Section 7.3
15.247(a)(1)	RSS-247 [5.1(b)]	Channel Separation	> 2/3 of 20 dB BW for systems with Output Power < 125mW		PASS	Section 7.5
15.247(a)(1)(iii)	RSS-247 [5.1(d)]	Time of Occupancy	< 0.4 sec in 31.6 sec period		PASS	Section 7.6
15.247(a)(1)(iii)	RSS-247 [5.1(d)]	Number of Channels	> 15 Channels		PASS	Section 7.7
15.247(d)	RSS-247 [5.5]	Band Edge / Out-of-Band Emissions	> 20dBc		PASS	Section 7.4 Section 7.8
15.205 15.209	RSS-Gen [8.9]	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-247 limits)	RADIATED	PASS	Section 7.9, Section 7.10 Section 7.11
15.207	RSS-Gen [8.8]	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 limits (RSS-Gen [8.8] limits)	LINE CONDUCTED	PASS	Section 7.12

Table 7-1. Summary of Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "BT Auto," Version 3.5.
- 5) For radiated band edge, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "Chamber Automation," Version 1.3.1.

FCC ID: BCGA2301 IC: 579C-A2301	 PCTEST [®] Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 13 of 91

7.2 Bandwidth Measurement

§2.1049; §15.247 (a.1); RSS-247 [5.1(a)]; RSS-Gen [6.7]

Test Overview and Limit

The bandwidth at 20dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the receive antenna while the EUT is operating in transmission mode at the appropriate frequencies.

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Procedure Used

ANSI C63.10-2013 – Section 6.9.2
 RSS-Gen [6.7]

Test Settings

1. The signal analyzers' automatic bandwidth measurement capability of the spectrum analyzer was used to perform the 99% occupied bandwidth and the 20dB bandwidth measurement. The "X" dB bandwidth parameter was set to X = 20. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% OBW
3. VBW \geq 3 x RBW
4. Reference level set to keep signal from exceeding maximum input mixer level for linear operation.
5. Detector = Peak
6. Trace mode = max hold
7. Sweep = auto couple
8. The trace was allowed to stabilize
9. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

FCC ID: BCGA2301 IC: 579C-A2301	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 14 of 91

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-1. Test Instrument & Measurement Setup

Test Notes

All supported modulation, antenna (including TxBF mode) and power schemes have been tested on the unit and only worst case configuration is reported.


FCC ID: BCGA2301 IC: 579C-A2301	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 15 of 91

Antenna 4a


Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	99% OBW Test Results [kHz]	20dB Bandwidth Test Results [kHz]
2402	1.0	GFSK	ePA	0	873.31	944.90
2441	1.0	GFSK	ePA	39	887.01	940.90
2480	1.0	GFSK	ePA	78	883.55	945.60
2402	3.0	8DPSK	ePA	0	1212.30	1359.00
2441	3.0	8DPSK	ePA	39	1213.10	1354.00
2480	3.0	8DPSK	ePA	78	1213.80	1366.00

Table 7-2. 20dB BW and 99% OBW Measurements Antenna 4a

FCC ID: BCGA2301 IC: 579C-A2301	 PCTEST Proud to be part of element			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device			




Plot 7-1. 20dB BW and 99% OBW Plot Antenna 4a (Bluetooth, GFSK, ePA – Ch. 0)




Plot 7-2. 20dB BW and 99% OBW Plot Antenna 4a (Bluetooth, GFSK, ePA – Ch. 39)

FCC ID: BCGA2301 IC: 579C-A2301	PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 17 of 91




Plot 7-3. 20dB BW and 99% OBW Plot Antenna 4a (Bluetooth, GFSK, ePA – Ch. 78)




Plot 7-4. 20dB BW and 99% OBW Plot Antenna 4a (Bluetooth, 8DPSK, ePA – Ch. 0)

FCC ID: BCGA2301 IC: 579C-A2301	PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 18 of 91



Plot 7-5. 20dB BW and 99% OBW Plot Antenna 4a (Bluetooth, 8DPSK, ePA – Ch. 39)



Plot 7-6. 20dB BW and 99% OBW Plot Antenna 4a (Bluetooth, 8DPSK, ePA – Ch. 78)


FCC ID: BCGA2301 IC: 579C-A2301	PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 19 of 91

Antenna 2a


Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	99% OBW Test Results [kHz]	20dB Bandwidth Test Results [kHz]
2402	1.0	GFSK	ePA	0	873.42	941.30
2441	1.0	GFSK	ePA	39	872.54	950.30
2480	1.0	GFSK	ePA	78	866.63	938.00
2402	3.0	8DPSK	ePA	0	1212.20	1350.00
2441	3.0	8DPSK	ePA	39	1211.10	1351.00
2480	3.0	8DPSK	ePA	78	1212.80	1350.00

Table 7-3. 20dB BW and 99% OBW Bandwidth Measurements Antenna 2a

FCC ID: BCGA2301 IC: 579C-A2301	 PCTEST [®] Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 20 of 91




Plot 7-7. 20dB BW and 99% OBW Plot Antenna 2a (Bluetooth, GFSK, ePA – Ch. 0)




Plot 7-8. 20dB BW and 99% OBW Plot Antenna 2a (Bluetooth, GFSK, ePA – Ch. 39)

FCC ID: BCGA2301 IC: 579C-A2301	PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 21 of 91




Plot 7-9. 20dB BW and 99% OBW Plot Antenna 2a (Bluetooth, GFSK, ePA – Ch. 78)




Plot 7-10. 20dB BW and 99% OBW Plot Antenna 2a (Bluetooth, 8DPSK, ePA – Ch. 0)

FCC ID: BCGA2301 IC: 579C-A2301	PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 22 of 91



Plot 7-11. 20dB BW and 99% OBW Plot Antenna 2a (Bluetooth, 8DPSK, ePA – Ch. 39)



Plot 7-12. 20dB BW and 99% OBW Plot Antenna 2a (Bluetooth, 8DPSK, ePA – Ch. 78)

FCC ID: BCGA2301 IC: 579C-A2301	PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 23 of 91

7.3 Output Power Measurement

§15.247 (b.1); RSS-247 [5.4(b)]

Test Overview and Limits

Measurement is made while the EUT is operating in non-hopping transmission mode. Peak and Average power measurements are performed using a broadband power meter with a pulse sensor.

The maximum peak conducted output power of frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels is 1 watt

The conducted output power limit on paragraph above is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For FHSS operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W if the hopset uses 75 or more hopping channels. The e.i.r.p. shall not exceed 4 W.

Test Procedure Used

ANSI C63.10-2013 – Section 7.8.5

ANSI C63.10-2013 – Section 11.9.2.3.2 method AVGPM-G

ANSI C63.10-2013 – Section 14.2 Measure-and-Sum Technique

Test Settings

Peak Power Measurement

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than the occupied bandwidth.

Method AVGPM-G (Average Power Measurement)

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-2. Test Instrument & Measurement Setup for Peak and Average Power Measurement

Note

All supported modulations have been tested and $\pi/4$ -DQPSK was found not as the worst case modulation so only GFSK and 8DPSK is reported.

FCC ID: BCGA2301 IC: 579C-A2301	 PCTEST [®] Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device		Page 24 of 91

7.3.1 Peak Output Power Measurement

Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Peak Conducted Power		Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]
					[dBm]	[mW]						
2402	1.0	GFSK	ePA	0	12.91	19.543	30.00	-17.09	1.50	14.41	36.02	-21.61
2441	1.0	GFSK	ePA	39	12.99	19.907	30.00	-17.01	1.50	14.49	36.02	-21.53
2480	1.0	GFSK	ePA	78	13.26	21.184	30.00	-16.74	1.50	14.76	36.02	-21.26
2402	1.0	GFSK	iPA	0	11.79	15.101	30.00	-18.21	1.50	13.29	36.02	-22.73
2441	1.0	GFSK	iPA	39	11.43	13.900	30.00	-18.57	1.50	12.93	36.02	-23.09
2480	1.0	GFSK	iPA	78	11.34	13.614	30.00	-18.66	1.50	12.84	36.02	-23.18
2402	3.0	8DPSK	ePA	0	16.10	40.738	30.00	-13.90	1.50	17.60	36.02	-18.42
2441	3.0	8DPSK	ePA	39	15.90	38.905	30.00	-14.10	1.50	17.40	36.02	-18.62
2480	3.0	8DPSK	ePA	78	15.88	38.726	30.00	-14.12	1.50	17.38	36.02	-18.64
2402	3.0	8DPSK	iPA	0	7.64	5.808	30.00	-22.36	1.50	9.14	36.02	-26.88
2441	3.0	8DPSK	iPA	39	8.09	6.442	30.00	-21.91	1.50	9.59	36.02	-26.43
2480	3.0	8DPSK	iPA	78	7.65	5.821	30.00	-22.35	1.50	9.15	36.02	-26.87

Table 7-4. Peak Conducted Output Power Measurements Antenna 4a

Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Peak Conducted Power		Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]
					[dBm]	[mW]						
2402	1.0	GFSK	ePA	0	14.26	26.669	30.00	-15.74	2.50	16.76	36.02	-19.26
2441	1.0	GFSK	ePA	39	14.13	25.882	30.00	-15.87	2.50	16.63	36.02	-19.39
2480	1.0	GFSK	ePA	78	14.46	27.925	30.00	-15.54	2.50	16.96	36.02	-19.06
2402	1.0	GFSK	iPA	0	10.37	10.889	30.00	-19.63	2.50	12.87	36.02	-23.15
2441	1.0	GFSK	iPA	39	10.19	10.447	30.00	-19.81	2.50	12.69	36.02	-23.33
2480	1.0	GFSK	iPA	78	10.24	10.568	30.00	-19.76	2.50	12.74	36.02	-23.28
2402	3.0	8DPSK	ePA	0	16.50	44.668	30.00	-13.50	2.50	19.00	36.02	-17.02
2441	3.0	8DPSK	ePA	39	16.18	41.495	30.00	-13.82	2.50	18.68	36.02	-17.34
2480	3.0	8DPSK	ePA	78	16.01	39.902	30.00	-13.99	2.50	18.51	36.02	-17.51
2402	3.0	8DPSK	iPA	0	8.15	6.531	30.00	-21.85	2.50	10.65	36.02	-25.37
2441	3.0	8DPSK	iPA	39	8.13	6.501	30.00	-21.87	2.50	10.63	36.02	-25.39
2480	3.0	8DPSK	iPA	78	8.19	6.592	30.00	-21.81	2.50	10.69	36.02	-25.33

Table 7-5. Peak Conducted Output Power Measurements Antenna 2a

Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Peak Conducted Power					Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Directional Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]	
					Antenna 4a		Antenna 2a		Summed							
					[dBm]	[mW]	[dBm]	[mW]	[dBm]							
2402	1.0	GFSK	ePA	0	12.62	18.281	14.35	27.227	16.58	45.499	30.00	-13.42	5.02	21.60	36.02	-14.42
2441	1.0	GFSK	ePA	39	12.75	18.836	14.31	26.977	16.61	45.814	30.00	-13.39	5.02	21.63	36.02	-14.39
2480	1.0	GFSK	ePA	78	13.06	20.230	14.34	27.164	16.76	47.424	30.00	-13.24	5.02	21.78	36.02	-14.24
2402	1.0	GFSK	iPA	0	11.30	13.490	10.09	10.209	13.75	23.714	30.00	-16.25	5.02	18.77	36.02	-17.25
2441	1.0	GFSK	iPA	39	11.91	15.524	9.88	9.727	14.02	25.235	30.00	-15.98	5.02	19.04	36.02	-16.98
2480	1.0	GFSK	iPA	78	11.48	14.060	10.14	10.328	13.87	24.378	30.00	-16.13	5.02	18.89	36.02	-17.13
2402	3.0	8DPSK	ePA	0	15.37	34.435	14.94	31.189	18.17	65.615	30.00	-11.83	5.02	23.19	36.02	-12.83
2441	3.0	8DPSK	ePA	39	15.71	37.239	14.96	31.333	18.36	68.549	30.00	-11.64	5.02	23.38	36.02	-12.64
2480	3.0	8DPSK	ePA	78	15.87	38.637	15.49	35.400	18.69	73.961	30.00	-11.31	5.02	23.71	36.02	-12.31
2402	3.0	8DPSK	iPA	0	10.57	11.402	8.22	6.637	12.56	18.030	30.00	-17.44	5.02	17.58	36.02	-18.44
2441	3.0	8DPSK	iPA	39	10.41	10.990	8.15	6.531	12.44	17.539	30.00	-17.56	5.02	17.46	36.02	-18.56
2480	3.0	8DPSK	iPA	78	10.19	10.447	8.57	7.194	12.47	17.660	30.00	-17.53	5.02	17.49	36.02	-18.53

Table 7-6. Peak Conducted Output Power Measurements TxBF

FCC ID: BCGA2301 IC: 579C-A2301	 PCTEST [®] Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 25 of 91

7.3.2 Average Output Power Measurement

Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Avg Conducted Power		Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]
					[dBm]	[mW]						
2402	1.0	GFSK	ePA	0	12.66	18.450	30.00	-17.34	1.50	14.16	36.02	-21.86
2441	1.0	GFSK	ePA	39	12.70	18.621	30.00	-17.30	1.50	14.20	36.02	-21.82
2480	1.0	GFSK	ePA	78	12.72	18.707	30.00	-17.28	1.50	14.22	36.02	-21.80
2402	1.0	GFSK	iPA	0	11.50	14.125	30.00	-18.50	1.50	13.00	36.02	-23.02
2441	1.0	GFSK	iPA	39	11.16	13.062	30.00	-18.84	1.50	12.66	36.02	-23.36
2480	1.0	GFSK	iPA	78	11.05	12.735	30.00	-18.95	1.50	12.55	36.02	-23.47
2402	3.0	8DPSK	ePA	0	12.72	18.707	30.00	-17.28	1.50	14.22	36.02	-21.80
2441	3.0	8DPSK	ePA	39	12.59	18.155	30.00	-17.41	1.50	14.09	36.02	-21.93
2480	3.0	8DPSK	ePA	78	12.51	17.824	30.00	-17.49	1.50	14.01	36.02	-22.01
2402	3.0	8DPSK	iPA	0	7.24	5.297	30.00	-22.76	1.50	8.74	36.02	-27.28
2441	3.0	8DPSK	iPA	39	7.50	5.623	30.00	-22.50	1.50	9.00	36.02	-27.02
2480	3.0	8DPSK	iPA	78	7.26	5.321	30.00	-22.74	1.50	8.76	36.02	-27.26

Table 7-7. Average Conducted Output Power Measurements Antenna 4a

Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Avg Conducted Power		Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]
					[dBm]	[mW]						
2402	1.0	GFSK	ePA	0	13.91	24.604	30.00	-16.09	2.50	16.41	36.02	-19.61
2441	1.0	GFSK	ePA	39	13.79	23.933	30.00	-16.21	2.50	16.29	36.02	-19.73
2480	1.0	GFSK	ePA	78	14.00	25.119	30.00	-16.00	2.50	16.50	36.02	-19.52
2402	1.0	GFSK	iPA	0	9.69	9.311	30.00	-20.31	2.50	12.19	36.02	-23.83
2441	1.0	GFSK	iPA	39	9.94	9.863	30.00	-20.06	2.50	12.44	36.02	-23.58
2480	1.0	GFSK	iPA	78	9.86	9.683	30.00	-20.14	2.50	12.36	36.02	-23.66
2402	3.0	8DPSK	ePA	0	13.00	19.953	30.00	-17.00	2.50	15.50	36.02	-20.52
2441	3.0	8DPSK	ePA	39	12.81	19.099	30.00	-17.19	2.50	15.31	36.02	-20.71
2480	3.0	8DPSK	ePA	78	12.60	18.197	30.00	-17.40	2.50	15.10	36.02	-20.92
2402	3.0	8DPSK	iPA	0	5.08	3.221	30.00	-24.92	2.50	7.58	36.02	-28.44
2441	3.0	8DPSK	iPA	39	5.01	3.170	30.00	-24.99	2.50	7.51	36.02	-28.51
2480	3.0	8DPSK	iPA	78	5.14	3.266	30.00	-24.86	2.50	7.64	36.02	-28.38

Table 7-8. Average Conducted Output Power Measurements Antenna 2a

Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Average Conducted Power					Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Directional Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]	
					Antenna 4a		Antenna 2a		Summed							
					[dBm]	[mW]	[dBm]	[mW]	[dBm]							
2402	1.0	GFSK	ePA	0	12.35	17.179	14.00	25.119	16.26	42.267	30.00	-13.74	5.02	21.28	36.02	-14.74
2441	1.0	GFSK	ePA	39	12.47	17.660	13.97	24.946	16.29	42.560	30.00	-13.71	5.02	21.31	36.02	-14.71
2480	1.0	GFSK	ePA	78	12.74	18.793	14.00	25.119	16.43	43.954	30.00	-13.57	5.02	21.45	36.02	-14.57
2402	1.0	GFSK	iPA	0	11.06	12.764	9.83	9.616	13.50	22.387	30.00	-16.50	5.02	18.52	36.02	-17.50
2441	1.0	GFSK	iPA	39	11.50	14.125	9.55	9.016	13.64	23.121	30.00	-16.36	5.02	18.66	36.02	-17.36
2480	1.0	GFSK	iPA	78	11.14	13.002	9.84	9.638	13.55	22.646	30.00	-16.45	5.02	18.57	36.02	-17.45
2402	3.0	8DPSK	ePA	0	11.96	15.704	11.51	14.158	14.75	29.854	30.00	-15.25	5.02	19.77	36.02	-16.25
2441	3.0	8DPSK	ePA	39	12.00	15.849	11.56	14.322	14.80	30.200	30.00	-15.20	5.02	19.82	36.02	-16.20
2480	3.0	8DPSK	ePA	78	12.00	15.849	11.60	14.454	14.81	30.269	30.00	-15.19	5.02	19.83	36.02	-16.19
2402	3.0	8DPSK	iPA	0	7.50	5.623	5.13	3.258	9.49	8.892	30.00	-20.51	5.02	14.51	36.02	-21.51
2441	3.0	8DPSK	iPA	39	7.35	5.433	5.05	3.199	9.36	8.630	30.00	-20.64	5.02	14.38	36.02	-21.64
2480	3.0	8DPSK	iPA	78	7.24	5.297	5.50	3.548	9.47	8.851	30.00	-20.53	5.02	14.49	36.02	-21.53

Table 7-9. Average Conducted Output Power Measurements TxBF

FCC ID: BCGA2301 IC: 579C-A2301	 PCTEST [®] Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCGC	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 26 of 91

Note:

Per ANSI C63.10-2013 and KDB 662911 D01 v02r01 Section E)1), the conducted powers at Antenna 4a and Antenna 2a were first measured separately during TxBF transmission as shown in the section above. The measured values were then summed in linear power units then converted back to dBm.

Per ANSI C63.10-2013 Section 14.4.3, the directional gain is calculated using the following formula, where G_N is the gain of the nth antenna and N_{ANT} , the total number of antennas used.

$$\text{Directional gain} = 10 \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_{N/20}})^2 / N_{ANT}] \text{ dBi}$$

Sample TxBF Calculation:

At 2402MHz, the average conducted output power was measured to be 12.35 dBm for Antenna 4a and 14 dBm for Antenna 2a.

$$\text{Antenna 4a} + \text{Antenna 2a} = \text{TxBF}$$

$$(12.35 \text{ dBm} + 14 \text{ dBm}) = (17.179 \text{ mW} + 25.119 \text{ mW}) = 42.267 \text{ mW} = 16.26 \text{ dBm}$$

Sample e.i.r.p. Calculation:

At 2402MHz, the average conducted output power was calculated to be 16.26 dBm with directional gain of 5.02 dBi.

$$\text{e.i.r.p. (dBm)} = \text{Conducted Power (dBm)} + \text{Ant gain (dBi)}$$

$$16.26 \text{ dBm} + 5.02 \text{ dBi} = 21.28 \text{ dBm}$$

FCC ID: BCGA2301 IC: 579C-A2301	 PCTEST Proud to be part of element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 27 of 91	

7.4 Conducted Authorized Band Edge

§15.247 (d); RSS-247 [5.5]

Test Overview and Limits

EUT operates in hopping and non-hopping transmission mode. Measurement is taken at the highest point located outside of the emission bandwidth. ***The maximum permissible out-of-band emission level is 20 dBc.***

Test Procedure Used

ANSI C63.10-2013 – Section 6.10.4

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW = 100kHz
4. VBW = 300kHz
5. Detector = Peak
6. Number of sweep points $\geq 2 \times \text{Span}/\text{RBW}$
7. Trace mode = max hold
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-3. Test Instrument & Measurement Setup

Test Notes


1. Out of band conducted spurious emissions at the band edge were investigated for all data rates in hopping and non-hopping modes. The worst case emissions were found with the EUT transmitting at 3 Mbps. Band edge emissions were also investigated with the EUT transmitting in all data rates. Plots of the worst case emissions are shown below.
2. All supported modulation, antenna (including TxBF mode) and power schemes have been tested on the unit and only worst case configuration is reported.

FCC ID: BCGA2301 IC: 579C-A2301	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 28 of 91

Antenna 4a




Plot 7-13. Band Edge Plot Antenna 4a (Bluetooth with Hopping Disabled, GFSK, ePA – Ch. 0)




Plot 7-14. Band Edge Plot Antenna 4a (Bluetooth with Hopping Disabled, GFSK, ePA – Ch. 78)

FCC ID: BCGA2301 IC: 579C-A2301	PCTEST® Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 29 of 91




Plot 7-15. Band Edge Plot Antenna 4a (Bluetooth with Hopping Enabled, GFSK, ePA)




Plot 7-16. Band Edge Plot Antenna 4a (Bluetooth with Hopping Enabled, GFSK, ePA)

FCC ID: BCGA2301 IC: 579C-A2301	PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 30 of 91




Plot 7-17. Band Edge Plot Antenna 4a (Bluetooth with Hopping Disabled, 8DPSK, ePA – Ch. 0)




Plot 7-18. Band Edge Plot Antenna 4a (Bluetooth with Hopping Disabled, 8DPSK, ePA – Ch. 78)

FCC ID: BCGA2301 IC: 579C-A2301	PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 31 of 91




Plot 7-19. Band Edge Plot Antenna 4a (Bluetooth with Hopping Enabled, 8DPSK, ePA)




Plot 7-20. Band Edge Plot Antenna 4a (Bluetooth with Hopping Enabled, 8DPSK, ePA)

FCC ID: BCGA2301 IC: 579C-A2301	PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020/2/25/2021	EUT Type: Tablet Device	Page 32 of 91

Antenna 2a




Plot 7-21. Band Edge Plot Antenna 2a (Bluetooth with Hopping Disabled, GFSK, ePA – Ch. 0)




Plot 7-22. Band Edge Plot Antenna 2a (Bluetooth with Hopping Disabled, GFSK, ePA – Ch. 78)

FCC ID: BCGA2301 IC: 579C-A2301	PCTEST® Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 33 of 91




Plot 7-23. Band Edge Plot Antenna 2a (Bluetooth with Hopping Enabled, GFSK, ePA)




Plot 7-24. Band Edge Plot Antenna 2a (Bluetooth with Hopping Enabled, GFSK, ePA)

FCC ID: BCGA2301 IC: 579C-A2301	PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 34 of 91




Plot 7-25. Band Edge Plot Antenna 2a (Bluetooth with Hopping Disabled, 8DPSK, ePA – Ch. 0)




Plot 7-26. Band Edge Plot Antenna 2a (Bluetooth with Hopping Disabled, 8DPSK, ePA – Ch. 78)

FCC ID: BCGA2301 IC: 579C-A2301	PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 35 of 91



Plot 7-27. Band Edge Plot Antenna 2a (Bluetooth with Hopping Enabled, 8DPSK, ePA)



Plot 7-28. Band Edge Plot Antenna 2a (Bluetooth with Hopping Enabled, 8DPSK, ePA)

FCC ID: BCGA2301 IC: 579C-A2301	PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 36 of 91

7.5 Carrier Frequency Separation

§15.247 (a.1); RSS-247 [5.1(b)]

Test Overview and Limit

Measurement is made with EUT operating in hopping mode. ***The minimum permissible channel separation for this system is 2/3 the value of the 20dB BW.***

Test Procedure Used

ANSI C63.10-2013 – Section 7.8.2

Test Settings

1. Span = Wide enough to capture peaks of two adjacent channels
2. RBW = 30% of channel spacing. Adjust as necessary to best identify center of each individual channel
3. VBW \geq RBW
4. Sweep = Auto
5. Detector = Peak
6. Trace mode = max hold
7. The trace was allowed to stabilize.
8. Marker-delta function used to determine separation between peaks of the adjacent channels

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-4. Test Instrument & Measurement Setup

Test Notes

1. The EUT complies with the minimum channel separation requirement when it is operating in 1x/EDR mode using 79 channels.
2. All supported modulation, antenna (including TxBF mode) and power schemes have been tested on the unit and only worst case configuration is reported.


FCC ID: BCGA2301 IC: 579C-A2301	 PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 37 of 91

Antenna 4a


Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Measured Channel Separation [MHz]	Min. Channel Separation Limit [MHz]	Pass / Fail
2441	1.0	GFSK	ePA	39	1.000	0.627	Pass
2441	3.0	8DPSK	ePA	39	1.000	0.903	Pass

Table 7-10. Minimum Channel Separation Antenna 4a


FCC ID: BCGA2301 IC: 579C-A2301	 PCTEST Proud to be part of element			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device			



Plot 7-29. Channel Spacing Plot Antenna 4a (Bluetooth, GFSK, ePA)



Plot 7-30. Channel Spacing Plot Antenna 4a (Bluetooth, 8DPSK, ePA)


FCC ID: BCGA2301 IC: 579C-A2301	PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 39 of 91

Antenna 2a


Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Measured Channel Separation [MHz]	Min. Channel Separation Limit [MHz]	Pass / Fail
2441	1.0	GFSK	ePA	39	1.000	0.634	Pass
2441	3.0	8DPSK	ePA	39	1.000	0.901	Pass

Table 7-11. Minimum Channel Separation Antenna 2a

FCC ID: BCGA2301 IC: 579C-A2301	 PCTEST Proud to be part of element			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device			



Plot 7-31. Channel Spacing Plot Antenna 2a (Bluetooth, GFSK, ePA)



Plot 7-32. Channel Spacing Plot Antenna 2a (Bluetooth, 8DPSK, ePA)

FCC ID: BCGA2301 IC: 579C-A2301	PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 41 of 91

7.6 Time of Occupancy

§15.247 (a.1.iii); RSS-247 [5.1(d)]

Test Overview and Limit

Measurement is made while EUT is operating in hopping mode with the spectrum analyzer set to zero span. ***The maximum permissible time of occupancy is 400 ms within a period of 400ms multiplied by the number of hopping channels employed.***

Test Procedure Used

ANSI C63.10-2013 – Section 7.8.4

Test Settings

1. Span = zero span, centered on a hopping channel
2. RBW \leq channel spacing and $\gg 1/T$, where T is expected dwell time per channel
3. Sweep = as necessary to capture entire dwell time. Second plot may be required to demonstrate two successive hops on a channel
4. Trigger is set with appropriate trigger delay to place pulse near the center of the plot
5. Detector = peak
6. Trace mode = max hold
7. Marker-delta function used to determine transmit time per hop

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-5. Test Instrument & Measurement Setup

Test Notes


All supported modulation, antenna (including TxBF mode) and power schemes have been tested on the unit and only worst case configuration is reported.

FCC ID: BCGA2301 IC: 579C-A2301	 PCTEST Proud to be part of element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 42 of 91	

Antenna 4a




Plot 7-33. Time of Occupancy Plot Antenna 4a (Bluetooth, GFSK, ePA)




Plot 7-34. Time of Occupancy Plot Antenna 4a (Bluetooth, 8DPSK, ePA)

FCC ID: BCGA2301 IC: 579C-A2301	 PCTEST® Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 43 of 91

Antenna 2a



Plot 7-35. Time of Occupancy Plot Antenna 2a (Bluetooth, GFSK, ePA)



Plot 7-36. Time of Occupancy Plot Antenna 2a (Bluetooth, 8DPSK, ePA)

FCC ID: BCGA2301 IC: 579C-A2301	PCTEST® Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 44 of 91

Bluetooth Time of Occupancy Calculation

Typically, Bluetooth 1x/EDR mode has a channel hopping rate of 1600 hops/s. Since 1x/EDR modes use 5 transmit and 1 receive slot, for a total of 6 slots, the Bluetooth transmitter is actually hopping at a rate of $1600 / 6 = 266.67$ hops/s/slot

- $400\text{ms} \times 79 \text{ hopping channels} = 31.6 \text{ sec (Time of Occupancy Limit)}$
- Worst case BT has 266.67 hops/second (for 1x/EDR modes with DH5 operation)
- $266.67 \text{ hops/second} / 79 \text{ channels} = 3.38 \text{ hops/second (# of hops/second on one channel)}$
- $3.38 \text{ hops/second/channel} \times 31.6 \text{ seconds} = 106.67 \text{ hops (# hops over a 31.6 second period)}$
- $106.67 \text{ hops} \times 2.91 \text{ ms/channel} = 310.41 \text{ ms (worst case dwell time for one channel in 1x/EDR modes)}$

With AFH, the number of channels is reduced to a minimum of 20 channels and the channel hopping rate is reduced by 50% to 800 hops/s. AFH mode also uses 6 total slots so the Bluetooth transmitter hops at a rate of $800 / 6 = 133.3$ hops/s/slot

- $400\text{ms} \times 20 \text{ hopping channels} = 8 \text{ sec (Time of Occupancy Limit)}$
- Worst case BT has 133.3 hops/second/slot (for AFH mode with DH5 operation)
- $133.3 \text{ hops/s} / 20 \text{ channels} = 6.67 \text{ hops/second (# of hops/second on one channel)}$
- $6.67 \text{ hops/s} / \text{channel} \times 8 \text{ seconds} = 53.34 \text{ hops (# hops over a 8 second period)}$
- $53.34 \text{ hops} \times 2.91 \text{ ms/channel} = 155.22 \text{ ms (worst case dwell time for one channel in AFH mode)}$

Test Result

The measured worst case dwell time is below the limit of 0.4s.

FCC ID: BCGA2301 IC: 579C-A2301	 PCTEST Proud to be part of element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 45 of 91	

7.7 Number of Hopping Channels

§15.247 (a.1.iii); RSS-247 [5.1(d)]

Test Overview and Limit

Measurement is made while EUT is operating in hopping mode. ***This frequency hopping system must employ a minimum of 15 hopping channels.***

Test Procedure Used

ANSI C63.10-2013 – Section 7.8.3

Test Settings

1. Span = frequency of band of operation (divided into two plots)
2. RBW < 30% of channel spacing or 20dB bandwidth, whichever is smaller.
3. VBW \geq RBW
4. Sweep = auto
5. Detector = peak
6. Trace mode = max hold
7. Trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-6. Test Instrument & Measurement Setup

Test Notes


1. The frequency spectrum was broken up into two sub-ranges to clearly show all of the hopping frequencies. In AFH mode, this device operates using 20 channels so the requirement for minimum number of hopping channels is satisfied.
2. All supported modulation, antenna (including TxBF mode) and power schemes have been tested on the unit and only worst case configuration is reported.

FCC ID: BCGA2301 IC: 579C-A2301	 PCTEST® Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 46 of 91

Antenna 4a




Plot 7-37. Low End Spectrum Channel Hopping Plot Antenna 4a (Bluetooth, GFSK, ePA)




Plot 7-38. High End Spectrum Channel Hopping Plot Antenna 4a (Bluetooth, GFSK, ePA)

FCC ID: BCGA2301 IC: 579C-A2301	PCTEST® Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 47 of 91




Plot 7-39. Low End Spectrum Channel Hopping Plot Antenna 4a (Bluetooth, 8DPSK, ePA)




Plot 7-40. High End Spectrum Channel Hopping Plot Antenna 4a (Bluetooth, 8DPSK, ePA)

FCC ID: BCGA2301 IC: 579C-A2301	PCTEST Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 48 of 91	

Antenna 2a




Plot 7-41. Low End Spectrum Channel Hopping Plot Antenna 2a (Bluetooth, GFSK, ePA)




Plot 7-42. High End Spectrum Channel Hopping Plot Antenna 2a (Bluetooth, GFSK, ePA)

FCC ID: BCGA2301 IC: 579C-A2301	PCTEST® Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 49 of 91	



Plot 7-43. Low End Spectrum Channel Hopping Plot Antenna 2a (Bluetooth, 8DPSK, ePA)



Plot 7-44. High End Spectrum Channel Hopping Plot Antenna 2a (Bluetooth, 8DPSK, ePA)

FCC ID: BCGA2301 IC: 579C-A2301	PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 50 of 91

7.8 Conducted Spurious Emissions

§15.247 (d); RSS-247 [5.5]

Test Overview and Limit

Conducted out-of-band spurious emissions were investigated from 30MHz up to 25GHz to include the 10th harmonic of the fundamental transmit frequency. **The maximum permissible out-of-band emission level is 20 dBc.**

Test Procedure Used

ANSI C63.10-2013 – Section 7.8.8

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 25GHz (separated into two plots per channel)
2. RBW = 1MHz* (See note below)
3. VBW = 3MHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-7. Test Instrument & Measurement Setup

Test Notes


1. Out-of-band conducted spurious emissions were investigated for all data rates and the worst case emissions were found with the EUT transmitting at 1Mbps. The display line shown in the following plots is the limit at 20dB below the fundamental emission level measured in a 100kHz bandwidth. However, the traces in the following plots are measured with a 1MHz RBW to reduce test time, so the display line may not necessarily appear to be 20dB below the level of the fundamental in a 1MHz bandwidth.
2. The unit was tested with all possible mode and power schemes and only the highest emission is reported.

FCC ID: BCGA2301 IC: 579C-A2301	 PCTEST Proud to be part of element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device		Page 51 of 91

Antenna 4a




Plot 7-45. Conducted Spurious Plot Antenna 4a (Bluetooth, GFSK, ePA – Ch. 0)




Plot 7-46. Conducted Spurious Plot Antenna 4a (Bluetooth, GFSK, ePA – Ch. 0)

FCC ID: BCGA2301 IC: 579C-A2301	PCTEST® Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 52 of 91




Plot 7-47. Conducted Spurious Plot Antenna 4a (Bluetooth, GFSK, ePA – Ch. 39)




Plot 7-48. Conducted Spurious Plot Antenna 4a (Bluetooth, GFSK, ePA Ch. 39)

FCC ID: BCGA2301 IC: 579C-A2301	PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 53 of 91




Plot 7-49. Conducted Spurious Plot Antenna 4a (Bluetooth, GFSK, ePA – Ch. 78)




Plot 7-50. Conducted Spurious Plot Antenna 4a (Bluetooth, GFSK, ePA – Ch. 78)

FCC ID: BCGA2301 IC: 579C-A2301	PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 54 of 91

Antenna 2a




Plot 7-51. Conducted Spurious Plot Antenna 2a (Bluetooth, GFSK, ePA – Ch. 0)




Plot 7-52. Conducted Spurious Plot Antenna 2a (Bluetooth, GFSK, ePA – Ch. 0)

FCC ID: BCGA2301 IC: 579C-A2301	PCTEST® Proud to be part of 		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 55 of 91	



Plot 7-53. Conducted Spurious Plot Antenna 2a (Bluetooth, GFSK, ePA – Ch. 39)



Plot 7-54. Conducted Spurious Plot Antenna 2a (Bluetooth, GFSK, ePA Ch. 39)

FCC ID: BCGA2301 IC: 579C-A2301	PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C2101020002-13.BCG	Test Dates: 12/15/2020-2/25/2021	EUT Type: Tablet Device	Page 56 of 91