



RF Exposure Analysis

FCC ID: BCGA2540

Analysis for FCC extremity portable use - Siri Remote

Standalone SAR test exclusion considerations are defined in KDB 447498D01 (v06) Chapter 4.3.1 where the 1-g head or body and 10-g extremity SAR exclusion threshold is defined by the following formula:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The maximum conducted output power for the device is 9.5 dBm (8.9mW).

Applying the above data using the given KDB 447498 D01 formula, and minimum separation distance of 5mm, the following results:

$(8.9\text{mW} / 5 \text{ mm}) \times \sqrt{2.45 \text{ GHz}} = 2.8$ (i.e.: ≤ 7.5 for 10-g SAR)

This demonstrates the device meets the criteria for 10-g extremity SAR test exemption.

Conclusion

The Siri Remote is exempt from SAR testing and can be used for Portable applications.

Signature: *SD Thomas* _____ Date: _____ 6 April 2021 _____