



Mode: 802.11ax - SU  
 Data Rate: MCS4  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2462MHz  
 Channel: 11



**Plot 7-699. Radiated Restricted Upper Band Edge Measurement CDD**


Mode: 802.11ax - SU  
 Data Rate: MCS5  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2462MHz  
 Channel: 11



**Plot 7-700. Radiated Restricted Upper Band Edge Measurement CDD**


FCC ID: BCGA2696 IC: 579C-A2696	 <b>element</b>	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090022-01.BCG	Test Dates: 05/30/2022 - 09/15/2022	EUT Type: Tablet Device	Page 416 of 430

Mode: 802.11ax - SU  
 Data Rate: MCS2  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2467MHz  
 Channel: 12



**Plot 7-701. Radiated Restricted Upper Band Edge Measurement CDD**


Mode: 802.11ax - SU  
 Data Rate: MCS4  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2467MHz  
 Channel: 12



**Plot 7-702. Radiated Restricted Upper Band Edge Measurement CDD**

FCC ID: BCGA2696 IC: 579C-A2696	 <b>element</b>	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090022-01.BCG	Test Dates: 05/30/2022 - 09/15/2022	EUT Type: Tablet Device	Page 417 of 430

Mode: 802.11ax - SU  
 Data Rate: MCS5  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2467MHz  
 Channel: 12



**Plot 7-703. Radiated Restricted Upper Band Edge Measurement CDD**

FCC ID: BCGA2696 IC: 579C-A2696	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090022-01.BCG	Test Dates: 05/30/2022 - 09/15/2022	EUT Type: Tablet Device	Page 418 of 430

## 7.8 Radiated Spurious Emissions – Below 1GHz

§15.209; RSS-Gen [8.9]

### Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

***All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 7 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-66 per Section 15.209 and RSS-Gen (8.9).***

Frequency	Field Strength [ $\mu$ V/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

**Table 7-66. Radiated Limits**

### Test Procedures Used

ANSI C63.10-2013

### Test Settings

#### Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize


#### Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. VBW = 300kHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold


FCC ID: BCGA2696 IC: 579C-A2696	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090022-01.BCG	Test Dates: 05/30/2022 - 09/15/2022	EUT Type: Tablet Device	Page 419 of 430

## Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.



**Figure 7-7. Radiated Test Setup < 30Mhz**



**Figure 7-8. Radiated Test Setup < 1GHz**

FCC ID: BCGA2696 IC: 579C-A2696	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090022-01.BCG	Test Dates: 05/30/2022 - 09/15/2022	EUT Type: Tablet Device	Page 420 of 430

## Test Notes

1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen(8.10) are below the limit shown in Table 7-66.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes. For below 30MHz the loop antenna was positioned in 3 orthogonal planes (X front, Y side, Z top) to determine the orientation resulting in the worst case emissions.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector for emissions within 6dB of the limit.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. Both configurations below were investigated, and the worst case has been reported.
  - a. EUT powered by AC/DC adaptor via USB-C cable with wire charger
  - b. EUT powered by host PC via USB-C cable with wire charger
9. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
10. The unit was tested with all possible modes and only the highest emission is reported.
11. All antenna configurations were investigated and only the worst case is reported.

## Sample Calculations


### Determining Spurious Emissions Levels

- Field Strength Level  $[\text{dB}_{\mu\text{V/m}}]$  = Analyzer Level  $[\text{dBm}]$  + 107 + AFCL  $[\text{dB}/\text{m}]$
- AFCL  $[\text{dB}/\text{m}]$  = Antenna Factor  $[\text{dB}/\text{m}]$  + Cable Loss  $[\text{dB}]$  – Preamplifier Gain  $[\text{dB}]$
- Margin  $[\text{dB}]$  = Field Strength Level  $[\text{dB}_{\mu\text{V/m}}]$  – Limit  $[\text{dB}_{\mu\text{V/m}}]$

FCC ID: BCGA2696 IC: 579C-A2696	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090022-01.BCG	Test Dates: 05/30/2022 - 09/15/2022	EUT Type: Tablet Device	Page 421 of 430

## CDD Radiated Spurious Emissions Measurements (Below 1GHz)

§15.209; RSS-Gen [8.9]




**Plot 7-704. Radiated Spurious Emissions below 1GHz CDD 11n Ch.6, with AC/DC Adapter**

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
35.53	Max Peak	V	100	358	-65.22	-12.12	29.66	40.00	-10.34
49.45	Max Peak	V	100	358	-67.50	-17.99	21.51	40.00	-18.49
130.44	Max Peak	V	100	110	-72.65	-15.67	18.68	43.52	-24.84
167.59	Max Peak	H	200	359	-64.75	-13.46	28.79	43.52	-14.73
313.29	Max Peak	H	100	316	-69.65	-9.53	27.82	46.02	-18.20
339.43	Max Peak	H	100	312	-70.58	-8.33	28.09	46.02	-17.93

**Table 7-67. Radiated Spurious Emissions below 1GHz CDD 11n Ch.6, with AC/DC Adapter**

FCC ID: BCGA2696 IC: 579C-A2696	 <b>element</b>	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090022-01.BCG	Test Dates: 05/30/2022 - 09/15/2022	EUT Type: Tablet Device	Page 422 of 430



**Plot 7-705. Radiated Spurious Emissions below 1GHz CDD 11ax - SU Ch.6, with AC/DC Adapter**

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
36.26	Max Peak	V	100	276	-58.72	-18.39	29.89	40.00	-10.11
59.05	Max Peak	V	100	231	-59.28	-16.74	30.98	40.00	-9.02
94.41	Max Peak	V	100	199	-65.55	-19.08	22.37	43.52	-21.15
166.38	Max Peak	H	200	239	-63.00	-20.20	23.80	43.52	-19.72
336.67	Max Peak	H	100	149	-66.67	-13.94	26.39	46.02	-19.63
712.98	Max Peak	V	300	145	-72.97	-7.13	26.90	46.02	-19.12

**Table 7-68. Radiated Spurious Emissions below 1GHz CDD 11ax – SU Ch.6, with AC/DC Adapter**

FCC ID: BCGA2696 IC: 579C-A2696	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090022-01.BCG	Test Dates: 05/30/2022 - 09/15/2022	EUT Type: Tablet Device	Page 423 of 430

## 7.9 AC Line-Conducted Emissions Measurement

§15.207; RSS-Gen [8.8]

### Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for AC Line conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

***All conducted emissions must not exceed the limits shown in the table below, per Section 15.207 and RSS-Gen (8.8).***

Frequency of emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

**Table 7-69. Conducted Limits**

\*Decreases with the logarithm of the frequency.

### Test Procedures Used

ANSI C63.10-2013, Subclause 6.2

### Test Settings

#### Quasi-Peak Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize


#### Average Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: BCGA2696 IC: 579C-A2696	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090022-01.BCG	Test Dates: 05/30/2022 - 09/15/2022	EUT Type: Tablet Device	Page 424 of 430

## Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-9. Test Instrument & Measurement Setup**

## Test Notes

1. All modes of operation were investigated and the worst-case emissions are reported. The emissions found were not affected by the choice of channel used during testing.
2. Both configurations below were investigated, and the worst case has been reported.
  - a. EUT powered by AC/DC adaptor via USB-C cable with wire charger
  - b. EUT powered by host PC via USB-C cable with wire charger
3. The limit for an intentional radiator from 150kHz to 30MHz are specified in Part 15.207 and RSS-Gen(8.8).
4. Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
5. QP/AV Level (dB $\mu$ V) = QP/AV Analyzer/Receiver Level (dB $\mu$ V) + Corr. (dB)
6. Margin (dB) = QP/AV Level (dB $\mu$ V) - QP/AV Limit (dB $\mu$ V)
7. Traces shown in plot are made using quasi peak and average detectors.
8. Deviations to the Specifications: None.
9. The unit was tested with all possible modes and only the highest emission is reported.

FCC ID: BCGA2696 IC: 579C-A2696	 <b>element</b>	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090022-01.BCG	Test Dates: 05/30/2022 - 09/15/2022	EUT Type: Tablet Device	Page 425 of 430




**Plot 7-706. AC Line Conducted Plot with CDD 11n Ch.6 (L1, with AC/DC Adapter)**

Frequency [MHz]	Process State	QuasiPeak [dB $\mu$ V]	Average [dB $\mu$ V]	Limit [dB $\mu$ V]	Margin [dB]	Line	PE
0.170	FINAL	50.0	—	64.95	-14.92	L1	GND
0.173	FINAL	—	35.32	54.84	-19.52	L1	GND
0.254	FINAL	45.6	—	61.64	-16.03	L1	GND
0.256	FINAL	—	29.17	51.57	-22.39	L1	GND
0.508	FINAL	37.2	—	56.00	-18.76	L1	GND
0.510	FINAL	—	21.24	46.00	-24.76	L1	GND
0.931	FINAL	32.1	—	56.00	-23.95	L1	GND
0.933	FINAL	—	17.97	46.00	-28.03	L1	GND
2.031	FINAL	—	8.42	46.00	-37.58	L1	GND
2.047	FINAL	19.6	—	56.00	-36.39	L1	GND
4.571	FINAL	31.3	—	56.00	-24.72	L1	GND
4.583	FINAL	—	17.86	46.00	-28.14	L1	GND

**Table 7-70. AC Line Conducted Data with CDD 11n Ch.6 (L1, with AC/DC Adapter)**

FCC ID: BCGA2696 IC: 579C-A2696	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090022-01.BCG	Test Dates: 05/30/2022 - 09/15/2022	EUT Type: Tablet Device	Page 426 of 430




**Plot 7-707. AC Line Conducted Plot with CDD 11n Ch.6 (N, with AC/DC Adapter)**

Frequency [MHz]	Process State	QuasiPeak [dB $\mu$ V]	Average [dB $\mu$ V]	Limit [dB $\mu$ V]	Margin [dB]	Line	PE
0.170	FINAL	46.4	—	64.95	-18.57	N	GND
0.175	FINAL	—	31.42	54.73	-23.32	N	GND
0.256	FINAL	42.5	—	61.57	-19.04	N	GND
0.258	FINAL	—	25.56	51.50	-25.93	N	GND
0.510	FINAL	37.6	—	56.00	-18.41	N	GND
0.512	FINAL	—	20.50	46.00	-25.50	N	GND
0.935	FINAL	34.5	—	56.00	-21.50	N	GND
0.940	FINAL	—	18.53	46.00	-27.47	N	GND
1.896	FINAL	—	13.33	46.00	-32.68	N	GND
1.910	FINAL	25.8	—	56.00	-30.23	N	GND
4.625	FINAL	33.6	—	56.00	-22.44	N	GND
4.684	FINAL	—	21.85	46.00	-24.15	N	GND

**Table 7-71. AC Line Conducted Data with CDD 11n Ch.6 (N, with AC/DC Adapter)**

FCC ID: BCGA2696 IC: 579C-A2696	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090022-01.BCG	Test Dates: 05/30/2022 - 09/15/2022	EUT Type: Tablet Device	Page 427 of 430




**Plot 7-708. AC Line Conducted Plot with CDD 11ax - SU Ch.6 (L1, with AC/DC Adapter)**

Frequency [MHz]	Process State	QuasiPeak [dB $\mu$ V]	Average [dB $\mu$ V]	Limit [dB $\mu$ V]	Margin [dB]	Line	PE
0.164	FINAL	53.2	—	65.28	-12.09	L1	GND
0.168	FINAL	—	40.55	55.06	-14.51	L1	GND
0.245	FINAL	48.5	—	61.94	-13.42	L1	GND
0.247	FINAL	—	33.41	51.87	-18.46	L1	GND
0.569	FINAL	38.0	—	56.00	-17.96	L1	GND
0.571	FINAL	—	22.88	46.00	-23.12	L1	GND
1.055	FINAL	33.4	—	56.00	-22.62	L1	GND
1.057	FINAL	—	20.05	46.00	-25.95	L1	GND
1.867	FINAL	23.8	—	56.00	-32.19	L1	GND
1.867	FINAL	—	13.07	46.00	-32.93	L1	GND
4.362	FINAL	31.7	—	56.00	-24.35	L1	GND
4.504	FINAL	—	18.84	46.00	-27.16	L1	GND

**Table 7-72. AC Line Conducted Data with CDD 11ax - SU Ch.6 (L1, with AC/DC Adapter)**

FCC ID: BCGA2696 IC: 579C-A2696	 <b>element</b>	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090022-01.BCG	Test Dates: 05/30/2022 - 09/15/2022	EUT Type: Tablet Device	Page 428 of 430



**Plot 7-709. AC Line Conducted Plot with CDD 11ax - SU Ch.6 (N, with AC/DC Adapter)**

Frequency [MHz]	Process State	QuasiPeak [dB $\mu$ V]	Average [dB $\mu$ V]	Limit [dB $\mu$ V]	Margin [dB]	Line	PE
0.164	FINAL	49.9	—	65.28	-15.37	N	GND
0.168	FINAL	—	37.31	55.06	-17.75	N	GND
0.245	FINAL	45.9	—	61.94	-16.00	N	GND
0.247	FINAL	—	30.53	51.87	-21.34	N	GND
0.488	FINAL	38.8	—	56.21	-17.41	N	GND
0.488	FINAL	—	24.43	46.21	-21.78	N	GND
1.300	FINAL	31.3	—	56.00	-24.70	N	GND
1.300	FINAL	—	17.04	46.00	-28.96	N	GND
2.146	FINAL	—	10.91	46.00	-35.09	N	GND
2.166	FINAL	20.1	—	56.00	-35.90	N	GND
4.371	FINAL	30.4	—	56.00	-25.64	N	GND
4.457	FINAL	—	16.96	46.00	-29.04	N	GND

**Table 7-73. AC Line Conducted Data with CDD 11ax - SU Ch.6 (N, with AC/DC Adapter)**

FCC ID: BCGA2696 IC: 579C-A2696	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090022-01.BCG	Test Dates: 05/30/2022 - 09/15/2022	EUT Type: Tablet Device	Page 429 of 430

## 8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Apple Tablet Device** **FCC ID: BCGA2696, IC: 579C-A2696** is in compliance with Part 15 Subpart C (15.247) of the FCC Rules and RSS-247 of the Innovation, Science and Economic Development Canada Rules.

FCC ID: BCGA2696 IC: 579C-A2696	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090022-01.BCG	Test Dates: 05/30/2022 - 09/15/2022	EUT Type: Tablet Device	Page 430 of 430