



Test Configuration			
Frequency Range:	2400-2483.5 MHz	Band:	2.4 GHz
Limit Clause(s):	15.247 (b)(3) RSS-247 5.4 d)	Test Method(s):	C63.10 11.9.2.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE20 SU	Duty Cycle (%):	96.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-0.21
Active Port(s):	B (2.4GHz Core 0)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
2412	-	14.80	-	-	-	30.00	-15.20
2437	-	22.50	-	-	-	30.00	-7.50
2472	-	4.82	-	-	-	30.00	-25.18

Table 47 - FCC Maximum Conducted (average) Output Power Results

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Limit (dBm)	Margin (dB)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ					
2412	-	14.80	-	-	-	30.00	-15.20	14.59	36.00	-21.41
2437	-	22.50	-	-	-	30.00	-7.50	22.29	36.00	-13.71
2472	-	4.82	-	-	-	30.00	-25.18	4.61	36.00	-31.39

Table 48 - ISSED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	2400-2483.5 MHz	Band:	2.4 GHz
Limit Clause(s):	15.247 (b)(3) RSS-247 5.4 d)	Test Method(s):	C63.10 11.9.2.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE20 RU26	Duty Cycle (%):	96.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-0.21
Active Port(s):	B (2.4GHz Core 0)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
2412	-	13.36	-	-	-	30.00	-16.64
2437	-	13.17	-	-	-	30.00	-16.83
2472	-	4.72	-	-	-	30.00	-25.28

Table 49 - FCC Maximum Conducted (average) Output Power Results

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Limit (dBm)	Margin (dB)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ					
2412	-	13.36	-	-	-	30.00	-16.64	13.15	36.00	-22.85
2437	-	13.17	-	-	-	30.00	-16.83	12.96	36.00	-23.04
2472	-	4.72	-	-	-	30.00	-25.28	4.51	36.00	-31.49

Table 50 - ISSED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	2400-2483.5 MHz	Band:	2.4 GHz
Limit Clause(s):	15.247 (b)(3) RSS-247 5.4 d)	Test Method(s):	C63.10 11.9.2.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE20 RU52	Duty Cycle (%):	96.8
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-0.21
Active Port(s):	B (2.4GHz Core 0)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
2412	-	14.72	-	-	-	30.00	-15.28
2437	-	16.50	-	-	-	30.00	-13.50
2472	-	4.94	-	-	-	30.00	-25.06

Table 51 - FCC Maximum Conducted (average) Output Power Results

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Limit (dBm)	Margin (dB)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ					
2412	-	14.72	-	-	-	30.00	-15.28	14.51	36.00	-21.49
2437	-	16.50	-	-	-	30.00	-13.50	16.29	36.00	-19.71
2472	-	4.94	-	-	-	30.00	-25.06	4.73	36.00	-31.27

Table 52 - ISD Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	2400-2483.5 MHz	Band:	2.4 GHz
Limit Clause(s):	15.247 (b)(3) RSS-247 5.4 d)	Test Method(s):	C63.10 11.9.2.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	802.11ax HE20 RU106	Duty Cycle (%):	98.1
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-0.21
Active Port(s):	B (2.4GHz Core 0)	Active Chain(s):	1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
2412	-	14.73	-	-	-	30.00	-15.27
2437	-	19.29	-	-	-	30.00	-10.71
2472	-	4.82	-	-	-	30.00	-25.18

Table 53 - FCC Maximum Conducted (average) Output Power Results

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Limit (dBm)	Margin (dB)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ					
2412	-	14.73	-	-	-	30.00	-15.27	14.52	36.00	-21.48
2437	-	19.29	-	-	-	30.00	-10.71	19.08	36.00	-16.92
2472	-	4.82	-	-	-	30.00	-25.18	4.61	36.00	-31.39

Table 54 - ISD Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	2400-2483.5 MHz	Band:	2.4 GHz
Limit Clause(s):	15.247 (b)(3) RSS-247 5.4 d)	Test Method(s):	C63.10 11.9.2.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11n HT20	Duty Cycle (%):	96.7
Modulation Coding Scheme:	MCS2	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	-0.21
Active Port(s):	A+B (2.4GHz Core 1 + 2.4GHz Core 0)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
2412	14.45	14.98	-	-	17.72	30.00	-12.28
2437	21.79	22.43	-	-	25.05	30.00	-4.95
2472	2.91	3.79	-	-	6.37	30.00	-23.63

Table 55 - FCC Maximum Conducted (average) Output Power Results

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Limit (dBm)	Margin (dB)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ					
2412	14.45	14.98	-	-	17.72	30.00	-12.28	17.51	36.00	-18.49
2437	21.79	22.43	-	-	25.05	30.00	-4.95	24.84	36.00	-11.16
2472	2.91	3.79	-	-	6.37	30.00	-23.63	6.16	36.00	-29.84

Table 56 - ISSED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	2400-2483.5 MHz	Band:	2.4 GHz
Limit Clause(s):	15.247 (b)(3) RSS-247 5.4 d)	Test Method(s):	C63.10 11.9.2.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE20 SU	Duty Cycle (%):	96.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	-0.21
Active Port(s):	A+B (2.4GHz Core 1 + 2.4GHz Core 0)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
2412	14.45	14.78	-	-	17.62	30.00	-12.38
2437	21.87	22.26	-	-	25.08	30.00	-4.92
2472	2.91	3.85	-	-	6.41	30.00	-23.59

Table 57 - FCC Maximum Conducted (average) Output Power Results

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Limit (dBm)	Margin (dB)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ					
2412	14.45	14.78	-	-	17.62	30.00	-12.38	17.41	36.00	-18.59
2437	21.87	22.26	-	-	25.08	30.00	-4.92	24.87	36.00	-11.13
2472	2.91	3.85	-	-	6.41	30.00	-23.59	6.20	36.00	-29.80

Table 58 - ISSED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	2400-2483.5 MHz	Band:	2.4 GHz
Limit Clause(s):	15.247 (b)(3) RSS-247 5.4 d)	Test Method(s):	C63.10 11.9.2.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE20 RU26	Duty Cycle (%):	96.6
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	-0.21
Active Port(s):	A+B (2.4GHz Core 1 + 2.4GHz Core 0)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
2412	12.89	13.36	-	-	16.14	30.00	-13.86
2437	13.05	13.31	-	-	16.19	30.00	-13.81
2472	2.85	3.89	-	-	6.39	30.00	-23.61

Table 59 - FCC Maximum Conducted (average) Output Power Results

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Limit (dBm)	Margin (dB)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ					
2412	12.89	13.36	-	-	16.14	30.00	-13.86	15.93	36.00	-20.07
2437	13.05	13.31	-	-	16.19	30.00	-13.81	15.98	36.00	-20.02
2472	2.85	3.89	-	-	6.39	30.00	-23.61	6.18	36.00	-29.82

Table 60 - ISSED Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	2400-2483.5 MHz	Band:	2.4 GHz
Limit Clause(s):	15.247 (b)(3) RSS-247 5.4 d)	Test Method(s):	C63.10 11.9.2.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE20 RU52	Duty Cycle (%):	96.5
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	-0.21
Active Port(s):	A+B (2.4GHz Core 1 + 2.4GHz Core 0)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
2412	14.68	14.83	-	-	17.76	30.00	-12.24
2437	15.95	16.32	-	-	19.14	30.00	-10.86
2472	3.07	3.85	-	-	6.47	30.00	-23.53

Table 61 - FCC Maximum Conducted (average) Output Power Results

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Limit (dBm)	Margin (dB)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ					
2412	14.68	14.83	-	-	17.76	30.00	-12.24	17.55	36.00	-18.45
2437	15.95	16.32	-	-	19.14	30.00	-10.86	18.93	36.00	-17.07
2472	3.07	3.85	-	-	6.47	30.00	-23.53	6.26	36.00	-29.74

Table 62 - ISD Maximum Conducted (average) Output Power Results



Test Configuration			
Frequency Range:	2400-2483.5 MHz	Band:	2.4 GHz
Limit Clause(s):	15.247 (b)(3) RSS-247 5.4 d)	Test Method(s):	C63.10 11.9.2.3.2
Additional Reference(s):	662911 D01 v02r01 F)2)f)(i), 662911 D01 v02r01 E)1)		

DUT Configuration			
Mode:	802.11ax HE20 RU106	Duty Cycle (%):	97.9
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	-
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	-0.21
Active Port(s):	A+B (2.4GHz Core 1 + 2.4GHz Core 0)	Active Chain(s):	0+1

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
2412	14.23	14.95	-	-	17.62	30.00	-12.38
2437	18.97	19.46	-	-	22.23	30.00	-7.77
2472	3.13	3.95	-	-	6.57	30.00	-23.43

Table 63 - FCC Maximum Conducted (average) Output Power Results

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Limit (dBm)	Margin (dB)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ					
2412	14.23	14.95	-	-	17.62	30.00	-12.38	17.41	36.00	-18.59
2437	18.97	19.46	-	-	22.23	30.00	-7.77	22.02	36.00	-13.98
2472	3.13	3.95	-	-	6.57	30.00	-23.43	6.36	36.00	-29.64

Table 64 - ISED Maximum Conducted (average) Output Power Results

FCC 47 CFR Part 15, Limit Clause 15.247 (b)(3)

For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

ISED RSS-247, Limit Clause 5.4 (b)

For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1 W. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e) of the specification.



2.3.7 Test Location and Test Equipment Used

This test was carried out in RF Laboratory 2.

Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Expires
Multimeter	Fluke	79 Series III	611	12	21-Dec-2022
Hygrometer	Rotronic	I-1000	3220	12	05-Nov-2022
AC Programmable Power Supply	iTech	IT7324	5225	-	O/P Mon
Signal Conditioning Unit	TUV SUD	SPECTRUM SCU001	5546	12	06-Apr-2023
USB Power Sensor	Boonton	RTP5008	5820	12	06-Apr-2023
USB Power Sensor	Boonton	RTP5008	5831	12	06-Apr-2023

Table 65

O/P Mon – Output Monitored using calibrated equipment



2.4 Spurious Radiated Emissions

2.4.1 Specification Reference

FCC 47 CFR Part 15C, Clause 15.247 (d) and 15.209
ISED RSS-247, Clause 3.3 and 5.5
ISED RSS-GEN, Clause 6.13 and 8.9

2.4.2 Equipment Under Test and Modification State

A2737, S/N: QQRXMCWXL5 - Modification State 0
A2737, S/N: H32RX9W726 - Modification State 0

2.4.3 Date of Test

05-July-2022 to 28-September-2022

2.4.4 Test Method

This test was performed in accordance with ANSI C63.10, clause 6.3, 6.5 and 6.6.

Ports on the EUT were terminated with loads as described in ANSI C63.4 clause 6.2.4. For EUT's with multiple connectors of the same type, additional interconnecting cables were connected, and pre-scans performed to determine whether the level of the emissions were increased by >2 dB.

In the 30 MHz to 1 GHz range pre-scans were only performed on the mid channel (2437 MHz) only.

The plots shown are the characterisation of the EUT. The limits on the plots represent the most stringent case for restricted bands, (74/54 dBuV/m) when compared to 20 dBc outside restricted bands. The limits shown have been used as a threshold to determine where further measurements are necessary. Where results are within 10 dB of the limits shown on the plots, further investigation was carried out and reported in results tables.

The following conversion can be applied to convert from dBµV/m to µV/m:
 $10^{(\text{Field Strength in dB}\mu\text{V/m}/20)}$

Above 18 GHz, the measurement distance was reduced to 1 m. The limit line was increased by $20 \cdot \text{LOG}(3/1) = 9.54$ dB.

Where formal measurements have been necessary, the results have been presented in the emissions table.

2.4.5 Test Setup Diagram




Figure 57

2.4.6 Environmental Conditions

Ambient Temperature	20.8 - 23.9 °C
Relative Humidity	41.5 - 64.2 %

2.4.7 Test Results

2.4 GHz WLAN

Frequency (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
4824.460	39.8	54.0	-14.3	RMS	26	107	Vertical
4825.270	38.2	54.0	-15.8	RMS	318	215	Horizontal

Table 66 - 2412 MHz (CH1), 802.11g, Core 0, 1 GHz to 26 GHz

No other emissions found within 10 dB of the limit.




Figure 58 - 2412 MHz (CH1), 802.11g, Core 0, 1 GHz to 26 GHz, Horizontal




Figure 59 - 2412 MHz (CH1), 802.11g, Core 0, 1 GHz to 26 GHz, Vertical

Frequency (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
4873.355	59.33	74.0	-14.67	Peak	118	135	Vertical
4873.000	62.20	74.0	-11.8	Peak	61	154	Horizontal
4876.074	47.83	54.0	-6.17	RMS	128	121	Vertical
4873.965	48.67	54.0	-5.33	RMS	61	154	Horizontal

Table 67 - 2437 MHz (CH6), 802.11g, Core 0, 30 MHz to 26 GHz

No other emissions found within 10 dB of the limit.




Figure 60 - 2437 MHz (CH6), 802.11g, Core 0, 30 MHz to 1 GHz, Horizontal (Peak)




Figure 61 - 2437 MHz (CH6), 802.11g, Core 0, 1 GHz to 26 GHz, Horizontal




Figure 62 - 2437 MHz (CH6), 802.11g, Core 0, 30 MHz to 1 GHz, Vertical (Peak)




Figure 63 - 2437 MHz (CH6), 802.11g, Core 0, 1 GHz to 26 GHz, Vertical

Frequency (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
*							

Table 68 - 2472 MHz (CH13), 802.11g, Core 0, 1 GHz to 26 GHz

*No emissions found within 10 dB of the limit.




Figure 64 - 2472 MHz (CH13), 802.11g, Core 0, 1 GHz to 26 GHz, Horizontal




Figure 65 - 2472 MHz (CH13), 802.11g, Core 0, 1 GHz to 26 GHz, Vertical

Frequency (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
4820.782	38.5	54.0	-15.6	RMS	54	201	Horizontal
4825.903	38.8	54.0	-15.2	RMS	118	144	Vertical

Table 69 - 2412 MHz (CH1), HT20, Core 0 + Core 1, 1 GHz to 26 GHz

No other emissions found within 10 dB of the limit.




Figure 66 - 2412 MHz (CH1), HT20, Core 0 + Core 1, 1 GHz to 26 GHz, Horizontal




Figure 67 - 2412 MHz (CH1), HT20, Core 0 + Core 1, 1 GHz to 26 GHz, Vertical

Frequency (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
4875.290	59.78	74.0	-14.22	Peak	118	100	Vertical
4873.395	46.38	54.0	-7.62	RMS	118	100	Vertical
4873.530	48.40	54.0	-5.6	RMS	61	225	Horizontal
4871.045	62.15	74.0	-11.85	Peak	61	225	Horizontal

Table 70 - 2437 MHz (CH6), HT20, Core 0 + Core 1, 30 MHz to 26 GHz

No other emissions found within 10 dB of the limit.




Figure 68 - 2437 MHz (CH6), HT20, Core 0 + Core 1, 30 MHz to 1 GHz, Horizontal (Peak)




Figure 69 - 2437 MHz (CH6), HT20, Core 0 + Core 1, 1 GHz to 26 GHz, Horizontal




Figure 70 - 2437 MHz (CH6), HT20, Core 0 + Core 1, 30 MHz to 1 GHz, Vertical (Peak)




Figure 71 - 2437 MHz (CH6), HT20, Core 0 + Core 1, 1 GHz to 26 GHz, Vertical

Frequency (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
*							

Table 71 - 2472 MHz (CH13), HT20, Core 0 + Core 1, 1 GHz to 26 GHz

*No emissions found within 10 dB of the limit.




Figure 72 - 2472 MHz (CH13), HT20, Core 0 + Core 1, 1 GHz to 26 GHz, Horizontal




Figure 73 - 2472 MHz (CH13), HT20, Core 0 + Core 1, 1 GHz to 26 GHz, Vertical



Frequency (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
4823.993	46.3	54.0	-7.7	RMS	118	128	Vertical
4824.025	42.5	54.0	-11.5	RMS	209	101	Horizontal

Table 72 - 2412 MHz (CH1), 802.11b, Core 1, 1 GHz to 26 GHz

No other emissions found within 10 dB of the limit.




Figure 74 - 2412 MHz (CH1), 802.11b, Core 1, 1 GHz to 26 GHz, Horizontal




Figure 75 - 2412 MHz (CH1), 802.11b, Core 1, 1 GHz to 26 GHz, Vertical

Frequency (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
4873.990	48.7	54.0	-5.3	RMS	117	137	Vertical
4874.050	45.2	54.0	-8.8	RMS	293	100	Horizontal

Table 73 - 2437 MHz (CH6), 802.11b, Core 1, 30 MHz to 26 GHz

No other emissions found within 10 dB of the limit.




Figure 76 - 2437 MHz (CH6), 802.11b, Core 1, 30 MHz to 1 GHz, Horizontal (Peak)




Figure 77 - 2437 MHz (CH6), 802.11b, Core 1, 1 GHz to 26 GHz, Horizontal




Figure 78 - 2437 MHz (CH6), 802.11b, Core 1, 30 MHz to 1 GHz, Vertical (Peak)




Figure 79 - 2437 MHz (CH6), 802.11b, Core 1, 1 GHz to 26 GHz, Vertical



Frequency (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
*							

Table 74 - 2472 MHz (CH13), 802.11b, Core 1, 1 GHz to 26 GHz

*No emissions found within 10 dB of the limit.




Figure 80 - 2472 MHz (CH13), 802.11b, Core 1, 1 GHz to 26 GHz, Horizontal




Figure 81 - 2472 MHz (CH13), 802.11b, Core 1, 1 GHz to 26 GHz, Vertical



Frequency (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
*							

Table 75 - 2412 MHz (CH1), 802.11g, Core 1, 1 GHz to 26 GHz

*No emissions found within 10 dB of the limit.




Figure 82 - 2412 MHz (CH1), 802.11g, Core 1, 1 GHz to 26 GHz, Horizontal




Figure 83 - 2412 MHz (CH1), 802.11g, Core 1, 1 GHz to 26 GHz, Vertical



Frequency (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
*							

Table 76 - 2437 MHz (CH6), 802.11g, Core 1, 30 MHz to 26 GHz

*No emissions found within 10 dB of the limit.




Figure 84 - 2437 MHz (CH6), 802.11g, Core 1, 30 MHz to 1 GHz, Horizontal (Peak)




Figure 85 - 2437 MHz (CH6), 802.11g, Core 1, 1 GHz to 26 GHz, Horizontal




Figure 86 - 2437 MHz (CH6), 802.11g, Core 1, 30 MHz to 1 GHz, Vertical (Peak)




Figure 87 - 2437 MHz (CH6), 802.11g, Core 1, 1 GHz to 26 GHz, Vertical

Frequency (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
*							

Table 77 - 2472 MHz (CH13), 802.11g, Core 1, 1 GHz to 26 GHz

*No emissions found within 10 dB of the limit.




Figure 88 - 2472 MHz (CH13), 802.11g, Core 1, 1 GHz to 26 GHz, Horizontal




Figure 89 - 2472 MHz (CH13), 802.11g, Core 1, 1 GHz to 26 GHz, Vertical

Frequency (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
4807.722	56.5	74.0	-17.5	Peak	124	111	Vertical
4807.966	40.5	54.0	-13.5	RMS	53	213	Horizontal
4808.124	57.5	74.0	-16.5	Peak	53	213	Horizontal
4808.222	40.7	54.0	-13.3	RMS	124	111	Vertical

Table 78 - 2412 MHz (CH1), HE20, RU26-0, Core 0 + Core 1, 1 GHz to 26 GHz

No other emissions found within 10 dB of the limit.




Figure 90 - 2412 MHz (CH1), HE20, RU26-0, Core 0 + Core 1, 1 GHz to 26 GHz, Horizontal




Figure 91 - 2412 MHz (CH1), HE20, RU26-0, Core 0 + Core 1, 1 GHz to 26 GHz, Vertical

Frequency (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
4857.647	56.3	74.0	-17.7	Peak	98	121	Horizontal
4857.767	58.1	74.0	-15.9	Peak	118	111	Vertical
4857.812	40.6	54.0	-13.4	RMS	98	121	Horizontal
4857.977	42.3	54.0	-11.7	RMS	118	111	Vertical

Table 79 - 2437 MHz (CH6), HE20, RU26-0, Core 0 + Core 1, 30 MHz to 26 GHz

No other emissions found within 10 dB of the limit.




Figure 92 - 2437 MHz (CH6), HE20, RU26-0, Core 0 + Core 1, 30 MHz to 1 GHz, Horizontal (Peak)




Figure 93 - 2437 MHz (CH6), HE20, RU26-0, Core 0 + Core 1, 1 GHz to 26 GHz, Horizontal




Figure 94 - 2437 MHz (CH6), HE20, RU26-0, Core 0 + Core 1, 30 MHz to 1 GHz, Vertical (Peak)




Figure 95 - 2437 MHz (CH6), HE20, RU26-0, Core 0 + Core 1, 1 GHz to 26 GHz, Vertical

Frequency (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation
*							

Table 80 - 2472 MHz (CH13), HE20, RU26-0, Core 0 + Core 1, 1 GHz to 26 GHz

*No emissions found within 10 dB of the limit.




Figure 96 - 2472 MHz (CH13), HE20, RU26-0, Core 0 + Core 1, 1 GHz to 26 GHz, Horizontal




Figure 97 - 2472 MHz (CH13), HE20, RU26-0, Core 0 + Core 1, 1 GHz to 26 GHz, Vertical



FCC 47 CFR Part 15, Limit Clause 15.247 (d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in 15.209(a)

ISED RSS-247, Limit Clause 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

In addition, radiated emissions which fall in the restricted bands, as defined in RSS-GEN, clause 8.10, must also comply with the radiated emission limits specified in RSS-GEN clause 8.9.



2.4.8 Test Location and Test Equipment Used

This test was carried out in RF Chamber 11 and RF Chamber 14.

Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Expires
DC Power Supply	Hewlett Packard	6269B	1909	-	TU
Band Reject Filter - 2.425 GHz	Wainwright	WRCGV14-2390-2400-2450-2460-50SS	5066	12	11-Oct-2022
Band Reject Filter - 2.4585 GHz	Wainwright	WRCGV14-2423.5-2433.5-2483.5-2493.5-50SS	5068	12	11-Oct-2022
EMI Test Receiver	Rohde & Schwarz	ESW44	5084	12	17-May-2023
Cable (18 GHz)	Rosenberger	LU7-071-1000	5102	12	20-Oct-2022
Cable (18 GHz)	Rosenberger	LU7-071-1000	5103	12	17-Nov-2022
Cable (18 GHz)	Rosenberger	LU7-071-1000	5104	12	13-Dec-2022
Emissions Software	TUV SUD	EmX V3.1.4	5125	-	Software
Screened Room (11)	Rainford	Rainford	5136	36	24-Nov-2024
Antenna (DRG 1-10.5GHz)	Schwarzbeck	BBHA9120B	5215	12	28-May-2023
DRG Horn Antenna (7.5-18GHz)	Schwarzbeck	HWRD750	5216	12	29-May-2023
Antenna (DRG, 15 GHz to 40 GHz)	Schwarzbeck	BBHA 9170	5217	12	25-Jan-2023
Pre Amp 1 - 26.5 GHz	Agilent Technologies	8449B	5445	12	12-May-2023
2m SMA Cable	Junkosha	MWX221-02000AMSAMS/A	5518	12	12-Apr-2023
8m N Type Cable	Junkosha	MWX221-08000NMSNMS/B	5522	12	24-Mar-2023
3 GHz High pass Filter	Wainwright	WHKX12-2580-3000-18000-80SS	5547	12	11-May-2023
7 GHz High pass Filter	Wainwright	WHKX12-5850-6800-18000-80SS	5550	12	19-May-2023
8 - 18 GHz Amplifier	Wright Technologies	APS06-0061	5595	12	21-Sep-2022*
Thermo-Hygro-Barometer	PCE Instruments	PCE-THB 40	5605	12	23-Sep-2022*
EMI Test Receiver	Rohde & Schwarz	ESW44	5912	12	17-Feb-2023
Cable (K Type 2m)	Junkosha	MWX241-01000KMSKMS/B	5934	12	14-May-2023
DRG Horn Antenna (7.5-18GHz)	Schwarzbeck	HWRD750	5941	12	29-May-2023
TRILOG Super Broadband Test Antenna	Schwarzbeck	VULB 9168	5943	24	03-Feb-2024
5m Semi-Anechoic Chamber (Dual-Axis)	Albatross Projects	RF Chamber 14	5958	36	26-Apr-2025



Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Expires
Compact Antenna Mast	Maturo Gmbh	CAM4.0-P	5959	-	TU
Mast & Turntable Controller	Maturo Gmbh	FCU3.0	5960	-	TU
Tilt Antenna Mast	Maturo Gmbh	BAM4.5-P	5961	-	TU
Turntable	Maturo Gmbh	TT1.5SI	5962	-	TU
Cable (sma to sma 1m)	Junkosha	MWX221-01000AMSAMS/A	5997	12	06-Jun-2023
Cable (SMA to SMA 4.5m)	Junkosha	MWX221-04500AMSAMS/A	6002	12	06-Jun-2023
Cable (SMA to SMA 6.5m)	Junkosha	MWX221-06500AMSAMS/B	6003	12	07-Jun-2023
Cable (SMA to SMA 1m)	Junkosha	MWX221-01000AMSAMS/A	6008	12	06-Jun-2023
Cable (N to N 8m)	Junkosha	MWX221-08000NMSNMS/A	6017	12	05-Jun-2023
Horn Antenna (1-10 GHz)	Schwarzbeck	BBHA9120B	6141	12	21-Jun-2023
SAC Switch Unit	TUV SUD	SSU001	6144	12	07-Jul-2023
Humidity & Temperature meter	R.S Components	1364	6150	12	17-Jun-2023
Double Ridge Active Horn Antenna (18-40 GHz)	Com-Power	AHA-840	6187	24	02-Jun-2024
8GHz Highpass Filter	Wainwright	WHKX 7150 8000 18000 50SS	6195	12	15-Jul-2023
Pre Amp 8 - 18 GHz	Wright Technologies	APS06 0061	6198	12	19-Jul-2023
Attenuator 4dB	Pasternack	PE7074-4	6202	24	16-Jul-2024
Cable (SMA to SMA 20cm)	TUV SUD	MH-FH 8-18	6215	12	25-Jul-2023

Table 81

* This equipment was only employed during its calibration period.

TU - Traceability Unscheduled



2.5 Authorised Band Edges

2.5.1 Specification Reference

FCC 47 CFR Part 15C, Clause 15.247 (d)
ISED RSS-247, Clause 5.5

2.5.2 Equipment Under Test and Modification State

A2737, S/N: QQRXMCWXL5 - Modification State 0

2.5.3 Date of Test

10-May-2022 to 26-May-2022

2.5.4 Test Method

The test was performed in accordance with ANSI C63.10, clause 6.10.4.

Since compliance with the power limits in section 2.1 was shown by RMS averaging across all symbols in the signaling alphabet, a 30 dBc limit rather than 20 dBc limit was applied in accordance with FCC 47 CFR Part 15.247(d) and RSS-247 clause 5.5.

2.5.5 Environmental Conditions

Ambient Temperature	21.5 - 25.7 °C
Relative Humidity	36.8 - 50.7 %



2.5.6 Test Results

2.4 GHz WLAN

SISO

Mode	Data Rate /MCS	Resource size	Resource Index	TX Frequency (MHz)	Band Edge Frequency (MHz)	Level (dBc)
802.11b, Core 0	1 Mbps	-	-	2412	2400	-46.50
802.11g, Core 0	54 Mbps	-	-	2412	2400	-34.79
802.11n HT20, Core 0	MCS2	-	-	2412	2400	-34.74
802.11ax HE20, Core 0	MCS4x1	SU	-	2412	2400	-34.53
802.11ax HE20, Core 0	MCS9x1	26	0	2412	2400	-47.12

Table 82 - SISO Authorised Band Edge Results




Figure 98 - 802.11b, Core 0 - 2412 MHz
Band Edge Frequency 2400 MHz




Figure 99- 802.11g, Core 0 - 2412 MHz
Band Edge Frequency 2400 MHz




Figure 100- 802.11n HT20, Core 0 - 2412 MHz
Band Edge Frequency 2400 MHz




Figure 101- 802.11ax HE20, Core 0, SU - 2412 MHz
Band Edge Frequency 2400 MHz





Figure 102- 802.11ax HE20, Core 0, 26-0 - 2412 MHz
Band Edge Frequency 2400 MHz


2TX MIMO

Mode	Data Rate /MCS	Resource size	Resource Index	TX Frequency (MHz)	Band Edge Frequency (MHz)	Level (dBc)
802.11n HT20, Cores 0-1	MCS2	-	-	2412	2400	-34.56
802.11ax HE20, Cores 0 -1	MCS2x1	SU	-	2412	2400	-34.67
802.11ax HE20, Cores 0 -1	MCS9x1	26	0	2412	2400	-50.22


Table 83 - 2TX MIMO Authorised Band Edge Results



**Figure 103 - 802.11n HT20, Cores 0-1 - 2412 MHz
Band Edge Frequency 2400 MHz**



**Figure 104- 802.11ax HE20, Cores 0-1, SU - 2412 MHz
Band Edge Frequency 2400 MHz**



**Figure 105- 802.11ax HE20, Cores 0-1, 26-0 - 2412 MHz
Band Edge Frequency 2400 MHz**



FCC 47 CFR Part 15, Limit Clause 15.247 (d)

20 dB below the fundamental measured in a 100 kHz bandwidth using a peak detector. If the transmitter complies with the conducted power limits, based on the use of RMS averaging over a time interval, the attenuation required shall be 30 dB below the fundamental instead of 20 dB.

ISED RSS-247, Limit Clause 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.



2.5.7 Test Location and Test Equipment Used

This test was carried out in EMC Chamber 5.

Instrument	Manufacturer	Type No.	TE No.	Calibration Period (months)	Calibration Expiry Date
EMI Test Receiver	Rohde & Schwarz	ESW44	5084	12	22-Mar-2022
EMI Test Receiver	Rohde & Schwarz	ESW44	5084	12	17-May-2023
Screened Room (5)	Rainford	Rainford	1545	36	15-Apr-2024
Turntable Controller	Inn-Co GmbH	CO 1000	1606	-	TU
Mast Controller	Maturo GmbH	NCD	4810	-	TU
Tilt Antenna Mast	Maturo GmbH	TAM 4.0-P	4811	-	TU
Antenna (DRG 1-10.5GHz)	Schwarzbeck	BBHA9120B	4848	12	28-May-2022
Attenuator 5W 10dB DC-18GHz	Aaren	AT40A-4041-D18-10	5492	12	11-Apr-2023
Emissions Software	TUV SUD	EmX V3.1.4	5125	-	Software
Preamplifier (30dB 1GHz to 18GHz)	Schwarzbeck	BBV 9718 C	5261	12	08-Apr-2023
1m -SMA Cable	Junkosha	MWX221-01000AMSAMS/A	5513	12	12-Apr-2023
2m SMA Cable	Junkosha	MWX221-02000AMSAMS/A	5517	12	12-Apr-2023
8m N-Type Cable	Junkosha	MWX221-08000NMSNMS/B	5520	12	24-Mar-2023
Thermo-Hygro-Barometer	PCE Instruments	PCE-THB 40	5604	12	22-Sep-2022

Table 84

TU - Traceability Unscheduled



2.6 Power Spectral Density

2.6.1 Specification Reference

FCC 47 CFR Part 15C, Clause 15.247 (e)
ISED RSS-247, Clause 5.2
ISED RSS-GEN, Clause, 6.12

2.6.2 Equipment Under Test and Modification State

A2737, S/N: MW5QG9Q771 - Modification State 0

2.6.3 Date of Test

20-September-2022

2.6.4 Test Method

This test was performed in accordance with ANSI C63.10, clause 11.10.5 (AVGPSD-2).

Where the EUT duty cycle was < 98 % and repeatable within 2 %, the spectrum analyser was set to trace (power) averaging and a duty cycle correction was added as calculated in the result tables below (Method AVGPSD-2).

MIMO output port summing was performed in accordance with KDB 662911 D01 E)2)b).

2.6.5 Environmental Conditions

Ambient Temperature	22.0 °C
Relative Humidity	51.1 %



2.6.6 Test Results

2.4 GHz WLAN

Test Configuration			
Frequency Range:	2400-2483.5 MHz	Band:	2.4 GHz
Limit Clause(s):	15.247 (e) RSS-247 5.2 b)	Test Method(s):	C63.10 11.10.5
Additional Reference(s):	-		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11b	Duty Cycle (%):	98.8
Data Rate:	1 Mbps	DCCF (dB):	0.05
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-
Active Port(s):	B (2.4GHz Core 0)	Active Chain(s):	1

Test Frequency (MHz)	RBW (kHz)	PSD (dBm/RBW)					Limit (dBm/3 kHz)	Margin (dB)
		A	B	C	D	Σ		
2412	3.0	-	-9.35	-	-	-	8.00	-17.35
2437	3.0	-	-7.61	-	-	-	8.00	-15.61
2472	3.0	-	-15.46	-	-	-	8.00	-23.46

Table 85 - Maximum Power Spectral Density Results

Test Configuration			
Frequency Range:	2400-2483.5 MHz	Band:	2.4 GHz
Limit Clause(s):	15.247 (e) RSS-247 5.2 b)	Test Method(s):	C63.10 11.10.5
Additional Reference(s):	-		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11g	Duty Cycle (%):	97.8
Data Rate:	12 Mbps	DCCF (dB):	0.10
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-
Active Port(s):	B (2.4GHz Core 0)	Active Chain(s):	1

Test Frequency (MHz)	RBW (kHz)	PSD (dBm/RBW)					Limit (dBm/3 kHz)	Margin (dB)
		A	B	C	D	Σ		
2412	3.0	-	-13.15	-	-	-	8.00	-21.15
2437	3.0	-	-6.74	-	-	-	8.00	-14.74
2472	3.0	-	-23.23	-	-	-	8.00	-31.23

Table 86 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	2400-2483.5 MHz	Band:	2.4 GHz
Limit Clause(s):	15.247 (e) RSS-247 5.2 b)	Test Method(s):	C63.10 11.10.5
Additional Reference(s):	-		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11n HT20	Duty Cycle (%):	96.7
Modulation Coding Scheme:	MCS2	DCCF (dB):	0.14
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-
Active Port(s):	B (2.4GHz Core 0)	Active Chain(s):	1

Test Frequency (MHz)	RBW (kHz)	PSD (dBm/RBW)					Limit (dBm/3 kHz)	Margin (dB)
		A	B	C	D	Σ		
2412	3.0	-	-14.61	-	-	-	8.00	-22.61
2437	3.0	-	-8.40	-	-	-	8.00	-16.40
2472	3.0	-	-25.53	-	-	-	8.00	-33.53

Table 87 - Maximum Power Spectral Density Results

Test Configuration			
Frequency Range:	2400-2483.5 MHz	Band:	2.4 GHz
Limit Clause(s):	15.247 (e) RSS-247 5.2 b)	Test Method(s):	C63.10 11.10.5
Additional Reference(s):	-		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 SU	Duty Cycle (%):	96.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.18
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-
Active Port(s):	B (2.4GHz Core 0)	Active Chain(s):	1

Test Frequency (MHz)	RBW (kHz)	PSD (dBm/RBW)					Limit (dBm/3 kHz)	Margin (dB)
		A	B	C	D	Σ		
2412	3.0	-	-16.19	-	-	-	8.00	-24.19
2437	3.0	-	-7.94	-	-	-	8.00	-15.94
2472	3.0	-	-25.63	-	-	-	8.00	-33.63

Table 88 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	2400-2483.5 MHz	Band:	2.4 GHz
Limit Clause(s):	15.247 (e) RSS-247 5.2 b)	Test Method(s):	C63.10 11.10.5
Additional Reference(s):	-		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU26	Duty Cycle (%):	96.7
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.15
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-
Active Port(s):	B (2.4GHz Core 0)	Active Chain(s):	1

Test Frequency (MHz)	RBW (kHz)	PSD (dBm/RBW)					Limit (dBm/3 kHz)	Margin (dB)
		A	B	C	D	Σ		
2412	3.0	-	-11.66	-	-	-	8.00	-19.66
2437	3.0	-	-11.96	-	-	-	8.00	-19.96
2472	3.0	-	-20.72	-	-	-	8.00	-28.72

Table 89 - Maximum Power Spectral Density Results

Test Configuration			
Frequency Range:	2400-2483.5 MHz	Band:	2.4 GHz
Limit Clause(s):	15.247 (e) RSS-247 5.2 b)	Test Method(s):	C63.10 11.10.5
Additional Reference(s):	-		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU52	Duty Cycle (%):	96.8
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.14
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-
Active Port(s):	B (2.4GHz Core 0)	Active Chain(s):	1

Test Frequency (MHz)	RBW (kHz)	PSD (dBm/RBW)					Limit (dBm/3 kHz)	Margin (dB)
		A	B	C	D	Σ		
2412	3.0	-	-11.35	-	-	-	8.00	-19.35
2437	3.0	-	-9.28	-	-	-	8.00	-17.28
2472	3.0	-	-21.08	-	-	-	8.00	-29.08

Table 90 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	2400-2483.5 MHz	Band:	2.4 GHz
Limit Clause(s):	15.247 (e) RSS-247 5.2 b)	Test Method(s):	C63.10 11.10.5
Additional Reference(s):	-		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU106	Duty Cycle (%):	98.1
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.08
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-
Active Port(s):	B (2.4GHz Core 0)	Active Chain(s):	1

Test Frequency (MHz)	RBW (kHz)	PSD (dBm/RBW)					Limit (dBm/3 kHz)	Margin (dB)
		A	B	C	D	Σ		
2412	3.0	-	-12.86	-	-	-	8.00	-20.86
2437	3.0	-	-10.95	-	-	-	8.00	-18.95
2472	3.0	-	-23.81	-	-	-	8.00	-31.81

Table 91 - Maximum Power Spectral Density Results

Test Configuration			
Frequency Range:	2400-2483.5 MHz	Band:	2.4 GHz
Limit Clause(s):	15.247 (e) RSS-247 5.2 b)	Test Method(s):	C63.10 11.10.5
Additional Reference(s):	662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11n HT20	Duty Cycle (%):	96.7
Modulation Coding Scheme:	MCS2	DCCF (dB):	0.15
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	-
Active Port(s):	A+B (2.4GHz Core 1 + 2.4GHz Core 0)	Active Chain(s):	0+1

Test Frequency (MHz)	RBW (kHz)	PSD (dBm/RBW)					Limit (dBm/3 kHz)	Margin (dB)
		A	B	C	D	Σ		
2412	3.0	-15.37	-15.61	-	-	-12.48	8.00	-20.48
2437	3.0	-8.03	-8.57	-	-	-5.28	8.00	-13.28
2472	3.0	-27.23	-26.89	-	-	-24.05	8.00	-32.05

Table 92 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	2400-2483.5 MHz	Band:	2.4 GHz
Limit Clause(s):	15.247 (e) RSS-247 5.2 b)	Test Method(s):	C63.10 11.10.5
Additional Reference(s):	662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 SU	Duty Cycle (%):	96.0
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.18
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	-
Active Port(s):	A+B (2.4GHz Core 1 + 2.4GHz Core 0)	Active Chain(s):	0+1

Test Frequency (MHz)	RBW (kHz)	PSD (dBm/RBW)					Limit (dBm/3 kHz)	Margin (dB)
		A	B	C	D	Σ		
2412	3.0	-17.10	-15.81	-	-	-13.39	8.00	-21.39
2437	3.0	-9.65	-8.73	-	-	-6.15	8.00	-14.15
2472	3.0	-27.96	-27.26	-	-	-24.59	8.00	-32.59

Table 93 - Maximum Power Spectral Density Results

Test Configuration			
Frequency Range:	2400-2483.5 MHz	Band:	2.4 GHz
Limit Clause(s):	15.247 (e) RSS-247 5.2 b)	Test Method(s):	C63.10 11.10.5
Additional Reference(s):	662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU26	Duty Cycle (%):	96.6
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.15
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	-
Active Port(s):	A+B (2.4GHz Core 1 + 2.4GHz Core 0)	Active Chain(s):	0+1

Test Frequency (MHz)	RBW (kHz)	PSD (dBm/RBW)					Limit (dBm/3 kHz)	Margin (dB)
		A	B	C	D	Σ		
2412	3.0	-12.07	-11.92	-	-	-8.98	8.00	-16.98
2437	3.0	-12.59	-11.99	-	-	-9.27	8.00	-17.27
2472	3.0	-22.49	-20.85	-	-	-18.58	8.00	-26.58

Table 94 - Maximum Power Spectral Density Results



Test Configuration			
Frequency Range:	2400-2483.5 MHz	Band:	2.4 GHz
Limit Clause(s):	15.247 (e) RSS-247 5.2 b)	Test Method(s):	C63.10 11.10.5
Additional Reference(s):	662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU52	Duty Cycle (%):	96.5
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.15
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	-
Active Port(s):	A+B (2.4GHz Core 1 + 2.4GHz Core 0)	Active Chain(s):	0+1

Test Frequency (MHz)	RBW (kHz)	PSD (dBm/RBW)					Limit (dBm/3 kHz)	Margin (dB)
		A	B	C	D	Σ		
2412	3.0	-11.40	-10.40	-	-	-7.86	8.00	-15.86
2437	3.0	-9.85	-9.28	-	-	-6.54	8.00	-14.54
2472	3.0	-22.96	-21.69	-	-	-19.27	8.00	-27.27

Table 95 - Maximum Power Spectral Density Results

Test Configuration			
Frequency Range:	2400-2483.5 MHz	Band:	2.4 GHz
Limit Clause(s):	15.247 (e) RSS-247 5.2 b)	Test Method(s):	C63.10 11.10.5
Additional Reference(s):	662911 D01 v02r01 E)2)b)		
Note(s):	DCCF was added to the spectrum analyser reference level offset.		

DUT Configuration			
Mode:	802.11ax HE20 RU106	Duty Cycle (%):	97.9
Modulation Coding Scheme:	MCS2x1	DCCF (dB):	0.09
Antenna Configuration:	MIMO CDD	Peak Antenna Gain (dBi):	-
Active Port(s):	A+B (2.4GHz Core 1 + 2.4GHz Core 0)	Active Chain(s):	0+1

Test Frequency (MHz)	RBW (kHz)	PSD (dBm/RBW)					Limit (dBm/3 kHz)	Margin (dB)
		A	B	C	D	Σ		
2412	3.0	-15.09	-13.69	-	-	-11.32	8.00	-19.32
2437	3.0	-11.23	-10.64	-	-	-7.92	8.00	-15.92
2472	3.0	-26.27	-25.32	-	-	-22.76	8.00	-30.76

Table 96 - Maximum Power Spectral Density Results



FCC 47 CFR Part 15, Limit Clause 15.247 (e)

The power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

ISED RSS-247, Limit Clause 5.2(b)

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission

2.6.7 Test Location and Test Equipment Used

This test was carried out in RF Laboratory 2.

Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Expires
Multimeter	Fluke	79 Series III	611	12	21-Dec-2022
Hygrometer	Rotronic	I-1000	3220	12	05-Nov-2022
Frequency Standard	Spectracom	SecureSync 1200-0408-0601	4393	6	01-Feb-2023
AC Programmable Power Supply	iTech	IT7324	5225	-	O/P Mon
MXA Signal Analyser	Keysight Technologies	N9020B	5528	24	21-Mar-2024
Signal Conditioning Unit	TUV SUD	SPECTRUM SCU001	5546	12	06-Apr-2023

Table 97

O/P Mon – Output Monitored using calibrated equipment



3 Measurement Uncertainty

For a 95% confidence level, the measurement uncertainties for defined systems are:

Test Name	Measurement Uncertainty
Restricted Band Edges	30 MHz to 1 GHz: ± 5.2 dB 1 GHz to 40 GHz: ± 6.3 dB
Emission Bandwidth	± 545.66 kHz
Maximum Conducted Output Power	± 3.2 dB
Spurious Radiated Emissions	30 MHz to 1 GHz: ± 5.2 dB 1 GHz to 40 GHz: ± 6.3 dB
Authorised Band Edges	30 MHz to 1 GHz: ± 5.2 dB 1 GHz to 40 GHz: ± 6.3 dB
Power Spectral Density	± 3.2 dB

Table 98

Measurement Uncertainty Decision Rule – Accuracy Method

Determination of conformity with the specification limits is based on the decision rule according to IEC Guide 115:2007, Clause 4.4.3 and 4.5.1. (Procedure 2). The measurement results are directly compared with the test limit to determine conformance with the requirements of the standard.

Risk: The uncertainty of measurement about the measured result is negligible with regard to the final pass/fail decision. The measurement result can be directly compared with the test limit to determine conformance with the requirement (compare IEC Guide 115). The level of risk to falsely accept and falsely reject items is further described in ILAC-G8.