

Frequency [MHz]	Channel No.	802.11 Mode	Mode	Data Rate [Mbps]	Antenna 3c Power Density [dBm/MHz]	Antenna 1b Power Density [dBm/MHz]	Summed Power Density [dBm/MHz]	Directional Antenna Gain [dBi]	e.i.r.p. Power Density [dBm/MHz]	ISED Max e.i.r.p. Power Density [dBm/MHz]	Margin [dB]
5180	36	n (20MHz)	SDM	13/14.4 (MCS8)	2.56	2.03	5.32	1.19	6.51	10.0	-3.49
5200	40	n (20MHz)	SDM	13/14.4 (MCS8)	2.57	1.69	5.16	1.19	6.35	10.0	-3.65
5240	48	n (20MHz)	SDM	13/14.4 (MCS8)	2.61	1.50	5.10	1.19	6.29	10.0	-3.71
5180	36	ax (SU) (20MHz)	SDM	16/17.2 (MCS0)	2.49	1.65	5.10	1.19	6.29	10.0	-3.71
5200	40	ax (SU) (20MHz)	SDM	16/17.2 (MCS0)	2.51	1.38	4.99	1.19	6.18	10.0	-3.82
5240	48	ax (SU) (20MHz)	SDM	16/17.2 (MCS0)	2.39	1.17	4.83	1.19	6.02	10.0	-3.98
5190	38	n (40MHz)	SDM	27/30 (MCS8)	0.57	-0.55	3.06	1.19	4.25	10.0	-5.75
5230	46	n (40MHz)	SDM	27/30 (MCS8)	2.29	1.66	5.00	1.19	6.19	10.0	-3.81
5190	38	ax (SU) (40MHz)	CDD	32/34.4 (MCS0)	-1.78	-2.61	0.83	3.96	4.79	10.0	-5.21
5230	46	ax (SU) (40MHz)	SDM	32/34.4 (MCS0)	1.27	0.21	3.78	1.19	4.97	10.0	-5.03
5210	42	ac (80MHz)	CDD	58.5/65 (MCS0)	-2.07	-2.98	0.51	3.96	4.47	10.0	-5.53
5210	42	ax (SU) (80MHz)	CDD	68/72.1 (MCS0)	-4.41	-5.17	-1.76	3.96	2.20	10.0	-7.80

**Table 7-200. ISED Band 1 e.i.r.p. Power Spectral Density Measurements CDD Diversity (Low Data Rate)**







Frequency [MHz]	Channel No.	802.11 Mode	Mode	Data Rate [Mbps]	Antenna 3c Power Density [dBm/MHz]	Antenna 1b Power Density [dBm/MHz]	Summed Power Density [dBm/MHz]	Directional Antenna Gain [dBi]	e.i.r.p. Power Density [dBm/MHz]	ISED Max e.i.r.p. Power Density [dBm/MHz]	Margin [dB]
5180	36	n (20MHz)	SDM	78/86.7 (MCS12)	3.26	2.31	5.82	1.19	7.01	10.0	-2.99
5200	40	n (20MHz)	SDM	78/86.7 (MCS12)	3.02	1.95	5.53	1.19	6.72	10.0	-3.28
5240	48	n (20MHz)	SDM	78/86.7 (MCS12)	2.99	2.01	5.54	1.19	6.73	10.0	-3.27
5180	36	ax (SU) (20MHz)	SDM	98/103.2 (MCS4)	3.04	2.31	5.70	1.19	6.89	10.0	-3.11
5200	40	ax (SU) (20MHz)	SDM	98/103.2 (MCS4)	3.20	2.09	5.69	1.19	6.88	10.0	-3.12
5240	48	ax (SU) (20MHz)	SDM	98/103.2 (MCS4)	2.81	1.77	5.33	1.19	6.52	10.0	-3.48
5190	38	n (40MHz)	SDM	162/180 (MCS12)	0.74	0.54	3.65	1.19	4.84	10.0	-5.16
5230	46	n (40MHz)	SDM	162/180 (MCS12)	2.92	2.07	5.52	1.19	6.71	10.0	-3.29
5190	38	ax (SU) (40MHz)	CDD	196/206.5 (MCS4)	-1.58	-2.46	1.01	3.96	4.98	10.0	-5.02
5230	46	ax (SU) (40MHz)	SDM	196/206.5 (MCS4)	1.61	0.84	4.25	1.19	5.44	10.0	-4.56
5210	42	ac (80MHz)	CDD	351/390 (MCS4)	-1.76	-2.90	0.72	3.96	4.68	10.0	-5.32
5210	42	ax (SU) (80MHz)	CDD	351/390 (MCS4)	-4.19	-4.92	-1.53	3.96	2.43	10.0	-7.57

**Table 7-201. ISED Band 1 e.i.r.p. Power Spectral Density Measurements CDD Diversity (Mid Data Rate)**


Frequency [MHz]	Channel No.	802.11 Mode	Mode	Data Rate [Mbps]	Antenna 3c Power Density [dBm/MHz]	Antenna 1b Power Density [dBm/MHz]	Summed Power Density [dBm/MHz]	Directional Antenna Gain [dBi]	e.i.r.p. Power Density [dBm/MHz]	ISED Max e.i.r.p. Power Density [dBm/MHz]	Margin [dB]
5180	36	n (20MHz)	SDM	130/144.4 (MCS15)	1.85	0.83	4.38	1.19	5.57	10.0	-4.43
5200	40	n (20MHz)	SDM	130/144.4 (MCS15)	1.91	0.81	4.41	1.19	5.60	10.0	-4.40
5240	48	n (20MHz)	SDM	130/144.4 (MCS15)	2.03	0.86	4.49	1.19	5.68	10.0	-4.32
5180	36	ax (SU) (20MHz)	SDM	270/286.8 (MCS11)	2.17	1.10	4.67	1.19	5.86	10.0	-4.14
5200	40	ax (SU) (20MHz)	SDM	270/286.8 (MCS11)	2.08	1.01	4.59	1.19	5.77	10.0	-4.23
5240	48	ax (SU) (20MHz)	SDM	270/286.8 (MCS11)	1.80	0.82	4.35	1.19	5.54	10.0	-4.46
5190	38	n (40MHz)	CDD	270/300 (MCS15)	-0.63	-1.73	1.86	3.96	5.83	10.0	-4.17
5230	46	n (40MHz)	SDM	270/300 (MCS15)	1.98	1.30	4.67	1.19	5.65	10.0	-4.15
5190	38	ax (SU) (40MHz)	CDD	540/573.5 (MCS11)	-2.10	-3.08	0.45	3.96	4.41	10.0	-5.59
5230	46	ax (SU) (40MHz)	SDM	540/573.5 (MCS11)	2.32	1.15	4.79	1.19	5.97	10.0	-4.03
5210	42	ac (80MHz)	CDD	780/866.7 (MCS9)	-3.19	-2.95	-0.06	3.96	3.90	10.0	-6.10
5210	42	ax (SU) (80MHz)	CDD	1134/1201 (MCS11)	-4.34	-5.43	-1.84	3.96	2.12	10.0	-7.88

**Table 7-202. ISED Band 1 e.i.r.p. Power Spectral Density Measurements CDD Diversity (High Data Rate)**


FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device	Page 249 of 534




FCC ID: BCGA2757 IC: 579C-A2757	 <b>element</b>	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device	Page 250 of 534




Plot 7-817. ISED PSD SDM Antenna 3c (40MHz BW 11ax(SU) – Ch.46, MCS0)




Plot 7-820. ISED PSD CDD Antenna 1b (80MHz BW 11ac – Ch.42, MCS0)




Plot 7-818. ISED SDM PSD Antenna 1b (40MHz BW 11ax(SU) – Ch.46, MCS0)



Plot 7-821. ISED PSD CDD Antenna 3c (80MHz BW 11ax (SU) – Ch.42, MCS0)



Plot 7-819. ISED PSD CDD Antenna 3c (80MHz BW 11ac – Ch.42, MCS0)



Plot 7-822. ISED PSD CDD Antenna 1b (80MHz BW 11ax (SU) – Ch.42, MCS0)

FCC ID: BCGA2757	 element
IC: 579C-A2757	
Test Report S/N: 1C2205090023-16.BCG	


**MEASUREMENT REPORT  
(CERTIFICATION)**

**Approved by:**  
Technical Manager


EUT Type:

Tablet Device


Page 251 of 534




Plot 7-823. ISED PSD SDM Antenna 3c (20MHz BW 11n – Ch.40, MCS12)




Plot 7-826. ISED PSD SDM Antenna 1b (20MHz BW 11ax(SU) – Ch.40, MCS4)




Plot 7-824. ISED PSD SDM Antenna 1b (20MHz BW 11n – Ch.40, MCS12)



Plot 7-827. ISED PSD SDM Antenna 3c (40MHz BW 11n – Ch.46, MCS12)




Plot 7-825. ISED PSD SDM Antenna 3c (20MHz BW 11ax(SU) – Ch.40, MCS4)




Plot 7-828. ISED PSD SDM Antenna 1b (40MHz BW 11n – Ch.46, MCS12)


FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device	Page 252 of 534




Plot 7-829. ISED PSD SDM Antenna 3c (40MHz BW 11ax(SU) – Ch.46, MCS4)




Plot 7-832. ISED PSD Antenna 1b (80MHz BW 11ac – Ch.42, MCS4)




Plot 7-830. ISED PSD SDM Antenna 1b (40MHz BW 11ax(SU) – Ch.46, MCS4)



Plot 7-833. ISED PSD CDD Antenna 3c (80MHz BW 11ax (SU) – Ch.42, MCS4)



Plot 7-831. ISED PSD CDD Antenna 3c (80MHz BW 11ac – Ch.42, MCS4)



Plot 7-834. ISED PSD CDD Antenna 1b (80MHz BW 11ax (SU) – Ch.42, MCS4)


FCC ID: BCGA2757	 element
IC: 579C-A2757	
Test Report S/N: 1C2205090023-16.BCG	

**MEASUREMENT REPORT  
(CERTIFICATION)**


**Approved by:**  
Technical Manager

Test Dates: 08/02/2022 – 09/14/2022      EUT Type: Tablet Device


Page 253 of 534




Plot 7-835. ISED PSD SDM Antenna 3c (20MHz BW 11n – Ch.40, MCS15)




Plot 7-838. ISED PSD SDM Antenna 1b (20MHz BW 11ax(SU) – Ch.40, MCS11)




Plot 7-836. ISED PSD SDM Antenna 1b (20MHz BW 11n – Ch.40, MCS15)



Plot 7-839. ISED PSD SDM Antenna 3c (40MHz BW 11n – Ch.46, MCS15)




Plot 7-837. ISED PSD SDM Antenna 3c (20MHz BW 11ax(SU) – Ch.40, MCS11)



Plot 7-840. ISED PSD SDM Antenna 1b (40MHz BW 11n – Ch.46, MCS15)


FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device	Page 254 of 534




Plot 7-841. ISED PSD SDM Antenna 3c (40MHz BW 11ax(SU) – Ch.46, MCS11)




Plot 7-844. ISED PSD CDD Antenna 1b (80MHz BW 11ac – Ch.42, MCS9)



Plot 7-842. ISED PSD SDM Antenna 1b (40MHz BW 11ax(SU) – Ch.46, MCS11)



Plot 7-845. ISED PSD CDD Antenna 3c (80MHz BW 11ax(SU) – Ch.42, MCS11)



Plot 7-843. ISED PSD CDD Antenna 3c (80MHz BW 11ac – Ch.42, MCS9)



Plot 7-846. ISED PSD CDD Antenna 1b (80MHz BW 11ax(SU) – Ch.42, MCS11)

FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device	Page 255 of 534

**Note:**

Per ANSI C63.10-2013 Section 14.3.2.2 and KDB 662911 v02r01 Section E2), the power spectral density at Antenna 3c and Antenna 3a were first measured separately as shown in the section above. The measured values were then summed in linear power units then converted back to dBm.

**Sample Directional Gain Calculation:**

For correlated signals, assuming the antenna gain is 2.8 dBi for Antenna 3c and 0.4 dBi for Antenna 3a.

$$\begin{aligned}\text{Directional gain} &= 10 \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / N_{\text{ANT}}] \text{ dBi} \\ &= 10 \log[(10^{2.8/20} + 10^{0.4/20} / 2] \text{ dBi} \\ &= 4.69 \text{ dBi}\end{aligned}$$

For uncorrelated signals, assuming the antenna gain is 2.8 dBi for Antenna 3c and 0.4 dBi for Antenna 3a.

$$\begin{aligned}\text{Directional gain} &= 10 \log[(10^{G_1/10} + 10^{G_2/10} + \dots + 10^{G_N/10}) / N_{\text{ANT}}] \text{ dBi} \\ &= 10 \log[(10^{2.8/10} + 10^{0.4/10} / 2] \text{ dBi} \\ &= 1.76 \text{ dBi}\end{aligned}$$

**Sample CDD/SDM Calculation:**

At 5180MHz in 802.11n (20MHz BW) mode, the average conducted power spectral density was measured to be 7.49 dBm for Antenna 3c and 7.47 dBm for Antenna 3a.

$$\text{Antenna 3c} + \text{Antenna 3a} = \text{CDD/SDM}$$

$$(7.49 \text{ dBm} + 7.47 \text{ dBm}) = (5.61 \text{ mW} + 5.59 \text{ mW}) = 11.20 \text{ mW} = 10.49 \text{ dBm}$$

**Sample e.i.r.p Power Spectral Density Calculation:**

At 5180MHz in 802.11n (20MHz BW) mode, the average CDD power density was calculated to be 10.49 dBm with directional gain of 4.69 dBi.

$$\text{e.i.r.p. Power Spectral Density(dBm)} = \text{Power Spectral Density (dBm)} + \text{Ant gain (dBi)}$$

$$10.49 \text{ dBm} + 4.69 \text{ dBi} = 15.18 \text{ dBm}$$

FCC ID: BCGA2757 IC: 579C-A2757		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device	Page 256 of 534

## 7.6 Radiated Spurious Emissions – Above 1GHz

§15.407(b) §15.205 §15.209; RSS-Gen [8.9]

### Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10-2013 and KDB 789033 D02 v02r01, and at the appropriate frequencies. All channels, modes (e.g. 802.11a, 802.11n, 802.11ax(SU) (20MHz BW), 802.11n, 802.11ax(SU) (40MHz BW), and 802.11ac, 802.11ax(SU) (80MHz), and modulations/data rates were investigated among all UNII bands. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

**For transmitters operating in the 5.15-5.25 GHz and 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz.**

**For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an EIRP of -27 dBm/MHz.**

**For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.**

**All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 7 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-203 per Section 15.209 and RSS-Gen (8.9).**

Frequency	Field Strength [ $\mu$ V/m]	Measured Distance [Meters]
Above 960.0 MHz	500	3

**Table 7-203. Radiated Limits**

### Test Procedures Used

ANSI C63.10-2013 – Sections 12.7.7.2, 12.7.6, 12.7.5  
KDB 789033 D02 v02r01 – Section G

### Test Settings

#### Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be  $\geq 2 \times$  span/RBW)
6. Averaging type = power (RMS)
7. Sweep time = auto couple
8. Trace was averaged over 100 sweeps


FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device	Page 257 of 534

### Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-5. Test Instrument & Measurement Setup**

FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device	Page 258 of 534

**Test Notes**

1. All emissions that lie in the restricted bands (denoted by a \* next to the frequency) specified in §15.205 and Section 8.10 of RSS-Gen are below the limit shown in Table 7-203.
2. All spurious emissions lying in restricted bands specified in §15.205 and Section 8.10 of RSS-Gen are below the limit shown in Table 7-203. All spurious emissions that do not lie in a restricted band are subject to a peak limit of -27dBm/MHz. At a distance of 3 meters, the field strength limit in dB $\mu$ V/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions of 68.2dB $\mu$ V/m.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas.
6. D is the measurement test distance and emissions 1-18GHz were measured at a 3 meters test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
7. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section.
8. All data rates were investigated and only the worse case is reported
9. The unit was tested with all possible modes and only the highest emission is reported.
10. The " - " shown in the following RSE tables are used to denote a noise floor measurement.
11. Per RSS-247 Section 6.2.3, transmission on channels which overlap the 5600-5650 MHz is prohibited. This device operates under these frequencies only under the control of a certified master device and does not support active scanning on these channels. This device does not transmit any beacons or initiate any transmissions in UNII Bands 2A or 2C.

FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device	Page 259 of 534

## Sample Calculations

### Determining Spurious Emissions Levels

- Field Strength Level [ $\text{dB}_{\mu\text{V/m}}$ ] = Analyzer Level [ $\text{dBm}$ ] + 107 + AFCL [ $\text{dB/m}$ ]
- AFCL [ $\text{dB/m}$ ] = Antenna Factor [ $\text{dB/m}$ ] + Cable Loss [ $\text{dB}$ ] – Preamplifier Gain [ $\text{dB}$ ]
- Margin [ $\text{dB}$ ] = Field Strength Level [ $\text{dB}_{\mu\text{V/m}}$ ] – Limit [ $\text{dB}_{\mu\text{V/m}}$ ]


### Radiated Band Edge Measurement Offset

- The amplitude offset shown in the radiated restricted band edge plots in Section 7.6 was calculated using the formula:

Offset (dB) = (Antenna Factor + Cable Loss + Attenuator) – Preamplifier Gain

FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device	Page 260 of 534

### 7.6.1 Antenna 3c Radiated Spurious Emission




**Plot 7-847. Radiated Spurious Emissions above 1GHz Antenna 3c (802.11n – Ch. 36)**

Mode: 802.11n  
 Data Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5180MHz  
 Channel: 36

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10360.00	Peak	H	-	-	-72.31	15.48	50.17	68.20	-18.03
* 15540.00	Average	H	-	-	-84.19	19.97	42.78	53.98	-11.20
* 15540.00	Peak	H	-	-	-72.81	19.97	54.16	73.98	-19.82

**Table 7-204. Radiated Spurious Emission Measurements Antenna 3c**

FCC ID: BCGA2757 IC: 579C-A2757	 <b>MEASUREMENT REPORT (CERTIFICATION)</b>			Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device	Page 261 of 534	




Plot 7-848. Radiated Spurious Emissions above 1GHz Antenna 3c (802.11n – Ch. 40)

Mode: 802.11n  
 Data Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5200MHz  
 Channel: 40

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]
10400.00	Peak	H	-	-	-72.42	15.45	50.03	68.20	-18.17
* 15600.00	Average	H	-	-	-84.34	20.22	42.88	53.98	-11.10
* 15600.00	Peak	H	-	-	-72.54	20.22	54.68	73.98	-19.30

Table 7-205. Radiated Spurious Emission Measurements Antenna 3c

FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device	Page 262 of 534




**Plot 7-849. Radiated Spurious Emissions above 1GHz Antenna 3c (802.11n – Ch. 48)**

Mode: 802.11n  
 Data Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5240MHz  
 Channel: 48

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]
10480.00	Peak	H	-	-	-71.97	15.09	50.12	68.20	-18.08
* 15720.00	Average	H	-	-	-84.72	21.50	43.78	53.98	-10.20
* 15720.00	Peak	H	-	-	-73.29	21.50	55.21	73.98	-18.77

**Table 7-206. Radiated Spurious Emission Measurements Antenna 3c**

FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device	Page 263 of 534




**Plot 7-850. Radiated Spurious Emissions above 1GHz Antenna 3c (802.11n – Ch. 52)**

Mode: 802.11n  
 Data Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5260MHz  
 Channel: 52

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]
10520.00	Peak	H	-	-	-72.48	14.85	49.37	68.20	-18.83
* 15780.00	Average	H	-	-	-84.60	20.56	42.96	53.98	-11.02
* 15780.00	Peak	H	-	-	-73.49	20.56	54.07	73.98	-19.91

**Table 7-207. Radiated Spurious Emission Measurements Antenna 3c**

FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device	Page 264 of 534




**Plot 7-851. Radiated Spurious Emissions above 1GHz Antenna 3c (802.11n – Ch. 56)**

Mode: 802.11n  
 Data Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5280MHz  
 Channel: 56

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]
10560.00	Peak	H	-	-	-72.33	15.23	49.90	68.20	-18.30
* 15840.00	Average	H	-	-	-84.58	20.87	43.29	53.98	-10.69
* 15840.00	Peak	H	-	-	-72.66	20.87	55.21	73.98	-18.77

**Table 7-208. Radiated Spurious Emission Measurements Antenna 3c**

FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device	Page 265 of 534




**Plot 7-852. Radiated Spurious Emissions above 1GHz Antenna 3c (802.11n – Ch. 64)**

Mode: 802.11n  
 Data Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5320MHz  
 Channel: 64

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]
* 10640.00	Average	H	-	-	-83.56	15.77	39.21	53.98	-14.77
* 10640.00	Peak	H	-	-	-72.53	15.77	50.24	73.98	-23.74
* 15960.00	Average	H	-	-	-84.75	21.66	43.91	53.98	-10.07
* 15960.00	Peak	H	-	-	-73.61	21.66	55.05	73.98	-18.93

**Table 7-209. Radiated Spurious Emission Measurements Antenna 3c**

FCC ID: BCGA2757 IC: 579C-A2757	 <b>element</b>	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device			




**Plot 7-853. Radiated Spurious Emissions above 1GHz Antenna 3c (802.11n – Ch. 100)**

Mode: 802.11n  
 Data Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5500MHz  
 Channel: 100

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]
* 11000.00	Average	H	-	-	-84.34	15.99	38.65	53.98	-15.33
* 11000.00	Peak	H	-	-	-72.79	15.99	50.20	73.98	-23.78
16500.00	Peak	H	-	-	-72.95	21.14	55.19	68.20	-13.01

**Table 7-210. Radiated Spurious Emission Measurements Antenna 3c**

FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device	Page 267 of 534




**Plot 7-854. Radiated Spurious Emissions above 1GHz Antenna 3c (802.11n – Ch. 116)**

Mode: 802.11n  
 Data Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5580Hz  
 Channel: 116

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]
* 11160.00	Average	H	-	-	-83.16	15.72	39.56	53.98	-14.42
* 11160.00	Peak	H	-	-	-72.23	15.72	50.49	73.98	-23.49
16740.00	Peak	H	-	-	-72.91	21.49	55.58	68.20	-12.62

**Table 7-211. Radiated Spurious Emission Measurements Antenna 3c**

FCC ID: BCGA2757 IC: 579C-A2757	 <b>MEASUREMENT REPORT (CERTIFICATION)</b>			Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device	Page 268 of 534	




**Plot 7-855. Radiated Spurious Emissions above 1GHz Antenna 3c (802.11n – Ch. 144)**

Mode: 802.11n  
 Data Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5720  
 Channel: 144

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]
* 11440.00	Average	H	-	-	-83.69	16.52	39.83	53.98	-14.15
* 11440.00	Peak	H	-	-	-72.67	16.52	50.85	73.98	-23.13
17160.00	Peak	H	-	-	-73.78	21.74	54.96	68.20	-13.24

**Table 7-212. Radiated Spurious Emission Measurements Antenna 3c**

FCC ID: BCGA2757 IC: 579C-A2757	 <b>element</b>	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device	Page 269 of 534




Plot 7-856. Radiated Spurious Emissions above 1GHz Antenna 3c (802.11n – Ch. 149)

Mode: 802.11n  
 Data Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5745MHz  
 Channel: 149

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]
* 11490.00	Average	H	-	-	-83.08	16.20	40.12	53.98	-13.86
* 11490.00	Peak	H	-	-	-72.37	16.20	50.83	73.98	-23.15
17235.00	Peak	H	-	-	-73.48	21.28	54.80	68.20	-13.40

Table 7-213. Radiated Spurious Emission Measurements Antenna 3c

FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device	Page 270 of 534




Plot 7-857. Radiated Spurious Emissions above 1GHz Antenna 3c (802.11n – Ch. 157)

Mode: 802.11n  
 Data Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5785MHz  
 Channel: 157

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]
* 11570.00	Average	H	-	-	-83.09	16.28	40.19	53.98	-13.79
* 11570.00	Peak	H	-	-	-72.31	16.28	50.97	73.98	-23.01
17355.00	Peak	H	-	-	-72.87	21.33	55.46	68.20	-12.74

Table 7-214. Radiated Spurious Emission Measurements Antenna 3c

FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device	Page 271 of 534




Plot 7-858. Radiated Spurious Emissions above 1GHz Antenna 3c (802.11n – Ch. 165)

Mode: 802.11n  
 Data Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5825MHz  
 Channel: 165

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]
* 11650.00	Average	H	-	-	-83.14	16.90	40.76	53.98	-13.22
* 11650.00	Peak	H	-	-	-72.06	16.90	51.84	73.98	-22.14
17475.00	Peak	H	-	-	-73.10	20.80	54.70	68.20	-13.50

Table 7-215. Radiated Spurious Emission Measurements Antenna 3c

FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device	Page 272 of 534




**Plot 7-859. Radiated Spurious Emissions above 1GHz Antenna 3c (802.11ax(SU) – Ch. 36)**

Mode: 802.11ax(SU)  
 Data Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5180MHz  
 Channel: 36

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]
10360.00	Peak	H	-	-	-71.99	15.48	50.49	68.20	-17.71
* 15540.00	Average	H	-	-	-84.17	19.97	42.80	53.98	-11.18
* 15540.00	Peak	H	-	-	-72.76	19.97	54.21	73.98	-19.77

**Table 7-216. Radiated Spurious Emission Measurements Antenna 3c**

FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device	Page 273 of 534




**Plot 7-860. Radiated Spurious Emissions above 1GHz Antenna 3c (802.11ax(SU) – Ch. 40)**

Mode: 802.11ax(SU)  
 Data Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5200MHz  
 Channel: 40

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]
10400.00	Peak	H	-	-	-72.55	15.45	49.90	68.20	-18.30
* 15600.00	Average	H	-	-	-84.21	20.22	43.01	53.98	-10.97
* 15600.00	Peak	H	-	-	-73.06	20.22	54.16	73.98	-19.82

**Table 7-217. Radiated Spurious Emission Measurements Antenna 3c**

FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device			




**Plot 7-861. Radiated Spurious Emissions above 1GHz Antenna 3c (802.11ax(SU) – Ch. 48)**

Mode: 802.11ax(SU)  
 Data Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5240MHz  
 Channel: 48

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]
10480.00	Peak	H	-	-	-72.12	15.09	49.97	68.20	-18.23
* 15720.00	Average	H	-	-	-84.49	21.50	44.01	53.98	-9.97
* 15720.00	Peak	H	-	-	-73.73	21.50	54.77	73.98	-19.21

**Table 7-218. Radiated Spurious Emission Measurements Antenna 3c**

FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device	Page 275 of 534




**Plot 7-862. Radiated Spurious Emissions above 1GHz Antenna 3c (802.11ax(SU) – Ch. 52)**

Mode: 802.11ax(SU)  
 Data Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5260MHz  
 Channel: 52

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]
10520.00	Peak	H	-	-	-72.00	14.85	49.85	68.20	-18.35
* 15780.00	Average	H	-	-	-84.65	20.56	42.91	53.98	-11.07
* 15780.00	Peak	H	-	-	-73.04	20.56	54.52	73.98	-19.46

**Table 7-219. Radiated Spurious Emission Measurements Antenna 3c**

FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device			




**Plot 7-863. Radiated Spurious Emissions above 1GHz Antenna 3c (802.11ax(SU) – Ch. 56)**

Mode: 802.11ax(SU)  
 Data Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5280MHz  
 Channel: 56

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]
10560.00	Peak	H	-	-	-71.64	15.23	50.59	68.20	-17.61
* 15840.00	Average	H	-	-	-84.20	20.87	43.67	53.98	-10.31
* 15840.00	Peak	H	-	-	-72.97	20.87	54.90	73.98	-19.08

**Table 7-220. Radiated Spurious Emission Measurements Antenna 3c**

FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device			




Plot 7-864. Radiated Spurious Emissions above 1GHz Antenna 3c (802.11ax(SU) – Ch. 64)

Mode: 802.11ax(SU)  
 Data Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5320MHz  
 Channel: 64

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]
* 10640.00	Average	H	-	-	-83.42	15.77	39.35	53.98	-14.63
* 10640.00	Peak	H	-	-	-72.60	15.77	50.17	73.98	-23.81
* 15960.00	Average	H	-	-	-84.82	21.66	43.84	53.98	-10.14
* 15960.00	Peak	H	-	-	-72.98	21.66	55.68	73.98	-18.30

Table 7-221. Radiated Spurious Emission Measurements Antenna 3c

FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device	Page 278 of 534




**Plot 7-865. Radiated Spurious Emissions above 1GHz Antenna 3c (802.11ax(SU) – Ch. 100)**

Mode: 802.11ax(SU)  
 Data Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5500MHz  
 Channel: 100

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]
* 11000.00	Average	H	-	-	-84.53	15.99	38.46	53.98	-15.52
* 11000.00	Peak	H	-	-	-72.98	15.99	50.01	73.98	-23.97
16500.00	Peak	H	-	-	-72.71	21.14	55.43	68.20	-12.77

**Table 7-222. Radiated Spurious Emission Measurements Antenna 3c**

FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device	Page 279 of 534




**Plot 7-866. Radiated Spurious Emissions above 1GHz Antenna 3c (802.11ax(SU) – Ch. 116)**

Mode: 802.11ax(SU)  
 Data Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5580MHz  
 Channel: 116

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]
* 11160.00	Average	H	-	-	-83.27	15.72	39.45	53.98	-14.53
* 11160.00	Peak	H	-	-	-72.24	15.72	50.48	73.98	-23.50
16740.00	Peak	H	-	-	-73.26	21.49	55.23	68.20	-12.97

**Table 7-223. Radiated Spurious Emission Measurements Antenna 3c**

FCC ID: BCGA2757 IC: 579C-A2757	element			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device			




**Plot 7-867. Radiated Spurious Emissions above 1GHz Antenna 3c (802.11ax(SU) – Ch. 144)**

Mode: 802.11ax(SU)  
 Data Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5720MHz  
 Channel: 144

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]
* 11440.00	Average	H	-	-	-83.55	16.52	39.97	53.98	-14.01
* 11440.00	Peak	H	-	-	-72.50	16.52	51.02	73.98	-22.96
17160.00	Peak	H	-	-	-72.91	21.74	55.83	68.20	-12.37

**Table 7-224. Radiated Spurious Emission Measurements Antenna 3c**

FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device	Page 281 of 534




**Plot 7-868. Radiated Spurious Emissions above 1GHz Antenna 3c (802.11ax(SU) – Ch. 149)**

Mode: 802.11ax(SU)  
 Data Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5745MHz  
 Channel: 149

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]
* 11490.00	Average	H	-	-	-83.11	16.20	40.09	53.98	-13.89
* 11490.00	Peak	H	-	-	-71.41	16.20	51.79	73.98	-22.19
17235.00	Peak	H	-	-	-73.25	21.28	55.03	68.20	-13.17

**Table 7-225. Radiated Spurious Emission Measurements Antenna 3c**

FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device	Page 282 of 534




Plot 7-869. Radiated Spurious Emissions above 1GHz Antenna 3c (802.11ax(SU) – Ch. 157)

Mode: 802.11ax(SU)  
 Data Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5785MHz  
 Channel: 157

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]
* 11570.00	Average	H	-	-	-83.12	16.28	40.16	53.98	-13.82
* 11570.00	Peak	H	-	-	-71.89	16.28	51.39	73.98	-22.59
17355.00	Peak	H	-	-	-72.61	21.33	55.72	68.20	-12.48

Table 7-226. Radiated Spurious Emission Measurements Antenna 3c

FCC ID: BCGA2757 IC: 579C-A2757	 <b>MEASUREMENT REPORT (CERTIFICATION)</b>			Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device	Page 283 of 534	



**Plot 7-870. Radiated Spurious Emissions above 1GHz Antenna 3c (802.11ax(SU) – Ch. 165)**


Mode: 802.11ax(SU)  
 Data Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5825MHz  
 Channel: 165

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]
* 11650.00	Average	H	-	-	-83.17	16.90	40.73	53.98	-13.25
* 11650.00	Peak	H	-	-	-72.34	16.90	51.56	73.98	-22.42
17475.00	Peak	H	-	-	-73.03	20.80	54.77	68.20	-13.43

**Table 7-227. Radiated Spurious Emission Measurements Antenna 3c**

FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device			

## 7.6.2 Antenna 3a Radiated Spurious Emission




Plot 7-871. Radiated Spurious Emissions above 1GHz Antenna 3a (802.11n – Ch. 36)

Mode: 802.11n  
 Data Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5180MHz  
 Channel: 36

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10360.00	Peak	H	-	-	-72.90	15.48	49.58	68.20	-18.62
* 15540.00	Average	H	-	-	-84.01	19.97	42.96	53.98	-11.02
* 15540.00	Peak	H	-	-	-73.34	19.97	53.63	73.98	-20.35

Table 7-228. Radiated Spurious Emission Measurements Antenna 3a

FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device	Page 285 of 534



**Plot 7-872. Radiated Spurious Emissions above 1GHz Antenna 3a (802.11n – Ch. 40)**

Mode: 802.11n  
 Data Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5200MHz  
 Channel: 40

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]
10400.00	Peak	H	-	-	-72.85	15.45	49.60	68.20	-18.60
* 15600.00	Average	H	-	-	-83.91	20.22	43.31	53.98	-10.67
* 15600.00	Peak	H	-	-	-73.13	20.22	54.09	73.98	-19.89

**Table 7-229. Radiated Spurious Emission Measurements Antenna 3a**

FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-16.BCG	Test Dates: 08/02/2022 – 09/14/2022	EUT Type: Tablet Device	Page 286 of 534