



Element Washington DC LLC

18855 Adams Court, Morgan Hill, CA 95037 USA

Tel. 410.290.6652 / Fax 410.290.6654

<http://www.element.com>



MEASUREMENT REPORT

FCC PART 15.407 / ISED RSS-247 UNII 802.11ax OFDMA

Applicant Name:

Apple Inc.
One Apple Park Way
Cupertino, CA 95014
United States

Date of Testing:

6/7/2022 - 9/18/2022

Test Site/Location:

Element Washington DC LLC, Morgan Hill, CA, USA

Test Report Serial No.:

1C2205090023-17.BCG

FCC ID:	BCGA2757
IC:	579C-A2757
APPLICANT:	Apple Inc.

Application Type:

Certification

Model/HVIN:

A2757(A2777)

EUT Type:

Tablet Device

Frequency Range:

5180 – 5825MHz

Modulation Type:

OFDMA

FCC Classification:

Unlicensed National Information Infrastructure (UNII)

FCC Rule Part(s):

Part 15 Subpart E (15.407)

ISED Specification:

RSS-247 Issue 2

Test Procedure(s):

ANSI C63.10-2013, KDB 789033 D02 v02r01,
KDB 662911 D01 v02r01

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013 and KDB 789033 D02 v02r01. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

RJ Ortanez

Executive Vice President



FCC ID: BCGA2757		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-17.BCG	Test Dates: 6/7/2022 - 9/18/2022	EUT Type: Tablet Device	Page 1 of 405


V 10.5 12/15/2021

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Washington DC LLC. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

T A B L E O F C O N T E N T S

1.0	INTRODUCTION	4
1.1	Scope	4
1.2	Element Washington DC LLC Test Location	4
1.3	Test Facility / Accreditations	4
2.0	PRODUCT INFORMATION.....	5
2.1	Equipment Description.....	5
2.2	Device Capabilities	5
2.3	Antenna Description.....	8
2.4	Test Support Equipment	8
2.5	Test Configuration	9
2.6	Software and Firmware.....	9
2.7	EMI Suppression Device(s)/Modifications.....	9
3.0	DESCRIPTION OF TESTS	10
3.1	Evaluation Procedure.....	10
3.2	AC Line Conducted Emissions	10
3.3	Radiated Emissions	11
3.4	Environmental Conditions	11
4.0	ANTENNA REQUIREMENTS	12
5.0	MEASUREMENT UNCERTAINTY	13
6.0	TEST EQUIPMENT CALIBRATION DATA.....	14
7.0	TEST RESULTS.....	15
7.1	Summary	15
7.2	26dB & 99% Bandwidth Measurement – 802.11ax OFDMA.....	16
7.3	6dB & 99% Bandwidth Measurement – 802.11ax OFDMA.....	41
7.4	Conducted Output Power and Max EIRP Measurement – 802.11ax OFDMA	51
7.5	Maximum Power Spectral Density – 802.11ax OFDMA.....	104
7.6	Radiated Spurious Emission – Above 1GHz.....	196
7.6.1	Antenna 3c Radiated Spurious Emission	200
7.6.2	Antenna 3a Radiated Spurious Emission.....	224
7.6.3	Antenna 1b Radiated Spurious Emission	248
7.6.4	CDD Primary Radiated Spurious Emissions	272
7.6.5	CDD Diversity Radiated Spurious Emissions	304
7.6.6	Antenna 3c Radiated Band Edge Measurements (20MHz BW)	336
7.6.7	Antenna 3c Radiated Band Edge Measurements (40MHz BW)	339
7.6.8	Antenna 3c Radiated Band Edge Measurements (80MHz BW)	343
7.6.9	Antenna 3a Radiated Band Edge Measurements (20MHz BW)	346
7.6.10	Antenna 3a Radiated Band Edge Measurements (40MHz BW)	350
7.6.11	Antenna 3a Radiated Band Edge Measurements (80MHz BW)	354
7.6.12	Antenna 1b Radiated Band Edge Measurements (20MHz BW)	358
7.6.13	Antenna 1b Radiated Band Edge Measurements (40MHz BW)	362
7.6.14	Antenna 1b Radiated Band Edge Measurements (80MHz BW)	366
7.6.15	CDD Primary Radiated Band Edge Measurements (20MHz BW)	370
7.6.16	CDD Primary Radiated Band Edge Measurements (40MHz BW)	373
7.6.17	CDD Primary Radiated Band Edge Measurements (80MHz BW)	377
7.6.18	CDD Diversity Radiated Band Edge Measurements (20MHz BW)	381
7.6.19	CDD Diversity Radiated Band Edge Measurements (40MHz BW)	384
7.6.20	CDD Diversity Radiated Band Edge Measurements (80MHz BW)	388
7.7	Radiated Spurious Emissions – Below 1GHz	392
7.8	AC Line Conducted Emissions Measurement.....	399
8.0	CONCLUSION	405

FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-17.BCG	Test Dates: 6/7/2022 - 9/18/2022	EUT Type: Tablet Device	Page 2 of 405 V 10.5 12/15/2021



MEASUREMENT REPORT



UNII Band	Channel Bandwidth (MHz)	Tx Frequency (MHz)	SISO						CDD/SDM Primary						CDD/SDM Diversity						CDD/SDM Diversity								
			Antenna 3c			Antenna 3a			Antenna 1b			Antenna 3c			Antenna 3a			Summed			Antenna 3c			Antenna 1b			Summed		
			Max. Power (mW)	Max. Power (dBm)	Max. Power (mW)	Max. Power (dBm)	Max. Power (mW)	Max. Power (dBm)	Max. Power (mW)	Max. Power (dBm)	Max. Power (mW)	Max. Power (dBm)	Max. Power (mW)	Max. Power (dBm)	Max. Power (mW)	Max. Power (dBm)													
1	20	5180 - 5240	96.383	19.84	99.083	19.96	97.724	19.90	49.204	16.92	50.003	16.99	99.312	19.97	50.003	16.99	49.659	16.96	99.663	19.99	5180 - 5240	96.383	19.84	99.083	19.96	97.724	19.90	49.204	16.92
2A		5260 - 5320	99.770	19.99	98.855	19.95	96.605	19.85	48.865	16.89	49.317	16.93	97.949	19.91	47.973	16.81	49.888	16.98	97.313	19.88	5260 - 5320	99.770	19.99	98.855	19.95	96.605	19.85	48.865	16.89
2C		5500 - 5720	99.312	19.97	98.175	19.92	99.083	19.96	48.865	16.89	49.431	16.94	98.175	19.92	49.431	16.94	49.659	16.96	98.636	19.94	5500 - 5720	99.312	19.97	98.175	19.92	99.083	19.96	48.865	16.89
3		5745 - 5825	111.944	20.49	108.143	20.34	111.944	20.49	111.944	20.49	223.872	23.50	109.901	20.41	111.173	20.46	219.548	23.42	5745 - 5825	111.944	20.49	108.143	20.34	111.944	20.49	223.872	23.50		
1	40	5190 - 5230	78.886	18.97	79.058	18.98	79.250	18.99	79.068	18.98	78.896	18.97	158.125	21.99	75.162	18.76	76.913	18.86	152.075	21.82	5190 - 5230	78.886	18.97	79.058	18.98	79.250	18.99	79.068	18.97
2A		5270 - 5310	78.524	18.95	78.343	18.94	79.250	18.99	75.509	18.78	76.736	18.85	152.405	21.83	78.705	18.96	74.389	18.75	153.694	21.87	5270 - 5310	78.524	18.95	78.343	18.94	79.250	18.99	75.509	18.78
2C		5510 - 5710	99.770	19.99	99.541	19.98	95.060	19.78	88.920	19.49	88.920	19.49	176.604	22.47	88.920	19.49	88.512	19.47	175.608	22.45	5510 - 5710	99.770	19.99	99.541	19.98	95.060	19.78	88.920	19.49
3		5755 - 5795	111.173	20.46	110.662	20.44	109.144	20.38	106.905	20.29	107.895	20.33	214.783	23.32	107.152	20.30	106.660	20.28	213.812	23.30	5755 - 5795	111.173	20.46	110.662	20.44	109.144	20.38	106.905	20.29
1	80	5210	25.119	14.00	25.119	14.00	25.119	14.00	15.812	11.99	15.560	11.92	31.189	14.94	21.627	13.35	22.182	13.46	43.809	16.42	5210	25.119	14.00	25.119	14.00	25.119	14.00	15.812	11.99
2A		5290	15.849	12.00	15.849	12.00	15.849	12.00	10.375	10.16	10.304	10.13	20.606	13.14	13.646	11.35	13.428	11.28	27.073	14.33	5290	15.849	12.00	15.849	12.00	15.849	12.00	10.375	10.16
2C		5530 - 5690	98.855	19.95	99.312	19.97	98.855	19.95	98.855	19.95	95.719	19.81	194.536	22.89	95.940	19.82	97.724	19.90	193.664	22.87	5530 - 5690	98.855	19.95	99.312	19.97	98.855	19.95	95.719	19.81
3		5775	50.003	16.99	49.091	16.91	49.659	16.96	33.189	15.21	33.266	15.22	66.222	18.21	54.075	17.33	53.333	17.27	107.409	20.31	5775	50.003	16.99	49.091	16.91	49.659	16.96	33.189	15.21

FCC EUT Overview

UNII Band	Channel Bandwidth (MHz)	Tx Frequency (MHz)	SISO						CDD/SDM Primary						CDD/SDM Diversity						CDD/SDM Diversity								
			Antenna 3c			Antenna 3a			Antenna 1b			Antenna 3c			Antenna 3a			Summed			Antenna 3c			Antenna 1b			Summed		
			Max. Power (mW)	Max. Power (dBm)	Max. Power (mW)	Max. Power (dBm)	Max. Power (mW)	Max. Power (dBm)	Max. Power (mW)	Max. Power (dBm)	Max. Power (mW)	Max. Power (dBm)	Max. Power (mW)	Max. Power (dBm)	Max. Power (mW)	Max. Power (dBm)													
1	20	5180 - 5240	39.446	15.96	38.637	15.87	38.637	15.87	24.491	13.89	24.604	13.91	49.091	16.91	24.491	13.89	24.660	13.92	49.204	16.92	5180 - 5240	39.446	15.96	38.637	15.87	38.637	15.87	24.491	13.89
2A		5260 - 5320	99.770	19.99	98.855	19.95	96.605	19.85	48.865	16.89	49.317	16.93	97.949	19.91	47.973	16.81	49.888	16.98	97.313	19.88	5260 - 5320	99.770	19.99	98.855	19.95	96.605	19.85	48.865	16.89
2C		5500 - 5720	99.312	19.97	98.175	19.92	99.083	19.96	48.865	16.89	49.431	16.94	98.175	19.92	49.431	16.94	49.659	16.96	98.636	19.94	5500 - 5720	99.312	19.97	98.175	19.92	99.083	19.96	48.865	16.89
3		5745 - 5825	111.944	20.46	108.143	20.34	111.944	20.46	111.944	20.46	223.872	23.50	109.901	20.41	111.173	20.46	219.548	23.42	5745 - 5825	111.944	20.46	108.143	20.34	111.944	20.46	223.872	23.50		
1	40	5190 - 5230	38.725	15.88	69.024	18.39	69.707	18.37	43.053	16.34	43.551	16.39	46.336	18.36	46.336	18.36	43.152	16.35	46.299	18.35	5190 - 5230	38.725	15.88	69.024	18.39	69.707	18.37	43.053	16.34
2A		5270 - 5310	78.524	18.95	78.343	18.94	79.250	18.99	75.509	18.78	76.736	18.85	152.405	21.83	78.705	18.96	74.389	18.75	153.694	21.87	5270 - 5310	78.524	18.95	78.343	18.94	79.250	18.99	75.509	18.78
2C		5510 - 5710	88.106	19.45	87.096	19.40	87.902	19.44	87.700	19.43	88.920	19.49	176.604	22.47	87.096	19.40	88.512	19.47	175.608	22.45	5510 - 5710	88.106	19.45	87.096	19.40	87.902	19.44	88.920	19.49
3		5755 - 5795	111.173	20.46	110.662	20.44	109.144	20.38	106.905	20.29	107.895	20.33	214.783	23.32	107.152	20.30	106.660	20.28	213.812	23.30	5755 - 5795	111.173	20.46	110.662	20.44	109.144	20.38	106.905	20.29
1	80	5210	25.119	14.00	25.119	14.00	25.119	14.00	15.812	11.99	15.560	11.92	31.189	14.94	15.849	12.00	15.812	11.99	31.589	15.00	5210	25.119	14.00	25.119	14.00	25.119	14.00	15.812	11.99
2A		5290	15.849	12.00	15.849	12.00	15.849	12.00	10.375	10.16	10.304	10.13	20.606	13.14	13.646	11.35	13.428	11.28	27.073	14.33	5290	15.849	12.00	15.849	12.00	15.849	12.00	10.375	10.16
2C		5530 - 5690	98.855	19.95	99.312	19.97	98.855	19.95	98.855	19.95	95.719	19.81	194.536	22.89	95.940	19.82	97.724	19.90	193.664	22.87	5530 - 5690	98.855	19.95	99.312	19.97	98.855	19.95	95.719	19.81
3		5775	50.003	16.99	49.091	16.91	49.659	16.96	33.189	15.21	33.266	15.22	66.222	18.21	54.075	17.33	53.333	17.27	107.409	20.31	5775	50.003	16.99	49.091	16.91	49.659	16.96	33.189	15.21

ISED EUT Overview

FCC ID: BCGA2757	IC: 579C-A2757	Test Report S/N: 1C2205090023-17.BCG	Test Dates:

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 Element Washington DC LLC Test Location

These measurement tests were conducted at the Element Washington DC LLC facility located at 18855 Adams Court, Morgan Hill, CA 95037. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014 and KDB 414788 D01 v01r01.

1.3 Test Facility / Accreditations

Measurements were performed at Element Washington DC LLC located in Morgan Hill, CA 95037, U.S.A.

- Element Washington DC LLC is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.02 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Washington DC LLC TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- Element Washington DC LLC facility is a registered (22831) test laboratory with the site description on file with ISED.

FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-17.BCG	Test Dates: 6/7/2022 - 9/18/2022	EUT Type: Tablet Device	Page 4 of 405 V 10.5 12/15/2021

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Apple Tablet Device FCC ID: BCGA2757 and IC: 579C-A2757**. The test data contained in this report pertains only to the emissions due to the EUT's UNII 802.11ax - RU transmitter.

Test Device Serial No.: W07L2L17MW, M419GH393R, C590R6TR4P, TPF4T67Q9F C47217501601K7N4A

2.2 Device Capabilities

This device contains the following capabilities:

850/1700/1900 WCDMA/HSPA, Multi-band LTE, 5G NR (FR1), 802.11b/g/n/ax WLAN, 802.11a/n/ac/ax UNII, Bluetooth (1x, EDR, LE1M, LE2M, HDR4, HDR8).

This device supports BT Beamforming.

Band 1		Band 2A		Band 2C		Band 3	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
36	5180	52	5260	100	5500	149	5745
:	:	:	:	:	:	:	:
42	5210	56	5280	116	5580	157	5785
:	:	:	:	:	:	:	:
48	5240	64	5320	144	5720	165	5825

Table 2-1. 802.11a / 802.11n / 802.11ac / 802.11ax (20MHz) Frequency / Channel Operations

Band 1		Band 2A		Band 2C		Band 3	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
38	5190	54	5270	102	5510	151	5755
:	:	:	:	:	:	:	:
46	5230	62	5310	110	5550	159	5795
				142	5710		

Table 2-2. 802.11n / 802.11ac / 802.11ax (40MHz BW) Frequency / Channel Operations

Band 1		Band 2A		Band 2C		Band 3	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
42	5210	58	5290	106	5530	155	5775
				138	5690		

Table 2-3. 802.11ac / 802.11ax (80MHz BW) Frequency / Channel Operations

FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-17.BCG	Test Dates: 6/7/2022 - 9/18/2022	EUT Type: Tablet Device	Page 5 of 405 V 10.5 12/15/2021



Notes:

- TDWR channels are not supported for ISED.
- 5GHz NII operation is possible in 20MHz, and 40MHz, and 80MHz channel bandwidths. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = peak per the guidance of Section B(2)b) of KDB 789033 D02 v02r01 and ANSI C63.10-2013. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Measure Duty Cycles						
802.11 Mode/Band			Duty Cycles [%]			
			Antenna 3c	Antenna 3a	Antenna 1b	CDD/SDM (Primary)
5GHz	11ax(RU) 26T HE20	89.4	90.0	89.8	89.7	89.3
	11ax(RU) 52T HE20	89.1	89.9	89.1	89.6	89.2
	11ax(RU) 242T HE20	85.8	87.1	86.1	85.9	87.3
	11ax(RU) 26T HE40	90.1	89.9	89.7	90.1	89.6
	11ax(RU) 52T HE40	89.5	89.4	89.2	89.5	89.1
	11ax(RU) 484T HE40	86.5	87.2	86.1	87.6	87.3
	11ax(RU) 26T HE80	89.6	89.9	90.1	89.7	90.0
	11ax(RU) 52T HE80	88.5	89.2	88.8	88.8	88.8
	11ax(RU) 996T HE80	89.6	89.8	89.2	87.9	88.4

Table 2-4. Measured Duty Cycles

CDD/SDM Primary = Antenna 3c + Antenna 3a

CDD/SDM Diversity = Antenna 3c + Antenna 1b

- The device employs CDD/SDM technology. Below are the possible configurations.

WiFi Configurations	SISO			Primary				Diversity							
				CDD		SDM		STBC		CDD		SDM		STBC	
	Antenna 3c	Antenna 3a	Antenna 1b	Antenna 3c	Antenna 3a	Antenna 3c	Antenna 3a	Antenna 3c	Antenna 3a	Antenna 3c	Antenna 1b	Antenna 3c	Antenna 1b	Antenna 3c	Antenna 1b
5GHz	11ax (20MHz)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	11ax (40MHz)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	11ax (80MHz)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

Table 2-5. WIFI Configurations

✓ = Support ; ✗ = NOT Support

SISO = Single Input Single Output

CDD = Cyclic Delay Diversity – 2Tx Function

SDM = Spatial Diversity Multiplexing – CDD/SDM function

STBC = Space-Time Block Coding – 2Tx Function

FCC ID: BCGA2757		MEASUREMENT REPORT (CERTIFICATION)					Approved by: Technical Manager
Test Report S/N: 1C2205090023-17.BCG	Test Dates: 6/7/2022 - 9/18/2022	EUT Type: Tablet Device					

V 10.5 12/15/2021

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Washington DC LLC. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Page 6 of 405



Data Rate(s) Support: 8/8.6, 16/17.2, 24/25.8, 33/34.4, 49/51.6, 65/68.8, 73/77.4, 81/86.0, 98/103.2, 108/114.7, 122/129.0, 135/143.4Mbps (ax – 20MHz)
16/17.2, 33/34.4, 49/51.6, 65/68.8, 98/103.2, 130/137.6, 146/154.9, 163/172.1, 195/206.5, 217/229.4, 244/258.1, 271/286.8Mbps (ax – 40MHz BW)
34/36.0, 68/72.1, 102/108.1, 136/144.1, 204/216.2, 272/288.2, 306/324.4, 340/360.3, 408/432.4, 453/480.4, 510/540.4, 567/600.5Mbps (ax – 80MHz BW)
16/17.2, 33/34.4, 49/51.6, 65/68.8, 98/103.2, 130/137.6, 146/154.9, 163/172.1, 195/206.5, 217/229.4, 244/258.1, 271/286.8Mbps (MIMO ax – 20MHz BW)
34/36.0, 68/72.1, 102/108.1, 136/144.1, 204/216.2, 272/288.2, 306/324.4, 340/360.3, 408/432.4, 453/480.4, 510/540.4, 567/600.5Mbps (MIMO ax – 40MHz BW)
68/72, 136/144.1, 204/216.2, 272/288.2, 408/432.4, 544/576.4, 612/648.8, 680/720.6, 816/864.8, 906/960.8, 1020/1080.8, 1134/1201Mbps (MIMO ax – 80MHz BW)

This device supports simultaneous transmission operations, which allows for multiple transmitters to transmit simultaneously on the same antenna. The table below shows all configurations possible.

Antenna	Simultaneous Tx Config	WiFi 2.4GHz	Bluetooth	WiFi 5GHz	WCDMA / LTE / FR1 NR		
		802.11 b/g/n/ax	BDR, EDR, HDR4/8, LE1/2M	802.11 a/n/ac/ax	Mid Band	High Band	Ultra High Band
3a	Config 1	✗	✓	✓	✗	✗	✗
3a	Config 2	✓	✗	✗	✓	✗	✗
3a	Config 3	✓	✗	✗	✗	✓	✗
3a	Config 4	✗	✓	✓	✓	✗	✗
3a	Config 5	✗	✓	✓	✗	✓	✗
1b	Config 6	✗	✗	✓	✓	✗	✗
1b	Config 7	✗	✗	✓	✗	✓	✗
1a	Config 8	✓	✗	✗	✗	✗	✓
1a	Config 9	✗	✓	✗	✗	✗	✓

Table 2-6. Simultaneous Transmission Configurations

✓ = Support; ✗ = Not Support

Note:

All of the above simultaneous transmission configurations have been tested and the worst case configuration was found to be Config 3 and reported in the RF WLAN and RF Part 27b test report.

Wi-Fi 2.4GHz and Bluetooth 2.4 GHz can transmit simultaneously on separate antennas. Specific 2.4 GHz Wi-Fi antenna that can only transmit simultaneously with 2.4 GHz Bluetooth antenna is listed in the SAR test report. For BT (2.4 GHz) in connected mode and Wi-Fi (2.4 GHz) – Wi-Fi max power will not exceed minimum of (13.5dBm, SAR max cap, Reg max cap) power. For BT (2.4 GHz) in disconnected mode and Wi-Fi (2.4 GHz) – BT will be using iPA only and Wi-Fi max power will not exceed minimum of (SAR max cap, Reg max cap) power.

FCC ID: BCGA2757 IC: 579C-A2757	e element MEASUREMENT REPORT (CERTIFICATION)			Approved by: Technical Manager
Test Report S/N: 1C2205090023-17.BCG	Test Dates: 6/7/2022 - 9/18/2022	EUT Type: Tablet Device	Page 7 of 405	



2.3 Antenna Description

Following antenna gains provided by manufacturer were used for testing.

Frequency [GHz]	Antenna Gain (dBi)		
	Antenna 3c	Antenna 3a	Antenna 1b
5.150 – 5.250	2.8	0.4	-1.4
5.250 – 5.350	1.9	1.2	-1.9
5.470 – 5.725	3.6	2.2	-1.1
5.725 – 5.850	3.2	1.3	-1.0

Table 2-7. Highest Antenna Gain

2.4 Test Support Equipment

Test Support Equipment List				
1	Apple MacBook Pro w/AC/DC Adapter	Model: A2141 Model: A2166	S/N: C02DV7VKMD6T S/N: N/A	
2	Apple USB-C Cable	Model: Spartan	S/N: 000MKTR02U	
3	USB-C Cable w/ AC Adapter	Model: A246 Model: A2305	S/N: N/A S/N: N/A	
4	DC Power Supply	Model: KPS3010D	S/N: N/A	

Table 2-8. Test Support Equipment List

FCC ID: BCGA2757 IC: 579C-A2757		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-17.BCG	Test Dates: 6/7/2022 - 9/18/2022	EUT Type: Tablet Device	Page 8 of 405

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Washington DC LLC. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

2.5 Test Configuration

The EUT was tested per the guidance of ANSI C63.10-2013 and KDB 789033 D02 v02r01. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See Sections 3.2 for AC line conducted emissions test setups, 3.3 for radiated emissions test setups, and 7.2, 7.3, 7.4, and 7.5 for antenna port conducted emissions test setups.

For emissions from 1GHz – 18GHz, low, mid, and high channels were tested with highest power and worst case configuration. The emissions below 1GHz and above 18GHz were tested with the highest transmitting power and the worst case channel.

The EUT was manipulated through three orthogonal planes of X-orientation (flatbed), Y-orientation (landscape), and Z-orientation (portrait) during the testing. Only the worst case emissions were reported in this test report.

For AC line conducted and radiated test below 1GHz, following configuration were investigated and EUT powered by AC/DC was the worst case.

- EUT powered by AC/DC adaptor via USB-C cable with wire charger
- EUT powered by host PC via USB-C cable with wire charger

802.11ax-RU HE20/40/80 2TX CDD/SDM mode test data provided in this report covers 802.11ax-RU HE20/40/80 2TX STBC mode.

For 802.11a/n/ac/ax-SU test results, see separate UNII report, 1C2205090023-16.BCG.

2.6 Software and Firmware

The test was conducted with firmware version 20A32640u installed on the EUT.

2.7 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-17.BCG	Test Dates: 6/7/2022 - 9/18/2022	EUT Type: Tablet Device	Page 9 of 405

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013) and the guidance provided in KDB 789033 D02 v02r01 were used in the measurement of the EUT.

Deviation from measurement procedure.....None

3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 7m x 3.66m x 2.7m shielded enclosure. The shielded enclosure is manufactured by AP Americas. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-6. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50µH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is EPCOS 2X60A Power Line Filter (100dB Attenuation, 14kHz-18GHz) and the two EPCOs 2X48A filters (100dB Minimum Insertion Loss, 14kHz - 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 7.8. Automated test software was used to perform the AC line conducted emissions testing. Automated measurement software utilized is Rohde & Schwarz EMC32, Version 10.50.40.

FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-17.BCG	Test Dates: 6/7/2022 - 9/18/2022	EUT Type: Tablet Device	Page 10 of 405 V 10.5 12/15/2021

3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

Per KDB 414788 D01 v01r01, radiated emission test sites other than open-field test sites (e.g., shielded anechoic chambers), may be employed for emission measurements below 30MHz if characterized so that the measurements correspond to those obtained at an open-field test site. To determine test site equivalency, a reference sample transmitting at 149kHz was measured on an open field test site (asphalt with no ground plane) and then measured in the 3m semi-anechoic chamber. A calibrated 60cm loop antenna was used while the reference device was rotated through the X, Y and Z axis in order to capture the worst case level. A maximum deviation of 2.77dB at 149kHz was measured when comparing the 3 meter semi-anechoic chamber to the open field site.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33 depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: BCGA2757 IC: 579C-A2757	element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-17.BCG	Test Dates: 6/7/2022 - 9/18/2022	EUT Type: Tablet Device		Page 11 of 405

4.0 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

- The antennas of the EUT are **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The EUT complies with the requirement of §15.203.

FCC ID: BCGA2757 IC: 579C-A2757	e element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-17.BCG	Test Dates: 6/7/2022 - 9/18/2022	EUT Type: Tablet Device		Page 12 of 405

5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.23-2012. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (\pm dB)
Conducted Bench Top Measurements	1.77
Line Conducted Disturbance	2.70
Radiated Disturbance (<30MHz)	4.38
Radiated Disturbance (30MHz - 1GHz)	4.75
Radiated Disturbance (1 - 18GHz)	5.20
Radiated Disturbance (>18GHz)	4.72

FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-17.BCG	Test Dates: 6/7/2022 - 9/18/2022	EUT Type: Tablet Device	Page 13 of 405

6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent Technologies	N9030A	3Hz-44GHz PXA Signal Analyzer	6/10/2022	Annual	6/10/2023	MY49430244
Agilent Technologies	N9020A	MXA Signal Analyzer	4/26/2022	Annual	4/26/2023	MY56470202
Anritsu	ML2496A	Power Meter	11/29/2021	Annual	11/29/2022	1840005
Anritsu	MA2411B	Pulse Power Sensor	11/30/2021	Annual	11/30/2022	1726261
Anritsu	MA2411B	Pulse Power Sensor	11/30/2021	Annual	11/30/2022	1726262
ATM	180-442A-KF	20dB Nominal Gain Horn Antenna	1/19/2022	Annual	1/19/2023	T058701-02
Com-Power Corporation	LIN-120A	Line Impedance Stabilization Network (LISN)	3/7/2022	Annual	3/7/2023	241296
ETS-Lindgren	3142E	Biconilog Antenna (26-6000MHz)	10/21/2021	Annual	10/21/2022	208204
ETS-Lindgren	3117	Double Ridged Guide Horn Antenna (1-18GHz)	10/25/2021	Annual	10/25/2022	227597
Keysight Technology	N9040B	UXA Signal Analyzer	2/8/2022	Annual	2/8/2023	MY57212015
Rohde & Schwarz	TS-PR8	Pre-Amplifier (30MHz-6GHz)	1/6/2022	Annual	1/6/2023	102328
Rohde & Schwarz	ESW26	EMI Test Receiver	5/19/2022	Annual	5/19/2023	101299
Rohde & Schwarz	ESW44	EMI Test Receiver	12/2/2021	Annual	12/2/2022	101570
Rohde & Schwarz	FSV40	Signal Analyzer (10Hz-40GHz)	3/4/2022	Annual	3/4/2023	101619
Rohde & Schwarz	FSVA3044	Signal Analyzer (up to 44 GHz)	5/12/2022	Annual	5/12/2023	101098
Rohde & Schwarz	HFH2-Z2	Loop Antenna	4/3/2022	Annual	4/3/2023	100546
Rohde & Schwarz	TC-TA18	Cross-Polarized Antenna 400MHz-18GHz	1/25/2022	Annual	1/25/2023	101063
Rohde & Schwarz	TS-PR18	Pre-Amplifier (1GHz-18GHz)	1/6/2022	Annual	1/6/2023	101639
Rohde & Schwarz	TS-PR1840	Pre-Amplifier (18GHz-40GHz)	4/18/2022	Annual	4/18/2023	100050

Table 6-1. Test Equipment List

Note:

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-17.BCG	Test Dates: 6/7/2022 - 9/18/2022	EUT Type: Tablet Device	Page 14 of 405 V 10.5 12/15/2021

7.0 TEST RESULTS

7.1 Summary

Company Name: Apple Inc.
 FCC ID: BCGA2757
 IC: 579C-A2757
 FCC Classification: Unlicensed National Information Infrastructure (UNII)

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.407	RSS-Gen [6.7]	26dB Bandwidth	N/A	CONDUCTED	N/A	Section 7.2
15.407(e)	RSS-Gen [6.7]	6dB Bandwidth	>500kHz(5725-5850MHz)		PASS	Section 7.3
2.1049	RSS-Gen [6.7]	Occupied Bandwidth	N/A		N/A	Section 7.2, 7.3
15.407 (a.1.iv), (a.2), (a.3)	RSS-247 [6.2]	Maximum Conducted Output Power	Maximum conducted powers must meet the limits detailed in 15.407 (a) (RSS-247 [6.2])		PASS	Section 7.4
15.407 (a.1.iv), (a.2), (a.3)	RSS-247 [6.2]	Maximum Power Spectral Density	Maximum power spectral density must meet the limits detailed in 15.407 (a) (RSS-247 [6.2])		PASS	Section 7.5
15.407(h)	RSS-247 [6.3]	Dynamic Frequency Selection	See DFS Test Report	RADIATED	PASS	See DFS Test Report (1C220509002 3-15.BCG)
15.407(b.1), (2), (3), (4)	RSS-247 [6.2]	Undesirable Emissions	Undesirable emissions must meet the limits detailed in 15.407(b) (RSS-247 [6.2])		PASS	Section 7.6
15.205; 15.209	RSS-Gen [8.9]	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-Gen [8.9])		PASS	Section 7.6, 7.7
15.207	RSS-Gen [8.8]	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 (RSS-Gen [8.8]) limits	AC LINE CONDUCTED	PASS	Section 7.8

Table 7-1. Summary of Test Results

Notes:

1. All channels, modes, and modulations/data rates were investigated among all UNII bands. The test results shown in the following sections represent the worst case emissions.
2. The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
3. All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
4. For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element "UNII Automation," Version 7.0.
5. For radiated band edge, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element "Chamber Automation," Version 1.3.2.
6. Per RSS-247 Section 6.2.3, transmission on channels which overlap the 5600-5650 MHz is prohibited. This device operates under these frequencies only under the control of a certified master device and does not support active scanning on these channels. This device does not transmit any beacons or initiate any transmissions in UNII Bands 2A or 2C.
7. 802.11ax OFDMA testing was performed for all signal tone configurations as specified by the 802.11ax standard. Worst case results are determined and reported per the guidance provided at the October 2018 TCB Workshop.
8. Only one RU index could be selected at a time so no contiguous or non-contiguous RU's were considered for testing.

FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-17.BCG	Test Dates: 6/7/2022 - 9/18/2022	EUT Type: Tablet Device	Page 15 of 405

7.2 26dB & 99% Bandwidth Measurement – 802.11ax OFDMA

[§2.1049; §15.407; RSS-Gen \[6.7\]](#)

Test Overview and Limit

The bandwidth at 26dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10-2013 and KDB 789033 D02 v02r01, and at the appropriate frequencies. The spectrum analyzer's bandwidth measurement function is configured to measure the 26dB bandwidth.

The 26dB bandwidth is used to determine the conducted power limits.

Test Procedure Used

ANSI C63.10-2013 – Subclause 12.4
KDB 789033 D02 v02r01 – Section C

Test Settings

1. The signal analyzers' automatic bandwidth measurement capability was used to perform the 26dB bandwidth measurement. The "X" dB bandwidth parameter was set to X = 26. The automatic bandwidth measurement function also has the capability of simultaneously measuring the 99% occupied bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = approximately 1% of the emission bandwidth
3. VBW \geq 3 x RBW
4. Detector = Peak
5. Trace mode = max hold

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-1. Test Instrument & Measurement Setup

Test Notes

1. All antenna configs were investigated and only the worst case is reported.
2. All RU's were investigated and only worst case partially-loaded and fully-loaded RU's were reported
3. Low, mid, and high channels were tested and tabular data has been reported. Only mid channel bandwidth plots have been reported.

FCC ID: BCGA2757 IC: 579C-A2757	element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-17.BCG	Test Dates: 6/7/2022 - 9/18/2022	EUT Type: Tablet Device	Page 16 of 405	
			V 10.5 12/15/2021	



Antenna 3c 26dB & 99% Bandwidth Measurements

	Frequency [MHz]	Channel No.	802.11 Mode	RU Size	RU Index	Data Rate [Mbps]	Measured 99% Occupied Bandwidth [MHz]	Measured 26dB Bandwidth [MHz]
Band 1	5180	36	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.31	19.80
				26	4	12.5/14.7 (MCS11)	17.36	19.08
				26	8	12.5/14.7 (MCS11)	18.53	20.14
	5200	40	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.29	19.81
				26	4	12.5/14.7 (MCS11)	17.35	18.72
				26	8	12.5/14.7 (MCS11)	18.46	20.14
	5240	48	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.32	19.70
				26	4	12.5/14.7 (MCS11)	17.36	18.71
				26	8	12.5/14.7 (MCS11)	18.50	20.38
	5190	38	ax (40MHz)	26	0	12.5/14.7 (MCS11)	18.34	20.22
				26	8	12.5/14.7 (MCS11)	19.21	20.74
				26	17	12.5/14.7 (MCS11)	18.15	19.81
Band 2A	5230	46	ax (40MHz)	26	0	12.5/14.7 (MCS11)	19.30	20.90
				26	8	12.5/14.7 (MCS11)	19.66	22.21
				26	17	12.5/14.7 (MCS11)	18.32	20.15
	5210	42	ax (80MHz)	26	0	12.5/14.7 (MCS11)	18.23	19.81
				26	18	12.5/14.7 (MCS11)	37.61	39.90
				26	36	12.5/14.7 (MCS11)	19.25	21.21
	5260	52	ax (20MHz)	52	37	25/29.4 (MCS11)	18.26	20.06
				52	38	25/29.4 (MCS11)	17.41	19.64
				52	40	25/29.4 (MCS11)	18.55	20.70
	5300	60	ax (20MHz)	52	37	25/29.4 (MCS11)	18.19	20.29
				52	38	25/29.4 (MCS11)	17.48	19.65
				52	40	25/29.4 (MCS11)	18.57	20.71
	5320	64	ax (20MHz)	52	37	25/29.4 (MCS11)	18.24	19.96
				52	38	25/29.4 (MCS11)	17.40	19.83
				52	40	25/29.4 (MCS11)	18.50	20.70
Band 2C	5270	54	ax (40MHz)	52	37	25/29.4 (MCS11)	18.17	21.00
				52	40	25/29.4 (MCS11)	19.35	23.79
				52	44	25/29.4 (MCS11)	18.24	22.07
	5310	62	ax (40MHz)	52	37	25/29.4 (MCS11)	19.29	22.70
				52	40	25/29.4 (MCS11)	19.56	22.18
				52	44	25/29.4 (MCS11)	19.54	23.67
	5290	58	ax (80MHz)	52	37	25/29.4 (MCS11)	18.00	20.13
				52	44	25/29.4 (MCS11)	18.40	22.64
				52	52	25/29.4 (MCS11)	18.73	21.80
	5500	100	ax (20MHz)	52	37	25/29.4 (MCS11)	18.26	20.43
				52	38	25/29.4 (MCS11)	17.39	20.03
				52	40	25/29.4 (MCS11)	18.40	20.40
	5580	116	ax (20MHz)	52	37	25/29.4 (MCS11)	18.21	20.21
				52	38	25/29.4 (MCS11)	17.41	19.89
				52	40	25/29.4 (MCS11)	18.47	20.90
	5720	144	ax (20MHz)	52	37	25/29.4 (MCS11)	18.19	20.16
				52	38	25/29.4 (MCS11)	17.52	20.13
				52	40	25/29.4 (MCS11)	18.37	20.69
	5510	102	ax (40MHz)	52	37	25/29.4 (MCS11)	19.45	22.68
				52	40	25/29.4 (MCS11)	20.81	24.82
				52	44	25/29.4 (MCS11)	19.36	22.95
	5550	110	ax (40MHz)	52	37	25/29.4 (MCS11)	18.14	20.54
				52	40	25/29.4 (MCS11)	20.09	23.80
				52	44	25/29.4 (MCS11)	18.17	21.46
	5710	142	ax (40MHz)	52	37	25/29.4 (MCS11)	18.93	22.74
				52	40	25/29.4 (MCS11)	20.18	24.79
				52	44	25/29.4 (MCS11)	19.65	22.95
	5530	106	ax (80MHz)	52	37	25/29.4 (MCS11)	18.12	20.49
				52	44	25/29.4 (MCS11)	18.51	22.45
				52	52	25/29.4 (MCS11)	18.59	21.76
	5690	138	ax (80MHz)	52	37	25/29.4 (MCS11)	19.65	22.76
				52	44	25/29.4 (MCS11)	21.48	30.70
				52	52	25/29.4 (MCS11)	25.67	26.93

Table 7-2. Conducted BW Measurements Antenna 3c (RU26, RU 52)

FCC ID: BCGA2757 IC: 579C-A2757	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-17.BCG	Test Dates: 6/7/2022 - 9/18/2022	EUT Type: Tablet Device	Page 17 of 405 V 10.5 12/15/2021






Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Washington DC LLC. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

	Frequency [MHz]	Channel No.	802.11 Mode	RU Size	RU Index	Data Rate [Mbps]	Measured 99% Occupied Bandwidth [MHz]	Measured 26dB Bandwidth [MHz]
Band 1	5180	36	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.03	21.09
	5200	40	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.01	21.11
	5240	48	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.03	21.12
	5190	38	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.89	41.44
	5230	46	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.99	41.37
	5210	42	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.07	81.61
Band 2A	5260	52	ax (20MHz)	242	61	121.9/143.4 (MCS11)	18.99	23.27
	5300	60	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.06	21.22
	5320	64	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.04	21.24
	5270	54	ax (40MHz)	484	65	243.8/286.8 (MCS11)	38.00	41.74
	5310	62	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.94	41.39
	5290	58	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.07	81.58
Band 2C	5500	100	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.00	21.20
	5580	116	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.02	21.11
	5720	144	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.06	22.96
	5510	102	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.94	41.28
	5550	110	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.92	40.94
	5710	142	ax (40MHz)	484	65	243.8/286.8 (MCS11)	38.07	41.03
	5530	106	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.19	81.51
	5690	138	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.41	99.69

Table 7-3. Conducted BW Measurements Antenna 3c (Fully – loaded RU)

FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-17.BCG	Test Dates: 6/7/2022 - 9/18/2022	EUT Type: Tablet Device	Page 18 of 405 V 10.5 12/15/2021







Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Washington DC LLC. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-1. 26dB BW & 99% OBW Antenna 3c (20MHz BW 11ax Index 0 – RU26 – Ch.40)

Plot 7-4. 26dB BW & 99% OBW Antenna 3c (20MHz BW 11ax Index 0 – RU26 – Ch.40)


FCC ID: BCGA2757 IC: 579C-A2757		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-17.BCG	Test Dates: 6/7/2022 - 9/18/2022	EUT Type: Tablet Device	Page 19 of 405



FCC ID: BCGA2757		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-17.BCG	Test Dates: 6/7/2022 - 9/18/2022	EUT Type: Tablet Device	Page 20 of 405



Plot 7-13. 26dB BW & 99% OBW Antenna 3c (20MHz BW 11ax Index 37 – RU52 – Ch.60)



Plot 7-16. 26dB BW & 99% OBW Antenna 3c (20MHz BW 11ax – RU242 – Ch.60)




Plot 7-14. 26dB BW & 99% OBW Antenna 3c (20MHz BW 11ax Index 38 – RU52 – Ch.60)



Plot 7-17. 26dB BW & 99% OBW Antenna 3c (40MHz BW 11ax Index 37 – RU52 – Ch.54)







Plot 7-15. 26dB BW & 99% OBW Antenna 3c (20MHz BW 11ax Index 40 – RU52 – Ch.60)



Plot 7-18. 26dB BW & 99% OBW Antenna 3c (40MHz BW 11ax Index 40 – RU52 – Ch.54)


FCC ID: BCGA2757		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-17.BCG	Test Dates: 6/7/2022 - 9/18/2022	EUT Type: Tablet Device	Page 21 of 405



FCC ID: BCGA2757		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
IC: 579C-A2757	Test Report S/N: 1C2205090023-17.BCG	Test Dates: 6/7/2022 - 9/18/2022	EUT Type: Tablet Device

V 10.5 12/15/2021





Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Washington DC LLC. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



FCC ID: BCGA2757		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
IC: 579C-A2757	Test Report S/N: 1C2205090023-17.BCG	Test Dates: 6/7/2022 - 9/18/2022	EUT Type: Tablet Device

V 10.5 12/15/2021

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Washington DC LLC. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



FCC ID: BCGA2757		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-17.BCG	Test Dates: 6/7/2022 - 9/18/2022	EUT Type: Tablet Device	Page 24 of 405

Antenna 3a 26dB & 99% Bandwidth Measurements

	Frequency [MHz]	Channel No.	802.11 Mode	RU Size	RU Index	Data Rate [Mbps]	Measured 99% Occupied Bandwidth [MHz]	Measured 26dB Bandwidth [MHz]
Band 1	5180	36	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.30	19.57
				26	4	12.5/14.7 (MCS11)	17.29	18.84
				26	8	12.5/14.7 (MCS11)	18.55	20.36
	5200	40	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.23	19.67
				26	4	12.5/14.7 (MCS11)	17.29	18.88
				26	8	12.5/14.7 (MCS11)	18.49	20.14
	5240	48	ax (20MHz)	26	0	12.5/14.7 (MCS11)	18.33	19.72
				26	4	12.5/14.7 (MCS11)	17.38	18.93
				26	8	12.5/14.7 (MCS11)	18.56	20.22
	5190	38	ax (40MHz)	26	0	12.5/14.7 (MCS11)	18.13	19.75
				26	8	12.5/14.7 (MCS11)	20.29	22.37
				26	17	12.5/14.7 (MCS11)	18.39	20.58
	5230	46	ax (40MHz)	26	0	12.5/14.7 (MCS11)	18.03	19.93
				26	8	12.5/14.7 (MCS11)	20.31	22.87
				26	17	12.5/14.7 (MCS11)	18.29	19.65
	5210	42	ax (80MHz)	26	0	12.5/14.7 (MCS11)	18.12	19.70
				26	18	12.5/14.7 (MCS11)	37.55	39.48
				26	36	12.5/14.7 (MCS11)	18.92	20.95
Band 2A	5260	52	ax (20MHz)	52	37	25/29.4 (MCS11)	18.14	20.04
				52	38	25/29.4 (MCS11)	17.49	19.75
				52	40	25/29.4 (MCS11)	18.46	20.82
	5300	60	ax (20MHz)	52	37	25/29.4 (MCS11)	18.21	20.16
				52	38	25/29.4 (MCS11)	17.40	19.62
				52	40	25/29.4 (MCS11)	18.40	20.73
	5320	64	ax (20MHz)	52	37	25/29.4 (MCS11)	18.23	20.45
				52	38	25/29.4 (MCS11)	17.31	19.34
				52	40	25/29.4 (MCS11)	18.35	20.51
	5270	54	ax (40MHz)	52	37	25/29.4 (MCS11)	18.29	20.98
				52	40	25/29.4 (MCS11)	19.35	22.31
				52	44	25/29.4 (MCS11)	18.17	21.23
	5310	62	ax (40MHz)	52	37	25/29.4 (MCS11)	19.07	23.51
				52	40	25/29.4 (MCS11)	20.68	24.61
				52	44	25/29.4 (MCS11)	18.95	22.33
	5290	58	ax (80MHz)	52	37	25/29.4 (MCS11)	17.97	20.26
				52	44	25/29.4 (MCS11)	18.61	22.73
				52	52	25/29.4 (MCS11)	18.51	21.44
Band 2C	5500	100	ax (20MHz)	52	37	25/29.4 (MCS11)	18.22	20.14
				52	38	25/29.4 (MCS11)	17.37	19.90
				52	40	25/29.4 (MCS11)	18.30	20.52
	5580	116	ax (20MHz)	52	37	25/29.4 (MCS11)	18.08	20.28
				52	38	25/29.4 (MCS11)	17.43	19.82
				52	40	25/29.4 (MCS11)	18.31	20.87
	5720	144	ax (20MHz)	52	37	25/29.4 (MCS11)	18.24	19.78
				52	38	25/29.4 (MCS11)	17.45	19.97
				52	40	25/29.4 (MCS11)	18.45	20.62
	5510	102	ax (40MHz)	52	37	25/29.4 (MCS11)	19.34	23.03
				52	40	25/29.4 (MCS11)	20.21	23.79
				52	44	25/29.4 (MCS11)	19.57	22.72
	5550	110	ax (40MHz)	52	37	25/29.4 (MCS11)	18.32	21.13
				52	40	25/29.4 (MCS11)	19.42	22.58
				52	44	25/29.4 (MCS11)	18.22	21.32
	5710	142	ax (40MHz)	52	37	25/29.4 (MCS11)	18.51	22.62
				52	40	25/29.4 (MCS11)	20.21	25.01
				52	44	25/29.4 (MCS11)	19.47	23.68
	5530	106	ax (80MHz)	52	37	25/29.4 (MCS11)	18.06	20.31
				52	44	25/29.4 (MCS11)	18.74	22.44
				52	52	25/29.4 (MCS11)	18.68	22.15
	5690	138	ax (80MHz)	52	37	25/29.4 (MCS11)	20.06	23.26
				52	44	25/29.4 (MCS11)	20.94	26.76
				52	52	25/29.4 (MCS11)	25.92	28.58

Table 7-4. Conducted Bandwidth Measurements Antenna 3a (RU26, RU52)






FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-17.BCG	Test Dates: 6/7/2022 - 9/18/2022	EUT Type: Tablet Device	Page 25 of 405 V 10.5 12/15/2021

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Washington DC LLC. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.






	Frequency [MHz]	Channel No.	802.11 Mode	RU Size	RU Index	Data Rate [Mbps]	Measured 99% Occupied Bandwidth [MHz]	Measured 26dB Bandwidth [MHz]
Band 1	5180	36	ax (20MHz)	242	61	121.9/143.4 (MCS11)	18.99	21.24
	5200	40	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.11	27.65
	5240	48	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.09	25.78
	5190	38	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.94	41.30
	5230	46	ax (40MHz)	484	65	243.8/286.8 (MCS11)	38.10	50.14
	5210	42	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.09	81.16
Band 2A	5260	52	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.06	25.07
	5300	60	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.08	23.73
	5320	64	ax (20MHz)	242	61	121.9/143.4 (MCS11)	18.99	20.97
	5270	54	ax (40MHz)	484	65	243.8/286.8 (MCS11)	38.01	41.96
	5310	62	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.93	41.16
	5290	58	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.15	81.14
Band 2C	5500	100	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.06	20.99
	5580	116	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.07	23.74
	5720	144	ax (20MHz)	242	61	121.9/143.4 (MCS11)	19.05	25.76
	5510	102	ax (40MHz)	484	65	243.8/286.8 (MCS11)	37.99	41.56
	5550	110	ax (40MHz)	484	65	243.8/286.8 (MCS11)	38.00	41.79
	5710	142	ax (40MHz)	484	65	243.8/286.8 (MCS11)	38.01	42.09
	5530	106	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.11	81.85
	5690	138	ax (80MHz)	996	67	510.4/600.5 (MCS11)	77.44	105.40

Table 7-5. Conducted Bandwidth Measurements Antenna 3a (Fully- loaded RU)

FCC ID: BCGA2757 IC: 579C-A2757	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-17.BCG	Test Dates: 6/7/2022 - 9/18/2022	EUT Type: Tablet Device	Page 26 of 405 V 10.5 12/15/2021




FCC ID: BCGA2757		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-17.BCG	Test Dates: 6/7/2022 - 9/18/2022	EUT Type: Tablet Device	Page 27 of 405



FCC ID: BCGA2757		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-17.BCG	Test Dates: 6/7/2022 - 9/18/2022	EUT Type: Tablet Device	Page 28 of 405




Plot 7-49. 26dB BW & 99% OBW Antenna 3a (20MHz BW 11ax Index 37 – RU52 – Ch.60)




Plot 7-52. 26dB BW & 99% OBW Antenna 3a (20MHz BW 11ax – RU242 – Ch.60)




Plot 7-50. 26dB BW & 99% OBW Antenna 3a (20MHz BW 11ax Index 38 – RU52 – Ch.60)



Plot 7-53. 26dB BW & 99% OBW Antenna 3a (40MHz BW 11ax Index 37 – RU52 – Ch.54)




Plot 7-51. 26dB BW & 99% OBW Antenna 3a (20MHz BW 11ax Index 40 – RU52 – Ch.60)




Plot 7-54. 26dB BW & 99% OBW Antenna 3a (40MHz BW 11ax Index 40 – RU52 – Ch.54)

FCC ID: BCGA2757		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-17.BCG	Test Dates: 6/7/2022 - 9/18/2022	EUT Type: Tablet Device	Page 29 of 405




Plot 7-55. 26dB BW & 99% OBW Antenna 3a (40MHz BW 11ax Index 44 – RU52 – Ch.54)




Plot 7-58. 26dB BW & 99% OBW Antenna 3a (80MHz BW 11ax Index 44 – RU52 – Ch.58)




Plot 7-56. 26dB BW & 99% OBW Antenna 3a (40MHz BW 11ax – RU484 – Ch.54)



Plot 7-59. 26dB BW & 99% OBW Antenna 3a (80MHz BW 11ax Index 52 – RU52 – Ch.58)



Plot 7-57. 26dB BW & 99% OBW Antenna 3a (80MHz BW 11ax Index 37 – RU52 – Ch.58)



Plot 7-60. 26dB BW & 99% OBW Antenna 3a (80MHz BW 11ax – RU996 – Ch.58)

FCC ID: BCGA2757		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090023-17.BCG	Test Dates: 6/7/2022 - 9/18/2022	EUT Type: Tablet Device	Page 30 of 405

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Washington DC LLC. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.