

MEASUREMENT REPORT

FCC PART 15.247 / ISED RSS-247 Bluetooth (Low Energy)

Applicant Name:

Apple Inc.
One Apple Park Way
Cupertino, CA 95014
United States

Date of Testing:

07/21/2022-09/23/2022

Test Site/Location:

Element Washington DC LLC, Morgan Hill, CA, USA

Test Report Serial No.:

1C2205090024-04.BCG

FCC ID:	BCGA2759
IC:	579C-A2759
APPLICANT:	Apple Inc.

Application Type:
Model/HVIN:
EUT Type:
Max. RF Output Power:
Frequency Range:
FCC Classification:
FCC Rule Part(s):
ISED Specification:
Test Procedure(s):

Certification
A2759
Tablet Device
133.045 mW (21.24 dBm) Peak Conducted
2402 – 2480MHz
Digital Transmission System (DTS)
Part 15 Subpart C (15.247)
RSS-247 Issue 2
ANSI C63.10-2013, KDB 558074 D01 v05r02

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013 and KDB 558074 D01 v05r02. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



RJ Ortiz

Executive Vice President



FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 1 of 104

V 10.5 12/15/2021

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Washington DC LLC. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

T A B L E O F C O N T E N T S

1.0	INTRODUCTION	3
1.1	Scope	3
1.2	Element Test Location	3
1.3	Test Facility / Accreditations	3
2.0	PRODUCT INFORMATION.....	4
2.1	Equipment Description	4
2.2	Device Capabilities	4
2.3	Antenna Description	5
2.4	Test Support Equipment	5
2.5	Test Configuration	6
2.6	Software and Firmware	6
2.7	EMI Suppression Device(s)/Modifications	6
3.0	DESCRIPTION OF TESTS	7
3.1	Evaluation Procedure	7
3.2	AC Line Conducted Emissions	7
3.3	Radiated Emissions.....	8
3.4	Environmental Conditions.....	8
4.0	ANTENNA REQUIREMENTS	9
5.0	MEASUREMENT UNCERTAINTY	10
6.0	TEST EQUIPMENT CALIBRATION DATA	11
7.0	TEST RESULTS.....	12
7.1	Summary	12
7.2	Bandwidth Measurement – Bluetooth (LE)	13
7.3	Output Power Measurement – Bluetooth (LE)	23
7.3.1	Peak Output Power Measurement – Bluetooth (LE).....	24
7.3.2	Average Output Power Measurement – Bluetooth (LE).....	26
7.4	Power Spectral Density – Bluetooth (LE)	29
7.5	Conducted Authorized Band Edge	58
7.6	Conducted Spurious Emissions.....	63
7.7	Radiated Spurious Emissions – Above 1GHz	71
7.7.1	Radiated Restricted Band Edge Measurements.....	84
7.8	Radiated Spurious Emissions – Below 1GHz.....	96
7.9	AC Line-Conducted Emissions Measurement	100
8.0	CONCLUSION.....	104

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 2 of 104

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 Element Washington DC LLC Test Location

These measurement tests were conducted at the Element facility located at 18855 Adams Court, Morgan Hill, CA 95037. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014 and KDB 414788 D01 v01r01.

1.3 Test Facility / Accreditations

Measurements were performed at Element Washington DC LLC located in Morgan Hill, CA 95037, U.S.A.

- Element Washington DC LLC is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.02 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Washington DC LLC TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- Element Washington DC LLC facility is a registered (22831) test laboratory with the site description on file with ISED.

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 3 of 104

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Apple Tablet Device FCC ID: BCGA2759 and IC: 579C-A2759**. The data found in this test report was taken with the EUT operating in Bluetooth low energy mode. While in low energy mode, the Bluetooth transmitter hops pseudo-randomly between 40 channels, three of which are “advertising channels”. When the transmitter is hopping only between the three advertising channels, the EUT does not fall under the category of a “hopper” as defined in 15.247(a)(iii) which states that a “frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.” As operation on only the advertising channels does not qualify the EUT as a hopper, the EUT is certified as a DTS device in this mode. The data found in this report is representative of the device when it transmits on its advertising channels. Typical Bluetooth operation is covered under the DSS report found with this application.

Test Device Serial No.: YGHDWDW2Y5, L6X0D9MM126, GQ3KW3V146, YD7VPKP9WD

2.2 Device Capabilities

This device contains the following capabilities:

802.11b/g/n/ax WLAN, 802.11a/n/ac/ax UNII, 802.11a/ax WiFi 6E, Bluetooth (1x, EDR, LE1M, LE2M, HDR4, HDR8), NB UNII (1x, HDR4, HDR8), WPT

This device supports BT Beamforming

BLE-1M		BLE-2M	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
00	2402	01	2404
:	:	:	:
19	2440	19	2440
:	:	:	:
39	2480	38	2478

Table 2-1. Bluetooth LE Frequency / Channel Operations

Note: This device is capable of operating in hopping and non-hopping mode. The EUT can hop between 40 different channels in the 2400 – 2483.5MHz band.

Measured Duty Cycles					
BLE Mode		Duty Cycle [%]			TxBF
		WF8	WF7		
1M	ePA	100.0	100.0	100.0	TxBF
	iPA	100.0	100.0	100.0	
2M	ePA	100.0	100.0	100.0	TxBF
	iPA	100.0	100.0	100.0	

Table 2-2. Measured Duty Cycles

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 4 of 104



Note:

Wi-Fi 2.4GHz and Bluetooth 2.4 GHz can transmit simultaneously on separate antennas. Specific 2.4 GHz Wi-Fi antenna that can only transmit simultaneously with 2.4 GHz Bluetooth antenna is listed in the SAR test report. For BT (2.4 GHz) in connected mode and Wi-Fi (2.4 GHz) – Wi-Fi max power will not exceed minimum of (13.5dBm, SAR max cap, Reg max cap) power. For BT (2.4 GHz) in disconnected mode and Wi-Fi (2.4 GHz) – BT will be using iPA only and Wi-Fi max power will not exceed minimum of (SAR max cap, Reg max cap) power.

2.3 Antenna Description

Following antennas gains provided by manufacturer were used for testing.

Frequency [GHz]	Antenna Gain (dBi)	
	Antenna WF8	Antenna WF7
2.4	2.2	2.6

Table 2-3. Highest Antenna Gain

2.4 Test Support Equipment

1	Apple MacBook Pro w/AC/DC Adapter	Model: A2141 Model: A2166	S/N: C02DV7VKMD6T S/N: N/A
2	Apple USB-C Cable	Model: Spartan	S/N: 000MKTR02U
3	USB-C Cable w/ AC Adapter	Model: A246 Model: A2305	S/N: N/A S/N: N/A
4	Apple Pencil	Model: N/A	S/N: GQXGSXBJKM9
5	DC Power Supply	Model: KPS3010D	S/N: N/A

Table 2-4. Test Support Equipment List

FCC ID: BCGA2759 IC: 579C-A2759	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 5 of 104

2.5 Test Configuration

The EUT was tested per the guidance of ANSI C63.10-2013 and KDB 558074 D01 v05r02. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See Sections 3.2 for AC line conducted emissions test setups, 3.3 for radiated emissions test setups, and 7.2, 7.3, 7.4, 7.5, and 7.6 for antenna port conducted emissions test setups.

There are two vendors of the WiFi/Bluetooth radio modules, variant 1 and variant 2. Both radio modules have the same mechanical outline, same on-board antenna matching circuit, identical antenna structure, and are built and tested to conform to the same specifications and to operate within the same tolerances. The worst case configuration was found between the two variants. The EUT was also investigated with and without charger.

For emissions from 1GHz – 18GHz, low, mid, and high channels were tested with highest power and worst case configuration. The emissions below 1GHz and above 18GHz were tested with the highest transmitting power and the worst case channel.

The EUT was manipulated through three orthogonal planes of X-orientation (flatbed), Y-orientation (landscape), and Z-orientation (portrait) during the testing. Only the worst case emissions were reported in this test report.

For AC line conducted and radiated test below 1GHz, following configuration were investigated and the worst case was reported.

- EUT powered by AC/DC adaptor via USB-C cable with wire charger
- EUT powered by host PC via USB-C cable with wire charger

2.6 Software and Firmware

The test was conducted with firmware version 20A8359 installed on the EUT.

2.7 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 6 of 104

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013) and the guidance provided in KDB 558074 D01 v05r02 were used in the measurement of the EUT.

Deviation from measurement procedure.....None

3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 7m x 3.66m x 2.7m shielded enclosure. The shielded enclosure is manufactured by AP Americas. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-6. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50µH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is EPCOS 2X60A Power Line Filter (100dB Attenuation, 14kHz-18GHz) and the two EPCOs 2X48A filters (100dB Minimum Insertion Loss, 14kHz - 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that the cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 7.9. Automated test software was used to perform the AC line conducted emissions testing. Automated measurement software utilized is Rohde & Schwarz EMC32, Version 10.50.40.

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 7 of 104 V 10.5 12/15/2021

3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

Per KDB 414788 D01 v01r01, radiated emission test sites other than open-field test sites (e.g., shielded anechoic chambers), may be employed for emission measurements below 30MHz if characterized so that the measurements correspond to those obtained at an open-field test site. To determine test site equivalency, a reference sample transmitting at 149kHz was measured on an open field test site (asphalt with no ground plane) and then measured in the 3m semi-anechoic chamber. A calibrated 60cm loop antenna was rotated about its vertical axis while the reference device was rotated through the X, Y and Z axis in order to capture the worst case level. A maximum deviation of 2.77dB at 149kHz was measured when comparing the 3 meter semi-anechoic chamber to the open field site.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33 depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: BCGA2759 IC: 579C-A2759	 element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device		Page 8 of 104

4.0 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

- The antenna(s) of the EUT are **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The EUT complies with the requirement of §15.203.

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 9 of 104

5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.23-2012. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (\pm dB)
Conducted Bench Top Measurements	1.77
Line Conducted Disturbance	2.70
Radiated Disturbance (<30MHz)	4.38
Radiated Disturbance (30MHz - 1GHz)	4.75
Radiated Disturbance (1 - 18GHz)	5.20
Radiated Disturbance (>18GHz)	4.72

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 10 of 104

6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent Technologies	N9030A	3Hz-44GHz PXA Signal Analyzer	6/10/2022	Annual	6/10/2023	MY49430244
Agilent Technologies	N9020A	MXA Signal Analyzer	4/26/2022	Annual	4/26/2023	MY56470202
Anritsu	ML2496A	Power Meter	11/29/2021	Annual	11/29/2022	1840005
Anritsu	MA2411B	Pulse Power Sensor	11/30/2021	Annual	11/30/2022	1726261
Anritsu	MA2411B	Pulse Power Sensor	11/30/2021	Annual	11/30/2022	1726262
ATM	180-442A-KF	20dB Nominal Gain Horn Antenna	1/19/2022	Annual	1/19/2023	T058701-02
Com-Power Corporation	LIN-120A	Line Impedance Stabilization Network (LISN)	3/7/2022	Annual	3/7/2023	241296
ETS-Lindgren	3142E	Biconilog Antenna (26-6000MHz)	10/21/2021	Annual	10/21/2022	208204
ETS-Lindgren	3117	Double Ridged Guide Horn Antenna (1-18GHz)	10/25/2021	Annual	10/25/2022	227597
Keysight Technology	N9040B	UXA Signal Analyzer	2/8/2022	Annual	2/8/2023	MY57212015
Rohde & Schwarz	TS-PR8	Pre-Amplifier (30MHz-6GHz)	1/6/2022	Annual	1/6/2023	102328
Rohde & Schwarz	ESW26	EMI Test Receiver	5/19/2022	Annual	5/19/2023	101299
Rohde & Schwarz	ESW44	EMI Test Receiver	12/2/2021	Annual	12/2/2022	101570
Rohde & Schwarz	FSV40	Signal Analyzer (10Hz-40GHz)	3/4/2022	Annual	3/4/2023	101619
Rohde & Schwarz	FSVA3044	Signal Analyzer (up to 44 GHz)	5/12/2022	Annual	5/12/2023	101098
Rohde & Schwarz	HFH2-Z2	Loop Antenna	4/3/2022	Annual	4/3/2023	100546
Rohde & Schwarz	TC-TA18	Cross-Polarized Antenna 400MHz-18GHz	1/25/2022	Annual	1/25/2023	101063
Rohde & Schwarz	TS-PR18	Pre-Amplifier (1GHz-18GHz)	1/6/2022	Annual	1/6/2023	101639
Rohde & Schwarz	TS-PR1840	Pre-Amplifier (18GHz-40GHz)	4/18/2022	Annual	4/18/2023	100050

Table 6-1. Test Equipment List

Note:

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 11 of 104

7.0 TEST RESULTS

7.1 Summary

Company Name: Apple Inc.
 FCC ID: BCGA2759
 IC: 579C-A2759
 FCC Classification: Digital Transmission System (DTS)
 Number of Channels: 40

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.247(a)(2)	RSS-247 [5.2]	6dB Bandwidth	> 500kHz	CONDUCTED	PASS	Section 7.2
2.1049	RSS-Gen [6.7]	Occupied Bandwidth	N/A		N/A	Section 7.2
15.247(b)(3)	RSS-247 [5.4(d)]	Transmitter Output Power	< 1 Watt		PASS	Sections 7.3
15.247(e)	RSS-247 [5.2]	Transmitter Power Spectral Density	< 8dBm / 3kHz Band		PASS	Section 7.4
15.247(d)	RSS-247 [5.5]	Band Edge / Out-of-Band Emissions	≥ 20dBc		PASS	Sections 7.5, 7.6
15.205 15.209	RSS-Gen [8.9]	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-Gen [8.9])	RADIATED	PASS	Sections 7.7, 7.7.1, 7.8
15.207	RSS-Gen [8.8]	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 limits (RSS-Gen[8.8])	LINE CONDUCTED	PASS	Section 7.9

Table 7-1. Summary of Test Results

Notes:

1. All modes of operation were investigated. The test results shown in the following sections represent the worst case emissions.
2. The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
3. All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
4. For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element "Bluetooth LE Automation," Version 4.0.
5. For radiated band edge, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element "Chamber Automation," Version 1.3.2.

FCC ID: BCGA2759 IC: 579C-A2759	 element MEASUREMENT REPORT (CERTIFICATION)			Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 12 of 104	

7.2 Bandwidth Measurement – Bluetooth (LE)

§2.1049; §15.247(a.2); RSS-247 [5.2]; RSS-Gen [6.7]

Test Overview and Limit

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the transmitter antenna terminal of the EUT while the EUT is operating at maximum power and at the appropriate frequencies. All modes of operation were investigated and the worst case configuration results are reported in this section.

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible 6dB bandwidth is 500 kHz.

Test Procedure Used

ANSI C63.10-2013 – Subclause 11.8.2 Option 2

KDB 558074 D01 v05r02 – Section 8.2

RSS-Gen [6.7]

Test Settings

1. The signal analyzers' automatic bandwidth measurement capability of the spectrum analyzer was used to perform the 99% occupied bandwidth and the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to X = 6. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 100kHz
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 13 of 104

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-1. Test Instrument & Measurement Setup

Test Notes

All supported modulation, antenna (including TxBF mode) and power schemes have been tested on the unit and only worst case configuration is reported.

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 14 of 104



Antenna WF8

Frequency [MHz]	Data Rate [Mbps]	Power Scheme	Channel No.	Measured 99% Occupied Bandwidth [kHz]	Measured 6dB Bandwidth [kHz]	Minimum 6dB Bandwidth [kHz]	Pass / Fail
2402	1.0	ePA	0	1058.8	720.9	500	Pass
2440	1.0	ePA	19	1059.3	721.6	500	Pass
2480	1.0	ePA	39	1058.7	720.9	500	Pass
2404	2.0	ePA	1	1957.1	1306.0	500	Pass
2440	2.0	ePA	19	2058.3	1269.0	500	Pass
2478	2.0	ePA	38	2054.3	1295.0	500	Pass

Table 7-2. 6dB BW & 99% OBW Measurements Antenna WF8

FCC ID: BCGA2759 IC: 579C-A2759		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 15 of 104



Plot 7-1. 6dB BW & 99% OBW Plot Antenna WF8 (Bluetooth (LE), 1Mbps, ePA – Ch. 0)



Plot 7-2. 6dB BW & 99% OBW Plot Antenna WF8 (Bluetooth (LE), 1Mbps, ePA – Ch. 19)

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 16 of 104



Plot 7-3. 6dB BW & 99% OBW Plot Antenna WF8 (Bluetooth (LE), 1Mbps, ePA – Ch. 39)



Plot 7-4. 6dB BW & 99% OBW Plot Antenna WF8 (Bluetooth (LE), 2Mbps, ePA – Ch. 1)

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 17 of 104



Plot 7-5. 6dB BW & 99% OBW Plot Antenna WF8 (Bluetooth (LE), 2Mbps, ePA – Ch. 19)



Plot 7-6. 6dB BW & 99% OBW Plot Antenna WF8 (Bluetooth (LE), 2Mbps, ePA – Ch. 38)

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 18 of 104



Antenna WF7

Frequency [MHz]	Data Rate [Mbps]	Power Scheme	Channel No.	Measured 99% Occupied Bandwidth [kHz]	Measured 6dB Bandwidth [kHz]	Minimum 6dB Bandwidth [kHz]	Pass / Fail
2402	1.0	ePA	0	1058.4	720.8	500	Pass
2440	1.0	ePA	19	1060.0	725.0	500	Pass
2480	1.0	ePA	39	1059.1	720.4	500	Pass
2404	2.0	ePA	1	1966.7	1313.0	500	Pass
2440	2.0	ePA	19	1964.8	1312.0	500	Pass
2478	2.0	ePA	38	1961.6	1312.0	500	Pass

Table 7-3. 6dB BW & 99% OBW Measurements Antenna WF7

FCC ID: BCGA2759 IC: 579C-A2759		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 19 of 104



Plot 7-7. 6dB BW & 99% OBW Plot Antenna WF7 (Bluetooth (LE), 1Mbps, ePA – Ch. 0)




Plot 7-8. 6dB BW & 99% OBW Plot Antenna WF7 (Bluetooth (LE), 1Mbps, ePA – Ch. 19)

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 20 of 104



Plot 7-9. 6dB BW & 99% OBW Plot Antenna WF7 (Bluetooth (LE), 1Mbps, ePA – Ch. 39)




Plot 7-10. 6dB BW & 99% OBW Plot Antenna WF7 (Bluetooth (LE), 2Mbps, ePA – Ch. 1)

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 21 of 104



Plot 7-11. 6dB BW & 99% OBW Plot Antenna WF7 (Bluetooth (LE), 2Mbps, ePA – Ch. 19)



Plot 7-12. 6dB BW & 99% OBW Antenna WF7 (Bluetooth (LE), 2Mbps, ePA – Ch. 38)

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 22 of 104

7.3 Output Power Measurement – Bluetooth (LE)

§15.247(b.3); RSS-247 [5.4(d)]

Test Overview and Limits

The transmitter antenna terminal of the EUT is connected to the input of a spectrum analyzer. Measurements are made while the EUT is operating at maximum power and at the appropriate frequencies.

The maximum peak conducted output power of digital modulation systems operating in the 2400-2483.5 MHz band is 1 Watt.

The conducted output power limit on paragraph above is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For DTSs employing digital modulation techniques operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1 W. The e.i.r.p. shall not exceed 4 W.

Test Procedure Used

ANSI C63.10-2013 – Subclause 11.9.1.3

ANSI C63.10-2013 – Subclause 11.9.2.3.2

KDB 558074 D01 v05r02 – Section 8.3.1.3, 8.3.2.3

ANSI C63.10-2013 – Subclause 14.2 Measure-and-Sum Technique

KDB 662911 D01 v02r01 – Section E1) Measure-and-Sum Technique

Test Settings

Method PKPM1 (Peak Power Measurement)

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

Method AVGPM-G (Average Power Measurement)

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-2. Test Instrument & Measurement Setup for Peak and Average Power Measurement

Test Notes

None

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 23 of 104



7.3.1 Peak Output Power Measurement – Bluetooth (LE)

Frequency [MHz]	Data Rate [Mbps]	Power Scheme	Channel No.	Peak Conducted Power		Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	EIRP Margin [dB]
				[dBm]	[mW]						
2402	1.0	ePA	0	19.06	80.538	30.00	-10.94	2.20	21.26	36.02	-14.76
2440	1.0	ePA	19	19.18	82.794	30.00	-10.82	2.20	21.38	36.02	-14.64
2480	1.0	ePA	39	19.13	81.846	30.00	-10.87	2.20	21.33	36.02	-14.69
2402	1.0	iPA	0	12.53	17.906	30.00	-17.47	2.20	14.73	36.02	-21.29
2440	1.0	iPA	19	12.41	17.418	30.00	-17.59	2.20	14.61	36.02	-21.41
2480	1.0	iPA	39	12.49	17.742	30.00	-17.51	2.20	14.69	36.02	-21.33
2404	2.0	ePA	1	19.40	87.096	30.00	-10.60	2.20	21.60	36.02	-14.42
2440	2.0	ePA	19	19.03	79.983	30.00	-10.97	2.20	21.23	36.02	-14.79
2478	2.0	ePA	38	19.21	83.368	30.00	-10.79	2.20	21.41	36.02	-14.61
2404	2.0	iPA	1	12.31	17.022	30.00	-17.69	2.20	14.51	36.02	-21.51
2440	2.0	iPA	19	12.27	16.866	30.00	-17.73	2.20	14.47	36.02	-21.55
2478	2.0	iPA	38	12.34	17.140	30.00	-17.66	2.20	14.54	36.02	-21.48

Table 7-4. Peak Conducted Output Power Measurements Antenna WF8 (Bluetooth LE)

Frequency [MHz]	Data Rate [Mbps]	Power Scheme	Channel No.	Peak Conducted Power		Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	EIRP Margin [dB]
				[dBm]	[mW]						
2402	1.0	ePA	0	17.32	53.951	30.00	-12.68	2.60	19.92	36.02	-16.10
2440	1.0	ePA	19	17.11	51.404	30.00	-12.89	2.60	19.71	36.02	-16.31
2480	1.0	ePA	39	17.18	52.240	30.00	-12.82	2.60	19.78	36.02	-16.24
2402	1.0	iPA	0	12.28	16.904	30.00	-17.72	2.60	14.88	36.02	-21.14
2440	1.0	iPA	19	12.53	17.906	30.00	-17.47	2.60	15.13	36.02	-20.89
2480	1.0	iPA	39	12.21	16.634	30.00	-17.79	2.60	14.81	36.02	-21.21
2404	2.0	ePA	1	17.33	54.075	30.00	-12.67	2.60	19.93	36.02	-16.09
2440	2.0	ePA	19	17.30	53.703	30.00	-12.70	2.60	19.90	36.02	-16.12
2478	2.0	ePA	38	17.20	52.481	30.00	-12.80	2.60	19.80	36.02	-16.22
2404	2.0	iPA	1	12.16	16.444	30.00	-17.84	2.60	14.76	36.02	-21.26
2440	2.0	iPA	19	12.21	16.634	30.00	-17.79	2.60	14.81	36.02	-21.21
2478	2.0	iPA	38	12.52	17.865	30.00	-17.48	2.60	15.12	36.02	-20.90

Table 7-5. Peak Conducted Output Power Measurements Antenna WF7 (Bluetooth LE)

FCC ID: BCGA2759 IC: 579C-A2759		element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device		Page 24 of 104

Frequency [MHz]	Data Rate [Mbps]	Power Scheme	Channel No.	Peak Conducted Power						Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Directional Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	EIRP Margin [dB]						
				Antenna WF8		Antenna WF7		Summed													
				[dBm]	[mW]	[dBm]	[mW]	[dBm]	[mW]												
2402	1.0	ePA	0	18.51	70.958	17.82	60.534	21.19	131.522	30.00	-8.81	5.41	26.60	36.02	-9.42						
2440	1.0	ePA	19	18.62	72.778	17.81	60.395	21.24	133.045	30.00	-8.76	5.41	26.65	36.02	-9.37						
2480	1.0	ePA	39	18.56	71.779	17.79	60.117	21.20	131.826	30.00	-8.80	5.41	26.61	36.02	-9.41						
2402	1.0	iPA	0	12.24	16.749	12.78	18.967	15.53	35.727	30.00	-14.47	5.41	20.94	36.02	-15.08						
2440	1.0	iPA	19	12.38	17.298	12.69	18.578	15.55	35.892	30.00	-14.45	5.41	20.96	36.02	-15.06						
2480	1.0	iPA	39	12.36	17.219	12.75	18.836	15.57	36.058	30.00	-14.43	5.41	20.98	36.02	-15.04						
2404	2.0	ePA	1	18.20	66.069	17.72	59.156	20.98	125.314	30.00	-9.02	5.41	26.39	36.02	-9.63						
2440	2.0	ePA	19	18.37	68.707	17.68	58.614	21.05	127.350	30.00	-8.95	5.41	26.46	36.02	-9.56						
2478	2.0	ePA	38	18.32	67.920	17.79	60.117	21.07	127.938	30.00	-8.93	5.41	26.48	36.02	-9.54						
2404	2.0	iPA	1	12.49	17.742	12.60	18.197	15.56	35.975	30.00	-14.44	5.41	20.97	36.02	-15.05						
2440	2.0	iPA	19	12.36	17.219	12.73	18.750	15.56	35.975	30.00	-14.44	5.41	20.97	36.02	-15.05						
2478	2.0	iPA	38	12.31	17.022	12.77	18.923	15.56	35.975	30.00	-14.44	5.41	20.97	36.02	-15.05						

Table 7-6. Peak Conducted Output Power Measurements TxBF (Bluetooth LE)

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 25 of 104

7.3.2 Average Output Power Measurement – Bluetooth (LE)

Frequency [MHz]	Data Rate [Mbps]	Power Scheme	Channel No.	Average Conducted Power		Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	EIRP Margin [dB]	Target [dBm]
				[dBm]	[mW]							
2402	1.0	ePA	0	17.41	55.081	30.00	-12.59	2.20	19.61	36.02	-16.41	17.50
2440	1.0	ePA	19	17.10	51.286	30.00	-12.90	2.20	19.30	36.02	-16.72	17.50
2480	1.0	ePA	39	17.09	51.168	30.00	-12.91	2.20	19.29	36.02	-16.73	17.50
2402	1.0	iPA	0	11.99	15.812	30.00	-18.01	2.20	14.19	36.02	-21.83	12.00
2440	1.0	iPA	19	11.57	14.355	30.00	-18.43	2.20	13.77	36.02	-22.25	12.00
2480	1.0	iPA	39	11.73	14.894	30.00	-18.27	2.20	13.93	36.02	-22.09	12.00
2404	2.0	ePA	1	17.43	55.335	30.00	-12.57	2.20	19.63	36.02	-16.39	17.50
2440	2.0	ePA	19	17.05	50.699	30.00	-12.95	2.20	19.25	36.02	-16.77	17.50
2478	2.0	ePA	38	17.47	55.847	30.00	-12.53	2.20	19.67	36.02	-16.35	17.50
2404	2.0	iPA	1	11.60	14.454	30.00	-18.40	2.20	13.80	36.02	-22.22	12.00
2440	2.0	iPA	19	11.69	14.757	30.00	-18.31	2.20	13.89	36.02	-22.13	12.00
2478	2.0	iPA	38	11.78	15.066	30.00	-18.22	2.20	13.98	36.02	-22.04	12.00

Table 7-7. Average Conducted Output Power Measurements Antenna WF8 (Bluetooth LE)

Frequency [MHz]	Data Rate [Mbps]	Power Scheme	Channel No.	Average Conducted Power		Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	EIRP Margin [dB]	Target [dBm]
				[dBm]	[mW]							
2402	1.0	ePA	0	15.79	37.931	30.00	-14.21	2.60	18.39	36.02	-17.63	16.00
2440	1.0	ePA	19	15.68	36.983	30.00	-14.32	2.60	18.28	36.02	-17.74	16.00
2480	1.0	ePA	39	15.57	36.058	30.00	-14.43	2.60	18.17	36.02	-17.85	16.00
2402	1.0	iPA	0	12.04	15.996	30.00	-17.96	2.60	14.64	36.02	-21.38	12.50
2440	1.0	iPA	19	12.48	17.701	30.00	-17.52	2.60	15.08	36.02	-20.94	12.50
2480	1.0	iPA	39	12.20	16.596	30.00	-17.80	2.60	14.80	36.02	-21.22	12.50
2404	2.0	ePA	1	15.96	39.446	30.00	-14.04	2.60	18.56	36.02	-17.46	16.00
2440	2.0	ePA	19	15.90	38.905	30.00	-14.10	2.60	18.50	36.02	-17.52	16.00
2478	2.0	ePA	38	15.55	35.892	30.00	-14.45	2.60	18.15	36.02	-17.87	16.00
2404	2.0	iPA	1	12.08	16.144	30.00	-17.92	2.60	14.68	36.02	-21.34	12.50
2440	2.0	iPA	19	12.05	16.032	30.00	-17.95	2.60	14.65	36.02	-21.37	12.50
2478	2.0	iPA	38	12.49	17.742	30.00	-17.51	2.60	15.09	36.02	-20.93	12.50

Table 7-8. Average Conducted Output Power Measurements Antenna WF7 (Bluetooth LE)

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 26 of 104

Frequency [MHz]	Data Rate [Mbps]	Power Scheme	Channel No.	Average Conducted Power						Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Directional Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	EIRP Margin [dB]						
				Antenna WF8		Antenna WF7		Summed													
				[dBm]	[mW]	[dBm]	[mW]	[dBm]	[mW]												
2402	1.0	ePA	0	16.56	45.290	15.96	39.446	19.28	84.723	30.00	-10.72	5.41	24.69	36.02	-11.33						
2440	1.0	ePA	19	16.78	47.643	15.65	36.728	19.26	84.333	30.00	-10.74	5.41	24.67	36.02	-11.35						
2480	1.0	ePA	39	16.83	48.195	15.51	35.563	19.23	83.753	30.00	-10.77	5.41	24.64	36.02	-11.38						
2402	1.0	iPA	0	11.77	15.031	12.40	17.378	15.11	32.434	30.00	-14.89	5.41	20.52	36.02	-15.50						
2440	1.0	iPA	19	11.67	14.689	12.15	16.406	14.93	31.117	30.00	-15.07	5.41	20.34	36.02	-15.68						
2480	1.0	iPA	39	11.55	14.289	12.40	17.378	15.01	31.696	30.00	-14.99	5.41	20.42	36.02	-15.60						
2404	2.0	ePA	1	16.66	46.345	15.50	35.481	19.13	81.846	30.00	-10.87	5.41	24.54	36.02	-11.48						
2440	2.0	ePA	19	16.85	48.417	15.98	39.628	19.45	88.105	30.00	-10.55	5.41	24.86	36.02	-11.16						
2478	2.0	ePA	38	16.57	45.394	15.55	35.892	19.10	81.283	30.00	-10.90	5.41	24.51	36.02	-11.51						
2404	2.0	iPA	1	11.83	15.241	12.01	15.885	14.93	31.117	30.00	-15.07	5.41	20.34	36.02	-15.68						
2440	2.0	iPA	19	11.80	15.136	12.21	16.634	15.02	31.769	30.00	-14.98	5.41	20.43	36.02	-15.59						
2478	2.0	iPA	38	11.83	15.241	12.34	17.140	15.10	32.359	30.00	-14.90	5.41	20.51	36.02	-15.51						

Table 7-9. Average Conducted Output Power Measurements TxBF (Bluetooth LE)

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 27 of 104

**Note:**

Per ANSI C63.10-2013 and KDB 662911 D01 v02r01 Section E1), the conducted powers at Antenna WF8 and Antenna WF7 were first measured separately during TxBF transmission as shown in the section above. The measured values were then summed in linear power units then converted back to dBm.

Per ANSI C63.10-2013 Section 14.4.3, the directional gain is calculated using the following formula, where G_N is the gain of the nth antenna and N_{ANT} , the total number of antennas used.

$$\text{Directional gain} = 10 \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / N_{ANT}] \text{ dBi}$$

Sample TxBF Calculation:

At 2402MHz the average conducted output power was measured to be 16.56 dBm for Antenna WF8 and 15.96 dBm for Antenna WF7.

$$\text{Antenna WF8} + \text{Antenna WF7} = \text{TxBF}$$

$$(16.56 \text{ dBm} + 15.96 \text{ dBm}) = (45.290 \text{ mW} + 39.446 \text{ mW}) = 84.723 \text{ mW} = 19.28 \text{ dBm}$$

Sample e.i.r.p. Calculation:

At 2402MHz, the average conducted output power was calculated to be 19.28 dBm with directional gain of 5.41 dBi.

$$\text{e.i.r.p. (dBm)} = \text{Conducted Power (dBm)} + \text{Ant gain (dBi)}$$

$$19.28 \text{ dBm} + 5.41 \text{ dBi} = 24.69 \text{ dBm}$$

FCC ID: BCGA2759 IC: 579C-A2759		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 28 of 104

7.4 Power Spectral Density – Bluetooth (LE)

§15.247(e); RSS-247 [5.2]

Test Overview and Limit

The peak power density is measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power and at the appropriate frequencies.

The maximum permissible power spectral density is 8 dBm in any 3 kHz band.

Test Procedure Used

ANSI C63.10-2013 – Subclause 11.10.2 Method PKPSD

KDB 558074 D01 v05r02 – Section 8.4 DTS Maximum Power Spectral Density level in the fundamental emission

ANSI C63.10-2013 – Subclause 14.3.2.2 Measure-and-Sum Technique

KDB 662911 D01 v02r01 – Section E2) Measure-and-Sum Technique

Test Settings

1. Analyzer was set to the center frequency of the DTS channel under investigation
2. Span = 1.5 times the DTS channel bandwidth
3. RBW = 3kHz
4. VBW = 1MHz
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-3. Test Instrument & Measurement Setup

Test Notes

None

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 29 of 104




Antenna WF8


Frequency [MHz]	Data Rate [Mbps]	Power Scheme	Channel No.	Measured Power Spectral Density [dBm / 3kHz]	Maximum Permissible Power Density [dBm / 3kHz]	Margin [dB]
2402	1.0	ePA	0	2.72	8.0	-5.28
2440	1.0	ePA	19	2.75	8.0	-5.25
2480	1.0	ePA	39	2.40	8.0	-5.61
2402	1.0	iPA	0	2.67	8.0	-5.33
2440	1.0	iPA	19	2.59	8.0	-5.41
2480	1.0	iPA	39	2.22	8.0	-5.78
2404	2.0	ePA	1	1.57	8.0	-6.43
2440	2.0	ePA	19	-2.67	8.0	-10.67
2478	2.0	ePA	38	1.43	8.0	-6.57
2404	2.0	iPA	1	0.85	8.0	-7.15
2440	2.0	iPA	19	-2.65	8.0	-10.65
2478	2.0	iPA	38	0.62	8.0	-7.38

Table 7-10. Conducted Power Density Measurements Antenna WF8

FCC ID: BCGA2759 IC: 579C-A2759		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 30 of 104




Plot 7-13. Power Spectral Density Plot Antenna WF8 (Bluetooth (LE), 1Mbps, ePA – Ch. 0)




Plot 7-14. Power Spectral Density Plot Antenna WF8 (Bluetooth (LE), 1Mbps, ePA – Ch. 19)

FCC ID: BCGA2759 IC: 579C-A2759		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 31 of 104




Plot 7-15. Power Spectral Density Plot Antenna WF8 (Bluetooth (LE), 1Mbps, ePA – Ch. 39)




Plot 7-16. Power Spectral Density Plot Antenna WF8 (Bluetooth (LE), 1Mbps, iPA – Ch. 0)

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 32 of 104



Plot 7-17. Power Spectral Density Plot Antenna WF8 (Bluetooth (LE), 1Mbps, iPA – Ch. 19)




Plot 7-18. Power Spectral Density Plot Antenna WF8 (Bluetooth (LE), 1Mbps, iPA – Ch. 39)

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 33 of 104




Plot 7-19. Power Spectral Density Plot Antenna WF8 (Bluetooth (LE), 2Mbps, ePA – Ch. 1)



Plot 7-20. Power Spectral Density Plot Antenna WF8 (Bluetooth (LE), 2Mbps, ePA – Ch. 19)

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 34 of 104



Plot 7-21. Power Spectral Density Plot Antenna WF8 (Bluetooth (LE), 2Mbps, ePA – Ch. 38)




Plot 7-22. Power Spectral Density Plot Antenna WF8 (Bluetooth (LE), 2Mbps, iPA – Ch. 1)

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 35 of 104



Plot 7-23. Power Spectral Density Plot Antenna WF8 (Bluetooth (LE), 2Mbps, iPA – Ch. 19)



Plot 7-24. Power Spectral Density Plot Antenna WF8 (Bluetooth (LE), 2Mbps, iPA – Ch. 38)

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 36 of 104




Antenna WF7


Frequency [MHz]	Data Rate [Mbps]	Power Scheme	Channel No.	Measured Power Spectral Density [dBm / 3kHz]	Maximum Permissible Power Density [dBm / 3kHz]	Margin [dB]
2402	1.0	ePA	0	3.24	8.0	-4.76
2440	1.0	ePA	19	3.28	8.0	-4.72
2480	1.0	ePA	39	3.09	8.0	-4.91
2402	1.0	iPA	0	3.35	8.0	-4.65
2440	1.0	iPA	19	3.34	8.0	-4.66
2480	1.0	iPA	39	3.04	8.0	-4.96
2404	2.0	ePA	1	1.03	8.0	-6.97
2440	2.0	ePA	19	-2.00	8.0	-10.00
2478	2.0	ePA	38	0.75	8.0	-7.25
2404	2.0	iPA	1	1.34	8.0	-6.66
2440	2.0	iPA	19	-2.00	8.0	-10.00
2478	2.0	iPA	38	0.75	8.0	-7.25

Table 7-11. Conducted Power Density Measurements Antenna WF7

FCC ID: BCGA2759 IC: 579C-A2759		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 37 of 104




Plot 7-25. Power Spectral Density Plot Antenna WF7 (Bluetooth (LE), 1Mbps, ePA – Ch. 0)




Plot 7-26. Power Spectral Density Plot Antenna WF7 (Bluetooth (LE), 1Mbps, ePA – Ch. 19)

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 38 of 104



Plot 7-27. Power Spectral Density Plot Antenna WF7 (Bluetooth (LE), 1Mbps, ePA – Ch. 39)




Plot 7-28. Power Spectral Density Plot Antenna WF7 (Bluetooth (LE), 1Mbps, iPA – Ch. 0)

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 39 of 104




Plot 7-29. Power Spectral Density Plot Antenna WF7 (Bluetooth (LE), 1Mbps, iPA – Ch. 19)




Plot 7-30. Power Spectral Density Plot Antenna WF7 (Bluetooth (LE), 1Mbps, iPA – Ch. 39)

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 40 of 104



Plot 7-31. Power Spectral Density Plot Antenna WF7 (Bluetooth (LE), 2Mbps, ePA – Ch. 1)




Plot 7-32. Power Spectral Density Plot Antenna WF7 (Bluetooth (LE), 2Mbps, ePA – Ch. 19)

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 41 of 104



Plot 7-33. Power Spectral Density Plot Antenna WF7 (Bluetooth (LE), 2Mbps, ePA – Ch. 38)




Plot 7-34. Power Spectral Density Plot Antenna WF7 (Bluetooth (LE), 2Mbps, iPA – Ch. 1)

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 42 of 104



Plot 7-35. Power Spectral Density Plot Antenna WF7 (Bluetooth (LE), 2Mbps, iPA – Ch. 19)



Plot 7-36. Power Spectral Density Plot Antenna WF7 (Bluetooth (LE), 2Mbps, iPA – Ch. 38)


FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 43 of 104

TxBF


Frequency [MHz]	Data Rate [Mbps]	Power Scheme	Channel No.	Measured Power Spectral Density [dBm / 3kHz]			Maximum Permissible Power Density [dBm / 3kHz]	Margin [dB]
				Ant WF8	Ant WF7	Summed		
2402	1.0	ePA	0	2.86	3.04	5.96	8.0	-2.04
2440	1.0	ePA	19	2.83	3.15	6.00	8.0	-2.00
2480	1.0	ePA	39	2.65	2.88	5.78	8.0	-2.22
2402	1.0	iPA	0	2.92	3.02	5.98	8.0	-2.02
2440	1.0	iPA	19	2.89	3.09	6.00	8.0	-2.00
2480	1.0	iPA	39	2.66	2.92	5.80	8.0	-2.20
2404	2.0	ePA	1	1.26	1.94	4.62	8.0	-3.38
2440	2.0	ePA	19	-2.59	-2.20	0.62	8.0	-7.38
2478	2.0	ePA	38	1.03	1.65	4.36	8.0	-3.64
2404	2.0	iPA	1	0.88	1.29	4.10	8.0	-3.90
2440	2.0	iPA	19	-2.44	-2.15	0.72	8.0	-7.28
2478	2.0	iPA	38	0.02	0.89	3.49	8.0	-4.51

Table 7-12. Conducted Power Density Measurements TxBF

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 44 of 104




Plot 7-37. Power Spectral Density Plot Antenna WF8 (Bluetooth (LE), 1Mbps, ePA – Ch. 0)




Plot 7-38. Power Spectral Density Plot Antenna WF7 (Bluetooth (LE), 1Mbps, ePA – Ch. 0)

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 45 of 104




Plot 7-39. Power Spectral Density Plot Antenna WF8 (Bluetooth (LE), 1Mbps, ePA – Ch. 19)




Plot 7-40. Power Spectral Density Plot Antenna WF7 (Bluetooth (LE), 1Mbps, ePA – Ch. 19)

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 46 of 104




Plot 7-41. Power Spectral Density Plot Antenna WF8 (Bluetooth (LE), 1Mbps, ePA – Ch. 39)




Plot 7-42. Power Spectral Density Plot Antenna WF7 (Bluetooth (LE), 1Mbps, ePA – Ch. 39)

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 47 of 104




Plot 7-43. Power Spectral Density Plot Antenna WF8 (Bluetooth (LE), 1Mbps, iPA – Ch. 0)




Plot 7-44. Power Spectral Density Plot Antenna WF7 (Bluetooth (LE), 1Mbps, iPA – Ch. 0)

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 48 of 104




Plot 7-45. Power Spectral Density Plot Antenna WF8 (Bluetooth (LE), 1Mbps, iPA – Ch. 19)




Plot 7-46. Power Spectral Density Plot Antenna WF7 (Bluetooth (LE), 1Mbps, iPA – Ch. 19)

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 49 of 104



Plot 7-47. Power Spectral Density Plot Antenna WF8 (Bluetooth (LE), 1Mbps, iPA – Ch. 39)



Plot 7-48. Power Spectral Density Plot Antenna WF7 (Bluetooth (LE), 1Mbps, iPA – Ch. 39)

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 50 of 104



Plot 7-49. Power Spectral Density Plot Antenna WF8 (Bluetooth (LE), 2Mbps, ePA – Ch. 1)




Plot 7-50. Power Spectral Density Plot Antenna WF7 (Bluetooth (LE), 2Mbps, ePA – Ch. 1)

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 51 of 104



Plot 7-51. Power Spectral Density Plot Antenna WF8 (Bluetooth (LE), 2Mbps, ePA – Ch. 19)




Plot 7-52. Power Spectral Density Plot Antenna WF7 (Bluetooth (LE), 2Mbps, ePA – Ch. 19)

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 52 of 104




Plot 7-53. Power Spectral Density Plot Antenna WF8 (Bluetooth (LE), 2Mbps, ePA – Ch. 38)




Plot 7-54. Power Spectral Density Plot Antenna WF7 (Bluetooth (LE), 2Mbps, ePA – Ch. 38)

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 53 of 104



Plot 7-55. Power Spectral Density Plot Antenna WF8 (Bluetooth (LE), 2Mbps, iPA – Ch. 1)



Plot 7-56. Power Spectral Density Plot Antenna WF7 (Bluetooth (LE), 2Mbps, iPA – Ch. 1)

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 54 of 104



Plot 7-57. Power Spectral Density Plot Antenna WF8 (Bluetooth (LE), 2Mbps, iPA – Ch. 19)




Plot 7-58. Power Spectral Density Plot Antenna WF7 (Bluetooth (LE), 2Mbps, iPA – Ch. 19)

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 55 of 104



Plot 7-59. Power Spectral Density Plot Antenna WF8 (Bluetooth (LE), 2Mbps, iPA – Ch. 38)



Plot 7-60. Power Spectral Density Plot Antenna WF7 (Bluetooth (LE), 2Mbps, iPA – Ch. 38)

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 56 of 104

**Note:**

Per ANSI C63.10-2013 Subclause 14.3.2.2 and KDB 662911 D01 v02r01 Section E(2), the power spectral density at Antenna WF8 and Antenna WF7 were first measured separately as shown in the section above. The measured values were then summed in linear power units then converted back to dBm.

Sample TxBF Calculation:

At 2402MHz the average conducted power spectral density was measured to be 2.86 dBm for Antenna WF8 and 3.04 dBm for Antenna WF7.

$$\text{Antenna WF8} + \text{Antenna WF7} = \text{TxBF}$$

$$(2.86 \text{ dBm} + 3.04 \text{ dBm}) = (1.93 \text{ mW} + 2.01 \text{ mW}) = 3.94 \text{ mW} = 5.96 \text{ dBm}$$

FCC ID: BCGA2759 IC: 579C-A2759	element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 57 of 104

7.5 Conducted Authorized Band Edge

§15.247(d); RSS-247 [5.5]

Test Overview and Limit

For the following out of band conducted spurious emissions plots at the band edge, the EUT was set to transmit at maximum power with the largest packet size available. These settings produced the worst-case emissions.

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth.

Test Procedure Used

ANSI C63.10-2013 – Subclause 11.11.3
KDB 558074 D01 v05r02 – Section 8.7.2

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW = 100kHz
4. VBW = 300kHz
5. Detector = Peak
6. Number of sweep points $\geq 2 \times \text{Span/RBW}$
7. Trace mode = max hold
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-4. Test Instrument & Measurement Setup

Test Notes

All supported modulation, antenna (including TxBF mode) and power schemes have been tested on the unit and only worst case configuration is reported.


FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 58 of 104

Antenna WF8

Plot 7-61. Band Edge Plot Antenna WF8 (Bluetooth (LE), 1Mbps, ePA – Ch. 0)

Plot 7-62. Band Edge Plot Antenna WF8 (Bluetooth (LE), 1Mbps, ePA – Ch. 39)

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 59 of 104





Plot 7-63. Band Edge Plot Antenna WF8 (Bluetooth (LE), 2Mbps, ePA – Ch. 1)



Plot 7-64. Band Edge Plot Antenna WF8 (Bluetooth (LE), 2Mbps, ePA – Ch. 38)

FCC ID: BCGA2759 IC: 579C-A2759		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 60 of 104

Antenna WF7

Plot 7-65. Band Edge Plot Antenna WF7 (Bluetooth (LE), 1Mbps, ePA – Ch. 0)

Plot 7-66. Band Edge Plot Antenna WF7 (Bluetooth (LE), 1Mbps, ePA – Ch. 39)

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 61 of 104



Plot 7-67. Band Edge Plot Antenna WF7 (Bluetooth (LE), 2Mbps, ePA – Ch. 1)



Plot 7-68. Band Edge Plot Antenna WF7 (Bluetooth (LE), 2Mbps, ePA – Ch. 38)

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 62 of 104

7.6 Conducted Spurious Emissions

§15.247(d); RSS-247 [5.5]

Test Overview and Limit

For the following out of band conducted spurious emissions plots, the EUT was set to transmit at maximum power with the largest packet size available. The worst case spurious emissions were found in this configuration.

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the procedure in Section 8.5 of KDB 558074 D01 v05r02 and Section 11.11 of ANSI C63.10-2013.

Test Procedure Used

ANSI C63.10-2013 – Subclause 11.11.3
KDB 558074 D01 v05r02 – Section 8.5

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 25GHz (separated into two plots per channel)
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-5. Test Instrument & Measurement Setup

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 63 of 104

Test Notes

1. RBW was set to 1MHz rather than 100kHz in order to increase the measurement speed.
2. The display line shown in the following plots denotes the limit at 20dB below the fundamental emission level measured in a 100kHz bandwidth. However, since the traces in the following plots are measured with a 1MHz RBW, the display line may not necessarily appear to be 20dB below the level of the fundamental in a 1MHz bandwidth.
3. For plots showing conducted spurious emissions near the limit, the frequencies were investigated with a reduced RBW to ensure that no emissions were present.
4. All supported modulation, antenna (including TxBF mode) and power schemes have been tested on the unit and only worst case configuration is reported.

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 64 of 104

Antenna WF8

Plot 7-69. Conducted Spurious Plot Antenna WF8 (Bluetooth (LE), 1Mbps, ePA – Ch. 0)

Plot 7-70. Conducted Spurious Plot Antenna WF8 (Bluetooth (LE), 1Mbps, ePA – Ch. 0)

FCC ID: BCGA2759 IC: 579C-A2759		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-04.BCG	Test Dates: 07/21/2022-09/23/2022	EUT Type: Tablet Device	Page 65 of 104