




FCC ID: BCGA2759 IC: 579C-A2759	 <b>element</b>		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-12-R2.BCG	Test Dates: 05/27/2022 - 9/26/2022	EUT Type: Tablet Device	Page 155 of 323	




Plot 7-614. In-Band Emission Plot SDM Antenna WF5b (20MHz 802.11ax RU242 (UNII Band 8) – Ch. 209)




Plot 7-617. In-Band Emission Plot SDM Antenna WF5t (40MHz 802.11ax RU26 (UNII Band 8) – Ch. 211)



Plot 7-615. In-Band Emission Plot SDM Antenna WF5t (40MHz 802.11ax RU26 (UNII Band 8) – Ch. 211)



Plot 7-618. In-Band Emission Plot SDM Antenna WF5b (40MHz 802.11ax RU26 (UNII Band 8) – Ch. 211)




Plot 7-616. In-Band Emission Plot SDM Antenna WF5b (40MHz 802.11ax RU26 (UNII Band 8) – Ch. 211)




Plot 7-619. In-Band Emission Plot SDM Antenna WF5t (40MHz 802.11ax RU26 (UNII Band 8) – Ch. 211)


FCC ID: BCGA2759 IC: 579C-A2759	 <b>MEASUREMENT REPORT (CERTIFICATION)</b>			Approved by: Technical Manager
Test Report S/N: 1C2205090024-12-R2.BCG	Test Dates: 05/27/2022 - 9/26/2022	EUT Type: Tablet Device	Page 156 of 323	




Plot 7-620. In-Band Emission Plot SDM Antenna WF5b (40MHz 802.11ax)  
RU26 (UNII Band 8) – Ch. 211




Plot 7-623. In-Band Emission Plot SDM Antenna WF5t (80MHz 802.11ax)  
RU26 (UNII Band 8) – Ch. 199




Plot 7-621. In-Band Emission Plot SDM Antenna WF5t (40MHz 802.11ax)  
RU484 (UNII Band 8) – Ch. 211



Plot 7-624. In-Band Emission Plot SDM Antenna WF5b (80MHz 802.11ax)  
RU26 (UNII Band 8) – Ch. 199









Plot 7-622. In-Band Emission Plot SDM Antenna WF5b (40MHz 802.11ax)  
RU484 (UNII Band 8) – Ch. 211









Plot 7-625. In-Band Emission Plot SDM Antenna WF5t (80MHz 802.11ax)  
RU26 (UNII Band 8) – Ch. 199


FCC ID: BCGA2759 IC: 579C-A2759	 <b>element</b>		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-12-R2.BCG	Test Dates: 05/27/2022 - 9/26/2022	EUT Type: Tablet Device	Page 157 of 323	



FCC ID: BCGA2759 IC: 579C-A2759	 <b>element</b>		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-12-R2.BCG	Test Dates: 05/27/2022 - 9/26/2022	EUT Type: Tablet Device	Page 158 of 323	



FCC ID: BCGA2759 IC: 579C-A2759	 <b>element</b>		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-12-R2.BCG	Test Dates: 05/27/2022 - 9/26/2022	EUT Type: Tablet Device	Page 159 of 323	



Plot 7-638. In-Band Emission Plot SDM Antenna WF5b (160MHz 802.11ax RU484 (UNII Band 8) – Ch. 207)

FCC ID: BCGA2759 IC: 579C-A2759	 <b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Technical Manager
Test Report S/N: 1C2205090024-12-R2.BCG	Test Dates: 05/27/2022 - 9/26/2022	EUT Type: Tablet Device	Page 160 of 323

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Washington DC LLC. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [ct.info@element.com](mailto:ct.info@element.com).

## 7.6 Contention Based Protocol – 802.11ax OFDMA

§15.407(d)(6), RSS-248 [4.8]

### Test Overview and Limit

Indoor access points, subordinate devices and client devices operating in the 5.925-7.125 GHz band (herein referred to as unlicensed devices) are required to use technologies that include a contention-based protocol to avoid co-channel interference with incumbent devices sharing the band. To ensure incumbent co-channel operations are detected in a technology-agnostic manner, unlicensed devices are required to detect co-channel radio frequency energy (energy detect) and avoid simultaneous transmission.

Unlicensed indoor low-power devices must detect co-channel radio frequency power that is at least -62 dBm or lower. Upon detection of energy in the band, unlicensed low power indoor devices must vacate the channel and stay off the channel as long as detected radio frequency power is equal to or greater than the threshold (-62 dBm). The -62 dBm (or lower) threshold is referenced to a 0 dBi antenna gain.

To ensure incumbent operations are reliably detected in the band, low power indoor devices must detect RF energy throughout their intended operating channel.

### Test Procedure Used

ANSI C63.10-2013 – Section 12.3.2.2


KDB 987594 D02 v01r01

### Test Settings

1. Configure the EUT to transmit with a constant duty cycle.
2. Set the operating parameters of the EUT including power level, operating frequency, modulation and bandwidth
3. Set the signal analyzer center frequency to the nominal EUT channel center frequency. The span range of the signal analyzer shall be between two times and five times the OBW of the EUT.
4. Connect the output port of the EUT to the signal analyzer 2, as shown in Figure 2. Ensure that the attenuator 2 provides enough attenuation to not overload the signal analyzer 2 receiver.
5. Monitoring the signal analyzer 2, verify the EUT is operating and transmitting with the parameters set at step two.
6. Using an AWGN signal source, generate (but do not transmit, i.e., RF OFF) a 10 MHz-wide AWGN signal. Use Table 1 to determine the center frequency of the 10 MHz AWGN signal relative to the EUT's channel bandwidth and center frequency.
7. Set the AWGN signal power to an extremely low level (more than 20 dB below the -62 dBm threshold). Connect the AWGN signal source, via a 3-dB splitter, to the signal analyzer 1 and the EUT as shown in Figure 2.
8. Transmit the AWGN signal (RF ON) and verify its characteristics on the signal analyzer 1.
9. Monitor the signal analyzer 2 to verify if the AWGN signal has been detected and the EUT has ceased transmission. If the EUT continues to transmit, then incrementally increase the AWGN signal power level until the EUT stops transmitting.
10. Including all losses in the RF paths) Determine and record the AWGN signal power level (at the EUT's antenna port) at which the EUT ceased transmission. Repeat the procedure at least 10 times to verify the EUT can detect an AWGN signal with 90% (or better) level of certainty.
11. Refer to Table 1 to determine number of times the detection threshold testing needs to be repeated. If testing is required more than once, then go back to step 5, choose a different center frequency for the AWGN signal and repeat the process.

FCC ID: BCGA2759 IC: 579C-A2759	 element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-12-R2.BCG	Test Dates: 05/27/2022 - 9/26/2022	EUT Type: Tablet Device		Page 161 of 323

## Test Setup



**Figure 2. Contention-based protocol test setup, conducted method Step-by-Step Procedure, Conducted Setup**

## Test Notes

1. Per guidance from KDB 987594 D02 v01r01, contention based protocol was tested using an AWGN signal with a bandwidth of 10MHz. The amplitude of the signal was increased until detected by the EUT, signaled by the ceasing of transmission, marker indicates the point at which the AWGN signal is introduced.
2. 15 trials were ran in order to assure that at least 90% of certainty was met.
3. Per Guidance from KDB 987594 D04 v01, contention based protocol was tested with receiver with the lowest antenna gain.

Detection Level = Injected AWGN Power (dBm) – Antenna Gain (dBi) + Path Loss (dB)

### Equation 7-1. Incumbent Detection Level Calculation

FCC ID: BCGA2759 IC: 579C-A2759	 <b>element</b>		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-12-R2.BCG	Test Dates: 05/27/2022 - 9/26/2022	EUT Type: Tablet Device	Page 162 of 323	

Channel	Channel Freqnency [MHz]	Channel BW [MHz]	Incumbent Frequency [MHz]	Injected (AWGN) [dBm]	Antenna Gain [dBi]	Adjusted Power Level [dBm]	Detection Limit [dBm]	Margin [dB]
53	6215	20	6215	-67.35	-1.20	-66.15	-62.0	-4.15
47	6185	160	6110	-65.85	-1.20	-64.65	-62.0	-2.65
			6185	-65.65	-1.20	-64.45	-62.0	-2.45
			6260	-63.65	-0.60	-63.05	-62.0	-1.05
			6455	-67.99	0.60	-68.59	-62.0	-6.59
111	6505	160	6430	-66.49	0.10	-66.59	-62.0	-4.59
			6505	-66.69	0.60	-67.29	-62.0	-5.29
			6580	-65.69	0.40	-66.09	-62.0	-4.09
			6695	-66.88	0.40	-67.28	-62.0	-5.28
143	6665	160	6590	-66.08	0.40	-66.48	-62.0	-4.48
			6665	-65.98	0.40	-66.38	-62.0	-4.38
			6740	-64.08	0.20	-64.28	-62.0	-2.28
197	6935	20	6935	-71.07	-0.90	-70.17	-62.0	-8.17
207	6985	160	6910	-69.57	-0.90	-68.67	-62.0	-6.67
			6985	-69.37	-0.90	-68.47	-62.0	-6.47
			7060	-67.67	-1.20	-66.47	-62.0	-4.47

**Table 7-48. Contention Based Protocol – Incumbent Detection Results**

Band	Channel	Channel Freqnency [MHz]	Channel BW [MHz]	Incumbent Frequency [MHz]	EUT Transmission Status		
					Adjusted AWGN Power (dBm)		
					Normal	Minimal	Ceased
UNII Band 5	53	6215	20	6215	-78.15	-67.65	-66.15
	47	6185	160	6110	-76.65	-66.15	-64.65
				6185	-76.45	-65.95	-64.45
				6260	-75.05	-64.55	-63.05
UNII Band 6	101	6455	20	6455	-80.59	-70.09	-68.59
	111	6505	160	6430	-78.59	-68.09	-66.59
				6505	-79.29	-68.79	-67.29
				6580	-78.09	-67.59	-66.09
UNII Band 7	149	6695	20	6695	-79.28	-68.78	-67.28
	175	6825	160	6750	-78.48	-67.98	-66.48
				6825	-78.38	-67.88	-66.38
				6900	-76.28	-65.78	-64.28
UNII Band 8	197	6935	20	6935	-82.17	-71.67	-70.17
	207	6985	160	6910	-80.67	-70.17	-68.67
				6985	-80.47	-69.97	-68.47
				7060	-78.47	-67.97	-66.47

**Table 7-49. Contention Based Protocol – Detection Results – All Tx Cases**

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-12-R2.BCG	Test Dates: 05/27/2022 - 9/26/2022	EUT Type: Tablet Device	Page 163 of 323

CBP Detection (1 = Detection, Blank = No Detection)																				
Band	Channel	Channel Frequency [MHz]	Channel BW [MHz]	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	Detection Rate [%]	Limit [%]
UNII Band 5	53	6215	20	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	
	47	6185	160	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	
				1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	
				1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	
UNII Band 6	101	6455	20	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	
	111	6505	160	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	
				1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	
UNII Band 7	149	6695	20	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	
	175	6825	160	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	
				1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	
				1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	
UNII Band 8	197	6935	20	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	
	207	6985	160	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	
				1	1	1	1	1	1	1	1	1	1	1	1	1	1	100.0	90	

**Table 7-50. Contention Based Protocol – Incumbent Detection Trial Results**

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-12-R2.BCG	Test Dates: 05/27/2022 - 9/26/2022	EUT Type: Tablet Device	Page 164 of 323


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Washington DC LLC. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [ct.info@element.com](mailto:ct.info@element.com).

V 10.5 12/15/2021

## AWGN Plots




Plot 7-639. AWGN Signal – UNII 5 – 20MHz




Plot 7-640. AWGN Signal – UNII 5 – 160MHz - Low

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-12-R2.BCG	Test Dates: 05/27/2022 - 9/26/2022	EUT Type: Tablet Device	Page 165 of 323




Plot 7-641. AWGN Signal – UNII 5 – 160MHz – Mid




Plot 7-642. AWGN Signal – UNII 5 – 160MHz - High

FCC ID: BCGA2759 IC: 579C-A2759	 <b>MEASUREMENT REPORT (CERTIFICATION)</b>			Approved by: Technical Manager
Test Report S/N: 1C2205090024-12-R2.BCG	Test Dates: 05/27/2022 - 9/26/2022	EUT Type: Tablet Device	Page 166 of 323	




Plot 7-643. AWGN Signal – UNII 6 – 20MHz



Plot 7-644. AWGN Signal – UNII 6 – 160MHz - Low

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-12-R2.BCG	Test Dates: 05/27/2022 - 9/26/2022	EUT Type: Tablet Device	Page 167 of 323




Plot 7-645. AWGN Signal – UNII 6 – 160MHz – Mid




Plot 7-646. AWGN Signal – UNII 6 – 160MHz - High

FCC ID: BCGA2759 IC: 579C-A2759	 <b>MEASUREMENT REPORT (CERTIFICATION)</b>			Approved by: Technical Manager
Test Report S/N: 1C2205090024-12-R2.BCG	Test Dates: 05/27/2022 - 9/26/2022	EUT Type: Tablet Device		Page 168 of 323




Plot 7-647. AWGN Signal – UNII 7 – 20MHz



Plot 7-648. AWGN Signal – UNII 7 – 160MHz - Low

FCC ID: BCGA2759 IC: 579C-A2759	 <b>element</b> <b>MEASUREMENT REPORT (CERTIFICATION)</b>			Approved by: Technical Manager
Test Report S/N: 1C2205090024-12-R2.BCG	Test Dates: 05/27/2022 - 9/26/2022	EUT Type: Tablet Device	Page 169 of 323	




Plot 7-649. AWGN Signal – UNII 7 – 160MHz – Mid




Plot 7-650. AWGN Signal – UNII 7 – 160MHz - High

FCC ID: BCGA2759 IC: 579C-A2759	 <b>element</b> <b>MEASUREMENT REPORT (CERTIFICATION)</b>			Approved by: Technical Manager
Test Report S/N: 1C2205090024-12-R2.BCG	Test Dates: 05/27/2022 - 9/26/2022	EUT Type: Tablet Device	Page 170 of 323	



Plot 7-651. AWGN Signal – UNII 8 – 20MHz




Plot 7-652. AWGN Signal – UNII 8 – 160MHz - Low


FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-12-R2.BCG	Test Dates: 05/27/2022 - 9/26/2022	EUT Type: Tablet Device	Page 171 of 323

V 10.5 12/15/2021

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Washington DC LLC. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [ct.info@element.com](mailto:ct.info@element.com).




Plot 7-653. AWGN Signal – UNII 8 – 160MHz – Mid




Plot 7-654. AWGN Signal – UNII 8 – 160MHz - High

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2205090024-12-R2.BCG	Test Dates: 05/27/2022 - 9/26/2022	EUT Type: Tablet Device	Page 172 of 323	


**Contention-Based Protocol Timing Plots**

**Plot 7-655. Contention Based Protocol Timing Plot – UNII 5 – 20MHz Channel 53**

**Plot 7-656. Contention Based Protocol Timing Plot – UNII 5 – 160MHz Channel 47 – Low**

FCC ID: BCGA2759 IC: 579C-A2759	 <b>element</b>		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-12-R2.BCG	Test Dates: 05/27/2022 - 9/26/2022	EUT Type: Tablet Device	Page 173 of 323	




Plot 7-657. Contention Based Protocol Timing Plot – UNII 5 – 160MHz Channel 47 – Mid




Plot 7-658. Contention Based Protocol Timing Plot – UNII 5 – 160MHz Channel 47 – High

FCC ID: BCGA2759 IC: 579C-A2759	 element <p>MEASUREMENT REPORT (CERTIFICATION)</p>			Approved by: Technical Manager
Test Report S/N: 1C2205090024-12-R2.BCG	Test Dates: 05/27/2022 - 9/26/2022	EUT Type: Tablet Device		Page 174 of 323



Plot 7-659. Contention Based Protocol Timing Plot – UNII 6 – 20MHz Channel 101




Plot 7-660. Contention Based Protocol Timing Plot – UNII 6 – 160MHz Channel 111 – Low

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-12-R2.BCG	Test Dates: 05/27/2022 - 9/26/2022	EUT Type: Tablet Device	Page 175 of 323




Plot 7-661. Contention Based Protocol Timing Plot – UNII 6 – 160MHz Channel 111 – Mid




Plot 7-662. Contention Based Protocol Timing Plot – UNII 6 – 160MHz Channel 111 – High

FCC ID: BCGA2759 IC: 579C-A2759	 <b>element</b>		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-12-R2.BCG	Test Dates: 05/27/2022 - 9/26/2022	EUT Type: Tablet Device	Page 176 of 323	




Plot 7-663. Contention Based Protocol Timing Plot – UNII 7 – 20MHz Channel 149



Plot 7-664. Contention Based Protocol Timing Plot – UNII 7 – 160MHz Channel 143 – Low

FCC ID: BCGA2759 IC: 579C-A2759	 <b>element</b> <b>MEASUREMENT REPORT (CERTIFICATION)</b>			Approved by: Technical Manager
Test Report S/N: 1C2205090024-12-R2.BCG	Test Dates: 05/27/2022 - 9/26/2022	EUT Type: Tablet Device	Page 177 of 323	



Plot 7-665. Contention Based Protocol Timing Plot – UNII 7 – 160MHz Channel 143 – Mid




Plot 7-666. Contention Based Protocol Timing Plot – UNII 7 – 160MHz Channel 143 – High

FCC ID: BCGA2759 IC: 579C-A2759	 element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-12-R2.BCG	Test Dates: 05/27/2022 - 9/26/2022	EUT Type: Tablet Device		Page 178 of 323




Plot 7-667. Contention Based Protocol Timing Plot – UNII 8 – 20MHz Channel 197




Plot 7-668. Contention Based Protocol Timing Plot – UNII 8 – 160MHz Channel 207 – Low

FCC ID: BCGA2759 IC: 579C-A2759	 <b>element</b>		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-12-R2.BCG	Test Dates: 05/27/2022 - 9/26/2022	EUT Type: Tablet Device	Page 179 of 323	



Plot 7-669. Contention Based Protocol Timing Plot – UNII 8 – 160MHz Channel 207 – Mid



Plot 7-670. Contention Based Protocol Timing Plot – UNII 8 – 160MHz Channel 207 – High

FCC ID: BCGA2759 IC: 579C-A2759	 <b>element</b>		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-12-R2.BCG	Test Dates: 05/27/2022 - 9/26/2022	EUT Type: Tablet Device	Page 180 of 323	

## 7.7 Radiated Spurious Emissions – Above 1GHz

§15.407(b) §15.205 §15.209; RSS-Gen [8.9]

### Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10-2013 and KDB 789033 D02 v02r01, and at the appropriate frequencies. All channels, modes (e.g. 802.11a, 802.11n, 802.11ax(SU) (20MHz BW), 802.11n, 802.11ax(SU) (40MHz BW), and 802.11ac, 802.11ax(SU) (80MHz), and modulations/data rates were investigated among all UNII bands. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

**For transmitters operating in the 5.925-7.125 GHz band: All emissions outside of the 5.925-7.125 GHz band shall not exceed an EIRP of -27 dBm/MHz. Emissions found in a restricted band are subject to the limits of 15.209 as shown in the table below.**

Frequency	Field Strength [ $\mu$ V/m]	Measured Distance [Meters]
Above 960.0 MHz	500	3

Table 7-51. Radiated Limits

### Test Procedures Used

ANSI C63.10-2013 – Sections 12.7.7.2, 12.7.6, 12.7.5  
KDB 789033 D02 v02r01 – Section G

### Test Settings

#### Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be  $\geq 2 \times$  span/RBW)
6. Averaging type = power (RMS)
7. Sweep time = auto couple
8. Trace was averaged over 100 sweeps


#### Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: BCGA2759 IC: 579C-A2759	element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-12-R2.BCG	Test Dates: 05/27/2022 - 9/26/2022	EUT Type: Tablet Device	Page 181 of 323	

## Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-5. Test Instrument & Measurement Setup**

FCC ID: BCGA2759 IC: 579C-A2759	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-12-R2.BCG	Test Dates: 05/27/2022 - 9/26/2022	EUT Type: Tablet Device	Page 182 of 323

## Test Notes

1. All emissions that lie in the restricted bands (denoted by a \* next to the frequency) specified in §15.205 and Section 8.10 of RSS-Gen are below the limit shown in Table 7-51.
2. All spurious emissions lying in restricted bands specified in §15.205 and Section 8.10 of RSS-Gen are below the limit shown in Table 7-51. All spurious emissions that do not lie in a restricted band are subject to a peak limit of -27dBm/MHz. At a distance of 3 meters, the field strength limit in dB $\mu$ V/m can be determined by adding a “conversion” factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions of 68.2dB $\mu$ V/m.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery.
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas.
6. D is the measurement test distance and emissions 1-18GHz were measured at a 3 meters test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
7. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section.
8. All data rates were investigated and only the worse case is reported
9. The unit was tested with all possible modes and only the highest emission is reported.
10. The “-” shown in the following RSE tables are used to denote a noise floor measurement.

## Sample Calculations

### Determining Spurious Emissions Levels

- Field Strength Level [dB $\mu$ V/m] = Analyzer Level [dBm] + 107 + AFCL [dB/m]
- AFCL [dB/m] = Antenna Factor [dB/m] + Cable Loss [dB] – Preamplifier Gain [dB]
- Margin [dB] = Field Strength Level [dB $\mu$ V/m] – Limit [dB $\mu$ V/m]


### Radiated Band Edge Measurement Offset

- The amplitude offset shown in the radiated restricted band edge plots in Section 7.7.4, 7.7.5, 7.7.6, 7.7.7, 7.7.8, 7.7.9, 7.7.10, 7.7.11, 7.7.12, 7.7.13, 7.7.14, 7.7.15 was calculated using the formula:  
Offset (dB) = (Antenna Factor + Cable Loss + Attenuator) – Preamplifier Gain

FCC ID: BCGA2759 IC: 579C-A2759	 <b>element</b>		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-12-R2.BCG	Test Dates: 05/27/2022 - 9/26/2022	EUT Type: Tablet Device		Page 183 of 323

### 7.7.1 Antenna WF5t Primary Radiated Spurious Emission

**RU26**




**Plot 7-671. Radiated Spurious Emissions above 1GHz Antenna WF5t (802.11ax – Ch. 1 – RU26)**

Mode:	802.11ax
Data Rate:	MCS11
Distance of Measurements:	3 Meters
Operating Frequency:	5955MHz
Channel:	1

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]
* 11910.00	Peak	V	-	-	-71.67	14.14	49.47	73.98	-24.51
* 11910.00	Average	V	-	-	-83.12	14.14	38.02	53.98	-15.96
* 17865.00	Peak	V	-	-	-75.28	24.21	55.93	73.98	-18.05
* 17865.00	Average	V	-	-	-86.62	24.21	44.59	53.98	-9.39

**Table 7-52. Radiated Spurious Emission Measurements Antenna WF5t – RU26**

FCC ID: BCGA2759 IC: 579C-A2759	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Technical Manager
Test Report S/N: 1C2205090024-12-R2.BCG	Test Dates: 05/27/2022 - 9/26/2022	EUT Type: Tablet Device	Page 184 of 323	



**Plot 7-672. Radiated Spurious Emissions above 1GHz Antenna WF5t (802.11ax – Ch. 45 – RU26)**

Mode: 802.11ax  
 Data Rate: MCS11  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 6175MHz  
 Channel: 45


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 12350.00	Peak	V	-	-	-72.66	14.67	49.01	73.98	-24.97
* 12350.00	Average	V	-	-	-84.39	14.67	37.28	53.98	-16.70

**Table 7-53. Radiated Spurious Emission Measurements Antenna WF5t – RU26**

FCC ID: BCGA2759 IC: 579C-A2759	element			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090024-12-R2.BCG	Test Dates: 05/27/2022 - 9/26/2022	EUT Type: Tablet Device			

V 10.5 12/15/2021

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Washington DC LLC. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact [ct.info@element.com](mailto:ct.info@element.com).




Plot 7-673. Radiated Spurious Emissions above 1GHz Antenna WF5t (802.11ax – Ch. 93 – RU26)

Mode: 802.11ax  
 Data Rate: MCS11  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 6415MHz  
 Channel: 93

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]
12830.00	Average	V	-	-	-84.75	15.67	37.92	68.20	-30.28

Table 7-54. Radiated Spurious Emission Measurements Antenna WF5t – RU26

FCC ID: BCGA2759 IC: 579C-A2759	 <b>MEASUREMENT REPORT (CERTIFICATION)</b>			Approved by: Technical Manager
Test Report S/N: 1C2205090024-12-R2.BCG	Test Dates: 05/27/2022 - 9/26/2022	EUT Type: Tablet Device	Page 186 of 323	




**Plot 7-674. Radiated Spurious Emissions above 1GHz Antenna WF5t (802.11ax – Ch. 97 – RU26)**

Mode: 802.11ax  
 Data Rate: MCS11  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 6435MHz  
 Channel: 97

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]
12870.00	Average	V	293	106	-80.16	19.59	46.43	68.20	-21.77

**Table 7-55. Radiated Spurious Emission Measurements Antenna WF5t – RU26**

FCC ID: BCGA2759 IC: 579C-A2759	 <b>MEASUREMENT REPORT (CERTIFICATION)</b>			Approved by: Technical Manager
Test Report S/N: 1C2205090024-12-R2.BCG	Test Dates: 05/27/2022 - 9/26/2022	EUT Type: Tablet Device	Page 187 of 323	



Plot 7-675. Radiated Spurious Emissions above 1GHz Antenna WF5t (802.11ax – Ch. 105 – RU26)

Mode: 802.11ax  
 Data Rate: MCS11  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 6475MHz  
 Channel: 105

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]
12950.00	Average	V	288	92	-75.90	19.17	50.27	68.20	-17.93

Table 7-56. Radiated Spurious Emission Measurements Antenna WF5t – RU26

FCC ID: BCGA2759 IC: 579C-A2759	 <b>MEASUREMENT REPORT (CERTIFICATION)</b>			Approved by: Technical Manager
Test Report S/N: 1C2205090024-12-R2.BCG	Test Dates: 05/27/2022 - 9/26/2022	EUT Type: Tablet Device	Page 188 of 323	