

**MEASUREMENT REPORT
FCC PART 15.225****Applicant Name:**

Apple Inc.
One Apple Park Way
Cupertino, CA 95014
United States

Date of Testing:

12/11/2023 - 3/12/2024

Test Report Issue Date:

3/28/2024

Test Site/Location:

Element Materials Technology, Morgan Hill, CA, USA

Test Report Serial No.:

1C2311270068-26-R1.BCG

FCC ID:	BCGA2837
APPLICANT:	Apple Inc.

Application Type:

Certification

Model/HVIN:

A2837, A3006

EUT Type:

Tablet Device

Frequency:

13.56MHz

FCC Classification:

Low Power Communications Device Transmitter (DXX)

FCC Rule Part(s):

Part 15 Subpart C (15.225)

Test Procedure(s):

ANSI C63.10-2020

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2020. Test results reported herein relate only to the item(s) tested.

This revised Test Report (S/N: 1C2311270068-26-R1.BCG) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



RJ Ortiz

Executive Vice President

Prepared by: WKR0000010551

Reviewed by: WKR0000005833



FCC ID: BCGA2837	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270068-26-R1.BCG	Test Dates: 12/11/2023 - 3/12/2024	EUT Type: Tablet Device	Page 1 of 29

V 10.5 12/15/2021

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

T A B L E O F C O N T E N T S

1.0	INTRODUCTION.....	3
1.1	Scope.....	3
1.2	Element Materials Technology Test Location	3
1.3	Test Facility / Accreditations	3
2.0	PRODUCT INFORMATION	4
2.1	Equipment Description.....	4
2.2	Device Capabilities	4
2.3	Test Support Equipment	4
2.4	Test Configuration	5
2.5	Software and Firmware.....	5
2.6	EMI Suppression Device(s)/Modifications.....	5
3.0	DESCRIPTION OF TEST	6
3.1	Evaluation Procedure.....	6
3.2	AC Line Conducted Emissions	6
3.3	Radiated Emissions	7
3.4	Environmental Conditions	7
4.0	ANTENNA REQUIREMENTS	8
5.0	MEASUREMENT UNCERTAINTY	9
6.0	TEST EQUIPMENT CALIBRATION DATA.....	10
7.0	TEST DATA	11
7.1	Summary	11
7.2	Bandwidth Measurement	12
7.3	Frequency Stability Test Data.....	15
7.4	In-Band Radiated Spurious Emission Measurements.....	17
7.5	Radiated Spurious Emission Measurements, Out-of-Band.....	20
7.6	AC Line Conducted Emissions Measurement.....	25
8.0	CONCLUSION	29

FCC ID: BCGA2837	 element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270068-26-R1.BCG	Test Dates: 12/11/2023 - 3/12/2024	EUT Type: Tablet Device	Page 2 of 29	

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 Element Materials Technology Test Location

These measurement tests were conducted at the Element Materials Technology facility located at 18855 Adams Court, Morgan Hill, CA 95037. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014 and KDB 414788 D01 v01r01.

1.3 Test Facility / Accreditations

Measurements were performed at Element Materials Technology.

- Element Materials Technology is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.02 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Washington DC LLC TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- Element Materials Technology facility is a registered (22831) test laboratory with the site description on file with ISED.
- Element Washington DC LLC is a Recognized U.S. Certification Assessment Body (CAB # US0110) for ISED Canada as designated by NIST under the U.S. and Canada Mutual Recognition Agreements (MRAs).

FCC ID: BCGA2837	 element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270068-26-R1.BCG	Test Dates: 12/11/2023 - 3/12/2024	EUT Type: Tablet Device	Page 3 of 29	

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Apple Tablet Device FCC ID: BCGA2837**. The test data contained in this report pertains only to the emissions due to the wireless power transfer function of the EUT.

Test Device Serial No.: CC6NGF04T0, KQ4V9YG4FQ

2.2 Device Capabilities

This device contains the following capabilities:

850/1700/1900 WCDMA/HSPA, Multi-band LTE, 5G NR (FR1), 802.11b/g/n/ax WLAN, 802.11a/n/ac/ax UNII, Bluetooth (1x, EDR, LE1M, LE2M, HDR4, HDR8) 802.11a/ax WIFI 6E, NB UNII (1x, HDR4, HDR8), 802.15.4, WPT

This device supports BT Beamforming.

This device supports different WPT charging rates.

Charging Rate
1.7C
2.6C

Table 2-1. WPT Charging Rate

2.3 Test Support Equipment

Test Support Equipment List			
1	Apple Macbook Pro w/AC/DC Adapter	Model: A2141 Model: A2166	S/N: C02DV7VGMD6T S/N: C4H22720425PM0WA1
2	USB-C Cable w/AC Adapter	Model: A246C Model: A2935	S/N: FTL806400FP26GV1J S/N: C4H30130NFG24XF43
3	Apple Pencil Battery Apple Pencil Resistive	Model: A2538 Model: A2538	S/N: K2QGKWJ4NC S/N: KJ7P9LT7RT
4	DC Power Supply	Model: KPS3010D	S/N: N/A

Table 2-2. Test Support Equipment List

FCC ID: BCGA2837	 element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270068-26-R1.BCG	Test Dates: 12/11/2023 - 3/12/2024	EUT Type: Tablet Device	Page 4 of 29	



2.4 Test Configuration

The EUT Tablet Device **FCC ID: BCGA2837**, contains a proprietary wireless power transfer (WPT) module, which uses a magnetic inductive charging system. This feature allows for the Apple Pencil to be wirelessly charged using the tablet device.

All equipment is placed on the test tabletop and arranged in a typical configuration in accordance with ANSI C63.10-2020. For more information, refer to Section 6.0 for test data and the test setup.

All Apple pencils with different configurations were investigated and only the worst-case pencil (Resistive load) was reported in this test report.

All charging rates were investigated and only the worst-case charging rate (2.6C) was reported in this test report.

The EUT was manipulated through three orthogonal planes of X-orientation (flatbed), Y-orientation (landscape), and Z-orientation (portrait) during the testing. Only the worst-case emissions were reported in this test report.

For AC line conducted and radiated emissions test, with the Apple Pencil wirelessly charging while attached to Tablet Device, following configuration were investigated and worst case was reported.

- Tablet Device powered by AC/DC adapter via USB-C cable with wire charger.
- Tablet Device powered by host PC via USB-C cable with wire charger.

2.5 Software and Firmware

The test was conducted with firmware version 21E21331f on the EUT.

2.6 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: BCGA2837	element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270068-26-R1.BCG	Test Dates: 12/11/2023 - 3/12/2024	EUT Type: Tablet Device		Page 5 of 29

3.0 DESCRIPTION OF TEST

3.1 Evaluation Procedure

The measurement procedure described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2020) was used in the measurement of the EUT.

Deviation from measurement procedure.....**None**

3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 7m x 3.66m x 2.7m shielded enclosure. The shielded enclosure is manufactured by AP Americas. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-6. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50µH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is EPCOS 2X60A Power Line Filter (100dB Attenuation, 14kHz-18GHz) and the two EPCOs 2X48A filters (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 7.6. Automated test software was used to perform the AC line conducted emissions testing. Automated measurement software utilized is Rohde & Schwarz EMC32, Version 10.50.40.

FCC ID: BCGA2837	 element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270068-26-R1.BCG	Test Dates: 12/11/2023 - 3/12/2024	EUT Type: Tablet Device		Page 6 of 29

3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. An 80cm tall test table made of Styrodur is placed on top of the turn table.

Per KDB 414788, radiated emission test sites other than open-field test sites (e.g., shielded anechoic chambers), may be employed for emission measurements below 30MHz if characterized so that the measurements correspond to those obtained at an open-field test site. To determine test site equivalency, a reference sample transmitting at 149kHz was measured on an open field test site (asphalt with no ground plane) and then measured in the 3m semi-anechoic chamber. A calibrated 60cm loop antenna was rotated about its vertical axis while the reference device was rotated through the X, Y and Z axis in order to capture the worst case level. A maximum deviation of 2.77dB at 149kHz was measured when comparing the 3 meter semi-anechoic chamber to the open field site.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33 depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: BCGA2837	 element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270068-26-R1.BCG	Test Dates: 12/11/2023 - 3/12/2024	EUT Type: Tablet Device		Page 7 of 29

4.0 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

- The antenna of the EUT are **permanently attached**.
- This unit was tested with its standard battery.

Conclusion:

The EUT complies with the requirement of §15.203.

FCC ID: BCGA2837	 element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270068-26-R1.BCG	Test Dates: 12/11/2023 - 3/12/2024	EUT Type: Tablet Device	Page 8 of 29	

5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.23-2012. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (\pm dB)
AC Line Conducted Disturbance	1.91
Radiated Disturbance (<30MHz)	4.12
Radiated Disturbance (30MHz-1GHz)	4.85

FCC ID: BCGA2837	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270068-26-R1.BCG	Test Dates: 12/11/2023 - 3/12/2024	EUT Type: Tablet Device	Page 9 of 29

6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
ESPEC	SU-241	Tabletop Temperature Chamber	11/17/2023	Annual	11/17/2024	92009574
Keysight Technologies	N9040B	UXA Spectrum Analyzer	7/10/2023	Annual	7/10/2024	US57212289
Rohde & Schwarz	ENV216	Two-Line V-Network	6/20/2023	Annual	6/20/2024	101363
Rohde & Schwarz	ESW44	EMI Test Receiver	6/6/2023	Annual	6/6/2024	101668
Rohde & Schwarz	HFH2-Z2	Loop Antenna	5/1/2023	Annual	5/1/2024	100519
Rohde & Schwarz	TS-PR8	Pre-Amplifier - Antenna System (30MHz-8GHz)	8/25/2023	Annual	8/25/2024	102333
Schwarzbeck	VULB 9162	Bilog Antenna (30MHz-6GHz)	9/14/2023	Annual	9/14/2024	00358

Table 6-1. Test Equipment List

Note:

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

FCC ID: BCGA2837	 element MEASUREMENT REPORT (CERTIFICATION)			Approved by: Technical Manager
Test Report S/N: 1C2311270068-26-R1.BCG	Test Dates: 12/11/2023 - 3/12/2024	EUT Type: Tablet Device	Page 10 of 29	

7.0 TEST DATA

7.1 Summary

Company Name: Apple Inc.

FCC ID: BCGA2837

FCC Classification: Low Power Communications Device Transmitter (DXX)

Frequencies Examined: 13.56MHz

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
2.1049	Bandwidth Measurement	N/A		PASS	Section 7.2
15.225 (a)(b)(c)	In-Band Emissions	15.848 μ V/m @ 30m 13.553 – 13.567 MHz 334 μ V/m @ 30m 13.410 – 13.553 MHz 13.567 – 13.710 MHz 106 μ V/m @ 30m 13.110 – 13.410 MHz 13.710 – 14.010 MHz	RADIATED	PASS	Section 7.4
15.225 (d) 15.209	Out-of-Band Emissions	Emissions outside of the specified band (13.110 – 14.010 MHz) must meet the radiated limits detailed in 15.209		PASS	Section 7.5
15.225 (e)	Frequency Stability Tolerance	\pm 0.01% of Operating Frequency	Temperature Chamber	PASS	Section 7.3
15.207	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 limits	LINE CONDUCTED	PASS	Section 7.6

Table 7-1. Summary of Test Results

Note:

1. This unit was tested with both its standard battery and dummy battery.
2. All charging rates were investigated. The test results shown in the following sections represent the worst-case emissions.
3. The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.

FCC ID: BCGA2837	 element MEASUREMENT REPORT (CERTIFICATION)			Approved by: Technical Manager
Test Report S/N: 1C2311270068-26-R1.BCG	Test Dates: 12/11/2023 - 3/12/2024	EUT Type: Tablet Device	Page 11 of 29	

7.2 Bandwidth Measurement

§2.1049

Test Overview and Limit

The bandwidth at 20dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the receive antenna while the EUT is operating in transmission mode at the appropriate frequency. The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. The signal analyzers' automatic bandwidth measurement capability of the spectrum analyzer was used to perform the 20dB bandwidth measurement. The "X" dB bandwidth parameter was set to X = 20. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% OBW
3. VBW \geq 3 x RBW
4. Reference level set to keep signal from exceeding maximum input mixer level for linear operation.
5. Detector = Peak
6. Trace mode = max hold
7. Sweep = auto couple
8. The trace was allowed to stabilize
9. Using the 99% power bandwidth function of the instrument and report the measured bandwidth.

FCC ID: BCGA2837	 element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270068-26-R1.BCG	Test Dates: 12/11/2023 - 3/12/2024	EUT Type: Tablet Device		Page 12 of 29

Test Setup




Figure 7-1. Test Instrument & Measurement Setup

Test Notes

None.

FCC ID: BCGA2837	 element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270068-26-R1.BCG	Test Dates: 12/11/2023 - 3/12/2024	EUT Type: Tablet Device	Page 13 of 29	

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.




Figure 7-2. 20dB and 99% Bandwidth WPT Plot (Charging Rate 2.6C)




Figure 7-3. 20dB and 99% Bandwidth Communication Mode Plot

FCC ID: BCGA2837	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270068-26-R1.BCG	Test Dates: 12/11/2023 - 3/12/2024	EUT Type: Tablet Device	Page 14 of 29

7.3 Frequency Stability Test Data

§15.225

Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.10-2020. The frequency stability of the transmitter is measured by:

- Temperature:** The temperature is varied from -20°C to +50°C in 10°C increments using an environmental chamber.
- Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

For Part 15.225, the frequency stability of the transmitter shall be maintained within $\pm 0.01\%$ of the center frequency.

Test Procedure Used

ANSI C63.10-2020 – Section 6.8

Test Settings

- The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
- The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
- Frequency measurements are made at 10°C intervals ranging from -20°C to +50°C. Measurements were taken at startup, at 2 minutes, 5 minutes, and 10 minutes after the EUT is energized at each temperature level.

Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.




Figure 7-4. Test Instrument & Measurement Setup

Test Notes

All possible configurations were investigated and only the worst case is reported.

FCC ID: BCGA2837	 element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270068-26-R1.BCG	Test Dates: 12/11/2023 - 3/12/2024	EUT Type: Tablet Device		Page 15 of 29

Frequency Stability Test Data

§15.225

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	- 20	13,559,770	-230.0	-0.0016962
100 %		- 10	13,559,805	-195.5	-0.0014417
100 %		0	13,559,835	-165.0	-0.0012168
100 %		+ 10	13,559,879	-121.5	-0.0008960
100 %		+ 20	13,559,974	-26.0	-0.0001917
100 %		+ 30	13,560,022	21.5	0.0001586
100 %		+ 40	13,560,049	48.5	0.0003577
100 %		+ 50	13,560,068	67.5	0.0004978
85 %	3.40	+ 20	13,559,722	-278.0	-0.0020501
115 %	4.37	+ 20	13,559,807	-193.0	-0.0014233

Table 7-2. Frequency Stability Test Data (Charging Rate 2.6C)




Figure 7-5. Frequency Stability Plot (Charging Rate 2.6C)

FCC ID: BCGA2837	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270068-26-R1.BCG	Test Dates: 12/11/2023 - 3/12/2024	EUT Type: Tablet Device	Page 16 of 29

7.4 In-Band Radiated Spurious Emission Measurements

§15.225(a)(b)(c)

Test Overview and Limit

The EUT was tested from 13.110 – 14.010 MHz. All in-band radiated spurious emissions are measured with a spectrum analyzer connected to a loop antenna while the EUT is operating at appropriate frequencies. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All in-band emissions appearing in a restricted band as specified in Section 15.225 of the Title 47 CFR must not exceed the limits shown in Table 7-3.

Frequency [MHz]	Field Strength [μ V/m]	Measured Distance [Meters]
13.553-13.567 MHz	15,848	30
13.410-13.553 MHz and 13.567-13.710 MHz	334	30
13.110-13.410 MHz and 13.710-14.010 MHz	106	30

Table 7-3. Radiated Limits

Test Procedures Used

ANSI C63.10-2020 – Section 6.4.7

Test Settings

1. RBW = 9kHz
2. VBW \geq 3 x RBW
3. Detector = peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: BCGA2837	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270068-26-R1.BCG	Test Dates: 12/11/2023 - 3/12/2024	EUT Type: Tablet Device	Page 17 of 29

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-6. Radiated Test Setup

Test Notes:

1. All emissions lying in restricted bands specified in §15.225 are below the limit shown in Table 7-3.
2. All measurements were performed using a loop antenna. The antenna was positioned in three orthogonal positions (X front, Y side, Z top) and the position with the highest emission level was recorded.
3. The EUT was positioned in three orthogonal planes to determine the orientation resulting in the worst case emissions.
4. Measurements were performed at 3m and the data was extrapolated to the specified measurement distance of 30m using the square of an inverse linear distance extrapolation factor (40 dB/decade) as specified in §15.31(f)(2). Extrapolation Factor = $20 \log_{10}(30/3)^2 = 40\text{dB}$.
5. The spectrum was investigated from 13.110MHz – 14.010MHz using the loop antenna. Only the emissions shown in the table below were found to be significant.
6. All measurements were recorded using a spectrum analyzer employing a peak detector.
7. The "-" shown in the following RSE tables are used to denote a noise floor measurement.
8. All possible configurations were investigated and only the worst case is reported.


Sample Calculation

- Field Strength Level $[\text{dB}_{\mu\text{V/m}}]$ = Analyzer Level $[\text{dBm}] + 107 + \text{AFCL} \text{ [dB/m]} + \text{Distance Extrapolation Factor} \text{ [dB]}$
- $\text{AFCL} \text{ [dB/m]} = (\text{Antenna Factor} \text{ [dB/m]} + \text{Cable Loss} \text{ [dB]} + \text{Attenuator} \text{ [dB]} - \text{Preamplifier Gain} \text{ [dB]})$
- $\text{Limit} \text{ [dB}_{\mu\text{V/m}}] = 20 * \text{Log} \text{ (Limit} \text{ [\mu\text{V/m}])}$
- Margin $[\text{dB}] = \text{Field Strength Level} \text{ [dB}_{\mu\text{V/m}}] - \text{Limit} \text{ [dB}_{\mu\text{V/m}}]$

FCC ID: BCGA2837	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270068-26-R1.BCG	Test Dates: 12/11/2023 - 3/12/2024	EUT Type: Tablet Device	Page 18 of 29

In-Band Radiated Spurious Emission Measurements

§15.225(a)(b)(c)



Plot 7-1. In Band Radiated Spurious Emissions (Charging Rate 2.6C, with AC/DC Adapter)

Frequency [MHz]	Detector	Ant. Pol. [X/Y/Z]	Antenna Height [cm]	Turntable Azimuth [degree]	Level [dBm]	AFCL [dB/m]	Field Strength @3m [dBμV/m]	Field Strength @30m [dBμV/m]	Limit @30m [dBμV/m]	Margin [dB]
13.167	Max Peak	X	100	1	-98.06	20.54	29.48	-10.52	40.51	-51.03
13.259	Max Peak	Y	100	338	-96.96	20.55	30.59	-9.41	40.51	-49.92
13.424	Max Peak	Y	100	258	-98.30	20.58	29.28	-10.72	50.47	-61.19
13.560	Max Peak	X	100	216	-72.02	20.60	55.58	15.58	84.00	-68.42
13.693	Max Peak	X	100	167	-98.12	20.62	29.50	-10.50	50.47	-60.97
13.755	Max Peak	X	100	139	-98.43	20.63	29.20	-10.80	40.51	-51.31
13.961	Max Peak	Y	100	355	-98.74	20.66	28.92	-11.08	40.51	-51.59

Table 7-4. In-Band Radiated Measurements (Charging Rate 2.6C, with AC/DC Adapter)

FCC ID: BCGA2837	 element	MEASUREMENT REPORT (CERTIFICATION)				Approved by: Technical Manager
Test Report S/N: 1C2311270068-26-R1.BCG	Test Dates: 12/11/2023 - 3/12/2024	EUT Type: Tablet Device				

V 10.5 12/15/2021

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Page 19 of 29

7.5 Radiated Spurious Emission Measurements, Out-of-Band

§15.209 §15.225(d)

Test Overview and Limit

The EUT was tested from 9kHz up to the 1GHz excluding the band 13.110 – 14.010 MHz. All measurements up to 960MHz were recorded with a spectrum analyzer employing a peak detector.

All out-of-band emissions appearing in a restricted band as specified in Section 15.225 of the Title 47 CFR must not exceed the limits shown in Table 7-5 per Section 15.209.

Frequency	Field Strength [μ V/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-5. Radiated Limits – Out of band

Test Procedures Used

ANSI C63.10-2020 – Section 6.5.4

Test Settings

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 9kHz for emissions below 30MHz and 100kHz for emissions between 30MHz and 1GHz
3. VBW \geq 3 x RBW
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: BCGA2837	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270068-26-R1.BCG	Test Dates: 12/11/2023 - 3/12/2024	EUT Type: Tablet Device	Page 20 of 29

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-7. Radiated Test Setup < 30MHz




Figure 7-8. Radiated Test Setup > 30MHz

FCC ID: BCGA2837	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270068-26-R1.BCG	Test Dates: 12/11/2023 - 3/12/2024	EUT Type: Tablet Device	Page 21 of 29

Test Notes:

1. Radiated measurements below 30MHz were measured using a loop antenna. The antenna was positioned in three orthogonal planes (X front, Y side, Z top) and the position with the highest emission level is reported.
2. For measurements made below 1GHz, the results recorded using the broadband antenna are known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antennas was found to be less than 2:1.
3. The EUT was positioned in three orthogonal planes to determine the orientation resulting in the worst case emissions.
4. Both configurations below were investigated, and the worst case has been reported.
 - a. Tablet Device powered by AC/DC adapter via USB-C cable with wire charger
 - b. Tablet Device powered by host PC via USB-C cable with wire charger
5. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported.
6. No spurious emissions levels were found to be greater than the level of the fundamental.
7. All possible configurations were investigated and only the worst case is reported.
8. The radiated limits for intentional radiators are shown in Table 7-6. At frequencies below 30 MHz, measurements were performed at 3m and the data was extrapolated to the specified measurement distance using the square of an inverse linear distance extrapolation factor (40 dB/decade) as specified in §15.31(f)(2).
 - a. Distance Extrapolation Factor $_{\text{dB}}$ = $20 \log_{10}(300/3)^2 = 80\text{dB}$ [For emissions within 9kHz-490kHz]
 - b. Distance Extrapolation Factor $_{\text{dB}}$ = $20 \log_{10}(30/3)^2 = 40\text{dB}$ [For emissions within 490kHz-30MHz]


Sample Calculation

- Field Strength Level $_{\text{dB}_{\mu}\text{V/m}}$ = Analyzer Level $_{\text{dBm}}$ + 107 + AFCL $_{\text{dB/m}}$ + Distance Extrapolation Factor $_{\text{dB}}$
- Distance Extrapolation Factor $_{\text{dB}}$ will be added only when applicable.
- AFCL $_{\text{dB/m}}$ = (Antenna Factor $_{\text{dB/m}}$ + Cable Loss $_{\text{dB}}$ + Attenuator $_{\text{dB}}$) – Preamplifier Gain $_{\text{dB}}$
- Margin $_{\text{dB}}$ = Field Strength Level $_{\text{dB}_{\mu}\text{V/m}}$ – Limit $_{\text{dB}_{\mu}\text{V/m}}$

FCC ID: BCGA2837	 element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270068-26-R1.BCG	Test Dates: 12/11/2023 - 3/12/2024	EUT Type: Tablet Device	Page 22 of 29	

Out-of-Band Radiated Spurious – Below 30MHz

§15.209 §15.225(d)



Plot 7-2. Radiated Spurious Plot 9kHz – 30MHz (Charging Rate 2.6C, with AC/DC Adapter)

Frequency [MHz]	Detector	Ant. Pol. [X/Y/Z]	Antenna Height [cm]	Turntable Azimuth [degree]	Level [dBm]	AFCL [dB/m]	Field Strength @3m [dBμV/m]	Field Strength @30m [dBμV/m]	Limit @30m [dBμV/m]	Field Strength @300m [dBμV/m]	Limit @300m [dBμV/m]	Margin [dB]
0.056	Max Peak	X	100	219	-94.27	19.79	32.52	-	-	-47.48	52.74	-100.22
0.082	Max Peak	X	100	212	-78.25	19.73	48.48	-	-	-31.52	49.36	-80.88
0.165	Max Peak	X	100	202	-82.96	19.53	43.57	-	-	-36.43	43.28	-79.71
0.244	Max Peak	X	100	218	-87.33	19.49	39.16	-	-	-40.84	39.86	-80.70
0.723	Max Peak	X	100	206	-91.85	19.64	34.79	-5.21	30.42	-	-	-35.63
1.617	Max Peak	X	100	41	-95.15	19.92	31.77	-8.23	23.43	-	-	-31.66

Table 7-6. Radiated Measurements (Charging Rate 2.6C, with AC/DC Adapter)


FCC ID: BCGA2837	 element	MEASUREMENT REPORT (CERTIFICATION)				Approved by: Technical Manager
Test Report S/N: 1C2311270068-26-R1.BCG	Test Dates: 12/11/2023 - 3/12/2024	EUT Type: Tablet Device				

V 10.5 12/15/2021

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Out-of-Band Radiated Spurious Emissions – 30MHz-1GHz

§15.209 §15.225(d)



Plot 7-3. Radiated Spurious Emissions 30MHz – 1GHz (Charging Rate 2.6C, with AC/DC Adapter)

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
40.67	Max Peak	V	100	95	-57.69	-21.39	27.92	40.00	-12.08
54.25	Max Peak	V	100	18	-55.49	-22.95	28.56	40.00	-11.44
81.36	Max Peak	V	100	155	-55.80	-23.83	27.37	40.00	-12.63
166.33	Max Peak	H	200	210	-61.79	-19.93	25.28	43.52	-18.24
325.46	Max Peak	H	100	0	-64.39	-14.16	28.45	46.02	-17.57
782.96	Max Peak	H	200	86	-76.55	-5.48	24.97	46.02	-21.05

Table 7-7. Radiated Measurements (Charging Rate 2.6C, with AC/DC Adapter)

FCC ID: BCGA2837	 element	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Technical Manager
Test Report S/N: 1C2311270068-26-R1.BCG	Test Dates: 12/11/2023 - 3/12/2024	EUT Type: Tablet Device			

V 10.5 12/15/2021

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.6 AC Line Conducted Emissions Measurement

§15.207

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for AC Line conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.207.

Frequency of emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-8. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10-2020, Section 6.2

Test Settings

Quasi-Peak Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Average Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: BCGA2837	 element		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270068-26-R1.BCG	Test Dates: 12/11/2023 - 3/12/2024	EUT Type: Tablet Device	Page 25 of 29	

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-9. Test Instrument & Measurement Setup

Test Notes

1. All modes of operation were investigated and the worst-case emissions are reported.
2. The limit for an intentional radiator from 150kHz to 30MHz are specified in 15.207.
3. Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
4. QP/AV Level (dB μ V) = QP/AV Analyzer/Receiver Level (dB μ V) + Corr. (dB)
5. Margin (dB) = QP/AV Level (dB μ V) - QP/AV Limit (dB μ V)
6. Traces shown in plot are made using a Quasi-peak and Average detectors.
7. Deviations to the Specifications: None.
8. Both configurations below were investigated, and the worst case has been reported.
 - a. Tablet Device powered by AC/DC adapter via USB-C cable with wire charger
 - b. Tablet Device powered by host PC via USB-C cable with wire charger

FCC ID: BCGA2837	 element	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270068-26-R1.BCG	Test Dates: 12/11/2023 - 3/12/2024	EUT Type: Tablet Device	Page 26 of 29



Plot 7-4. AC Line-Conducted Plot (L1, Charging Rate 2.6C, with Laptop)


Frequency [MHz]	Process State	QuasiPeak [dB μ V]	Average [dB μ V]	Limit [dB μ V]	Margin [dB]	Line	PE
0.188	FINAL	51.9	—	64.11	-12.21	L1	GND
0.191	FINAL	—	34.09	54.02	-19.93	L1	GND
0.618	FINAL	—	26.90	46.00	-19.10	L1	GND
0.618	FINAL	34.7	—	56.00	-21.33	L1	GND
2.049	FINAL	—	23.06	46.00	-22.94	L1	GND
2.069	FINAL	30.0	—	56.00	-26.03	L1	GND
7.109	FINAL	27.1	—	60.00	-32.87	L1	GND
7.121	FINAL	—	11.05	50.00	-38.95	L1	GND
16.260	FINAL	17.3	—	60.00	-42.73	L1	GND
16.260	FINAL	—	11.23	50.00	-38.77	L1	GND
27.121	FINAL	—	19.82	50.00	-30.18	L1	GND
27.121	FINAL	25.8	—	60.00	-34.22	L1	GND

Table 7-9. AC Line-Conducted Data (L1, Charging Rate 2.6C, with Laptop)

FCC ID: BCGA2837	 element	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Technical Manager
Test Report S/N: 1C2311270068-26-R1.BCG	Test Dates: 12/11/2023 - 3/12/2024	EUT Type: Tablet Device			

V 10.5 12/15/2021

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-5. AC Line-Conducted Plot (N, Charging Rate 2.6C, with Laptop)

Frequency [MHz]	Process State	QuasiPeak [dB μ V]	Average [dB μ V]	Limit [dB μ V]	Margin [dB]	Line	PE
0.188	FINAL	52.1	—	64.11	-11.98	N	GND
0.191	FINAL	—	36.32	54.02	-17.70	N	GND
0.629	FINAL	—	25.07	46.00	-20.93	N	GND
0.629	FINAL	34.9	—	56.00	-21.10	N	GND
1.923	FINAL	28.0	—	56.00	-28.02	N	GND
1.925	FINAL	—	19.14	46.00	-26.86	N	GND
5.840	FINAL	—	11.92	50.00	-38.08	N	GND
5.843	FINAL	19.7	—	60.00	-40.28	N	GND
16.271	FINAL	18.5	—	60.00	-41.46	N	GND
16.271	FINAL	—	12.55	50.00	-37.45	N	GND
27.121	FINAL	—	18.23	50.00	-31.77	N	GND
27.121	FINAL	23.2	—	60.00	-36.85	N	GND

Table 7-10. AC Line-Conducted Data (N, Charging Rate 2.6C, with Laptop)

FCC ID: BCGA2837	 element	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Technical Manager
Test Report S/N: 1C2311270068-26-R1.BCG	Test Dates: 12/11/2023 - 3/12/2024	EUT Type: Tablet Device			

V 10.5 12/15/2021

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Apple Tablet Device FCC ID: BCGA2837** has been tested to show compliance with Part 15 Subpart C (15.225) of the FCC Rules.

FCC ID: BCGA2837	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2311270068-26-R1.BCG	Test Dates: 12/11/2023 - 3/12/2024	EUT Type: Tablet Device	Page 29 of 29