





Plot 7-984. Radiated Spurious Emissions above 1GHz CDD (802.11n – Ch. 56)



Plot 7-985. Radiated Spurious Emissions 18GHz – 40GHz CDD (802.11n – Ch. 56)


Mode: 802.11n
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5280MHz
Channel: 56

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10560.00	Peak	V	-	-	-68.80	11.03	49.23	68.20	-18.97
* 15840.00	Average	V	-	-	-79.13	17.92	45.79	53.98	-8.19
* 15840.00	Peak	V	-	-	-69.37	17.68	55.31	73.98	-18.67

Table 7-322. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)						Approved by: Technical Manager	
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device						Page 355 of 547	

V 10.5 12/15/2021




Plot 7-986. Radiated Spurious Emissions above 1GHz CDD (802.11n – Ch. 64)

Mode: 802.11n
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5320MHz
Channel: 64

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 10640.00	Average	V	-	-	-80.71	11.23	37.52	53.98	-16.46
* 10640.00	Peak	V	-	-	-69.68	11.23	48.55	73.98	-25.43
* 15960.00	Average	V	-	-	-81.41	15.53	41.12	53.98	-12.86
* 15960.00	Peak	V	-	-	-70.98	15.53	51.55	73.98	-22.43

Table 7-323. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 356 of 547



Plot 7-987. Radiated Spurious Emissions above 1GHz CDD (802.11n – Ch. 100)


Mode: 802.11n
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5500MHz
Channel: 100

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
*	11000.00	Average	V	-	-	-80.18	12.04	38.86	53.98	-15.12
*	11000.00	Peak	V	-	-	-69.02	12.10	50.08	73.98	-23.90
	16500.00	Peak	V	-	-	-69.62	19.50	56.88	68.20	-11.32


Table 7-324. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 357 of 547

V 10.5 12/15/2021



Plot 7-988. Radiated Spurious Emissions above 1GHz CDD (802.11n – Ch. 116)



Plot 7-989. Radiated Spurious Emissions 18GHz – 40GHz CDD (802.11n – Ch. 116)


Mode: 802.11n
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5580MHz
Channel: 116

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11160.00	Average	V	-	-	-80.12	11.21	38.09	53.98	-15.89
* 11160.00	Peak	V	-	-	-68.61	11.21	49.60	73.98	-24.38
16740.00	Peak	V	-	-	-70.75	19.48	55.72	68.20	-12.48

Table 7-325. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 358 of 547

V 10.5 12/15/2021



Plot 7-990. Radiated Spurious Emissions above 1GHz CDD (802.11n – Ch. 144)


Mode: 802.11n
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5720MHz
Channel: 144

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11440.00	Average	V	-	-	-80.21	12.05	38.84	53.98	-15.14
* 11440.00	Peak	V	-	-	-69.23	12.08	49.85	73.98	-24.13
17160.00	Peak	V	-	-	-70.11	20.84	57.74	68.20	-10.46

Table 7-326. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 359 of 547

V 10.5 12/15/2021



Plot 7-991. Radiated Spurious Emissions above 1GHz CDD (802.11n – Ch. 149)


Mode: 802.11n
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5745MHz
Channel: 149

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
*	11490.00	Average	V	-	-	-80.12	11.97	38.85	53.98	-15.13
*	11490.00	Peak	V	-	-	-69.24	11.97	49.73	73.98	-24.25
	17235.00	Peak	V	-	-	-70.71	20.88	57.17	68.20	-11.03


Table 7-327. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 360 of 547

V 10.5 12/15/2021



Plot 7-992. Radiated Spurious Emissions above 1GHz CDD (802.11n – Ch. 157)



Plot 7-993. Radiated Spurious Emissions 18GHz – 40GHz CDD (802.11n – Ch. 157)


Mode: 802.11n
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5785MHz
Channel: 157

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11570.00	Average	V	-	-	-79.85	12.03	39.18	53.98	-14.80
* 11570.00	Peak	V	-	-	-69.06	12.03	49.96	73.98	-24.02
17355.00	Peak	V	-	-	-70.35	21.00	57.65	68.20	-10.55

Table 7-328. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)						Approved by: Technical Manager	
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device						Page 361 of 547	

V 10.5 12/15/2021



Plot 7-994. Radiated Spurious Emissions above 1GHz CDD (802.11n – Ch. 165)


Mode: 802.11n
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5825MHz
Channel: 165

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11650.00	Average	V	-	-	-79.89	11.95	39.06	53.98	-14.92
* 11650.00	Peak	V	-	-	-69.82	12.00	49.18	73.98	-24.80
17475.00	Peak	V	-	-	-71.12	21.76	57.64	68.20	-10.56

Table 7-329. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 362 of 547

V 10.5 12/15/2021



Plot 7-995. Radiated Spurious Emissions above 1GHz CDD (802.11ax(SU) – Ch. 36)


Mode: 802.11ax(SU)
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5180MHz
Channel: 36

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10360.00	Peak	V	-	-	-68.94	10.49	48.55	68.20	-19.65
* 15540.00	Average	V	-	-	-81.25	15.99	41.74	53.98	-12.24
* 15540.00	Peak	V	-	-	-70.18	15.99	52.81	73.98	-21.17


Table 7-330. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 363 of 547

V 10.5 12/15/2021



Plot 7-996. Radiated Spurious Emissions above 1GHz CDD (802.11ax(SU) – Ch. 40)



Plot 7-997. Radiated Spurious Emissions 18GHz – 40GHz CDD (802.11ax(SU) – Ch. 40)

Mode: 802.11ax(SU)

Data Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5200MHz


Channel: 40

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10400.00	Peak	V	-	-	-68.86	10.62	48.76	68.20	-19.44
* 15600.00	Average	V	-	-	-81.54	16.10	41.56	53.98	-12.41
* 15600.00	Peak	V	-	-	-69.82	16.26	53.44	73.98	-20.54

Table 7-331. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 364 of 547

V 10.5 12/15/2021



Plot 7-998. Radiated Spurious Emissions above 1GHz CDD (802.11ax(SU) – Ch. 48)


Mode: 802.11ax(SU)
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5240MHz
Channel: 48

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10480.00	Peak	V	-	-	-68.53	11.14	49.61	68.20	-18.59
* 15720.00	Average	V	-	-	-81.12	15.98	41.86	53.98	-12.12
* 15720.00	Peak	V	-	-	-69.63	15.68	53.05	73.98	-20.93

Table 7-332. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 365 of 547

V 10.5 12/15/2021



Plot 7-999. Radiated Spurious Emissions above 1GHz CDD (802.11ax(SU) – Ch. 52)


Mode: 802.11ax(SU)
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5260MHz
Channel: 52

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10520.00	Peak	V	-	-	-69.02	11.24	49.21	68.20	-18.99
* 15780.00	Average	V	-	-	-81.84	15.58	40.74	53.98	-13.24
* 15780.00	Peak	V	-	-	-70.42	15.44	52.02	73.98	-21.96


Table 7-333. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 366 of 547

V 10.5 12/15/2021



Plot 7-1000. Radiated Spurious Emissions above 1GHz CDD (802.11ax(SU) – Ch. 56)



Plot 7-1001. Radiated Spurious Emissions 18GHz – 40GHz CDD (802.11ax(SU) – Ch. 56)

Mode: 802.11ax(SU)

Data Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5280MHz


Channel: 56

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10560.00	Peak	V	-	-	-69.93	11.38	48.45	68.20	-19.75
* 15840.00	Average	V	-	-	-81.05	15.45	41.40	53.98	-12.58
* 15840.00	Peak	V	-	-	-70.34	15.49	52.16	73.98	-21.82

Table 7-334. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)						Approved by: Technical Manager	
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device						Page 367 of 547	

V 10.5 12/15/2021




Plot 7-1002. Radiated Spurious Emissions above 1GHz CDD (802.11ax(SU) – Ch. 64)

Mode: 802.11ax(SU)
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5320MHz
Channel: 64

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 10640.00	Average	V	-	-	-80.60	11.23	37.63	53.98	-16.35
* 10640.00	Peak	V	-	-	-69.56	11.23	48.67	73.98	-25.31
* 15960.00	Average	V	-	-	-81.20	15.53	41.33	53.98	-12.65
* 15960.00	Peak	V	-	-	-70.04	15.53	52.49	73.98	-21.49

Table 7-335. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 368 of 547



Plot 7-1003. Radiated Spurious Emissions above 1GHz CDD (802.11ax(SU) – Ch. 100)


Mode: 802.11ax(SU)
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5500MHz
Channel: 100

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
*	11000.00	Average	V	-	-	-81.35	11.68	37.33	53.98	-16.65
*	11000.00	Peak	V	-	-	-70.24	11.83	48.59	73.98	-25.39
	16500.00	Peak	V	-	-	-69.72	17.06	54.34	68.20	-13.86


Table 7-336. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 369 of 547

V 10.5 12/15/2021



Plot 7-1004. Radiated Spurious Emissions above 1GHz CDD (802.11ax(SU) – Ch. 116)



Plot 7-1005. Radiated Spurious Emissions 18GHz – 40GHz CDD (802.11ax(SU) – Ch. 116)


Mode: 802.11ax(SU)
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5580MHz
Channel: 116

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11160.00	Average	V	-	-	-81.28	11.28	37.00	53.98	-16.97
* 11160.00	Peak	V	-	-	-69.96	11.20	48.24	73.98	-25.74
16740.00	Peak	V	-	-	-70.49	17.78	54.30	68.20	-13.90

Table 7-337. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device		Page 370 of 547

V 10.5 12/15/2021



Plot 7-1006. Radiated Spurious Emissions above 1GHz CDD (802.11ax(SU) – Ch. 144)


Mode: 802.11ax(SU)
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5720MHz
Channel: 144

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11440.00	Average	V	-	-	-80.96	11.96	38.00	53.98	-15.98
* 11440.00	Peak	V	-	-	-70.09	12.04	48.95	73.98	-25.03
17160.00	Peak	V	-	-	-69.90	17.49	54.59	68.20	-13.61

Table 7-338. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 371 of 547

V 10.5 12/15/2021



Plot 7-1007. Radiated Spurious Emissions above 1GHz CDD (802.11ax(SU) – Ch. 149)


Mode: 802.11ax(SU)
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5745MHz
Channel: 149

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
*	11490.00	Average	V	-	-	-80.04	11.93	38.89	53.98	-15.09
*	11490.00	Peak	V	-	-	-69.78	11.85	49.07	73.98	-24.91
	17235.00	Peak	V	-	-	-69.16	17.25	55.09	68.20	-13.11


Table 7-339. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 372 of 547

V 10.5 12/15/2021



Plot 7-1008. Radiated Spurious Emissions above 1GHz CDD (802.11ax(SU) – Ch. 157)



Plot 7-1009. Radiated Spurious Emissions 18GHz – 40GHz CDD (802.11ax(SU) – Ch. 157)


Mode: 802.11ax(SU)
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5785MHz
Channel: 157

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11570.00	Average	V	-	-	-80.58	11.99	38.41	53.98	-15.57
* 11570.00	Peak	V	-	-	-68.99	11.92	49.93	73.98	-24.05
17355.00	Peak	V	-	-	-70.06	17.28	54.22	68.20	-13.98

Table 7-340. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)						Approved by: Technical Manager	
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device						Page 373 of 547	

V 10.5 12/15/2021



Plot 7-1010. Radiated Spurious Emissions above 1GHz CDD (802.11ax(SU) – Ch. 165)

Mode: 802.11ax(SU)
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5825MHz
Channel: 165


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11650.00	Average	V	-	-	-81.50	12.00	37.50	53.98	-16.48
* 11650.00	Peak	V	-	-	-70.04	12.00	48.96	73.98	-25.02
17475.00	Peak	V	-	-	-71.12	21.86	57.75	68.20	-10.45

Table 7-341. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 374 of 547

V 10.5 12/15/2021

7.6.5 CDD Diversity Radiated Spurious Emission



Plot 7-1011. Radiated Spurious Emissions above 1GHz CDD (802.11n – Ch. 36)


Mode:	802.11n
Data Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5180MHz
Channel:	36

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10360.00	Peak	V	-	-	-69.17	11.07	48.90	68.20	-19.30
* 15540.00	Average	V	-	-	-81.66	17.35	42.69	53.98	-11.29
* 15540.00	Peak	V	-	-	-70.15	17.43	54.28	73.98	-19.70


Table 7-342. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 375 of 547

V 10.5 12/15/2021



Plot 7-1012. Radiated Spurious Emissions above 1GHz CDD (802.11n – Ch. 40)



Plot 7-1013. Radiated Spurious Emissions 18GHz – 40GHz CDD (802.11n – Ch. 40)

Mode: 802.11n

Data Rate: MCS0

Distance of Measurements: 3 Meters


Operating Frequency: 5200MHz

Channel: 40

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10400.00	Peak	V	-	-	-69.09	11.19	49.10	68.20	-19.10
* 15600.00	Average	V	-	-	-82.01	17.07	42.06	53.98	-11.92
* 15600.00	Peak	V	-	-	-70.31	17.31	54.00	73.98	-19.98

Table 7-343. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 376 of 547



Plot 7-1014. Radiated Spurious Emissions above 1GHz CDD (802.11n – Ch. 48)


Mode: 802.11n
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5240MHz
Channel: 48

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10480.00	Peak	V	-	-	-68.88	11.33	49.45	68.20	-18.75
* 15720.00	Average	V	-	-	-82.10	16.69	41.58	53.98	-12.39
* 15720.00	Peak	V	-	-	-70.23	16.78	53.55	73.98	-20.43

Table 7-344. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 377 of 547

V 10.5 12/15/2021



Plot 7-1015. Radiated Spurious Emissions above 1GHz CDD (802.11n – Ch. 52)


Mode: 802.11n
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5260MHz
Channel: 52

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10520.00	Peak	V	-	-	-68.85	11.21	49.36	68.20	-18.84
* 15780.00	Average	V	-	-	-81.67	17.34	42.67	53.98	-11.31
* 15780.00	Peak	V	-	-	-70.08	17.34	54.27	73.98	-19.71


Table 7-345. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 378 of 547

V 10.5 12/15/2021



Plot 7-1016. Radiated Spurious Emissions above 1GHz CDD (802.11n – Ch. 56)



Plot 7-1017. Radiated Spurious Emissions 18GHz – 40GHz CDD (802.11n – Ch. 56)


Mode: 802.11n
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5280MHz
Channel: 56

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10560.00	Peak	V	-	-	-68.72	11.03	49.32	68.20	-18.88
* 15840.00	Average	V	-	-	-81.51	17.92	43.41	53.98	-10.57
* 15840.00	Peak	V	-	-	-70.05	17.92	54.87	73.98	-19.11

Table 7-346. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 379 of 547

V 10.5 12/15/2021



Plot 7-1018. Radiated Spurious Emissions above 1GHz CDD (802.11n – Ch. 64)


Mode: 802.11n
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5320MHz
Channel: 64

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
*	10640.00	Average	V	-	-	-80.92	11.03	37.12	53.98	-16.86
*	10640.00	Peak	V	-	-	-69.10	11.03	48.93	73.98	-25.05
*	15960.00	Average	V	-	-	-81.68	17.91	43.22	53.98	-10.75
*	15960.00	Peak	V	-	-	-69.18	17.97	55.78	73.98	-18.20

Table 7-347. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 380 of 547

V 10.5 12/15/2021



Plot 7-1019. Radiated Spurious Emissions above 1GHz CDD (802.11n – Ch. 100)


Mode: 802.11n
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5500MHz
Channel: 100

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
*	11000.00	Average	V	-	-	-81.14	11.90	37.75	53.98	-16.23
*	11000.00	Peak	V	-	-	-69.45	12.17	49.72	73.98	-24.26
	16500.00	Peak	V	-	-	-70.46	19.59	56.13	68.20	-12.07


Table 7-348. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 381 of 547

V 10.5 12/15/2021



Plot 7-1020. Radiated Spurious Emissions above 1GHz CDD (802.11n – Ch. 116)



Plot 7-1021. Radiated Spurious Emissions 18GHz – 40GHz CDD (802.11n – Ch. 116)

Mode: 802.11n

Data Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5580MHz


Channel: 116

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11160.00	Average	V	-	-	-80.83	11.21	37.39	53.98	-16.59
* 11160.00	Peak	V	-	-	-69.25	11.30	49.05	73.98	-24.93
16740.00	Peak	V	-	-	-70.24	19.48	56.23	68.20	-11.97

Table 7-349. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device		Page 382 of 547

V 10.5 12/15/2021



Plot 7-1022. Radiated Spurious Emissions above 1GHz CDD (802.11n – Ch. 144)


Mode: 802.11n
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5720MHz
Channel: 144

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
*	11440.00	Average	V	-	-	-80.66	12.08	38.42	53.98	-15.56
*	11440.00	Peak	V	-	-	-69.08	12.08	50.00	73.98	-23.98
	17160.00	Peak	V	-	-	-71.01	20.84	56.84	68.20	-11.36

Table 7-350. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 383 of 547

V 10.5 12/15/2021



Plot 7-1023. Radiated Spurious Emissions above 1GHz CDD (802.11n – Ch. 149)


Mode: 802.11n
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5745MHz
Channel: 149

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
*	11490.00	Average	V	-	-	-80.90	11.92	38.02	53.98	-15.96
*	11490.00	Peak	V	-	-	-68.83	11.92	50.09	73.98	-23.89
	17235.00	Peak	V	-	-	-70.79	20.88	57.08	68.20	-11.12


Table 7-351. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 384 of 547

V 10.5 12/15/2021



Plot 7-1024. Radiated Spurious Emissions above 1GHz CDD (802.11n – Ch. 157)



Plot 7-1025. Radiated Spurious Emissions 18GHz – 40GHz CDD (802.11n – Ch. 157)


Mode: 802.11n
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5785MHz
Channel: 157

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11570.00	Average	V	-	-	-81.07	12.10	38.03	53.98	-15.95
* 11570.00	Peak	V	-	-	-69.20	12.03	49.82	73.98	-24.16
17355.00	Peak	V	-	-	-71.21	20.99	56.77	68.20	-11.43

Table 7-352. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device		Page 385 of 547

V 10.5 12/15/2021



Plot 7-1026. Radiated Spurious Emissions above 1GHz CDD (802.11n – Ch. 165)


Mode: 802.11n
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5825MHz
Channel: 165

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
*	11650.00	Average	V	-	-	-81.29	11.84	37.55	53.98	-16.43
*	11650.00	Peak	V	-	-	-69.84	12.00	49.16	73.98	-24.82
	17475.00	Peak	V	-	-	-70.92	21.76	57.84	68.20	-10.36

Table 7-353. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device		Page 386 of 547

V 10.5 12/15/2021



Plot 7-1027. Radiated Spurious Emissions above 1GHz CDD (802.11ax(SU) – Ch. 36)


Mode: 802.11ax(SU)
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5180MHz
Channel: 36

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10360.00	Peak	V	-	-	-69.17	11.19	49.02	68.20	-19.18
* 15540.00	Average	V	-	-	-82.17	17.35	42.18	53.98	-11.80
* 15540.00	Peak	V	-	-	-70.18	17.63	54.45	73.98	-19.53


Table 7-354. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 387 of 547

V 10.5 12/15/2021



Plot 7-1028. Radiated Spurious Emissions above 1GHz CDD (802.11ax(SU) – Ch. 40)



Plot 7-1029. Radiated Spurious Emissions 18GHz – 40GHz CDD (802.11ax(SU) – Ch. 40)


Mode: 802.11ax(SU)
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5200MHz
Channel: 40

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
10400.00	Peak	V	-	-	-67.85	11.23	50.38	68.20	-17.82
* 15600.00	Average	V	-	-	-81.74	17.14	42.40	53.98	-11.58
* 15600.00	Peak	V	-	-	-70.18	17.07	53.88	73.98	-20.10

Table 7-355. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 388 of 547

V 10.5 12/15/2021



Plot 7-1030. Radiated Spurious Emissions above 1GHz CDD (802.11ax(SU) – Ch. 48)


Mode: 802.11ax(SU)
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5240MHz
Channel: 48

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10480.00	Peak	V	-	-	-68.10	11.33	50.23	68.20	-17.97
* 15720.00	Average	V	102	197	-80.46	16.78	43.32	53.98	-10.66
* 15720.00	Peak	V	102	197	-61.57	16.69	62.12	73.98	-11.86

Table 7-356. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 389 of 547

V 10.5 12/15/2021



Plot 7-1031. Radiated Spurious Emissions above 1GHz CDD (802.11ax(SU) – Ch. 52)


Mode: 802.11ax(SU)
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5260MHz
Channel: 52

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10520.00	Peak	V	-	-	-69.21	11.14	48.93	68.20	-19.27
* 15780.00	Average	V	-	-	-81.72	17.34	42.62	53.98	-11.36
* 15780.00	Peak	V	-	-	-69.76	17.54	54.78	73.98	-19.20


Table 7-357. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 390 of 547

V 10.5 12/15/2021



Plot 7-1032. Radiated Spurious Emissions above 1GHz CDD (802.11ax(SU) – Ch. 56)



Plot 7-1033. Radiated Spurious Emissions 18GHz – 40GHz CDD (802.11ax(SU) – Ch. 56)


Mode: 802.11ax(SU)
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5280MHz
Channel: 56

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10560.00	Peak	V	-	-	-69.08	11.03	48.95	68.20	-19.25
* 15840.00	Average	V	-	-	-81.93	17.68	42.75	53.98	-11.23
* 15840.00	Peak	V	-	-	-70.44	17.92	54.48	73.98	-19.50

Table 7-358. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 391 of 547

V 10.5 12/15/2021



Plot 7-1034. Radiated Spurious Emissions above 1GHz CDD (802.11ax(SU) – Ch. 64)


Mode: 802.11ax(SU)
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5320MHz
Channel: 64

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
*	10640.00	Average	V	-	-	-80.81	11.03	37.22	53.98	-16.76
*	10640.00	Peak	V	-	-	-69.40	10.87	48.47	73.98	-25.51
*	15960.00	Average	V	-	-	-81.53	17.91	43.38	53.98	-10.60
*	15960.00	Peak	V	-	-	-70.04	17.91	54.87	73.98	-19.11

Table 7-359. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898			MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device		Page 392 of 547

V 10.5 12/15/2021



Plot 7-1035. Radiated Spurious Emissions above 1GHz CDD (802.11ax(SU) – Ch. 100)


Mode: 802.11ax(SU)
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5500MHz
Channel: 100

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
*	11000.00	Average	V	-	-	-81.21	12.04	37.83	53.98	-16.15
*	11000.00	Peak	V	-	-	-69.43	12.17	49.74	73.98	-24.24
	16500.00	Peak	V	-	-	-69.72	19.59	56.87	68.20	-11.33


Table 7-360. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 393 of 547

V 10.5 12/15/2021



Plot 7-1036. Radiated Spurious Emissions above 1GHz CDD (802.11ax(SU) – Ch. 116)




Plot 7-1037. Radiated Spurious Emissions 18GHz – 40GHz CDD (802.11ax(SU) – Ch. 116)

Mode: 802.11ax(SU)
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5580MHz
Channel: 116

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11160.00	Average	V	-	-	-80.68	11.30	37.63	53.98	-16.35
* 11160.00	Peak	V	-	-	-68.92	11.30	49.38	73.98	-24.60
16740.00	Peak	V	-	-	-70.89	19.71	55.82	68.20	-12.38

Table 7-361. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 394 of 547



Plot 7-1038. Radiated Spurious Emissions above 1GHz CDD (802.11ax(SU) – Ch. 144)


Mode: 802.11ax(SU)
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5720MHz
Channel: 144

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
*	11440.00	Average	V	-	-	-80.69	12.27	38.58	53.98	-15.40
*	11440.00	Peak	V	-	-	-69.35	12.08	49.73	73.98	-24.25
	17160.00	Peak	V	-	-	-70.34	20.84	57.50	68.20	-10.70

Table 7-362. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 395 of 547

V 10.5 12/15/2021



Plot 7-1039. Radiated Spurious Emissions above 1GHz CDD (802.11ax(SU) – Ch. 149)


Mode: 802.11ax(SU)
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5745MHz
Channel: 149

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
*	11490.00	Average	V	-	-	-80.95	12.03	38.08	53.98	-15.90
*	11490.00	Peak	V	-	-	-69.65	11.97	49.31	73.98	-24.67
	17235.00	Peak	V	-	-	-70.45	20.84	57.39	68.20	-10.81


Table 7-363. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 396 of 547

V 10.5 12/15/2021



Plot 7-1040. Radiated Spurious Emissions above 1GHz CDD (802.11ax(SU) – Ch. 157)



Plot 7-1041. Radiated Spurious Emissions 18GHz – 40GHz CDD (802.11ax(SU) – Ch. 157)

Mode: 802.11ax(SU)

Data Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5785MHz


Channel: 157

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
* 11570.00	Average	V	-	-	-81.12	12.03	37.91	53.98	-16.07
* 11570.00	Peak	V	-	-	-69.89	12.03	49.13	73.98	-24.85
17355.00	Peak	V	-	-	-70.78	20.99	57.21	68.20	-10.99

Table 7-364. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 397 of 547

V 10.5 12/15/2021



Plot 7-1042. Radiated Spurious Emissions above 1GHz CDD/SDM (802.11ax(SU) – Ch. 165)

Mode: 802.11ax(SU)
Data Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5825MHz
Channel: 165

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
*	11650.00	Average	V	-	-	-81.24	12.00	37.76	53.98	-16.22
*	11650.00	Peak	V	-	-	-69.69	11.95	49.26	73.98	-24.72
	17475.00	Peak	V	-	-	-70.49	21.97	58.48	68.20	-9.72

Table 7-365. Radiated Measurements CDD

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 398 of 547


V 10.5 12/15/2021

7.6.6 Simultaneous Tx Radiated Spurious Emissions Measurements


§15.209; RSS-Gen [8.9]

Description	Bluetooth	UNII
Antenna	WF7b	WF7b
Channel	79	36
Operating Frequency (MHz)	2480	5180
Mode/Modulation	GFSK ePA	802.11n

Table 7-366. Worst Case Simultaneous Transmission Configuration



Plot 7-1043. Radiated Spurious Emissions 1 - 18GHz – Simultaneous Transmission



Plot 7-1044. Radiated Spurious Emissions Above 18GHz – Simultaneous Transmission

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 399 of 547

V 10.5 12/15/2021

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
4960.00	Peak	V	-	-	-67.42	15.70	55.28	73.98	-18.70
7440.00	Peak	V	-	-	-67.81	9.17	48.36	73.98	-25.62
12400.00	Peak	V	-	-	-71.20	15.81	51.61	73.98	-22.36

Table 7-367. Bluetooth Harmonics Emission Measurements – Simultaneous Transmission

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
10360.00	Peak	V	-	-	-69.89	11.93	49.04	68.23	-19.19
15540.00	Avg	V	-	-	-82.81	19.69	43.88	53.98	-10.10
15540.00	Peak	V	-	-	-72.12	19.69	54.57	73.98	-19.41


Table 7-368. UNII and Intermodulation's Emissions Measurements – Simultaneous Transmission

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 400 of 547


V 10.5 12/15/2021

7.6.7 Antenna WF7a Radiated Band Edge Measurements (20MHz BW)


§15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]; RSS-Gen [8.9]




Plot 7-1045. ANTENNA WF7A (PK & AVG, CH.36, 802.11N, MCS2)




Plot 7-1048. ANTENNA WF7A (PK & AVG, CH.40, 802.11N, MCS2)




Plot 7-1046. ANTENNA WF7A (PK & AVG, CH.36, 802.11N, MCS4)



Plot 7-1049. ANTENNA WF7A (PK & AVG, CH.40, 802.11N, MCS4)



Plot 7-1047. ANTENNA WF7A (PK & AVG, CH.36, 802.11N, MCS7)



Plot 7-1050. ANTENNA WF7A (PK & AVG, CH.40, 802.11N, MCS7)

FCC ID: BCGA2898 IC: 579C-A2898		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2311270065-11-R1.BCG	Test Dates: 11/29/2024 - 1/15/2024	EUT Type: Tablet Device	Page 401 of 547

V 10.5 12/15/2021

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.