



Element Materials Technology

(formerly PCTEST)

18855 Adams Court, Morgan Hill, CA 95037 USA

Tel. 408.538.5600

<http://www.element.com>



PART 22 MEASUREMENT REPORT

Applicant Name:

Apple Inc.
One Apple Park Way
Cupertino, CA 95014
United States

Date of Testing:

7/1/2024 - 12/26/2024

Test Report Issue Date:

1/14/2025

Test Site/Location:

Element Materials Technology Morgan Hill, CA, USA

Test Report Serial No.:

1C2410210075-07-R1.BCG

FCC ID:**BCGA3269****Applicant Name:****Apple Inc.****Application Type:**

Certification

Model:

A3269, A3271

EUT Type:

Tablet Device

FCC Classification:

PCS Licensed Transmitter (PCB)

FCC Rule Part:

22

Test Procedure(s):

ANSI C63.26-2015, TIA-603-E-2016, KDB 971168 D01
v03r01

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

This revised Test Report (S/N: 1C2410210075-07-R1.BCG) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

RJ Ortiz

Executive Vice President



ACCREDITED

CERT #2041.02

FCC ID: BCGA3269	element	PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device		Page 1 of 112



V2.2 08/24/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

T A B L E O F C O N T E N T S

1.0	INTRODUCTION.....	5
1.1	Scope.....	5
1.2	Element Materials Technology Test Location.....	5
1.3	Test Facility / Accreditations.....	5
2.0	PRODUCT INFORMATION.....	6
2.1	Equipment Description.....	6
2.2	Device Capabilities	6
2.3	Antenna Description.....	7
2.4	Test Support Equipment.....	7
2.5	Test Configuration	7
2.6	Software and Firmware.....	7
2.7	EMI Suppression Device(s)/Modifications	7
3.0	DESCRIPTION OF TESTS.....	8
3.1	Measurement Procedure.....	8
3.2	Radiated Spurious Emissions.....	8
4.0	MEASUREMENT UNCERTAINTY.....	9
5.0	TEST EQUIPMENT CALIBRATION DATA	10
6.0	SAMPLE CALCULATIONS.....	11
7.0	TEST RESULTS	12
7.1	Summary.....	12
7.2	Occupied Bandwidth.....	13
7.3	Spurious and Harmonic Emissions at Antenna Terminal.....	36
7.4	Band Edge Emissions at Antenna Terminal	58
7.5	Radiated Power (ERP).....	78
7.6	Radiated Spurious Emissions.....	92
7.7	Frequency Stability / Temperature Variation.....	107
8.0	CONCLUSION	112

FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device	Page 2 of 112

PART 22 MEASUREMENT REPORT

Mode	Bandwidth	Modulation	Tx Frequency Range [MHz]	OBW [MHz]	ERP		Emission Designator
					Max. Power [W]	Max. Power [dBm]	
WCDMA850	5 MHz	Spread Spectrum	826.4 - 846.6	4.1654	0.132	21.19	4M17F9W
Band 5	1.4 MHz	QPSK	824.7 - 848.3	1.1146	0.133	21.25	1M11G7W
		16QAM	824.7 - 848.3	1.1167	0.113	20.54	1M12D7W
		64QAM	824.7 - 848.3	1.1145	0.087	19.41	1M11D7W
		256QAM	824.7 - 848.3	1.1144	0.043	16.35	1M11D7W
	3 MHz	QPSK	825.5 - 847.5	2.7291	0.130	21.15	2M73G7W
		16QAM	825.5 - 847.5	2.7265	0.111	20.47	2M73D7W
		64QAM	825.5 - 847.5	2.7325	0.090	19.54	2M73D7W
		256QAM	825.5 - 847.5	2.7300	0.043	16.36	2M73D7W
	5 MHz	QPSK	826.5 - 846.5	4.5525	0.130	21.13	4M55G7W
		16QAM	826.5 - 846.5	4.5674	0.114	20.55	4M57D7W
		64QAM	826.5 - 846.5	4.5508	0.086	19.36	4M55D7W
		256QAM	826.5 - 846.5	4.5658	0.044	16.43	4M57D7W
	10 MHz	QPSK	829.0 - 844.0	9.0738	0.128	21.07	9M07G7W
		16QAM	829.0 - 844.0	9.0583	0.110	20.40	9M06D7W
		64QAM	829.0 - 844.0	9.0603	0.086	19.36	9M06D7W
		256QAM	829.0 - 844.0	9.0529	0.044	16.40	9M05D7W
Band 26	1.4 MHz	QPSK	824.7 - 848.3	1.1146	0.133	21.23	1M11G7W
		16QAM	824.7 - 848.3	1.1167	0.113	20.52	1M12D7W
		64QAM	824.7 - 848.3	1.1145	0.087	19.38	1M11D7W
		256QAM	824.7 - 848.3	1.1144	0.044	16.46	1M11D7W
	3 MHz	QPSK	825.5 - 847.5	2.7291	0.133	21.25	2M73G7W
		16QAM	825.5 - 847.5	2.7265	0.114	20.58	2M73D7W
		64QAM	825.5 - 847.5	2.7325	0.089	19.49	2M73D7W
		256QAM	825.5 - 847.5	2.7300	0.045	16.55	2M73D7W
	5 MHz	QPSK	826.5 - 846.5	4.5525	0.130	21.14	4M55G7W
		16QAM	826.5 - 846.5	4.5674	0.115	20.60	4M57D7W
		64QAM	826.5 - 846.5	4.5508	0.087	19.41	4M55D7W
		256QAM	826.5 - 846.5	4.5658	0.044	16.47	4M57D7W
	10 MHz	QPSK	829.0 - 844.0	9.0738	0.132	21.22	9M07G7W
		16QAM	829.0 - 844.0	9.0583	0.111	20.47	9M06D7W
		64QAM	829.0 - 844.0	9.0603	0.088	19.46	9M06D7W
		256QAM	829.0 - 844.0	9.0529	0.044	16.40	9M05D7W
ULCA Band 5	10 + 10 MHz	QPSK	829.0 - 844.0	18.9182	0.129	21.10	18M9G7W
		16QAM	829.0 - 844.0	18.8811	0.079	18.97	18M9D7W
		64QAM	829.0 - 844.0	18.8513	0.073	18.64	18M9D7W
		256QAM	829.0 - 844.0	18.8486	0.047	16.70	18M8D7W

EUT Overview

FCC ID: BCGA3269	 element	PART 22 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device			

Mode	Bandwidth	Modulation	Tx Frequency Range [MHz]	OBW [MHz]	ERP		Emission Designator
					Max. Power [W]	Max. Power [dBm]	
NR Band n5	5 MHz	TT/2 BPSK	826.5 - 846.5	4.4797	0.132	21.20	4M48G7W
		QPSK	826.5 - 846.5	4.4559	0.133	21.25	4M46G7W
		16QAM	826.5 - 846.5	4.4892	0.104	20.16	4M49D7W
		64QAM	826.5 - 846.5	4.4715	0.085	19.27	4M47D7W
		256QAM	826.5 - 846.5	4.5000	0.043	16.37	4M50D7W
	10 MHz	TT/2 BPSK	829.0 - 844.0	8.9678	0.133	21.25	8M97G7W
		QPSK	829.0 - 844.0	9.3523	0.133	21.24	9M35G7W
		16QAM	829.0 - 844.0	9.2868	0.106	20.25	9M29D7W
		64QAM	829.0 - 844.0	9.2380	0.083	19.21	9M24D7W
		256QAM	829.0 - 844.0	9.2781	0.042	16.28	9M28D7W
NR Band n26	15 MHz	TT/2 BPSK	831.5 - 841.5	13.4718	0.131	21.17	13M5G7W
		QPSK	831.5 - 841.5	14.1273	0.133	21.25	14M1G7W
		16QAM	831.5 - 841.5	14.0707	0.105	20.22	14M1D7W
		64QAM	831.5 - 841.5	14.0983	0.083	19.21	14M1D7W
		256QAM	831.5 - 841.5	14.0797	0.042	16.24	14M1D7W
	20 MHz	TT/2 BPSK	834.0 - 839.0	17.9492	0.131	21.17	17M9G7W
		QPSK	834.0 - 839.0	18.9630	0.133	21.25	19M0G7W
		16QAM	834.0 - 839.0	18.9407	0.106	20.24	18M9D7W
		64QAM	834.0 - 839.0	18.9271	0.083	19.21	18M9D7W
		256QAM	834.0 - 839.0	18.9243	0.043	16.31	18M9D7W

EUT Overview

FCC ID: BCGA3269	 element	PART 22 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device			Page 4 of 112

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 Element Materials Technology Test Location

These measurement tests were conducted at the Element Materials Technology facility located at 18855 Adams Court, Morgan Hill, CA 95037. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014 and KDB 414788 D01 v01r01.

1.3 Test Facility / Accreditations

Measurements were performed at Element Materials Technology.

- Element Materials Technology is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.02 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Materials Technology TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- Element Materials Technology facility is a registered (22831) test laboratory with the site description on file with ISED.
- Element Washington DC LLC is a Recognized U.S. Certification Assessment Body (CAB # US0110) for ISED Canada as designated by NIST under the U.S. and Canada Mutual Recognition Agreements (MRAs).

FCC ID: BCGA3269	 element		
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device	Approved by: Technical Manager

V2.2 08/24/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Apple Tablet Device FCC ID: BCGA3269**. The test data contained in this report pertains only to the emissions due to the EUT's licensed transmitters that operate under the provisions of Part 22.

Test Device Serial No.: RTF5C4W1KX, XD4R967RNY, TJ4463YD19, DLXH57000060000RJY, DLXH570002H0000RJY

2.2 Device Capabilities

This device contains the following capabilities:

850/1700/1900 WCDMA/HSPA, Multi-band LTE, 5G NR (FR1), 802.11b/g/n/ax WLAN, 802.11a/n/ac/ax UNII, 802.11a/ax WIFI 6E, 802.15.4, Bluetooth (1x, EDR, LE1M, LE2M, HDR4, HDR8), NB UNII (1x, HDR4, HDR8), WPT

This device supports BT Beamforming

This device supports simultaneous transmission operations, which allows for multiple transmitters to transmit simultaneously on the same antenna. The table below shows all configurations possible.

Antenna	Simultaneous Tx Config	Bluetooth 2.4GHz	Thread	WLAN	NB UNII	WIFI 5GHz	WIFI 6GHz	LTE / FR1 NR		
		BDR, EDR, HDR4/8, LE1/2M	802.15.4	802.11 b/g/n/ax	BDR, HDR4/8	802.11 a/n/ac/ax	802.11 a/ax	LB	MB/HB	Ultra High Band
Ant 3b	Config 1	✗	✗	✗	✓	✗	✗	✗	✓	✗
Ant 3b	Config 2	✗	✗	✗	✗	✓	✗	✗	✓	✗
Ant 3b	Config 3	✗	✗	✗	✗	✗	✓	✗	✓	✗
Ant 3a	Config 4	✓	✗	✗	✗	✗	✗	✗	✗	✓
Ant 3a	Config 5	✗	✓	✗	✗	✗	✗	✗	✗	✓
Ant 3a	Config 6	✗	✗	✓	✗	✗	✗	✗	✗	✓
Ant 1a	Config 7	✓	✗	✗	✗	✗	✗	✗	✗	✓
Ant 1a	Config 8	✗	✓	✗	✗	✗	✗	✗	✗	✓
Ant 1a	Config 9	✗	✗	✓	✗	✗	✗	✗	✗	✓
Ant 1b	Config 10	✗	✗	✗	✓	✗	✗	✗	✓	✗
Ant 1b	Config 11	✗	✗	✗	✗	✓	✗	✗	✓	✗
Ant 1b	Config 12	✗	✗	✗	✗	✗	✓	✗	✓	✗

Table 2-1. Simultaneous Transmission Configurations

✓ = Support; ✗ = Not Support

Note:

All the above simultaneous transmission configurations have been tested and the worst-case configuration was found to be Config 2 and reported in RF UNII OFDM, and RF FCC Part 27b test reports.

Specific 2.4GHz Wi-Fi antenna that can only transmit simultaneously with 2.4GHz Bluetooth antenna is listed in the SAR test report. For BT (2.4GHz), in both connected and disconnected modes, and Wi-Fi (2.4GHz) - Wi-Fi max power will not exceed minimum of (13.5dBm, SAR max cap, Reg max cap) power. Bluetooth can simultaneously transmit with IEEE 802.11a/n/ac/ax 5/6 GHz on separate antenna.

FCC ID: BCGA3269	 element	PART 22 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device			Page 6 of 112

2.3 Antenna Description

The following antenna gains provided by the manufacturer were used for testing.

Band	Antenna Gain [dBi]	
	Antenna 4	Antenna 2
WCDMA 850	-2.3	-2.0

Table 2-2. Highest Antenna Gain

2.4 Test Support Equipment

Test Support Equipment					
1	Apple MacBook Pro w/AC/DC Adapter	Model: A2141 Model: A2166	S/N: C02H604EQ05D S/N: C4H042705ZNP0WA6		
2	Apple USB-C Cable	Model: Spartan	S/N: GXK1336018XKTR024		
3	USB-C Cable w/ AC Adapter	Model: A246C Model: A2305	S/N: DWH80115BK826GV19 S/N: C4H95160004PF4F4V		
4	Apple Pencil	Model: A2538	S/N: KJ26TCFXJW		
5	DC Power Supply	Model: KPS3010D	S/N: N/A		

Table 2-3. Test Support Equipment

2.5 Test Configuration

The EUT was tested per the guidance of ANSI C63.26 2015, TIA-603-E-2016 and KDB 971168 D01 v03r01. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

For emissions from 1GHz – 18GHz, low, mid, and high channels were tested with highest power and worst case configuration. The emissions below 1GHz were tested with the highest transmitting power and the worst case channel.

The EUT was manipulated through three orthogonal planes of X-orientation (flatbed), Y-orientation (landscape), and Z-orientation (portrait) during the testing. Only the worst case emissions were reported in this test report.

2.6 Software and Firmware

The test was conducted with firmware version 22D20 installed on the EUT.

2.7 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device		Page 7 of 112

3.0 DESCRIPTION OF TESTS

3.1 Measurement Procedure

The measurement procedures described in the documents titled “American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services” (ANSI C63.26-2015 and TIA-603-E-2016) and “Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems” (KDB 971168 D01 v03r01) were used in the measurement of the EUT.

Deviation from Measurement Procedure.....None

3.2 Radiated Spurious Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm tall test table made of Styrodur is placed on top of the turn table. A Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

The equipment under test was transmitting while connected to its integral antenna and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer.

For radiated spurious emissions measurements and calculations, conversion method is used per the formulas in KDB 971168 Section 5.8.4. Field Strength (EIRP) is calculated using the following formulas:

$$E_{[\text{dB}\mu\text{V}/\text{m}]} = \text{Measured amplitude level}_{[\text{dBm}]} + 107 + \text{Cable Loss}_{[\text{dB}]} + \text{Antenna Factor}_{[\text{dB}/\text{m}]}$$

And

$$\text{EIRP}_{[\text{dBm}]} = E_{[\text{dB}\mu\text{V}/\text{m}]} + 20\log D - 104.8; \text{ where } D \text{ is the measurement distance in meters.}$$

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014.

Per KDB 414788 D01 v01r01, radiated emission test sites other than open-field test sites (e.g., shielded anechoic chambers), may be employed for emission measurements below 30MHz if characterized so that the measurements correspond to those obtained at an open-field test site. To determine test site equivalency, a reference sample transmitting at 149kHz was measured on an open field test site (asphalt with no ground plane) and then measured in the 3m semi-anechoic chamber. A calibrated 60cm loop antenna was used while the reference device was rotated through the X, Y and Z axis in order to capture the worst case level. A maximum deviation of 2.77dB at 149kHz was measured when comparing the 3 meter semi-anechoic chamber to the open field site.

Radiated spurious emission levels are investigated with the receive antenna horizontally and vertically polarized per ANSI C63.26-2015 and TIA-603-E-2016.

FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device	Page 8 of 112

4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.23-2012. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (\pm dB)
Conducted Bench Top Measurements	2.07
Radiated Disturbance (<30MHz)	4.12
Radiated Disturbance (30MHz-1GHz)	4.85
Radiated Disturbance (1-18GHz)	5.08
Radiated Disturbance (>18GHz)	5.22

FCC ID: BCGA3269	 element		
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device	Approved by: Technical Manager

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
ATM	180-442A-KF	20dB Nominal Gain Horn Antenna	3/14/2024	Annual	3/14/2025	T058701-01
ESPEC	SU-241	Tabletop Temperature Chamber	10/24/2024	Annual	10/24/2025	92009574
ETS-Lindgren	3117	Double Ridged Guide Antenna (1-18 GHz)	4/9/2024	Annual	4/9/2025	00218555
Fairview Microwave/MCL	FMCA1975-36/BW-K10-2W44+	30MHz-40GHz RF Cable/Attenuator *	6/10/2024	Annual	6/10/2025	-
Fairview Microwave	M2CP1122-10	RF Directional Coupler *	6/10/2024	Annual	6/10/2025	1946
Keysight Technology	N9040B	UXA Signal Analyzer	5/28/2024	Annual	5/28/2025	MY57212015
Rohde & Schwarz	FSW67	Signal and Spectrum Analyzer (2Hz-67GHz)	7/5/2024	Annual	7/5/2025	101366
Rohde & Schwarz	TS-PR18	Pre-Amplifier (1GHz - 18GHz)	3/1/2024	Annual	3/1/2025	102143
Rohde & Schwarz	FSV40	Signal Analyzer (10Hz-40GHz)	5/29/2024	Annual	5/29/2025	101619
Rohde & Schwarz	ESW44	EMI Test Receiver	5/1/2024	Annual	5/1/2025	101867
Rohde & Schwarz	TS-PR8	Pre-Amplifier (30MHz - 8GHz)	7/3/2024	Annual	7/3/2025	102356
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	12/27/2023	Annual	12/27/2024	164715
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	10/21/2024	Annual	10/21/2025	187423
Rohde & Schwarz	TS-PR1840	Pre-Amplifier (18GHz - 40GHz)	6/10/2024	Annual	6/10/2025	100057
Rohde & Schwarz	HFH2-Z2	Loop Antenna	6/21/2024	Annual	6/21/2025	100519
Rohde & Schwarz	ENV216	Two-Line V-Network	4/24/2024	Annual	4/24/2025	101364
Schwarzbeck	VULB 9162	Bilog Antenna (30MHz - 6GHz)	4/29/2024	Annual	4/29/2025	00304

Table 5-1. Test Equipment

Notes:

1. For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.
2. * denotes passive equipment that have been internally verified/calibrated.

FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device		Page 10 of 112

6.0 SAMPLE CALCULATIONS

Emission Designator

Emission Designator = 4M16F9W

WCDMA BW = 4.16 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

$\pi/2$ BPSK / QPSK Modulation

Emission Designator = 8M62G7W

BW = 8.62 MHz

G = Phase Modulation

7 = Quantized/Digital Info

W = Combination of Any

QAM Modulation

Emission Designator = 8M45D7W

BW = 8.45 MHz

D = Amplitude/Angle Modulated

7 = Quantized/Digital Info

W = Combination of Any

Spurious Radiated Emission

Example: Spurious emission at 3700.40 MHz

The receive spectrum analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3700.40 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.50 dBm so this harmonic was 25.50 dBm $- (-24.80) = 50.3$ dBc.

FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device	Page 11 of 112

7.0 TEST RESULTS

7.1 Summary

Company Name: Apple Inc.
 FCC ID: BCGA3269
 FCC Classification: PCS Licensed Transmitter (PCB)
 Mode(s): WCDMA/LTE/NR

Test Condition	Test Description	FCC Part Section(s)	Test Limit	Test Result	Reference
CONDUCTED	Occupied Bandwidth	2.1049	N/A	N/A	Section 7.2
	Conducted Band Edge / Spurious Emissions	2.1051, 22.917(a)	-13 dBm at Band Edge and for all out-of-band emissions	PASS	Sections 7.3, 7.4
	Transmitter Conducted Output Power	2.1046	N/A	N/A	See RF Exposure Report
	Effective Radiated Power / Equivalent Isotropic Radiated Power	22.913(a)(5)	< 7 Watts max. ERP	PASS	Section 7.5
	Frequency Stability	2.1055, 22.355	±2.5 ppm	PASS	Section 7.7
RADIATED	Radiated Spurious Emissions	2.1053, 22.917(a)	-13 dBm for all out-of-band emissions	PASS	Section 7.6

Table 7-1. Summary of Test Results

Notes:

1. All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
2. The analyzer plots were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
3. All antenna ports conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
4. All conducted emissions measurements are performed with automated test software to capture the corresponding plots necessary to show compliance. The measurement software utilized is Element EMC Software Tool v1.1
5. For radiated spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element "Chamber Automation," Version 3.1.0.

FCC ID: BCGA3269	 element		PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device		Page 12 of 112

7.2 Occupied Bandwidth

§2.1049

Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section. All ports were tested and only the worst case data were reported.

Test Procedure Used

KDB 971168 D01 v03r01 – Section 4.2

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW \geq 3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

FCC ID: BCGA3269	 element		
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device	Approved by: Technical Manager

V2.2 08/24/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Materials Technology. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Page 13 of 112

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-1. LTE Test Instrument & Measurement Setup




Figure 7-2. FR1 Test Instrument & Measurement Setup

Test Notes


None.

FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device	Page 14 of 112

LTE Band 26/5




Plot 7-1. Occupied Bandwidth Plot (LTE Band 26/5 - 1.4MHz QPSK - Full RB Configuration)




Plot 7-2. Occupied Bandwidth Plot (LTE Band 26/5 - 1.4MHz 16-QAM - Full RB Configuration)

FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device	Page 15 of 112





Plot 7-3. Occupied Bandwidth Plot (LTE Band 26/5 - 1.4MHz 64-QAM - Full RB Configuration)




Plot 7-4. Occupied Bandwidth Plot (LTE Band 26/5 - 1.4MHz 256-QAM - Full RB Configuration)



FCC ID: BCGA3269	 element	PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device	Page 16 of 112	





FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device	Page 17 of 112




FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device	Page 18 of 112




FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device	Page 19 of 112



FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device	Page 20 of 112




Plot 7-13. Occupied Bandwidth Plot (LTE Band 26/5 - 10MHz QPSK - Full RB Configuration)




Plot 7-14. Occupied Bandwidth Plot (LTE Band 26/5 - 10MHz 16-QAM - Full RB Configuration)

FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device		Page 21 of 112



Plot 7-15. Occupied Bandwidth Plot (LTE Band 26/5 - 10MHz 64-QAM - Full RB Configuration)




Plot 7-16. Occupied Bandwidth Plot (LTE Band 26/5 - 10MHz 256-QAM - Full RB Configuration)

FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device		Page 22 of 112

ULCA – LTE Band 5



FCC ID: BCGA3269	 element		PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device		Page 23 of 112





Plot 7-19. Conducted Spurious Plot (ULCA LTE Band 5 – (10 + 10)MHz 64-QAM - Full RB Configuration)





Plot 7-20. Conducted Spurious Plot (ULCA LTE Band 5 – (10 + 10)MHz 256-QAM - Full RB Configuration)

FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device		Page 24 of 112



NR Band n26/n5




FCC ID: BCGA3269	 element		PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device		Page 25 of 112




FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device		Page 26 of 112



FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device		Page 27 of 112





Plot 7-27. Occupied Bandwidth Plot (NR Band n26/n5 - 10MHz CP-OFDM QPSK - Full RB Configuration)





Plot 7-28. Occupied Bandwidth Plot (NR Band n26/n5 - 10MHz CP-OFDM 16-QAM - Full RB Configuration)



FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device		Page 28 of 112



FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device	Page 29 of 112




FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device		Page 30 of 112



FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device	Page 31 of 112



Plot 7-35. Occupied Bandwidth Plot (NR Band n26/n5 - 15MHz CP-OFDM 256-QAM - Full RB Configuration)




Plot 7-36. Occupied Bandwidth Plot (NR Band n26/n5 - 20MHz DFT-s-OFDM π/2 BPSK - Full RB Configuration)

FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device		Page 32 of 112





Plot 7-37. Occupied Bandwidth Plot (NR Band n26/n5 - 20MHz CP-OFDM QPSK - Full RB Configuration)




Plot 7-38. Occupied Bandwidth Plot (NR Band n26/n5 - 20MHz CP-OFDM 16-QAM - Full RB Configuration)

FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device		Page 33 of 112



FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device		Page 34 of 112

WCDMA Cell



Plot 7-41. Occupied Bandwidth Plot (WCDMA, Ch. 4183)

FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device	Page 35 of 112

7.3 Spurious and Harmonic Emissions at Antenna Terminal

§2.1051, 22.917(a)

Test Overview and Limit

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section. All ports were tested and only the worst case data were reported.

The minimum permissible attenuation level of any spurious emission is $43 + 10 \log_{10}(P_{\text{Watts}})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v03r01 – Section 6.0

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 10GHz (separated into at least two plots per channel)
2. Detector = RMS
3. Trace mode = trace average for continuous emissions, max hold for pulse emissions
4. Sweep time = auto couple
5. The trace was allowed to stabilize
6. Please see test notes below for RBW and VBW settings

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-3. LTE Test Instrument & Measurement Setup




Figure 7-4. FR1 Test Instrument & Measurement Setup


FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device	Page 36 of 112

Test Notes


1. Per Part 22, compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth 100 kHz or greater for measurements below 1GHz. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.
2. For NR operation, all subcarrier spacings (SCS) and transmission schemes (e.g. CP-OFDM and DFT-s-OFDM) were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.
3. Uplink carrier aggregation conducted spurious emissions measurements were evaluated for the two contiguous channels using various combinations of RB size, RB offset, modulation, and channel bandwidth. The worst case (highest) powers were found while operating with QPSK modulation with both carriers set to transmit using 1RB.
4. Uplink carrier aggregation inter-band emission was investigated and found to not be the worst case

FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device	Page 37 of 112

LTE Band 26/5




Plot 7-42. Conducted Spurious Plot (LTE Band 26/5 - 10MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-43. Conducted Spurious Plot (LTE Band 26/5 - 10MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)

FCC ID: BCGA3269	 element		PART 22 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device		Page 38 of 112




Plot 7-44. Conducted Spurious Plot (LTE Band 26/5 - 10MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-45. Conducted Spurious Plot (LTE Band 26/5 - 10MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device		Page 39 of 112




Plot 7-46. Conducted Spurious Plot (LTE Band 26/5 - 10MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)




Plot 7-47. Conducted Spurious Plot (LTE Band 26/5 - 10MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT		
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device	Approved by: Technical Manager



Plot 7-48. Conducted Spurious Plot (LTE Band 26/5 - 10MHz QPSK - RB Size 1, RB Offset 0 - High Channel)



Plot 7-49. Conducted Spurious Plot (LTE Band 26/5 - 10MHz QPSK - RB Size 1, RB Offset 0 - High Channel)


FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device		Page 41 of 112




Plot 7-50. Conducted Spurious Plot (LTE Band 26/5 - 10MHz QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT		
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device	Approved by: Technical Manager

ULCA LTE Band 5




Plot 7-51. Conducted Spurious Plot (ULCA LTE Band 5 – (10 + 10)MHz QPSK – PCC 1/49 SCC 1/0 - Low Channel)




Plot 7-52. Conducted Spurious Plot (ULCA LTE Band 5 – (10 + 10)MHz QPSK – PCC 1/49 SCC 1/0 - Low Channel)

FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device	Page 43 of 112




Plot 7-53. Conducted Spurious Plot (ULCA LTE Band 5 – (10 + 10)MHz QPSK – PCC 1/49 SCC 1/0 - Low Channel)




Plot 7-54. Conducted Spurious Plot (ULCA LTE Band 5 – (10 + 10)MHz QPSK – PCC 1/49 SCC 1/0 - Mid Channel)

FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device		Page 44 of 112




Plot 7-55. Conducted Spurious Plot (ULCA LTE Band 5 – (10 + 10)MHz QPSK – PCC 1/49 SCC 1/0 - Mid Channel)




Plot 7-56. Conducted Spurious Plot (ULCA LTE Band 5 – (10 + 10)MHz QPSK – PCC 1/49 SCC 1/0 - Mid Channel)

FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device	Page 45 of 112




Plot 7-57. Conducted Spurious Plot (ULCA LTE Band 5 – (10 + 10)MHz QPSK – PCC 1/0 SCC 1/49 - High Channel)



Plot 7-58. Conducted Spurious Plot (ULCA LTE Band 5 – (10 + 10)MHz QPSK – PCC 1/0 SCC 1/49 - High Channel)


FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device		Page 46 of 112




Plot 7-59. Conducted Spurious Plot (ULCA LTE Band 5 – (10 + 10)MHz QPSK – PCC 1/0 SCC 1/49 - High Channel)

FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device	Page 47 of 112

NR Band n26/n5




Plot 7-60. Conducted Spurious Plot (NR Band n26/n5 - 20.0MHz DFT-s-OFDM QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-61. Conducted Spurious Plot (NR Band n26/n5 - 20.0MHz DFT-s-OFDM QPSK - RB Size 1, RB Offset 0 - Low Channel)

FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device	Page 48 of 112





Plot 7-62. Conducted Spurious Plot (NR Band n26/n5 - 20.0MHz DFT-s-OFDM QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-63. Conducted Spurious Plot (NR Band n26/n5 - 20.0MHz DFT-s-OFDM QPSK - RB Size 1, RB Offset 0 - Mid Channel)


FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device	Page 49 of 112



FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device	Page 50 of 112




Plot 7-66. Conducted Spurious Plot (NR Band n26/n5 - 20.0MHz DFT-s-OFDM QPSK - RB Size 1, RB Offset 0 - High Channel)



Plot 7-67. Conducted Spurious Plot (NR Band n26/n5 - 20.0MHz DFT-s-OFDM QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device	Page 51 of 112



Plot 7-68. Conducted Spurious Plot (NR Band n26/n5 - 20.0MHz DFT-s-OFDM QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: BCGA3269	PART 22 MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1C2410210075-07-R1.BCG	Test Dates: 7/1/2024 - 12/26/2024	EUT Type: Tablet Device		Page 52 of 112