

Maximum Permissible Exposure (MPE)

Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended to comply with Section Part 22, subpart H and Part 24, subpart E of the FCC CFR 47 Rules. For 47 CFR 1.1310 Radio frequency Radiation Exposure requirement.

Special Accessories

Not available for this EUT intended for grant.

Equipment Modifications

Not available for this EUT intended for grant.

Limitation

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-15000	/	/	1.0	30

F = frequency in MHz

* = Plane-wave equipment power density

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan / 台北縣五股工業區五工路134號

台灣檢驗科技股份有限公司 t (886-2) 2299-3279 f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Maximum Permissible Exposure (MPE) Evaluation

In this application we seek approval to the 3G Data Module. Based on the FCC OET Bulletin 65 Supplement C and 47 CFR §2.1091, we have concluded that the SIM340 module will comply with the FCC rules on RF exposure for mobile devices in cellular band and PCS band. The following analysis will demonstrate such compliance. The analysis will be done in two US bands.

Operation in GPRS 850 band (824 – 850 MHz)

The ERP of 3G Data Module in GPRS 850 is 31.95dBm max. The resulted ERP can be expressed as follows:

EUT Mode	Frequency (MHz)	CH	EUT Pol.	Antenna Pol.	SPA Reading (dBuV)	S.G. Output (dBm)	Antenna Gain (dBd)	Cable Loss (dB)	ERP (dBm)	Limit (dBm)
GPRS 850	824.20	128	E2	V	119.41	33.02	-7.87	3.62	21.52	38.40
				H	129.72	43.45	-7.87	3.62	31.95	38.40
	836.60	190	E2	V	119.94	33.69	-7.88	3.65	22.16	38.40
				H	129.32	43.09	-7.88	3.65	31.56	38.40
	848.80	251	E2	V	119.94	33.82	-7.88	3.68	22.26	38.40
				H	129.30	43.11	-7.88	3.68	31.55	38.40

$$\text{ERP} = 31.95 = 1566.75 \text{ mW}$$

$$\text{Power Density} = \text{ERP} * \text{Duty Cycle} / (4 \pi R^2)$$

$$= 1566.75 * 0.25 / (4 * \pi * 20^2) = 0.07796 \text{ mW/cm}^2$$

where Duty Cycle is 0.25 for GPRS 850 band operation (class 10) and R is 20 cm.

The MPE limit for General Population/Uncontrolled Exposure is shown in the FCC OET Bulletin 65 Supplement C and can be calculated as follows:

$$\text{MPE limit} = 824/1500 = 0.55 \text{ mW/cm}^2$$

As we can see the resulted power density is below the MPE limit, therefore 3G Data Module in Cellular band is compliant with the FCC rules on RF exposure.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan / 台北縣五股工業區五工路134號

台灣檢驗科技股份有限公司 t (886-2) 2299-3279 f (886-2) 2298-0488

www.tw.sgs.com

Operation in GPRS 1900 band (1850 – 1910 MHz)

The EIRP of 3G Data Module in GPRS 1900 band is 25.53dBm max. The resulted EIRP can be expressed as follows:

EUT Mode	Frequency (MHz)	CH	EUT Pol.	Antenna Pol.	SPA Reading (dBuV)	S.G. Output (dBm)	Antenna Gain (dBi)	Cable Loss (dB)	EIRP (dBm)	Limit (dBm)
GPRS 1900	1850.20	512	E2	V	117.05	12.66	9.90	5.56	17.00	33.00
				H	125.18	21.00	9.90	5.56	25.34	33.00
	1880.00	661	E2	V	118.12	13.76	9.99	5.61	18.14	33.00
				H	124.98	20.84	9.99	5.61	25.21	33.00
	1909.80	810	E2	V	118.50	14.17	10.08	5.66	18.59	33.00
				H	125.22	21.11	10.08	5.66	25.53	33.00

$$\text{EIRP} = 25.53 \text{ dBm} = 357.3 \text{ mW}$$

$$\begin{aligned} \text{Power Density} &= \text{EIRP} * \text{Duty Cycle} / (4 \pi R^2) \\ &= 357.3 * 0.25 / (4 * \pi * 20^2) = 0.01778 \text{ mW/cm}^2 \end{aligned}$$

where Duty Cycle is 0.25 for GPRS 1900 operation (class 10) and R is 20 cm.

The MPE limit for General Population/Uncontrolled Exposure is shown in the FCC OET Bulletin 65 Supplement C and can be calculated as follows:

$$\text{MPE limit} = 1.0 \text{ mW/cm}^2$$

As we can see the resulted power density is below the MPE limit, therefore 3G Data Module in PCS band is compliant with the FCC rules on RF exposure.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan / 台北縣五股工業區五工路134號

台灣檢驗科技股份有限公司 t (886-2) 2299-3279 f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Operation in EDGE 850 band (824~850 MHz)

The EIRP of 3G Data Module in EDGE 850 band is 29.68dBm max. The resulted EIRP can be expressed as follows:

EUT Mode	Frequency (MHz)	CH	EUT Pol.	Antenna Pol.	SPA Reading (dBuV)	S.G. Output (dBm)	Antenna Gain (dBd)	Cable Loss (dB)	EIRP (dBm)	Limit (dBm)
EDGE 850	824.20	128	E2	V	116.77	30.38	-7.87	3.62	18.88	38.40
				H	127.45	41.18	-7.87	3.62	29.68	38.40
	836.60	190	E2	V	115.62	29.37	-7.88	3.65	17.84	38.40
				H	127.08	40.85	-7.88	3.65	29.32	38.40
	848.80	251	E2	V	116.02	29.90	-7.88	3.68	18.34	38.40
				H	126.94	40.75	-7.88	3.68	29.19	38.40

$$\text{EIRP} = 29.68 \text{ dBm} = 928.9 \text{ mW}$$

$$\text{Power Density} = \text{EIRP} * \text{Duty Cycle} / (4 \pi R^2)$$

$$= 928.9 * 0.25 / (4 * \pi * 20^2) = 0.04623 \text{ mW/cm}^2$$

where Duty Cycle is 0.25 for EDGE 850 operation (class 10) and R is 20 cm.

The MPE limit for General Population/Uncontrolled Exposure is shown in the FCC OET Bulletin 65 Supplement C and can be calculated as follows:

$$\text{MPE limit} = 824/1500 = 0.55 \text{ mW/cm}^2$$

As we can see the resulted power density is below the MPE limit, therefore 3G Data Module in Cellular band is compliant with the FCC rules on RF exposure.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan / 台北縣五股工業區五工路134號

台灣檢驗科技股份有限公司 t (886-2) 2299-3279 f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Operation in EDGE 1900 band (1850 – 1910 MHz)

The EIRP of 3G Data Module in EDGE 1900 band is 23.26dBm max. The resulted EIRP can be expressed as follows:

EUT Mode	Frequency (MHz)	CH	EUT Pol.	Antenna Pol.	SPA Reading (dBuV)	S.G. Output (dBm)	Antenna Gain (dBi)	Cable Loss (dB)	EIRP (dBm)	Limit (dBm)
EDGE 1900	1850.20	512	E2	V	116.23	11.84	9.90	5.56	16.18	33.00
				H	123.10	18.92	9.90	5.56	23.26	33.00
	1880.00	661	E2	V	114.80	10.44	9.99	5.61	14.82	33.00
				H	121.86	17.72	9.99	5.61	22.09	33.00
	1909.80	810	E2	V	115.81	11.48	10.08	5.66	15.90	33.00
				H	122.56	18.45	10.08	5.66	22.87	33.00

$$\text{EIRP} = 23.26 \text{ dBm} = 211.8 \text{ mW}$$

$$\begin{aligned} \text{Power Density} &= \text{EIRP} * \text{Duty Cycle} / (4 \pi R^2) \\ &= 211.8 * 0.25 / (4 * \pi * 20^2) = 0.01054 \text{ mW/cm}^2 \end{aligned}$$

where Duty Cycle is 0.25 for EDGE 1900 operation (class 10) and R is 20 cm.

The MPE limit for General Population/Uncontrolled Exposure is shown in the FCC OET Bulletin 65 Supplement C and can be calculated as follows:

$$\text{MPE limit} = 1.0 \text{ mW/cm}^2$$

As we can see the resulted power density is below the MPE limit, therefore 3G Data Module in PCS band is compliant with the FCC rules on RF exposure.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan / 台北縣五股工業區五工路134號

台灣檢驗科技股份有限公司 t (886-2) 2299-3279 f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Operation in WCDMA band II (1850 – 1910 MHz)

The EIRP of 3G Data Module in WCDMA band II is 25.44dBm max. The resulted EIRP can be expressed as follows:

EUT				Measurement					
Operation Band	Pol.	Fundamental Frequency	CH	Antenna Pol.	S.G. Output	Antenna Gain	Cable Loss	EIRP	Limit
WCDMA B2	E2	MHz		V/H	dBm	dBd	dB	dBm	dBm
		1852.4	9262	V	24.83	4.17	-5.49	23.51	33.00
				H	26.42	4.51	-5.49	25.44	33.00
		1880.0	9400	V	24.74	4.13	-5.56	23.31	33.00
				H	23.05	4.44	-5.56	21.93	33.00
		1907.6	9538	V	24.09	4.10	-5.62	22.56	33.00
				H	25.40	4.37	-5.62	24.14	33.00

$$\text{EIRP} = 25.44 \text{ dBm} = 349.9 \text{ mW}$$

$$\begin{aligned} \text{Power Density} &= \text{EIRP} * \text{Duty Cycle} / (4 \pi R^2) \\ &= 349.9 * 1 / (4 * \pi * 20^2) = 0.06965 \text{ mW/cm}^2 \end{aligned}$$

where Duty Cycle is 1 for WCDMA band II and R is 20 cm.

The MPE limit for General Population/Uncontrolled Exposure is shown in the FCC OET Bulletin 65 Supplement C and can be calculated as follows:

$$\text{MPE limit} = 1.0 \text{ mW/cm}^2$$

As we can see the resulted power density is below the MPE limit, therefore 3G Data Module in WCDMA band II band is compliant with the FCC rules on RF exposure.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan / 台北縣五股工業區五工路134號

台灣檢驗科技股份有限公司 t (886-2) 2299-3279 f (886-2) 2298-0488

www.tw.sgs.com

Operation in HSDPA band II (1850 – 1910 MHz)

The EIRP of 3G Data Module in HSDPA band II is 26.64dBm max. The resulted EIRP can be expressed as follows:

EUT				Measurement					
Operation Band	Pol.	Fundamental Frequency	CH	Antenna Pol.	S.G. Output	Antenna Gain	Cable Loss	EIRP	Limit
		MHz		V/H	dBm	dBd	dB	dBm	dBm
HSDPA B2	E2	1852.4	9262	V	25.94	4.17	-5.49	24.62	33.00
				H	27.38	4.51	-5.49	26.40	33.00
		1880.0	9400	V	25.76	4.13	-5.56	24.33	33.00
				H	27.77	4.44	-5.56	26.64	33.00
		1907.6	9538	V	24.45	4.10	-5.62	22.92	33.00
				H	26.90	4.37	-5.62	25.65	33.00

$$\text{EIRP} = 26.64 \text{ dBm} = 461.3 \text{ mW}$$

$$\text{Power Density} = \text{EIRP} * \text{Duty Cycle} / (4 \pi R^2)$$

$$= 461.3 * 1 / (4 * \pi * 20^2) = 0.09182 \text{ mW/cm}^2$$

where Duty Cycle is 1 for HSDPA band II and R is 20 cm.

The MPE limit for General Population/Uncontrolled Exposure is shown in the FCC OET Bulletin 65 Supplement C and can be calculated as follows:

$$\text{MPE limit} = 1.0 \text{ mW/cm}^2$$

As we can see the resulted power density is below the MPE limit, therefore 3G Data Module in HSDPA band II band is compliant with the FCC rules on RF exposure.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan / 台北縣五股工業區五工路134號

台灣檢驗科技股份有限公司 t (886-2) 2299-3279 f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Operation in HSUPA band II (1850 – 1910 MHz)

The EIRP of 3G Data Module in HSUPA band II is 27.18dBm max. The resulted EIRP can be expressed as follows:

EUT				Measurement					
Operation Band	Pol.	Fundamental Frequency	CH	Antenna Pol.	S.G. Output	Antenna Gain	Cable Loss	EIRP	Limit
		MHz		V/H	dBm	dBd	dB	dBm	dBm
HSUPA B2	E2	1852.4	9262	V	25.28	4.17	-5.49	23.97	33.00
				H	27.49	4.51	-5.49	26.51	33.00
		1880.0	9400	V	24.39	4.13	-5.56	22.96	33.00
				H	28.30	4.44	-5.56	27.18	33.00
		1907.6	9538	V	25.01	4.10	-5.62	23.49	33.00
				H	26.54	4.37	-5.62	25.29	33.00

$$\text{EIRP} = 27.18 \text{ dBm} = 522.4 \text{ mW}$$

$$\begin{aligned} \text{Power Density} &= \text{EIRP} * \text{Duty Cycle} / (4 \pi R^2) \\ &= 522.4 * 1 / (4 * \pi * 20^2) = 0.10398 \text{ mW/cm}^2 \end{aligned}$$

where Duty Cycle is 1 for HSUPA band II and R is 20 cm.

The MPE limit for General Population/Uncontrolled Exposure is shown in the FCC OET Bulletin 65 Supplement C and can be calculated as follows:

$$\text{MPE limit} = 1.0 \text{ mW/cm}^2$$

As we can see the resulted power density is below the MPE limit, therefore 3G Data Module in HSUPA band II band is compliant with the FCC rules on RF exposure.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan / 台北縣五股工業區五工路134號

台灣檢驗科技股份有限公司 t (886-2) 2299-3279 f (886-2) 2298-0488

www.tw.sgs.com

Operation in WCDMA band V(824 – 850 MHz)

The ERP of 3G Data Module in WCDMA band V is 20.99dBm. max. The resulted ERP can be expressed as follows:

EUT				Measurement					
Operation Band	Pol.	Fundamental Frequency	CH	Antenna Pol.	S.G. Output	Antenna Gain	Cable Loss	ERP	Limit
		MHz		V/H	dBm	dBd	dB	dBm	dBm
WCDMA B5	E2	826.4	4132	V	13.73	3.97	-4.22	13.47	38.45
				H	20.35	3.97	-4.22	20.10	38.45
		836.6	4183	V	14.01	3.99	-4.24	13.77	38.45
				H	21.23	4.00	-4.24	20.99	38.45
		846.6	4233	V	13.26	4.02	-4.24	13.04	38.45
				H	20.38	4.02	-4.24	20.16	38.45

$$\text{ERP} = 20.99 = 125.6 \text{ mW}$$

$$\begin{aligned} \text{Power Density} &= \text{ERP} * \text{Duty Cycle} / (4 \pi R^2) \\ &= 125.6 * 1 / (4 * \pi * 20^2) = 0.025 \text{ mW/cm}^2 \end{aligned}$$

where Duty Cycle is 1 for WCDMA Band V operation and R is 20 cm.

The MPE limit for General Population/Uncontrolled Exposure is shown in the FCC OET Bulletin 65 Supplement C and can be calculated as follows:

$$\text{MPE limit} = 826/1500 = 0.55 \text{ mW/cm}^2$$

As we can see the resulted power density is below the MPE limit, therefore 3G Data Module in WCDMA Band V band is compliant with the FCC rules on RF exposure.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Operation in HSDPA band V (824 – 850 MHz)

The ERP of 3G Data Module in HSDPA band V is 22.00dBm max. The resulted ERP can be expressed as follows:

EUT				Measurement					
Operation Band	Pol.	Fundamental Frequency	CH	Antenna Pol.	S.G. Output	Antenna Gain	Cable Loss	ERP	Limit
		MHz		V/H	dBm	dBd	dB	dBm	dBm
HSDPA B5	E2	826.4	4132	V	14.84	3.97	-4.22	14.59	38.45
				H	21.45	3.97	-4.22	21.20	38.45
		836.6	4183	V	14.99	3.99	-4.24	14.75	38.45
				H	22.24	3.99	-4.24	22.00	38.45
		846.6	4233	V	14.81	4.02	-4.24	14.59	38.45
				H	21.67	4.02	-4.24	21.45	38.45

$$\text{ERP} = 22.00 \text{ dBm} = 158.5 \text{ mW}$$

$$\text{Power Density} = \text{ERP} * \text{Duty Cycle} / (4 \pi R^2)$$

$$= 158.8 * 1 / (4 * \pi * 20^2) = 0.03155 \text{ mW/cm}^2$$

where Duty Cycle is 1 for HSDPA Band V operation and R is 20 cm.

The MPE limit for General Population/Uncontrolled Exposure is shown in the FCC OET Bulletin 65 Supplement C and can be calculated as follows:

$$\text{MPE limit} = 826/1500 = 0.55 \text{ mW/cm}^2$$

As we can see the resulted power density is below the MPE limit, therefore 3G Data Module in HSDPA Band V band is compliant with the FCC rules on RF exposure.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Operation in HSUPA band V (824 – 850 MHz)

The ERP of 3G Data Module in HSUPA band V is 21.92dBm max. The resulted ERP can be expressed as follows:

EUT				Measurement					
Operation Band	Pol.	Fundamental Frequency	CH	Antenna Pol.	S.G. Output	Antenna Gain	Cable Loss	ERP	Limit
		MHz		V/H	dBm	dBd	dB	dBm	dBm
HSUPA B5	E2	826.4	4132	V	14.38	3.97	-4.22	14.12	38.45
				H	21.59	3.97	-4.22	21.33	38.45
		836.6	4183	V	15.18	4.00	-4.24	14.94	38.45
				H	22.16	3.99	-4.24	21.92	38.45
		846.6	4233	V	14.91	4.02	-4.24	14.69	38.45
				H	21.63	4.02	-4.24	21.42	38.45

$$\text{ERP} = 21.92 \text{ dBm} = 155.6 \text{ mW}$$

$$\begin{aligned} \text{Power Density} &= \text{ERP} * \text{Duty Cycle} / (4 \pi R^2) \\ &= 155.6 * 1 / (4 * \pi * 20^2) = 0.03097 \text{ mW/cm}^2 \end{aligned}$$

where Duty Cycle is 1 for HSUPA Band V operation and R is 20 cm.

The MPE limit for General Population/Uncontrolled Exposure is shown in the FCC OET Bulletin 65 Supplement C and can be calculated as follows:

$$\text{MPE limit} = 826/1500 = 0.55 \text{ mW/cm}^2$$

As we can see the resulted power density is below the MPE limit, therefore 3G Data Module in HSUPA Band V band is compliant with the FCC rules on RF exposure.

~ End of Report ~

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan / 台北縣五股工業區五工路134號

台灣檢驗科技股份有限公司 t (886-2) 2299-3279 f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group