

 ESTECH Co., Ltd. Rm 1015, World Venture Center II, 426-5 Gasan-dong, Guncheon-gu, Seoul, 158-803, Korea	   		Electromagnetic Interference Test Report

Test Report for FCC

FCC ID:BEJ60PZ750UA

Report Number		ESTF151011-001			
Applicant	Company name	LG Electronics USA			
	Address	1000 Sylvan Avenue Englewood Cliffs, NJ 07632			
	Telephone	847-941-8373			
Product	Product name	PLASMA TV/MONITOR			
	Model name	60PZ750-UA	Manufacturer	LG Electronics Inc.	
	Serial number	NONE	Country of origin	KOREA	
Test date	1-Nov-10		Date of issue	2-Nov-10	
Testing location	ESTECH. Co., Ltd. 97-1 Hoiuk-Ri Majang-Myon, Icheon-city, KyungKi-Do, Korea				
Standard	FCC PART 15 (2008) & ICES-003 , ANSI C 63.4 2003				
Test item	☒ Conducted Emission	☐ Class A	☒ Class B	Test result	OK
	☒ Radiated Emission	☐ Class A	☒ Class B	Test result	OK
Measurement facility registration number		94696			
Tested by	Engineer H.K.LEE		(Signature)		
Reviewed by	Engineering Manager J.M.Yang		(Signature)		
Abbreviation	OK, Pass = Passed, Fail = Failed, N/A = not applicable				
* Note - Basic model: 60PZ750-UA Additional model(s): 60PZ550-UA, 60PZ540-UB - Basic model have four HDMI ports , but 60PZ540-UB have three HDMI ports. - 60PZ550-UA is different front case from Basic model. - This test report is not permitted to copy partly without our permission - This test result is dependent on only equipment to be used - This test result based on a single evaluation of one sample of the above mentioned					

Contents

1. Laboratory Information	3
2. Description of EUT	4
3. Test Standards	5
4. Measurement condition	6
5. Measurement of radiated emission	8
5.1 Measurement equipment	8
5.2 Environmental conditions	8
5.3 Test data	9
5.4 Test data	10
6. Measurement of conducted emission	11
6.1 Measurement equipment	11
6.2 Environmental conditions	11
6.3 Test data	12
7. Photographs of test setup	13
8. Photographs of EUT	15

Appendix 1. Spectral diagram

1. Laboratory Information

1.1 General

This EUT (Equipment Under Test) has been shown to be capable of compliance with the applicable technical standards and is tested in accordance with the measurement procedures as indicated in this report. ESTECH Lab attests to accuracy of test data. All measurement reported herein were performed by ESTECH Co., Ltd.

ESTECH Lab assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

1.2 Test Lab.

Corporation Name : ESTECH Co., Ltd.

Head Office : Rm 1015, World Venture Center II, 426-5, Gasan-dong, Geumcheon-gu, Seoul, Korea
(Safety & Telecom. Test Lab)

EMC Test Lab : 97-1, Hoeok-ri, Majang-myun, Ichion-city, Kyonggi-do, South Korea

1.3 Official Qualification(s)

KCC : Granted Accreditation from Ministry of Information & Communication for EMC, Safety and Telecommunication

KOLAS : Accredited Lab By Korea Laboratory Accreditation Schema base on CENELEC requirements

FCC : Filed Laboratory at Federal Communications Commission

VCCI : Granted Accreditation from Voluntary Control Council for Interference from ITE

2. Description of EUT

2.1 Summary of Equipment Under Test

Product Name : PLASMA TV/MONITOR
 Model Number : 60PZ750-UA
 Serial Number : NONE
 Manufacturer : LG Electronic Inc.
 Country of origin : KOREA
 Rating : AC (100 – 240) V , (50 – 60) Hz
 Receipt Date : 22-Oct-10
 X-tal list(s) : 4 MHz, 10 MHz, 25 MHz, 54 MHz

2.2 General descriptions of EUT

MODELS		50PZ540 (50PZ540-UB) 50PZ550 (50PZ550-UA)	60PZ540 (60PZ540-UB) 60PZ550 (60PZ550-UA)
Dimensions (Width x Height x Depth)	With stand	1170.5 mm X 767.7 mm X 289.7 mm	1390.4 mm X 905.2 mm X 334.7 mm
	Without stand	1170.5 mm X 711.6 mm X 52.5 mm	1390.4 mm X 835.5 mm X 52.5 mm
Weight	With stand	29.6 kg	42.6 kg
	Without stand	27.3 kg	38.5 kg

MODELS		50PZ750 (50PZ750-UA)	60PZ750 (60PZ750-UA)
Dimensions (Width x Height x Depth)	With stand		1404.0 mm X 911.4 mm X 346.5 mm
	Without stand		1404.0 mm X 837.8 mm X 49.6 mm
Weight	With stand		45.3 kg
	Without stand		39.3 kg

Power requirement		AC 100-240 V - 50 / 60 Hz
Television System		NTSC-M, ATSC, 64 & 256 QAM
Program Coverage		VHF 2-13, UHF 14-69, CATV 1-135, DTV 2-69, CADTV 1-135
External Antenna Impedance		75 Ω
Environment condition	Operating Temperature	0 °C to 40 °C (32 °F to 104 °F)
	Operating Humidity	Less than 80 %
	Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
	Storage Humidity	Less than 85 %

3. Test Standards

Test Standard : FCC PART 15 (2008) & ICES-003

This Standard sets out the regulations under which an intentional, unintentional, or incidental radiator may be operated without an individual license. It also contains the technical specifications, administrative requirements and other conditions relating to the marketing of Part 15 devices.

Test Method : ANSI C 63.4 (2003)


This standard sets forth uniform methods of measurement of radio-frequency (RF) signals and noise emitted from both unintentional and intentional emitters of RF energy in the frequency range 9 kHz to 40 GHz. Methods for the measurement of radiated and AC power-line conducted radio noise are covered and may be applied to any such equipment unless otherwise specified by individual equipment requirements. These methods cover measurement of certain devices that deliberately radiate energy, such as intentional emitters, but does not cover licensed transmitters. This standard is not intended for certification/approval of avionic equipment or for industrial, scientific, and medical (ISM) equipment. These methods apply to the measurement of individual units or systems comprised of multiple units.

4. Measurement Condition

4.1 EUT Operation.

- * The EUT was in the following operation mode during all testing
- * The operational conditions of the EUT was determined by the manufacturer according to the typical use of the EUT with respect to the expected highest level of emission
- * After setting as test arrangement diagram, we tested the EUT under continuous displaying "H" character and playing Audio out /Video
- * Execute ping data between Personal Computer and the EUT.

4.2 Configuration and Peripherals



	ESTECH Co., Ltd. Rm 1015, World Venture Center II, 426-5 Gasan-dong, Guncheon-gu, Seoul, 158-803, Korea	  	Electromagnetic Interference Test Report
---	---	--	---

4.3 EUT and Support equipment

Equipment Name	Model	S/N	Manufacturer	Remark (FCC ID)
PLASMA TV/MONITOR	60PZ750-UA	NONE	LG Electronics Inc.	EUT
Personal Computer	DCSM	6RDJJ1S	Dell Asia Pacific Sdn.	-
Printer	K10299	NONE	CANON VIETNAM Co., Ltd.	-
Keyboard	L100	65890-85H	Dell Asia Pacific Sdn.	-
Mouse	Wheel Mouse Optical	OEM-8345672	Microsoft	-
Wireless Ready Dongle	NONE	NONE	LG Electronics Inc.	-
USB to Serial Converter	UCR-100S	NONE	UNICORN CO., LTD.	-
USB Memory Stick	NONE	NONE	NONE	-

4.4 Cable Connecting

Start Equipment		End Equipment		Cable Standard		Remark
Name	I/O port	Name	I/O port	Length	Shielded	
PLASMA TV/MONITOR	RGB	Personal Computer	RGB	2	Y	
PLASMA TV/MONITOR	HDMI	Personal Computer	DVI	2	Y	
PLASMA TV/MONITOR	Audio In	Personal Computer	Audio Out	2	N	
PLASMA TV/MONITOR	Component1 * 5 Port	-	-	2	N	
PLASMA TV/MONITOR	Component2 * 5 Port	-	-	2	N	
PLASMA TV/MONITOR	USB	USB Memory Stick	USB	-	-	
PLASMA TV/MONITOR	Serial	USB to Serial Converter	Serial	2	N	
PLASMA TV/MONITOR	ANTENNA	-	-	2	Y	
PLASMA TV/MONITOR	LAN	External Network	LAN	20	N	
PLASMA TV/MONITOR	AV IN1 * 3 Port	-	-	2	N	
PLASMA TV/MONITOR	AV IN2 * 3 Port	-	-	2	N	
PLASMA TV/MONITOR	Wireless Control	WIRELESS READY DONGLE	Wireless Control	0.5	Y	
Personal computer	USB	Keyboard	USB	2	Y	
Personal computer	USB	Mouse	USB	2	Y	
Personal computer	USB	Printer	USB	2	Y	
Personal computer	USB	USB to Serial Converter	Serial	1	N	

5. Measurement of radiated disturbance

Above 30 MHz Electric Field strength was measured in accordance with FCC Part 15 (2008) & ICES-003. The test setup was made according to ANSI C 63.4 (2003) on an open test site, which allows a 3m distance measurement. The EUT was placed in the center of wooden turntable. The height of this table was 0.8 m. The measurement was conducted with both horizontal and vertical antenna polarization. The turntable has fully rotated. For further description of the configuration refer to the picture of the test setup.

5.1 Measurement equipments

Equipment Name	Type	Manufacturer	Serial No.	Next Calibration date
TEST Receiver	ESVS10	Rohde & Schwarz	838562/002	2011. 2. 01
Spectrum Analyzer	R3273	ADVANTEST	110600592	2011. 2. 01
LogBicon Antenna	VULB 9160	Schwarzbeck	3142	2011. 5. 19
Amplifier	8447F	HP	2805A02972	2011. 2. 01
Turn Table	2087	EMCO	2129	—
Antenna Mast	2070-01	EMCO	9702-203	—
ANT Mast Controller	2090	EMCO	1535	—
Turn Table Controller	2090	EMCO	1535	—

5.2 Environmental Condition

Test Place : Open site(3m)

HDMI mode

Temperature (°C) : 8 °C

Humidity (%) : 40 % R.H.

RGB mode

Temperature (°C) : 10 °C

Humidity (%) : 39 % R.H.

5.3 Test data (HDMI MODE)

Test Date : 1-Nov-10

Measurement Distance : 3 m

Frequency (MHz)	Reading (dB μ V)	Position (V/H)	Height (m)	Correction Factor		Result Value		
				Ant Factor (dB)	Cable (dB)	Limit (dB μ V/m)	Result (dB μ V/m)	Margin (dB)
38.93	16.10	V	1.0	11.14	1.0	40.0	28.19	-11.81
49.74	13.10	V	1.0	11.99	1.1	40.0	26.18	-13.82
60.32	20.90	V	1.0	11.03	1.2	40.0	33.11	-6.89
81.00	16.20	V	1.0	8.28	1.4	40.0	25.86	-14.14
120.65	14.10	H	2.0	10.96	1.8	43.5	26.82	-16.68
134.48	17.80	H	1.6	11.98	1.9	43.5	31.67	-11.83
150.67	8.80	V	1.0	12.69	2.0	43.5	23.48	-20.02
166.27	9.10	V	1.0	12.46	2.1	43.5	23.71	-19.79
214.43	11.20	H	1.0	10.99	2.5	43.5	24.66	-18.84
228.37	22.80	H	1.0	10.86	2.6	46.0	36.25	-9.75
250.00	20.00	H	1.0	11.97	2.8	46.0	34.76	-11.24
288.02	10.30	H	1.0	13.16	3.1	46.0	26.57	-19.43
300.01	13.20	V	1.0	13.54	3.2	46.0	29.92	-16.08
375.00	9.10	H	1.0	15.23	3.8	46.0	28.15	-17.85
415.51	12.30	V	1.0	16.10	4.2	46.0	32.56	-13.44
500.00	12.50	H	1.0	17.81	4.8	46.0	35.06	-10.94
600.00	6.80	H	1.0	20.15	5.5	46.0	32.41	-13.59
750.00	10.80	H	1.0	22.03	6.7	46.0	39.52	-6.48

Remark	H : Horizontal, V : Vertical TEST MODE : Resolution1 920*1 080 (60Hz) at HDMI mode (Worse Case) *CL = Cable Loss-Amplifier Gain(In case of above 1 000 Mhz) *CL = Cable Loss(In case of below 1 000 Mhz) *The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120KHz for Quasi-peak detection at frequency below 1GHz. *After connect with ferrite cores to RGB cable, tested radiated emission.
--------	---

5.3 Test data (RGB MODE)

Test Date : 1-Nov-10

Measurement Distance : 3 m

Frequency (MHz)	Reading (dB μ V)	Position (V/H)	Height (m)	Correction Factor		Result Value		
				Ant Factor (dB)	Cable (dB)	Limit (dB μ V/m)	Result (dB μ V/m)	Margin (dB)
33.02	21.00	V	1.0	10.55	0.9	40.0	32.45	-7.55
49.50	23.00	H	3.0	11.98	1.1	40.0	36.06	-3.94
66.02	25.00	H	2.6	10.23	1.3	40.0	36.48	-3.52
115.51	23.40	V	1.0	10.49	1.7	43.5	35.58	-7.92
132.00	22.00	V	1.0	11.80	1.8	43.5	35.63	-7.87
144.00	15.80	H	1.0	12.50	2.0	43.5	30.30	-13.20
150.81	15.60	H	1.0	12.69	2.0	43.5	30.29	-13.21
164.99	18.50	H	1.0	12.56	2.1	43.5	33.19	-10.31
214.52	27.00	H	1.0	11.01	2.5	43.5	40.48	-3.02
247.50	23.80	H	1.0	11.41	2.8	46.0	37.98	-8.02
264.02	19.60	V	1.0	12.41	2.9	46.0	34.91	-11.09
300.00	14.30	H	1.0	13.54	3.2	46.0	31.02	-14.98
375.00	10.80	H	1.0	15.23	3.8	46.0	29.85	-16.15
432.01	9.50	H	1.0	16.44	4.3	46.0	30.27	-15.73
500.00	12.40	V	1.0	17.81	4.8	46.0	34.96	-11.04
625.00	9.60	V	1.0	20.42	5.7	46.0	35.68	-10.32
750.00	10.10	H	1.0	22.03	6.7	46.0	38.82	-7.18

Remark	H : Horizontal, V : Vertical TEST MODE : Resolution1 920*1 080(60Hz) at RGB mode (Worse Case) *CL = Cable Loss-Amplifier Gain(In case of above 1 000 Mhz) *CL = Cable Loss(In case of below 1 000 Mhz) *The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120KHz for Quasi-peak detection at frequency below 1GHz. *After connect with ferrite cores to RGB cable, tested radiated emission.
--------	---

6. Measurement of conducted disturbance

The continuous disturbance voltage of AC Mains in the frequency from 0.15 MHz to 30 MHz was measured in accordance to FCC Part 15 (2008) & ICES-003. The test setup was made according to ANSI C 63.4 (2003) in a shielded. The EUT was placed on a non-conductive table at least 0.8 m above the ground plan. A grounded vertical reference plane was positioned in a distance of 0.4 m from the EUT. The distance from the EUT to other metal surfaces was at least 0.8 m. The EUT was only earthen by its power cord through the line impedance stabilizing network. The power cord has been bundled to a length of 1.0 m. The test receiver with Quasi Peak detector complies with CISPR 16.

6.1 Measurement equipments

Equipment Name	Type	Manufacturer	Serial No.	Next Calibration date
LISN	ESH3-Z5	Rohde & Schwarz	838979/010	2011. 2. 1
LISN	NSLK8127	Schwarzbeck	8127304	2011. 1.18
TEST Receiver	ESPI7	Rohde & Schwarz	100185	2011. 8. 24
Pulse Limiter	ESH3Z2	Rohde & Schwarz	NONE	2011. 2. 1

6.2 Environmental Condition

Test Place : Shield Room
 Temperature (°C) : 23 °C
 Humidity (%) : 40 % R.H.

6.3 Test data

Test Date : 1-Nov-10

Frequency (MHz)	Correction Factor		Line (H/N)	Quasi-peak Value			Average Value		
	Lisn (dB)	Cable (dB)		Limit (dB μ V)	Reading (dB μ V)	Result (dB μ V)	Limit (dB μ V)	Reading (dB μ V)	Result (dB)
0.20	0.10	0.4	N	63.82	37.62	38.11	53.82	31.07	31.56
0.21	0.10	0.4	N	63.24	44.14	44.63	53.24	31.09	31.58
0.22	0.10	0.4	N	62.67	33.54	34.03	52.67	24.80	25.29
0.31	0.11	0.4	N	59.89	33.28	33.79	49.89	25.07	25.58
0.41	0.12	0.4	H	57.57	32.92	33.46	47.57	27.01	27.55
0.42	0.12	0.4	N	57.51	33.36	33.90	47.51	26.46	27.00
0.63	0.12	0.5	H	56.00	36.00	36.58	46.00	26.84	27.42
0.74	0.12	0.5	N	56.00	30.30	30.89	46.00	22.10	22.69
0.75	0.12	0.5	H	56.00	29.47	30.06	46.00	22.96	23.55
0.94	0.12	0.5	N	56.00	41.72	42.33	46.00	31.31	31.92
1.25	0.13	0.5	H	56.00	29.73	30.37	46.00	20.12	20.76
2.45	0.20	0.6	N	56.00	28.28	29.06	46.00	14.16	14.94
12.26	0.47	1.1	H	60.00	29.14	30.66	50.00	25.72	27.24
12.37	0.47	1.1	N	60.00	28.37	29.90	50.00	25.71	27.24
16.47	0.61	1.2	H	60.00	43.01	44.82	50.00	41.41	43.22
18.83	0.69	1.2	H	60.00	30.94	32.87	50.00	25.47	27.40
19.01	0.70	1.2	N	60.00	30.97	32.91	50.00	24.85	26.79
20.18	0.73	1.3	H	60.00	29.56	31.56	50.00	23.79	25.79
Remark	H : Hot Line, N : Neutral Line								

7. Photographs of test setup

7.1 Setup for Radiated Test : 30 MHz ~ 1 000 MHz

[Front]



[Rear]




7.2 Setup for Conducted Test : 0.15 MHz ~ 30 MHz

[Front]



[Rear]



8. Photographs of EUT

[Front]




[Rear]



Appendix 1. Spectral diagram

*HOT



Comment: 60PZ750-UA_HOT

Date: 1.NOV.2010 10:44:46


*NEUTRAL



RBW 9 kHz

MT 1 s

Att 10 dB AUTO PREAMP OFF



Comment: 60PZ750-UA_NEUTRAL

Date: 1.NOV.2010 10:40:24